

APPENDIX E: MULTI-TX AND ANTENNA SAR CONSIDERATIONS

E.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter

E.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore, simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1g or 10g SAR. Total Exposure Ratio (TER) is used to show the maximum TER between APD and SAR values therefor the limit for simultaneous exposure becomes $TER \leq 1.0$.

Per FCC KDB Publication 941225 D06v02r01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-”).

This device is enabled with Qualcomm® Smart Transmit Gen2 with pre-defined antenna groups (AG0 and AG1) and 1 mmW module group (MG). Sub6 and mmW antennas cannot be decoupled from each other due to lack of regulatory criteria. This device operates using GEN2_SUB6 (Sub6-favor mode) which assumes all mmW modules (MG) are collocated with each sub6 AG0 and AG1 in this device. The Simultaneous transmission analysis is performed per antenna groups. Below analysis demonstrates the mutually exclusive operation of AG0 and AG1, and the compliance between each antenna group with non-Smart Transmit Radios. For this model, WWAN/WLAN/BT/mmWave Radios are managed under Smart Transmit. Non-Smart Transmit Radios include NFC/UWB.

When operating in the same antenna group, the compliance under dynamic transmission condition, including all supported simultaneous transmission scenarios, should be assessed and demonstrated in the Part 2 Report during algorithm validation. Therefore, no further simultaneous analysis is needed within an antenna group.

When all WWAN/WLAN/BT/mmWave Radios are managed under Smart Transmit, TER for WWAN/WLAN/BT/mmWave is covered in Part 2 testing. Only external radios outside of WWAN/WLAN/BT/mmWave (UWB, NFC) require TER analysis with WWAN/WLAN/BT/mmWave during simultaneous transmissions.

E.3 Antenna Groups

The 2nd generation of Smart Transmit (GEN2) operates based on pre-defined antenna groups (AG). Sub6/WLAN/BT Tx antennas and/or mmW module groups (MG) in the device are grouped based on spatial variation of RF exposure distributions, where the RF exposure of one AG is mutually exclusive from other AG. This is accomplished by demonstrating either of below conditions for all exposure scenarios:

- a) Sum of SAR of one antenna from each of the sub6 AGs and the RF exposure from radios outside Smart Transmit is less than regulatory limits. This condition must be demonstrated for all antenna combinations of sub6 AGs.

(or)

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 1 of 8

- b) Every antenna from each sub6 AG meets SPLSR criteria (Section 4.3.2(c) in FCC KDB 447498 D04) with every antenna from another sub6 AG. These criteria must be demonstrated for all antenna combinations for each pair of AGs.

This device supports two AGs: AG0 and AG1, with AG0 having 4 antennas (A, B, C, D) and AG1 having 5 antennas (E, F, H, I, J) and MG having 1 antenna (M). The conditions are verified through the following criteria:

- i) In Sub6-favor mode: All mmW antennas are assumed to collocate with each sub6 antenna group (AG). Also, since all mmW MGs are controlled by Smart Transmit, maximum mmW exposure is given by maximum out of all mmW modules:

$$\max.\text{norm.exp.mmW} = \max.\text{norm.exp.MG}$$
- ii) Sum of SAR: Demonstrate that the sum of $\max.\text{norm.exp.AG0}$ and $\max.\text{norm.exp.AG1}$ and the reported normalized SAR values from radios outside Smart Transmit (denoted as $\text{reported.norm.exp.ER}$) should be less than the regulatory limit for each supported DSI following the below procedure:
 1. Obtain the worst-case *adjusted SAR* for each antenna group, i.e., maximum *reported SAR* at EFS $P_{\text{limit}} + \text{unc}$ (or max of $\{P_{\text{max}} + \text{unc}, \text{EFS } P_{\text{limit}}\}$ when $\text{EFS } P_{\text{limit}} > P_{\text{max}}$) out of all supported technologies, frequency bands and antennas in AG0 and AG1, then normalized to the regulatory limit to get the maximum normalized SAR for each antenna group, denoted as $\max.\text{norm.exp.AG0}$ and $\max.\text{norm.exp.AG1}$
 2. For external radios outside of Smart Transmit (NFC/UWB): Obtain the worst-case RF exposure for each external radio normalized to regulatory limit to get the normalized SAR for each external radio, denoted as $\text{reported.norm.exp.NFC}$ and $\text{reported.norm.exp.UWB}$
 3. Demonstrate that the sum of these RF exposures meets: $\{\max.\text{norm.exp.AG0} + \max.\text{norm.exp.AG1} + \text{normalized NFC SAR} + \text{normalized UWB SAR}\} \leq 1$.
- iii) SPLSR or composite exposure distribution criteria: when TER sum of an antenna pair is over the limit for a DSI/exposure position, SPLSR or composite exposure distribution can be done to demonstrate simultaneous transmission compliance.
 1. SPLSR analysis for sub6 antenna pairs: For each antenna, obtain the highest *adjusted SAR* at EFS $P_{\text{limit}} + \text{unc}$ (or max of $\{P_{\text{max}} + \text{unc}, \text{EFS } P_{\text{limit}}\}$ when $\text{EFS } P_{\text{limit}} > P_{\text{max}}$) out of all supported technologies for each frequency band. Using these values, demonstrate for a given DSI that every antenna from one AG meets SPLSR criteria with every antenna in another AG for all frequency bands. This criterion must be demonstrated for all antenna pair combinations irrespective of supported simultaneous transmission scenarios as given below for each DSI. As it can be seen, these include all combinations of antenna groups, antennas, and frequency bands.
 - If SPLSR criteria evaluation and analysis is needed to determine compliance for a certain DSI configuration, SPLSR is performed by taking the highest reported SAR for each of the supported technologies and bands per antenna, along with the peak SAR locations. Per Qualcomm guidance, only Y-axis coordinates are recorded in the analysis for calculation simplicity (assumes all 0mm of separation on the x-axis). Peak locations are documented in the Highest Report SAR and Hotspot Location Section below for each DSI configuration. For bottom AG0, Y_{max} coordinates represents the worst-case hotspot location that is closest to the top AG1. Similarly, for top AG1, Y_{min} coordinate represents the worst-case hotspot location that is closest to the bottom AG0
 - The following formula is used to calculate the SPLSR between AG0 and AG1 for each exposure configuration:

$$\text{SPLSR} = \frac{(\text{Max SAR AG0} + \text{Max SAR AG1})^{1.5}}{|Y_{\text{max}} - Y_{\text{min}}|}$$

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 2 of 8

E.4 Head (DSI = 1) SAR Antenna Group Analysis

Table E-1
DSI=1 Held-to-ear AG0 Highest Adjusted SAR

AG0 Ratio to Limit						
Head SAR	Configuration	A	B	C	D	Max
	Right Cheek	0.329	0.141	0.000	0.000	0.329
	Right Tilt	0.203	0.162	0.003	0.000	0.203
	Left Cheek	0.283	0.281	0.006	0.000	0.283
	Left Tilt	0.273	0.104	0.001	0.000	0.273

Table E-2
DSI=1 Held-to-ear AG1 Highest Adjusted SAR

AG1 Ratio to Limit								
Head SAR	Configuration	E	F	I	H	J	MIMO	Max
	Right Cheek	0.566	0.669	0.274	0.388	0.141	0.611	0.669
	Right Tilt	0.534	0.695	0.024	0.138	0.019	0.220	0.695
	Left Cheek	0.715	0.411	0.253	0.070	0.214	0.475	0.715
	Left Tilt	0.723	0.644	0.028	0.053	0.030	0.088	0.723

Table E-3
DSI=1 Held-to-ear AG Verification

Head SAR	Configuration	AG0 Ratio to Limit	AG1 Ratio to Limit	AG0 + AG1 Ratio to Limit
	Limit	1	1	1
	Right Cheek	0.329	0.669	0.998
	Right Tilt	0.203	0.695	0.898
	Left Cheek	0.283	0.715	0.998
	Left Tilt	0.273	0.723	0.996

Notes:

- For all combinations where the TER sum of AG0+AG1 is not greater than 1, there's no further analysis required for compliance demonstration.

E.5 Body-worn (DSI = 0) SAR Antenna Group Analysis

Table E-4
DSI=0 Body-worn AG0 Highest Adjusted SAR

AG0 Ratio to Limit						
Bodyworn SAR	Configuration	A	B	C	D	Max
	Back	0.621	0.148	0.051	0.099	0.621

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 3 of 8

Table E-5
DSI=0 Body-worn AG1 Highest Adjusted SAR

AG1 Ratio to Limit								
Bodyworn SAR	Configuration	E	F	I	H	J	MIMO	Max
	Back	0.623	0.244	0.099	0.329	0.258	0.343	0.623

Table E-6
DSI=0 Body-worn AG Verification

Bodyworn SAR	Configuration	AG0 Ratio to Limit	AG1 Ratio to Limit	AG0 + AG1 Ratio to Limit
	Limit	1	1	1
	Back	0.621	0.623	See Table Below

Back							
AG0			AG1			AG0 + AG1 Ratio to Limit	SPLSR
Antenna	Ratio to Limit	Position	Antenna	Ratio to Limit	Position		
Ant A	0.621	-67.300	Ant E	0.623	64.700	See Note 1	0.01
Ant A	0.621	N/A	Ant F	0.244	N/A	0.865	N/A
Ant A	0.621	N/A	Ant I	0.099	N/A	0.720	N/A
Ant A	0.621	N/A	Ant H	0.253	N/A	0.874	N/A
Ant A	0.621	N/A	Ant J	0.258	N/A	0.879	N/A
Ant A	0.621	N/A	MIMO	0.343	N/A	0.964	N/A
Ant B	0.148	N/A	Ant E	0.623	N/A	0.771	N/A
Ant B	0.148	N/A	Ant F	0.244	N/A	0.392	N/A
Ant B	0.148	N/A	Ant I	0.099	N/A	0.247	N/A
Ant B	0.148	N/A	Ant H	0.253	N/A	0.401	N/A
Ant B	0.148	N/A	Ant J	0.258	N/A	0.406	N/A
Ant B	0.148	N/A	MIMO	0.343	N/A	0.491	N/A
Ant C	0.051	N/A	Ant E	0.623	N/A	0.674	N/A
Ant C	0.051	N/A	Ant F	0.244	N/A	0.295	N/A
Ant C	0.051	N/A	Ant I	0.099	N/A	0.150	N/A
Ant C	0.051	N/A	Ant H	0.253	N/A	0.304	N/A
Ant C	0.051	N/A	Ant J	0.258	N/A	0.309	N/A
Ant C	0.051	N/A	MIMO	0.343	N/A	0.394	N/A
Ant D	0.099	N/A	Ant E	0.623	N/A	0.722	N/A
Ant D	0.099	N/A	Ant F	0.244	N/A	0.343	N/A
Ant D	0.099	N/A	Ant I	0.099	N/A	0.198	N/A
Ant D	0.099	N/A	Ant H	0.253	N/A	0.352	N/A
Ant D	0.099	N/A	Ant J	0.258	N/A	0.357	N/A
Ant D	0.099	N/A	MIMO	0.343	N/A	0.442	N/A

Notes:

1. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.02 per FCC KDB 447498 D01v06. Since TER was used in this evaluation the FCC SPLSR Limit of 0.04 is equivalent to the TER SPLSR of 0.02.
2. As a conservative assessment, the distances between AG0 and AG1 were determined using the worst case Y-axis coordinates of the peak locations only (assumes 0 mm separation on x/z axis) per antenna.
3. For all combinations where the TER sum of AG0+AG1 is not greater than 1, there's no further analysis required for compliance demonstration.

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 4 of 8

E.6 Hotspot (DSI = 0) SAR Antenna Group Analysis

Table E-7
DSI=0 Hotspot AG0 Highest Adjusted SAR

AG0 Ratio to Limit						
Hotspot SAR	Configuration	A	B	C	D	Max
	Back	0.621	0.148	0.051	0.099	0.621
	Front	0.407	0.104	0.026	0.007	0.407
	Top	-	-	-	-	-
	Bottom	0.676	0.150	0.024	0.018	0.676
	Right	0.368	-	-	0.005	0.368
	Left	0.297	0.178	0.078	-	0.297

Table E-8
DSI=0 Hotspot AG1 Highest Adjusted SAR

AG1 Ratio to Limit								
Hotspot SAR	Configuration	E	F	I	H	J	MIMO	Max
	Back	0.623	0.244	0.099	0.253	0.258	0.343	0.623
	Front	0.598	0.200	0.099	0.188	0.447	0.256	0.598
	Top	0.624	0.611	0.011	0.208	0.017	0.265	0.624
	Bottom	-	-	-	-	-	-	-
	Right	0.625	-	-	-	0.124	0.073	0.625
	Left	-	0.131	0.054	0.330	-	0.340	0.340

Table E-9
DSI=0 Hotspot AG Verification

Hotspot SAR	Configuration	AG0 Ratio to Limit	AG1 Ratio to Limit	AG0 + AG1 Ratio to Limit
	Limit	1	1	1
	Back	0.621	0.623	See Table Below
	Front	0.407	0.598	See Table Below
	Top	-	0.624	0.624
	Bottom	0.676	-	0.676
	Right	0.368	0.625	0.993
	Left	0.297	0.340	0.637

Back							
AG0			AG1			AG0 + AG1 Ratio to Limit	SPLSR
Antenna	Ratio to Limit	Position	Antenna	Ratio to Limit	Position		
Ant A	0.621	-67.300	Ant E	0.623	64.700	See Note 1	0.01
Ant A	0.621	N/A	Ant F	0.244	N/A	0.865	N/A
Ant A	0.621	N/A	Ant I	0.099	N/A	0.720	N/A
Ant A	0.621	N/A	Ant H	0.253	N/A	0.874	N/A
Ant A	0.621	N/A	Ant J	0.258	N/A	0.879	N/A
Ant A	0.621	N/A	MIMO	0.343	N/A	0.964	N/A
Ant B	0.148	N/A	Ant E	0.623	N/A	0.771	N/A
Ant B	0.148	N/A	Ant F	0.244	N/A	0.392	N/A
Ant B	0.148	N/A	Ant I	0.099	N/A	0.247	N/A
Ant B	0.148	N/A	Ant H	0.253	N/A	0.401	N/A
Ant B	0.148	N/A	Ant J	0.258	N/A	0.406	N/A
Ant B	0.148	N/A	MIMO	0.343	N/A	0.491	N/A
Ant C	0.051	N/A	Ant E	0.623	N/A	0.674	N/A
Ant C	0.051	N/A	Ant F	0.244	N/A	0.295	N/A
Ant C	0.051	N/A	Ant I	0.099	N/A	0.150	N/A
Ant C	0.051	N/A	Ant H	0.253	N/A	0.304	N/A
Ant C	0.051	N/A	Ant J	0.258	N/A	0.309	N/A
Ant C	0.051	N/A	MIMO	0.343	N/A	0.394	N/A
Ant D	0.099	N/A	Ant E	0.623	N/A	0.722	N/A
Ant D	0.099	N/A	Ant F	0.244	N/A	0.343	N/A
Ant D	0.099	N/A	Ant I	0.099	N/A	0.198	N/A
Ant D	0.099	N/A	Ant H	0.253	N/A	0.352	N/A
Ant D	0.099	N/A	Ant J	0.258	N/A	0.357	N/A
Ant D	0.099	N/A	MIMO	0.343	N/A	0.442	N/A

Front							
AG0			AG1			AG0 + AG1 Ratio to Limit	SPLSR
Antenna	Ratio to Limit	Position	Antenna	Ratio to Limit	Position		
Ant A	0.407	-53.000	Ant E	0.598	82.600	See Note 1	0.01
Ant A	0.407	N/A	Ant F	0.200	N/A	0.607	N/A
Ant A	0.407	N/A	Ant I	0.099	N/A	0.506	N/A
Ant A	0.407	N/A	Ant H	0.188	N/A	0.595	N/A
Ant A	0.407	N/A	Ant J	0.447	N/A	0.854	N/A
Ant A	0.407	N/A	MIMO	0.256	N/A	0.663	N/A
Ant B	0.104	N/A	Ant E	0.598	N/A	0.702	N/A
Ant B	0.104	N/A	Ant F	0.200	N/A	0.304	N/A
Ant B	0.104	N/A	Ant I	0.099	N/A	0.203	N/A
Ant B	0.104	N/A	Ant H	0.188	N/A	0.292	N/A
Ant B	0.104	N/A	Ant J	0.447	N/A	0.551	N/A
Ant B	0.104	N/A	MIMO	0.256	N/A	0.360	N/A
Ant C	0.026	N/A	Ant E	0.598	N/A	0.624	N/A
Ant C	0.026	N/A	Ant F	0.200	N/A	0.226	N/A
Ant C	0.026	N/A	Ant I	0.099	N/A	0.125	N/A
Ant C	0.026	N/A	Ant H	0.188	N/A	0.214	N/A
Ant C	0.026	N/A	Ant J	0.447	N/A	0.473	N/A
Ant C	0.026	N/A	MIMO	0.256	N/A	0.282	N/A
Ant D	0.007	N/A	Ant E	0.598	N/A	0.605	N/A
Ant D	0.007	N/A	Ant F	0.200	N/A	0.207	N/A
Ant D	0.007	N/A	Ant I	0.099	N/A	0.106	N/A
Ant D	0.007	N/A	Ant H	0.188	N/A	0.195	N/A
Ant D	0.007	N/A	Ant J	0.447	N/A	0.454	N/A
Ant D	0.007	N/A	MIMO	0.256	N/A	0.263	N/A

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 6 of 8

Notes:

1. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.02 per FCC KDB 447498 D01v06. Since TER was used in this evaluation the FCC SPLSR Limit of 0.04 is equivalent to the TER SPLSR of 0.02.
2. As a conservative assessment, the distances between AG0 and AG1 were determined using the worst case Y-axis coordinates of the peak locations only (assumes 0 mm separation on x/z axis) per antenna.
3. For all combinations where the TER sum of AG0+AG1 is not greater than 1, there's no further analysis required for compliance demonstration.

E.7 Phablet (DSI = 0) SAR Antenna Group Analysis

Per FCC KDB Publication 648474 D04 Handset SAR, Phablet SAR tests were not required if wireless router 1g SAR (scaled to the maximum output power, including tolerance) < 1.2 W/kg. Therefore, no further analysis beyond the tables included in this section was required to determine that possible simultaneous transmission scenarios would not exceed the SAR limit.

Table E-10
DSI=0 Phablet AG1 Highest Adjusted SAR

AG1 Ratio to Limit					
Phablet SAR	Configuration	E	H	MIMO	Max
	Back	0.564	0.280	0.286	0.564
	Front	0.069	0.226	0.344	0.344
	Top	0.129	0.080	0.145	0.145
	Bottom	-	-	-	-
	Right	0.028	-	0.062	0.062
	Left	-	0.614	0.735	0.735

Table E-11
DSI=0 Phablet AG, NFC and UWB Verification

Phablet SAR	Configuration	AG1 Ratio to Limit	NFC Ratio to Limit	UWB Ratio to Limit	AG1 + NFC + UWB Ratio to Limit
	Back	0.554	0.004	0.001	0.559
	Front	0.344	0.000	0.001	0.345
	Top	0.145	0.000	0.001	0.146
	Bottom	-	-	-	0.000
	Right	0.062	-	-	0.062
	Left	0.735	0.000	0.001	0.736

Notes:

1. For all combinations where the TER sum of AG1 +UWB+NFC is not greater than 1, there's no further analysis required for compliance demonstration.

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 7 of 8

E.8 Power Density Theoretical Calculations

Table E-12
Worst Case PD Theoretical Exposure

MG PD Antenna - Theoretical Worst Case						
Antenna	Bands	PD Design Target (W/m ²)	PD Uncertainty (dB)	Permanent Back off (dB)	PD Limit (W/m ²)	Theoretical Ratio to Limit
M	n258/n261/n260	7.24	1.4	0.5	10	0.891

Table E-13
DSI=0 Phablet MG Verification

Phablet SAR	Configuration	MG PD Ratio to Limit	NFC Ratio to Limit	UWB Ratio to Limit	MG + NFC + UWB Ratio to Limit
	Back	0.891	0.004	0.001	0.896
	Front	0.891	0.000	0.001	0.892
	Top	0.891	0.000	0.001	0.892
	Bottom	-	-	-	0.000
	Right	-	-	-	-
	Left	0.891	0.000	0.001	0.892

Notes:

1. For all combinations where the TER sum of MG +UWB+NFC is not greater than 1, there's no further analysis required for compliance demonstration.

E.9 Conclusion

The above numerical summed SAR results and SPLSR for all the combinations of antenna groups are sufficient to show that AG0 is mutually exclusive from AG1 and that MG is <1 TER. TER simultaneous transmission cases will not exceed the SAR limit or PD limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528- 2013 Section 6.3.4.1.

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 8 of 8