

APPENDIX H: LTE AND NR LOWER BANDWIDTH RF CONDUCTED POWERS

Note: Some bands do not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 1 of 207

H.1 LTE Lower Bandwidth RF Conducted Powers

H.1.1 LTE Band 71

Table H-1
LTE Band 71 Ant A Measured P_{Max} for all DSI - 15 MHz Bandwidth

LTE Band 71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.26	0	0
	1	36	24.21		0
	1	74	24.22		0
	36	0	23.16	0-1	1
	36	18	23.22		1
	36	37	23.29		1
16QAM	75	0	23.17	0-1	1
	1	0	23.26		1
	1	36	23.51		1
	1	74	23.38	0-2	1
	36	0	22.21		2
	36	18	22.23		2
64QAM	36	37	22.29	0-2	2
	75	0	22.21		2
	1	0	22.28	0-2	2
	1	36	22.51		2
	1	74	22.53		2
	36	0	21.17	0-3	3
256QAM	36	18	21.25		3
	36	37	21.31		3
	75	0	21.22	0-5	3
	1	0	19.21		5
	1	36	19.35		5
	1	74	19.26		5
	36	0	19.12		5
	36	18	19.21		5
	36	37	19.23		5
	75	0	19.16		5
					5
					5

Table H-2
LTE Band 71 Ant A Measured P_{Max} for all DSI - 10 MHz Bandwidth

LTE Band 71							
10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133172 (668.0 MHz)	133297 (680.5 MHz)	133422 (693.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.30	24.66	24.63	0	0
	1	25	24.44	24.82	24.54		0
	1	49	24.32	24.53	24.44		0
	25	0	23.13	23.48	23.55	0-1	1
	25	12	23.21	23.48	23.59		1
	25	25	23.22	23.55	23.61		1
	50	0	23.18	23.44	23.54		1
16QAM	1	0	23.32	23.59	23.78	0-1	1
	1	25	23.38	23.88	23.82		1
	1	49	23.44	23.81	23.70		1
	25	0	22.15	22.51	22.56	0-2	2
	25	12	22.25	22.54	22.60		2
	25	25	22.25	22.57	22.61		2
	50	0	22.21	22.45	22.54	0-2	2
1	0	22.43	22.68	22.77	2		
1	25	22.47	22.86	22.93	2		
64QAM	1	49	22.42	22.77	22.93		0-2
	25	0	21.15	21.47	21.53	3	
	25	12	21.26	21.48	21.60	3	
	25	25	21.22	21.53	21.60	0-3	3
	50	0	21.20	21.46	21.55		3
	1	0	19.22	19.52	19.62		0-5
	1	25	19.28	19.69	19.68	5	
1	49	19.37	19.66	19.55	5		
25	0	19.12	19.39	19.50	5		
25	12	19.20	19.45	19.46	5		
25	25	19.19	19.45	19.58	5		
256QAM	50	0	19.17	19.38	19.51		5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 2 of 207

Table H-3
LTE Band 71 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

LTE Band 71 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133147 (665.5 MHz)	133297 (680.5 MHz)	133447 (695.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.36	24.49	24.67	0	0
	1	12	24.27	24.66	24.77		0
	1	24	24.29	24.50	24.65		0
	12	0	23.19	23.46	23.53	0-1	1
	12	6	23.20	23.49	23.56		1
	12	13	23.17	23.52	23.55		1
	25	0	23.16	23.45	23.49		1
16QAM	1	0	23.57	23.78	23.92	0-1	1
	1	12	23.61	23.92	23.96		1
	1	24	23.55	23.87	23.78		1
	12	0	22.23	22.50	22.59	0-2	2
	12	6	22.25	22.54	22.59		2
	12	13	22.23	22.52	22.59		2
	25	0	22.17	22.46	22.54		2
64QAM	1	0	22.35	22.65	22.93	0-2	2
	1	12	22.43	22.79	22.89		2
	1	24	22.43	22.73	22.86		2
	12	0	21.18	21.44	21.55	0-3	3
	12	6	21.24	21.54	21.60		3
	12	13	21.16	21.55	21.59		3
	25	0	21.14	21.41	21.51		3
256QAM	1	0	19.27	19.57	19.62	0-5	5
	1	12	19.36	19.71	19.67		5
	1	24	19.33	19.60	19.57		5
	12	0	19.14	19.41	19.52		5
	12	6	19.17	19.48	19.56		5
	12	13	19.10	19.48	19.48		5
	25	0	19.14	19.40	19.45		5

Table H-4
LTE Band 71 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

LTE Band 71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.55	0	0
	1	36	23.70		0
	1	74	23.76		0
	36	0	22.68	0-1	1
	36	18	22.73		1
	36	37	22.79		1
	75	0	22.75		1
16QAM	1	0	22.73	0-1	1
	1	36	22.89		1
	1	74	22.98		1
	36	0	21.72	0-2	2
	36	18	21.76		2
	36	37	21.82		2
	75	0	21.72		2
64QAM	1	0	21.87	0-2	2
	1	36	22.09		2
	1	74	22.03		2
	36	0	20.70	0-3	3
	36	18	20.80		3
	36	37	20.80		3
	75	0	20.73		3
256QAM	1	0	18.69	0-5	5
	1	36	18.97		5
	1	74	18.88		5
	36	0	18.64		5
	36	18	18.70		5
	36	37	18.78		5
	75	0	18.69		5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 3 of 207

Table H-5

LTE Band 71 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 71 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133172 (668.0 MHz)	133297 (680.5 MHz)	133422 (693.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.58	23.75	23.79	0	0
	1	25	23.61	24.20	23.84		0
	1	49	23.59	24.03	23.79		0
	25	0	22.42	22.78	22.87	0-1	1
	25	12	22.49	22.80	22.90		1
	25	25	22.53	22.84	22.91		1
	50	0	22.47	22.76	22.85		1
16QAM	1	0	22.60	23.02	23.19	0-1	1
	1	25	22.70	23.23	23.17		1
	1	49	22.67	23.09	23.03		1
	25	0	21.47	21.81	21.89	0-2	2
	25	12	21.58	21.82	21.93		2
	25	25	21.58	21.87	21.96		2
	50	0	21.51	21.84	21.87		2
64QAM	1	0	21.61	21.97	22.17	0-2	2
	1	25	21.73	22.20	22.26		2
	1	49	21.73	22.12	22.12		2
	25	0	20.50	20.80	20.87	0-3	3
	25	12	20.57	20.88	20.88		3
	25	25	20.53	20.86	20.93		3
	50	0	20.51	20.78	20.87		3
256QAM	1	0	18.41	18.74	18.94	0-5	5
	1	25	18.60	19.03	19.11		5
	1	49	18.63	18.88	18.94		5
	25	0	18.41	18.73	18.81		5
	25	12	18.49	18.77	18.82		5
	25	25	18.53	18.83	18.87		5
	50	0	18.48	18.77	18.78		5

Table H-6

LTE Band 71 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 71 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133147 (665.5 MHz)	133297 (680.5 MHz)	133447 (695.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.49	23.79	23.93	0	0
	1	12	23.48	24.00	24.05		0
	1	24	23.39	23.92	23.97		0
	12	0	22.44	22.73	22.85	0-1	1
	12	6	22.46	22.76	22.85		1
	12	13	22.37	22.76	22.87		1
	25	0	22.41	22.72	22.80		1
16QAM	1	0	22.72	23.06	23.37	0-1	1
	1	12	22.76	23.11	23.45		1
	1	24	22.74	23.17	23.23		1
	12	0	21.50	21.78	21.85	0-2	2
	12	6	21.49	21.84	21.91		2
	12	13	21.43	21.85	21.87		2
	25	0	21.37	21.77	21.80		2
64QAM	1	0	21.72	22.08	22.06	0-2	2
	1	12	21.77	22.17	22.37		2
	1	24	21.66	22.09	22.07		2
	12	0	20.50	20.80	20.84	0-3	3
	12	6	20.46	20.81	20.89		3
	12	13	20.45	20.85	20.86		3
	25	0	20.40	20.76	20.81		3
256QAM	1	0	18.55	18.85	18.93	0-5	5
	1	12	18.51	19.09	19.04		5
	1	24	18.67	18.93	18.99		5
	12	0	18.42	18.73	18.83		5
	12	6	18.45	18.73	18.89		5
	12	13	18.33	18.77	18.83		5
	25	0	18.38	18.67	18.76		5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 4 of 207

Table H-7
LTE Band 71 Ant E Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz) Conducted Power [dBm]		
QPSK	1	0	17.24	0	0
	1	36	17.37		0
	1	74	17.42		0
	36	0	17.35	0-1	0
	36	18	17.44		0
	36	37	17.46		0
	75	0	17.44		0
16QAM	1	0	17.39	0-1	0
	1	36	17.66		0
	1	74	17.65		0
	36	0	17.43	0-2	0
	36	18	17.51		0
	36	37	17.55		0
	75	0	17.45		0
64QAM	1	0	17.62	0-2	0
	1	36	17.83		0
	1	74	17.74		0
	36	0	17.43	0-3	0
	36	18	17.48		0
	36	37	17.58		0
	75	0	17.48		0
256QAM	1	0	17.46	0-5	0
	1	36	17.74		0
	1	74	17.62		0
	36	0	17.43		0
	36	18	17.50		0
	36	37	17.52		0
	75	0	17.48		0

Table H-8
LTE Band 71 Ant E Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 71 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133172 (668.0 MHz)	133297 (680.5 MHz)	133422 (693.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.26	17.45	17.60	0	0
	1	25	17.39	17.61	17.74		0
	1	49	17.53	17.50	17.47		0
	25	0	17.14	17.49	17.59	0-1	0
	25	12	17.23	17.52	17.60		0
	25	25	17.27	17.54	17.62		0
	50	0	17.24	17.49	17.57		0
16QAM	1	0	17.43	17.59	17.83	0-1	0
	1	25	17.64	17.79	17.96		0
	1	49	17.65	17.79	17.66		0
	25	0	17.21	17.52	17.63	0-2	0
	25	12	17.29	17.56	17.65		0
	25	25	17.32	17.60	17.70		0
	50	0	17.23	17.51	17.60		0
64QAM	1	0	17.23	17.68	17.89	0-2	0
	1	25	17.60	17.91	17.86		0
	1	49	17.49	17.87	17.84		0
	25	0	17.18	17.54	17.63	0-3	0
	25	12	17.33	17.56	17.65		0
	25	25	17.33	17.60	17.67		0
	50	0	17.26	17.50	17.55		0
256QAM	1	0	17.24	17.63	17.67	0-5	0
	1	25	17.52	17.81	17.88		0
	1	49	17.50	17.71	17.57		0
	25	0	17.19	17.51	17.59		0
	25	12	17.26	17.59	17.64		0
	25	25	17.31	17.60	17.68		0
	50	0	17.27	17.52	17.58		0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 5 of 207

Table H-9
LTE Band 71 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 71 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			133147 (665.5 MHz)	133297 (680.5 MHz)	133447 (695.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	17.36	17.35	17.72	0	0	
	1	12	17.34	17.60	17.74		0	
	1	24	17.28	17.39	17.63		0	
	12	0	17.20	17.45	17.60	0-1	0	
	12	6	17.18	17.55	17.60		0	
	12	13	17.17	17.52	17.62		0	
16QAM	25	0	17.17	17.50	17.57	0-1	0	
	1	0	17.50	17.69	17.56		0-2	0
	1	12	17.57	17.88	17.58			0
	1	24	17.52	17.74	17.88	0		
	12	0	17.23	17.54	17.64	0		
	12	6	17.25	17.56	17.69	0		
64QAM	12	13	17.23	17.56	17.69	0-2	0	
	25	0	17.21	17.52	17.60		0	
	1	0	17.47	17.58	17.79		0-2	0
	1	12	17.40	17.78	17.88	0		
	1	24	17.46	17.63	17.74	0-3		0
	12	0	17.21	17.49	17.63		0	
256QAM	12	6	17.28	17.56	17.63		0-3	0
	12	13	17.28	17.57	17.66	0		
	25	0	17.16	17.51	17.55	0-5		0
	1	0	17.37	17.67	17.71		0-5	0
	1	12	17.42	17.82	17.73			0
	1	24	17.30	17.74	17.77	0		
256QAM	12	0	17.23	17.54	17.61	0-5	0	
	12	6	17.24	17.58	17.65		0	
	12	13	17.17	17.62	17.63		0	
	25	0	17.20	17.53	17.61		0	

H.1.2 LTE Band 12

Table H-10
LTE Band 12 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.85	24.73	24.81	0	0
	1	12	24.88	24.82	24.79		0
	1	24	24.83	24.61	24.65		0
	12	0	23.69	23.77	23.71	0-1	1
	12	6	23.84	23.78	23.73		1
	12	13	23.74	23.67	23.66		1
16QAM	25	0	23.78	23.74	23.67	0-1	1
	1	0	24.16	24.17	24.14		1
	1	12	24.15	24.14	24.10		1
	1	24	24.09	24.00	24.01	0-2	1
	12	0	22.75	22.75	22.74		2
	12	6	22.86	22.78	22.75		2
64QAM	12	13	22.80	22.70	22.70	0-2	2
	25	0	22.77	22.72	22.64		2
	1	0	23.07	22.97	22.88	0-2	2
	1	12	23.15	23.02	23.03		2
	1	24	23.15	22.89	22.91		2
	12	0	21.77	21.71	21.74	0-3	3
12	6	21.87	21.78	21.77	3		
12	13	21.80	21.69	21.67	3		
256QAM	25	0	21.77	21.71	21.68	0-5	3
	1	0	19.83	19.88	19.94		5
	1	12	19.97	19.97	19.86		5
	1	24	19.80	19.79	19.62		5
	12	0	19.74	19.68	19.66		5
	12	6	19.81	19.75	19.68		5
	12	13	19.69	19.64	19.57		5
	25	0	19.72	19.65	19.66		5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 6 of 207

Table H-11
LTE Band 12 Ant A Measured P_{Max} for all DSI - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.83	24.77	24.59	0	0
	1	7	25.04	24.83	24.70		0
	1	14	24.89	24.73	24.56		0
	8	0	23.80	23.76	23.71	0-1	1
	8	4	23.85	23.74	23.68		1
	8	7	23.82	23.70	23.66		1
	15	0	23.81	23.73	23.67		1
16QAM	1	0	24.14	23.93	23.77	0-1	1
	1	7	24.28	24.09	23.93		1
	1	14	24.16	23.92	23.76		1
	8	0	22.89	22.82	22.75	0-2	2
	8	4	22.89	22.84	22.72		2
	8	7	22.92	22.81	22.69		2
	15	0	22.82	22.75	22.67		2
64QAM	1	0	22.97	23.08	22.79	0-2	2
	1	7	23.22	23.09	22.93		2
	1	14	23.03	22.86	22.90		2
	8	0	21.88	21.74	21.67	0-3	3
	8	4	21.92	21.73	21.71		3
	8	7	21.88	21.74	21.62		3
	15	0	21.77	21.75	21.68		3
256QAM	1	0	19.75	19.73	19.70	0-5	5
	1	7	19.99	20.00	19.77		5
	1	14	19.79	19.75	19.57		5
	8	0	19.76	19.73	19.61		5
	8	4	19.79	19.75	19.65		5
	8	7	19.74	19.67	19.58		5
	15	0	19.77	19.72	19.63		5

Table H-12
LTE Band 12 Ant A Measured P_{Max} for all DSI – 1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]		
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)				
			Conducted Power [dBm]						
QPSK	1	0	24.69	24.83	24.68	0	0		
	1	2	24.69	24.78	24.60		0		
	1	5	24.81	24.84	24.68		0		
	3	0	24.81	24.77	24.58		0		
	3	2	24.78	24.79	24.58		0		
	3	3	24.79	24.74	24.59		0		
16QAM	6	0	23.75	23.70	23.56	0-1	1		
	1	0	24.09	24.24	23.79		1		
	1	2	24.30	24.10	23.87		1		
	1	5	24.07	24.16	23.78		1		
	3	0	24.00	23.95	23.85		1		
	3	2	23.95	23.98	23.86		1		
64QAM	3	3	23.90	23.94	23.85	0-1	1		
	6	0	22.84	22.77	22.69		0-2	2	
	1	0	22.88	23.04	22.94			2	
	1	2	22.97	23.00	22.98			2	
	1	5	22.97	22.94	22.83			2	
	3	0	22.88	22.95	22.77			2	
256QAM	3	2	22.90	23.07	22.93	0-2		2	
	3	3	22.94	23.12	22.81		2		
	6	0	21.80	21.82	21.62		0-3	3	
	1	0	19.88	19.86	19.66			0-5	5
	1	2	19.95	19.89	19.70				5
	1	5	19.93	19.93	19.64				5
3	0	19.77	19.85	19.62	5				
3	2	19.82	19.80	19.71	5				
256QAM	3	3	19.77	19.75	19.60	0-5	5		
	6	0	19.73	19.66	19.53		5		

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 7 of 207

Table H-13

LTE Band 12 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.34	24.26	24.32	0	0
	1	12	24.35	24.32	24.27		0
	1	24	24.33	24.13	24.16		0
	12	0	23.21	23.23	23.19	0-1	1
	12	6	23.32	23.29	23.20		1
	12	13	23.23	23.19	23.14		1
	25	0	23.27	23.22	23.19		1
16QAM	1	0	23.74	23.62	23.62	0-1	1
	1	12	23.79	23.56	23.64		1
	1	24	23.48	23.44	23.55		1
	12	0	22.29	22.25	22.23	0-2	2
	12	6	22.39	22.32	22.27		2
	12	13	22.27	22.23	22.18		2
	25	0	22.28	22.22	22.18		2
64QAM	1	0	22.68	22.59	22.42	0-2	2
	1	12	22.66	22.61	22.45		2
	1	24	22.61	22.41	22.40		2
	12	0	21.24	21.27	21.17	0-3	3
	12	6	21.34	21.30	21.26		3
	12	13	21.29	21.21	21.14		3
	25	0	21.28	21.16	21.14		3
256QAM	1	0	19.35	19.38	19.38	0-5	5
	1	12	19.39	19.48	19.40		5
	1	24	19.30	19.26	19.16		5
	12	0	19.16	19.19	19.16		5
	12	6	19.28	19.26	19.13		5
	12	13	19.19	19.16	19.09		5
	25	0	19.24	19.21	19.14		5

Table H-14

LTE Band 12 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.21	24.20	24.23	0	0
	1	7	24.35	24.26	24.31		0
	1	14	24.22	24.19	24.13		0
	8	0	23.22	23.23	23.20	0-1	1
	8	4	23.26	23.31	23.20		1
	8	7	23.23	23.30	23.15		1
	15	0	23.23	23.31	23.17		1
16QAM	1	0	23.41	23.53	23.44	0-1	1
	1	7	23.61	23.71	23.56		1
	1	14	23.46	23.35	23.43		1
	8	0	22.36	22.33	22.28	0-2	2
	8	4	22.37	22.34	22.27		2
	8	7	22.33	22.31	22.23		2
	15	0	22.29	22.31	22.24		2
64QAM	1	0	22.60	22.49	22.39	0-2	2
	1	7	22.68	22.67	22.47		2
	1	14	22.40	22.40	22.29		2
	8	0	21.35	21.22	21.24	0-3	3
	8	4	21.32	21.32	21.22		3
	8	7	21.31	21.28	21.17		3
	15	0	21.28	21.30	21.17		3
256QAM	1	0	19.25	19.19	19.16	0-5	5
	1	7	19.49	19.53	19.28		5
	1	14	19.23	19.29	19.15		5
	8	0	19.26	19.21	19.15		5
	8	4	19.24	19.30	19.17		5
	8	7	19.24	19.23	19.14		5
	15	0	19.22	19.27	19.17		5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 8 of 207

Table H-15
LTE Band 12 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) – 1.4 MHz Bandwidth

LTE Band 12							
1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.27	24.27	24.09	0	0
	1	2	24.30	24.27	24.15		0
	1	5	24.24	24.30	24.10		0
	3	0	24.24	24.25	24.16		0
	3	2	24.31	24.23	24.05		0
	3	3	24.26	24.28	24.04		0
	6	0	23.26	23.21	23.12		0-1
16QAM	1	0	23.43	23.47	23.40	0-1	1
	1	2	23.48	23.39	23.40		1
	1	5	23.41	23.46	23.40		1
	3	0	23.55	23.55	23.38		1
	3	2	23.59	23.55	23.31		1
	3	3	23.53	23.49	23.29		1
	6	0	22.42	22.36	22.22		0-2
64QAM	1	0	22.59	22.48	22.45	0-2	2
	1	2	22.47	22.64	22.43		2
	1	5	22.52	22.51	22.50		2
	3	0	22.40	22.41	22.35		2
	3	2	22.43	22.44	22.47		2
	3	3	22.44	22.40	22.31		2
	6	0	21.33	21.29	21.21		0-3
256QAM	1	0	19.37	19.26	19.39	0-5	5
	1	2	19.32	19.43	19.24		5
	1	5	19.29	19.36	19.16		5
	3	0	19.30	19.30	19.19		5
	3	2	19.39	19.26	19.21		5
	3	3	19.28	19.32	19.05		5
	6	0	19.23	19.25	19.11		5

Table H-16
LTE Band 12 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.77	20.65	20.76	0	0
	1	12	20.86	20.75	20.70		0
	1	24	20.70	20.55	20.56		0
	12	0	20.68	20.70	20.63	0-1	0
	12	6	20.77	20.71	20.65		0
	12	13	20.73	20.62	20.60		0
	25	0	20.73	20.66	20.59		0
16QAM	1	0	21.05	20.98	21.04	0-1	0
	1	12	21.08	21.08	21.02		0
	1	24	20.91	20.89	21.04		0
	12	0	20.74	20.75	20.71	0-2	0
	12	6	20.85	20.78	20.69		0
	12	13	20.75	20.70	20.63		0
	25	0	20.76	20.66	20.66		0
64QAM	1	0	21.05	20.98	20.89	0-2	0
	1	12	21.00	21.04	21.03		0
	1	24	20.90	20.91	20.82		0
	12	0	20.72	20.71	20.74	0-3	0
	12	6	20.80	20.78	20.73		0
	12	13	20.74	20.68	20.68		0
	25	0	20.74	20.71	20.65		0
256QAM	1	0	19.35	19.40	19.31	0-5	2
	1	12	19.43	19.42	19.36		2
	1	24	19.32	19.37	19.17		2
	12	0	19.19	19.19	19.18		2
	12	6	19.32	19.27	19.19		2
	12	13	19.29	19.18	19.13		2
	25	0	19.24	19.19	19.17		2

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 9 of 207

Table H-17
LTE Band 12 Ant E Measured P_{Limit} for DSI = 1 (Head) - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.74	20.67	20.50	0	0
	1	7	20.89	20.86	20.57		0
	1	14	20.71	20.54	20.38		0
	8	0	20.73	20.68	20.60	0-1	0
	8	4	20.73	20.70	20.61		0
	8	7	20.69	20.65	20.55		0
	15	0	20.73	20.66	20.61		0
16QAM	1	0	20.97	20.88	20.73	0-1	0
	1	7	21.10	21.00	20.89		0
	1	14	21.02	20.86	20.62		0
	8	0	20.84	20.78	20.69	0-2	0
	8	4	20.87	20.79	20.75		0
	8	7	20.83	20.74	20.64		0
	15	0	20.79	20.68	20.61		0
64QAM	1	0	20.92	20.81	20.82	0-2	0
	1	7	20.95	20.98	20.85		0
	1	14	20.84	20.88	20.79		0
	8	0	20.83	20.76	20.63	0-3	0
	8	4	20.87	20.77	20.67		0
	8	7	20.82	20.74	20.62		0
	15	0	20.78	20.69	20.66		0
256QAM	1	0	19.34	19.17	19.23	0-5	2
	1	7	19.47	19.47	19.28		2
	1	14	19.30	19.21	19.19		2
	8	0	19.26	19.20	19.18		2
	8	4	19.35	19.23	19.16		2
	8	7	19.24	19.21	19.13		2
	15	0	19.28	19.18	19.11		2

Table H-18
LTE Band 12 Ant E Measured P_{Limit} for DSI = 1 (Head) – 1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.64	20.69	20.56	0	0
	1	2	20.59	20.66	20.54		0
	1	5	20.59	20.71	20.54		0
	3	0	20.56	20.68	20.53		0
	3	2	20.60	20.67	20.51		0
	3	3	20.65	20.65	20.50		0
16QAM	6	0	20.65	20.59	20.49	0-1	0
	1	0	20.83	20.84	20.98	0-1	0
	1	2	20.98	20.95	20.96		0
	1	5	20.95	20.78	20.92		0
	3	0	20.84	20.84	20.70		0
	3	2	20.90	20.88	20.69		0
64QAM	3	3	20.91	20.99	20.68		0
	6	0	20.80	20.74	20.63	0-2	0
	1	0	21.05	21.09	20.75	0-2	0
	1	2	21.09	20.99	20.88		0
	1	5	21.00	20.91	20.71		0
	3	0	20.93	20.77	20.77		0
3	2	20.89	20.88	20.74	0		
3	3	20.84	20.77	20.75	0		
256QAM	6	0	20.72	20.73	20.62	0-3	0
	1	0	19.34	19.26	19.23	0-5	2
	1	2	19.40	19.46	19.32		2
	1	5	19.30	19.38	19.13		2
	3	0	19.30	19.28	19.09		2
	3	2	19.37	19.29	19.14		2
3	3	19.40	19.31	19.09	2		
256QAM	6	0	19.23	19.16	19.08		2

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 10 of 207

H.1.3 LTE Band 13

Table H-19
LTE Band 13 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz) Conducted Power [dBm]		
QPSK	1	0	24.15	0	0
	1	12	24.30		0
	1	24	24.29		0
	12	0	23.13	0-1	1
	12	6	23.23		1
	12	13	23.18		1
16QAM	25	0	23.22	0-1	1
	1	0	23.41		1
	1	12	23.63		1
	1	24	23.68	0-2	1
	12	0	22.18		2
	12	6	22.32		2
64QAM	12	13	22.25	0-2	2
	25	0	22.25		2
	1	0	22.22	0-2	2
	1	12	22.40		2
	1	24	22.62		2
	12	0	21.17	0-3	3
256QAM	12	6	21.28		3
	12	13	21.24		3
	25	0	21.26	0-5	3
	1	0	19.41		5
	1	12	19.42		5
	1	24	19.38		5
256QAM	12	0	19.19		5
	12	6	19.28		5
	12	13	19.23		5
	25	0	19.23		5

Table H-20
LTE Band 13 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz) Conducted Power [dBm]		
QPSK	1	0	23.71	0	0
	1	12	23.76		0
	1	24	23.72		0
	12	0	22.43	0-1	1
	12	6	22.67		1
	12	13	22.59		1
16QAM	25	0	22.63	0-1	1
	1	0	22.19		1
	1	12	23.01		1
	1	24	22.97	0-2	1
	12	0	21.48		2
	12	6	21.69		2
64QAM	12	13	21.64	0-2	2
	25	0	21.63		2
	1	0	21.25	0-2	2
	1	12	21.88		2
	1	24	22.08		2
	12	0	20.58	0-3	3
256QAM	12	6	20.66		3
	12	13	20.58		3
	25	0	20.61	0-5	3
	1	0	18.52		5
	1	12	18.77		5
	1	24	18.60		5
	12	0	18.53		5
	12	6	18.63		5
256QAM	12	13	18.60		5
	25	0	18.63		5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 11 of 207

Table H-21
LTE Band 13 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	20.41	0	0
	1	12	20.41		0
	1	24	20.41		0
	12	0	20.28	0-1	0
	12	6	20.40		0
	12	13	20.34		0
	25	0	20.39		0
16QAM	1	0	20.67	0-1	0
	1	12	20.71		0
	1	24	20.72		0
	12	0	20.35	0-2	0
	12	6	20.50		0
	12	13	20.39		0
	25	0	20.39		0
64QAM	1	0	20.47	0-2	0
	1	12	20.61		0
	1	24	20.52		0
	12	0	20.33	0-3	0
	12	6	20.48		0
	12	13	20.41		0
	25	0	20.37		0
256QAM	1	0	18.44	0-5	2
	1	12	18.88		2
	1	24	18.66		2
	12	0	18.52		2
	12	6	18.64		2
	12	13	18.59		2
	25	0	18.61		2

H.1.4 LTE Band 14

Table H-22
LTE Band 14 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

LTE Band 14 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23330 (793.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.83	0	0
	1	12	24.87		0
	1	24	24.77		0
	12	0	23.66	0-1	1
	12	6	23.75		1
	12	13	23.72		1
	25	0	23.73		1
16QAM	1	0	24.14	0-1	1
	1	12	24.22		1
	1	24	24.09		1
	12	0	22.71	0-2	2
	12	6	22.83		2
	12	13	22.73		2
	25	0	22.73		2
64QAM	1	0	22.81	0-2	2
	1	12	23.01		2
	1	24	23.12		2
	12	0	21.71	0-3	3
	12	6	21.79		3
	12	13	21.73		3
	25	0	21.76		3
256QAM	1	0	19.70	0-5	5
	1	12	19.89		5
	1	24	19.80		5
	12	0	19.64		5
	12	6	19.77		5
	12	13	19.68		5
	25	0	19.69		5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 12 of 207

Table H-23
LTE Band 14 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 14 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23330 (793.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.03	0	0
	1	12	24.09		0
	1	24	24.05		0
	12	0	23.02	0-1	1
	12	6	23.09		1
	12	13	23.06		1
	25	0	23.09		1
16QAM	1	0	23.32	0-1	1
	1	12	23.46		1
	1	24	23.46		1
	12	0	22.02	0-2	2
	12	6	22.17		2
	12	13	22.11		2
	25	0	22.06		2
64QAM	1	0	22.16	0-2	2
	1	12	22.44		2
	1	24	22.28		2
	12	0	21.04	0-3	3
	12	6	21.16		3
	12	13	21.12		3
	25	0	21.08		3
256QAM	1	0	19.20	0-5	5
	1	12	19.30		5
	1	24	19.09		5
	12	0	18.99		5
	12	6	19.08		5
	12	13	19.05		5
	25	0	19.04		5

Table H-24
LTE Band 14 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 14 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23330 (793.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	20.47	0	0
	1	12	20.51		0
	1	24	20.39		0
	12	0	20.49	0-1	0
	12	6	20.59		0
	12	13	20.51		0
	25	0	20.53		0
16QAM	1	0	20.70	0-1	0
	1	12	20.79		0
	1	24	20.77		0
	12	0	20.49	0-2	0
	12	6	20.57		0
	12	13	20.50		0
	25	0	20.49		0
64QAM	1	0	20.64	0-2	0
	1	12	20.80		0
	1	24	20.70		0
	12	0	20.44	0-3	0
	12	6	20.62		0
	12	13	20.50		0
	25	0	20.51		0
256QAM	1	0	19.08	0-5	1.7
	1	12	19.24		1.7
	1	24	19.15		1.7
	12	0	18.98		1.7
	12	6	19.06		1.7
	12	13	19.02		1.7
	25	0	18.99		1.7

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 13 of 207

H.1.5 LTE Band 26

Table H-25
LTE Band 26 Ant A Measured P_{Max} for all DSI - 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.47	24.23	24.39	0	0
	1	25	24.40	24.30	24.45		0
	1	49	24.55	24.28	24.42		0
	25	0	23.35	23.31	23.41	0-1	1
	25	12	23.43	23.38	23.52		1
	25	25	23.38	23.36	23.51		1
	50	0	23.39	23.38	23.52		1
16QAM	1	0	23.83	23.70	23.77	0-1	1
	1	25	23.94	23.83	23.92		1
	1	49	23.87	23.80	23.63		1
	25	0	22.34	22.31	22.46	0-2	2
	25	12	22.41	22.34	22.51		2
	25	25	22.36	22.34	22.51		2
	50	0	22.40	22.35	22.52		2
64QAM	1	0	22.71	22.71	22.72	0-2	2
	1	25	22.91	22.81	22.91		2
	1	49	22.96	22.68	22.66		2
	25	0	21.34	21.29	21.41	0-3	3
	25	12	21.41	21.42	21.52		3
	25	25	21.41	21.41	21.50		3
	50	0	21.41	21.37	21.48		3
256QAM	1	0	19.60	19.40	19.53	0-5	5
	1	25	19.47	19.46	19.63		5
	1	49	19.47	19.50	19.51		5
	25	0	19.38	19.26	19.41		5
	25	12	19.42	19.36	19.53		5
	25	25	19.37	19.34	19.48		5
	50	0	19.38	19.32	19.47		5

Table H-26
LTE Band 26 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.24	24.27	24.35	0	0
	1	12	24.25	24.29	24.40		0
	1	24	24.20	24.24	24.29		0
	12	0	23.31	23.25	23.44	0-1	1
	12	6	23.39	23.34	23.53		1
	12	13	23.36	23.29	23.44		1
	25	0	23.34	23.27	23.46		1
16QAM	1	0	23.69	23.42	23.81	0-1	1
	1	12	23.77	23.47	23.72		1
	1	24	23.63	23.56	23.71		1
	12	0	22.31	22.27	22.46	0-2	2
	12	6	22.41	22.37	22.56		2
	12	13	22.34	22.32	22.54		2
	25	0	22.35	22.30	22.52		2
64QAM	1	0	22.59	22.56	22.82	0-2	2
	1	12	22.64	22.66	22.84		2
	1	24	22.62	22.50	22.66		2
	12	0	21.32	21.30	21.47	0-3	3
	12	6	21.45	21.34	21.58		3
	12	13	21.38	21.36	21.55		3
	25	0	21.39	21.32	21.52		3
256QAM	1	0	19.50	19.40	19.62	0-5	5
	1	12	19.57	19.49	19.72		5
	1	24	19.47	19.51	19.65		5
	12	0	19.31	19.26	19.44		5
	12	6	19.38	19.35	19.52		5
	12	13	19.37	19.31	19.49		5
	25	0	19.37	19.34	19.49		5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 14 of 207

Table H-27
LTE Band 26 Ant A Measured P_{Max} for all DSI - 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.39	24.13	24.32	0	0
	1	7	24.40	24.19	24.44		0
	1	14	24.38	24.14	24.31		0
	8	0	23.41	23.30	23.38	0-1	1
	8	4	23.40	23.30	23.46		1
	8	7	23.39	23.37	23.45		1
	15	0	23.41	23.33	23.43		1
16QAM	1	0	23.74	23.49	23.64	0-1	1
	1	7	23.63	23.64	23.69		1
	1	14	23.67	23.60	23.70		1
	8	0	22.45	22.27	22.51	0-2	2
	8	4	22.43	22.40	22.54		2
	8	7	22.43	22.28	22.56		2
	15	0	22.38	22.35	22.44		2
64QAM	1	0	22.77	22.55	22.82	0-2	2
	1	7	22.81	22.72	22.80		2
	1	14	22.72	22.63	22.71		2
	8	0	21.53	21.31	21.49	0-3	3
	8	4	21.46	21.33	21.57		3
	8	7	21.46	21.37	21.52		3
	15	0	21.39	21.32	21.47		3
256QAM	1	0	19.51	19.40	19.58	0-5	5
	1	7	19.57	19.56	19.75		5
	1	14	19.40	19.52	19.59		5
	8	0	19.43	19.28	19.44		5
	8	4	19.41	19.36	19.53		5
	8	7	19.41	19.36	19.56		5
	15	0	19.37	19.30	19.45		5

Table H-28
LTE Band 26 Ant A Measured P_{Max} for all DSI – 1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.24	24.21	24.33	0	0
	1	2	24.28	24.29	24.32		0
	1	5	24.23	24.31	24.33		0
	3	0	24.37	24.29	24.45		0
	3	2	24.37	24.32	24.50		0
	3	3	24.39	24.34	24.50		0
	6	0	22.89	22.83	23.10		0-1
16QAM	1	0	23.77	23.70	23.88	0-1	1
	1	2	23.76	23.72	23.79		1
	1	5	23.78	23.59	23.77		1
	3	0	23.53	23.33	23.65		1
	3	2	23.43	23.38	23.66		1
	3	3	23.43	23.37	23.62		1
	6	0	22.45	22.34	22.54		0-2
64QAM	1	0	22.72	22.61	22.77	0-2	2
	1	2	22.71	22.69	22.75		2
	1	5	22.72	22.70	22.87		2
	3	0	22.46	22.36	22.66		2
	3	2	22.45	22.40	22.62		2
	3	3	22.41	22.40	22.56		2
	6	0	21.43	21.32	21.55		0-3
256QAM	1	0	19.64	19.43	19.66	0-5	5
	1	2	19.64	19.42	19.70		5
	1	5	19.57	19.44	19.72		5
	3	0	19.48	19.23	19.54		5
	3	2	19.45	19.31	19.59		5
	3	3	19.44	19.31	19.52		5
	6	0	19.38	19.34	19.47		5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 15 of 207

Table H-29

LTE Band 26 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.03	23.70	23.74	0	0
	1	25	24.01	23.89	23.76		0
	1	49	23.92	23.70	23.74		0
	25	0	22.75	22.68	22.79	0-1	1
	25	12	22.83	22.78	22.90		1
	25	25	22.79	22.76	22.89		1
	50	0	22.83	22.73	22.90		1
16QAM	1	0	23.07	22.73	22.89	0-1	1
	1	25	23.09	22.92	23.01		1
	1	49	22.92	22.83	23.12		1
	25	0	21.79	21.71	21.80	0-2	2
	25	12	21.86	21.78	21.89		2
	25	25	21.83	21.77	21.89		2
	50	0	21.84	21.79	21.90		2
64QAM	1	0	22.03	21.92	22.07	0-2	2
	1	25	22.09	21.92	22.20		2
	1	49	21.86	21.99	22.07		2
	25	0	20.74	20.68	20.79	0-3	3
	25	12	20.82	20.77	20.91		3
	25	25	20.80	20.79	20.86		3
	50	0	20.81	20.73	20.87		3
256QAM	1	0	19.02	18.85	19.03	0-5	5
	1	25	19.00	19.02	19.04		5
	1	49	18.93	18.81	18.88		5
	25	0	18.76	18.66	18.80		5
	25	12	18.82	18.77	18.85		5
	25	25	18.78	18.77	18.85		5
	50	0	18.80	18.72	18.81		5

Table H-30

LTE Band 26 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.87	23.69	23.87	0	0
	1	12	23.90	23.73	23.97		0
	1	24	23.84	23.62	23.90		0
	12	0	22.74	22.69	22.83	0-1	1
	12	6	22.84	22.76	22.91		1
	12	13	22.77	22.72	22.85		1
	25	0	22.80	22.72	22.89		1
16QAM	1	0	23.11	23.03	23.33	0-1	1
	1	12	23.05	23.08	23.48		1
	1	24	23.03	23.10	23.23		1
	12	0	21.76	21.72	21.86	0-2	2
	12	6	21.88	21.80	21.98		2
	12	13	21.81	21.71	21.90		2
	25	0	21.81	21.76	21.86		2
64QAM	1	0	22.10	21.96	22.13	0-2	2
	1	12	22.16	21.96	22.09		2
	1	24	22.01	21.90	22.02		2
	12	0	20.80	20.67	20.82	0-3	3
	12	6	20.91	20.79	20.97		3
	12	13	20.79	20.73	20.88		3
	25	0	20.79	20.73	20.93		3
256QAM	1	0	18.80	18.88	18.90	0-5	5
	1	12	18.91	18.90	18.96		5
	1	24	18.92	18.88	19.04		5
	12	0	18.78	18.69	18.81		5
	12	6	18.79	18.78	18.94		5
	12	13	18.73	18.77	18.85		5
	25	0	18.79	18.70	18.86		5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 16 of 207

Table H-31

LTE Band 26 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.86	23.70	23.92	0	0
	1	7	24.02	23.80	23.89		0
	1	14	23.88	23.71	23.79		0
	8	0	22.79	22.65	22.87	0-1	1
	8	4	22.80	22.74	22.88		1
	8	7	22.76	22.73	22.91		1
	15	0	22.83	22.74	22.80		1
16QAM	1	0	23.07	22.83	23.15	0-1	1
	1	7	23.16	22.98	23.07		1
	1	14	23.11	22.90	23.05		1
	8	0	21.90	21.72	21.93	0-2	2
	8	4	21.91	21.79	21.97		2
	8	7	21.92	21.75	21.98		2
	15	0	21.83	21.75	21.85		2
64QAM	1	0	21.97	21.94	22.11	0-2	2
	1	7	22.08	22.09	22.14		2
	1	14	21.92	22.04	22.03		2
	8	0	20.86	20.68	20.85	0-3	3
	8	4	20.87	20.77	20.95		3
	8	7	20.85	20.76	20.87		3
	15	0	20.80	20.75	20.82		3
256QAM	1	0	18.84	18.66	18.90	0-5	5
	1	7	18.87	18.85	19.06		5
	1	14	18.84	18.75	18.93		5
	8	0	18.86	18.69	18.84		5
	8	4	18.83	18.72	18.93		5
	8	7	18.88	18.74	18.86		5
	15	0	18.82	18.73	18.83		5

Table H-32

LTE Band 26 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) – 1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.85	23.64	23.93	0	0
	1	2	23.82	23.92	23.97		0
	1	5	23.82	23.89	23.86		0
	3	0	23.78	23.67	23.78		0
	3	2	23.81	23.75	23.80		0
	3	3	23.81	23.77	23.86		0
	6	0	22.31	22.32	22.41	0-1	1
16QAM	1	0	23.03	23.03	23.11	0-1	1
	1	2	23.02	23.12	23.15		1
	1	5	22.91	23.19	23.15		1
	3	0	23.02	22.88	23.05		1
	3	2	23.07	22.94	23.07		1
	3	3	23.00	22.89	23.05		1
	6	0	21.87	21.85	21.96	0-2	2
64QAM	1	0	22.05	21.90	22.09	0-2	2
	1	2	22.09	22.11	22.19		2
	1	5	22.12	22.10	22.26		2
	3	0	21.96	21.84	22.11		2
	3	2	21.90	21.98	22.07		2
	3	3	21.95	21.94	22.04		2
	6	0	20.85	20.76	20.91	0-3	3
256QAM	1	0	18.97	18.75	18.94	0-5	5
	1	2	18.94	18.90	18.93		5
	1	5	18.90	18.87	18.89		5
	3	0	18.75	18.66	18.99		5
	3	2	18.83	18.79	18.96		5
	3	3	18.81	18.75	18.90		5
	6	0	18.78	18.71	18.84	5	

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 17 of 207

Table H-33
LTE Band 26 Ant E Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.31	20.24	20.17	0	0
	1	25	20.37	20.05	20.26		0
	1	49	20.26	20.19	20.08		0
	25	0	20.17	20.09	20.23	0-1	0
	25	12	20.23	20.21	20.34		0
	25	25	20.21	20.19	20.31		0
	50	0	20.24	20.16	20.30		0
16QAM	1	0	20.54	20.28	20.39	0-1	0
	1	25	20.58	20.34	20.57		0
	1	49	20.49	20.28	20.38		0
	25	0	20.23	20.10	20.29	0-2	0
	25	12	20.32	20.22	20.36		0
	25	25	20.26	20.17	20.31		0
	50	0	20.28	20.19	20.35		0
64QAM	1	0	20.40	20.34	20.57	0-2	0
	1	25	20.42	20.43	20.51		0
	1	49	20.32	20.36	20.51		0
	25	0	20.21	20.13	20.25	0-3	0
	25	12	20.30	20.22	20.35		0
	25	25	20.23	20.25	20.35		0
	50	0	20.27	20.21	20.33		0
256QAM	1	0	18.53	18.54	18.59	0-5	2
	1	25	18.57	18.51	18.66		2
	1	49	18.47	18.50	18.54		2
	25	0	18.44	18.40	18.43		2
	25	12	18.52	18.47	18.57		2
	25	25	18.44	18.43	18.54		2
	50	0	18.50	18.40	18.57		2

Table H-34
LTE Band 26 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.26	20.04	20.26	0	0
	1	12	20.32	20.14	20.33		0
	1	24	20.22	20.05	20.26		0
	12	0	20.16	20.12	20.21	0-1	0
	12	6	20.27	20.23	20.32		0
	12	13	20.18	20.14	20.27		0
	25	0	20.23	20.14	20.28		0
16QAM	1	0	20.41	20.43	20.58	0-1	0
	1	12	20.44	20.38	20.64		0
	1	24	20.35	20.35	20.57		0
	12	0	20.27	20.14	20.29	0-2	0
	12	6	20.31	20.23	20.40		0
	12	13	20.22	20.19	20.36		0
	25	0	20.27	20.17	20.32		0
64QAM	1	0	20.40	20.39	20.46	0-2	0
	1	12	20.48	20.37	20.57		0
	1	24	20.35	20.39	20.39		0
	12	0	20.21	20.16	20.23	0-3	0
	12	6	20.27	20.20	20.39		0
	12	13	20.25	20.17	20.28		0
	25	0	20.28	20.19	20.35		0
256QAM	1	0	18.56	18.52	18.57	0-5	2
	1	12	18.62	18.62	18.68		2
	1	24	18.54	18.54	18.62		2
	12	0	18.41	18.33	18.46		2
	12	6	18.49	18.44	18.55		2
	12	13	18.45	18.37	18.53		2
	25	0	18.51	18.40	18.56		2

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 18 of 207

Table H-35
LTE Band 26 Ant E Measured P_{Limit} for DSI = 1 (Head) - 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.24	20.10	20.18	0	0
	1	7	20.39	20.14	20.33		0
	1	14	20.28	20.07	20.23		0
	8	0	20.26	20.04	20.22	0-1	0
	8	4	20.27	20.14	20.29		0
	8	7	20.25	20.11	20.29		0
	15	0	20.23	20.15	20.21		0
16QAM	1	0	20.54	20.29	20.37	0-1	0
	1	7	20.69	20.37	20.55		0
	1	14	20.44	20.26	20.47		0
	8	0	20.35	20.17	20.30	0-2	0
	8	4	20.39	20.28	20.36		0
	8	7	20.30	20.26	20.39		0
	15	0	20.30	20.20	20.25		0
64QAM	1	0	20.40	20.28	20.43	0-2	0
	1	7	20.38	20.50	20.53		0
	1	14	20.32	20.26	20.37		0
	8	0	20.34	20.13	20.31	0-3	0
	8	4	20.31	20.24	20.38		0
	8	7	20.24	20.12	20.31		0
	15	0	20.25	20.18	20.28		0
256QAM	1	0	18.42	18.36	18.58	0-5	2
	1	7	18.63	18.47	18.68		2
	1	14	18.53	18.45	18.62		2
	8	0	18.54	18.34	18.50		2
	8	4	18.49	18.40	18.57		2
	8	7	18.44	18.41	18.56		2
	15	0	18.49	18.37	18.45		2

Table H-36
LTE Band 26 Ant E Measured P_{Limit} for DSI = 1 (Head) – 1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.31	19.99	20.22	0	0
	1	2	20.33	20.07	20.28		0
	1	5	20.26	20.02	20.21		0
	3	0	20.30	19.99	20.21		0
	3	2	20.29	20.06	20.26		0
	3	3	20.24	20.07	20.26		0
	6	0	20.25	20.07	20.20	0-1	0
16QAM	1	0	20.66	20.30	20.61	0-1	0
	1	2	20.66	20.35	20.53		0
	1	5	20.48	20.30	20.50		0
	3	0	20.39	20.26	20.42		0
	3	2	20.36	20.20	20.43		0
	3	3	20.36	20.26	20.41		0
	6	0	20.34	20.26	20.32	0-2	0
64QAM	1	0	20.45	20.26	20.44	0-2	0
	1	2	20.51	20.42	20.60		0
	1	5	20.42	20.45	20.51		0
	3	0	20.41	20.23	20.42		0
	3	2	20.44	20.33	20.47		0
	3	3	20.39	20.28	20.41		0
	6	0	20.30	20.17	20.38	0-3	0
256QAM	1	0	18.56	18.28	18.54	0-5	2
	1	2	18.69	18.47	18.56		2
	1	5	18.57	18.43	18.68		2
	3	0	18.54	18.38	18.50		2
	3	2	18.57	18.49	18.51		2
	3	3	18.55	18.44	18.58		2
	6	0	18.50	18.33	18.51	2	

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 19 of 207

H.1.6 LTE Band 66

Table H-37
LTE Band 66 (AWS) Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.89	18.58	18.61	0	0
	1	36	18.98	18.55	18.39		0
	1	74	18.79	18.41	18.37		0
	36	0	18.85	18.47	18.46	0-1	0
	36	18	18.75	18.45	18.45		0
	36	37	18.70	18.44	18.49		0
	75	0	18.73	18.46	18.43		0
16QAM	1	0	19.09	18.65	18.62	0-1	0
	1	36	18.96	18.53	18.50		0
	1	74	18.86	18.54	18.56		0
	36	0	18.86	18.51	18.48	0-2	0
	36	18	18.79	18.48	18.48		0
	36	37	18.73	18.48	18.54		0
	75	0	18.78	18.48	18.47		0
64QAM	1	0	19.10	18.77	18.65	0-2	0
	1	36	18.98	18.74	18.78		0
	1	74	18.83	18.63	18.49		0
	36	0	18.85	18.51	18.47	0-3	0
	36	18	18.76	18.45	18.49		0
	36	37	18.73	18.42	18.51		0
	75	0	18.73	18.46	18.47		0
256QAM	1	0	19.16	18.69	18.57	0-5	0
	1	36	19.03	18.49	18.65		0
	1	74	18.86	18.55	18.63		0
	36	0	18.83	18.49	18.48		0
	36	18	18.75	18.48	18.49		0
	36	37	18.74	18.46	18.52		0
	75	0	18.76	18.48	18.49		0

Table H-38
LTE Band 66 (AWS) Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.88	18.66	18.43	0	0
	1	25	19.12	18.53	18.46		0
	1	49	18.87	18.34	18.33		0
	25	0	18.91	18.47	18.49	0-1	0
	25	12	18.90	18.50	18.59		0
	25	25	18.75	18.43	18.57		0
	50	0	18.83	18.46	18.57		0
16QAM	1	0	19.19	18.69	18.69	0-1	0
	1	25	19.10	18.73	18.71		0
	1	49	19.02	18.63	18.55		0
	25	0	18.90	18.50	18.51	0-2	0
	25	12	18.90	18.55	18.60		0
	25	25	18.75	18.47	18.60		0
	50	0	18.85	18.50	18.57		0
64QAM	1	0	19.05	18.69	18.72	0-2	0
	1	25	19.08	18.82	18.81		0
	1	49	18.89	18.64	18.64		0
	25	0	18.88	18.47	18.47	0-3	0
	25	12	18.91	18.49	18.54		0
	25	25	18.79	18.45	18.59		0
	50	0	18.90	18.47	18.56		0
256QAM	1	0	19.00	18.57	18.62	0-5	0
	1	25	19.09	18.53	18.68		0
	1	49	18.83	18.65	18.66		0
	25	0	18.88	18.55	18.51		0
	25	12	18.93	18.53	18.59		0
	25	25	18.80	18.47	18.58		0
	50	0	18.84	18.48	18.59		0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 20 of 207

Table H-39
LTE Band 66 (AWS) Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.99	18.40	18.60	0	0
	1	12	19.02	18.45	18.66		0
	1	24	18.97	18.36	18.59		0
	12	0	18.94	18.49	18.50	0-1	0
	12	6	18.94	18.53	18.60		0
	12	13	18.77	18.46	18.55		0
	25	0	18.82	18.47	18.57		0
16QAM	1	0	19.20	18.76	19.00	0-1	0
	1	12	19.25	18.75	18.96		0
	1	24	19.11	18.70	18.91		0
	12	0	18.94	18.51	18.54	0-2	0
	12	6	18.97	18.54	18.64		0
	12	13	18.85	18.48	18.57		0
	25	0	18.83	18.50	18.58		0
64QAM	1	0	19.11	18.64	18.75	0-2	0
	1	12	19.14	18.67	18.83		0
	1	24	18.98	18.66	18.69		0
	12	0	18.94	18.46	18.52	0-3	0
	12	6	18.99	18.55	18.66		0
	12	13	18.78	18.48	18.59		0
	25	0	18.82	18.47	18.59		0
256QAM	1	0	18.90	18.63	18.60	0-5	0
	1	12	18.99	18.56	18.75		0
	1	24	18.83	18.49	18.65		0
	12	0	18.90	18.50	18.53		0
	12	6	18.98	18.54	18.62		0
	12	13	18.82	18.47	18.61		0
	25	0	18.80	18.46	18.59		0

Table H-40
LTE Band 66 (AWS) Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.96	18.42	18.47	0	0
	1	7	19.10	18.57	18.60		0
	1	14	18.88	18.37	18.43		0
	8	0	18.90	18.48	18.49	0-1	0
	8	4	18.89	18.50	18.61		0
	8	7	18.88	18.42	18.56		0
	15	0	18.88	18.45	18.59		0
16QAM	1	0	19.33	18.60	18.65	0-1	0
	1	7	19.30	18.68	18.73		0
	1	14	19.15	18.56	18.54		0
	8	0	19.01	18.56	18.56	0-2	0
	8	4	19.02	18.60	18.62		0
	8	7	18.96	18.57	18.62		0
	15	0	18.93	18.49	18.57		0
64QAM	1	0	19.02	18.62	18.65	0-2	0
	1	7	19.15	18.75	18.90		0
	1	14	19.00	18.52	18.69		0
	8	0	18.95	18.51	18.60	0-3	0
	8	4	18.94	18.55	18.63		0
	8	7	18.94	18.49	18.60		0
	15	0	18.88	18.47	18.64		0
256QAM	1	0	18.93	18.52	18.44	0-5	0
	1	7	19.06	18.68	18.76		0
	1	14	18.92	18.54	18.57		0
	8	0	18.95	18.49	18.54		0
	8	4	18.98	18.53	18.63		0
	8	7	18.95	18.51	18.57		0
	15	0	18.94	18.49	18.63		0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 21 of 207

Table H-41
LTE Band 66 (AWS) Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	18.97	18.41	18.60	0	0	
	1	2	18.79	18.35	18.50		0	
	1	5	18.86	18.39	18.56		0	
	3	0	18.88	18.38	18.50		0	
	3	2	18.82	18.33	18.46		0	
	3	3	18.84	18.37	18.49		0	
	6	0	18.79	18.37	18.49		0-1	0
16QAM	1	0	19.26	18.64	18.66	0	0	
	1	2	19.31	18.65	18.64		0-1	0
	1	5	19.18	18.67	18.60			0
	3	0	19.04	18.60	18.73			0
	3	2	18.96	18.50	18.69			0
	3	3	19.09	18.51	18.73			0
	6	0	18.97	18.47	18.65		0-2	0
64QAM	1	0	19.04	18.65	18.79	0	0	
	1	2	19.19	18.68	18.72		0	
	1	5	19.17	18.74	18.69		0-2	0
	3	0	19.07	18.58	18.74			0
	3	2	18.99	18.56	18.72			0
	3	3	19.04	18.60	18.66			0
	6	0	18.91	18.50	18.64			0-3
256QAM	1	0	19.12	18.62	18.69	0	0	
	1	2	19.04	18.50	18.62		0	
	1	5	19.11	18.55	18.72		0	
	3	0	18.97	18.56	18.58		0-5	0
	3	2	18.94	18.47	18.68			0
	3	3	19.11	18.53	18.63			0
	6	0	18.88	18.52	18.53			0

Table H-42
LTE Band 66 (AWS) Ant A Measured P_{Max} for DSI = 1 (Head) – 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.98	23.89	23.79	0	0
	1	36	24.05	23.85	23.51		0
	1	74	23.84	23.50	23.52		0
	36	0	22.93	22.60	22.56	0-1	1
	36	18	22.86	22.56	22.57		1
	36	37	22.83	22.57	22.64		1
	75	0	22.80	22.56	22.56		1
16QAM	1	0	23.27	22.77	22.79	0-1	1
	1	36	23.13	22.69	22.82		1
	1	74	22.97	22.66	22.74		1
	36	0	21.98	21.65	21.60	0-2	2
	36	18	21.90	21.60	21.62		2
	36	37	21.83	21.59	21.65		2
	75	0	21.87	21.60	21.59		2
64QAM	1	0	22.21	21.97	21.81	0-2	2
	1	36	22.13	21.79	21.86		2
	1	74	22.00	21.86	21.82		2
	36	0	20.97	20.61	20.62	0-3	3
	36	18	20.90	20.60	20.58		3
	36	37	20.82	20.58	20.64		3
	75	0	20.82	20.59	20.58		3
256QAM	1	0	19.12	18.92	18.79	0-5	5
	1	36	19.09	18.74	18.74		5
	1	74	18.87	18.64	18.71		5
	36	0	19.00	18.62	18.65		5
	36	18	18.88	18.62	18.60		5
	36	37	18.83	18.54	18.62		5
	75	0	18.85	18.60	18.58		5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 22 of 207

Table H-43
LTE Band 66 (AWS) Ant A Measured P_{Max} for DSI = 1 (Head) – 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.00	23.57	23.51	0	0
	1	25	23.91	23.61	23.70		0
	1	49	23.81	23.51	23.50		0
	25	0	22.97	22.62	22.61	0-1	1
	25	12	23.00	22.64	22.70		1
	25	25	22.86	22.60	22.68		1
16QAM	50	0	22.99	22.58	22.70	0-1	1
	1	0	23.32	22.75	22.87		1
	1	25	23.25	22.82	22.85		1
	1	49	23.09	22.72	22.82	0-2	1
	25	0	22.00	21.64	21.64		2
	25	12	22.06	21.62	21.73		2
64QAM	25	25	21.87	21.59	21.74	0-2	2
	50	0	21.97	21.65	21.70		2
	1	0	22.21	21.85	21.85		2
	1	25	22.21	21.87	22.00	0-2	2
	1	49	22.10	21.91	21.72		2
	25	0	20.99	20.65	20.65		0-3
256QAM	25	12	21.01	20.66	20.74	3	
	25	25	20.89	20.60	20.68	3	
	50	0	20.97	20.61	20.67	0-5	3
	1	0	19.17	18.62	18.79		5
	1	25	19.13	18.72	18.99		5
	1	49	18.95	18.61	18.79		5
	25	0	18.98	18.64	18.64	0-5	5
	25	12	19.02	18.65	18.73		5
	25	25	18.89	18.60	18.64		5
	50	0	18.99	18.63	18.69		5

Table H-44
LTE Band 66 (AWS) Ant A Measured P_{Max} for DSI = 1 (Head) – 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.94	23.53	23.71	0	0
	1	12	24.19	23.57	23.82		0
	1	24	23.98	23.45	23.72		0
	12	0	22.99	22.60	22.61	0-1	1
	12	6	23.07	22.63	22.73		1
	12	13	22.91	22.56	22.70		1
	25	0	22.90	22.59	22.69		1
16QAM	1	0	23.19	22.98	22.97	0-1	1
	1	12	23.18	22.90	23.15		1
	1	24	23.10	22.81	22.99		1
	12	0	22.01	21.63	21.65	0-2	2
	12	6	22.02	21.73	21.77		2
	12	13	21.90	21.65	21.72		2
	25	0	21.91	21.61	21.69		2
64QAM	1	0	22.28	21.70	21.89	0-2	2
	1	12	22.33	21.82	21.89		2
	1	24	22.09	21.80	21.87		2
	12	0	21.04	20.60	20.61	0-3	3
	12	6	21.12	20.68	20.76		3
	12	13	21.05	20.66	20.70		3
	25	0	20.93	20.63	20.72		3
256QAM	1	0	19.11	18.80	18.65	0-5	5
	1	12	19.22	18.87	18.92		5
	1	24	18.97	18.75	18.84		5
	12	0	19.03	18.63	18.64		5
	12	6	19.04	18.62	18.72	5	
	12	13	18.94	18.56	18.70	5	
	25	0	18.91	18.59	18.68	5	

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 23 of 207

Table H-45
LTE Band 66 (AWS) Ant A Measured P_{Max} for DSI = 1 (Head) – 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.95	23.61	23.61	0	0
	1	7	24.08	23.63	23.63		0
	1	14	23.93	23.60	23.62		0
	8	0	23.00	22.59	22.64	0-1	1
	8	4	23.01	22.61	22.71		1
	8	7	22.99	22.54	22.68		1
	15	0	22.99	22.56	22.71		1
16QAM	1	0	23.15	22.68	22.82	0-1	1
	1	7	23.16	22.83	22.89		1
	1	14	23.10	22.68	22.91		1
	8	0	22.09	21.68	21.69	0-2	2
	8	4	22.12	21.69	21.80		2
	8	7	22.09	21.70	21.72		2
	15	0	22.04	21.62	21.74		2
64QAM	1	0	22.09	21.82	21.84	0-2	2
	1	7	22.29	21.87	22.09		2
	1	14	21.98	21.78	21.79		2
	8	0	21.11	20.67	20.67	0-3	3
	8	4	21.08	20.70	20.75		3
	8	7	21.08	20.58	20.72		3
	15	0	21.06	20.59	20.70		3
256QAM	1	0	19.09	18.70	18.74	0-5	5
	1	7	19.21	18.83	18.87		5
	1	14	19.13	18.61	18.60		5
	8	0	19.07	18.63	18.68		5
	8	4	19.09	18.64	18.74		5
	8	7	19.06	18.63	18.67		5
	15	0	19.01	18.62	18.70		5

Table H-46
LTE Band 66 (AWS) Ant A Measured P_{Max} for DSI = 1 (Head) – 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.90	23.64	23.74	0	0
	1	2	23.97	23.61	23.68		0
	1	5	23.91	23.53	23.67		0
	3	0	23.94	23.48	23.64		0
	3	2	23.88	23.51	23.56		0
	3	3	23.94	23.53	23.64		0
	6	0	22.94	22.53	22.58	0-1	1
16QAM	1	0	23.38	22.66	23.11	0-1	1
	1	2	23.15	22.69	23.05		1
	1	5	23.08	22.58	22.98		1
	3	0	23.10	22.74	22.81		1
	3	2	23.01	22.71	22.78		1
	3	3	23.05	22.71	22.80		1
	6	0	22.05	21.62	21.73	0-2	2
64QAM	1	0	22.18	21.77	21.88	0-2	2
	1	2	22.37	21.78	21.83		2
	1	5	22.11	21.87	22.05		2
	3	0	22.22	21.71	21.86		2
	3	2	22.17	21.63	21.96		2
	3	3	22.22	21.77	21.83		2
	6	0	21.03	20.53	20.75	0-3	3
256QAM	1	0	19.20	18.69	18.89	0-5	5
	1	2	19.21	18.64	18.78		5
	1	5	19.06	18.80	18.91		5
	3	0	18.99	18.68	18.81		5
	3	2	19.05	18.63	18.82		5
	3	3	19.05	18.63	18.85		5
	6	0	18.95	18.54	18.68	5	

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 24 of 207

Table H-47
LTE Band 66 (AWS) Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.38	19.97	20.05	0	0
	1	36	20.39	19.99	19.80		0
	1	74	20.24	19.91	19.75		0
	36	0	20.34	19.94	19.88	0-1	0
	36	18	20.25	19.94	19.90		0
	36	37	20.17	19.93	19.90		0
	75	0	20.19	19.92	19.83		0
16QAM	1	0	20.65	20.13	20.13	0-1	0
	1	36	20.49	20.13	20.10		0
	1	74	20.38	20.06	20.04		0
	36	0	20.39	20.01	19.95	0-2	0
	36	18	20.28	20.00	19.93		0
	36	37	20.23	19.99	19.99		0
	75	0	20.23	20.00	19.93		0
64QAM	1	0	20.64	20.12	20.18	0-2	0
	1	36	20.45	20.15	20.21		0
	1	74	20.40	20.15	20.01		0
	36	0	20.29	19.99	19.90	0-3	0
	36	18	20.26	19.98	19.93		0
	36	37	20.17	19.96	19.97		0
	75	0	20.39	19.96	19.88		0
256QAM	1	0	19.23	18.88	18.87	0-5	1.5
	1	36	19.20	18.95	18.77		1.5
	1	74	19.06	18.88	18.70		1.5
	36	0	19.09	18.70	18.66		1.5
	36	18	19.00	18.73	18.66		1.5
	36	37	18.95	18.65	18.67		1.5
	75	0	18.95	18.67	18.61		1.5

Table H-48
LTE Band 66 (AWS) Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.34	19.98	19.91	0	0
	1	25	20.67	20.01	19.83		0
	1	49	20.36	19.85	19.77		0
	25	0	20.33	19.97	19.92	0-1	0
	25	12	20.37	19.98	19.92		0
	25	25	20.25	19.94	19.99		0
	50	0	20.34	19.98	19.89		0
16QAM	1	0	20.67	20.05	20.11	0-1	0
	1	25	20.61	20.18	20.23		0
	1	49	20.56	20.02	19.95		0
	25	0	20.39	20.03	19.93	0-2	0
	25	12	20.41	20.03	19.92		0
	25	25	20.31	20.01	20.01		0
	50	0	20.37	20.00	19.94		0
64QAM	1	0	20.65	20.25	20.17	0-2	0
	1	25	20.50	20.21	20.13		0
	1	49	20.59	20.12	20.02		0
	25	0	20.40	20.02	19.95	0-3	0
	25	12	20.44	20.03	19.97		0
	25	25	20.27	19.99	20.02		0
	50	0	20.33	19.98	19.91		0
256QAM	1	0	19.18	18.69	18.74	0-5	1.5
	1	25	19.24	18.87	18.85		1.5
	1	49	19.19	18.74	18.66		1.5
	25	0	19.09	18.74	18.66		1.5
	25	12	19.13	18.75	18.68		1.5
	25	25	18.99	18.70	18.69		1.5
	50	0	19.11	18.71	18.64		1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 25 of 207

Table H-49
LTE Band 66 (AWS) Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	20.43	19.86	19.98	0	0	
	1	12	20.41	19.97	20.13		0	
	1	24	20.30	19.88	20.02		0	
	12	0	20.40	19.92	19.89	0-1	0	
	12	6	20.42	19.98	19.96		0	
	12	13	20.24	19.94	19.96		0	
16QAM	25	0	20.28	19.93	19.88	0-1	0	
	1	0	20.61	20.17	20.25		0-2	0
	1	12	20.67	20.29	20.53			0
	1	24	20.67	20.18	20.36	0		
	12	0	20.49	20.01	19.95	0		
	12	6	20.53	20.03	20.03	0		
64QAM	12	13	20.33	19.96	19.99	0-2	0	
	25	0	20.33	19.99	19.93		0-3	0
	1	0	20.66	20.20	20.27			0
	1	12	20.68	20.26	20.45	0-2		0
	1	24	20.58	20.18	20.19		0	
	12	0	20.47	19.97	19.92		0	
256QAM	12	6	20.46	20.02	19.97	0-3	0	
	12	13	20.33	19.99	20.05		0	
	25	0	20.33	19.94	19.87		0	
	256QAM	1	0	19.27	19.01	18.88	0-5	1.5
		1	12	19.21	19.01	19.04		1.5
		1	24	19.06	19.02	18.84		1.5
12		0	19.17	18.64	18.62	1.5		
12		6	19.20	18.69	18.70	1.5		
12		13	19.02	18.71	18.69	1.5		
25	0	19.04	18.68	18.64	1.5			

Table H-50
LTE Band 66 (AWS) Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.34	19.85	19.94	0	0
	1	7	20.70	20.03	20.02		0
	1	14	20.29	19.96	19.88		0
	8	0	20.43	19.95	19.96	0-1	0
	8	4	20.38	20.00	19.90		0
	8	7	20.31	20.00	20.00		0
16QAM	15	0	20.35	19.98	19.92	0-1	0
	1	0	20.60	20.03	20.19		0
	1	7	20.56	20.31	20.13		0
	1	14	20.59	20.10	20.12	0-2	0
	8	0	20.55	20.07	20.05		0
	8	4	20.51	20.09	20.00		0
64QAM	8	7	20.42	20.07	20.05	0-2	0
	15	0	20.40	19.99	19.94		0
	1	0	20.63	20.02	20.25	0-2	0
	1	7	20.53	20.36	20.27		0
	1	14	20.50	20.26	20.16		0-3
	8	0	20.56	20.04	20.00	0	
256QAM	8	4	20.46	20.08	20.00	0-3	
	8	7	20.33	20.03	20.04		0
	15	0	20.39	20.01	19.96		0
	1	0	19.17	18.75	18.74	0-5	1.5
	1	7	19.53	19.02	18.80		1.5
	1	14	18.98	18.75	18.82		1.5
	8	0	19.22	18.67	18.72		1.5
	8	4	19.18	18.79	18.68		1.5
8	7	19.06	18.73	18.69	1.5		
15	0	19.08	18.71	18.66	1.5		

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 26 of 207

Table H-51
LTE Band 66 (AWS) Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.42	19.86	19.87	0	0
	1	2	20.48	19.92	19.83		0
	1	5	20.45	19.86	19.93		0
	3	0	20.34	19.95	19.82		0
	3	2	20.39	19.81	19.83		0
	3	3	20.38	19.86	19.89		0
	6	0	20.35	19.95	19.85		0
16QAM	1	0	20.58	20.14	20.05	0-1	0
	1	2	20.69	20.30	20.10	0-1	0
	1	5	20.57	20.16	20.08		0
	3	0	20.52	20.09	20.08		0
	3	2	20.53	20.11	20.13		0
	3	3	20.53	20.08	20.22		0
	6	0	20.51	20.08	20.03	0-2	0
64QAM	1	0	20.57	20.22	20.12	0-2	0
	1	2	20.64	20.33	20.14		0
	1	5	20.53	20.24	20.29		0
	3	0	20.64	20.08	20.02		0
	3	2	20.57	20.20	20.02		0
	3	3	20.55	20.19	20.12		0
	6	0	20.49	19.99	20.04		0-3
256QAM	1	0	19.45	18.78	18.75	0-5	1.5
	1	2	19.28	18.81	18.78		1.5
	1	5	19.34	18.96	18.94		1.5
	3	0	19.25	18.72	18.69		1.5
	3	2	19.14	18.82	18.58		1.5
	3	3	19.26	18.81	18.76		1.5
	6	0	19.12	18.67	18.63		1.5

Table H-52
LTE Band 66 (AWS) Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	15.95	15.66	16.22	0	0
	1	36	16.06	15.74	15.77		0
	1	74	16.09	15.64	15.75		0
	36	0	15.98	15.64	15.57	0-1	0
	36	18	15.94	15.71	15.71		0
	36	37	15.90	15.74	15.74		0
	75	0	15.97	15.73	15.82		0
16QAM	1	0	16.24	15.84	15.98	0-1	0
	1	36	16.18	15.80	15.86		0
	1	74	16.11	15.99	15.96		0
	36	0	16.03	15.79	15.70	0-2	0
	36	18	16.02	15.77	15.79		0
	36	37	15.96	15.74	15.77		0
	75	0	16.02	15.75	15.79		0
64QAM	1	0	16.25	15.80	15.91	0-2	0
	1	36	16.14	15.81	16.00		0
	1	74	15.85	15.85	15.87		0
	36	0	15.97	15.73	15.67	0-3	0
	36	18	16.08	15.74	15.79		0
	36	37	15.92	15.80	15.79		0
	75	0	16.02	15.77	15.78		0
256QAM	1	0	16.24	15.87	15.82	0-5	0
	1	36	16.22	15.88	15.97		0
	1	74	15.96	15.76	15.84		0
	36	0	16.04	15.77	15.69		0
	36	18	16.08	15.72	15.82		0
	36	37	15.97	15.74	15.79		0
	75	0	16.09	15.76	15.79		0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 27 of 207

Table H-53
LTE Band 66 (AWS) Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	16.03	15.59	15.74	0	0
	1	25	16.08	15.65	15.99		0
	1	49	15.99	15.62	15.65		0
	25	0	16.10	15.71	15.74	0-1	0
	25	12	16.04	15.74	15.75		0
	25	25	15.90	15.77	15.73		0
16QAM	50	0	16.09	15.76	15.74	0-1	0
	1	0	16.25	15.72	15.96		0
	1	25	16.26	15.86	15.98		0
	1	49	16.17	15.75	16.01	0-2	0
	25	0	16.06	15.82	15.74		0
	25	12	16.14	15.77	15.88		0
64QAM	25	25	16.04	15.81	15.75	0-2	0
	50	0	16.07	15.81	15.86		0
	1	0	16.27	15.70	15.91		0-2
	1	25	16.20	15.81	15.84	0	
	1	49	16.02	15.82	15.94	0-3	
	25	0	16.08	15.84	15.72		0
256QAM	25	12	16.07	15.76	15.86		0-3
	25	25	16.07	15.74	15.81	0	
	50	0	16.09	15.73	15.79	0-5	
	1	0	16.22	15.69	15.73		0
	1	25	16.28	15.78	15.97		0-5
	1	49	16.10	15.82	15.80	0	
256QAM	25	0	16.12	15.84	15.69	0-5	
	25	12	16.19	15.86	15.86		0
	25	25	16.03	15.89	15.87		0
	50	0	16.11	15.77	15.83	0	

Table H-54
LTE Band 66 (AWS) Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	16.08	15.54	15.64	0	0
	1	12	16.09	15.65	15.87		0
	1	24	16.08	15.54	15.79		0
	12	0	16.04	15.77	15.73	0-1	0
	12	6	16.04	15.83	15.71		0
	12	13	15.96	15.74	15.74		0
	25	0	16.08	15.77	15.71		0
16QAM	1	0	16.36	15.67	15.75	0-1	0
	1	12	16.29	15.86	16.30		0
	1	24	16.33	15.81	16.04		0
	12	0	16.09	15.85	15.72	0-2	0
	12	6	16.19	15.86	15.71		0
	12	13	15.99	15.82	15.85		0
	25	0	16.14	15.72	15.75		0
64QAM	1	0	16.21	15.79	15.76	0-2	0
	1	12	16.24	15.88	16.03		0
	1	24	16.26	15.88	15.96		0
	12	0	16.13	15.77	15.74	0-3	0
	12	6	16.14	15.79	15.78		0
	12	13	15.98	15.79	15.84		0
	25	0	16.13	15.77	15.70		0
256QAM	1	0	16.23	15.69	15.86	0-5	0
	1	12	16.38	15.81	16.02		0
	1	24	16.16	15.68	15.98		0
	12	0	16.10	15.82	15.81		0
	12	6	16.04	15.82	15.78		0
	12	13	16.06	15.84	15.81		0
	25	0	16.09	15.77	15.78		0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 28 of 207

Table H-55
LTE Band 66 (AWS) Ant F Measured P_{Limit} for DSI = 1 (Head) - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	15.91	15.66	15.63	0	0
	1	7	16.02	15.71	15.66		0
	1	14	16.01	15.76	15.72		0
	8	0	16.13	15.71	15.55	0-1	0
	8	4	16.01	15.70	15.80		0
	8	7	15.95	15.75	15.77		0
	15	0	16.07	15.74	15.77		0
16QAM	1	0	16.31	15.86	15.94	0-1	0
	1	7	16.16	15.90	16.00		0
	1	14	16.33	15.88	15.91		0
	8	0	16.10	15.81	15.70	0-2	0
	8	4	16.12	15.70	15.79		0
	8	7	16.01	15.81	15.87		0
	15	0	16.00	15.74	15.74		0
64QAM	1	0	16.20	15.90	15.83	0-2	0
	1	7	16.26	15.85	15.87		0
	1	14	16.24	15.89	16.01		0
	8	0	16.22	15.97	15.71	0-3	0
	8	4	16.10	15.85	15.86		0
	8	7	16.09	15.79	15.81		0
	15	0	16.02	15.79	15.77		0
256QAM	1	0	16.15	15.88	15.80	0-5	0
	1	7	16.21	15.80	16.04		0
	1	14	16.08	15.73	15.87		0
	8	0	16.14	15.79	15.72		0
	8	4	16.15	15.84	15.80		0
	8	7	16.15	15.81	15.81		0
	15	0	16.09	15.81	15.71		0

Table H-56
LTE Band 66 (AWS) Ant F Measured P_{Limit} for DSI = 1 (Head) – 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	15.86	15.60	15.57	0	0
	1	2	15.99	15.71	15.79		0
	1	5	16.08	15.65	15.84		0
	3	0	16.03	15.54	15.65		0
	3	2	15.91	15.80	15.63		0
	3	3	16.00	15.51	15.65		0
	6	0	16.10	15.53	15.72	0-1	0
16QAM	1	0	16.14	15.83	16.16	0-1	0
	1	2	16.35	15.77	16.01		0
	1	5	16.27	15.95	15.98		0
	3	0	16.21	15.82	15.70		0
	3	2	16.01	15.67	15.80		0
	3	3	16.19	16.05	15.90		0
	6	0	16.31	15.81	15.87	0-2	0
64QAM	1	0	16.31	16.15	15.79	0-2	0
	1	2	16.32	15.82	15.93		0
	1	5	16.29	15.98	16.04		0
	3	0	16.28	15.72	15.83		0
	3	2	16.27	15.66	15.87		0
	3	3	16.17	15.59	16.04		0
	6	0	16.18	15.75	15.82	0-3	0
256QAM	1	0	16.37	15.75	15.79	0-5	0
	1	2	16.36	15.69	15.99		0
	1	5	16.16	15.76	16.10		0
	3	0	16.38	15.77	16.03		0
	3	2	16.20	15.71	15.99		0
	3	3	16.17	15.76	16.00		0
	6	0	16.20	15.82	15.85		0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 29 of 207

H.1.7 LTE Band 25

Table H-57
LTE Band 25 (PCS) Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.35	18.31	17.81	0	0
	1	36	18.40	18.38	17.73		0
	1	74	18.26	18.22	17.64		0
	36	0	18.34	18.28	17.91	0-1	0
	36	18	18.34	18.30	17.89		0
	36	37	18.29	18.22	17.75		0
	75	0	18.32	18.27	17.85		0
16QAM	1	0	18.59	18.45	18.08	0-1	0
	1	36	18.38	18.55	18.00		0
	1	74	18.37	18.42	17.89		0
	36	0	18.41	18.34	17.92	0-2	0
	36	18	18.37	18.33	17.91		0
	36	37	18.34	18.27	17.79		0
	75	0	18.33	18.31	17.91		0
64QAM	1	0	18.44	18.57	18.09	0-2	0
	1	36	18.50	18.67	18.11		0
	1	74	18.35	18.47	17.99		0
	36	0	18.38	18.31	17.91	0-3	0
	36	18	18.36	18.34	17.93		0
	36	37	18.32	18.28	17.75		0
	75	0	18.32	18.30	17.91		0
256QAM	1	0	18.39	18.38	18.04	0-5	0
	1	36	18.52	18.54	18.06		0
	1	74	18.42	18.39	17.82		0
	36	0	18.42	18.35	17.93		0
	36	18	18.39	18.36	17.97		0
	36	37	18.35	18.31	17.82		0
	75	0	18.36	18.32	17.93		0

Table H-58
LTE Band 25 (PCS) Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.42	18.25	17.85	0	0
	1	25	18.50	18.42	17.73		0
	1	49	18.35	18.19	17.63		0
	25	0	18.39	18.30	17.88	0-1	0
	25	12	18.39	18.33	17.90		0
	25	25	18.34	18.27	17.76		0
	50	0	18.33	18.32	17.88		0
16QAM	1	0	18.71	18.55	18.08	0-1	0
	1	25	18.69	18.61	18.06		0
	1	49	18.57	18.41	17.91		0
	25	0	18.40	18.31	17.93	0-2	0
	25	12	18.44	18.39	17.95		0
	25	25	18.41	18.32	17.81		0
	50	0	18.38	18.33	17.92		0
64QAM	1	0	18.60	18.70	18.06	0-2	0
	1	25	18.65	18.72	18.09		0
	1	49	18.48	18.45	18.03		0
	25	0	18.43	18.31	17.92	0-3	0
	25	12	18.44	18.35	17.91		0
	25	25	18.37	18.30	17.83		0
	50	0	18.35	18.31	17.89		0
256QAM	1	0	18.56	18.41	18.03	0-5	0
	1	25	18.45	18.60	18.06		0
	1	49	18.47	18.51	17.88		0
	25	0	18.42	18.36	17.89		0
	25	12	18.45	18.39	17.97		0
	25	25	18.39	18.31	17.81		0
	50	0	18.41	18.34	17.93		0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 30 of 207

Table H-59
LTE Band 25 (PCS) Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.53	18.27	17.94	0	0
	1	12	18.49	18.37	17.94		0
	1	24	18.41	18.22	17.86		0
	12	0	18.37	18.29	17.83	0-1	0
	12	6	18.42	18.36	17.87		0
	12	13	18.37	18.31	17.78		0
	25	0	18.39	18.31	17.81		0
16QAM	1	0	18.67	18.58	18.22	0-1	0
	1	12	18.69	18.68	18.20		0
	1	24	18.67	18.55	18.27		0
	12	0	18.44	18.31	17.88	0-2	0
	12	6	18.47	18.38	17.92		0
	12	13	18.46	18.34	17.78		0
	25	0	18.38	18.32	17.88		0
64QAM	1	0	18.61	18.47	18.07	0-2	0
	1	12	18.76	18.53	18.19		0
	1	24	18.71	18.52	18.06		0
	12	0	18.47	18.33	17.92	0-3	0
	12	6	18.47	18.38	17.93		0
	12	13	18.45	18.34	17.82		0
	25	0	18.45	18.37	17.86		0
256QAM	1	0	18.61	18.54	17.99	0-5	0
	1	12	18.61	18.65	18.14		0
	1	24	18.49	18.48	17.88		0
	12	0	18.36	18.35	17.88		0
	12	6	18.50	18.41	17.93		0
	12	13	18.43	18.39	17.76		0
	25	0	18.42	18.35	17.88		0

Table H-60
LTE Band 25 (PCS) Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.30	18.30	17.65	0	0
	1	7	18.45	18.41	17.75		0
	1	14	18.33	18.32	17.65		0
	8	0	18.37	18.31	17.80	0-1	0
	8	4	18.40	18.35	17.82		0
	8	7	18.41	18.33	17.84		0
	15	0	18.38	18.32	17.80		0
16QAM	1	0	18.63	18.47	17.96	0-1	0
	1	7	18.77	18.67	18.12		0
	1	14	18.70	18.47	17.94		0
	8	0	18.52	18.40	17.87	0-2	0
	8	4	18.56	18.45	17.92		0
	8	7	18.51	18.43	17.90		0
	15	0	18.48	18.38	17.88		0
64QAM	1	0	18.58	18.57	17.92	0-2	0
	1	7	18.71	18.70	18.15		0
	1	14	18.59	18.56	17.96		0
	8	0	18.45	18.37	17.84	0-3	0
	8	4	18.52	18.35	17.88		0
	8	7	18.48	18.35	17.87		0
	15	0	18.43	18.34	17.85		0
256QAM	1	0	18.51	18.42	17.86	0-5	0
	1	7	18.67	18.59	18.06		0
	1	14	18.52	18.46	17.88		0
	8	0	18.49	18.37	17.86		0
	8	4	18.50	18.44	17.94		0
	8	7	18.46	18.41	17.87		0
	15	0	18.42	18.37	17.84		0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 31 of 207

Table H-61
LTE Band 25 (PCS) Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.33	18.32	17.77	0	0
	1	2	18.37	18.23	17.79		0
	1	5	18.44	18.28	17.76		0
	3	0	18.32	18.30	17.74		0
	3	2	18.31	18.25	17.70		0
	3	3	18.32	18.24	17.72		0
	6	0	18.34	18.34	17.69		0-1
16QAM	1	0	18.72	18.57	18.02	0-1	0
	1	2	18.74	18.56	17.96		0
	1	5	18.64	18.41	17.91		0
	3	0	18.55	18.50	17.95		0
	3	2	18.44	18.50	17.90		0
	3	3	18.53	18.46	18.04		0
	6	0	18.51	18.43	17.92		0-2
64QAM	1	0	18.67	18.70	18.05	0-2	0
	1	2	18.67	18.64	18.10		0
	1	5	18.69	18.66	18.01		0
	3	0	18.56	18.50	17.91		0
	3	2	18.53	18.43	17.85		0
	3	3	18.50	18.59	17.92		0
	6	0	18.47	18.45	17.80		0-3
256QAM	1	0	18.76	18.62	18.00	0-5	0
	1	2	18.59	18.58	17.97		0
	1	5	18.57	18.65	17.93		0
	3	0	18.48	18.48	17.90		0
	3	2	18.40	18.44	17.89		0
	3	3	18.46	18.47	17.91		0
	6	0	18.40	18.32	17.80		0

Table H-62
LTE Band 25 (PCS) Ant A Measured P_{Max} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.06	24.28	23.72	0	0
	1	36	24.28	24.12	23.72		0
	1	74	24.10	23.99	23.37		0
	36	0	23.07	23.01	22.62	0-1	1
	36	18	23.08	23.04	22.62		1
	36	37	23.03	22.94	22.67		1
	75	0	23.03	22.99	22.71		1
16QAM	1	0	23.17	23.26	22.91	0-1	1
	1	36	23.27	23.26	22.83		1
	1	74	23.15	23.18	22.60		1
	36	0	22.11	22.04	21.64	0-2	2
	36	18	22.11	22.05	21.63		2
	36	37	22.07	22.01	21.51		2
	75	0	22.07	22.00	21.62		2
64QAM	1	0	22.21	22.40	21.91	0-2	2
	1	36	22.20	22.37	21.78		2
	1	74	22.22	22.25	21.72		2
	36	0	21.12	21.05	20.67	0-3	3
	36	18	21.11	21.06	20.64		3
	36	37	21.01	21.01	20.50		3
	75	0	21.07	21.04	20.61		3
256QAM	1	0	19.24	19.23	18.72	0-5	5
	1	36	19.29	19.30	18.61		5
	1	74	19.15	19.12	18.56		5
	36	0	19.08	19.07	18.65		5
	36	18	19.11	19.06	18.69		5
	36	37	19.05	18.98	18.50		5
	75	0	19.07	19.02	18.61		5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 32 of 207

Table H-63
LTE Band 25 (PCS) Ant A Measured P_{Max} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.01	23.99	23.48	0	0
	1	25	24.36	24.09	23.44		0
	1	49	24.15	23.95	23.13		0
	25	0	23.12	23.03	22.59	0-1	1
	25	12	23.12	23.08	22.60		1
	25	25	23.08	23.03	22.45		1
16QAM	50	0	23.06	23.01	22.58	0-1	1
	1	0	23.35	23.34	22.82		1
	1	25	23.39	23.40	22.82		1
	1	49	23.14	23.18	22.74	0-2	1
	25	0	22.18	22.08	21.60		2
	25	12	22.17	22.11	21.66		2
64QAM	25	25	22.12	22.06	21.50	0-2	2
	50	0	22.09	22.04	21.57		2
	1	0	22.29	22.26	21.88	0-2	2
	1	25	22.39	22.38	21.82		2
	1	49	22.07	22.26	21.69		2
	25	0	21.14	21.07	20.64	0-3	3
25	12	21.15	21.11	20.65	3		
25	25	21.09	21.08	20.48	3		
256QAM	50	0	21.10	21.09	20.56	0-5	3
	1	0	19.29	19.09	18.74		5
	1	25	19.29	19.35	18.77		5
	1	49	19.04	19.09	18.50		5
	25	0	19.12	19.06	18.59	5	
	25	12	19.12	19.11	18.61	5	
256QAM	25	25	19.11	19.02	18.48	5	
	50	0	19.08	19.03	18.58	5	

Table H-64
LTE Band 25 (PCS) Ant A Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.16	24.01	23.69	0	0
	1	12	24.15	24.09	23.58		0
	1	24	24.25	23.98	23.61		0
	12	0	23.12	23.04	22.54	0-1	1
	12	6	23.18	23.09	22.58		1
	12	13	23.11	23.05	22.48		1
16QAM	25	0	23.10	23.07	22.55	0-1	1
	1	0	23.37	23.31	22.87		1
	1	12	23.47	23.45	23.03		1
	1	24	23.41	23.43	23.06	0-2	1
	12	0	22.16	22.07	21.55		2
	12	6	22.23	22.18	21.63		2
64QAM	12	13	22.19	22.12	21.50	0-2	2
	25	0	22.14	22.07	21.56		2
	1	0	22.48	22.38	21.81	0-2	2
	1	12	22.44	22.46	21.88		2
	1	24	22.43	22.29	21.73		2
	12	0	21.12	21.08	20.61	0-3	3
12	6	21.22	21.14	20.61	3		
12	13	21.17	21.11	20.51	3		
256QAM	25	0	21.14	21.06	20.57	0-5	3
	1	0	19.36	19.24	18.71		5
	1	12	19.41	19.40	18.81		5
	1	24	19.22	19.17	18.63		5
	12	0	19.09	19.05	18.56	5	
	12	6	19.18	19.16	18.61	5	
12	13	19.15	19.08	18.51	5		
25	0	19.11	19.03	18.55	5		

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 33 of 207

Table H-65
LTE Band 25 (PCS) Ant A Measured P_{Max} for DSI = 1 (Head) - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.12	24.05	23.44	0	0
	1	7	24.28	24.18	23.59		0
	1	14	24.24	24.05	23.41		0
	8	0	23.06	23.04	22.51	0-1	1
	8	4	23.16	23.09	22.56		1
	8	7	23.09	23.06	22.53		1
16QAM	15	0	23.13	23.06	22.64	0-1	1
	1	0	23.32	23.24	22.92		1
	1	7	23.35	23.47	22.81		1
	1	14	23.32	23.17	22.64	0-2	1
	8	0	22.25	22.11	21.65		2
	8	4	22.25	22.19	21.64		2
64QAM	8	7	22.23	22.16	21.64	0-2	2
	15	0	22.17	22.10	21.61		2
	1	0	22.41	22.24	21.67	0-2	2
	1	7	22.48	22.47	21.85		2
	1	14	22.42	22.38	21.63		2
	8	0	21.18	21.07	20.58	0-3	3
8	4	21.20	21.13	20.66	3		
8	7	21.20	21.10	20.58	3		
256QAM	15	0	21.16	21.09	20.54	0-5	3
	1	0	19.17	19.08	18.77		5
	1	7	19.39	19.36	18.67		5
	1	14	19.20	19.17	18.53		5
	8	0	19.11	19.10	18.50		5
	8	4	19.17	19.18	18.62		5
	8	7	19.12	19.10	18.59		5
	15	0	19.17	19.10	18.52		5

Table H-66
LTE Band 25 (PCS) Ant A Measured P_{Max} for DSI = 1 (Head) – 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.17	24.07	23.44	0	0
	1	2	24.10	23.99	23.44		0
	1	5	24.18	24.06	23.57		0
	3	0	24.06	24.04	23.36		0
	3	2	24.08	24.00	23.38		0
	3	3	24.04	23.99	23.36		0
	6	0	22.96	23.02	22.44		0-1
16QAM	1	0	23.47	23.28	22.90	0-1	1
	1	2	23.43	23.09	22.81		1
	1	5	23.33	23.14	22.67		1
	3	0	23.27	23.37	22.56		1
	3	2	23.19	23.23	22.66		1
	3	3	23.31	23.26	22.82		1
	6	0	22.14	22.17	21.60		0-2
64QAM	1	0	22.33	22.37	21.81	0-2	2
	1	2	22.45	22.37	21.84		2
	1	5	22.36	22.32	21.80		2
	3	0	22.39	22.20	21.63		2
	3	2	22.29	22.24	21.73		2
	3	3	22.34	22.23	21.70		2
	6	0	21.09	21.14	20.59		0-3
256QAM	1	0	19.37	19.27	18.73	0-5	5
	1	2	19.24	19.18	18.84		5
	1	5	19.24	19.17	18.77		5
	3	0	19.15	19.23	18.51		5
	3	2	19.12	19.18	18.55		5
	3	3	19.04	19.13	18.59		5
	6	0	19.05	19.11	18.46		5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 34 of 207

Table H-67
LTE Band 25 (PCS) Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.20	20.30	19.86	0	0
	1	36	20.28	20.50	19.74		0
	1	74	20.14	20.20	19.61		0
	36	0	20.15	20.13	19.93	0-1	0
	36	18	20.11	20.16	19.90		0
	36	37	20.10	20.11	19.80		0
	75	0	20.13	20.12	19.91		0
16QAM	1	0	20.34	20.30	20.09	0-1	0
	1	36	20.34	20.41	20.02		0
	1	74	20.23	20.36	19.96		0
	36	0	20.16	20.15	19.93	0-2	0
	36	18	20.16	20.17	19.96		0
	36	37	20.14	20.15	19.82		0
	75	0	20.13	20.15	19.95		0
64QAM	1	0	20.27	20.39	20.18	0-2	0
	1	36	20.40	20.51	20.13		0
	1	74	20.28	20.37	19.94		0
	36	0	20.19	20.19	19.92	0-3	0
	36	18	20.18	20.18	19.94		0
	36	37	20.15	20.11	19.82		0
	75	0	20.15	20.16	19.93		0
256QAM	1	0	19.04	18.94	18.89	0-5	1.5
	1	36	19.03	19.01	18.73		1.5
	1	74	18.88	18.93	18.58		1.5
	36	0	18.86	18.89	18.67		1.5
	36	18	18.88	18.87	18.66		1.5
	36	37	18.83	18.82	18.55		1.5
	75	0	18.85	18.87	18.64		1.5

Table H-68
LTE Band 25 (PCS) Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.24	20.04	19.72	0	0
	1	25	20.31	20.24	19.89		0
	1	49	20.12	20.07	19.65		0
	25	0	20.17	20.20	19.90	0-1	0
	25	12	20.15	20.20	20.01		0
	25	25	20.15	20.12	19.77		0
	50	0	20.16	20.16	19.91		0
16QAM	1	0	20.42	20.25	19.93	0-1	0
	1	25	20.56	20.34	20.15		0
	1	49	20.33	20.31	19.96		0
	25	0	20.19	20.18	19.97	0-2	0
	25	12	20.17	20.21	20.03		0
	25	25	20.19	20.15	19.80		0
	50	0	20.15	20.16	19.93		0
64QAM	1	0	20.37	20.34	19.97	0-2	0
	1	25	20.31	20.48	20.27		0
	1	49	20.38	20.45	19.99		0
	25	0	20.18	20.21	19.98	0-3	0
	25	12	20.22	20.24	20.04		0
	25	25	20.18	20.12	19.80		0
	50	0	20.19	20.19	19.95		0
256QAM	1	0	19.01	18.88	18.66	0-5	1.5
	1	25	19.05	19.16	18.95		1.5
	1	49	18.87	18.90	18.39		1.5
	25	0	18.89	18.93	18.66		1.5
	25	12	18.89	19.00	18.73		1.5
	25	25	18.86	18.88	18.54		1.5
	50	0	18.86	18.92	18.63		1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 35 of 207

Table H-69
LTE Band 25 (PCS) Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.21	20.17	20.04	0	0
	1	12	20.24	20.19	19.81		0
	1	24	20.15	20.02	19.81		0
	12	0	20.19	20.17	19.88	0-1	0
	12	6	20.21	20.23	19.84		0
	12	13	20.15	20.12	19.77		0
	25	0	20.18	20.18	19.77		0
16QAM	1	0	20.48	20.44	20.40	0-1	0
	1	12	20.52	20.65	20.13		0
	1	24	20.44	20.37	20.25		0
	12	0	20.20	20.19	19.93	0-2	0
	12	6	20.30	20.26	19.90		0
	12	13	20.15	20.11	19.85		0
	25	0	20.18	20.22	19.85		0
64QAM	1	0	20.47	20.36	20.27	0-2	0
	1	12	20.55	20.56	20.05		0
	1	24	20.41	20.26	20.05		0
	12	0	20.19	20.22	19.93	0-3	0
	12	6	20.30	20.28	19.89		0
	12	13	20.22	20.16	19.84		0
	25	0	20.21	20.19	19.88		0
256QAM	1	0	18.95	19.14	18.80	0-5	1.5
	1	12	19.14	19.21	18.78		1.5
	1	24	19.04	19.04	18.64		1.5
	12	0	18.92	18.95	18.57		1.5
	12	6	18.97	18.99	18.55		1.5
	12	13	18.94	18.90	18.53		1.5
	25	0	18.91	18.92	18.56		1.5

Table H-70
LTE Band 25 (PCS) Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.03	20.19	19.61	0	0
	1	7	20.40	20.29	19.70		0
	1	14	20.16	20.13	19.67		0
	8	0	20.16	20.19	19.72	0-1	0
	8	4	20.22	20.22	19.79		0
	8	7	20.20	20.13	19.83		0
	15	0	20.19	20.17	19.75		0
16QAM	1	0	20.31	20.36	19.93	0-1	0
	1	7	20.57	20.52	20.08		0
	1	14	20.46	20.31	19.93		0
	8	0	20.24	20.26	19.82	0-2	0
	8	4	20.29	20.27	19.89		0
	8	7	20.25	20.19	19.87		0
	15	0	20.16	20.18	19.78		0
64QAM	1	0	20.27	20.43	20.00	0-2	0
	1	7	20.52	20.55	20.09		0
	1	14	20.42	20.35	19.94		0
	8	0	20.19	20.28	19.79	0-3	0
	8	4	20.32	20.24	19.91		0
	8	7	20.26	20.19	19.89		0
	15	0	20.26	20.22	19.83		0
256QAM	1	0	18.89	18.93	18.55	0-5	1.5
	1	7	19.14	19.08	18.63		1.5
	1	14	18.97	19.00	18.60		1.5
	8	0	18.87	18.94	18.47		1.5
	8	4	18.96	19.00	18.57		1.5
	8	7	18.91	18.94	18.57		1.5
	15	0	18.93	18.97	18.49		1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 36 of 207

Table H-71
LTE Band 25 (PCS) Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.18	20.30	19.87	0	0
	1	2	20.35	20.20	19.53		0
	1	5	20.38	20.20	19.58		0
	3	0	20.29	20.26	19.56		0
	3	2	20.20	20.20	19.66		0
	3	3	20.23	20.15	19.65		0
	6	0	20.20	20.26	19.62		0-1
16QAM	1	0	20.69	20.58	19.90	0-1	0
	1	2	20.61	20.47	19.81		0
	1	5	20.64	20.47	19.86		0
	3	0	20.43	20.44	19.85		0
	3	2	20.46	20.43	19.80		0
	3	3	20.48	20.43	19.78		0
	6	0	20.33	20.35	19.77		0-2
64QAM	1	0	20.55	20.70	20.08	0-2	0
	1	2	20.56	20.57	19.99		0
	1	5	20.48	20.48	20.03		0
	3	0	20.45	20.44	19.98		0
	3	2	20.46	20.52	19.92		0
	3	3	20.51	20.53	20.01		0
	6	0	20.43	20.43	19.83		0-3
256QAM	1	0	19.18	19.38	18.69	0-5	1.5
	1	2	19.19	19.26	18.60		1.5
	1	5	19.27	19.24	18.61		1.5
	3	0	19.04	19.24	18.50		1.5
	3	2	19.10	19.15	18.50		1.5
	3	3	19.05	19.12	18.48		1.5
	6	0	19.03	19.13	18.44		1.5

Table H-72
LTE Band 25 (PCS) Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.21	18.32	17.88	0	0
	1	36	18.33	18.35	17.74		0
	1	74	18.14	18.22	17.62		0
	36	0	18.23	18.17	17.97	0-1	0
	36	18	18.19	18.21	17.95		0
	36	37	18.19	18.14	17.86		0
16QAM	75	0	18.18	18.17	17.99	0-1	0
	1	0	18.27	18.35	18.14		0
	1	36	18.33	18.53	18.02		0
	1	74	18.24	18.45	17.87	0-2	0
	36	0	18.24	18.26	17.99		0
	36	18	18.27	18.26	17.97		0
64QAM	36	37	18.23	18.21	17.91	0-2	0
	75	0	18.22	18.21	17.98		0
	1	0	18.31	18.64	18.19		0-2
	1	36	18.37	18.57	18.13	0	
	1	74	18.27	18.58	17.98	0	
	36	0	18.23	18.22	18.01	0-3	0
256QAM	36	18	18.29	18.25	18.03		0
	36	37	18.20	18.19	17.89		0
	75	0	18.24	18.21	18.00	0-5	0
	1	0	18.25	18.29	18.08		0
	1	36	18.36	18.46	18.06		0
	256QAM	1	74	18.34	18.40	17.74	0-5
36		0	18.24	18.25	18.03	0	
36		18	18.26	18.18	18.02	0	
36		37	18.20	18.10	17.97	0	
75		0	18.21	18.23	18.05	0	

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 37 of 207

Table H-73
LTE Band 25 (PCS) Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.16	18.07	17.73	0	0
	1	25	18.40	18.25	17.90		0
	1	49	18.24	18.11	17.63		0
	25	0	18.23	18.21	17.93	0-1	0
	25	12	18.25	18.27	18.04		0
	25	25	18.19	18.16	17.86		0
	50	0	18.20	18.16	17.90		0
16QAM	1	0	18.45	18.37	17.97	0-1	0
	1	25	18.52	18.43	18.28		0
	1	49	18.43	18.39	17.81		0
	25	0	18.28	18.26	17.96	0-2	0
	25	12	18.28	18.28	18.08		0
	25	25	18.26	18.20	17.88		0
	50	0	18.24	18.23	17.95		0
64QAM	1	0	18.33	18.41	18.19	0-2	0
	1	25	18.41	18.65	18.26		0
	1	49	18.31	18.47	18.06		0
	25	0	18.20	18.29	17.96	0-3	0
	25	12	18.27	18.31	18.09		0
	25	25	18.27	18.19	17.91		0
	50	0	18.23	18.26	17.96		0
256QAM	1	0	18.23	18.17	17.91	0-5	0
	1	25	18.31	18.48	18.20		0
	1	49	18.29	18.18	17.84		0
	25	0	18.29	18.26	17.99		0
	25	12	18.22	18.33	18.08		0
	25	25	18.22	18.17	17.88		0
	50	0	18.26	18.27	17.97		0

Table H-74
LTE Band 25 (PCS) Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.20	18.15	18.11	0	0
	1	12	18.31	18.34	18.01		0
	1	24	18.14	18.07	17.90		0
	12	0	18.17	18.26	18.00	0-1	0
	12	6	18.27	18.25	17.95		0
	12	13	18.21	18.18	17.83		0
	25	0	18.20	18.26	17.91		0
16QAM	1	0	18.49	18.48	18.51	0-1	0
	1	12	18.52	18.40	18.33		0
	1	24	18.42	18.39	18.18		0
	12	0	18.22	18.28	18.05	0-2	0
	12	6	18.33	18.32	18.05		0
	12	13	18.28	18.23	17.91		0
	25	0	18.25	18.28	17.97		0
64QAM	1	0	18.37	18.47	18.32	0-2	0
	1	12	18.48	18.60	18.17		0
	1	24	18.39	18.32	18.07		0
	12	0	18.20	18.33	18.07	0-3	0
	12	6	18.33	18.37	18.05		0
	12	13	18.32	18.25	17.90		0
	25	0	18.27	18.23	17.98		0
256QAM	1	0	18.25	18.29	18.29	0-5	0
	1	12	18.43	18.65	18.19		0
	1	24	18.26	18.25	18.04		0
	12	0	18.17	18.26	18.03		0
	12	6	18.31	18.31	18.00		0
	12	13	18.24	18.22	17.89		0
	25	0	18.23	18.26	17.99		0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 38 of 207

Table H-75
LTE Band 25 (PCS) Ant F Measured P_{Limit} for DSI = 1 (Head) - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.13	18.18	17.71	0	0
	1	7	18.38	18.34	17.80		0
	1	14	18.17	18.18	17.70		0
	8	0	18.21	18.21	17.81	0-1	0
	8	4	18.29	18.28	17.83		0
	8	7	18.27	18.18	17.85		0
16QAM	15	0	18.22	18.27	17.83	0	
	1	0	18.37	18.36	17.94	0-1	0
	1	7	18.56	18.55	18.03		0
	1	14	18.46	18.32	17.86		0
	8	0	18.30	18.35	17.91	0-2	0
	8	4	18.42	18.37	17.89		0
8	7	18.36	18.36	17.89	0		
64QAM	15	0	18.25	18.29	17.87	0	
	1	0	18.32	18.48	18.02	0-2	0
	1	7	18.58	18.67	17.99		0
	1	14	18.37	18.37	18.01		0
	8	0	18.30	18.32	17.87	0-3	0
	8	4	18.37	18.35	17.90		0
8	7	18.35	18.35	17.91	0		
256QAM	15	0	18.30	18.31	17.93	0	
	1	0	18.23	18.34	18.00	0-5	0
	1	7	18.60	18.61	18.07		0
	1	14	18.38	18.33	18.03		0
	8	0	18.28	18.31	17.92		0
	8	4	18.35	18.34	17.90		0
8	7	18.32	18.23	17.91	0		
	15	0	18.27	18.26	17.87	0	

Table H-76
LTE Band 25 (PCS) Ant F Measured P_{Limit} for DSI = 1 (Head) – 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.13	18.25	17.75	0	0
	1	2	18.09	18.19	17.69		0
	1	5	18.16	18.18	17.79		0
	3	0	18.05	18.18	17.67		0
	3	2	18.09	18.13	17.72		0
	3	3	18.04	18.18	17.71		0
	6	0	18.05	18.24	17.71	0-1	0
16QAM	1	0	18.61	18.48	17.95	0-1	0
	1	2	18.52	18.60	17.98		0
	1	5	18.50	18.45	17.88		0
	3	0	18.25	18.46	18.04		0
	3	2	18.25	18.39	17.96		0
	3	3	18.29	18.46	17.99		0
	6	0	18.24	18.39	17.92	0-2	0
64QAM	1	0	18.42	18.62	18.07	0-2	0
	1	2	18.49	18.61	18.10		0
	1	5	18.32	18.46	18.06		0
	3	0	18.36	18.58	18.04		0
	3	2	18.33	18.45	18.02		0
	3	3	18.44	18.45	17.95		0
	6	0	18.23	18.36	17.88	0-3	0
256QAM	1	0	18.48	18.50	17.95	0-5	0
	1	2	18.28	18.32	18.01		0
	1	5	18.47	18.45	18.21		0
	3	0	18.32	18.46	17.92		0
	3	2	18.28	18.38	17.89		0
	3	3	18.28	18.35	17.93		0
	6	0	18.19	18.32	17.85	0	

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 39 of 207

H.1.8 LTE Band 30

Table H-77

LTE Band 30 Ant A Measured P_{limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz) Conducted Power [dBm]		
QPSK	1	0	19.47	0	0
	1	12	19.45		0
	1	24	19.25		0
	12	0	19.34	0-1	0
	12	6	19.34		0
	12	13	19.28		0
16QAM	25	0	19.33	0-1	0
	1	0	19.79		0
	1	12	19.74		0
	1	24	19.66	0-2	0
	12	0	19.38		0
	12	6	19.41		0
64QAM	12	13	19.28	0-2	0
	25	0	19.33		0
	1	0	19.58	0-3	0
	1	12	19.51		0
	1	24	19.47		0
	12	0	19.41	0-3	0
256QAM	12	6	19.43		0
	12	13	19.29		0
	25	0	19.32	0-5	0
	1	0	18.12		1.5
	1	12	18.22		1.5
	1	24	17.94		1.5
	12	0	18.00		1.5
	12	6	18.02		1.5
	12	13	17.87		1.5
	25	0	17.95		1.5

Table H-78

LTE Band 30 Ant A Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz) Conducted Power [dBm]		
QPSK	1	0	23.12	0	0
	1	12	23.15		0
	1	24	23.05		0
	12	0	22.14	0-1	1
	12	6	22.14		1
	12	13	22.03		1
16QAM	25	0	22.10	0-1	1
	1	0	22.65		1
	1	12	22.48		1
	1	24	22.41	0-2	1
	12	0	21.19		2
	12	6	21.19		2
64QAM	12	13	21.05	0-2	2
	25	0	21.13		2
	1	0	21.43	0-3	2
	1	12	21.38		2
	1	24	21.31		2
	12	0	20.16	0-3	3
256QAM	12	6	20.17		3
	12	13	20.05		3
	25	0	20.10	0-5	3
	1	0	18.12		5
	1	12	18.32		5
	1	24	18.01		5
	12	0	18.06		5
	12	6	18.09		5
	12	13	17.99		5
	25	0	18.02		5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 40 of 207

Table H-79
LTE Band 30 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	18.20	0	0
	1	12	18.24		0
	1	24	18.23		0
	12	0	18.20	0-1	0
	12	6	18.20		0
	12	13	18.15		0
	25	0	18.16		0
16QAM	1	0	18.51	0-1	0
	1	12	18.52		0
	1	24	18.57		0
	12	0	18.26	0-2	0
	12	6	18.27		0
	12	13	18.20		0
	25	0	18.17		0
64QAM	1	0	18.41	0-2	0
	1	12	18.50		0
	1	24	18.39		0
	12	0	18.24	0-3	0
	12	6	18.24		0
	12	13	18.15		0
	25	0	18.15		0
256QAM	1	0	18.01	0-5	0.5
	1	12	18.15		0.5
	1	24	17.93		0.5
	12	0	17.97		0.5
	12	6	17.96		0.5
	12	13	17.90		0.5
	25	0	17.89		0.5

Table H-80
LTE Band 30 Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	16.60	0	0
	1	12	16.63		0
	1	24	16.55		0
	12	0	16.59	0-1	0
	12	6	16.58		0
	12	13	16.57		0
	25	0	16.57		0
16QAM	1	0	16.93	0-1	0
	1	12	16.95		0
	1	24	16.90		0
	12	0	16.65	0-2	0
	12	6	16.62		0
	12	13	16.60		0
	25	0	16.58		0
64QAM	1	0	16.69	0-2	0
	1	12	16.91		0
	1	24	16.61		0
	12	0	16.61	0-3	0
	12	6	16.61		0
	12	13	16.59		0
	25	0	16.57		0
256QAM	1	0	16.70	0-5	0
	1	12	16.88		0
	1	24	16.63		0
	12	0	16.61		0
	12	6	16.60		0
	12	13	16.58		0
	25	0	16.56		0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 41 of 207

H.1.9 LTE Band 7

Table H-81

LTE Band 7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.41	19.36	19.25	0	0
	1	36	19.40	19.20	19.38		0
	1	74	19.47	19.26	19.29		0
	36	0	19.48	19.29	19.25	0-1	0
	36	18	19.49	19.27	19.21		0
	36	37	19.42	19.26	19.24		0
	75	0	19.51	19.29	19.18		0
16QAM	1	0	19.67	19.51	19.38	0-1	0
	1	36	19.63	19.44	19.35		0
	1	74	19.57	19.41	19.37		0
	36	0	19.52	19.29	19.25	0-2	0
	36	18	19.53	19.31	19.24		0
	36	37	19.44	19.33	19.30		0
	75	0	19.52	19.31	19.24		0
64QAM	1	0	19.54	19.61	19.34	0-2	0
	1	36	19.75	19.62	19.47		0
	1	74	19.63	19.55	19.38		0
	36	0	19.57	19.34	19.26	0-3	0
	36	18	19.54	19.32	19.28		0
	36	37	19.47	19.30	19.30		0
	75	0	19.58	19.33	19.26		0
256QAM	1	0	18.75	18.61	18.51	0-5	1
	1	36	18.74	18.57	18.39		1
	1	74	18.74	18.50	18.52		1
	36	0	18.62	18.43	18.35		1
	36	18	18.64	18.45	18.41		1
	36	37	18.59	18.43	18.46		1
	75	0	18.68	18.45	18.36		1

Table H-82

LTE Band 7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.60	19.43	19.26	0	0
	1	25	19.80	19.20	19.23		0
	1	49	19.53	19.36	19.17		0
	25	0	19.54	19.31	19.25	0-1	0
	25	12	19.57	19.32	19.35		0
	25	25	19.43	19.29	19.32		0
	50	0	19.54	19.32	19.30		0
16QAM	1	0	19.87	19.60	19.47	0-1	0
	1	25	19.99	19.45	19.51		0
	1	49	19.81	19.45	19.50		0
	25	0	19.55	19.35	19.27	0-2	0
	25	12	19.60	19.33	19.37		0
	25	25	19.50	19.32	19.36		0
	50	0	19.53	19.32	19.32		0
64QAM	1	0	19.75	19.57	19.44	0-2	0
	1	25	19.82	19.64	19.59		0
	1	49	19.77	19.66	19.59		0
	25	0	19.60	19.39	19.26	0-3	0
	25	12	19.60	19.33	19.39		0
	25	25	19.48	19.32	19.40		0
	50	0	19.57	19.32	19.36		0
256QAM	1	0	18.50	18.68	18.52	0-5	1
	1	25	18.87	18.66	18.64		1
	1	49	18.77	18.54	18.58		1
	25	0	18.71	18.48	18.37		1
	25	12	18.68	18.43	18.45		1
	25	25	18.56	18.42	18.43		1
	50	0	18.70	18.48	18.45		1

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 42 of 207

Table H-83
LTE Band 7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.73	19.24	19.42	0	0
	1	12	19.77	19.28	19.42		0
	1	24	19.67	19.22	19.43		0
	12	0	19.62	19.30	19.25	0-1	0
	12	6	19.61	19.34	19.34		0
	12	13	19.54	19.31	19.35		0
	25	0	19.55	19.31	19.33		0
16QAM	1	0	19.93	19.68	19.65	0-1	0
	1	12	19.90	19.60	19.70		0
	1	24	19.92	19.61	19.67		0
	12	0	19.63	19.36	19.28	0-2	0
	12	6	19.61	19.44	19.37		0
	12	13	19.58	19.37	19.41		0
	25	0	19.53	19.35	19.35		0
64QAM	1	0	19.77	19.55	19.49	0-2	0
	1	12	19.94	19.46	19.66		0
	1	24	19.93	19.50	19.62		0
	12	0	19.60	19.39	19.35	0-3	0
	12	6	19.61	19.42	19.35		0
	12	13	19.57	19.36	19.40		0
	25	0	19.53	19.33	19.40		0
256QAM	1	0	18.81	18.52	18.50	0-5	1
	1	12	18.82	18.59	18.67		1
	1	24	18.67	18.50	18.49		1
	12	0	18.40	18.43	18.38		1
	12	6	18.75	18.45	18.46		1
	12	13	18.65	18.44	18.48		1
	25	0	18.62	18.47	18.49		1

Table H-84
LTE Band 7 Ant B Measured P_{Max} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 7							
15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.38	23.56	23.50	0	0
	1	36	23.80	23.42	23.57		0
	1	74	23.70	23.38	23.24		0
	36	0	22.69	22.46	22.40	0-1	1
	36	18	22.70	22.46	22.42		1
	36	37	22.61	22.45	22.44		1
	75	0	22.68	22.47	22.41		1
16QAM	1	0	22.23	22.68	22.61	0-1	1
	1	36	22.85	22.57	22.50		1
	1	74	22.92	22.53	22.51		1
	36	0	21.72	21.52	21.42	0-2	2
	36	18	21.75	21.51	21.43		2
	36	37	21.64	21.50	21.50		2
	75	0	21.72	21.53	21.43		2
64QAM	1	0	21.14	21.81	21.65	0-2	2
	1	36	21.95	21.75	21.68		2
	1	74	21.86	21.59	21.64		2
	36	0	20.72	20.52	20.42	0-3	3
	36	18	20.72	20.52	20.40		3
	36	37	20.62	20.47	20.46		3
	75	0	20.73	20.48	20.43		3
256QAM	1	0	18.31	18.77	18.63	0-5	5
	1	36	18.90	18.56	18.66		5
	1	74	18.79	18.60	18.63		5
	36	0	18.68	18.51	18.39		5
	36	18	18.70	18.49	18.41		5
	36	37	18.65	18.51	18.48		5
	75	0	18.70	18.50	18.41		5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 43 of 207

Table H-85
LTE Band 7 Ant B Measured P_{Max} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.03	23.51	23.33	0	0
	1	25	23.81	23.42	23.35		0
	1	49	23.82	23.39	23.27		0
	25	0	22.50	22.50	22.45	0-1	1
	25	12	22.77	22.48	22.54		1
	25	25	22.69	22.44	22.48		1
	50	0	22.74	22.51	22.55		1
16QAM	1	0	22.23	22.75	22.74	0-1	1
	1	25	22.81	22.64	22.58		1
	1	49	22.88	22.75	22.53		1
	25	0	21.61	21.55	21.47	0-2	2
	25	12	21.81	21.51	21.55		2
	25	25	21.68	21.52	21.52		2
	50	0	21.78	21.48	21.52		2
64QAM	1	0	21.20	21.87	21.69	0-2	2
	1	25	21.82	21.82	21.79		2
	1	49	21.83	21.69	21.69		2
	25	0	20.56	20.54	20.46	0-3	3
	25	12	20.81	20.55	20.55		3
	25	25	20.69	20.49	20.54		3
	50	0	20.78	20.51	20.54		3
256QAM	1	0	18.35	18.60	18.59	0-5	5
	1	25	18.80	18.64	18.69		5
	1	49	18.76	18.54	18.61		5
	25	0	18.65	18.53	18.44		5
	25	12	18.79	18.52	18.52		5
	25	25	18.66	18.48	18.51		5
	50	0	18.75	18.50	18.51		5

Table H-86
LTE Band 7 Ant B Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.33	23.41	23.51	0	0
	1	12	23.36	23.41	23.52		0
	1	24	23.76	23.36	23.26		0
	12	0	22.91	22.47	22.43	0-1	1
	12	6	22.40	22.53	22.47		1
	12	13	22.64	22.49	22.44		1
	25	0	22.41	22.49	22.49		1
16QAM	1	0	22.20	22.65	22.82	0-1	1
	1	12	22.65	22.77	22.82		1
	1	24	22.98	22.78	22.58		1
	12	0	21.48	21.53	21.47	0-2	2
	12	6	21.43	21.58	21.57		2
	12	13	21.74	21.57	21.61		2
	25	0	21.39	21.52	21.54		2
64QAM	1	0	21.15	21.71	21.78	0-2	2
	1	12	21.64	21.68	21.80		2
	1	24	21.94	21.63	21.73		2
	12	0	20.46	20.48	20.46	0-3	3
	12	6	20.48	20.54	20.53		3
	12	13	20.65	20.54	20.58		3
	25	0	20.47	20.47	20.60		3
256QAM	1	0	18.33	18.58	18.64	0-5	5
	1	12	18.77	18.71	18.77		5
	1	24	18.75	18.55	18.53		5
	12	0	18.60	18.48	18.46		5
	12	6	18.66	18.48	18.52		5
	12	13	18.65	18.49	18.56		5
	25	0	18.64	18.46	18.50		5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 44 of 207

Table H-87

LTE Band 7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

LTE Band 7							
15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	16.97	17.09	16.67	0	0
	1	36	16.57	16.70	16.41		0
	1	74	16.63	16.74	16.42		0
	36	0	16.63	16.77	16.50	0-1	0
	36	18	16.45	16.75	16.49		0
	36	37	16.51	16.72	16.42		0
	75	0	16.60	16.81	16.46		0
16QAM	1	0	16.63	16.89	16.66	0-1	0
	1	36	16.76	16.91	16.56		0
	1	74	16.76	16.75	16.52		0
	36	0	16.59	16.85	16.51	0-2	0
	36	18	16.67	16.85	16.53		0
	36	37	16.65	16.73	16.45		0
	75	0	16.61	16.82	16.55		0
64QAM	1	0	16.62	16.94	16.75	0-2	0
	1	36	16.82	16.83	16.70		0
	1	74	16.66	16.85	16.43		0
	36	0	16.68	16.86	16.57	0-3	0
	36	18	16.62	16.81	16.51		0
	36	37	16.65	16.82	16.49		0
	75	0	16.63	16.77	16.58		0
256QAM	1	0	16.67	16.82	16.82	0-5	0
	1	36	16.79	16.74	16.70		0
	1	74	16.81	16.71	16.49		0
	36	0	16.78	16.85	16.58		0
	36	18	16.53	16.94	16.57		0
	36	37	16.63	16.85	16.54		0
	75	0	16.62	16.76	16.62		0

Table H-88

LTE Band 7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	16.73	16.80	16.51	0	0
	1	25	16.64	16.89	16.53		0
	1	49	16.53	16.75	16.47		0
	25	0	16.63	16.81	16.49	0-1	0
	25	12	16.63	16.92	16.56		0
	25	25	16.62	16.85	16.48		0
	50	0	16.65	16.85	16.51		0
16QAM	1	0	16.92	17.12	16.65	0-1	0
	1	25	17.00	17.08	16.81		0
	1	49	16.99	17.00	16.60		0
	25	0	16.67	16.88	16.62	0-2	0
	25	12	16.78	16.85	16.62		0
	25	25	16.70	16.87	16.50		0
	50	0	16.62	16.82	16.60		0
64QAM	1	0	16.72	16.99	16.75	0-2	0
	1	25	16.87	17.09	16.67		0
	1	49	16.82	16.85	16.61		0
	25	0	16.74	16.90	16.63	0-3	0
	25	12	16.72	16.89	16.60		0
	25	25	16.73	16.88	16.56		0
	50	0	16.65	16.88	16.58		0
256QAM	1	0	16.75	16.95	16.75	0-5	0
	1	25	16.75	17.00	16.66		0
	1	49	16.75	16.98	16.49		0
	25	0	16.81	16.92	16.65		0
	25	12	16.78	16.87	16.65		0
	25	25	16.72	16.91	16.60		0
	50	0	16.78	16.85	16.62		0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 45 of 207

Table H-89
LTE Band 7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 7							
5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	16.72	16.98	16.40	0	0
	1	12	16.77	16.85	16.47		0
	1	24	16.72	16.82	16.44		0
	12	0	16.66	16.88	16.44	0-1	0
	12	6	16.76	17.00	16.54		0
	12	13	16.67	16.83	16.49		0
	25	0	16.66	16.88	16.50		0
16QAM	1	0	16.67	16.90	16.63	0-1	0
	1	12	16.90	17.16	16.68		0
	1	24	16.90	16.96	16.68		0
	12	0	16.70	16.96	16.50	0-2	0
	12	6	16.82	16.87	16.57		0
	12	13	16.74	16.95	16.50		0
	25	0	16.75	16.86	16.54		0
64QAM	1	0	16.93	17.02	16.61	0-2	0
	1	12	16.98	17.03	16.56		0
	1	24	16.83	17.13	16.48		0
	12	0	16.78	16.89	16.53	0-3	0
	12	6	16.79	16.83	16.55		0
	12	13	16.77	16.85	16.52		0
	25	0	16.72	16.88	16.52		0
256QAM	1	0	16.83	16.91	16.48	0-5	0
	1	12	16.89	17.02	16.73		0
	1	24	16.81	17.02	16.48		0
	12	0	16.77	16.78	16.52		0
	12	6	16.91	16.86	16.55		0
	12	13	16.70	16.87	16.57		0
	25	0	16.79	16.88	16.58		0

Table H-90
LTE Band 7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	15.84	15.82	15.58	0	0
	1	36	15.93	15.88	15.52		0
	1	74	15.79	15.77	15.49		0
	36	0	15.84	15.88	15.65	0-1	0
	36	18	15.85	15.84	15.62		0
	36	37	15.83	15.86	15.62		0
	75	0	15.86	15.86	15.64		0
16QAM	1	0	15.99	16.00	15.82	0-1	0
	1	36	15.96	15.93	15.81		0
	1	74	15.96	15.82	15.69		0
	36	0	15.92	15.83	15.70	0-2	0
	36	18	15.87	15.85	15.67		0
	36	37	15.86	15.82	15.64		0
	75	0	15.84	15.84	15.65		0
64QAM	1	0	15.93	16.02	15.91	0-2	0
	1	36	16.07	16.05	15.79		0
	1	74	15.92	16.06	15.72		0
	36	0	15.90	15.86	15.73	0-3	0
	36	18	15.91	15.84	15.67		0
	36	37	15.81	15.82	15.65		0
	75	0	15.87	15.85	15.69		0
256QAM	1	0	16.13	15.99	15.93	0-5	0
	1	36	16.01	15.95	15.80		0
	1	74	15.99	15.98	15.59		0
	36	0	15.87	15.83	15.72		0
	36	18	15.88	15.87	15.71		0
	36	37	15.88	15.87	15.71		0
	75	0	15.87	15.86	15.71		0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 46 of 207

Table H-91
LTE Band 7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	16.01	15.84	15.66	0	0
	1	25	16.02	15.95	15.57		0
	1	49	15.90	15.81	15.54		0
	25	0	15.93	15.84	15.68	0-1	0
	25	12	15.95	15.90	15.68		0
	25	25	15.92	15.91	15.66		0
	50	0	15.90	15.90	15.68		0
16QAM	1	0	16.24	16.11	15.81	0-1	0
	1	25	16.10	16.08	15.81		0
	1	49	16.20	15.95	15.74		0
	25	0	15.95	15.86	15.69	0-2	0
	25	12	15.97	15.89	15.70		0
	25	25	15.90	15.85	15.68		0
	50	0	15.93	15.86	15.67		0
64QAM	1	0	16.04	16.11	15.92	0-2	0
	1	25	16.11	16.12	15.87		0
	1	49	16.09	16.00	15.83		0
	25	0	16.00	15.83	15.67	0-3	0
	25	12	15.97	15.86	15.72		0
	25	25	15.92	15.89	15.71		0
	50	0	15.91	15.87	15.69		0
256QAM	1	0	16.14	15.99	15.82	0-5	0
	1	25	16.00	16.02	15.88		0
	1	49	16.03	15.90	15.79		0
	25	0	15.99	15.88	15.78		0
	25	12	15.99	15.92	15.75		0
	25	25	15.93	15.87	15.71		0
	50	0	15.95	15.89	15.77		0

Table H-92
LTE Band 7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 7							
5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	15.96	15.83	15.71	0	0
	1	12	15.97	15.85	15.71		0
	1	24	15.93	15.75	15.70		0
	12	0	15.87	15.84	15.65	0-1	0
	12	6	15.88	15.89	15.68		0
	12	13	15.87	15.86	15.64		0
	25	0	15.83	15.82	15.64		0
16QAM	1	0	16.13	16.03	15.96	0-1	0
	1	12	16.15	16.22	16.03		0
	1	24	16.14	16.05	16.03		0
	12	0	15.81	15.83	15.69	0-2	0
	12	6	15.91	15.91	15.72		0
	12	13	15.86	15.89	15.68		0
	25	0	15.89	15.87	15.66		0
64QAM	1	0	16.06	16.08	15.89	0-2	0
	1	12	16.02	16.09	15.94		0
	1	24	15.99	16.00	15.83		0
	12	0	15.91	15.82	15.67	0-3	0
	12	6	15.93	15.91	15.70		0
	12	13	15.85	15.87	15.63		0
	25	0	15.90	15.85	15.67		0
256QAM	1	0	16.00	16.02	15.85	0-5	0
	1	12	16.12	16.12	15.91		0
	1	24	16.03	16.04	15.93		0
	12	0	15.86	15.88	15.71		0
	12	6	15.98	15.94	15.72		0
	12	13	15.91	15.89	15.70		0
	25	0	15.92	15.92	15.67		0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 47 of 207

H.1.10 LTE Band 41

Table H-93

LTE Band 41 PC3 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	21.87	21.69	21.89	21.81	21.39	0	0	
	1	36	21.91	21.80	21.82	21.74	21.34		0	
	1	74	21.77	21.71	21.73	21.59	21.15		0	
	36	0	21.93	21.75	21.78	21.86	21.41	0-1	0	
	36	18	21.91	21.83	21.82	21.78	21.36		0	
	36	37	21.91	21.78	21.78	21.66	21.21		0	
16QAM	75	0	21.89	21.80	21.80	21.80	21.34	0-1	0	
	1	0	21.89	21.65	21.68	21.92	21.40		0	
	1	36	21.91	21.78	21.70	21.83	21.25		0	
	1	74	21.92	21.53	21.58	21.68	20.95	0-2	0	
	36	0	21.96	21.74	21.85	21.86	21.42		0	
	36	18	21.92	21.83	21.88	21.86	21.42		0	
64QAM	36	37	21.87	21.80	21.80	21.70	21.22	0-2	0	
	75	0	21.90	21.80	21.86	21.78	21.37		0	
	1	0	21.91	21.67	21.77	21.94	21.51		0-2	0
	1	36	21.92	21.83	21.72	21.92	21.42	0		
	1	74	21.76	21.69	21.58	21.58	21.14	0		
	36	0	21.77	21.57	21.64	21.63	21.25	0-3	0	
36	18	21.72	21.67	21.62	21.65	21.21	0			
36	37	21.72	21.61	21.61	21.49	21.05	0			
256QAM	75	0	21.75	21.60	21.64	21.61	21.15	0-3	0	
	1	0	19.63	19.48	19.48	19.67	19.09		0-5	2
	1	36	19.76	19.50	19.51	19.48	19.15			2
	1	74	19.58	19.48	19.45	19.33	18.81	2		
	36	0	19.72	19.53	19.56	19.66	19.23	2		
	36	18	19.75	19.64	19.64	19.63	19.17	2		
36	37	19.66	19.58	19.61	19.46	19.01	2			
256QAM	75	0	19.71	19.56	19.64	19.59	19.17	0-5	2	

Table H-94

LTE Band 41 PC3 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	21.92	21.72	21.92	21.96	21.42	0	0
	1	25	21.90	21.79	21.89	21.89	21.38		0
	1	49	21.82	21.69	21.81	21.74	21.18		0
	25	0	21.90	21.76	21.85	21.91	21.46	0-1	0
	25	12	21.94	21.88	21.90	21.94	21.45		0
	25	25	21.88	21.87	21.86	21.86	21.37		0
	50	0	21.89	21.84	21.85	21.90	21.41		0
16QAM	1	0	21.83	21.65	21.75	21.91	21.37	0-1	0
	1	25	21.90	21.68	21.67	21.88	21.36		0
	1	49	21.82	21.67	21.66	21.64	21.32		0
	25	0	21.92	21.77	21.81	21.93	21.50	0-2	0
	25	12	21.93	21.87	21.94	21.92	21.44		0
	25	25	21.88	21.85	21.88	21.83	21.35		0
	50	0	21.92	21.86	21.89	21.87	21.43		0
64QAM	1	0	21.91	21.88	21.77	21.81	21.56	0-2	0
	1	25	21.97	21.77	21.68	21.93	21.33		0
	1	49	21.82	21.81	21.74	21.70	21.35		0
	25	0	21.74	21.54	21.63	21.72	21.25	0-3	0
	25	12	21.75	21.66	21.72	21.71	21.26		0
	25	25	21.67	21.64	21.67	21.66	21.18		0
	50	0	21.71	21.65	21.70	21.69	21.23		0
256QAM	1	0	19.61	19.50	19.55	19.69	19.29	0-5	2
	1	25	19.69	19.54	19.63	19.65	19.13		2
	1	49	19.58	19.61	19.48	19.49	18.99		2
	25	0	19.70	19.53	19.63	19.72	19.29		2
	25	12	19.74	19.67	19.73	19.75	19.25		2
	25	25	19.66	19.61	19.67	19.64	19.16		2
	50	0	19.71	19.61	19.72	19.67	19.19		2

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 48 of 207

Table H-95

LTE Band 41 PC3 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	21.80	21.73	21.71	21.83	21.32	0	0
	1	12	21.89	21.74	21.80	21.93	21.31		0
	1	24	21.82	21.66	21.70	21.73	21.16		0
	12	0	21.89	21.86	21.88	21.88	21.41	0-1	0
	12	6	21.86	21.84	21.89	21.89	21.41		0
	12	13	21.88	21.78	21.85	21.85	21.33		0
16QAM	25	0	21.88	21.81	21.84	21.85	21.35	0	
	1	0	21.80	21.71	21.70	21.82	21.20	0	
	1	12	21.94	21.81	21.74	21.83	21.33	0-1	0
	1	24	21.76	21.69	21.57	21.67	21.11		0
	12	0	21.85	21.87	21.89	21.92	21.43		0
	12	6	21.91	21.88	21.91	21.87	21.42	0-2	0
12	13	21.91	21.83	21.82	21.86	21.38	0		
25	0	21.91	21.89	21.89	21.84	21.38	0		
64QAM	1	0	21.78	21.65	21.71	21.67	21.24	0-2	0
	1	12	21.95	21.69	21.81	21.85	21.31		0
	1	24	21.65	21.66	21.64	21.52	21.23		0
	12	0	21.78	21.72	21.71	21.68	21.23	0-3	0
	12	6	21.72	21.66	21.66	21.67	21.24		0
	12	13	21.73	21.63	21.64	21.63	21.19		0
256QAM	25	0	21.71	21.65	21.61	21.65	21.19	0	
	1	0	19.48	19.56	19.54	19.54	19.12	2	
	1	12	19.65	19.64	19.68	19.68	19.19	2	
	1	24	19.61	19.52	19.44	19.41	18.93	0-5	2
	12	0	19.74	19.64	19.66	19.68	19.18		2
	12	6	19.72	19.65	19.74	19.71	19.24		2
256QAM	12	13	19.70	19.62	19.65	19.62	19.17	2	
	25	0	19.69	19.67	19.67	19.63	19.19	2	

Table H-96

LTE Band 41 PC3 Ant B Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	21.27	21.12	21.27	21.24	20.82	0	0
	1	36	21.28	21.18	21.24	21.19	20.70		0
	1	74	21.16	21.13	21.12	20.98	20.52		0
	36	0	21.33	21.17	21.16	21.24	20.84	0-1	0
	36	18	21.34	21.27	21.24	21.20	20.79		0
	36	37	21.29	21.20	21.15	21.06	20.66		0
	75	0	21.29	21.19	21.18	21.21	20.75		0
16QAM	1	0	21.17	21.06	21.12	21.27	20.80	0-1	0
	1	36	21.38	21.04	21.00	21.26	20.70		0
	1	74	21.24	21.19	21.02	21.08	20.41		0
	36	0	21.34	21.11	21.25	21.26	20.88	0-2	0
	36	18	21.35	21.27	21.29	21.27	20.83		0
	36	37	21.30	21.21	21.19	21.11	20.65		0
	75	0	21.34	21.20	21.26	21.19	20.78		0
64QAM	1	0	21.34	21.11	21.12	21.09	20.75	0-2	0
	1	36	21.27	21.24	21.06	21.23	20.88		0
	1	74	21.20	21.18	20.97	21.08	20.54		0
	36	0	21.40	21.15	21.20	21.27	20.84	0-3	0
	36	18	21.39	21.25	21.22	21.20	20.79		0
	36	37	21.33	21.24	21.17	21.06	20.64		0
	75	0	21.36	21.22	21.21	21.19	20.76		0
256QAM	1	0	19.57	19.38	19.55	19.65	19.23	0-5	1.4
	1	36	19.60	19.54	19.66	19.54	19.16		1.4
	1	74	19.54	19.45	19.37	19.40	18.90		1.4
	36	0	19.74	19.53	19.60	19.66	19.28	0-5	1.4
	36	18	19.76	19.65	19.63	19.63	19.19		1.4
	36	37	19.70	19.58	19.61	19.45	19.06		1.4
	75	0	19.72	19.57	19.63	19.57	19.16		1.4

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 49 of 207

Table H-97
LTE Band 41 PC3 Ant B Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	21.23	21.11	21.33	21.33	20.80	0	0
	1	25	21.32	21.22	21.30	21.25	20.80		0
	1	49	21.22	21.09	21.18	21.07	20.59		0
	25	0	21.30	21.13	21.24	21.27	20.85	0-1	0
	25	12	21.30	21.29	21.34	21.31	20.87		0
	25	25	21.30	21.22	21.25	21.22	20.78		0
	50	0	21.30	21.21	21.30	21.27	20.81		0
16QAM	1	0	21.29	21.04	21.15	21.40	20.89	0-1	0
	1	25	21.21	21.24	21.18	21.27	20.79		0
	1	49	21.20	21.16	20.98	21.07	20.53		0
	25	0	21.32	21.11	21.22	21.30	20.85	0-2	0
	25	12	21.31	21.24	21.28	21.32	20.88		0
	25	25	21.28	21.21	21.25	21.26	20.78		0
	50	0	21.28	21.23	21.30	21.29	20.84		0
64QAM	1	0	21.39	21.10	21.10	21.37	20.79	0-2	0
	1	25	21.22	21.23	21.24	21.16	20.83		0
	1	49	21.16	21.16	21.02	21.11	20.55		0
	25	0	21.36	21.14	21.24	21.29	20.85	0-3	0
	25	12	21.37	21.23	21.31	21.28	20.86		0
	25	25	21.28	21.25	21.29	21.19	20.80		0
	50	0	21.32	21.21	21.27	21.27	20.83		0
256QAM	1	0	19.59	19.40	19.46	19.69	19.25	0-5	1.4
	1	25	19.74	19.54	19.62	19.66	19.12		1.4
	1	49	19.56	19.48	19.51	19.42	19.12		1.4
	25	0	19.73	19.48	19.63	19.69	19.27		1.4
	25	12	19.70	19.62	19.74	19.73	19.25		1.4
	25	25	19.65	19.60	19.66	19.63	19.12		1.4
	50	0	19.68	19.60	19.71	19.68	19.23		1.4

Table H-98
LTE Band 41 PC3 Ant B Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	21.25	21.09	21.08	21.16	20.65	0	0
	1	12	21.33	21.15	21.20	21.25	20.72		0
	1	24	21.23	21.04	21.08	21.11	20.51		0
	12	0	21.30	21.23	21.28	21.25	20.82	0-1	0
	12	6	21.31	21.27	21.27	21.27	20.77		0
	12	13	21.27	21.20	21.23	21.22	20.74		0
16QAM	25	0	21.29	21.23	21.25	21.22	20.77	0-1	0
	1	0	21.21	21.16	21.03	21.15	20.64		0
	1	12	21.38	21.07	21.03	21.27	20.77		0
	1	24	21.27	21.03	21.07	20.99	20.51	0-2	0
	12	0	21.33	21.21	21.30	21.28	20.82		0
	12	6	21.31	21.22	21.29	21.29	20.81		0
	12	13	21.32	21.20	21.22	21.29	20.78	0	
	25	0	21.34	21.20	21.32	21.21	20.78	0	
64QAM	1	0	21.19	21.08	21.09	21.12	20.64	0-2	0
	1	12	21.31	21.13	21.21	21.23	20.71		0
	1	24	21.18	21.10	21.18	21.00	20.50		0
	12	0	21.32	21.26	21.27	21.27	20.78	0-3	0
	12	6	21.30	21.27	21.33	21.30	20.82		0
	12	13	21.35	21.23	21.21	21.21	20.73		0
	25	0	21.33	21.25	21.24	21.22	20.79	0	
	256QAM	1	0	19.61	19.51	19.48	19.48	19.10	0-5
1		12	19.86	19.64	19.57	19.54	19.21	1.4	
1		24	19.65	19.47	19.41	19.40	18.94	1.4	
12		0	19.76	19.62	19.67	19.61	19.22	1.4	
12		6	19.71	19.62	19.70	19.67	19.22	1.4	
12		13	19.68	19.62	19.63	19.60	19.12	1.4	
25		0	19.69	19.56	19.68	19.62	19.14	1.4	

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 50 of 207

Table H-99

LTE Band 41 PC3 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	17.89	17.88	17.89	17.93	17.85	0	0
	1	36	18.00	17.87	17.87	17.92	17.80		0
	1	74	17.99	17.82	17.83	17.79	17.71		0
	36	0	17.98	17.98	17.92	17.93	17.86	0-1	0
	36	18	18.07	18.01	17.96	17.92	17.81		0
	36	37	18.08	17.87	17.92	17.91	17.83		0
	75	0	18.08	17.96	17.94	17.90	17.89		0
16QAM	1	0	18.02	17.86	17.85	17.88	17.91	0-1	0
	1	36	17.95	17.88	18.04	17.97	17.84		0
	1	74	18.07	17.93	17.79	17.73	17.63		0
	36	0	18.04	17.99	17.94	17.98	17.91	0-2	0
	36	18	18.13	17.98	18.02	17.96	17.84		0
	36	37	18.13	17.81	17.96	17.97	17.87		0
	75	0	18.05	17.98	17.98	17.91	17.90		0
64QAM	1	0	18.02	18.01	17.97	18.16	18.09	0-2	0
	1	36	18.16	18.04	18.03	17.95	17.98		0
	1	74	18.04	18.01	17.95	17.89	17.78		0
	36	0	18.05	17.98	17.97	17.98	17.93	0-3	0
	36	18	18.13	18.02	18.01	17.96	17.88		0
	36	37	18.14	17.87	17.97	17.97	17.87		0
	75	0	18.11	17.97	17.99	17.96	17.92		0
256QAM	1	0	17.83	17.92	17.91	17.91	17.84	0-5	0
	1	36	18.20	17.92	17.97	18.02	17.85		0
	1	74	18.02	17.84	17.83	17.83	17.71		0
	36	0	18.05	18.01	17.94	17.98	17.90		0
	36	18	18.16	18.01	18.02	17.97	17.88		0
	36	37	18.17	17.93	17.99	17.95	17.85		0
	75	0	18.13	18.01	18.01	17.93	17.90		0

Table H-100

LTE Band 41 PC3 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	17.94	17.95	17.94	17.94	17.87	0	0
	1	25	18.09	17.92	17.91	17.91	17.79		0
	1	49	18.06	17.78	17.87	17.81	17.73		0
	25	0	18.08	18.00	17.96	17.93	17.87	0-1	0
	25	12	18.11	17.99	18.02	17.92	17.93		0
	25	25	18.07	17.88	17.96	17.94	17.87		0
	50	0	18.12	17.96	17.98	17.89	17.90		0
16QAM	1	0	17.88	17.76	17.87	17.84	17.87	0-1	0
	1	25	18.10	17.83	17.91	17.92	17.74		0
	1	49	18.01	17.82	17.83	17.83	17.82		0
	25	0	18.14	17.95	17.96	17.98	17.86	0-2	0
	25	12	18.12	17.97	18.01	17.95	17.95		0
	25	25	18.09	17.84	17.99	17.96	17.90		0
	50	0	18.13	17.96	17.99	17.92	17.93		0
64QAM	1	0	18.08	17.90	18.01	17.99	18.07	0-2	0
	1	25	18.09	17.95	18.05	18.07	17.80		0
	1	49	18.11	17.85	17.86	17.94	17.92		0
	25	0	18.13	18.01	17.98	17.97	17.87	0-3	0
	25	12	18.12	17.97	18.06	17.92	17.93		0
	25	25	18.10	17.86	18.00	17.97	17.89		0
	50	0	18.11	17.99	18.03	17.93	17.97		0
256QAM	1	0	17.94	17.99	17.78	17.82	17.92	0-5	0
	1	25	18.04	17.96	17.99	17.83	17.85		0
	1	49	17.97	17.73	17.77	17.76	17.75		0
	25	0	18.14	17.97	17.96	17.94	17.92		0
	25	12	18.17	17.96	18.06	17.93	17.97		0
	25	25	18.13	17.90	18.02	17.94	17.90		0
	50	0	18.16	17.98	18.00	17.91	17.98		0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 51 of 207

Table H-101

LTE Band 41 PC3 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	18.04	17.96	17.85	17.88	17.78	0	0
	1	12	18.13	17.99	17.98	17.97	17.80		0
	1	24	18.03	17.85	17.88	17.81	17.75		0
	12	0	18.12	18.05	18.03	17.96	17.86	0-1	0
	12	6	18.18	18.04	18.06	17.97	17.95		0
	12	13	18.13	17.92	17.98	18.01	17.91		0
	25	0	18.14	18.03	18.01	17.92	17.92		0
16QAM	1	0	17.98	17.96	17.88	17.94	17.73	0-1	0
	1	12	18.08	18.02	18.03	18.12	17.87		0
	1	24	18.07	17.82	17.87	17.90	17.73		0
	12	0	18.14	18.02	18.05	18.00	17.86	0-2	0
	12	6	18.17	17.98	18.08	17.96	17.94		0
	12	13	18.11	17.90	18.00	18.01	17.93		0
	25	0	18.13	18.01	18.04	17.98	17.96		0
64QAM	1	0	18.18	18.01	18.03	17.94	17.87	0-2	0
	1	12	18.21	17.95	18.13	18.07	18.02		0
	1	24	18.03	17.89	17.98	17.97	17.87		0
	12	0	18.15	18.02	18.05	18.00	17.91	0-3	0
	12	6	18.15	18.05	18.04	18.02	17.98		0
	12	13	18.14	17.86	18.04	17.98	17.93		0
	25	0	18.12	17.99	18.05	17.95	17.93		0
256QAM	1	0	18.04	17.97	17.87	17.80	17.73	0-5	0
	1	12	18.20	17.90	18.06	17.97	17.90		0
	1	24	17.95	17.88	17.88	17.83	17.83		0
	12	0	18.15	18.05	18.05	17.98	17.91		0
	12	6	18.10	18.03	18.07	18.00	18.02		0
	12	13	18.12	17.88	18.03	17.99	17.96		0
	25	0	18.15	18.01	18.04	17.97	17.99		0

Table H-102

LTE Band 41 PC3 Ant F Measured P_{Limit} for DSI = 1 (Head) – 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	16.29	16.42	16.34	16.40	16.29	0	0
	1	36	16.26	16.43	16.33	16.33	16.21		0
	1	74	16.32	16.33	16.21	16.16	16.08		0
	36	0	16.31	16.51	16.35	16.38	16.28	0-1	0
	36	18	16.38	16.55	16.42	16.42	16.23		0
	36	37	16.35	16.42	16.36	16.32	16.27		0
	75	0	16.37	16.49	16.40	16.39	16.20		0
16QAM	1	0	16.57	16.46	16.29	16.40	16.25	0-1	0
	1	36	16.31	16.60	16.35	16.39	16.23		0
	1	74	16.18	16.45	16.20	16.28	16.13		0
	36	0	16.35	16.53	16.37	16.38	16.24	0-2	0
	36	18	16.40	16.56	16.40	16.43	16.25		0
	36	37	16.38	16.41	16.35	16.34	16.27		0
	75	0	16.40	16.53	16.38	16.40	16.19		0
64QAM	1	0	16.48	16.49	16.48	16.44	16.38	0-2	0
	1	36	16.45	16.51	16.49	16.48	16.47		0
	1	74	16.33	16.46	16.28	16.27	16.25		0
	36	0	16.36	16.52	16.39	16.40	16.29	0-3	0
	36	18	16.43	16.57	16.44	16.44	16.28		0
	36	37	16.42	16.44	16.36	16.37	16.28		0
	75	0	16.44	16.52	16.46	16.42	16.26		0
256QAM	1	0	16.31	16.43	16.38	16.36	16.26	0-5	0
	1	36	16.24	16.48	16.45	16.44	16.25		0
	1	74	16.39	16.30	16.31	16.27	16.09		0
	36	0	16.38	16.55	16.39	16.39	16.29		0
	36	18	16.45	16.59	16.50	16.48	16.26		0
	36	37	16.46	16.43	16.39	16.39	16.29		0
	75	0	16.44	16.54	16.47	16.45	16.25		0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 52 of 207

Table H-103
LTE Band 41 PC3 Ant F Measured P_{Limit} for DSI = 1 (Head) – 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	16.37	16.48	16.44	16.46	16.37	0	0
	1	25	16.28	16.51	16.28	16.37	16.31		0
	1	49	16.34	16.35	16.36	16.33	16.27		0
	25	0	16.33	16.53	16.40	16.43	16.34	0-1	0
	25	12	16.41	16.54	16.48	16.47	16.29		0
	25	25	16.38	16.41	16.45	16.40	16.37		0
16QAM	50	0	16.41	16.50	16.44	16.47	16.27	0	
	1	0	16.36	16.37	16.29	16.42	16.34	0	
	1	25	16.37	16.42	16.33	16.33	16.26	0-1	0
	1	49	16.32	16.32	16.23	16.28	16.21		0
	25	0	16.36	16.52	16.39	16.45	16.31		0
	25	12	16.44	16.57	16.47	16.47	16.33	0-2	0
25	25	16.39	16.47	16.43	16.38	16.38	0		
50	0	16.39	16.51	16.46	16.43	16.31	0		
64QAM	1	0	16.48	16.49	16.42	16.53	16.52	0-2	0
	1	25	16.40	16.60	16.53	16.64	16.43		0
	1	49	16.39	16.47	16.44	16.31	16.35		0
	25	0	16.34	16.54	16.43	16.42	16.37	0	
	25	12	16.48	16.57	16.47	16.49	16.36	0-3	0
	25	25	16.42	16.46	16.44	16.45	16.38		0
50	0	16.44	16.53	16.50	16.46	16.34	0		
256QAM	1	0	16.28	16.40	16.23	16.42	16.40	0	
	1	25	16.43	16.47	16.40	16.45	16.30	0	
	1	49	16.33	16.39	16.38	16.32	16.22	0	
	25	0	16.41	16.53	16.39	16.48	16.37	0-5	0
	25	12	16.51	16.55	16.51	16.51	16.33		0
	25	25	16.45	16.51	16.46	16.46	16.38		0
50	0	16.46	16.54	16.50	16.50	16.34	0		

Table H-104
LTE Band 41 PC3 Ant F Measured P_{Limit} for DSI = 1 (Head) – 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	16.42	16.38	16.24	16.28	16.16	0	0
	1	12	16.52	16.53	16.34	16.36	16.32		0
	1	24	16.43	16.36	16.24	16.22	16.16		0
	12	0	16.52	16.53	16.42	16.39	16.26	0-1	0
	12	6	16.57	16.53	16.42	16.44	16.27		0
	12	13	16.55	16.39	16.37	16.41	16.34		0
16QAM	25	0	16.51	16.52	16.37	16.42	16.22	0	
	1	0	16.49	16.43	16.20	16.31	16.12	0	
	1	12	16.52	16.54	16.51	16.31	16.25	0-1	0
	1	24	16.41	16.29	16.19	16.23	16.15		0
	12	0	16.58	16.54	16.39	16.37	16.24		0
	12	6	16.57	16.51	16.45	16.52	16.27	0-2	0
12	13	16.57	16.43	16.37	16.38	16.33	0		
25	0	16.60	16.48	16.42	16.46	16.29	0		
64QAM	1	0	16.51	16.55	16.43	16.44	16.18	0-2	0
	1	12	16.57	16.61	16.44	16.47	16.33		0
	1	24	16.58	16.49	16.46	16.31	16.23		0
	12	0	16.60	16.52	16.43	16.41	16.30	0	
	12	6	16.63	16.56	16.48	16.50	16.32	0-3	0
	12	13	16.62	16.42	16.41	16.44	16.31		0
25	0	16.58	16.49	16.41	16.47	16.27	0		
256QAM	1	0	16.46	16.45	16.27	16.31	16.12	0	
	1	12	16.51	16.50	16.49	16.50	16.35	0	
	1	24	16.46	16.30	16.29	16.28	16.23	0	
	12	0	16.59	16.49	16.42	16.43	16.31	0-5	0
	12	6	16.61	16.53	16.47	16.51	16.32		0
	12	13	16.56	16.43	16.43	16.42	16.36		0
25	0	16.61	16.52	16.43	16.47	16.31	0		

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 53 of 207

H.1.11 LTE Band 48

Table H-105

LTE Band 48 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

LTE Band 48 15 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55315 (3557.5 MHz)	55765 (3602.5 MHz)	56215 (3647.5 MHz)	56665 (3692.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	19.06	19.01	19.22	19.06	0	0
	1	36	19.09	19.09	19.25	19.22		0
	1	74	19.07	19.18	19.23	19.26		0
	36	0	19.17	19.18	19.32	19.25	0-1	0
	36	18	19.21	19.27	19.39	19.32		0
	36	37	19.19	19.31	19.34	19.29		0
	75	0	19.16	19.21	19.41	19.31		0
16QAM	1	0	19.10	19.00	19.21	19.23	0-1	0
	1	36	19.09	19.24	19.41	19.18		0
	1	74	19.25	19.17	19.20	19.36		0
	36	0	19.18	19.20	19.36	19.25	0-2	0
	36	18	19.22	19.23	19.38	19.35		0
	36	37	19.23	19.29	19.34	19.33		0
	75	0	19.17	19.23	19.38	19.33		0
64QAM	1	0	19.16	19.17	19.40	19.15	0-2	0
	1	36	19.16	19.19	19.48	19.23		0
	1	74	19.21	19.34	19.43	19.33		0
	36	0	18.68	18.70	18.89	18.74	0-3	0
	36	18	18.72	18.76	18.91	18.82		0
	36	37	18.71	18.80	18.86	18.82		0
	75	0	18.74	18.74	18.91	18.84		0
256QAM	1	0	16.74	16.57	16.74	16.72	0-5	2
	1	36	16.69	16.61	16.81	16.72		2
	1	74	16.67	16.72	16.80	16.74		2
	36	0	16.67	16.74	16.90	16.79		2
	36	18	16.77	16.74	16.96	16.86		2
	36	37	16.74	16.82	16.85	16.84		2
	75	0	16.75	16.77	16.90	16.86		2

Table H-106

LTE Band 48 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

LTE Band 48 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55290 (3555.0 MHz)	55757 (3601.7 MHz)	56223 (3648.3 MHz)	56690 (3695.0 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	19.31	19.19	19.33	19.26	0	0
	1	25	19.39	19.16	19.27	19.36		0
	1	49	19.40	19.26	19.30	19.36		0
	25	0	19.44	19.27	19.47	19.41	0-1	0
	25	12	19.46	19.33	19.48	19.40		0
	25	25	19.37	19.30	19.32	19.39		0
	50	0	19.41	19.31	19.42	19.37		0
16QAM	1	0	19.36	19.12	19.29	19.31	0-1	0
	1	25	19.22	19.18	19.36	19.29		0
	1	49	19.47	19.18	19.43	19.43		0
	25	0	19.47	19.27	19.45	19.34	0-2	0
	25	12	19.45	19.28	19.48	19.41		0
	25	25	19.35	19.30	19.36	19.40		0
	50	0	19.44	19.26	19.40	19.41		0
64QAM	1	0	19.46	19.24	19.41	19.44	0-2	0
	1	25	19.49	19.44	19.32	19.48		0
	1	49	19.39	19.31	19.41	19.44		0
	25	0	18.94	18.77	18.94	18.87	0-3	0
	25	12	18.93	18.78	19.00	18.94		0
	25	25	18.86	18.76	18.87	18.89		0
	50	0	18.96	18.77	18.93	18.89		0
256QAM	1	0	16.84	16.77	16.82	16.81	0-5	2
	1	25	16.89	16.76	16.83	16.84		2
	1	49	16.76	16.68	16.72	16.83		2
	25	0	16.95	16.75	16.97	16.87		2
	25	12	16.99	16.82	16.96	16.95		2
	25	25	16.88	16.79	16.88	16.95		2
	50	0	16.95	16.77	16.96	16.91		2

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 54 of 207

Table H-107

LTE Band 48 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

LTE Band 48 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55265 (3552.5 MHz)	55748 (3600.8 MHz)	56232 (3649.2 MHz)	56715 (3697.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	18.92	19.22	19.34	19.29	0	0
	1	12	19.27	19.36	19.44	19.37		0
	1	24	19.17	19.25	19.29	19.34		0
	12	0	19.29	19.31	19.46	19.40	0-1	0
	12	6	19.32	19.41	19.48	19.49		0
	12	13	19.30	19.35	19.35	19.44		0
	25	0	19.32	19.34	19.45	19.44		0
16QAM	1	0	19.12	19.15	19.32	19.31	0-1	0
	1	12	19.16	19.30	19.42	19.50		0
	1	24	19.20	19.21	19.40	19.32		0
	12	0	19.31	19.29	19.45	19.41	0-2	0
	12	6	19.35	19.33	19.47	19.44		0
	12	13	19.26	19.27	19.41	19.45		0
	25	0	19.32	19.31	19.50	19.45		0
64QAM	1	0	19.26	19.41	19.38	19.38	0-2	0
	1	12	19.49	19.28	19.43	19.48		0
	1	24	19.38	19.21	19.38	19.50		0
	12	0	18.83	18.81	18.96	18.95	0-3	0
	12	6	18.87	18.84	19.05	18.99		0
	12	13	18.80	18.80	18.90	18.94		0
	25	0	18.81	18.82	19.00	18.92		0
256QAM	1	0	16.64	16.67	16.78	16.75	0-5	2
	1	12	16.76	16.79	16.96	16.86		2
	1	24	16.66	16.60	16.74	16.75		2
	12	0	16.81	16.80	17.01	16.93		2
	12	6	16.87	16.85	17.09	16.97		2
	12	13	16.83	16.84	16.93	16.94		2
	25	0	16.83	16.80	17.04	16.95		2

Table H-108

LTE Band 48 Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

LTE Band 48 15 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55315 (3557.5 MHz)	55765 (3602.5 MHz)	56215 (3647.5 MHz)	56665 (3692.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	15.01	14.95	15.13	14.95	0	0
	1	36	15.00	15.04	15.17	15.06		0
	1	74	15.04	15.10	15.15	15.17		0
	36	0	15.10	15.13	15.31	15.18	0-1	0
	36	18	15.16	15.16	15.32	15.24		0
	36	37	15.14	15.20	15.23	15.24		0
	75	0	15.13	15.15	15.31	15.22		0
16QAM	1	0	15.00	15.11	15.23	15.06	0-1	0
	1	36	15.09	15.08	15.20	15.10		0
	1	74	15.05	15.19	15.26	15.20		0
	36	0	15.13	15.14	15.31	15.19	0-2	0
	36	18	15.16	15.17	15.35	15.21		0
	36	37	15.15	15.24	15.29	15.28		0
	75	0	15.13	15.16	15.33	15.24		0
64QAM	1	0	15.09	15.15	15.33	15.07	0-2	0
	1	36	15.19	15.18	15.29	15.24		0
	1	74	15.20	15.22	15.36	15.37		0
	36	0	15.14	15.16	15.32	15.20	0-3	0
	36	18	15.16	15.19	15.37	15.25		0
	36	37	15.22	15.25	15.28	15.29		0
	75	0	15.16	15.16	15.34	15.29		0
256QAM	1	0	15.00	15.03	15.16	15.01	0-5	0
	1	36	15.05	15.18	15.29	15.12		0
	1	74	15.13	15.18	15.13	15.29		0
	36	0	15.17	15.15	15.33	15.20		0
	36	18	15.15	15.22	15.36	15.30		0
	36	37	15.19	15.22	15.31	15.27		0
	75	0	15.16	15.19	15.37	15.27		0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 55 of 207

Table H-109
LTE Band 48 Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

LTE Band 48 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55290 (3555.0 MHz)	55757 (3601.7 MHz)	56223 (3648.3 MHz)	56690 (3695.0 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	15.19	15.12	15.33	15.16	0	0
	1	25	15.24	15.14	15.22	15.21		0
	1	49	15.20	15.22	15.26	15.29		0
	25	0	15.25	15.21	15.38	15.30	0-1	0
	25	12	15.26	15.27	15.43	15.34		0
	25	25	15.22	15.27	15.28	15.28		0
	50	0	15.21	15.22	15.35	15.33		0
16QAM	1	0	15.10	15.08	15.38	15.10	0-1	0
	1	25	15.20	15.11	15.32	15.20		0
	1	49	15.13	15.16	15.27	15.28		0
	25	0	15.21	15.20	15.41	15.29	0-2	0
	25	12	15.26	15.26	15.41	15.33		0
	25	25	15.21	15.24	15.35	15.29		0
	50	0	15.25	15.25	15.37	15.31		0
64QAM	1	0	15.18	15.20	15.32	15.29	0-2	0
	1	25	15.29	15.26	15.39	15.36		0
	1	49	15.27	15.37	15.37	15.29		0
	25	0	15.25	15.21	15.41	15.25	0-3	0
	25	12	15.27	15.25	15.44	15.36		0
	25	25	15.27	15.28	15.33	15.26		0
	50	0	15.23	15.25	15.38	15.37		0
256QAM	1	0	15.11	15.09	15.27	15.23	0-5	0
	1	25	15.21	15.14	15.33	15.33		0
	1	49	15.22	15.18	15.18	15.21		0
	25	0	15.24	15.24	15.42	15.31		0
	25	12	15.24	15.28	15.47	15.35		0
	25	25	15.26	15.29	15.32	15.31		0
	50	0	15.25	15.25	15.41	15.33		0

Table H-110
LTE Band 48 Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

LTE Band 48 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55265 (3552.5 MHz)	55748 (3600.8 MHz)	56232 (3649.2 MHz)	56715 (3697.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	15.11	15.12	15.30	15.24	0	0
	1	12	15.19	15.22	15.39	15.35		0
	1	24	15.13	15.16	15.28	15.27		0
	12	0	15.23	15.23	15.42	15.37	0-1	0
	12	6	15.31	15.28	15.42	15.39		0
	12	13	15.23	15.23	15.33	15.41		0
	25	0	15.20	15.21	15.40	15.38		0
16QAM	1	0	15.18	15.15	15.33	15.23	0-1	0
	1	12	15.32	15.14	15.43	15.26		0
	1	24	15.16	15.19	15.31	15.16		0
	12	0	15.26	15.25	15.41	15.33	0-2	0
	12	6	15.31	15.31	15.44	15.43		0
	12	13	15.17	15.27	15.34	15.35		0
	25	0	15.20	15.26	15.40	15.40		0
64QAM	1	0	15.25	15.21	15.34	15.39	0-2	0
	1	12	15.25	15.27	15.49	15.49		0
	1	24	15.19	15.21	15.28	15.43		0
	12	0	15.23	15.28	15.44	15.36	0-3	0
	12	6	15.31	15.34	15.48	15.46		0
	12	13	15.24	15.29	15.35	15.43		0
	25	0	15.25	15.27	15.44	15.38		0
256QAM	1	0	15.12	15.18	15.27	15.24	0-5	0
	1	12	15.24	15.22	15.31	15.39		0
	1	24	15.16	15.11	15.25	15.31		0
	12	0	15.24	15.26	15.45	15.40		0
	12	6	15.30	15.32	15.44	15.44		0
	12	13	15.25	15.26	15.41	15.43		0
	25	0	15.28	15.28	15.45	15.39		0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 56 of 207

H.2 NR Lower Bandwidth RF Conducted Powers

H.2.1 NR Band n71

Table H-111
NR Band n71 Ant A Measured P_{Max} for all DSI - 30 MHz Bandwidth

NR Band n71 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	24.14	0	0.0
	1	80	24.40		0.0
	1	158	24.62		0.0
	80	0	23.19	0-1	1.0
	80	40	24.37	0	0.0
	80	80	23.51	0-1	1.0
	160	0	23.35		1.0
DFT-s-OFDM 16QAM	1	1	22.98	0-1	1.0
CP-OFDM QPSK	1	1	22.84	0-1.5	1.5

Table H-112
NR Band n71 Ant A Measured P_{Max} for all DSI - 25 MHz Bandwidth

NR Band n71 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	24.31	0	0.0
	1	67	24.49		0.0
	1	131	24.57		0.0
	64	0	23.19	0-1	1.0
	64	35	24.40	0	0.0
	64	69	23.41	0-1	1.0
	128	0	23.24		1.0
DFT-s-OFDM 16QAM	1	1	23.03	0-1	1.0
CP-OFDM QPSK	1	1	22.84	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 57 of 207

Table H-113
NR Band n71 Ant A Measured P_{Max} for all DSI - 20 MHz Bandwidth

NR Band n71 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	24.16	0	0.0
	1	53	24.28		0.0
	1	104	24.39		0.0
	50	0	23.20	0-1	1.0
	50	28	24.39	0	0.0
	50	56	23.39	0-1	1.0
	100	0	23.51		1.0
DFT-s-OFDM 16QAM	1	1	22.99	0-1	1.0
CP-OFDM QPSK	1	1	22.72	0-1.5	1.5

Table H-114
NR Band n71 Ant A Measured P_{Max} for all DSI - 15 MHz Bandwidth

NR Band n71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	24.22	0	0.0
	1	40	24.28		0.0
	1	77	24.48		0.0
	36	0	23.27	0-1	1.0
	36	22	24.49	0	0.0
	36	43	23.33	0-1	1.0
	75	0	23.44		1.0
DFT-s-OFDM 16QAM	1	1	22.95	0-1	1.0
CP-OFDM QPSK	1	1	22.98	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 58 of 207

Table H-115
NR Band n71 Ant A Measured P_{Max} for all DSI - 10 MHz Bandwidth

NR Band n71 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133600 (668 MHz)	136100 (680.5 MHz)	138600 (693 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.07	24.27	24.32	0	0.0
	1	26	24.10	24.42	24.31		0.0
	1	50	24.08	24.50	24.32		0.0
	25	0	23.12	23.32	23.36	0-1	1.0
	25	14	24.22	24.41	24.44	0	0.0
	25	27	23.11	23.38	23.44	0-1	1.0
	50	0	23.21	23.35	23.41		1.0
DFT-s-OFDM 16QAM	1	1	22.95	23.03	23.17	0-1	1.0
CP-OFDM QPSK	1	1	22.92	22.75	22.97	0-1.5	1.5

Table H-116
NR Band n71 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

NR Band n71 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133100 (665.5 MHz)	136100 (680.5 MHz)	139100 (695.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.13	24.41	24.52	0	0.0
	1	13	24.08	24.35	24.39		0.0
	1	23	24.01	24.51	24.53		0.0
	12	0	23.09	23.47	23.53	0-1	1.0
	12	7	24.14	24.46	24.47	0	0.0
	12	13	23.21	23.44	23.58	0-1	1.0
	25	0	23.24	23.47	23.48		1.0
DFT-s-OFDM 16QAM	1	1	22.96	23.24	23.43	0-1	1.0
CP-OFDM QPSK	1	1	22.76	22.98	23.17	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 59 of 207

Table H-117
NR Band n71 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n71 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.59	0	0.0
	1	80	23.89		0.0
	1	158	23.98		0.0
	80	0	22.62	0-1	1.0
	80	40	23.74	0	0.0
	80	80	22.83	0-1	1.0
	160	0	22.75		1.0
DFT-s-OFDM 16QAM	1	1	22.35	0-1	1.0
CP-OFDM QPSK	1	1	22.14	0-1.5	1.5

Table H-118
NR Band n71 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n71 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.72	0	0.0
	1	67	23.97		0.0
	1	131	24.19		0.0
	64	0	22.69	0-1	1.0
	64	35	23.85	0	0.0
	64	69	22.91	0-1	1.0
	128	0	22.80		1.0
DFT-s-OFDM 16QAM	1	1	22.65	0-1	1.0
CP-OFDM QPSK	1	1	22.33	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 60 of 207

Table H-119
NR Band n71 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n71 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.54	0	0.0
	1	53	23.81		0.0
	1	104	23.82		0.0
	50	0	22.63	0-1	1.0
	50	28	23.81	0	0.0
	50	56	22.83	0-1	1.0
	100	0	22.89		1.0
DFT-s-OFDM 16QAM	1	1	22.38	0-1	1.0
CP-OFDM QPSK	1	1	22.05	0-1.5	1.5

Table H-120
NR Band n71 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.67	0	0.0
	1	40	23.82		0.0
	1	77	23.85		0.0
	36	0	22.70	0-1	1.0
	36	22	23.96	0	0.0
	36	43	22.86	0-1	1.0
	75	0	22.85		1.0
DFT-s-OFDM 16QAM	1	1	22.55	0-1	1.0
CP-OFDM QPSK	1	1	22.33	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 61 of 207

Table H-121

NR Band n71 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n71 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133600 (668 MHz)	136100 (680.5 MHz)	138600 (693 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.39	23.51	23.74	0	0.0
	1	26	23.44	23.73	23.70		0.0
	1	50	23.77	23.86	23.86		0.0
	25	0	22.52	22.85	22.83	0-1	1.0
	25	14	23.60	23.84	23.89	0	0.0
	25	27	22.52	22.86	22.80	0-1	1.0
	50	0	22.65	22.83	22.86		1.0
DFT-s-OFDM 16QAM	1	1	22.36	22.49	22.71	0-1	1.0
CP-OFDM QPSK	1	1	21.99	22.16	22.37	0-1.5	1.5

Table H-122

NR Band n71 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n71 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133100 (665.5 MHz)	136100 (680.5 MHz)	139100 (695.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.42	23.70	23.88	0	0.0
	1	13	23.54	23.86	23.97		0.0
	1	23	23.61	23.91	24.00		0.0
	12	0	22.56	22.78	22.86	0-1	1.0
	12	7	23.62	23.82	23.77	0	0.0
	12	13	22.52	22.80	22.80	0-1	1.0
	25	0	22.60	22.89	22.86		1.0
DFT-s-OFDM 16QAM	1	1	22.52	22.71	22.79	0-1	1.0
CP-OFDM QPSK	1	1	22.13	22.42	22.48	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 62 of 207

Table H-123
NR Band n71 Ant E Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n71 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.17	0	0.0
	1	80	17.51		0.0
	1	158	17.54		0.0
	80	0	17.25	0-1	0.0
	80	40	17.39	0	0.0
	80	80	17.46	0-1	0.0
	160	0	17.37		0.0
DFT-s-OFDM 16QAM	1	1	17.22	0-1	0.0
CP-OFDM QPSK	1	1	17.38	0-1.5	0.0

Table H-124
NR Band n71 Ant E Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n71 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.21	0	0.0
	1	67	17.45		0.0
	1	131	17.64		0.0
	64	0	17.22	0-1	0.0
	64	35	17.28	0	0.0
	64	69	17.38	0-1	0.0
	128	0	17.31		0.0
DFT-s-OFDM 16QAM	1	1	17.18	0-1	0.0
CP-OFDM QPSK	1	1	17.34	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 63 of 207

Table H-125
NR Band n71 Ant E Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n71 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.26	0	0.0
	1	53	17.38		0.0
	1	104	17.51		0.0
	50	0	17.45	0-1	0.0
	50	28	17.63	0	0.0
	50	56	17.60	0-1	0.0
	100	0	17.50		0.0
DFT-s-OFDM 16QAM	1	1	17.23	0-1	0.0
CP-OFDM QPSK	1	1	17.35	0-1.5	0.0

Table H-126
NR Band n71 Ant E Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.22	0	0.0
	1	40	17.33		0.0
	1	77	17.39		0.0
	36	0	17.19	0-1	0.0
	36	22	17.48	0	0.0
	36	43	17.42	0-1	0.0
	75	0	17.51		0.0
DFT-s-OFDM 16QAM	1	1	17.20	0-1	0.0
CP-OFDM QPSK	1	1	17.24	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 64 of 207

Table H-127
NR Band n71 Ant E Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n71 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133600 (668 MHz)	136100 (680.5 MHz)	138600 (693 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.19	17.21	17.27	0	0.0
	1	26	17.20	17.28	17.28		0.0
	1	50	17.13	17.29	17.30		0.0
	25	0	17.17	17.46	17.37	0-1	0.0
	25	14	17.19	17.49	17.37	0	0.0
	25	27	17.26	17.40	17.42	0-1	0.0
	50	0	17.29	17.41	17.39		0.0
DFT-s-OFDM 16QAM	1	1	17.13	17.18	17.20	0-1	0.0
CP-OFDM QPSK	1	1	17.22	17.31	17.44	0-1.5	0.0

Table H-128
NR Band n71 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n71 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133100 (665.5 MHz)	136100 (680.5 MHz)	139100 (695.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.14	17.51	17.51	0	0.0
	1	13	17.13	17.32	17.33		0.0
	1	23	17.17	17.39	17.40		0.0
	12	0	17.20	17.52	17.54	0-1	0.0
	12	7	17.16	17.37	17.43	0	0.0
	12	13	17.25	17.41	17.42	0-1	0.0
	25	0	17.25	17.47	17.49		0.0
DFT-s-OFDM 16QAM	1	1	17.12	17.50	17.59	0-1	0.0
CP-OFDM QPSK	1	1	17.36	17.61	17.60	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 65 of 207

H.2.2 NR Band n12

Table H-129
NR Band n12 Ant A Measured P_{Max} for all DSI - 10 MHz Bandwidth

NR Band n12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			141500 (707.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	24.50	0	0.0
	1	26	24.25		0.0
	1	50	24.39		0.0
	25	0	23.34	0-1	1.0
	25	14	24.18	0	0.0
	25	27	23.32	0-1	1.0
	50	0	23.23		1.0
DFT-s-OFDM 16QAM	1	1	23.39	0-1	1.0
CP-OFDM QPSK	1	1	23.03	0-1.5	1.5

Table H-130
NR Band n12 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

NR Band n12 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	140300 (701.5 MHz)	141500 (707.5 MHz)	142700 (713.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.60	24.25	24.34	0	0.0
	1	13	24.21	24.29	24.47		0.0
	1	23	24.39	24.23	23.98		0.0
	12	0	23.68	23.30	23.55	0-1	1.0
	12	7	24.33	24.22	24.38	0	0.0
	12	13	23.45	23.23	23.27	0-1	1.0
	25	0	23.70	23.29	23.32		1.0
DFT-s-OFDM 16QAM	1	1	23.52	23.23	23.25	0-1	1.0
CP-OFDM QPSK	1	1	23.24	23.12	23.19	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 66 of 207

Table H-131
NR Band n12 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			141500 (707.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.05	0	0.0
	1	26	23.49		0.0
	1	50	23.67		0.0
	25	0	22.12	0-1	1.0
	25	14	23.39	0	0.0
	25	27	22.73	0-1	1.0
	50	0	22.37		1.0
DFT-s-OFDM 16QAM	1	1	22.03	0-1	1.0
CP-OFDM QPSK	1	1	21.63	0-1.5	1.5

Table H-132
NR Band n12 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n12 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	140300 (701.5 MHz)	141500 (707.5 MHz)	142700 (713.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.92	23.45	23.84	0	0.0
	1	13	23.66	23.83	23.78		0.0
	1	23	23.51	23.89	23.40		0.0
	12	0	22.83	22.54	22.84	0-1	1.0
	12	7	23.51	23.70	23.65	0	0.0
	12	13	22.43	22.91	22.51	0-1	1.0
	25	0	22.74	22.70	22.70		1.0
DFT-s-OFDM 16QAM	1	1	22.87	22.29	22.73	0-1	1.0
CP-OFDM QPSK	1	1	22.54	21.86	22.40	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 67 of 207

Table H-133
NR Band n12 Ant E Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			141500 (707.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.74	0	0.0
	1	26	20.82		0.0
	1	50	20.72		0.0
	25	0	20.67	0-1	0.0
	25	14	20.83	0	0.0
	25	27	20.58	0-1	0.0
	50	0	20.60		0.0
DFT-s-OFDM 16QAM	1	1	20.55	0-1	0.0
CP-OFDM QPSK	1	1	20.81	0-1.5	0.0

Table H-134
NR Band n12 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n12 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	140300 (701.5 MHz)	141500 (707.5 MHz)	142700 (713.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.59	20.67	20.62	0	0.0
	1	13	20.82	20.81	20.69		0.0
	1	23	20.60	20.76	20.56		0.0
	12	0	20.61	20.66	20.61	0-1	0.0
	12	7	20.78	20.63	20.62	0	0.0
	12	13	20.60	20.70	20.57	0-1	0.0
	25	0	20.66	20.74	20.62		0.0
DFT-s-OFDM 16QAM	1	1	20.52	20.68	20.63	0-1	0.0
CP-OFDM QPSK	1	1	20.75	20.79	20.70	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 68 of 207

H.2.3 NR Band n14

Table H-135
NR Band n14 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth

NR Band n14 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	158100 (790.5 MHz)	159100 (795.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	24.07	24.31	0	0.0
	1	13	24.33	24.32		0.0
	1	23	24.14	24.23		0.0
	12	0	23.09	23.11	0-1	1.0
	12	7	24.15	24.16	0	0.0
	12	13	23.14	23.14	0-1	1.0
	25	0	23.23	23.11		1.0
DFT-s-OFDM 16QAM	1	1	23.12	23.06	0-1	1.0
CP-OFDM QPSK	1	1	22.75	22.93	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 69 of 207

Table H-136
NR Band n14 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n14 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	158100 (790.5 MHz)	159100 (795.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.60	23.74	0	0.0
	1	13	23.59	24.00		0.0
	1	23	23.95	23.98		0.0
	12	0	22.73	22.79	0-1	1.0
	12	7	23.79	23.81	0	0.0
	12	13	22.69	22.72	0-1	1.0
	25	0	22.73	22.79		1.0
DFT-s-OFDM 16QAM	1	1	22.62	22.63	0-1	1.0
CP-OFDM QPSK	1	1	22.19	22.38	0-1.5	1.5

Table H-137
NR Band n14 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n12 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	140300 (701.5 MHz)	141500 (707.5 MHz)	142700 (713.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.59	20.67	20.62	0	0.0
	1	13	20.82	20.81	20.69		0.0
	1	23	20.60	20.76	20.56		0.0
	12	0	20.61	20.66	20.61	0-1	0.0
	12	7	20.78	20.63	20.62	0	0.0
	12	13	20.60	20.70	20.57	0-1	0.0
	25	0	20.66	20.74	20.62		0.0
DFT-s-OFDM 16QAM	1	1	20.52	20.68	20.63	0-1	0.0
CP-OFDM OPSK	1	1	20.75	20.79	20.70	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 70 of 207

H.2.4 NR Band n26

Table H-138
NR Band n26 Ant A Measured P_{Max} for all DSI - 15 MHz Bandwidth

NR Band n26 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	164300 (821.5 MHz)	168300 (841.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	24.06	24.09	0	0.0
	1	40	24.02	24.01		0.0
	1	77	24.02	24.29		0.0
	36	0	22.98	22.94	0-1	1.0
	36	22	24.07	24.23	0	0.0
	36	43	22.84	23.14	0-1	1.0
	75	0	22.97	23.05		1.0
DFT-s-OFDM 16QAM	1	1	22.91	22.79	0-1	1.0
CP-OFDM QPSK	1	1	22.48	22.70	0-1.5	1.5

Table H-139
NR Band n26 Ant A Measured P_{Max} for all DSI - 10 MHz Bandwidth

NR Band n26 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163800 (819 MHz)	166300 (831.5 MHz)	168800 (844 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.12	23.99	24.11	0	0.0
	1	26	24.03	24.02	24.16		0.0
	1	50	24.00	24.05	24.11		0.0
	25	0	23.06	22.93	23.05	0-1	1.0
	25	14	24.11	24.06	24.08	0	0.0
	25	27	22.97	22.93	23.14	0-1	1.0
	50	0	22.96	22.91	23.04		1.0
DFT-s-OFDM 16QAM	1	1	22.89	22.82	22.89	0-1	1.0
CP-OFDM QPSK	1	1	22.67	22.57	22.70	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 71 of 207

Table H-140
NR Band n26 Ant A Measured P_{Max} for all DSI - 5 MHz Bandwidth
NR Band n26
5 MHz Bandwidth

			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163300 (816.5 MHz)	166300 (831.5 MHz)	169300 (846.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.09	23.96	24.18	0	0.0
	1	13	24.16	24.12	24.20		0.0
	1	23	24.02	24.04	24.10		0.0
	12	0	23.05	22.85	23.14	0-1	1.0
	12	7	24.06	23.90	24.18	0	0.0
	12	13	22.99	22.93	23.10	0-1	1.0
	25	0	23.01	22.91	23.10		1.0
DFT-s-OFDM 16QAM	1	1	23.01	22.82	23.02	0-1	1.0
CP-OFDM QPSK	1	1	22.78	22.58	22.77	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 72 of 207

Table H-141
NR Band n26 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n26 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	164300 (821.5 MHz)	168300 (841.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.51	23.59	0	0.0
	1	40	23.47	23.56		0.0
	1	77	23.79	23.76		0.0
	36	0	22.42	22.50	0-1	1.0
	36	22	23.56	23.62	0	0.0
	36	43	22.41	22.60	0-1	1.0
	75	0	22.44	22.50		1.0
DFT-s-OFDM 16QAM	1	1	22.35	22.28	0-1	1.0
CP-OFDM QPSK	1	1	22.13	22.24	0-1.5	1.5

Table H-142
NR Band n26 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n26							
10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163800 (819 MHz)	166300 (831.5 MHz)	168800 (844 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.44	23.45	23.59	0	0.0
	1	26	23.45	23.47	23.58		0.0
	1	50	23.78	23.56	23.76		0.0
	25	0	22.43	22.50	22.54	0-1	1.0
	25	14	23.59	23.53	23.57	0	0.0
	25	27	22.50	22.45	22.56	0-1	1.0
	50	0	22.53	22.42	22.50		1.0
DFT-s-OFDM 16QAM	1	1	22.34	22.22	22.48	0-1	1.0
CP-OFDM QPSK	1	1	22.07	22.11	22.14	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 73 of 207

Table H-143

NR Band n26 Ant E Measured P_{Max} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n26 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163300 (816.5 MHz)	166300 (831.5 MHz)	169300 (846.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.56	23.48	23.59	0	0.0
	1	13	23.70	23.63	23.70		0.0
	1	23	23.80	23.45	23.56		0.0
	12	0	22.43	22.45	22.53	0-1	1.0
	12	7	23.58	23.48	23.58	0	0.0
	12	13	22.45	22.40	22.53	0-1	1.0
	25	0	22.54	22.40	22.53		1.0
DFT-s-OFDM 16QAM	1	1	22.42	22.33	22.42	0-1	1.0
CP-OFDM QPSK	1	1	22.14	21.99	22.20	0-1.5	1.5

Table H-144

NR Band n26 Ant E Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n26 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	164300 (821.5 MHz)	168300 (841.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	20.24	20.37	0	0.0
	1	40	20.26	20.22		0.0
	1	77	20.38	20.26		0.0
	36	0	20.16	20.17	0-1	0.0
	36	22	20.28	20.34	0	0.0
	36	43	20.14	20.26	0-1	0.0
	75	0	20.11	20.29		0.0
DFT-s-OFDM 16QAM	1	1	20.18	20.24	0-1	0.0
CP-OFDM QPSK	1	1	20.31	20.46	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 74 of 207

Table H-145
NR Band n26 Ant E Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n26 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163800 (819 MHz)	166300 (831.5 MHz)	168800 (844 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.15	20.27	20.21	0	0.0
	1	26	20.29	20.26	20.14		0.0
	1	50	20.19	20.28	20.31		0.0
	25	0	20.11	20.25	20.22	0-1	0.0
	25	14	20.35	20.27	20.31	0	0.0
	25	27	20.27	20.33	20.26	0-1	0.0
	50	0	20.25	20.22	20.19		0.0
DFT-s-OFDM 16QAM	1	1	20.15	20.07	20.23	0-1	0.0
CP-OFDM QPSK	1	1	20.40	20.28	20.41	0-1.5	0.0

Table H-146
NR Band n26 Ant E Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n26 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163300 (816.5 MHz)	166300 (831.5 MHz)	169300 (846.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.33	20.26	20.37	0	0.0
	1	13	20.38	20.33	20.42		0.0
	1	23	20.30	20.24	20.32		0.0
	12	0	20.34	20.24	20.29	0-1	0.0
	12	7	20.30	20.39	20.42	0	0.0
	12	13	20.23	20.24	20.27	0-1	0.0
	25	0	20.21	20.30	20.33		0.0
DFT-s-OFDM 16QAM	1	1	20.36	20.28	20.40	0-1	0.0
CP-OFDM QPSK	1	1	20.50	20.38	20.55	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 75 of 207

H.2.1 NR Band n70

Table H-147

NR Band n70 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n70 10 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	340500 (1702.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.28	0	0.0
	1	26	19.37		0.0
	1	50	19.31		0.0
	25	0	19.25	0-1	0.0
	25	14	19.27	0	0.0
	25	27	19.28	0-1	0.0
	50	0	19.21		0.0
DFT-s-OFDM 16QAM	1	1	19.61	0-1	0.0
CP-OFDM QPSK	1	1	19.25	0-1.5	0.0

Table H-148

NR Band n70 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n70 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	339504 (1697.52 MHz)	341496 (1707.48 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	19.23	19.23	0	0.0
	1	13	19.30	19.36		0.0
	1	23	19.31	19.34		0.0
	12	0	19.22	19.30	0-1	0.0
	12	7	19.45	19.41	0	0.0
	12	13	19.35	19.30	0-1	0.0
	25	0	19.32	19.29		0.0
DFT-s-OFDM 16QAM	1	1	19.76	19.74	0-1	0.0
CP-OFDM QPSK	1	1	19.36	19.41	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 76 of 207

Table H-149
NR Band n70 Ant A Measured P_{Max} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n70 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			340500 (1702.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.43	0	0.0
	1	26	23.47		0.0
	1	50	23.55		0.0
	25	0	22.43	0-1	1.0
	25	14	23.45	0	0.0
	25	27	22.46	0-1	1.0
	50	0	22.49		1.0
DFT-s-OFDM 16QAM	1	1	22.94	0-1	1.0
CP-OFDM QPSK	1	1	22.06	0-1.5	1.5

Table H-150
NR Band n70 Ant A Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n70 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	339504 (1697.52 MHz)	341496 (1707.48 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.40	23.47	0	0.0
	1	13	23.53	23.62		0.0
	1	23	23.42	23.50		0.0
	12	0	22.49	22.47	0-1	1.0
	12	7	23.58	23.62	0	0.0
	12	13	22.52	22.61	0-1	1.0
	25	0	22.51	22.54		1.0
DFT-s-OFDM 16QAM	1	1	22.88	22.95	0-1	1.0
CP-OFDM QPSK	1	1	22.16	22.07	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 77 of 207

Table H-151
NR Band n70 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n70 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			340500 (1702.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.01	0	0.0
	1	26	19.15		0.0
	1	50	18.90		0.0
	25	0	19.04	0-1	0.0
	25	14	19.11	0	0.0
	25	27	19.10	0-1	0.0
	50	0	19.13		0.0
DFT-s-OFDM 16QAM	1	1	19.57	0-1	0.0
CP-OFDM QPSK	1	1	19.26	0-1.5	0.0

Table H-152
NR Band n70 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n70 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	339504 (1697.52 MHz)	341496 (1707.48 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.83	19.17	0	0.0
	1	13	18.95	19.15		0.0
	1	23	18.95	19.14		0.0
	12	0	18.91	19.10	0-1	0.0
	12	7	19.18	19.22	0	0.0
	12	13	18.98	19.13	0-1	0.0
	25	0	19.06	19.17		0.0
DFT-s-OFDM 16QAM	1	1	19.46	19.57	0-1	0.0
CP-OFDM QPSK	1	1	19.06	19.30	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 78 of 207

Table H-153
NR Band n70 Ant F Measured P_{Limit} for DSI = 0 (Head) - 10 MHz Bandwidth

NR Band n70 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			340500 (1702.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.04	0	0.0
	1	26	16.41		0.0
	1	50	16.12		0.0
	25	0	16.02	0-1	0.0
	25	14	16.22	0	0.0
	25	27	16.23	0-1	0.0
	50	0	16.23		0.0
DFT-s-OFDM 16QAM	1	1	16.61	0-1	0.0
CP-OFDM QPSK	1	1	16.35	0-1.5	0.0

Table H-154
NR Band n70 Ant F Measured P_{Limit} for DSI = 0 (Head) - 5 MHz Bandwidth

NR Band n70 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	339504 (1697.52 MHz)	341496 (1707.48 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.08	16.21	0	0.0
	1	13	16.15	16.00		0.0
	1	23	16.08	16.07		0.0
	12	0	16.00	16.19	0-1	0.0
	12	7	16.18	16.26	0	0.0
	12	13	16.19	16.18	0-1	0.0
	25	0	16.18	16.25		0.0
DFT-s-OFDM 16QAM	1	1	16.53	16.86	0-1	0.0
CP-OFDM QPSK	1	1	16.20	16.48	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 79 of 207

H.2.2 NR Band n66

Table H-155

NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n66 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.26	0	0.0
	1	108	17.95		0.0
	1	214	18.05		0.0
	108	0	18.07	0-1	0.0
	108	54	18.03	0	0.0
	108	108	17.98	0-1	0.0
	216	0	18.01		0.0
DFT-s-OFDM 16QAM	1	1	18.19	0-1	0.0
CP-OFDM QPSK	1	1	18.34	0-1.5	0.0

Table H-156

NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n66 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.45	0	0.0
	1	94	18.32		0.0
	1	186	18.23		0.0
	90	0	18.31	0-1	0.0
	90	49	18.29	0	0.0
	90	98	18.21	0-1	0.0
	180	0	18.18		0.0
DFT-s-OFDM 16QAM	1	1	18.45	0-1	0.0
CP-OFDM QPSK	1	1	18.57	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 80 of 207

Table H-157

NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.54	0	0.0
	1	80	18.31		0.0
	1	158	18.29		0.0
	80	0	18.33	0-1	0.0
	80	40	18.29	0	0.0
	80	80	18.10	0-1	0.0
	160	0	18.22		0.0
DFT-s-OFDM 16QAM	1	1	18.42	0-1	0.0
CP-OFDM QPSK	1	1	18.62	0-1.5	0.0

Table H-158

NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.46	0	0.0
	1	67	18.26		0.0
	1	131	18.18		0.0
	64	0	18.27	0-1	0.0
	64	35	18.23	0	0.0
	64	69	18.14	0-1	0.0
	128	0	18.21		0.0
DFT-s-OFDM 16QAM	1	1	18.42	0-1	0.0
CP-OFDM QPSK	1	1	18.53	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 81 of 207

Table H-159

NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.23	17.85	17.71	0	0.0
	1	53	18.06	17.72	17.59		0.0
	1	104	17.96	17.79	17.58		0.0
	50	0	18.07	17.73	17.60	0-1	0.0
	50	28	17.97	17.72	17.55	0	0.0
	50	56	17.87	17.54	17.54	0-1	0.0
	100	0	18.06	17.73	17.65		0.0
DFT-s-OFDM 16QAM	1	1	18.02	17.73	17.62	0-1	0.0
CP-OFDM QPSK	1	1	18.16	17.95	17.78	0-1.5	0.0

Table H-160

NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.68	18.25	18.06	0	0.0
	1	40	18.54	18.14	17.90		0.0
	1	77	18.43	18.12	17.89		0.0
	36	0	18.59	18.18	17.99	0-1	0.0
	36	22	18.55	18.12	17.95	0	0.0
	36	43	18.40	18.03	17.85	0-1	0.0
	75	0	18.47	18.11	17.90		0.0
DFT-s-OFDM 16QAM	1	1	18.70	18.25	18.11	0-1	0.0
CP-OFDM QPSK	1	1	18.80	18.28	18.15	0-1.5	0.0

FCC ID A3LSMS936U

RF Exposure Part 1 Test Report

Approved by:
Technical ManagerDUT Type:
Portable HandsetAPPENDIX H:
Page 82 of 207

Table H-161
NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.74	18.23	18.01	0	0.0
	1	26	18.71	18.17	17.94		0.0
	1	50	18.62	18.21	18.03		0.0
	25	0	18.61	18.14	18.03	0-1	0.0
	25	14	18.70	18.20	18.12	0	0.0
	25	27	18.64	18.06	18.05	0-1	0.0
	50	0	18.60	18.12	18.06		0.0
DFT-s-OFDM 16QAM	1	1	18.66	18.14	18.00	0-1	0.0
CP-OFDM QPSK	1	1	18.84	18.28	18.13	0-1.5	0.0

Table H-162
NR Band n66 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.65	18.21	18.09	0	0.0
	1	13	18.72	18.30	18.18		0.0
	1	23	18.63	18.10	18.00		0.0
	12	0	18.59	18.16	18.06	0-1	0.0
	12	7	18.73	18.23	18.19	0	0.0
	12	13	18.62	18.13	18.03	0-1	0.0
	25	0	18.64	18.13	18.10		0.0
DFT-s-OFDM 16QAM	1	1	18.60	18.13	17.98	0-1	0.0
CP-OFDM QPSK	1	1	18.85	18.32	18.27	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 83 of 207

Table H-163
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n66 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.29	0	0.0
	1	108	22.96		0.0
	1	214	23.03		0.0
	108	0	22.07	0-1	1.0
	108	54	23.02	0	0.0
	108	108	22.03	0-1	1.0
	216	0	22.01		1.0
DFT-s-OFDM 16QAM	1	1	22.27	0-1	1.0
CP-OFDM QPSK	1	1	21.91	0-1.5	1.5

Table H-164
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n66 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.45	0	0.0
	1	94	23.33		0.0
	1	186	23.28		0.0
	90	0	22.41	0-1	1.0
	90	49	23.31	0	0.0
	90	98	22.27	0-1	1.0
	180	0	22.25		1.0
DFT-s-OFDM 16QAM	1	1	22.47	0-1	1.0
CP-OFDM QPSK	1	1	22.17	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 84 of 207

Table H-165
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.64	0	0.0
	1	80	23.31		0.0
	1	158	23.25		0.0
	80	0	22.32	0-1	1.0
	80	40	23.26	0	0.0
	80	80	22.26	0-1	1.0
	160	0	22.25		1.0
DFT-s-OFDM 16QAM	1	1	22.48	0-1	1.0
CP-OFDM QPSK	1	1	22.12	0-1.5	1.5

Table H-166
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.50	0	0.0
	1	67	23.23		0.0
	1	131	23.08		0.0
	64	0	22.32	0-1	1.0
	64	35	23.28	0	0.0
	64	69	22.20	0-1	1.0
	128	0	22.24		1.0
DFT-s-OFDM 16QAM	1	1	22.49	0-1	1.0
CP-OFDM QPSK	1	1	22.16	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 85 of 207

Table H-167
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.69	23.41	23.19	0	0.0
	1	53	23.66	23.22	23.22		0.0
	1	104	23.48	23.15	23.18		0.0
	50	0	22.63	22.24	22.12	0-1	1.0
	50	28	23.65	23.19	23.19	0	0.0
	50	56	22.41	22.19	22.09	0-1	1.0
	100	0	22.60	22.32	22.28		1.0
DFT-s-OFDM 16QAM	1	1	22.60	22.34	22.10	0-1	1.0
CP-OFDM QPSK	1	1	22.25	21.97	21.79	0-1.5	1.5

Table H-168
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.71	23.37	23.19	0	0.0
	1	40	23.48	23.21	23.12		0.0
	1	77	23.50	23.11	22.98		0.0
	36	0	22.71	22.29	22.12	0-1	1.0
	36	22	23.71	23.19	23.02	0	0.0
	36	43	22.60	22.18	22.11	0-1	1.0
	75	0	22.65	22.23	22.17		1.0
DFT-s-OFDM 16QAM	1	1	22.76	22.35	22.22	0-1	1.0
CP-OFDM QPSK	1	1	22.38	21.96	21.81	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 86 of 207

Table H-169
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.79	23.34	23.18	0	0.0
	1	26	23.83	23.18	23.20		0.0
	1	50	23.61	23.27	23.06		0.0
	25	0	22.77	22.20	22.10	0-1	1.0
	25	14	23.75	23.22	23.08	0	0.0
	25	27	22.68	22.21	22.12	0-1	1.0
	50	0	22.68	22.17	22.12		1.0
DFT-s-OFDM 16QAM	1	1	22.66	22.24	22.09	0-1	1.0
CP-OFDM QPSK	1	1	22.32	21.91	21.75	0-1.5	1.5

Table H-170
NR Band n66 Ant A Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.60	23.21	23.10	0	0.0
	1	13	23.72	23.25	23.27		0.0
	1	23	23.58	23.17	23.11		0.0
	12	0	22.68	22.20	22.13	0-1	1.0
	12	7	23.73	23.33	23.12	0	0.0
	12	13	22.67	22.26	22.19	0-1	1.0
	25	0	22.71	22.20	22.04		1.0
DFT-s-OFDM 16QAM	1	1	22.66	22.25	22.09	0-1	1.0
CP-OFDM QPSK	1	1	22.33	21.94	21.76	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 87 of 207

Table H-171
NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n66 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.18	0	0.0
	1	108	20.03		0.0
	1	214	20.03		0.0
	108	0	20.06	0-1	0.0
	108	54	20.11	0	0.0
	108	108	20.03	0-1	0.0
	216	0	20.05		0.0
DFT-s-OFDM 16QAM	1	1	20.10	0-1	0.0
CP-OFDM QPSK	1	1	20.34	0-1.5	0.0

Table H-172
NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n66 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.01	0	0.0
	1	94	19.81		0.0
	1	186	19.91		0.0
	90	0	19.92	0-1	0.0
	90	49	20.01	0	0.0
	90	98	19.74	0-1	0.0
	180	0	19.86		0.0
DFT-s-OFDM 16QAM	1	1	20.03	0-1	0.0
CP-OFDM QPSK	1	1	20.16	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 88 of 207

Table H-173
NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.16	0	0.0
	1	80	19.82		0.0
	1	158	20.02		0.0
	80	0	19.93	0-1	0.0
	80	40	19.98	0	0.0
	80	80	19.81	0-1	0.0
	160	0	19.84		0.0
DFT-s-OFDM 16QAM	1	1	20.06	0-1	0.0
CP-OFDM QPSK	1	1	20.33	0-1.5	0.0

Table H-174
NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.16	0	0.0
	1	67	19.97		0.0
	1	131	19.89		0.0
	64	0	19.81	0-1	0.0
	64	35	19.86	0	0.0
	64	69	19.83	0-1	0.0
	128	0	19.83		0.0
DFT-s-OFDM 16QAM	1	1	19.98	0-1	0.0
CP-OFDM QPSK	1	1	20.19	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 89 of 207

Table H-175
NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.01	19.90	19.88	0	0.0
	1	53	20.09	19.80	19.76		0.0
	1	104	19.77	19.80	19.76		0.0
	50	0	20.04	19.77	19.72	0-1	0.0
	50	28	20.12	19.91	19.75	0	0.0
	50	56	19.88	19.76	19.65	0-1	0.0
	100	0	19.97	19.82	19.80		0.0
DFT-s-OFDM 16QAM	1	1	19.94	19.83	19.39	0-1	0.0
CP-OFDM QPSK	1	1	20.27	20.04	19.81	0-1.5	0.0

Table H-176
NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.10	19.98	19.94	0	0.0
	1	40	20.12	19.90	19.75		0.0
	1	77	20.05	19.84	19.70		0.0
	36	0	20.06	19.70	19.63	0-1	0.0
	36	22	20.15	19.78	19.73	0	0.0
	36	43	19.95	19.73	19.65	0-1	0.0
	75	0	19.98	19.87	19.72		0.0
DFT-s-OFDM 16QAM	1	1	20.12	19.97	19.70	0-1	0.0
CP-OFDM QPSK	1	1	20.26	20.24	19.94	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 90 of 207

Table H-177

NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.25	19.95	19.67	0	0.0
	1	26	20.11	19.96	19.67		0.0
	1	50	20.06	19.83	19.71		0.0
	25	0	20.09	19.84	19.63	0-1	0.0
	25	14	20.16	19.86	19.69	0	0.0
	25	27	20.06	19.73	19.62	0-1	0.0
	50	0	20.09	19.79	19.66		0.0
DFT-s-OFDM 16QAM	1	1	20.03	19.85	19.71	0-1	0.0
CP-OFDM QPSK	1	1	20.12	20.08	19.90	0-1.5	0.0

Table H-178

NR Band n66 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.02	19.86	20.19	0	0.0
	1	13	20.17	19.89	20.12		0.0
	1	23	19.95	19.82	19.97		0.0
	12	0	20.02	19.81	20.11	0-1	0.0
	12	7	20.25	19.95	20.19	0	0.0
	12	13	20.01	19.80	20.12	0-1	0.0
	25	0	20.14	19.83	20.14		0.0
DFT-s-OFDM 16QAM	1	1	20.03	19.82	20.16	0-1	0.0
CP-OFDM QPSK	1	1	20.33	20.07	20.34	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 91 of 207

Table H-179
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n66 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.13	0	0.0
	1	108	15.90		0.0
	1	214	15.85		0.0
	108	0	15.92	0-1	0.0
	108	54	15.91	0	0.0
	108	108	15.84	0-1	0.0
	216	0	15.90		0.0
DFT-s-OFDM 16QAM	1	1	15.96	0-1	0.0
CP-OFDM QPSK	1	1	16.14	0-1.5	0.0

Table H-180
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n66 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.90	0	0.0
	1	94	15.75		0.0
	1	186	15.71		0.0
	90	0	15.79	0-1	0.0
	90	49	15.85	0	0.0
	90	98	15.71	0-1	0.0
	180	0	15.72		0.0
DFT-s-OFDM 16QAM	1	1	15.91	0-1	0.0
CP-OFDM QPSK	1	1	16.18	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 92 of 207

Table H-181
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.22	0	0.0
	1	80	15.72		0.0
	1	158	15.91		0.0
	80	0	15.81	0-1	0.0
	80	40	15.79	0	0.0
	80	80	15.66	0-1	0.0
	160	0	15.78		0.0
DFT-s-OFDM 16QAM	1	1	15.79	0-1	0.0
CP-OFDM QPSK	1	1	16.16	0-1.5	0.0

Table H-182
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.05	0	0.0
	1	67	15.74		0.0
	1	131	16.04		0.0
	64	0	15.76	0-1	0.0
	64	35	15.86	0	0.0
	64	69	15.73	0-1	0.0
	128	0	15.75		0.0
DFT-s-OFDM 16QAM	1	1	15.87	0-1	0.0
CP-OFDM QPSK	1	1	16.04	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 93 of 207

Table H-183
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	15.82	15.79	15.40	0	0.0
	1	53	15.83	15.58	15.63		0.0
	1	104	15.68	15.74	15.48		0.0
	50	0	15.84	15.70	15.48	0-1	0.0
	50	28	15.87	15.65	15.52	0	0.0
	50	56	15.76	15.62	15.46	0-1	0.0
	100	0	15.90	15.75	15.54		0.0
DFT-s-OFDM 16QAM	1	1	15.88	15.68	15.47	0-1	0.0
CP-OFDM QPSK	1	1	16.06	15.81	15.60	0-1.5	0.0

Table H-184
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.10	15.88	15.52	0	0.0
	1	40	15.93	15.68	15.52		0.0
	1	77	15.91	15.65	15.53		0.0
	36	0	15.96	15.71	15.45	0-1	0.0
	36	22	16.05	15.71	15.60	0	0.0
	36	43	15.86	15.66	15.40	0-1	0.0
	75	0	15.93	15.71	15.44		0.0
DFT-s-OFDM 16QAM	1	1	16.04	15.72	15.45	0-1	0.0
CP-OFDM QPSK	1	1	16.35	15.96	15.73	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 94 of 207

Table H-185
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.04	15.61	15.66	0	0.0
	1	26	15.98	15.61	15.69		0.0
	1	50	15.93	15.62	15.65		0.0
	25	0	15.91	15.64	15.59	0-1	0.0
	25	14	15.96	15.76	15.56	0	0.0
	25	27	15.89	15.66	15.55	0-1	0.0
	50	0	15.89	15.65	15.59		0.0
DFT-s-OFDM 16QAM	1	1	15.92	15.50	15.49	0-1	0.0
CP-OFDM QPSK	1	1	16.15	15.78	15.63	0-1.5	0.0

Table H-186
NR Band n66 Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	15.93	15.64	15.49	0	0.0
	1	13	16.02	15.64	15.58		0.0
	1	23	15.88	15.68	15.55		0.0
	12	0	15.84	15.70	15.55	0-1	0.0
	12	7	15.92	15.77	15.61	0	0.0
	12	13	15.89	15.69	15.46	0-1	0.0
	25	0	15.88	15.72	15.46		0.0
DFT-s-OFDM 16QAM	1	1	15.88	15.49	15.44	0-1	0.0
CP-OFDM QPSK	1	1	16.10	15.75	15.64	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 95 of 207

H.2.3 NR Band n25

Table H-187

NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n25 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.75	0	0.0
	1	94	17.82		0.0
	1	186	17.45		0.0
	90	0	17.68	0-1	0.0
	90	49	17.68	0	0.0
	90	98	17.59	0-1	0.0
	180	0	17.62		0.0
DFT-s-OFDM 16QAM	1	1	17.62	0-1	0.0
CP-OFDM QPSK	1	1	17.74	0-1.5	0.0

Table H-188

NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.12	0	0.0
	1	80	18.16		0.0
	1	158	17.90		0.0
	80	0	18.00	0-1	0.0
	80	40	18.12	0	0.0
	80	80	17.99	0-1	0.0
	160	0	17.93		0.0
DFT-s-OFDM 16QAM	1	1	18.11	0-1	0.0
CP-OFDM QPSK	1	1	18.24	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 96 of 207

Table H-189
NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.03	0	0.0
	1	67	18.17		0.0
	1	131	17.80		0.0
	64	0	18.09	0-1	0.0
	64	35	18.10	0	0.0
	64	69	18.03	0-1	0.0
	128	0	18.06		0.0
DFT-s-OFDM 16QAM	1	1	18.17	0-1	0.0
CP-OFDM QPSK	1	1	18.16	0-1.5	0.0

Table H-190
NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.19	18.02	17.95	0	0.0
	1	53	18.12	18.01	17.64		0.0
	1	104	18.12	18.06	17.67		0.0
	50	0	18.11	17.97	17.74	0-1	0.0
	50	28	18.06	17.96	17.75	0	0.0
	50	56	17.98	17.92	17.70	0-1	0.0
	100	0	18.09	18.04	17.81		0.0
DFT-s-OFDM 16QAM	1	1	18.03	17.87	17.80	0-1	0.0
CP-OFDM QPSK	1	1	18.28	18.08	18.03	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 97 of 207

Table H-191

NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.24	18.06	17.73	0	0.0
	1	40	18.08	17.95	17.57		0.0
	1	77	17.98	17.89	17.62		0.0
	36	0	18.16	17.95	17.64	0-1	0.0
	36	22	18.13	18.03	17.68	0	0.0
	36	43	18.04	17.92	17.62	0-1	0.0
	75	0	18.15	18.00	17.69		0.0
DFT-s-OFDM 16QAM	1	1	18.19	18.09	17.80	0-1	0.0
CP-OFDM QPSK	1	1	18.35	18.18	17.83	0-1.5	0.0

Table H-192

NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.26	18.01	17.67	0	0.0
	1	26	18.17	17.93	17.62		0.0
	1	50	18.16	17.96	17.57		0.0
	25	0	18.15	17.90	17.57	0-1	0.0
	25	14	18.19	17.98	17.64	0	0.0
	25	27	18.05	17.88	17.54	0-1	0.0
	50	0	18.04	17.93	17.56		0.0
DFT-s-OFDM 16QAM	1	1	18.13	17.89	17.57	0-1	0.0
CP-OFDM QPSK	1	1	18.32	18.10	17.73	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 98 of 207

Table H-193

NR Band n25 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.24	18.09	17.58	0	0.0
	1	13	18.17	18.08	17.68		0.0
	1	23	18.09	17.97	17.56		0.0
	12	0	18.21	18.05	17.65	0-1	0.0
	12	7	18.17	18.05	17.70	0	0.0
	12	13	18.11	17.94	17.59	0-1	0.0
	25	0	18.15	17.98	17.48		0.0
DFT-s-OFDM 16QAM	1	1	18.14	18.03	17.61	0-1	0.0
CP-OFDM QPSK	1	1	18.42	18.21	17.83	0-1.5	0.0

Table H-194

NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n25 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.82	0	0.0
	1	94	23.94		0.0
	1	186	23.61		0.0
	90	0	22.80	0-1	1.0
	90	49	23.87	0	0.0
	90	98	22.66	0-1	1.0
	180	0	22.72		1.0
DFT-s-OFDM 16QAM	1	1	22.76	0-1	1.0
CP-OFDM QPSK	1	1	22.57	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 99 of 207

Table H-195
NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.84	0	0.0
	1	80	23.84		0.0
	1	158	23.71		0.0
	80	0	22.77	0-1	1.0
	80	40	23.79	0	0.0
	80	80	22.68	0-1	1.0
	160	0	22.70		1.0
DFT-s-OFDM 16QAM	1	1	22.79	0-1	1.0
CP-OFDM QPSK	1	1	22.56	0-1.5	1.5

Table H-196
NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.82	0	0.0
	1	67	23.79		0.0
	1	131	23.62		0.0
	64	0	22.80	0-1	1.0
	64	35	23.74	0	0.0
	64	69	22.65	0-1	1.0
	128	0	22.66		1.0
DFT-s-OFDM 16QAM	1	1	22.73	0-1	1.0
CP-OFDM QPSK	1	1	22.44	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 100 of 207

Table H-197
NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.87	23.81	23.63	0	0.0
	1	53	23.88	23.79	23.46		0.0
	1	104	23.82	23.64	23.36		0.0
	50	0	22.83	22.76	22.54	0-1	1.0
	50	28	23.78	23.72	23.54	0	0.0
	50	56	22.69	22.73	22.37	0-1	1.0
	100	0	22.84	22.76	22.60		1.0
DFT-s-OFDM 16QAM	1	1	22.78	22.59	22.52	0-1	1.0
CP-OFDM QPSK	1	1	22.60	22.26	22.34	0-1.5	1.5

Table H-198
NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.88	23.77	23.51	0	0.0
	1	40	23.76	23.63	23.35		0.0
	1	77	23.74	23.64	23.24		0.0
	36	0	22.82	22.78	22.43	0-1	1.0
	36	22	23.79	23.69	23.44	0	0.0
	36	43	22.76	22.73	22.29	0-1	1.0
	75	0	22.82	22.77	22.37		1.0
DFT-s-OFDM 16QAM	1	1	22.88	22.68	22.42	0-1	1.0
CP-OFDM QPSK	1	1	22.57	22.33	22.20	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 101 of 207

Table H-199
NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.97	23.79	23.47	0	0.0
	1	26	23.91	23.81	23.45		0.0
	1	50	23.81	23.74	23.20		0.0
	25	0	22.91	22.75	22.44	0-1	1.0
	25	14	23.90	23.84	23.35	0	0.0
	25	27	22.85	22.81	22.22	0-1	1.0
	50	0	22.88	22.80	22.24		1.0
DFT-s-OFDM 16QAM	1	1	22.87	22.69	22.42	0-1	1.0
CP-OFDM QPSK	1	1	22.54	22.45	22.17	0-1.5	1.5

Table H-200
NR Band n25 Ant A Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.86	23.79	23.30	0	0.0
	1	13	23.86	23.78	23.34		0.0
	1	23	23.78	23.79	22.89		0.0
	12	0	22.84	22.74	22.39	0-1	1.0
	12	7	23.85	23.77	23.31	0	0.0
	12	13	22.83	22.69	22.10	0-1	1.0
	25	0	22.84	22.79	22.12		1.0
DFT-s-OFDM 16QAM	1	1	22.86	22.84	22.28	0-1	1.0
CP-OFDM QPSK	1	1	22.60	22.47	22.00	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 102 of 207

Table H-201

NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n25 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.93	0	0.0
	1	94	20.23		0.0
	1	186	20.06		0.0
	90	0	20.06	0-1	0.0
	90	49	20.23	0	0.0
	90	98	20.06	0-1	0.0
	180	0	20.05		0.0
DFT-s-OFDM 16QAM	1	1	19.99	0-1	0.0
CP-OFDM QPSK	1	1	20.18	0-1.5	0.0

Table H-202

NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.05	0	0.0
	1	80	20.09		0.0
	1	158	20.04		0.0
	80	0	20.02	0-1	0.0
	80	40	20.21	0	0.0
	80	80	20.05	0-1	0.0
	160	0	19.96		0.0
DFT-s-OFDM 16QAM	1	1	20.00	0-1	0.0
CP-OFDM QPSK	1	1	20.18	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 103 of 207

Table H-203

NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.27	0	0.0
	1	67	20.11		0.0
	1	131	20.00		0.0
	64	0	20.00	0-1	0.0
	64	35	20.11	0	0.0
	64	69	20.02	0-1	0.0
	128	0	20.04		0.0
DFT-s-OFDM 16QAM	1	1	20.18	0-1	0.0
CP-OFDM QPSK	1	1	20.35	0-1.5	0.0

Table H-204

NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.98	19.97	19.95	0	0.0
	1	53	19.93	19.99	19.95		0.0
	1	104	20.04	20.11	19.91		0.0
	50	0	19.81	20.02	19.91	0-1	0.0
	50	28	20.01	20.04	19.91	0	0.0
	50	56	19.83	19.96	19.81	0-1	0.0
	100	0	19.99	20.04	20.00		0.0
DFT-s-OFDM 16QAM	1	1	19.78	19.88	19.84	0-1	0.0
CP-OFDM QPSK	1	1	20.00	20.12	19.97	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 104 of 207

Table H-205

NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.86	20.02	20.08	0	0.0
	1	40	19.79	20.12	19.84		0.0
	1	77	19.85	19.97	19.84		0.0
	36	0	19.79	19.94	19.75	0-1	0.0
	36	22	19.98	20.09	20.00	0	0.0
	36	43	19.77	19.87	19.77	0-1	0.0
	75	0	19.79	19.99	19.76		0.0
DFT-s-OFDM 16QAM	1	1	19.92	19.95	19.88	0-1	0.0
CP-OFDM QPSK	1	1	20.10	20.26	20.07	0-1.5	0.0

Table H-206

NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.91	19.99	19.96	0	0.0
	1	26	19.95	19.90	19.66		0.0
	1	50	19.84	20.01	19.91		0.0
	25	0	19.88	19.98	19.82	0-1	0.0
	25	14	20.01	20.01	19.78	0	0.0
	25	27	19.86	19.98	19.67	0-1	0.0
	50	0	19.79	20.05	19.78		0.0
DFT-s-OFDM 16QAM	1	1	19.83	19.99	19.85	0-1	0.0
CP-OFDM QPSK	1	1	19.99	20.24	20.05	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 105 of 207

Table H-207

NR Band n25 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.84	19.99	19.69	0	0.0
	1	13	19.82	20.11	19.86		0.0
	1	23	19.84	20.19	19.77		0.0
	12	0	19.78	20.00	19.71	0-1	0.0
	12	7	19.86	20.05	19.84	0	0.0
	12	13	19.77	20.04	19.80	0-1	0.0
	25	0	19.77	20.06	19.72		0.0
DFT-s-OFDM 16QAM	1	1	19.94	20.04	19.64	0-1	0.0
CP-OFDM QPSK	1	1	20.10	20.28	19.81	0-1.5	0.0

Table H-208

NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n25 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.88	0	0.0
	1	94	18.19		0.0
	1	186	18.00		0.0
	90	0	18.03	0-1	0.0
	90	49	18.11	0	0.0
	90	98	18.01	0-1	0.0
	180	0	17.99		0.0
DFT-s-OFDM 16QAM	1	1	17.89	0-1	0.0
CP-OFDM QPSK	1	1	18.01	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 106 of 207

Table H-209
NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.00	0	0.0
	1	80	18.14		0.0
	1	158	18.06		0.0
	80	0	18.03	0-1	0.0
	80	40	18.18	0	0.0
	80	80	18.00	0-1	0.0
	160	0	17.91		0.0
DFT-s-OFDM 16QAM	1	1	17.91	0-1	0.0
CP-OFDM QPSK	1	1	18.07	0-1.5	0.0

Table H-210
NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.21	0	0.0
	1	67	18.13		0.0
	1	131	18.08		0.0
	64	0	17.97	0-1	0.0
	64	35	18.19	0	0.0
	64	69	18.06	0-1	0.0
	128	0	18.11		0.0
DFT-s-OFDM 16QAM	1	1	18.21	0-1	0.0
CP-OFDM QPSK	1	1	18.39	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 107 of 207

Table H-211
NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.93	18.00	17.93	0	0.0
	1	53	17.85	18.01	17.79		0.0
	1	104	18.05	18.04	17.90		0.0
	50	0	17.81	18.01	17.94	0-1	0.0
	50	28	17.87	18.02	17.73	0	0.0
	50	56	17.91	17.98	17.75	0-1	0.0
	100	0	17.97	18.01	17.90		0.0
DFT-s-OFDM 16QAM	1	1	17.88	17.90	17.77	0-1	0.0
CP-OFDM QPSK	1	1	18.08	18.11	18.04	0-1.5	0.0

Table H-212
NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.98	17.92	18.14	0	0.0
	1	40	17.88	17.87	17.98		0.0
	1	77	17.88	17.84	17.89		0.0
	36	0	17.81	18.00	17.83	0-1	0.0
	36	22	18.06	18.17	17.93	0	0.0
	36	43	17.83	18.02	17.71	0-1	0.0
	75	0	17.93	17.92	17.74		0.0
DFT-s-OFDM 16QAM	1	1	17.87	17.98	17.98	0-1	0.0
CP-OFDM QPSK	1	1	18.17	18.19	18.19	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 108 of 207

Table H-213
NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.99	18.10	17.77	0	0.0
	1	26	17.85	18.00	17.62		0.0
	1	50	17.79	18.11	17.81		0.0
	25	0	17.85	17.96	17.87	0-1	0.0
	25	14	17.86	18.11	17.72	0	0.0
	25	27	17.85	18.10	17.61	0-1	0.0
	50	0	17.82	18.07	17.67		0.0
DFT-s-OFDM 16QAM	1	1	17.90	18.12	17.87	0-1	0.0
CP-OFDM QPSK	1	1	18.06	18.30	18.11	0-1.5	0.0

Table H-214
NR Band n25 Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.88	18.08	17.56	0	0.0
	1	13	17.70	17.95	17.79		0.0
	1	23	17.90	18.13	17.72		0.0
	12	0	17.82	18.00	17.58	0-1	0.0
	12	7	17.89	18.06	17.77	0	0.0
	12	13	17.80	18.10	17.75	0-1	0.0
	25	0	17.80	17.95	17.72		0.0
DFT-s-OFDM 16QAM	1	1	17.92	17.98	17.61	0-1	0.0
CP-OFDM QPSK	1	1	18.14	18.21	17.79	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 109 of 207

H.2.4 NR Band n30

Table H-215
NR Band n30 Ant A Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			462000 (2310 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.87	0	0.0
	1	13	18.86		0.0
	1	23	18.80		0.0
	12	0	18.93	0-1	0.0
	12	7	19.00	0	0.0
	12	13	18.90	0-1	0.0
	25	0	18.92		0.0
DFT-s-OFDM 16QAM	1	1	18.96	0-1	0.0
CP-OFDM QPSK	1	1	19.08	0-1.5	0.0

Table H-216
NR Band n30 Ant A Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			462000 (2310 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	22.54	0	0.0
	1	13	22.69		0.0
	1	23	22.52		0.0
	12	0	21.59	0-1	1.0
	12	7	22.65	0	0.0
	12	13	21.51	0-1	1.0
	25	0	21.54		1.0
DFT-s-OFDM 16QAM	1	1	21.60	0-1	1.0
CP-OFDM QPSK	1	1	21.20	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 110 of 207

Table H-217
NR Band n30 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			462000 (2310 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.47	0	0.0
	1	13	17.58		0.0
	1	23	17.59		0.0
	12	0	17.47	0-1	0.0
	12	7	17.51	0	0.0
	12	13	17.53	0-1	0.0
	25	0	17.58		0.0
DFT-s-OFDM 16QAM	1	1	17.38	0-1	0.0
CP-OFDM QPSK	1	1	17.70	0-1.5	0.0

Table H-218
NR Band n30 Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			462000 (2310 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.01	0	0.0
	1	13	16.31		0.0
	1	23	16.23		0.0
	12	0	16.05	0-1	0.0
	12	7	16.17	0	0.0
	12	13	16.12	0-1	0.0
	25	0	16.08		0.0
DFT-s-OFDM 16QAM	1	1	15.92	0-1	0.0
CP-OFDM QPSK	1	1	16.21	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 111 of 207

H.2.5 NR Band n7

Table H-219

NR Band n7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n7 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.84	0	0.0
	1	108	18.72		0.0
	1	214	18.80		0.0
	108	0	18.78	0-1	0.0
	108	54	18.86	0	0.0
	108	108	18.74	0-1	0.0
	216	0	18.80		0.0
DFT-s-OFDM 16QAM	1	1	18.81	0-1	0.0
CP-OFDM QPSK	1	1	18.99	0-1.5	0.0

Table H-220

NR Band n7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n7 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.21	0	0.0
	1	94	19.14		0.0
	1	186	18.95		0.0
	90	0	19.21	0-1	0.0
	90	49	19.14	0	0.0
	90	98	19.08	0-1	0.0
	180	0	19.13		0.0
DFT-s-OFDM 16QAM	1	1	19.30	0-1	0.0
CP-OFDM QPSK	1	1	19.43	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 112 of 207

Table H-221
NR Band n7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n7 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.10	0	0.0
	1	80	18.95		0.0
	1	158	18.93		0.0
	80	0	19.00	0-1	0.0
	80	40	19.01	0	0.0
	80	80	18.88	0-1	0.0
	160	0	18.95		0.0
DFT-s-OFDM 16QAM	1	1	18.89	0-1	0.0
CP-OFDM QPSK	1	1	19.16	0-1.5	0.0

Table H-222
NR Band n7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n7 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.77	0	0.0
	1	67	18.71		0.0
	1	131	18.85		0.0
	64	0	18.87	0-1	0.0
	64	35	18.80	0	0.0
	64	69	18.75	0-1	0.0
	128	0	18.79		0.0
DFT-s-OFDM 16QAM	1	1	18.94	0-1	0.0
CP-OFDM QPSK	1	1	19.04	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 113 of 207

Table H

NR Band n7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n7 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502000 (2510 MHz)	507000 (2535 MHz)	512000 (2560 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.81	18.72	18.73	0	0.0
	1	53	18.83	18.60	18.72		0.0
	1	104	18.85	18.80	18.73		0.0
	50	0	18.95	18.77	18.77	0-1	0.0
	50	28	18.98	18.81	18.89	0	0.0
	50	56	18.97	18.77	18.86	0-1	0.0
	100	0	18.90	18.73	18.82		0.0
DFT-s-OFDM 16QAM	1	1	18.93	18.77	18.87	0-1	0.0
CP-OFDM QPSK	1	1	19.06	19.02	18.91	0-1.5	0.0

Table H-223

NR Band n7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n7 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501500 (2507.5 MHz)	507000 (2535 MHz)	512500 (2562.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.86	18.80	18.92	0	0.0
	1	40	18.88	18.68	18.78		0.0
	1	77	18.93	18.81	18.88		0.0
	36	0	18.90	18.78	18.98	0-1	0.0
	36	22	19.02	18.79	18.97	0	0.0
	36	43	18.95	18.75	18.93	0-1	0.0
	75	0	18.99	18.73	18.98		0.0
DFT-s-OFDM 16QAM	1	1	19.05	18.80	18.89	0-1	0.0
CP-OFDM QPSK	1	1	19.10	18.96	18.97	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 114 of 207

Table H-224

NR Band n7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n7 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501000 (2505 MHz)	507000 (2535 MHz)	513000 (2565 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.85	18.68	18.46	0	0.0
	1	26	18.80	18.61	18.47		0.0
	1	50	18.88	18.82	18.47		0.0
	25	0	18.93	18.73	18.63	0-1	0.0
	25	14	18.85	18.80	18.48	0	0.0
	25	27	18.86	18.76	18.57	0-1	0.0
	50	0	18.91	18.82	18.61		0.0
DFT-s-OFDM 16QAM	1	1	19.00	18.87	18.68	0-1	0.0
CP-OFDM QPSK	1	1	19.05	18.93	18.78	0-1.5	0.0

Table H-225

NR Band n7 Ant B Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n7 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500500 (2502.5 MHz)	507000 (2535 MHz)	513500 (2567.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.04	18.66	18.59	0	0.0
	1	13	19.08	18.71	18.65		0.0
	1	23	19.11	18.81	18.79		0.0
	12	0	19.09	18.78	18.66	0-1	0.0
	12	7	19.19	18.84	18.70	0	0.0
	12	13	19.06	18.86	18.77	0-1	0.0
	25	0	19.08	18.84	18.68		0.0
DFT-s-OFDM 16QAM	1	1	19.13	18.81	18.81	0-1	0.0
CP-OFDM QPSK	1	1	19.23	18.90	18.94	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 115 of 207

Table H-226
NR Band n7 Ant B Measured P_{Max} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n7 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	22.96	0	0.0
	1	108	22.84		0.0
	1	214	22.71		0.0
	108	0	21.91	0-1	1.0
	108	54	22.82	0	0.0
	108	108	21.84	0-1	1.0
	216	0	21.80		1.0
DFT-s-OFDM 16QAM	1	1	21.93	0-1	1.0
CP-OFDM QPSK	1	1	21.61	0-1.5	1.5

Table H-227
NR Band n7 Ant B Measured P_{Max} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n7 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.27	0	0.0
	1	94	23.22		0.0
	1	186	22.98		0.0
	90	0	22.38	0-1	1.0
	90	49	23.38	0	0.0
	90	98	22.37	0-1	1.0
	180	0	22.31		1.0
DFT-s-OFDM 16QAM	1	1	22.38	0-1	1.0
CP-OFDM QPSK	1	1	22.03	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 116 of 207

Table H-228
NR Band n7 Ant B Measured P_{Max} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n7 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.22	0	0.0
	1	80	23.07		0.0
	1	158	23.14		0.0
	80	0	22.13	0-1	1.0
	80	40	23.09	0	0.0
	80	80	22.02	0-1	1.0
	160	0	22.09		1.0
DFT-s-OFDM 16QAM	1	1	22.13	0-1	1.0
CP-OFDM QPSK	1	1	21.80	0-1.5	1.5

Table H-229
NR Band n7 Ant B Measured P_{Max} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n7 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	22.99	0	0.0
	1	67	22.95		0.0
	1	131	23.03		0.0
	64	0	22.11	0-1	1.0
	64	35	23.06	0	0.0
	64	69	22.09	0-1	1.0
	128	0	22.12		1.0
DFT-s-OFDM 16QAM	1	1	22.03	0-1	1.0
CP-OFDM QPSK	1	1	21.72	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 117 of 207

Table H-230
NR Band n7 Ant B Measured P_{Max} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n7 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502000 (2510 MHz)	507000 (2535 MHz)	512000 (2560 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	22.99	22.98	22.98	0	0.0
	1	53	23.06	22.88	22.97		0.0
	1	104	23.14	22.98	23.03		0.0
	50	0	22.21	22.01	21.98	0-1	1.0
	50	28	23.22	23.02	23.10	0	0.0
	50	56	22.25	21.99	22.08	0-1	1.0
	100	0	22.15	22.00	22.05		1.0
DFT-s-OFDM 16QAM	1	1	22.09	22.05	21.99	0-1	1.0
CP-OFDM QPSK	1	1	21.78	21.62	21.60	0-1.5	1.5

Table H-231
NR Band n7 Ant B Measured P_{Max} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n7 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501500 (2507.5 MHz)	507000 (2535 MHz)	512500 (2562.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.07	22.98	22.97	0	0.0
	1	40	23.13	22.91	22.93		0.0
	1	77	23.21	23.03	23.17		0.0
	36	0	22.18	21.95	22.11	0-1	1.0
	36	22	23.16	22.93	23.11	0	0.0
	36	43	22.13	21.93	22.11	0-1	1.0
	75	0	22.12	21.95	22.11		1.0
DFT-s-OFDM 16QAM	1	1	22.12	21.98	22.04	0-1	1.0
CP-OFDM QPSK	1	1	21.75	21.66	21.68	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 118 of 207

Table H-232
NR Band n7 Ant B Measured P_{Max} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n7 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501000 (2505 MHz)	507000 (2535 MHz)	513000 (2565 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.02	23.00	22.92	0	0.0
	1	26	23.00	22.98	22.95		0.0
	1	50	23.17	22.96	23.03		0.0
	25	0	22.13	22.05	21.95	0-1	1.0
	25	14	23.11	22.96	22.92	0	0.0
	25	27	22.19	22.01	21.98	0-1	1.0
	50	0	22.14	22.02	21.95		1.0
DFT-s-OFDM 16QAM	1	1	22.03	22.02	21.92	0-1	1.0
CP-OFDM QPSK	1	1	21.69	21.62	21.61	0-1.5	1.5

Table H-233
NR Band n7 Ant B Measured P_{Max} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n7 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500500 (2502.5 MHz)	507000 (2535 MHz)	513500 (2567.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.18	22.74	22.94	0	0.0
	1	13	23.24	22.70	22.95		0.0
	1	23	23.38	22.76	22.90		0.0
	12	0	22.33	21.79	21.90	0-1	1.0
	12	7	23.20	22.80	22.89	0	0.0
	12	13	22.29	21.87	21.95	0-1	1.0
	25	0	22.24	21.85	21.94		1.0
DFT-s-OFDM 16QAM	1	1	22.25	21.92	21.92	0-1	1.0
CP-OFDM QPSK	1	1	21.45	21.54	21.59	0-1.5	1.5

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 119 of 207

Table H-234
NR Band n7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n7 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.24	0	0.0
	1	108	17.01		0.0
	1	214	17.00		0.0
	108	0	17.09	0-1	0.0
	108	54	17.20	0	0.0
	108	108	17.07	0-1	0.0
	216	0	17.27		0.0
DFT-s-OFDM 16QAM	1	1	17.35	0-1	0.0
CP-OFDM QPSK	1	1	17.16	0-1.5	0.0

Table H-235
NR Band n7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n7 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.72	0	0.0
	1	108	15.46		0.0
	1	214	15.53		0.0
	108	0	15.65	0-1	0.0
	108	54	15.59	0	0.0
	108	108	15.53	0-1	0.0
	216	0	15.66		0.0
DFT-s-OFDM 16QAM	1	1	16.14	0-1	0.0
CP-OFDM QPSK	1	1	15.61	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 120 of 207

Table H-236

NR Band n7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n7 30 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.11	0	0.0
	1	80	17.08		0.0
	1	158	17.02		0.0
	80	0	17.05	0-1	0.0
	80	40	17.06	0	0.0
	80	80	17.03	0-1	0.0
	160	0	17.09		0.0
DFT-s-OFDM 16QAM	1	1	17.03	0-1	0.0
CP-OFDM QPSK	1	1	17.33	0-1.5	0.0

Table H-237

NR Band n7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n7 25 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.16	0	0.0
	1	67	17.08		0.0
	1	131	17.00		0.0
	64	0	16.95	0-1	0.0
	64	35	17.06	0	0.0
	64	69	16.95	0-1	0.0
	128	0	17.00		0.0
DFT-s-OFDM 16QAM	1	1	16.93	0-1	0.0
CP-OFDM QPSK	1	1	17.30	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 121 of 207

Table H-238

NR Band n7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n7 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502000 (2510 MHz)	507000 (2535 MHz)	512000 (2560 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.34	17.08	17.03	0	0.0
	1	53	17.30	17.04	17.00		0.0
	1	104	17.24	17.03	16.71		0.0
	50	0	17.31	17.08	16.93	0-1	0.0
	50	28	17.36	17.06	17.02	0	0.0
	50	56	17.11	16.93	16.76	0-1	0.0
	100	0	17.29	16.94	17.02		0.0
DFT-s-OFDM 16QAM	1	1	17.30	16.95	16.92	0-1	0.0
CP-OFDM QPSK	1	1	17.44	17.17	17.01	0-1.5	0.0

Table H-239

NR Band n7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n7 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501500 (2507.5 MHz)	507000 (2535 MHz)	512500 (2562.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.34	17.17	17.06	0	0.0
	1	40	17.28	17.15	16.94		0.0
	1	77	17.25	17.11	16.94		0.0
	36	0	17.22	16.93	16.92	0-1	0.0
	36	22	17.34	17.14	17.04	0	0.0
	36	43	17.13	17.05	16.90	0-1	0.0
	75	0	17.17	17.03	16.82		0.0
DFT-s-OFDM 16QAM	1	1	17.24	17.03	16.85	0-1	0.0
CP-OFDM QPSK	1	1	17.48	17.24	17.04	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 122 of 207

Table H-240

NR Band n7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n7 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501000 (2505 MHz)	507000 (2535 MHz)	513000 (2565 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.54	17.13	17.11	0	0.0
	1	26	17.32	17.09	16.62		0.0
	1	50	17.25	17.10	16.74		0.0
	25	0	17.22	17.00	16.80	0-1	0.0
	25	14	17.26	17.14	16.80	0	0.0
	25	27	17.18	17.04	16.60	0-1	0.0
	50	0	17.24	17.04	16.67		0.0
DFT-s-OFDM 16QAM	1	1	17.27	17.00	16.68	0-1	0.0
CP-OFDM QPSK	1	1	17.55	17.26	16.94	0-1.5	0.0

Table H-241

NR Band n7 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 5 MHz Bandwidth

NR Band n7 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500500 (2502.5 MHz)	507000 (2535 MHz)	513500 (2567.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.27	16.94	16.78	0	0.0
	1	13	17.47	17.09	16.88		0.0
	1	23	17.35	17.08	16.78		0.0
	12	0	17.29	16.94	16.71	0-1	0.0
	12	7	17.44	17.05	16.80	0	0.0
	12	13	17.37	17.02	16.69	0-1	0.0
	25	0	17.32	16.93	16.80		0.0
DFT-s-OFDM 16QAM	1	1	17.30	16.88	16.75	0-1	0.0
CP-OFDM QPSK	1	1	17.52	17.12	16.99	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 123 of 207

Table H-242
NR Band n7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n7 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.72	0	0.0
	1	108	15.46		0.0
	1	214	15.53		0.0
	108	0	15.65	0-1	0.0
	108	54	15.59	0	0.0
	108	108	15.53	0-1	0.0
	216	0	15.66		0.0
DFT-s-OFDM 16QAM	1	1	16.14	0-1	0.0
CP-OFDM QPSK	1	1	15.61	0-1.5	0.0

Table H-243
NR Band n7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n7 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.53	0	0.0
	1	94	15.62		0.0
	1	186	15.47		0.0
	90	0	15.60	0-1	0.0
	90	49	15.69	0	0.0
	90	98	15.53	0-1	0.0
	180	0	15.55		0.0
DFT-s-OFDM 16QAM	1	1	16.06	0-1	0.0
CP-OFDM QPSK	1	1	15.69	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 124 of 207

Table H-244
NR Band n7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n7 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.98	0	0.0
	1	80	15.75		0.0
	1	158	15.82		0.0
	80	0	15.82	0-1	0.0
	80	40	15.81	0	0.0
	80	80	15.87	0-1	0.0
	160	0	15.81		0.0
DFT-s-OFDM 16QAM	1	1	15.66	0-1	0.0
CP-OFDM QPSK	1	1	16.02	0-1.5	0.0

Table H-245
NR Band n7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n7 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.90	0	0.0
	1	67	15.95		0.0
	1	131	15.87		0.0
	64	0	15.84	0-1	0.0
	64	35	15.92	0	0.0
	64	69	15.77	0-1	0.0
	128	0	15.79		0.0
DFT-s-OFDM 16QAM	1	1	15.73	0-1	0.0
CP-OFDM QPSK	1	1	15.96	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 125 of 207

Table H-246
NR Band n7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n7 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502000 (2510 MHz)	507000 (2535 MHz)	512000 (2560 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	15.95	15.83	15.73	0	0.0
	1	53	15.90	15.85	15.80		0.0
	1	104	15.80	15.76	15.69		0.0
	50	0	15.82	15.68	15.67	0-1	0.0
	50	28	15.88	15.84	15.74	0	0.0
	50	56	15.76	15.81	15.67	0-1	0.0
	100	0	15.88	15.90	15.69		0.0
DFT-s-OFDM 16QAM	1	1	15.73	15.64	15.60	0-1	0.0
CP-OFDM QPSK	1	1	16.07	15.85	16.02	0-1.5	0.0

Table H-247
NR Band n7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n7 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501500 (2507.5 MHz)	507000 (2535 MHz)	512500 (2562.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	15.93	15.69	15.73	0	0.0
	1	40	15.73	15.67	15.74		0.0
	1	77	15.82	15.66	15.74		0.0
	36	0	15.68	15.77	15.71	0-1	0.0
	36	22	15.89	15.76	15.84	0	0.0
	36	43	15.75	15.69	15.70	0-1	0.0
	75	0	15.71	15.77	15.74		0.0
DFT-s-OFDM 16QAM	1	1	15.68	15.62	15.64	0-1	0.0
CP-OFDM QPSK	1	1	15.95	15.92	15.95	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 126 of 207

Table H-248
NR Band n7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n7 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501000 (2505 MHz)	507000 (2535 MHz)	513000 (2565 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	15.88	15.76	15.70	0	0.0
	1	26	15.79	15.81	15.61		0.0
	1	50	15.79	15.74	15.61		0.0
	25	0	15.73	15.78	15.56	0-1	0.0
	25	14	15.85	15.78	15.58	0	0.0
	25	27	15.71	15.83	15.54	0-1	0.0
	50	0	15.83	15.83	15.53		0.0
DFT-s-OFDM 16QAM	1	1	15.77	15.73	15.58	0-1	0.0
CP-OFDM QPSK	1	1	15.90	16.02	15.75	0-1.5	0.0

Table H-249
NR Band n7 Ant F Measured P_{Limit} for DSI = 1 (Head) - 5 MHz Bandwidth

NR Band n7 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500500 (2502.5 MHz)	507000 (2535 MHz)	513500 (2567.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	15.87	15.80	15.63	0	0.0
	1	13	16.06	15.78	15.75		0.0
	1	23	15.91	15.79	15.69		0.0
	12	0	15.92	15.72	15.62	0-1	0.0
	12	7	16.03	15.77	15.64	0	0.0
	12	13	15.95	15.83	15.58	0-1	0.0
	25	0	15.96	15.77	15.57		0.0
DFT-s-OFDM 16QAM	1	1	15.88	15.74	15.53	0-1	0.0
CP-OFDM QPSK	1	1	16.11	15.99	15.81	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 127 of 207

H.2.6 NR Band n41

Table H-250

NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	508200 (2541 MHz)	528996 (2644.98 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.49	17.48	0	0.0
	1	123	17.28	17.05		0.0
	1	243	17.47	17.17		0.0
	120	0	17.30	17.10	0-1	0.0
	120	63	17.24	17.02	0	0.0
	120	125	17.24	16.94	0-1	0.0
	243	0	17.17	17.18		0.0
DFT-s-OFDM 16QAM	1	1	17.46	17.41	0-1	0.0
CP-OFDM QPSK	1	1	17.41	17.43	0-1.5	0.0

Table H-251

NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.47	17.43	0	0.0
	1	109	17.09	16.95		0.0
	1	215	17.25	17.09		0.0
	108	0	17.33	17.11	0-1	0.0
	108	55	17.31	17.12	0	0.0
	108	109	17.28	17.06	0-1	0.0
	216	0	17.29	17.25		0.0
DFT-s-OFDM 16QAM	1	1	17.41	17.30	0-1	0.0
CP-OFDM QPSK	1	1	17.48	17.41	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 128 of 207

Table H-252
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.49	17.16	0	0.0
	1	95	17.32	17.03		0.0
	1	187	17.38	17.04		0.0
	90	0	17.49	17.16	0-1	0.0
	90	50	17.32	17.12	0	0.0
	90	99	17.31	17.06	0-1	0.0
	180	0	17.38	17.08		0.0
DFT-s-OFDM 16QAM	1	1	17.46	17.28	0-1	0.0
CP-OFDM QPSK	1	1	17.46	17.34	0-1.5	0.0

Table H-253
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.46	17.34	17.14	0	0.0
	1	81	17.23	17.16	16.88		0.0
	1	160	17.33	17.30	17.02		0.0
	81	0	17.30	17.26	16.95	0-1	0.0
	81	41	17.37	17.33	17.08	0	0.0
	81	81	17.20	17.22	16.91	0-1	0.0
	162	0	17.40	17.36	17.16		0.0
DFT-s-OFDM 16QAM	1	1	17.49	17.34	17.06	0-1	0.0
CP-OFDM QPSK	1	1	17.46	17.38	17.21	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 129 of 207

Table H-254
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.46	17.47	17.29	0	0.0
	1	67	17.36	17.38	17.13		0.0
	1	131	17.37	17.42	17.21		0.0
	64	0	17.42	17.47	17.19	0-1	0.0
	64	35	17.43	17.50	17.27	0	0.0
	64	69	17.39	17.41	17.12	0-1	0.0
	128	0	17.49	17.50	17.19		0.0
DFT-s-OFDM 16QAM	1	1	17.47	17.43	17.19	0-1	0.0
CP-OFDM QPSK	1	1	17.50	17.49	17.31	0-1.5	0.0

Table H-255
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.47	17.22	17.34	17.34	0	0.0
	1	60	17.13	17.06	17.21	17.08		0.0
	1	117	17.20	17.36	17.38	17.06		0.0
	54	0	17.32	17.21	17.29	17.17	0-1	0.0
	54	27	17.25	17.13	17.24	17.20	0	0.0
	54	54	17.22	17.14	17.23	17.10	0-1	0.0
	108	0	17.33	17.20	17.32	17.20		0.0
DFT-s-OFDM 16QAM	1	1	17.45	17.17	17.42	17.36	0-1	0.0
CP-OFDM QPSK	1	1	17.49	17.32	17.45	17.44	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 130 of 207

Table H-256
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.48	17.16	17.13	17.03	0	0.0
	1	53	17.33	17.22	17.06	17.03		0.0
	1	104	17.13	17.29	16.91	17.09		0.0
	50	0	17.40	17.20	17.17	16.98	0-1	0.0
	50	28	17.35	17.31	17.18	17.20	0	0.0
	50	56	17.26	17.25	16.98	17.08	0-1	0.0
	100	0	17.40	17.28	17.25	17.13		0.0
DFT-s-OFDM 16QAM	1	1	17.49	17.11	17.23	16.94	0-1	0.0
CP-OFDM QPSK	1	1	17.45	17.16	17.30	17.10	0-1.5	0.0

Table H-257
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.44	17.24	17.19	17.20	17.07	0	0.0
	1	46	17.35	17.35	17.31	17.21	17.05		0.0
	1	90	17.21	17.29	17.33	17.10	16.90		0.0
	45	0	17.42	17.28	17.28	17.15	17.05	0-1	0.0
	45	22	17.37	17.36	17.38	17.28	17.08	0	0.0
	45	45	17.24	17.32	17.28	17.20	17.00	0-1	0.0
	90	0	17.37	17.29	17.33	17.22	17.04		0.0
DFT-s-OFDM 16QAM	1	1	17.40	17.36	17.31	17.25	17.14	0-1	0.0
CP-OFDM QPSK	1	1	17.45	17.48	17.36	17.36	17.26	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 131 of 207

Table H-266
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.50	17.47	17.22	17.17	17.15	0	0.0
	1	39	17.43	17.45	17.29	17.05	17.05		0.0
	1	76	17.46	17.46	17.27	16.96	17.14		0.0
	36	0	17.43	17.32	17.21	17.02	17.06	0-1	0.0
	36	21	17.46	17.43	17.21	17.02	17.08	0	0.0
	36	42	17.43	17.37	17.17	16.92	16.98	0-1	0.0
	75	0	17.45	17.39	17.26	17.05	16.95		0.0
DFT-s-OFDM 16QAM	1	1	17.47	17.39	17.32	17.23	17.09	0-1	0.0
CP-OFDM QPSK	1	1	17.50	17.43	17.50	17.37	17.21	0-1.5	0.0

Table H-258
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.47	17.21	17.29	17.00	16.99	0	0.0
	1	26	17.39	17.14	17.31	17.07	17.03		0.0
	1	49	17.30	17.15	17.23	16.99	16.94		0.0
	25	0	17.40	17.13	17.22	16.94	16.99	0-1	0.0
	25	13	17.31	17.25	17.34	17.01	17.12	0	0.0
	25	26	17.24	17.12	17.19	16.93	16.94	0-1	0.0
	50	0	17.39	17.27	17.33	17.06	17.10		0.0
DFT-s-OFDM 16QAM	1	1	17.44	17.08	17.32	17.08	17.10	0-1	0.0
CP-OFDM QPSK	1	1	17.44	17.27	17.36	17.12	17.14	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 132 of 207

Table H-259
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.46	17.28	17.38	17.13	17.07	0	0.0
	1	12	17.50	17.25	17.34	17.08	17.06		0.0
	1	22	17.50	17.33	17.35	17.10	17.11		0.0
	12	0	17.50	17.11	17.13	17.02	16.89	0-1	0.0
	12	6	17.45	17.24	17.26	17.08	16.98	0	0.0
	12	12	17.45	17.17	17.18	17.01	16.95	0-1	0.0
	24	0	17.50	17.18	17.22	17.04	16.96		0.0
DFT-s-OFDM 16QAM	1	1	17.42	17.24	17.32	17.01	17.05	0-1	0.0
CP-OFDM QPSK	1	1	17.49	17.39	17.44	17.09	17.07	0-1.5	0.0

Table H-260
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	508200 (2541 MHz)	528996 (2644.98 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	14.49	14.36	0	0.0
	1	123	14.14	13.94		0.0
	1	243	14.41	14.00		0.0
	120	0	14.20	14.06	0-1	0.0
	120	63	14.22	13.90	0	0.0
	120	125	14.15	13.94	0-1	0.0
	243	0	14.30	14.10		0.0
DFT-s-OFDM 16QAM	1	1	14.42	14.38	0-1	0.0
CP-OFDM QPSK	1	1	14.47	14.43	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 133 of 207

Table H-261
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	14.42	14.31	0	0.0
	1	109	14.21	13.99		0.0
	1	215	14.43	14.07		0.0
	108	0	14.29	14.14	0-1	0.0
	108	55	14.29	14.01	0	0.0
	108	109	14.28	13.97	0-1	0.0
	216	0	14.40	14.14		0.0
DFT-s-OFDM 16QAM	1	1	14.45	14.38	0-1	0.0
CP-OFDM QPSK	1	1	14.44	14.49	0-1.5	0.0

Table H-262
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	14.50	14.13	0	0.0
	1	95	14.31	14.03		0.0
	1	187	14.42	14.04		0.0
	90	0	14.43	14.09	0-1	0.0
	90	50	14.41	14.12	0	0.0
	90	99	14.35	14.02	0-1	0.0
	180	0	14.36	14.12		0.0
DFT-s-OFDM 16QAM	1	1	14.50	14.18	0-1	0.0
CP-OFDM QPSK	1	1	14.47	14.32	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 134 of 207

Table H-263
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	14.48	14.36	14.14	0	0.0
	1	81	14.12	14.20	13.90		0.0
	1	160	14.30	14.23	14.07		0.0
	81	0	14.41	14.29	13.91	0-1	0.0
	81	41	14.23	14.40	14.06	0	0.0
	81	81	14.14	14.22	13.89	0-1	0.0
	162	0	14.32	14.38	14.05		0.0
DFT-s-OFDM 16QAM	1	1	14.47	14.25	14.08	0-1	0.0
CP-OFDM QPSK	1	1	14.41	14.41	14.16	0-1.5	0.0

Table H-264
NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	14.50	14.47	14.07	0	0.0
	1	67	14.30	14.33	14.07		0.0
	1	131	14.39	14.41	14.25		0.0
	64	0	14.47	14.36	14.07	0-1	0.0
	64	35	14.48	14.45	14.22	0	0.0
	64	69	14.23	14.39	14.10	0-1	0.0
	128	0	14.42	14.37	14.06		0.0
DFT-s-OFDM 16QAM	1	1	14.43	14.44	14.11	0-1	0.0
CP-OFDM QPSK	1	1	14.48	14.46	14.25	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 135 of 207

Table H-265

NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	14.43	14.20	14.40	14.10	0	0.0
	1	60	14.20	14.13	14.21	14.04		0.0
	1	117	14.23	14.21	14.37	14.00		0.0
	54	0	14.44	14.16	14.33	14.14	0-1	0.0
	54	27	14.27	14.15	14.28	14.03	0	0.0
	54	54	14.18	14.21	14.29	13.95	0-1	0.0
	108	0	14.29	14.20	14.30	14.14		0.0
DFT-s-OFDM 16QAM	1	1	14.40	14.16	14.33	14.31	0-1	0.0
CP-OFDM QPSK	1	1	14.45	14.24	14.45	14.48	0-1.5	0.0

Table H-266

NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	14.42	14.14	14.32	14.05	0	0.0
	1	53	14.20	14.20	14.18	14.02		0.0
	1	104	14.08	14.30	14.14	14.08		0.0
	50	0	14.43	14.12	14.24	14.02	0-1	0.0
	50	28	14.36	14.27	14.26	14.01	0	0.0
	50	56	14.13	14.21	14.05	14.03	0-1	0.0
	100	0	14.42	14.28	14.28	14.16		0.0
DFT-s-OFDM 16QAM	1	1	14.44	14.10	14.18	13.91	0-1	0.0
CP-OFDM QPSK	1	1	14.41	14.19	14.23	14.02	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 136 of 207

Table H-267

NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	14.48	14.00	14.34	14.20	14.19	0	0.0
	1	46	14.35	14.17	14.30	14.25	14.18		0.0
	1	90	14.18	14.02	14.26	14.12	13.98		0.0
	45	0	14.40	14.03	14.31	14.17	14.22	0-1	0.0
	45	22	14.34	14.16	14.30	14.14	14.14	0	0.0
	45	45	14.23	14.12	14.25	14.24	14.00	0-1	0.0
	90	0	14.31	14.33	14.27	14.15	14.10		0.0
DFT-s-OFDM 16QAM	1	1	14.44	14.22	14.25	14.24	14.18	0-1	0.0
CP-OFDM QPSK	1	1	14.49	14.36	14.35	14.36	14.22	0-1.5	0.0

Table H-279

NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	14.45	14.38	14.41	14.35	13.93	0	0.0
	1	39	14.33	14.44	14.33	14.12	14.06		0.0
	1	76	14.36	14.47	14.32	14.03	14.10		0.0
	36	0	14.41	14.25	14.25	14.12	13.99	0-1	0.0
	36	21	14.44	14.35	14.18	14.08	14.00	0	0.0
	36	42	14.23	14.30	14.18	13.94	13.91	0-1	0.0
	75	0	14.33	14.27	14.20	14.01	13.98		0.0
DFT-s-OFDM 16QAM	1	1	14.45	14.36	14.29	14.29	14.00	0-1	0.0
CP-OFDM QPSK	1	1	14.46	14.44	14.34	14.42	14.08	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 137 of 207

Table H-268

NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	14.47	14.15	14.35	14.11	14.03	0	0.0
	1	26	14.46	14.25	14.37	14.14	14.04		0.0
	1	49	14.36	14.22	14.29	14.02	13.95		0.0
	25	0	14.36	14.07	14.28	14.01	13.91	0-1	0.0
	25	13	14.42	14.17	14.32	14.09	14.00	0	0.0
	25	26	14.30	14.06	14.20	13.94	13.92	0-1	0.0
	50	0	14.46	14.08	14.30	14.08	14.05		0.0
DFT-s-OFDM 16QAM	1	1	14.44	14.08	14.24	14.04	13.92	0-1	0.0
CP-OFDM QPSK	1	1	14.42	14.20	14.34	14.09	14.11	0-1.5	0.0

Table H-269

NR Band n41 PC2 Antenna F Path 1 Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	14.44	14.32	14.36	14.16	13.95	0	0.0
	1	12	14.43	14.32	14.34	14.17	14.00		0.0
	1	22	14.43	14.36	14.37	14.19	14.08		0.0
	12	0	14.34	14.22	14.17	14.07	13.96	0-1	0.0
	12	6	14.46	14.33	14.28	14.10	14.05	0	0.0
	12	12	14.31	14.22	14.22	14.02	13.92	0-1	0.0
	24	0	14.34	14.18	14.22	14.04	14.00		0.0
DFT-s-OFDM 16QAM	1	1	14.49	14.23	14.30	14.05	13.98	0-1	0.0
CP-OFDM QPSK	1	1	14.46	14.30	14.42	14.25	14.00	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 138 of 207

Table H-270

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth		
Channel		
Antenna	508200 (2541 MHz)	528996 (2644.98 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	19.94	19.52
SRS #3 Ant E	18.47	18.18
SRS #4 Ant D	16.25	15.79

Table H-271

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth		
Channel		
Antenna	507204 (2536.02 MHz)	529998 (2649.99 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	19.94	19.63
SRS #3 Ant E	18.46	18.20
SRS #4 Ant D	16.41	15.97

Table H-272

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth		
Channel		
Antenna	506202 (2531.01 MHz)	531000 (2655 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	19.96	19.61
SRS #3 Ant E	18.47	18.25
SRS #4 Ant D	16.19	16.06

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 139 of 207

Table H-273

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth			
Channel			
Antenna	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)
	Conducted Power [dBm]		
SRS #2 Ant B	19.93	19.50	19.75
SRS #3 Ant E	18.46	18.34	18.30
SRS #4 Ant D	16.40	15.52	16.27

Table H-274

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth			
Channel			
Antenna	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)
	Conducted Power [dBm]		
SRS #2 Ant B	19.91	19.71	19.88
SRS #3 Ant E	18.49	18.40	18.36
SRS #4 Ant D	16.49	15.54	16.29

Table H-275

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth				
Channel				
Antenna	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)
	Conducted Power [dBm]			
SRS #2 Ant B	19.87	19.48	19.11	19.49
SRS #3 Ant E	18.49	18.41	18.31	18.40
SRS #4 Ant D	16.47	16.23	16.05	16.03

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 140 of 207

Table H-276

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth				
Channel				
Antenna	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)
	Conducted Power [dBm]			
SRS #2 Ant B	19.94	19.90	19.46	19.82
SRS #3 Ant E	18.45	18.47	18.25	18.31
SRS #4 Ant D	16.44	15.80	15.47	15.33

Table H-277

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth					
Channel					
Antenna	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.97	19.82	19.55	19.34	19.51
SRS #3 Ant E	18.45	18.39	18.33	18.26	18.32
SRS #4 Ant D	16.49	16.45	15.74	15.93	15.71

Table H-292

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth					
Channel					
Antenna	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.90	19.87	19.57	19.50	19.81
SRS #3 Ant E	18.15	18.47	18.34	18.16	18.25
SRS #4 Ant D	16.42	16.21	15.32	15.78	15.33

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 141 of 207

Table H-278
NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth					
Channel					
Antenna	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.98	19.83	19.64	19.52	19.81
SRS #3 Ant E	18.47	18.41	18.29	17.99	18.03
SRS #4 Ant D	16.43	16.19	15.17	15.60	15.35

Table H-279
NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth					
Channel					
Antenna	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.94	19.86	19.60	19.45	19.70
SRS #3 Ant E	18.49	18.36	18.32	18.03	18.24
SRS #4 Ant D	16.47	16.09	15.39	15.48	15.46

Table H-280
NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth					
Channel					
Antenna	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.95	19.84	19.59	19.46	19.78
SRS #3 Ant E	18.49	18.40	18.26	18.02	18.29
SRS #4 Ant D	16.44	16.20	15.36	15.66	15.30

Table H-281

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 142 of 207

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth					
Channel					
Antenna	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.94	19.97	19.74	19.52	19.75
SRS #3 Ant E	18.39	18.20	18.10	17.80	17.85
SRS #4 Ant D	16.41	16.28	15.51	15.61	15.36

Table H-282

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth		
Channel		
Antenna	508200 (2541 MHz)	528996 (2644.98 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	18.49	17.96
SRS #3 Ant E	16.91	16.65
SRS #4 Ant D	14.86	14.47

Table H-283

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth		
Channel		
Antenna	507204 (2536.02 MHz)	529998 (2649.99 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	18.47	18.07
SRS #3 Ant E	16.96	16.73
SRS #4 Ant D	14.88	14.37

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 143 of 207

Table H-284
NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth		
Channel		
Antenna	506202 (2531.01 MHz)	531000 (2655 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	18.47	18.08
SRS #3 Ant E	16.92	16.58
SRS #4 Ant D	14.79	14.46

Table H-285
NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth			
Channel			
Antenna	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)
	Conducted Power [dBm]		
SRS #2 Ant B	18.44	17.94	18.29
SRS #3 Ant E	16.95	16.81	16.75
SRS #4 Ant D	14.88	14.05	14.84

Table H-286
NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth			
Channel			
Antenna	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)
	Conducted Power [dBm]		
SRS #2 Ant B	18.47	18.24	18.32
SRS #3 Ant E	16.99	16.93	16.81
SRS #4 Ant D	15.00	14.10	14.95

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 144 of 207

Table H-287

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth				
Channel				
Antenna	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)
	Conducted Power [dBm]			
SRS #2 Ant B	18.37	18.00	17.67	17.91
SRS #3 Ant E	16.96	16.92	16.87	16.96
SRS #4 Ant D	14.92	14.71	14.55	14.40

Table H-288

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth				
Channel				
Antenna	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)
	Conducted Power [dBm]			
SRS #2 Ant B	18.44	18.39	17.97	18.34
SRS #3 Ant E	16.91	16.91	16.81	16.79
SRS #4 Ant D	14.99	14.25	13.93	14.88

Table H-289

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth					
Channel					
Antenna	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	18.49	18.41	18.05	17.86	18.35
SRS #3 Ant E	16.94	16.91	16.84	16.88	16.81
SRS #4 Ant D	14.98	14.92	14.27	14.36	14.49

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 145 of 207

Table H-290
NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth					
Channel					
Antenna	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	18.48	18.42	18.10	17.91	18.32
SRS #3 Ant E	17.00	16.92	16.87	16.58	16.72
SRS #4 Ant D	14.91	14.68	14.12	14.24	14.73

Table H-291
NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth					
Channel					
Antenna	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	18.42	18.33	18.10	17.99	18.35
SRS #3 Ant E	16.98	16.93	16.73	16.49	16.65
SRS #4 Ant D	14.98	14.68	14.04	14.14	14.84

Table H-292
NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth					
Channel					
Antenna	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	18.43	18.33	18.15	17.94	18.29
SRS #3 Ant E	16.96	16.79	16.82	16.56	16.74
SRS #4 Ant D	14.95	14.49	13.86	13.92	14.81

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 146 of 207

Table H-293

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth					
Channel					
Antenna	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	18.48	18.32	18.10	17.95	18.12
SRS #3 Ant E	16.98	16.85	16.79	16.61	16.75
SRS #4 Ant D	14.91	14.64	13.94	14.11	14.83

Table H-294

NR Band n41 PC2 Antenna B, E, D Path 1 Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth					
Channel					
Antenna	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	18.48	18.36	18.24	18.02	18.31
SRS #3 Ant E	16.91	16.71	16.58	16.45	16.48
SRS #4 Ant D	14.93	14.75	13.95	14.14	14.83

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 147 of 207

Table H-295
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	508200 (2541 MHz)	528996 (2644.98 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	20.94	20.83	0	0.0
	1	123	20.75	20.64		0.0
	1	243	20.81	20.43		0.0
	120	0	20.83	20.84	0-1	0.0
	120	63	20.73	20.58	0	0.0
	120	125	20.74	20.60	0-1	0.0
	243	0	20.81	20.70		0.0
DFT-s-OFDM 16QAM	1	1	20.77	20.81	0-1	0.0
CP-OFDM QPSK	1	1	20.41	20.85	0-1.5	0.0

Table H-296
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	20.68	20.88	0	0.0
	1	109	20.33	20.42		0.0
	1	215	20.57	20.20		0.0
	108	0	20.65	20.66	0-1	0.0
	108	55	20.56	20.55	0	0.0
	108	109	20.56	20.41	0-1	0.0
	216	0	20.61	20.58		0.0
DFT-s-OFDM 16QAM	1	1	20.88	20.98	0-1	0.0
CP-OFDM QPSK	1	1	20.46	20.95	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 148 of 207

Table H-297
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	20.84	20.86	0	0.0
	1	95	20.41	20.46		0.0
	1	187	20.55	20.29		0.0
	90	0	20.49	20.63	0-1	0.0
	90	50	20.53	20.59	0	0.0
	90	99	20.50	20.45	0-1	0.0
	180	0	20.36	20.62		0.0
DFT-s-OFDM 16QAM	1	1	20.39	20.88	0-1	0.0
CP-OFDM QPSK	1	1	20.09	20.96	0-1.5	0.0

Table H-298
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.93	20.77	20.87	0	0.0
	1	81	20.60	20.84	20.43		0.0
	1	160	20.73	20.89	20.49		0.0
	81	0	20.68	20.80	20.56	0-1	0.0
	81	41	20.65	20.86	20.55	0	0.0
	81	81	20.59	20.85	20.42	0-1	0.0
	162	0	20.62	20.87	20.65		0.0
DFT-s-OFDM 16QAM	1	1	20.91	20.66	20.67	0-1	0.0
CP-OFDM QPSK	1	1	20.74	20.75	20.73	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 149 of 207

Table H-299
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.77	20.67	20.63	0	0.0
	1	67	20.54	20.83	20.44		0.0
	1	131	20.61	20.83	20.43		0.0
	64	0	20.66	20.79	20.56	0-1	0.0
	64	35	20.70	20.97	20.64	0	0.0
	64	69	20.59	20.89	20.43	0-1	0.0
	128	0	20.67	20.91	20.61		0.0
DFT-s-OFDM 16QAM	1	1	20.91	20.81	20.74	0-1	0.0
CP-OFDM QPSK	1	1	20.84	20.87	20.80	0-1.5	0.0

Table H-300
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	20.85	20.44	20.56	20.42	0	0.0
	1	60	20.78	20.47	20.43	20.32		0.0
	1	117	20.74	20.62	20.25	20.20		0.0
	54	0	20.82	20.44	20.52	20.46	0-1	0.0
	54	27	20.81	20.31	20.35	20.30	0	0.0
	54	54	20.83	20.49	20.40	20.35	0-1	0.0
	108	0	20.85	20.43	20.50	20.42		0.0
DFT-s-OFDM 16QAM	1	1	20.78	20.35	20.49	20.51	0-1	0.0
CP-OFDM QPSK	1	1	20.83	20.45	20.54	20.59	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 150 of 207

Table H-301
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
Conducted Power [dBm]								
DFT-s-OFDM QPSK	1	1	20.88	20.62	20.92	20.46	0	0.0
	1	53	20.78	20.76	20.94	20.42		0.0
	1	104	20.66	20.85	20.70	20.33		0.0
	50	0	20.90	20.81	20.99	20.55	0-1	0.0
	50	28	20.83	20.83	20.94	20.50	0	0.0
	50	56	20.80	20.89	20.88	20.45	0-1	0.0
	100	0	20.85	20.84	20.90	20.49		0.0
DFT-s-OFDM 16QAM	1	1	20.73	20.69	20.97	20.54	0-1	0.0
CP-OFDM QPSK	1	1	20.51	20.74	20.92	20.55	0-1.5	0.0

Table H-302
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.90	20.63	20.53	20.52	20.48	0	0.0
	1	46	20.88	20.62	20.69	20.46	20.19		0.0
	1	90	20.64	20.50	20.67	20.29	20.18		0.0
	45	0	20.92	20.53	20.65	20.53	20.40	0-1	0.0
	45	22	20.84	20.54	20.56	20.50	20.15	0	0.0
	45	45	20.75	20.57	20.66	20.38	20.30	0-1	0.0
	90	0	20.78	20.55	20.59	20.44	20.27		0.0
DFT-s-OFDM 16QAM	1	1	20.76	20.54	20.55	20.44	20.40	0-1	0.0
CP-OFDM QPSK	1	1	20.90	20.66	20.70	20.54	20.48	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 151 of 207

Table H-303
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.98	20.80	20.76	20.92	20.77	0	0.0
	1	39	20.77	20.72	20.73	20.71	20.69		0.0
	1	76	20.77	20.77	20.85	20.62	20.63		0.0
	36	0	20.82	20.70	20.63	20.74	20.62	0-1	0.0
	36	21	20.71	20.45	20.64	20.59	20.50	0	0.0
	36	42	20.71	20.54	20.76	20.56	20.54	0-1	0.0
	75	0	20.73	20.44	20.80	20.66	20.55		0.0
DFT-s-OFDM 16QAM	1	1	20.97	20.51	20.76	20.87	20.71	0-1	0.0
CP-OFDM QPSK	1	1	20.75	20.69	20.83	20.88	20.68	0-1.5	0.0

Table H-304
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.86	20.62	20.86	20.93	20.50	0	0.0
	1	33	20.72	20.67	20.89	20.72	20.43		0.0
	1	63	20.69	20.66	20.85	20.58	20.35		0.0
	32	0	20.83	20.64	20.79	20.55	20.39	0-1	0.0
	32	17	20.77	20.65	20.81	20.64	20.37	0	0.0
	32	33	20.70	20.67	20.84	20.65	20.45	0-1	0.0
	64	0	20.72	20.68	20.89	20.73	20.42		0.0
DFT-s-OFDM 16QAM	1	1	20.94	20.69	20.86	20.92	20.63	0-1	0.0
CP-OFDM QPSK	1	1	20.84	20.76	20.88	20.96	20.55	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 152 of 207

Table H-305
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.90	20.62	20.73	20.75	20.58	0	0.0
	1	26	20.82	20.72	20.77	20.62	20.65		0.0
	1	49	20.74	20.58	20.72	20.46	20.47		0.0
	25	0	20.70	20.43	20.68	20.64	20.54	0-1	0.0
	25	13	20.73	20.55	20.66	20.53	20.51	0	0.0
	25	26	20.63	20.54	20.68	20.47	20.51	0-1	0.0
	50	0	20.85	20.68	20.86	20.67	20.56		0.0
DFT-s-OFDM 16QAM	1	1	20.87	20.43	20.76	20.68	20.50	0-1	0.0
CP-OFDM QPSK	1	1	20.82	20.51	20.77	20.83	20.54	0-1.5	0.0

Table H-306
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.89	20.69	20.90	20.83	20.52	0	0.0
	1	19	20.92	20.66	20.86	20.65	20.41		0.0
	1	36	20.83	20.71	20.93	20.66	20.43		0.0
	18	0	20.93	20.68	20.93	20.73	20.43	0-1	0.0
	18	10	20.87	20.75	20.92	20.76	20.52	0	0.0
	18	20	20.85	20.73	20.97	20.71	20.45	0-1	0.0
	36	0	20.89	20.70	20.85	20.74	20.48		0.0
DFT-s-OFDM 16QAM	1	1	20.92	20.74	20.92	20.87	20.54	0-1	0.0
CP-OFDM QPSK	1	1	20.87	20.81	20.91	20.86	20.51	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 153 of 207

Table H-307
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.90	20.66	20.90	20.74	20.44	0	0.0
	1	12	20.81	20.63	20.92	20.66	20.42		0.0
	1	22	20.83	20.71	20.96	20.70	20.47		0.0
	12	0	20.77	20.57	20.79	20.59	20.43	0-1	0.0
	12	6	20.82	20.62	20.83	20.67	20.41	0	0.0
	12	12	20.79	20.55	20.85	20.59	20.37	0-1	0.0
	24	0	20.72	20.58	20.74	20.56	20.33		0.0
DFT-s-OFDM 16QAM	1	1	20.89	20.68	20.91	20.74	20.42	0-1	0.0
CP-OFDM QPSK	1	1	20.43	20.70	20.97	20.81	20.54	0-1.5	0.0

Table H-308
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	508200 (2541 MHz)	528996 (2644.98 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	24.98	24.42	0	0.0
	1	123	24.62	23.89		0.0
	1	243	24.67	23.84		0.0
	120	0	24.73	24.18	0-1	0.0
	120	63	24.55	23.95	0	0.0
	120	125	24.59	23.84	0-1	0.0
	243	0	24.63	23.97		0.0
DFT-s-OFDM 16QAM	1	1	24.97	24.47	0-1	0.0
CP-OFDM QPSK	1	1	24.74	24.57	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 154 of 207

Table H-309
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	24.68	24.49	0	0.0
	1	109	24.31	23.75		0.0
	1	215	24.67	23.68		0.0
	108	0	24.48	24.36	0-1	0.0
	108	55	24.33	23.93	0	0.0
	108	109	24.49	23.87	0-1	0.0
	216	0	24.55	24.15		0.0
DFT-s-OFDM 16QAM	1	1	24.63	24.46	0-1	0.0
CP-OFDM QPSK	1	1	24.76	24.56	0-1.5	0.0

Table H-310
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	24.65	24.24	0	0.0
	1	95	24.27	23.93		0.0
	1	187	24.34	23.92		0.0
	90	0	24.47	24.15	0-1	0.0
	90	50	24.41	23.95	0	0.0
	90	99	24.31	24.03	0-1	0.0
	180	0	24.48	24.07		0.0
DFT-s-OFDM 16QAM	1	1	24.60	24.35	0-1	0.0
CP-OFDM QPSK	1	1	24.74	24.42	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 155 of 207

Table H-311
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.92	24.81	24.66	0	0.0
	1	81	24.46	24.83	24.29		0.0
	1	160	24.47	24.77	24.32		0.0
	81	0	24.70	24.81	24.44	0-1	0.0
	81	41	24.49	24.80	24.30	0	0.0
	81	81	24.55	24.90	24.33	0-1	0.0
	162	0	24.62	24.85	24.43		0.0
DFT-s-OFDM 16QAM	1	1	24.65	24.74	24.54	0-1	0.0
CP-OFDM QPSK	1	1	24.79	24.77	24.65	0-1.5	0.0

Table H-312
NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.78	24.70	24.41	0	0.0
	1	67	24.49	24.93	24.06		0.0
	1	131	24.43	24.54	24.11		0.0
	64	0	24.72	24.96	24.22	0-1	0.0
	64	35	24.67	24.93	24.17	0	0.0
	64	69	24.47	24.82	24.16	0-1	0.0
	128	0	24.66	24.92	24.20		0.0
DFT-s-OFDM 16QAM	1	1	24.74	24.66	24.40	0-1	0.0
CP-OFDM OPSK	1	1	24.78	24.87	24.46	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 156 of 207

Table H-313

NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth							
			Channel				MPR Allowed per 3GPP [dB]
Modulation	RB Size	RB Offset	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)	
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.86	24.42	24.54	24.35	0
	1	60	24.68	24.40	24.45	24.08	
	1	117	24.58	24.64	24.47	24.04	
	54	0	24.84	24.44	24.53	24.24	0-1
	54	27	24.63	24.44	24.41	24.12	0
	54	54	24.61	24.55	24.53	24.11	0-1
	108	0	24.79	24.51	24.57	24.21	
DFT-s-OFDM 16QAM	1	1	24.87	24.36	24.52	24.26	0-1
CP-OFDM QPSK	1	1	24.62	24.50	24.64	24.41	0-1.5

Table H-314

NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	24.79	23.96	24.16	23.93	0	0.0
	1	53	24.70	24.13	24.10	23.73		0.0
	1	104	24.52	24.29	23.82	23.74		0.0
	50	0	24.77	24.05	24.25	23.80	0-1	0.0
	50	28	24.69	24.23	24.15	23.81	0	0.0
	50	56	24.58	24.29	24.06	23.84	0-1	0.0
	100	0	24.72	24.16	24.12	23.81		0.0
DFT-s-OFDM 16QAM	1	1	24.73	23.94	24.11	24.06	0-1	0.0
CP-OFDM QPSK	1	1	24.85	24.02	24.19	24.07	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 157 of 207

Table H-315

NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	24.75	24.52	24.50	24.30	24.26	0	0.0
	1	46	24.64	24.52	24.46	24.24	24.07		0.0
	1	90	24.40	24.53	24.48	24.12	24.06		0.0
	45	0	24.68	24.53	24.45	24.27	24.28	0-1	0.0
	45	22	24.70	24.50	24.36	24.24	23.93	0	0.0
	45	45	24.50	24.51	24.44	24.23	24.08	0-1	0.0
	90	0	24.69	24.45	24.40	24.19	24.05		0.0
DFT-s-OFDM 16QAM	1	1	24.74	24.56	24.47	24.16	24.35	0-1	0.0
CP-OFDM QPSK	1	1	24.26	24.60	24.41	24.38	24.40	0-1.5	0.0

Table H-316

NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	24.78	24.35	24.87	24.35	24.45	0	0.0
	1	39	24.58	24.20	24.88	24.06	24.36		0.0
	1	76	24.46	24.38	24.71	24.01	24.33		0.0
	36	0	24.62	24.20	24.90	24.22	23.82	0-1	0.0
	36	21	24.50	24.20	24.85	24.06	24.26	0	0.0
	36	42	24.58	24.32	24.76	24.07	24.34	0-1	0.0
	75	0	24.59	24.25	24.88	24.15	24.37		0.0
DFT-s-OFDM 16QAM	1	1	24.88	24.22	24.79	24.33	24.39	0-1	0.0
CP-OFDM QPSK	1	1	24.76	24.34	24.90	24.41	24.51	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 158 of 207

Table H-317

NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	24.71	24.26	24.84	24.37	24.34	0	0.0
	1	33	24.61	24.31	24.99	24.14	24.24		0.0
	1	63	24.43	24.25	24.72	24.01	24.16		0.0
	32	0	24.63	24.26	24.94	24.19	24.31	0-1	0.0
	32	17	24.46	24.22	24.87	24.07	24.17	0	0.0
	32	33	24.45	24.26	24.87	24.13	24.27	0-1	0.0
	64	0	24.57	24.33	24.94	24.18	24.29		0.0
DFT-s-OFDM 16QAM	1	1	24.62	24.21	24.83	24.28	24.29	0-1	0.0
CP-OFDM QPSK	1	1	24.73	24.32	24.91	24.38	24.34	0-1.5	0.0

Table H-318

NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	24.69	24.12	24.89	24.16	24.16	0	0.0
	1	26	24.65	24.20	24.98	24.05	24.21		0.0
	1	49	24.66	24.16	24.88	23.89	24.10		0.0
	25	0	24.68	24.18	24.97	24.15	24.24	0-1	0.0
	25	13	24.68	24.10	24.94	24.08	24.21	0	0.0
	25	26	24.73	24.16	24.89	23.98	24.15	0-1	0.0
	50	0	24.75	24.18	24.96	24.03	24.18		0.0
DFT-s-OFDM 16QAM	1	1	24.73	24.14	24.82	24.08	24.07	0-1	0.0
CP-OFDM QPSK	1	1	24.71	24.22	24.87	24.14	24.25	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 159 of 207

Table H-319

NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	24.64	24.21	24.93	24.13	24.21	0	0.0
	1	19	24.60	24.10	24.98	23.97	24.11		0.0
	1	36	24.66	24.17	24.85	23.93	24.15		0.0
	18	0	24.70	24.13	25.00	24.05	24.18	0-1	0.0
	18	10	24.72	24.18	25.00	24.03	24.21	0	0.0
	18	20	24.73	24.21	24.93	24.01	24.24	0-1	0.0
	36	0	24.71	24.14	24.95	24.00	24.20		0.0
DFT-s-OFDM 16QAM	1	1	24.74	24.10	24.86	24.06	24.09	0-1	0.0
CP-OFDM QPSK	1	1	24.84	24.19	25.00	24.14	24.18	0-1.5	0.0

Table H-320

NR Band n41 PC2 Antenna B Path 2 Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	24.60	24.03	24.89	23.99	24.10	0	0.0
	1	12	24.61	24.05	24.90	23.95	24.10		0.0
	1	22	24.66	24.17	24.94	23.94	24.13		0.0
	12	0	24.68	24.10	24.89	23.95	24.09	0-1	0.0
	12	6	24.55	24.06	24.83	23.88	24.05	0	0.0
	12	12	24.65	24.16	24.89	23.98	24.14	0-1	0.0
	24	0	24.62	24.08	24.86	23.92	24.07		0.0
DFT-s-OFDM 16QAM	1	1	24.69	24.10	24.92	24.00	24.09	0-1	0.0
CP-OFDM QPSK	1	1	24.77	24.20	25.00	24.09	24.14	0-1.5	0.0

FCC ID A3LSMS936U

RF Exposure Part 1 Test Report

Approved by:
Technical ManagerDUT Type:
Portable HandsetAPPENDIX H:
Page 160 of 207

Table H-321

NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) – 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth		
Channel		
Antenna	508200 (2541 MHz)	528996 (2644.98 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	17.32	16.18
SRS #3 Ant D	16.32	16.39
SRS #4 Ant E	18.10	17.49

Table H-322

NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) – 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth		
Channel		
Antenna	507204 (2536.02 MHz)	529998 (2649.99 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	17.11	16.33
SRS #3 Ant D	16.21	16.15
SRS #4 Ant E	17.70	18.02

Table H-323

NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) – 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth		
Channel		
Antenna	506202 (2531.01 MHz)	531000 (2655 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	17.48	16.46
SRS #3 Ant D	16.27	16.19
SRS #4 Ant E	17.95	17.74

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 161 of 207

Table H-324
NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) – 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth			
Channel			
Antenna	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)
	Conducted Power [dBm]		
SRS #2 Ant F	17.47	16.80	15.98
SRS #3 Ant D	16.42	16.38	16.50
SRS #4 Ant E	18.02	17.66	17.30

Table H-325
NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) – 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth			
Channel			
Antenna	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)
	Conducted Power [dBm]		
SRS #2 Ant F	17.44	17.23	16.15
SRS #3 Ant D	16.48	16.36	16.41
SRS #4 Ant E	17.81	18.03	17.22

Table H-326
NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth				
Channel				
Antenna	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	17.32	16.89	16.20	16.23
SRS #3 Ant D	16.47	16.26	16.35	16.31
SRS #4 Ant E	18.06	17.03	16.62	17.00

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 162 of 207

Table H-327

NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth					
Channel					
Antenna	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	17.31	16.50	17.10	15.84	16.28
SRS #3 Ant D	16.45	16.28	16.27	16.30	16.30
SRS #4 Ant E	18.05	16.97	17.77	16.52	17.11

Table H-328

NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth					
Channel					
Antenna	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	17.45	16.42	16.92	15.84	16.25
SRS #3 Ant D	16.44	16.17	16.10	16.11	16.12
SRS #4 Ant E	17.88	17.04	17.70	16.58	17.03

Table H-329

NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth					
Channel					
Antenna	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	17.22	16.71	16.84	15.85	16.27
SRS #3 Ant D	16.36	16.17	16.17	16.08	16.15
SRS #4 Ant E	17.64	17.02	17.42	16.31	17.22

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 163 of 207

Table H-330

NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth					
Channel					
Antenna	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	17.20	16.68	16.79	15.88	16.43
SRS #3 Ant D	16.48	16.13	16.07	16.05	16.10
SRS #4 Ant E	17.65	16.59	17.44	16.17	17.30

Table H-331

NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth					
Channel					
Antenna	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	17.25	16.87	16.94	15.91	16.40
SRS #3 Ant D	16.48	16.26	16.20	16.16	16.27
SRS #4 Ant E	17.60	16.55	17.50	16.34	17.24

Table H-332

NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth		
Channel		
Antenna	508200 (2541 MHz)	528996 (2644.98 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	14.16	13.03
SRS #3 Ant D	14.74	14.82
SRS #4 Ant E	16.59	16.35

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 164 of 207

Table H-333
NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth		
Channel		
Antenna	507204 (2536.02 MHz)	529998 (2649.99 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	14.34	13.13
SRS #3 Ant D	14.64	14.70
SRS #4 Ant E	16.16	16.50

Table H-334
NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth		
Channel		
Antenna	506202 (2531.01 MHz)	531000 (2655 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	14.32	12.80
SRS #3 Ant D	14.73	14.72
SRS #4 Ant E	16.39	16.58

Table H-335
NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth			
Channel			
Antenna	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)
	Conducted Power [dBm]		
SRS #2 Ant F	14.24	13.78	12.86
SRS #3 Ant D	14.95	14.91	15.00
SRS #4 Ant E	16.58	16.16	16.60

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 165 of 207

Table H-336
NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth			
Channel			
Antenna	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)
	Conducted Power [dBm]		
SRS #2 Ant F	14.21	14.21	13.21
SRS #3 Ant D	15.00	14.88	14.92
SRS #4 Ant E	16.41	16.57	15.98

Table H-337
NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth				
Channel				
Antenna	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	14.29	13.56	12.96	13.07
SRS #3 Ant D	15.00	14.75	14.87	14.89
SRS #4 Ant E	16.49	15.86	15.14	16.21

Table H-338
NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth					
Channel					
Antenna	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	14.37	13.31	13.99	12.67	13.24
SRS #3 Ant D	15.00	14.71	14.78	14.76	14.82
SRS #4 Ant E	16.58	15.85	16.31	14.99	16.25

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 166 of 207

Table H-339
NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 1 (Head) - 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth					
Channel					
Antenna	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	14.23	13.24	14.12	12.70	13.20
SRS #3 Ant D	14.97	14.68	14.61	14.64	14.56
SRS #4 Ant E	16.37	15.93	16.20	15.15	15.94

Table H-340
NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth					
Channel					
Antenna	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	14.04	13.28	14.00	12.54	13.13
SRS #3 Ant D	14.88	14.63	14.64	14.63	14.61
SRS #4 Ant E	16.11	16.27	15.94	14.85	15.97

Table H-341
NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth					
Channel					
Antenna	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	13.92	13.32	13.70	12.61	13.21
SRS #3 Ant D	14.98	14.59	14.57	14.62	14.57
SRS #4 Ant E	16.17	15.53	15.92	14.64	15.86

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 167 of 207

Table H-342

NR Band n41 PC2 Antenna F, D, E Path 2 Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth					
Channel					
Antenna	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)
	Conducted Power [dBm]				
SRS #2 Ant F	13.81	13.60	13.82	12.58	13.19
SRS #3 Ant D	14.98	14.73	14.66	14.67	14.75
SRS #4 Ant E	16.12	15.73	15.96	14.66	15.98

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 168 of 207

H.2.7 NR Band n48

Table H-343

NR Band n48 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n48 30 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637668 (3565.02 MHz)	640334 (3605.01 MHz)	643000 (3645 MHz)	645666 (3684.99 MHz)		
Conducted Power [dBm]								
DFT-s-OFDM QPSK	1	1	18.28	18.25	18.41	18.23	0	0.0
	1	39	18.37	18.19	18.22	18.30		0.0
	1	76	18.55	18.30	18.24	18.47		0.0
	36	0	18.29	18.21	18.21	18.20	0-1	0.0
	36	21	18.34	18.18	18.16	18.30	0	0.0
	36	42	18.44	18.14	18.11	18.32	0-1	0.0
	75	0	18.34	18.20	18.19	18.30		0.0
DFT-s-OFDM 16QAM	1	1	18.24	18.27	18.39	18.26	0-1	0.0
CP-OFDM QPSK	1	1	18.32	18.33	18.44	18.32	0-1.5	0.0

Table H-344

NR Band n48 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n48 20 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)		
Conducted Power [dBm]								
DFT-s-OFDM QPSK	1	1	18.18	18.17	18.33	18.28	0	0.0
	1	26	18.29	18.20	18.20	18.26		0.0
	1	49	18.36	18.20	18.07	18.22		0.0
	25	0	18.20	18.19	18.11	18.24	0-1	0.0
	25	13	18.29	18.22	18.14	18.21	0	0.0
	25	26	18.29	18.18	18.06	18.18	0-1	0.0
	50	0	18.32	18.25	18.20	18.33		0.0
DFT-s-OFDM 16QAM	1	1	18.04	18.21	18.16	18.16	0-1	0.0
CP-OFDM QPSK	1	1	18.21	18.30	18.20	18.24	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 169 of 207

Table H-345
NR Band n48 Ant F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n48 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	18.20	18.23	18.27	18.28	0	0.0
	1	12	18.31	18.17	18.11	18.26		0.0
	1	22	18.39	18.21	18.08	18.34		0.0
	12	0	18.22	18.13	18.07	18.25	0-1	0.0
	12	6	18.23	18.20	18.14	18.28	0	0.0
	12	12	18.18	18.13	18.05	18.26	0-1	0.0
	24	0	18.15	18.12	18.08	18.21		0.0
DFT-s-OFDM 16QAM	1	1	18.19	18.24	18.25	18.30	0-1	0.0
CP-OFDM QPSK	1	1	18.21	18.31	18.31	18.33	0-1.5	0.0

Table H-346
NR Band n48 Ant F Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n48 30 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637668 (3565.02 MHz)	640334 (3605.01 MHz)	643000 (3645 MHz)	645666 (3684.99 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	14.38	14.45	14.63	14.60	0	0.0
	1	39	14.47	14.39	14.47	14.58		0.0
	1	76	14.69	14.52	14.54	14.72		0.0
	36	0	14.42	14.41	14.48	14.47	0-1	0.0
	36	21	14.50	14.37	14.42	14.53	0	0.0
	36	42	14.60	14.42	14.39	14.57	0-1	0.0
	75	0	14.52	14.44	14.49	14.57		0.0
DFT-s-OFDM 16QAM	1	1	14.38	14.42	14.66	14.52	0-1	0.0
CP-OFDM QPSK	1	1	14.39	14.56	14.65	14.53	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 170 of 207

Table H-347
NR Band n48 Ant F Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n48 20 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	14.28	14.39	14.49	14.49	0	0.0
	1	26	14.37	14.42	14.42	14.55		0.0
	1	49	14.49	14.30	14.28	14.54		0.0
	25	0	14.34	14.31	14.40	14.46	0-1	0.0
	25	13	14.40	14.28	14.37	14.48	0	0.0
	25	26	14.43	14.31	14.30	14.38	0-1	0.0
	50	0	14.51	14.43	14.39	14.47		0.0
DFT-s-OFDM 16QAM	1	1	14.30	14.29	14.44	14.36	0-1	0.0
CP-OFDM QPSK	1	1	14.34	14.47	14.56	14.41	0-1.5	0.0

Table H-348
NR Band n48 Ant F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n48 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	14.35	14.46	14.51	14.60	0	0.0
	1	12	14.43	14.40	14.39	14.53		0.0
	1	22	14.49	14.36	14.35	14.54		0.0
	12	0	14.32	14.37	14.36	14.48	0-1	0.0
	12	6	14.40	14.39	14.38	14.55	0	0.0
	12	12	14.37	14.37	14.30	14.45	0-1	0.0
	24	0	14.31	14.27	14.33	14.44		0.0
DFT-s-OFDM 16QAM	1	1	14.36	14.46	14.51	14.54	0-1	0.0
CP-OFDM QPSK	1	1	14.39	14.51	14.53	14.61	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 171 of 207

Table H-349
NR Band n48 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 30 MHz Bandwidth

NR Band n48 30 MHz Bandwidth				
Channel				
Antenna	637668 (3565.02 MHz)	640334 (3605.01 MHz)	643000 (3645 MHz)	645666 (3684.99 MHz)
	Conducted Power [dBm]			
SRS #2 Ant C	12.85	13.27	13.46	13.43
SRS #3 Ant I	16.17	16.15	16.22	16.14
SRS #4 Ant D	12.23	12.20	12.22	12.21

Table H-350
NR Band n48 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 20 MHz Bandwidth

NR Band n48 20 MHz Bandwidth				
Channel				
Antenna	637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)
	Conducted Power [dBm]			
SRS #2 Ant C	13.02	13.15	13.34	13.36
SRS #3 Ant I	16.07	16.03	16.17	16.06
SRS #4 Ant D	12.19	12.21	12.34	12.23

Table H-371
NR Band n48 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 10 MHz Bandwidth

NR Band n48 10 MHz Bandwidth				
Channel				
Antenna	637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)
	Conducted Power [dBm]			
SRS #2 Ant C	12.82	13.08	13.33	13.34
SRS #3 Ant I	16.00	15.96	16.08	16.05
SRS #4 Ant D	12.06	12.10	12.29	12.20

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 172 of 207

Table H-372
NR Band n48 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n48 30 MHz Bandwidth				
Channel				
Antenna	637668 (3565.02 MHz)	640334 (3605.01 MHz)	643000 (3645 MHz)	645666 (3684.99 MHz)
	Conducted Power [dBm]			
SRS #2 Ant C	8.95	9.36	9.56	9.52
SRS #3 Ant I	12.25	12.18	12.36	12.23
SRS #4 Ant D	8.30	8.35	8.40	8.37

Table H-373
NR Band n48 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n48 20 MHz Bandwidth				
Channel				
Antenna	637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)
	Conducted Power [dBm]			
SRS #2 Ant C	9.15	9.24	9.52	9.58
SRS #3 Ant I	12.14	12.24	12.30	12.22
SRS #4 Ant D	8.30	8.29	8.45	8.43

Table H-374
NR Band n48 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n48 10 MHz Bandwidth				
Channel				
Antenna	637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)
	Conducted Power [dBm]			
SRS #2 Ant C	8.94	9.22	9.45	9.56
SRS #3 Ant I	12.07	12.08	12.17	12.21
SRS #4 Ant D	8.12	8.17	8.39	8.41

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 173 of 207

H.2.8 NR Band n77

Table H-351
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.75	0	0.0
	1	123	17.33		0.0
	1	243	17.58		0.0
	120	0	17.43	0-1	0.0
	120	63	17.35	0	0.0
	120	125	17.45	0-1	0.0
	243	0	17.40		0.0
DFT-s-OFDM 16QAM	1	1	17.72	0-1	0.0
CP-OFDM QPSK	1	1	17.64	0-1.5	0.0

Table H-352
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.57	0	0.0
	1	109	17.35		0.0
	1	215	17.56		0.0
	108	0	17.45	0-1	0.0
	108	55	17.41	0	0.0
	108	109	17.42	0-1	0.0
	216	0	17.45		0.0
DFT-s-OFDM 16QAM	1	1	17.65	0-1	0.0
CP-OFDM QPSK	1	1	17.63	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 174 of 207

Table H-353
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.64	0	0.0
	1	95	17.37		0.0
	1	187	17.47		0.0
	90	0	17.54	0-1	0.0
	90	50	17.49	0	0.0
	90	99	17.40	0-1	0.0
	180	0	17.50		0.0
DFT-s-OFDM 16QAM	1	1	17.65	0-1	0.0
CP-OFDM QPSK	1	1	17.61	0-1.5	0.0

Table H-354
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.56	0	0.0
	1	81	17.34		0.0
	1	160	17.52		0.0
	81	0	17.38	0-1	0.0
	81	41	17.40	0	0.0
	81	81	17.34	0-1	0.0
	162	0	17.45		0.0
DFT-s-OFDM 16QAM	1	1	17.50	0-1	0.0
CP-OFDM QPSK	1	1	17.56	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 175 of 207

Table H-355
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.68	0	0.0
	1	67	17.55		0.0
	1	131	17.53		0.0
	64	0	17.67	0-1	0.0
	64	35	17.59	0	0.0
	64	69	17.55	0-1	0.0
	128	0	17.61		0.0
DFT-s-OFDM 16QAM	1	1	17.60	0-1	0.0
CP-OFDM QPSK	1	1	17.77	0-1.5	0.0

Table H-356
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.43	0	0.0
	1	53	17.35		0.0
	1	104	17.28		0.0
	50	0	17.44	0-1	0.0
	50	28	17.43	0	0.0
	50	56	17.33	0-1	0.0
	100	0	17.39		0.0
DFT-s-OFDM 16QAM	1	1	17.47	0-1	0.0
CP-OFDM QPSK	1	1	17.49	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 176 of 207

Table H-357
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.66	0	0.0
	1	39	17.53		0.0
	1	76	17.50		0.0
	36	0	17.43	0-1	0.0
	36	21	17.40	0	0.0
	36	42	17.39	0-1	0.0
	75	0	17.44		0.0
DFT-s-OFDM 16QAM	1	1	17.56	0-1	0.0
CP-OFDM QPSK	1	1	17.63	0-1.5	0.0

Table H-358
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.50	0	0.0
	1	26	17.41		0.0
	1	49	17.37		0.0
	25	0	17.32	0-1	0.0
	25	13	17.34	0	0.0
	25	26	17.29	0-1	0.0
	50	0	17.41		0.0
DFT-s-OFDM 16QAM	1	1	17.43	0-1	0.0
CP-OFDM QPSK	1	1	17.47	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 177 of 207

Table H-359
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.24	0	0.0
	1	19	17.17		0.0
	1	36	17.16		0.0
	18	0	17.26	0-1	0.0
	18	10	17.31	0	0.0
	18	20	17.25	0-1	0.0
	36	0	17.26		0.0
DFT-s-OFDM 16QAM	1	1	17.33	0-1	0.0
CP-OFDM QPSK	1	1	17.29	0-1.5	0.0

Table H-360
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.45	0	0.0
	1	12	17.36		0.0
	1	22	17.40		0.0
	12	0	17.29	0-1	0.0
	12	6	17.37	0	0.0
	12	12	17.29	0-1	0.0
	24	0	17.25		0.0
DFT-s-OFDM 16QAM	1	1	17.33	0-1	0.0
CP-OFDM QPSK	1	1	17.36	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 178 of 207

Table H-361
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.63	0	0.0
	1	123	15.26		0.0
	1	243	15.47		0.0
	120	0	15.35	0-1	0.0
	120	63	15.25	0	0.0
	120	125	15.20	0-1	0.0
	243	0	15.27		0.0
DFT-s-OFDM 16QAM	1	1	15.60	0-1	0.0
CP-OFDM QPSK	1	1	15.56	0-1.5	0.0

Table H-362
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.62	0	0.0
	1	109	15.33		0.0
	1	215	15.49		0.0
	108	0	15.54	0-1	0.0
	108	55	15.34	0	0.0
	108	109	15.36	0-1	0.0
	216	0	15.39		0.0
DFT-s-OFDM 16QAM	1	1	15.66	0-1	0.0
CP-OFDM QPSK	1	1	15.63	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 179 of 207

Table H-363
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.63	0	0.0
	1	95	15.33		0.0
	1	187	15.54		0.0
	90	0	15.53	0-1	0.0
	90	50	15.37	0	0.0
	90	99	15.41	0-1	0.0
	180	0	15.50		0.0
DFT-s-OFDM 16QAM	1	1	15.77	0-1	0.0
CP-OFDM QPSK	1	1	15.75	0-1.5	0.0

Table H-364
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.59	0	0.0
	1	81	15.24		0.0
	1	160	15.43		0.0
	81	0	15.39	0-1	0.0
	81	41	15.34	0	0.0
	81	81	15.24	0-1	0.0
	162	0	15.42		0.0
DFT-s-OFDM 16QAM	1	1	15.50	0-1	0.0
CP-OFDM QPSK	1	1	15.58	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 180 of 207

Table H-365
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.57	0	0.0
	1	67	15.36		0.0
	1	131	15.51		0.0
	64	0	15.54	0-1	0.0
	64	35	15.37	0	0.0
	64	69	15.41	0-1	0.0
	128	0	15.49		0.0
DFT-s-OFDM 16QAM	1	1	15.66	0-1	0.0
CP-OFDM QPSK	1	1	15.62	0-1.5	0.0

Table H-366
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.47	0	0.0
	1	53	15.36		0.0
	1	104	15.33		0.0
	50	0	15.48	0-1	0.0
	50	28	15.36	0	0.0
	50	56	15.40	0-1	0.0
	100	0	15.44		0.0
DFT-s-OFDM 16QAM	1	1	15.55	0-1	0.0
CP-OFDM QPSK	1	1	15.57	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 181 of 207

Table H-367
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.66	0	0.0
	1	39	15.35		0.0
	1	76	15.49		0.0
	36	0	15.45	0-1	0.0
	36	21	15.37	0	0.0
	36	42	15.38	0-1	0.0
	75	0	15.41		0.0
DFT-s-OFDM 16QAM	1	1	15.57	0-1	0.0
CP-OFDM QPSK	1	1	15.66	0-1.5	0.0

Table H-368
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.48	0	0.0
	1	26	15.37		0.0
	1	49	15.39		0.0
	25	0	15.34	0-1	0.0
	25	13	15.29	0	0.0
	25	26	15.31	0-1	0.0
	50	0	15.40		0.0
DFT-s-OFDM 16QAM	1	1	15.45	0-1	0.0
CP-OFDM QPSK	1	1	15.51	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 182 of 207

Table H-369
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.32	0	0.0
	1	19	15.26		0.0
	1	36	15.25		0.0
	18	0	15.30	0-1	0.0
	18	10	15.33	0	0.0
	18	20	15.27	0-1	0.0
	36	0	15.30		0.0
DFT-s-OFDM 16QAM	1	1	15.33	0-1	0.0
CP-OFDM QPSK	1	1	15.30	0-1.5	0.0

Table H-370
NR Band n77 DoD Antenna F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.37	0	0.0
	1	12	15.33		0.0
	1	22	15.34		0.0
	12	0	15.23	0-1	0.0
	12	6	15.37	0	0.0
	12	12	15.29	0-1	0.0
	24	0	15.23		0.0
DFT-s-OFDM 16QAM	1	1	15.39	0-1	0.0
CP-OFDM QPSK	1	1	15.40	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 183 of 207

Table H-371

NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	11.46
SRS #3 Ant I	15.42
SRS #4 Ant D	10.92

Table H-372

NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	11.52
SRS #3 Ant I	15.36
SRS #4 Ant D	10.88

Table H-373

NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	11.55
SRS #3 Ant I	15.37
SRS #4 Ant D	10.89

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 184 of 207

Table H-374

NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	11.53
SRS #3 Ant I	15.41
SRS #4 Ant D	10.95

Table H-375

NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	11.65
SRS #3 Ant I	15.57
SRS #4 Ant D	10.98

Table H-376

NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	11.49
SRS #3 Ant I	15.45
SRS #4 Ant D	10.92

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 185 of 207

Table H-377

NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	11.61
SRS #3 Ant I	15.56
SRS #4 Ant D	10.96

Table H-378

NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	11.58
SRS #3 Ant I	15.50
SRS #4 Ant D	10.90

Table H-379

NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	11.63
SRS #3 Ant I	15.18
SRS #4 Ant D	10.41

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 186 of 207

Table H-380
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet) - 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	11.59
SRS #3 Ant I	15.46
SRS #4 Ant D	10.87

Table H-381
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.49
SRS #3 Ant I	14.33
SRS #4 Ant D	9.90

Table H-382
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.57
SRS #3 Ant I	14.34
SRS #4 Ant D	9.86

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 187 of 207

Table H-383
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.60
SRS #3 Ant I	14.36
SRS #4 Ant D	9.87

Table H-384
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.41
SRS #3 Ant I	14.30
SRS #4 Ant D	9.84

Table H-385
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.70
SRS #3 Ant I	14.58
SRS #4 Ant D	9.98

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 188 of 207

Table H-386
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.51
SRS #3 Ant I	14.43
SRS #4 Ant D	9.90

Table H-387
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.64
SRS #3 Ant I	14.47
SRS #4 Ant D	9.96

Table H-388
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.59
SRS #3 Ant I	14.38
SRS #4 Ant D	9.88

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 189 of 207

Table H-389
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.61
SRS #3 Ant I	13.94
SRS #4 Ant D	9.37

Table H-390
NR Band n77 DoD Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.57
SRS #3 Ant I	14.45
SRS #4 Ant D	9.85

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 190 of 207

Table H-391
NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 90 MHz Bandwidth

NR Band n77 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.82	17.30	0	0.0
	1	123	17.59	17.45		0.0
	1	243	17.55	17.58		0.0
	120	0	17.70	17.24	0-1	0.0
	120	63	17.63	17.44	0	0.0
	120	125	17.54	17.50	0-1	0.0
	243	0	17.62	17.42		0.0
DFT-s-OFDM 16QAM	1	1	17.88	17.39	0-1	0.0
CP-OFDM QPSK	1	1	17.94	17.45	0-1.5	0.0

Table H-392
NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 80 MHz Bandwidth

NR Band n77 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.88	17.31	0	0.0
	1	109	17.70	17.44		0.0
	1	215	17.67	17.76		0.0
	108	0	17.78	17.40	0-1	0.0
	108	55	17.68	17.62	0	0.0
	108	109	17.62	17.65	0-1	0.0
	216	0	17.73	17.58		0.0
DFT-s-OFDM 16QAM	1	1	17.92	17.44	0-1	0.0
CP-OFDM QPSK	1	1	17.88	17.47	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 191 of 207

Table H-393
NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 70 MHz Bandwidth

NR Band n77 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.88	17.40	0	0.0
	1	95	17.70	17.44		0.0
	1	187	17.64	17.70		0.0
	90	0	17.78	17.42	0-1	0.0
	90	50	17.75	17.59	0	0.0
	90	99	17.66	17.61	0-1	0.0
	180	0	17.71	17.50		0.0
DFT-s-OFDM 16QAM	1	1	17.78	17.37	0-1	0.0
CP-OFDM QPSK	1	1	17.81	17.50	0-1.5	0.0

Table H-394
NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 60 MHz Bandwidth

NR Band n77 60 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.90	17.27	0	0.0
	1	81	17.58	17.36		0.0
	1	160	17.57	17.60		0.0
	81	0	17.62	17.34	0-1	0.0
	81	41	17.68	17.40	0	0.0
	81	81	17.56	17.43	0-1	0.0
	162	0	17.70	17.42		0.0
DFT-s-OFDM 16QAM	1	1	17.80	17.36	0-1	0.0
CP-OFDM QPSK	1	1	17.84	17.40	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 192 of 207

Table H-395
NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 50 MHz Bandwidth

NR Band n77 50 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.84	17.47	0	0.0
	1	67	17.74	17.70		0.0
	1	131	17.66	17.75		0.0
	64	0	17.86	17.54	0-1	0.0
	64	35	17.77	17.77	0	0.0
	64	69	17.58	17.69	0-1	0.0
	128	0	17.80	17.57		0.0
DFT-s-OFDM 16QAM	1	1	17.92	17.50	0-1	0.0
CP-OFDM QPSK	1	1	17.84	17.57	0-1.5	0.0

Table H-396
NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 40 MHz Bandwidth

NR Band n77 40 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.72	17.30	0	0.0
	1	53	17.71	17.48		0.0
	1	104	17.59	17.55		0.0
	50	0	17.73	17.46	0-1	0.0
	50	28	17.69	17.52	0	0.0
	50	56	17.62	17.53	0-1	0.0
	100	0	17.68	17.47		0.0
DFT-s-OFDM 16QAM	1	1	17.76	17.43	0-1	0.0
CP-OFDM QPSK	1	1	17.78	17.37	0-1.5	0.0

Table H-397

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 193 of 207

NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 30 MHz Bandwidth

NR Band n77 30 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.75	17.58	0	0.0
	1	39	17.78	17.56		0.0
	1	76	17.70	17.70		0.0
	36	0	17.70	17.56	0-1	0.0
	36	21	17.65	17.50	0	0.0
	36	42	17.60	17.57	0-1	0.0
	75	0	17.68	17.53		0.0
DFT-s-OFDM 16QAM	1	1	17.66	17.52	0-1	0.0
CP-OFDM QPSK	1	1	17.80	17.60	0-1.5	0.0

Table H-398

NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 20 MHz Bandwidth

NR Band n77 20 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.68	17.46	0	0.0
	1	26	17.72	17.50		0.0
	1	49	17.62	17.53		0.0
	25	0	17.63	17.43	0-1	0.0
	25	13	17.66	17.46	0	0.0
	25	26	17.53	17.51	0-1	0.0
	50	0	17.70	17.52		0.0
DFT-s-OFDM 16QAM	1	1	17.64	17.43	0-1	0.0
CP-OFDM QPSK	1	1	17.69	17.52	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 194 of 207

Table H-399
NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 15 MHz Bandwidth

NR Band n77 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.60	17.47	0	0.0
	1	19	17.57	17.39		0.0
	1	36	17.58	17.52		0.0
	18	0	17.65	17.39	0-1	0.0
	18	10	17.69	17.47	0	0.0
	18	20	17.56	17.55	0-1	0.0
	36	0	17.67	17.44		0.0
DFT-s-OFDM 16QAM	1	1	17.73	17.47	0-1	0.0
CP-OFDM QPSK	1	1	17.68	17.48	0-1.5	0.0

Table H-400
NR Band n77 Antenna F Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 10 MHz Bandwidth

NR Band n77 10 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.78	17.60	0	0.0
	1	12	17.74	17.59		0.0
	1	22	17.70	17.79		0.0
	12	0	17.67	17.50	0-1	0.0
	12	6	17.72	17.60	0	0.0
	12	12	17.60	17.61	0-1	0.0
	24	0	17.55	17.52		0.0
DFT-s-OFDM 16QAM	1	1	17.73	17.50	0-1	0.0
CP-OFDM QPSK	1	1	17.83	17.58	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 195 of 207

Table H-401
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n77 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	15.78	15.06	0	0.0
	1	123	15.47	15.18		0.0
	1	243	15.46	15.44		0.0
	120	0	15.56	15.04	0-1	0.0
	120	63	15.41	15.13	0	0.0
	120	125	15.32	15.26	0-1	0.0
	243	0	15.46	15.17		0.0
DFT-s-OFDM 16QAM	1	1	15.85	15.13	0-1	0.0
CP-OFDM QPSK	1	1	15.92	15.14	0-1.5	0.0

Table H-402
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n77 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	15.75	14.97	0	0.0
	1	109	15.48	15.13		0.0
	1	215	15.34	15.37		0.0
	108	0	15.61	15.13	0-1	0.0
	108	55	15.53	15.17	0	0.0
	108	109	15.43	15.35	0-1	0.0
	216	0	15.56	15.15		0.0
DFT-s-OFDM 16QAM	1	1	15.78	15.11	0-1	0.0
CP-OFDM QPSK	1	1	15.83	15.09	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 196 of 207

Table H-403
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n77 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	15.75	15.07	0	0.0
	1	95	15.54	15.12		0.0
	1	187	15.32	15.34		0.0
	90	0	15.57	15.18	0-1	0.0
	90	50	15.54	15.19	0	0.0
	90	99	15.41	15.36	0-1	0.0
	180	0	15.53	15.20		0.0
DFT-s-OFDM 16QAM	1	1	15.67	15.20	0-1	0.0
CP-OFDM QPSK	1	1	15.77	15.12	0-1.5	0.0

Table H-404
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n77 60 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	15.74	15.06	0	0.0
	1	81	15.40	15.13		0.0
	1	160	15.39	15.33		0.0
	81	0	15.58	15.06	0-1	0.0
	81	41	15.46	15.14	0	0.0
	81	81	15.39	15.12	0-1	0.0
	162	0	15.54	15.24		0.0
DFT-s-OFDM 16QAM	1	1	15.73	15.12	0-1	0.0
CP-OFDM QPSK	1	1	15.83	15.17	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 197 of 207

Table H-405
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n77 50 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	15.78	15.27	0	0.0
	1	67	15.66	15.41		0.0
	1	131	15.48	15.46		0.0
	64	0	15.70	15.28	0-1	0.0
	64	35	15.68	15.39	0	0.0
	64	69	15.62	15.45	0-1	0.0
	128	0	15.67	15.37		0.0
DFT-s-OFDM 16QAM	1	1	15.83	15.22	0-1	0.0
CP-OFDM QPSK	1	1	15.79	15.20	0-1.5	0.0

Table H-406
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n77 40 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	15.65	15.05	0	0.0
	1	53	15.52	15.20		0.0
	1	104	15.36	15.23		0.0
	50	0	15.56	15.15	0-1	0.0
	50	28	15.50	15.30	0	0.0
	50	56	15.43	15.32	0-1	0.0
	100	0	15.52	15.28		0.0
DFT-s-OFDM 16QAM	1	1	15.72	15.08	0-1	0.0
CP-OFDM QPSK	1	1	15.74	15.12	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 198 of 207

Table H-407
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n77 30 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	15.72	15.33	0	0.0
	1	39	15.64	15.29		0.0
	1	76	15.57	15.32		0.0
	36	0	15.59	15.20	0-1	0.0
	36	21	15.49	15.24	0	0.0
	36	42	15.40	15.33	0-1	0.0
	75	0	15.50	15.26		0.0
DFT-s-OFDM 16QAM	1	1	15.62	15.30	0-1	0.0
CP-OFDM QPSK	1	1	15.67	15.32	0-1.5	0.0

Table H-408
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n77 20 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	15.59	15.11	0	0.0
	1	26	15.49	15.25		0.0
	1	49	15.40	15.23		0.0
	25	0	15.53	15.14	0-1	0.0
	25	13	15.53	15.23	0	0.0
	25	26	15.46	15.20	0-1	0.0
	50	0	15.55	15.30		0.0
DFT-s-OFDM 16QAM	1	1	15.55	15.11	0-1	0.0
CP-OFDM QPSK	1	1	15.65	15.19	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 199 of 207

Table H-409
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n77 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	15.62	15.47	0	0.0
	1	19	15.57	15.41		0.0
	1	36	15.56	15.55		0.0
	18	0	15.67	15.49	0-1	0.0
	18	10	15.60	15.59	0	0.0
	18	20	15.60	15.68	0-1	0.0
	36	0	15.65	15.58		0.0
DFT-s-OFDM 16QAM	1	1	15.72	15.55	0-1	0.0
CP-OFDM QPSK	1	1	15.73	15.62	0-1.5	0.0

Table H-410
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n77 10 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	15.60	15.18	0	0.0
	1	12	15.53	15.25		0.0
	1	22	15.56	15.36		0.0
	12	0	15.55	15.17	0-1	0.0
	12	6	15.49	15.28	0	0.0
	12	12	15.48	15.27	0-1	0.0
	24	0	15.45	15.20		0.0
DFT-s-OFDM 16QAM	1	1	15.59	15.19	0-1	0.0
CP-OFDM QPSK	1	1	15.70	15.25	0-1.5	0.0

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 200 of 207

Table H-411
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 90 MHz Bandwidth

NR Band n77 90 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	11.35	10.65
SRS #3 Ant I	15.43	15.12
SRS #4 Ant D	10.70	10.50

Table H-412
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 80 MHz Bandwidth

NR Band n77 80 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	11.39	10.65
SRS #3 Ant I	15.44	15.14
SRS #4 Ant D	10.75	10.51

Table H-413
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 70 MHz Bandwidth

NR Band n77 70 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	11.39	10.61
SRS #3 Ant I	15.39	15.11
SRS #4 Ant D	10.75	10.45

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 201 of 207

Table H-414
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 60 MHz Bandwidth

NR Band n77 60 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	11.45	10.53
SRS #3 Ant I	15.48	15.13
SRS #4 Ant D	10.73	10.42

Table H-415
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 50 MHz Bandwidth

NR Band n77 50 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	11.65	10.62
SRS #3 Ant I	15.63	15.21
SRS #4 Ant D	10.88	10.54

Table H-416
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 40 MHz Bandwidth

NR Band n77 40 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	11.46	10.54
SRS #3 Ant I	15.44	15.09
SRS #4 Ant D	10.66	10.42

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 202 of 207

Table H-417
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 30 MHz Bandwidth

NR Band n77 30 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	11.71	10.73
SRS #3 Ant I	15.58	15.22
SRS #4 Ant D	10.77	10.54

Table H-418
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 20 MHz Bandwidth

NR Band n77 20 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	11.67	10.67
SRS #3 Ant I	15.47	15.02
SRS #4 Ant D	10.72	10.42

Table H-419
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 15 MHz Bandwidth

NR Band n77 15 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	11.57	10.55
SRS #3 Ant I	15.33	14.95
SRS #4 Ant D	10.57	10.32

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 203 of 207

Table H-420
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 0 (Body-worn, Hotspot or Phablet)
- 10 MHz Bandwidth

NR Band n77 10 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	11.77	10.63
SRS #3 Ant I	15.53	15.00
SRS #4 Ant D	10.65	10.40

Table H-421
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 90 MHz Bandwidth

NR Band n77 90 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	10.37	9.66
SRS #3 Ant I	14.41	14.14
SRS #4 Ant D	9.71	9.49

Table H-422
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 80 MHz Bandwidth

NR Band n77 80 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	10.38	9.63
SRS #3 Ant I	14.45	14.13
SRS #4 Ant D	9.72	9.48

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 204 of 207

Table H-423
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 70 MHz Bandwidth

NR Band n77 70 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	10.37	9.64
SRS #3 Ant I	14.42	14.10
SRS #4 Ant D	9.73	9.45

Table H-424
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 60 MHz Bandwidth

NR Band n77 60 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	10.43	9.51
SRS #3 Ant I	14.58	14.02
SRS #4 Ant D	9.63	9.45

Table H-425
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 50 MHz Bandwidth

NR Band n77 50 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	10.65	9.63
SRS #3 Ant I	14.64	14.17
SRS #4 Ant D	9.89	9.53

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 205 of 207

Table H-426
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 40 MHz Bandwidth

NR Band n77 40 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	10.44	9.52
SRS #3 Ant I	14.45	14.05
SRS #4 Ant D	9.67	9.42

Table H-427
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 30 MHz Bandwidth

NR Band n77 30 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	10.74	9.73
SRS #3 Ant I	14.54	14.16
SRS #4 Ant D	9.79	9.53

Table H-428
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 20 MHz Bandwidth

NR Band n77 20 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	10.64	9.67
SRS #3 Ant I	14.47	14.01
SRS #4 Ant D	9.72	9.41

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 206 of 207

Table H-429
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 15 MHz Bandwidth

NR Band n77 15 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	10.58	9.54
SRS #3 Ant I	14.37	13.96
SRS #4 Ant D	9.57	9.30

Table H-430
NR Band n77 Antenna C, I, D Measured P_{Limit} for DSI = 1 (Head) - 10 MHz Bandwidth

NR Band n77 10 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	10.75	9.64
SRS #3 Ant I	14.45	14.02
SRS #4 Ant D	9.68	9.42

FCC ID A3LSMS936U	RF Exposure Part 1 Test Report	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 207 of 207