






Plot 7-102. In Band Emissions Plot MIMO ANT2 (40MHz 802.11ax/be (UNII Band 5) – Ch. 43) - SP



Plot 7-103. In Band Emissions Plot MIMO ANT2 (80MHz 802.11ax/be (UNII Band 5) – Ch. 39) - SP

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 107 of 152




Plot 7-104. In Band Emissions Plot MIMO ANT2 (160MHz 802.11ax/be (UNII Band 5) – Ch. 47) - SP




Plot 7-105. In Band Emissions Plot MIMO ANT2 (320MHz 802.11be (UNII Band 5) – Ch. 31) - SP

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 108 of 152

Standard Power (Punctured) Operation



Plot 7-106. In Band Emissions Plot MIMO ANT2 (80MHz 802.11ax/be (UNII Band 5) – Ch. 39) – 20MHz Punctured - SP



Plot 7-107. In Band Emissions Plot MIMO ANT2 (160MHz 802.11ax/be (UNII Band 5) – Ch. 47) – 20MHz Punctured - SP

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 109 of 152

7.6 Contention Based Protocol

Test Overview and Limit

Indoor access points, subordinate devices and client devices operating in the 5.925-7.125 GHz band (herein referred to as unlicensed devices) are required to use technologies that include a contention-based protocol to avoid co-channel interference with incumbent devices sharing the band. To ensure incumbent co-channel operations are detected in a technology-agnostic manner, unlicensed devices are required to detect co-channel radio frequency energy (energy detect) and avoid simultaneous transmission.

Unlicensed indoor low-power devices must detect co-channel radio frequency power that is at least -62 dBm or lower. Upon detection of energy in the band, unlicensed low power indoor devices must vacate the channel and stay off the channel if detected radio frequency power is equal to or greater than the threshold (-62 dBm). The -62 dBm (or lower) threshold is referenced to a 0 dBi antenna gain.

To ensure incumbent operations are reliably detected in the band, low power indoor devices must detect RF energy throughout their intended operating channel.

Test Procedure Used

KDB 987594 D02 v01r01

Test Settings

1. Configure the EUT to transmit with a constant duty cycle.
2. Set the operating parameters of the EUT including power level, operating frequency, modulation, and bandwidth.
3. Set the signal analyzer center frequency to the nominal EUT channel center frequency. The span range of the signal analyzer shall be between two times and five times the OBW of the EUT. Connect the output port of the EUT to the signal analyzer 2. Ensure that the attenuator 2 provides enough attenuation to not overload the signal analyzer 2 receiver.
4. Monitoring the signal analyzer 2, verify the EUT is operating and transmitting with the parameters set at step two.
5. Using an AWGN signal source, generate (but do not transmit, i.e., RF OFF) a 10 MHz-wide AWGN signal. Use Table 1 to determine the center frequency of the 10 MHz AWGN signal relative to the EUT's channel bandwidth and center frequency.
6. Set the AWGN signal power to an extremely low level (more than 20 dB below the -62 dBm threshold). Connect the AWGN signal source, via a 3-dB splitter, to the signal analyzer 1 and the EUT as shown in Figure 2.
7. Transmit the AWGN signal (RF ON) and verify its characteristics on the signal analyzer 1.
8. Monitor the signal analyzer 2 to verify if the AWGN signal has been detected and the EUT has ceased transmission. If the EUT continues to transmit, then incrementally increase the AWGN signal power level until the EUT stops transmitting.
9. (Including all losses in the RF paths) Determine and record the AWGN signal power level (at the EUT's antenna port) at which the EUT ceased transmission. Repeat the procedure at least 10 times to verify the EUT can detect an AWGN signal with 90% (or better) level of certainty.
10. Refer to Table 1 of KDB 987594 D02 v01r01 to determine the number of times the detection threshold testing needs to be repeated. If testing is required more than once, then go back to step 5, choose a different center frequency for the AWGN signal, and repeat the process.

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 111 of 152

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Contention-based protocol test setup conducted method.

Test Notes

1. Per guidance from KDB 987594 D02 v01r01, contention-based protocol was tested using an AWGN signal with a bandwidth of 10MHz (see Plot 7-109). The amplitude of the signal was increased until detected by the EUT, signaled by the ceasing of transmission (see Plot 7-110), M1 indicates the point at which the AWGN signal is introduced. D1 indicates where the AWGN signal is terminated, at least 10 seconds following M1.
2. 15 trials were run to assure that at least 90% of certainty was met.
3. Per Guidance from KDB 987594 D04 v01, contention-based protocol was tested with receiver with the lowest antenna gain.
4. All CBP Timing Plots shown are for the ceased condition. Some spikes that may be shown are from adjacent portions of the spectrum that are still transmitting.
5. In the presence of an AWGN signal, the EUT was shown to either completely move out of the channel or to reduce its bandwidth for the purpose of incumbent avoidance. Representative channel move plots are included for one sub-band to show how the channel reduces when the AWGN is injected at the lower edge, the center, and the upper edge of a channel.
6. This device only punctures to optimize network performance and never to avoid licensed incumbents.
7. For the channel move demonstration in Section 7.6.3, only plots from UNII-5 band are included. Additionally, the AWGN signal is not visible because the AWGN level is well below the noise floor.

$$\text{Detection Level} = \text{Injected AWGN Power (dBm)} - \text{Antenna Gain (dBi)} + \text{Path Loss (dB)}$$

Equation 7-1. Detection Level Calculation

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 112 of 152

Band	Channel	Channel Freq [MHz]	Channel BW [MHz]	Incumbent Freq [MHz]	Injected (AWGN) [dBm]	Antenna Gain [dBi]	Path Loss (dB)	Adjusted Power Level [dBm]	Detection Limit [dBm]	Margin [dB]
UNII Band 5	53	6215	20	6215	-73.20	-7.48	0.85	-64.87	-62.0	-2.87
				6110	-76.99	-6.57	0.85	-69.57	-62.0	-7.57
	31	6265	320	6265	-73.11	-7.48	0.85	-64.78	-62.0	-2.78
				6420	-74.30	-6.13	0.85	-67.32	-62.0	-5.32
UNII Band 6	101	6455	20	6455	-74.14	-6.13	0.85	-67.16	-62.0	-5.16
				6270	-75.19	-7.48	0.85	-66.86	-62.0	-4.86
	95	6425	320	6425	-74.09	-6.13	0.85	-67.11	-62.0	-5.11
				6580	-74.60	-8.47	0.85	-65.28	-62.0	-3.28
UNII Band 7	149	6695	20	6695	-74.09	-8.93	0.85	-64.31	-62.0	-2.31
				6590	-73.70	-8.47	0.85	-64.38	-62.0	-2.38
	159	6745	320	6745	-74.07	-8.93	0.85	-64.29	-62.0	-2.29
				6900	-73.52	-7.49	0.85	-65.18	-62.0	-3.18
UNII Band 8	197	6935	20	6935	-75.60	-7.49	0.85	-67.26	-62.0	-5.26
				6750	-74.50	-8.93	0.85	-64.72	-62.0	-2.72
	191	6905	320	6905	-75.49	-7.49	0.85	-67.15	-62.0	-5.15
				7060	-72.48	-6.78	0.85	-64.85	-62.0	-2.85

Table 7-85. Contention Based Protocol – Incumbent Detection Results

Band	Channel	Channel Freq [MHz]	Channel BW [MHz]	Incumbent Freq [MHz]	Antenna Gain [dBi]	EUT Transmission Status			Detection Limit [dBm]	Margin [dB]
						Adjusted AWGN Power (dBm)				
						Normal	Minimal	Ceased		
UNII Band 5	53	6215	20	6215	-0.82	-66.32	-65.60	-64.87	-62.0	-2.87
				6110	-0.82	-70.54	-70.30	-69.57	-62.0	-7.57
	31	6265	320	6265	-0.82	-66.23	-65.51	-64.78	-62.0	-2.78
				6420	-0.82	-67.93	-67.56	-67.32	-62.0	-5.32
UNII Band 6	101	6455	20	6455	-0.86	-68.49	-67.89	-67.16	-62.0	-5.16
	95	6425	320	6270	-0.86	-67.83	-67.47	-66.86	-62.0	-4.86
				6425	-0.86	-68.44	-67.84	-67.11	-62.0	-5.11
				6580	-0.86	-66.01	-65.64	-65.28	-62.0	-3.28
UNII Band 7	149	6695	20	6695	-0.87	-65.76	-65.04	-64.31	-62.0	-2.31
	159	6745	320	6590	-0.87	-65.35	-64.74	-64.38	-62.0	-2.38
				6745	-0.87	-65.02	-64.77	-64.29	-62.0	-2.29
				6900	-0.87	-65.91	-65.66	-65.18	-62.0	-3.18
UNII Band 8	197	6935	20	6935	-1.29	-68.35	-67.62	-67.26	-62.0	-5.26
	191	6905	320	6750	-1.29	-65.81	-65.33	-64.72	-62.0	-2.72
				6905	-1.29	-68.12	-67.63	-67.15	-62.0	-5.15
				7060	-1.29	-66.06	-65.33	-64.85	-62.0	-2.85

Table 7-86. Contention Based Protocol – Detection Results – All Tx Cases


FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 113 of 152

Band	Channel	Channel Freq [MHz]	Channel BW [MHz]	Incumbent Freq [MHz]	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Detection Rate (%)
UNII Band 5	53	6215	20	6215	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
	31	6265	320	6110	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
				6265	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
				6420	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
UNII Band 6	101	6455	20	6455	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
	95	6425	320	6270	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
				6425	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
				6580	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
UNII Band 7	149	6695	20	6695	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
	159	6745	320	6590	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
				6745	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
				6900	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
UNII Band 8	197	6935	20	6935	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
	191	6905	320	6750	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
				6905	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
				7060	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100

Table 7-87. Contention Based Protocol – Incumbent Detection Trial Results

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 114 of 152

7.6.1 AWGN Plots




Date: 31.JUL.2024 09:46:42


Plot 7-109. AWGN Signal (Demonstration)

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 115 of 152

7.6.2 CBP Timing Plots




Plot 7-110. Contention Based Protocol Timing Plot (20MHz (UNII Band 5) – Ch. 53)




Plot 7-111. Contention Based Protocol Timing Plot (320MHz (UNII Band 5) – Ch. 31 Low)

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 116 of 152



Date: 22.OCT.2024 08:24:18


Plot 7-112. Contention Based Protocol Timing Plot (320MHz (UNII Band 5) – Ch. 31 Mid)



Date: 22.OCT.2024 08:25:05


Plot 7-113. Contention Based Protocol Timing Plot (320MHz (UNII Band 5) – Ch. 31 High)

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 117 of 152



Date: 22.OCT.2024 08:16:09


Plot 7-114. Contention Based Protocol Timing Plot (20MHz (UNII Band 6) – Ch. 101)



Date: 22.OCT.2024 08:11:44


Plot 7-115. Contention Based Protocol Timing Plot (320MHz (UNII Band 6) – Ch. 95 Low)

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 118 of 152



Date: 22.OCT.2024 08:13:23


Plot 7-116. Contention Based Protocol Timing Plot (320MHz (UNII Band 6) – Ch. 95 Mid)



Date: 22.OCT.2024 08:14:52


Plot 7-117. Contention Based Protocol Timing Plot (320MHz (UNII Band 6) – Ch. 95 High)

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 119 of 152



Date: 22.OCT.2024 07:59:00


Plot 7-118. Contention Based Protocol Timing Plot (20MHz (UNII Band 7) – Ch. 149)



Date: 22.OCT.2024 08:10:04


Plot 7-119. Contention Based Protocol Timing Plot (320MHz (UNII Band 7) – Ch. 159 Low)

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 120 of 152



Date: 22.OCT.2024 08:08:06


Plot 7-120. Contention Based Protocol Timing Plot (320MHz (UNII Band 7) – Ch. 159 Mid)



Date: 22.OCT.2024 08:06:59


Plot 7-121. Contention Based Protocol Timing Plot (320MHz (UNII Band 7) – Ch. 159 High)

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 121 of 152



Date: 22.OCT.2024 07:56:16


Plot 7-122. Contention Based Protocol Timing Plot (20MHz (UNII Band 8) – Ch. 197)



Date: 22.OCT.2024 07:54:18


Plot 7-123. Contention Based Protocol Timing Plot (320MHz (UNII Band 8) – Ch. 191 Low)

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 122 of 152



Date: 19.NOV.2024 15:21:31

Plot 7-124. Contention Based Protocol Timing Plot (320MHz (UNII Band 8) – Ch. 191 Mid)



Date: 22.OCT.2024 07:51:59


Plot 7-125. Contention Based Protocol Timing Plot (320MHz (UNII Band 8) – Ch. 191 High)

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 123 of 152

7.6.3 Channel Move Plots

This section demonstrates the effect of injecting the AWGN signal at various locations throughout the 802.11be 320MHz signal. The blue trace shows the full 320MHz signal prior to AWGN injection while the black trace shows the spectrum following AWGN injection. The following items were observed as demonstrated in the three plots shown below:

- When a 10 MHz AWGN signal centered at 6110 MHz (lower edge of channel) is injected, the channel completely stops transmitting.
- When a 10 MHz AWGN signal centered at 6265 MHz (middle of channel) is injected, the channel completely stops transmitting.
- When a 10 MHz AWGN signal centered at 6420 MHz (upper edge of channel) is injected, the channel completely stops transmitting.



Date: 22.OCT.2024 08:59:28

Plot 7-126. CBP 320MHz Channel - Injection Lower Edge – [6110 MHz]

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 124 of 152

7.7 Radiated Emission Measurements

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013, and at the appropriate frequencies. All channels, modes (e.g. 802.11a, 802.11ax (20/40/80/160MHz), and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst-case emissions are reported in this section.

For transmitters operating in the 5.925-7.125 GHz band: All emissions outside of the 5.925-7.125 GHz band shall not exceed an EIRP of -27dBm/MHz (68.2dBuV/m at a 3m distance). Emissions found in a restricted band are subject to the limits of 15.209 as shown in the table below.

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400\F (kHz)	300
0.490 – 1.705 MHz	24000\F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-88. Radiated Limits

Test Procedures Used

ANSI C63.10-2013 – Sections 12.7.7.2, 12.7.6, 12.7.5

Test Settings – Above 1GHz

Average Field Strength Measurements (Method AD – Average Detection)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span} \backslash \text{RBW}$)
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces.

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 126 of 152

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize.

Test Settings – Below 1GHz

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-6. Radiated Test Setup < 30MHz

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 127 of 152




Figure 7-7. Radiated Test Setup < 1GHz




Figure 7-8. Radiated Test Setup > 1GHz

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 128 of 152

Test Notes

1. All spurious emissions lying in restricted bands specified in §15.205 are below the limits specified in §15.209. All spurious emissions that do not lie in a restricted band are subject to an average limit of -27dBm/MHz. At 3 meters, the field strength limit in dB μ V/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dB μ V/m.
2. All spurious emissions that do not lie in a restricted band are subject to a peak limit not to exceed 20dB of the average limit [68.2dB μ V/m]. If a peak measurement passes the average limit, it was determined no further investigation is necessary.
3. The antenna is manipulated through typical positions, polarity, and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported, however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Emissions below 18GHz were measured at a 3-meter test distance while emissions above 18GHz were measured at a 1-meter test distance with the application of a distance correction factor.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
8. In the case where a peak-detector measurement passed the given RMS limit it was determined sufficient to demonstrate compliance.
9. The results recorded using the broadband antenna are known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.

Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level [dB μ V/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB]
- Margin [dB] = Field Strength Level [dB μ V/m] – Limit [dB μ V/m]


Radiated Band Edge Measurement Offset

The amplitude offset shown in the radiated restricted band edge plots was calculated using the formula:


$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 129 of 152


7.7.1 MIMO Radiated Spurious Emission Measurements



Plot 7-129. Radiated Spurious Plot 1GHz – 18GHz MIMO (802.11a – UNII Band 5 Ch. 45)




Plot 7-130. Radiated Spurious Plot 1GHz – 18GHz MIMO (802.11a – UNII Band 6 Ch. 105)




Plot 7-131. Radiated Spurious Plot 1GHz – 18GHz MIMO (802.11a – UNII Band 7 Ch. 149)


FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 130 of 152



Plot 7-132. Radiated Spurious Plot 1GHz – 18GHz MIMO (802.11a – U Band 8 Ch. 209)



Plot 7-133. Radiated Spurious Plot 18GHz - 26.5GHz (802.11a)



Plot 7-134. Radiated Spurious Plot 26.5GHz - 40GHz (802.11a)

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 131 of 152

MIMO Radiated Spurious Emission Measurements – UNII Band 5

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6Mbps
Distance of Measurements: 1 & 3 Meters

Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11a	MIMO	5	2	5935	*	11870.00	Average	V	-	-	-84.98	21.15	0.00	43.17	53.98	-10.81
					*	11870.00	Peak	V	-	-	-73.52	21.00	0.00	54.48	73.98	-19.50
					*	17805.00	Average	V	-	-	-84.82	30.33	0.00	52.51	53.98	-1.47
					*	17805.00	Peak	V	-	-	-73.18	30.33	0.00	64.15	73.98	-9.83
					*	23740.00	Average	V	-	-	-66.42	3.58	-9.54	34.62	53.98	-19.36
					*	23740.00	Peak	V	-	-	-55.73	3.58	-9.54	45.31	73.98	-28.67
			45	6175	*	29675.00	Peak	V	-	-	-56.96	5.33	-9.54	45.83	68.20	-22.37
					*	12350.00	Average	V	-	-	-85.40	21.65	0.00	43.25	53.98	-10.73
					*	12350.00	Peak	V	-	-	-74.67	21.89	0.00	54.22	73.98	-19.76
					*	18525.00	Average	V	-	-	-65.31	1.16	-9.54	33.32	53.98	-20.66
					*	18525.00	Peak	V	-	-	-54.55	1.16	-9.54	44.08	73.98	-29.90
					*	24700.00	Peak	V	-	-	-55.97	3.72	-9.54	45.20	68.20	-23.00
			93	6415	*	30875.00	Peak	V	-	-	-56.34	6.32	-9.54	47.45	68.20	-20.75
					*	12830.00	Peak	V	-	-	-72.05	17.82	0.00	52.77	68.20	-15.43
					*	19245.00	Average	V	-	-	-65.34	1.84	-9.54	33.96	53.98	-20.02
					*	19245.00	Peak	V	-	-	-54.73	1.84	-9.54	44.57	73.98	-29.41
					*	25660.00	Peak	V	-	-	-55.82	3.90	-9.54	45.55	68.20	-22.65
					*	32075.00	Peak	V	-	-	-56.58	6.64	-9.54	47.52	68.20	-20.68

Table 7-89. Radiated Measurements MIMO – SP

MIMO Radiated Spurious Emission Measurements – UNII Band 6

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6Mbps
Distance of Measurements: 1 & 3 Meters

Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11a	MIMO	6	97	6435	*	12870.00	Peak	V	-	-	-71.70	18.10	0.00	53.40	68.20	-14.80
					*	19305.00	Average	V	-	-	-65.66	1.64	-9.54	33.45	53.98	-20.53
					*	19305.00	Peak	V	-	-	-55.40	1.64	-9.54	43.71	73.98	-30.27
					*	25740.00	Peak	V	-	-	-55.80	3.84	-9.54	45.50	68.20	-22.70
					*	32175.00	Peak	V	-	-	-56.54	6.80	-9.54	47.72	68.20	-20.48
			105	6475	*	12950.00	Peak	V	-	-	-72.75	17.98	0.00	52.23	68.20	-15.97
					*	19425.00	Average	V	-	-	-65.59	1.80	-9.54	33.67	53.98	-20.31
					*	19425.00	Peak	V	-	-	-54.89	1.80	-9.54	44.38	73.98	-29.60
					*	25900.00	Peak	V	-	-	-55.73	4.24	-9.54	45.96	68.20	-22.24
					*	32375.00	Peak	V	-	-	-56.19	6.46	-9.54	47.73	68.20	-20.47
			113	6515	*	13030.00	Peak	V	-	-	-72.73	18.44	0.00	52.71	68.20	-15.49
					*	19545.00	Average	V	-	-	-66.07	1.84	-9.54	33.23	53.98	-20.75
					*	19545.00	Peak	V	-	-	-55.24	1.84	-9.54	44.06	73.98	-29.92
					*	26060.00	Peak	V	-	-	-56.33	4.18	-9.54	45.31	68.20	-22.89
					*	32575.00	Peak	V	-	-	-55.80	6.18	-9.54	47.84	68.20	-20.36

Table 7-90. Radiated Measurements MIMO – LPI

FCC ID: A3LSMS936U	MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset		Page 132 of 152

MIMO Radiated Spurious Emission Measurements – UNII Band 7

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6Mbps
Distance of Measurements: 1 & 3 Meters

Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11a	MIMO	7	117	6535		13070.00	Peak	V	-	-	-72.24	18.33	0.00	53.09	68.20	-15.11
					*	19605.00	Average	V	-	-	-65.46	2.38	-9.54	34.38	53.98	-19.60
					*	19605.00	Peak	V	-	-	-54.99	2.38	-9.54	44.85	73.98	-29.13
						26140.00	Peak	V	-	-	-55.56	4.03	-9.54	45.93	68.20	-22.27
						32675.00	Peak	V	-	-	-56.57	6.46	-9.54	47.34	68.20	-20.86
			149	6695	*	13390.00	Average	V	-	-	-83.98	17.76	0.00	40.78	53.98	-13.20
					*	13390.00	Peak	V	-	-	-72.40	17.72	0.00	52.32	73.98	-21.66
					*	20085.00	Average	V	-	-	-65.56	2.58	-9.54	34.48	53.98	-19.50
					*	20085.00	Peak	V	-	-	-54.69	2.58	-9.54	45.35	73.98	-28.63
						26780.00	Average	V	-	-	-66.70	4.33	-9.54	35.08	68.20	-33.12
			185	6875		33475.00	Peak	V	-	-	-56.57	6.96	-9.54	47.85	68.20	-20.35
						13750.00	Peak	V	-	-	-70.98	17.51	0.00	53.53	68.20	-14.67
					*	20625.00	Average	V	-	-	-65.49	3.01	-9.54	34.98	53.98	-19.00
					*	20625.00	Peak	V	-	-	-54.80	3.01	-9.54	45.67	73.98	-28.31
						27500.00	Peak	V	-	-	-55.89	3.97	-9.54	45.54	68.20	-22.66
						34375.00	Peak	V	-	-	-56.80	7.33	-9.54	47.99	68.20	-20.21

Table 7-91. Radiated Measurements MIMO – SP

MIMO Radiated Spurious Emission Measurements – UNII Band 8

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6Mbps
Distance of Measurements: 1 & 3 Meters


Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11a	MIMO	8	189	6895		13790.00	Peak	V	-	-	-70.92	16.97	0.00	53.05	68.20	-15.15
					*	20685.00	Average	V	-	-	-65.68	3.01	-9.54	34.79	53.98	-19.19
					*	20685.00	Peak	V	-	-	-55.40	3.01	-9.54	45.07	73.98	-28.91
						27580.00	Peak	V	-	-	-56.21	4.40	-9.54	45.65	68.20	-22.55
						34475.00	Peak	V	-	-	-55.92	7.31	-9.54	48.85	68.20	-19.35
			209	6995		13990.00	Peak	V	-	-	-71.17	17.93	0.00	53.76	68.20	-14.44
					*	20985.00	Average	V	-	-	-65.71	3.27	-9.54	35.01	53.98	-18.97
					*	20985.00	Peak	V	-	-	-54.69	3.27	-9.54	46.04	73.98	-27.94
						27980.00	Peak	V	-	-	-55.54	4.40	-9.54	46.32	68.20	-21.88
						34975.00	Peak	V	-	-	-57.52	7.79	-9.54	47.73	68.20	-20.47
			233	7115		14230.00	Peak	V	-	-	-71.69	17.89	0.00	53.20	68.20	-15.00
					*	21345.00	Average	V	-	-	-65.35	3.57	-9.54	35.68	53.98	-18.30
					*	21345.00	Peak	V	-	-	-54.35	3.57	-9.54	46.68	73.98	-27.30
						28460.00	Peak	V	-	-	-56.93	5.01	-9.54	45.54	68.20	-22.66
						35575.00	Peak	V	-	-	-56.85	7.78	-9.54	48.39	68.20	-19.81

Table 7-92. Radiated Measurements MIMO – LPI


FCC ID: A3LSMS936U	MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset		Page 133 of 152

7.7.2 MIMO Radiated Band Edge Measurements (20MHz BW)

Worst Case Mode:	802.11a
Worst Case Transfer Rate:	6Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	5935MHz
Channel:	2




Plot 7-135. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 5)




Plot 7-136. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 5)

Worst Case Mode:	802.11be
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	7115MHz
Channel:	233



Plot 7-137. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 8)




Plot 7-138. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 8)


FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 134 of 152

7.7.3 MIMO Radiated Band Edge Measurements (40MHz BW)

Worst Case Mode:	802.11be
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5965MHz
Channel:	3




Plot 7-139. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 5)




Plot 7-140. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 5)

Worst Case Mode:	802.11be
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	7085MHz
Channel:	227



Plot 7-141. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 8)




Plot 7-142. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 8)


FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 135 of 152

7.7.4 MIMO Radiated Band Edge Measurements (80MHz BW)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5985MHz
Channel: 7




Plot 7-143. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 5)




Plot 7-144. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 5)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 7025MHz
Channel: 215



Plot 7-145. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 8)




Plot 7-146. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 8)


FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 136 of 152

7.7.5 MIMO Radiated Band Edge Measurements (80MHz BW - Punctured)

Worst Case Mode:	802.11be
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5985MHz
Channel:	7




Plot 7-147. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 5)




Plot 7-148. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 5)

Worst Case Mode:	802.11be
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	7025MHz
Channel:	215



Plot 7-149. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 8)




Plot 7-150. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 8)


FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 137 of 152

7.7.6 MIMO Radiated Band Edge Measurements (160MHz BW)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6025MHz
Channel: 15




Plot 7-151. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 5)




Plot 7-152. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 5)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6985MHz
Channel: 207



Plot 7-153. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 8)




Plot 7-154. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 8)


FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 138 of 152

7.7.7 MIMO Radiated Band Edge Measurements (160MHz BW - Punctured)

Worst Case Mode:	802.11be
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6025MHz
Channel:	15




Plot 7-155. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 5)




Plot 7-156. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 5)

Worst Case Mode:	802.11be
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6985MHz
Channel:	207



Plot 7-157. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 8)




Plot 7-158. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 8)


FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 139 of 152

7.7.8 MIMO Radiated Band Edge Measurements (320MHz BW)

Worst Case Mode:	802.11be
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6105MHz
Channel:	31




Plot 7-159. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 5)




Plot 7-160. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 5)

Worst Case Mode:	802.11be
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	6905MHz
Channel:	191



Plot 7-161. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 8)




Plot 7-162. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 8)


FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 140 of 152

7.7.9 MIMO Radiated Band Edge Measurements (320MHz BW – Punctured)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6105MHz
Channel: 31




Plot 7-163. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 5)




Plot 7-164. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 5)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6905MHz
Channel: 191



Plot 7-165. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 8)



Plot 7-166. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 8)

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 141 of 152

7.8 Line Conducted Test Data

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst-case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207.

Frequency of emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-93. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2013, Section 6.2

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest.
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize.

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest.
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize.

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 142 of 152

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-9. Test Instrument & Measurement Setup


Test Notes

1. All modes of operation were investigated, and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz is specified in 15.207.
3. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5. $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 143 of 152




Plot 7-167. Line Conducted Plot with 802.11a UNII Band 5 (L1)




Plot 7-168. Line Conducted Plot with 802.11a UNII Band 5 (N)

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 144 of 152




Plot 7-169. Line Conducted Plot with 802.11a UNII Band 6 (L1)




Plot 7-170. Line Conducted Plot with 802.11a UNII Band 6 (N)

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 145 of 152




Plot 7-171. Line Conducted Plot with 802.11a UNII Band 7 (L1)




Plot 7-172. Line Conducted Plot with 802.11a UNII Band 7 (N)

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 146 of 152




Plot 7-173. Line Conducted Plot with 802.11a UNII Band 8 (L1)




Plot 7-174. Line Conducted Plot with 802.11a UNII Band 8 (N)

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 147 of 152




Plot 7-175. Line Conducted Plot with 802.11a UNII Band 5 (L1) with WCP




Plot 7-176. Line Conducted Plot with 802.11a UNII Band 5 (N) with WCP

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 148 of 152




Plot 7-177. Line Conducted Plot with 802.11a UNII Band 6 (L1) with WCP




Plot 7-178. Line Conducted Plot with 802.11a UNII Band 6 (N) with WCP

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 149 of 152




Plot 7-179. Line Conducted Plot with 802.11a UNII Band 7 (L1) with WCP




Plot 7-180. Line Conducted Plot with 802.11a UNII Band 7 (N) with WCP

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 150 of 152



Plot 7-181. Line Conducted Plot with 802.11a UNII Band 8 (L1) with WCP



Plot 7-182. Line Conducted Plot with 802.11a UNII Band 8 (N) with WCP

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 151 of 152

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMS936U** is in compliance with FCC Part Subpart E (15.407) of the FCC rules for operation as a client device.

FCC ID: A3LSMS936U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260064-17-R1.A3L	Test Dates: 09/03/2024 – 11/19/2024	EUT Type: Portable Handset	Page 152 of 152