

MEASUREMENT REPORT**FCC Part 15.407 802.11ax/be WiFi 6GHz VLP (OFDMA)****Applicant Name:**

Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

09/03/2024 - 10/31/2024

Test Report Issue Date:

10/31/2024

Test Site/Location:

Element lab., Columbia, MD, USA
Element Lab., Morgan Hill, CA, USA

Test Report Serial No.:

1M2408260067-33-R1.A3L

FCC ID:

A3LSMS938U

APPLICANT:

Samsung Electronics Co., Ltd.

Application Type:

Certification

Model:

SM-S938U

Additional Model(s):

SM-S938U1

EUT Type:

Portable Handset

Frequency Range:

5925 - 6425MHz and 6525 - 6875MHz

Modulation Type:

OFDMA

FCC Classification:

15E 6GHz Very Low Power Device (6VL)

FCC Rule Part(s):

Part 15 Subpart E (15.407)

Test Procedure(s):

ANSI C63.10-2013, KDB 987594 D02 v03,
KDB 648474 D03 v01r04

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1M2408260067-33-R1.A3L) supersedes and replaces the previously issued test report (S/N: 1M2408260067-33.A3L) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



RJ Ortanez
Executive Vice President



FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 1 of 124

T A B L E O F C O N T E N T S

1	INTRODUCTION.....	5
1.1	Scope	5
1.2	Element Test Location	5
1.3	Test Facility / Accreditations	5
2	PRODUCT INFORMATION	6
2.1	Equipment Description.....	6
2.2	Device Capabilities.....	6
2.3	Antenna Description.....	10
2.4	Test Configuration.....	10
2.5	Software and Firmware	10
2.6	EMI Suppression Device(s) / Modifications	10
3	DESCRIPTION OF TESTS	11
3.1	Evaluation Procedure.....	11
3.2	AC Line Conducted Emissions	11
3.3	Radiated Emissions	12
3.4	Environmental Conditions	12
4	ANTENNA REQUIREMENTS	13
5	MEASUREMENT UNCERTAINTY	14
6	TEST EQUIPMENT CALIBRATION DATA.....	15
7	TEST RESULTS	16
7.1	Summary.....	16
7.2	26dB Bandwidth Measurement.....	18
7.2.1	MIMO Antenna-1 Bandwidth Measurements - (Partial Tones).....	21
7.2.2	MIMO Antenna-1 Bandwidth Measurements - (Full Tones)	26
7.2.3	MIMO Antenna-2 Bandwidth Measurements – (Partial Tones)	29
7.2.4	MIMO Antenna-2 Bandwidth Measurements – (Full Tones)	34
7.3	UNII Output Power Measurement.....	37
7.4	Maximum Power Spectral Density	56
7.4.1	MIMO Antenna-1 Power Spectral Density Measurements	59
7.4.2	MIMO Antenna-2 Power Spectral Density Measurements	66
7.5	In-Band Emissions	74
7.5.1	MIMO Antenna-1 In-Band Emission Measurements	77
7.5.2	MIMO Antenna-2 In-Band Emission Measurements	84
7.6	Contention Based Protocol	91
7.6.1	AWGN Plots.....	94
7.6.2	CBP Timing Plots.....	95
7.6.3	Channel Move Plots.....	99
7.7	Radiated Emission Measurements	102
7.7.1	MIMO Radiated Spurious Emission Measurements (26 Tones)	106

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 2 of 124

7.7.2	MIMO Radiated Spurious Emission Measurements (242 Tones)	110
7.7.3	MIMO Radiated Band Edge Measurements (20MHz BW – Partial Tone – 106T).....	114
7.7.4	MIMO Radiated Band Edge Measurements (20MHz BW – MRU – 106+26T).....	115
7.7.5	MIMO Radiated Band Edge Measurements (20MHz BW – Full Tone – 242T)	116
7.7.6	MIMO Radiated Band Edge Measurements (40MHz BW – Full Tone – 484T)	117
7.7.7	MIMO Radiated Band Edge Measurements (40MHz BW – Full Tone – 484T)	117
7.7.8	MIMO Radiated Band Edge Measurements (80MHz BW – Full Tone – 996T)	118
7.7.9	MIMO Radiated Band Edge Measurements (80MHz BW – MRU – 484+242T).....	119
7.7.10	MIMO Radiated Band Edge Measurements (160MHz BW – Full Tone – 2x996T)	120
7.7.11	MIMO Radiated Band Edge Measurements (160MHz BW – MRU – 996+484T).....	121
7.7.12	MIMO Radiated Band Edge Measurements (320MHz BW – Full Tone – 4*996T).....	122
7.7.13	MIMO Radiated Band Edge Measurements (320MHz BW – MRU – 3*996+484T)	123
8	CONCLUSION	124

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 3 of 124

MEASUREMENT REPORT

Channel Bandwidth [MHz]	UNII Band	Tx Frequency [MHz]	Antenna-1		Antenna-2		MIMO	
			Max. Power [mW]	Max. Power [dBm]	Max. Power [mW]	Max. Power [dBm]	Max. Power [mW]	Max. Power [dBm]
20	5	5935 - 6415	1.00	0.01	1.10	0.42	3.92	5.93
	7	6535 - 6875	0.88	-0.56	0.82	-0.87	3.28	5.16
40	5	5965 - 6405	1.97	2.95	2.18	3.39	7.64	8.83
	7	6565 - 6845	1.77	2.47	1.78	2.51	6.98	8.44
80	5	5985 - 6385	3.71	5.69	4.36	6.39	15.00	11.76
	7	6545 - 6865	3.49	5.43	3.13	4.95	12.68	11.03
160	5	6025 - 6345	3.92	5.93	4.47	6.50	17.10	12.33
	7	6665 - 6825	3.52	5.47	3.19	5.04	13.46	11.29
320	5	6105 - 6265	3.74	5.73	4.01	6.03	16.60	12.20
	7	6585 - 6745	3.41	5.33	3.18	5.02	12.33	10.91

EUT Overview - EIRP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 4 of 124

1 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Test Location

These measurement tests were conducted at the Element laboratory located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at Element lab located in Columbia, MD 21046, U.S.A.

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Washington DC LLC facility is a registered (2451B) test laboratory with the site description on file with ISED.
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

Measurements were performed at Element located in Morgan Hill, CA 95037, U.S.A. ("CA")

- Element is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element facility is a registered (22831) test laboratory with the site description on file with ISED

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 5 of 124

2 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Electronics Co., Ltd. Portable Handset FCC: A3LSMS938U**. The test data contained in this report pertains only to the emissions due to the EUT's UNII transmitter while operating in the 6GHz band in very low power (VLP) mode.

Test Device Serial No.: 2054M, 2284M, 1150M, 1292M, 1182M, 1250M, 2066M, 1295M, 1259M, 1258M

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, Multi-band 5G NR (FR1 and FR2), 802.11b/g/n/ax/be WLAN, 802.11a/n/ac/ax/be UNII (5GHz and 6GHz), Bluetooth (1x, EDR, LE), NFC, Wireless Power Transfer, UWB

Band 5		Band 7	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
2	5935	117	6535
:	:	:	:
45	6175	149	6695
:	:	:	:
93	6415	185	6875

Table 2-1. 802.11ax/be (20MHz) Frequency / Channel Operations

Band 5		Band 7	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
3	5965	123	6565
:	:	:	:
43	6165	155	6725
:	:	:	:
91	6405	179	6845

Table 2-2. 802.11ax/be (40MHz BW) Frequency / Channel Operations

Band 5		Band 7	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
7	5985	119	6545
:	:	:	:
39	6145	151	6705
:	:	:	:
87	6385	183	6865

Table 2-3. 802.11ax/be (80MHz BW) Frequency / Channel Operations

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 6 of 124

Band 5

Ch.	Frequency (MHz)
15	6025
:	:
47	6185
:	:
79	6345

Band 7

Ch.	Frequency (MHz)
143	6665
:	:
175	6825

Table 2-4. 802.11ax/be (160MHz BW) Frequency / Channel Operations

Band 5

Ch.	Frequency (MHz)
31	6105
63	6265

Band 7

Ch.	Frequency (MHz)
127	6585
159	6745

Table 2-5. 802.11be (320MHz BW) Frequency / Channel Operations

Notes:

- 6GHz NII operation is possible in 20MHz, 40MHz, 80MHz, 160MHz, and 320MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section B)2)b) of ANSI C63.10-2013. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 7 of 124

Target Maximum Average Conducted Powers / Maximum Achievable Duty Cycles															
Band	Bandwidth	Tone Type	Tone Size	ANT1				ANT2				MIMO (1+2)			
				Duty Cycle [%]	Pulse Width	Period	Radiated DCCF [dB]	Duty Cycle [%]	Pulse Width	Period	Radiated DCCF [dB]	Duty Cycle [%]	Pulse Width	Period	Radiated DCCF [dB]
6GHz	20MHz	RU	26T	98.05	5.030	5.130	N/A	99.54	4.578	4.599	N/A	99.15	2.344	2.364	N/A
			52T	99.54	4.565	4.586	N/A	99.54	4.563	4.584	N/A	99.19	2.341	2.360	N/A
			106T	99.08	2.484	2.507	N/A	99.20	2.488	2.508	N/A	98.56	1.300	1.319	N/A
			242T	98.07	1.118	1.140	N/A	98.33	1.121	1.140	N/A	97.07	0.617	0.635	0.13
		MRU	52+26T	99.40	3.499	3.520	N/A	99.43	3.500	3.520	N/A	98.96	1.808	1.827	N/A
			106+26T	98.97	2.027	2.048	N/A	99.02	2.027	2.047	N/A	98.35	1.070	1.088	N/A
	40MHz	RU	26T	99.43	4.572	4.598	N/A	99.56	4.575	4.595	N/A	99.24	2.345	2.363	N/A
			52T	99.52	4.562	4.584	N/A	99.52	4.563	4.585	N/A	99.24	2.341	2.359	N/A
			106T	99.12	2.473	2.495	N/A	99.20	2.488	2.508	N/A	98.63	1.300	1.318	N/A
			242T	98.25	1.120	1.140	N/A	98.33	1.120	1.139	N/A	97.21	0.617	0.635	0.12
		MRU	484T	99.15	2.105	2.123	N/A	98.12	1.095	1.116	N/A	97.15	0.606	0.624	0.13
			52+26T	99.29	3.495	3.520	N/A	99.46	3.500	3.519	N/A	99.01	1.808	1.826	N/A
	80MHz	RU	106+26T	99.12	2.027	2.045	N/A	99.07	2.027	2.046	N/A	98.44	1.070	1.087	N/A
			26T	99.50	4.572	4.595	N/A	99.54	4.574	4.595	N/A	99.24	2.345	2.363	N/A
			52T	99.45	4.560	4.585	N/A	99.59	4.566	4.585	N/A	99.24	2.342	2.360	N/A
			106T	98.96	2.481	2.507	N/A	99.20	2.479	2.499	N/A	98.63	1.299	1.317	N/A
			242T	98.07	1.119	1.141	N/A	98.33	1.120	1.139	N/A	97.19	0.616	0.634	0.12
			484T	99.06	2.102	2.122	N/A	99.06	2.102	2.122	N/A	95.26	0.357	0.375	0.21
		MRU	996T	99.06	2.003	2.022	N/A	98.11	1.037	1.057	N/A	95.26	0.357	0.375	0.21
			52+26T	99.40	3.498	3.519	N/A	99.43	3.499	3.519	N/A	99.01	1.808	1.826	N/A
			106+26T	98.97	2.024	2.045	N/A	99.02	2.027	2.047	N/A	98.44	1.070	1.087	N/A
			484+242T	98.54	1.420	1.441	N/A	98.54	1.420	1.441	N/A	96.35	0.462	0.480	0.16
	160MHz	RU	26T	99.41	4.561	4.588	N/A	99.46	4.572	4.597	N/A	99.24	2.345	2.363	N/A
			52T	99.50	4.563	4.586	N/A	99.48	4.565	4.589	N/A	99.24	2.341	2.359	N/A
			106T	99.04	2.485	2.509	N/A	99.12	2.487	2.509	N/A	98.63	1.300	1.318	N/A
			242T	98.24	1.119	1.139	N/A	98.24	1.119	1.139	N/A	97.20	0.617	0.635	0.12
			484T	99.10	2.102	2.121	N/A	99.06	2.103	2.123	N/A	95.23	0.358	0.375	0.21
			996T	98.11	1.037	1.057	N/A	98.11	1.038	1.058	N/A	95.18	0.358	0.376	0.21
		MRU	2x996T	98.10	1.033	1.053	N/A	98.20	1.034	1.053	N/A	95.13	0.353	0.372	0.22
			52+26T	99.56	4.550	4.570	N/A	99.46	3.500	3.519	N/A	99.01	1.808	1.826	N/A
			106+26T	99.54	4.551	4.572	N/A	99.07	2.027	2.046	N/A	98.35	1.070	1.088	N/A
			484+242T	97.50	809.600	830.400	0.11	98.54	1.421	1.442	N/A	96.23	0.462	0.481	0.17
			996+484T	98.61	1.422	1.442	N/A	98.49	1.373	1.394	N/A	96.16	0.448	0.466	0.17
			966+484+242T	99.58	5.448	5.471	N/A	99.65	5.452	5.471	N/A	99.65	5.446	5.465	N/A
	320MHz	RU	26T	99.56	4.571	4.591	N/A	99.24	4.574	4.609	N/A	99.24	2.345	2.363	N/A
			52T	99.48	4.562	4.586	N/A	99.43	4.560	4.586	N/A	99.24	2.341	2.359	N/A
			106T	99.04	2.485	2.509	N/A	99.28	2.489	2.507	N/A	98.63	1.300	1.318	N/A
			242T	98.07	1.116	1.138	N/A	100.36	1.118	1.114	N/A	97.18	0.617	0.634	0.12
			484T	99.01	2.101	2.122	N/A	99.06	2.102	2.122	N/A	95.26	0.358	0.376	0.21
			996T	98.02	1.037	1.058	N/A	98.20	1.038	1.057	N/A	95.23	0.358	0.376	0.21
			2x996T	98.00	1.030	1.051	N/A	97.00	595.200	613.600	0.13	95.02	0.353	0.372	0.22
			4x996T	98.18	1.027	1.046	N/A	98.28	1.028	1.046	N/A	96.90	0.569	0.588	0.14
		MRU	52+26T	99.29	3.499	3.524	N/A	99.29	3.496	3.521	N/A	98.96	1.808	1.827	N/A
			106+26T	99.46	3.500	3.519	N/A	99.07	2.026	2.045	N/A	98.34	1.069	1.087	N/A
			484+242T	99.85	812.000	813.200	N/A	98.68	1.423	1.442	N/A	96.25	0.462	0.480	0.17
			996+484T	97.71	784.000	802.400	0.10	99.22	2.670	2.691	N/A	96.05	0.447	0.466	0.18
			966+484+242T	99.54	5.449	5.474	N/A	99.63	5.455	5.475	N/A	99.67	5.451	5.469	N/A
			2x996+484T	97.95	846.300	864.000	0.09	98.60	1.618	1.641	N/A	96.30	0.479	0.497	0.16
			3x996T	97.48	712.000	730.400	0.11	98.46	1.345	1.366	N/A	95.67	0.411	0.429	0.19
			3x996+484T	98.40	1.170	1.189	N/A	99.13	2.272	2.292	N/A	97.18	0.641	0.660	0.12

Table 2-6. Measured Duty Cycles

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 8 of 124

2. The device employs MIMO technology. Below are the possible configurations.

WiFi Configurations		SISO		CDD		SDM	
		ANT1	ANT2	ANT1	ANT2	ANT1	ANT2
6 GHz	11ax	✓	✓	✓	✓	✓	✓
	11be	✓	✓	✓	✓	✓	✓

Table 2-7. Frequency / Channel Operations

✓ = Support; ✗ = NOT Support

SISO = Single Input Single Output

SDM = Spatial Diversity Multiplexing – MIMO function

CDD = Cyclic Delay Diversity - 2Tx Function

3. The device supports the following data rates (shown in Mbps):

MCS Index		Spatial Stream	OFDMA (802.11ax/be)																								OFDMA (802.11be)														
			26T						52T						106T						242T						484T						996T			2x996T			4x996T		
			0.8us GI	1.6us GI	3.2us GI	0.8us GI	1.6us GI	3.2us GI	0.8us GI	1.6us GI	3.2us GI	0.8us GI	1.6us GI	3.2us GI	0.8us GI	1.6us GI	3.2us GI	0.8us GI	1.6us GI	3.2us GI	0.8us GI	1.6us GI	3.2us GI	0.8us GI	1.6us GI	3.2us GI	0.8us GI	1.6us GI	3.2us GI	0.8us GI	1.6us GI	3.2us GI									
0	0	1	0.9	0.8	0.8	1.8	1.7	1.5	3.8	3.5	3.2	8.6	8.1	7.3	17.2	16.3	14.6	36	34	30.6	72.1	68.1	61.3	144.1	136.1	122.5															
1	1	1	1.8	1.7	1.5	3.5	3.3	3	7.5	7.1	6.4	17.2	16.3	14.6	34.4	32.5	29.3	72.1	68.1	61.3	144.1	136.1	122.5	288.2	272.2	245															
2	2	1	2.6	2.5	2.3	5.3	5	4.5	11.3	10.6	9.6	25.8	24.4	21.9	51.6	48.8	43.9	108.1	102.1	91.9	216.2	204.2	183.8	432.4	408.3	367.5															
3	3	1	3.5	3.3	3	7.1	6.7	6	15	14.2	12.8	34.4	32.5	29.3	68.8	65	58.5	144.1	136.1	122.5	288.2	272.2	245	576.5	544.4	490															
4	4	1	5.3	5	4.5	10.6	10	9	22.5	21.3	19.1	51.6	48.8	43.9	103.2	97.5	87.8	216.2	204.2	183.8	432.4	408.3	367.5	864.7	816.7	735															
5	5	1	7.1	6.7	6	14.1	13.3	12	30	28.3	25.5	68.8	65	58.5	137.6	130	117	288.2	272.2	245	576.5	544.4	490	1152.9	1088.9	980															
6	6	1	7.9	7.5	6.8	15.9	15	13.5	33.8	31.9	28.7	77.4	73.1	65.8	154.9	146.3	131.6	324.3	306.3	275.6	648.5	612.5	551.3	1297.1	1225	1102.5															
7	7	1	8.8	8.3	7.5	17.6	16.7	15	37.5	35.4	31.9	86	81.3	73.1	172.1	162.5	146.3	360.3	340.3	306.3	720.6	680.6	612.5	1441.2	1361.1	1225															
8	8	1	10.6	10	9	21.2	20	18	45	42.5	38.3	103.2	97.5	87.8	206.5	195	175.5	432.4	408.3	367.5	864.7	816.7	735	1729.4	1633.3	1470															
9	9	1	11.8	11.1	10	23.5	22.2	20	50	47.2	42.5	114.7	108.3	97.5	229.4	216.7	195	480.4	453.7	408.3	960.8	907.4	816.7	1921.6	1814.8	1633.3															
10	10	1	13.2	12.5	11.3	26.5	25	22.5	56.3	53.1	47.8	129	121.9	109.7	258.1	243.8	219.4	540.4	510.4	459.4	1080.9	1020.8	918.8	2161.8	2041.7	1837.5															
11	11	1	14.7	13.9	12.5	29.4	27.8	25	62.5	59	53.1	143.4	135.4	121.9	286.8	270.8	243.8	600.5	567.1	510.4	1201	1134.3	1020.8	2402	2268.5	2041.7															
12	12	1	15.9	15	13.5	31.8	30	27	67.5	63.8	57.4	154.9	146.3	131.6	309.7	292.5	263.3	648.5	612.5	551.3	1297.1	1225	1102.5	2594.1	2450	2205															
13	13	1	17.6	16.7	15	35.3	33.3	30	75	70.8	63.8	172.1	162.5	146.3	344.1	325	292.5	720.6	680.6	612.5	1441.2	1361.1	1225	2882.4	2722.2	2450															
0	0	2	1.8	1.7	1.5	3.5	3.3	3	7.5	7.1	6.4	17.2	16.3	14.6	34.4	32.5	29.3	72.1	68.1	61.3	144.1	136.1	122.5	288.2	272.2	245															
1	1	2	3.5	3.3	3	7.1	6.7	6	15	14.2	12.8	34.4	32.5	29.3	68.8	65	58.5	144.1	136.1	122.5	288.2	272.2	245	576.5	544.4	490															
2	2	2	5.3	5	4.5	10.6	10	9	22.5	21.3	19.1	51.6	48.8	43.9	103.2	97.5	87.8	216.2	204.2	183.8	432.4	408.3	367.5	864.7	816.7	735															
3	3	2	7.1	6.7	6	14.1	13.3	12	30	28.3	25.5	68.8	65	58.5	137.6	130	117	288.2	272.2	245	576.5	544.4	490	1152.9	1088.9	980															
4	4	2	10.6	10	9	21.2	20	18	45	42.5	38.3	103.2	97.5	87.8	206.5	195	175.5	432.4	408.3	367.5	864.7	816.7	735	1729.4	1633.3	1470															
5	5	2	14.1	13.3	12	28.2	26.7	24	60	56.7	51	137.6	130	117	275.3	260	234	576.5	544.4	490	1152.9	1088.9	980	2305.9	2177.8	1960															
6	6	2	15.9	15	13.5	31.8	30	27	67.5	63.8	57.4	154.9	146.3	131.6	309.7	292.5	263.3	648.5	612.5	551.3	1297.1	1225	1102.5	2594.1	2450	2205															
7	7	2	17.6	16.7	15	35.3	33.3	30	75	70.8	63.8	172.1	162.5	146.3	344.1	325	292.5	720.6	680.6	612.5	1441.2	1361.1	1225	2882.4	2722.2	2450															
8	8	2	21.2	20	18	42.4	40	36	90	85	76.5	206.5	195	175.5	412.9	390	351	864.7	816.7	735	1729.4	1633.3	1470	3458.8	3266.7	2940															
9	9	2	23.5	22.2	20	47.1	44.4	40	100	94.4	85	229.4	216.7	195	458.8	433.3	390	960.8	907.4	816.7	1921.6	1814.8	1633.3	3843.1	3629.6	3266.7															
10	10	2	26.5	25	22.5	52.9	50	45	112.5	106.3	95.6	258.1	243.8	219.4	516.2	487.5	438.8	1080.9	1020.8	918.8	2161.8	2041.7	1837.5	4323.5	4083.3	3675															
11	11	2	29.4	27.8	25	58.8	55.6	50	125	118.1	106.3	286.8	270.8	243.8	573.5	541.7	487.5	1201	1134.3	1020.8	2402	2268.5	2041.7	4803.9	4537	4083.3															
12	12	2	31.8	30	27	63.5	60	54	135	127.5	114.8	309.7	292.5	263.3	619.4	585	526.5	1297.1	1225	1102.5	2594.1	2450	2205	5188.2	4900	4410															
13	13	2	35.3	33.3	30	70.6	66.7	60	150	141.7	127.5	344.1	325	292.5	688.2	650	585	1441.2	1361.1	1225	2882.4	2722.2	2450	5764.7	5444.4	4900															

Table 2-8. Supported Data Rates

4. The device supports either Standard Power (SP) or Low Power Indoor (LPI) or Very Low Power (VLP) operation in the following UNII bands:

UNII Band	Standard Power (SP)	Low Power Indoor (LPI)	Very Low Power (VLP)
UNII 5	✓	✓	✓
UNII 6	✗	✓	✗
UNII 7	✓	✓	✓
UNII 8	✗	✓	✗

Table 2-9. Power Operation

✓ = Support; ✗ = NOT Support

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 9 of 124

2.3 Antenna Description

The following antenna gains were used for the testing.

Frequency	Ant1 Peak Gain [dBi]	Ant2 Peak Gain [dBi]	Directional Gain [dBi]
5925 MHz	-6.12	-5.30	-2.69
6025 MHz	-6.49	-5.01	-2.71
6125 MHz	-6.22	-5.37	-2.77
6225 MHz	-6.31	-6.15	-3.22
6325 MHz	-5.91	-5.38	-2.63
6425 MHz	-5.88	-5.84	-2.85
6525 MHz	-6.52	-6.25	-3.37
6625MHz	-6.69	-6.56	-3.61
6725MHz	-6.97	-6.80	-3.87
6825MHz	-6.85	-6.82	-3.82
6925MHz	-6.97	-6.41	-2.09
7025MHz	-6.50	-6.03	-3.44
7125MHz	-6.49	-6.84	-3.65

Table 2-10 Antenna Peak Gain per Frequency

	Ant1 Peak Gain [dBi]	Ant2 Peak Gain [dBi]	Directional Gain [dBi]
5925 – 6425 MHz	-5.91	-5.38	-2.63
6425 – 6525 MHz	-5.88	-5.84	-2.85
6525 – 6875 MHz	-6.52	-6.25	-3.37
6875 – 7125 MHz	-6.50	-6.03	-3.25

Table 2-11. Antenna Peak Gain

2.4 Test Configuration

ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5 and 7.6 for antenna port conducted emissions test setups.

This device supports operation in very low power mode limited to the 5925 - 6425MHz and 6525 - 6875MHz bands.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on an authorized wireless charging pad (WCP) Model: NQ-WC-06 while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

2.5 Software and Firmware

The test was conducted with firmware version S938USQUOAXJ3 installed on the EUT.

2.6 EMI Suppression Device(s) / Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 10 of 124

3 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 987594 D02 to v03 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1-meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst-case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 11 of 124

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3-meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01 v01r01.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 12 of 124

4 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 13 of 124

5 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Contention Based Protocol Conducted Measurements	0.86
Conducted Bench Top Measurements	1.13
Line Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

Table 5-1. Measurement Uncertainty Budget – MD

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.65
Line Conducted Disturbance	2.71
Radiated Disturbance (<30MHz)	4.06
Radiated Disturbance (30MHz - 1GHz)	4.30
Radiated Disturbance (1 - 18GHz)	4.78
Radiated Disturbance (>18GHz)	4.79

Table 5-2. Measurement Uncertainty Budget – CA

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 14 of 124

6 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	WL25-1	Conducted Cable Set (25GHz)	4/2/2024	Annual	4/2/2025	WL25-1
-	WL25-2	Conducted Cable Set (25GHz)	4/2/2024	Annual	4/2/2025	WL25-2
-	WL40-1	Conducted Cable Set (40GHz)	4/2/2024	Annual	4/2/2025	WL40-1
-	AP1-002	EMC Cable and Switch System	4/2/2024	Annual	4/2/2025	AP1-002
-	ETS-001	EMC Cable and Switch System	4/2/2024	Annual	4/2/2025	ETS-001
-	ETS-002	EMC Cable and Switch System	4/2/2024	Annual	4/2/2025	ETS-002
-	MD 1M 18-40	EMC Cable and Switch System	4/2/2024	Annual	4/2/2025	MD 1M 18-40
Anritsu	MA24408A	Microwave Peak Power Sensor	5/21/2024	Annual	5/21/2025	11675
Anritsu	MA24408A	Microwave Peak Power Sensor	4/10/2024	Annual	4/10/2025	12798
ETS-Lindgren	3116C	Horn Antenna (18-40GHz)	2/27/2023	Biennial	2/27/2025	218893
Rohde & Schwarz	TC-TA18	Vivaldi Antenna	2/23/2023	Biennial	2/23/2025	26040036
Rohde & Schwarz	FSW26	Signal and Spectrum Analyzer (26.5GHz)	3/8/2024	Annual	3/8/2025	103187
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	9/25/2023	Annual	9/25/2024	100342
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	9/11/2023	Annual	9/11/2024	100348
Rohde & Schwarz	ESW44	EMI Test Receiver (44GHz)	4/5/2024	Annual	4/5/2025	101716
Pasternak	NMLC-2	EMI Test Receiver (2Hz to 44GHz)	4/2/2024	Annual	4/2/2025	NMLC-2
Rohde & Schwarz	ENV216	Two-Line V-Network	1/31/2023	Biennial	1/31/2025	101379
Keysight Technologies	N9030A	PXA Signal Analyzer (44GHz)	4/9/2024	Annual	4/9/2025	MY52350166
Keysight Technologies	N9020A	MXA Signal Analyzer	4/11/2024	Annual	4/11/2025	MY54500644
Keysight Technologies	N9030A	PXA Signal Analyzer	2/29/2024	Annual	3/1/2025	MY55410501
Keysight Technologies	N9030B	PXA Signal Analyzer, Multi-touch	9/19/2024	Annual	9/19/2025	MY57141001
Sunol	JB6	JB6 Antenna	3/2/2023	Biennial	3/2/2025	A082816
Sunol	JB5	Bi-Log Antenna (20M-5GHz)	9/11/2024	Biennial	9/11/2026	A051107
Rohde & Schwarz	SMW200A	Vector Signal Generator	4/4/2024	Annual	4/4/2025	109456

Table 6-1. Annual Test Equipment Calibration Schedule – MD

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
ETS-Lindgren	3117	Double Ridged Guide Antenna (1-18 GHz)	4/9/2024	Annual	4/9/2025	00218555
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz - 18GHz)	5/29/2024	Annual	11/29/2024	102132
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz - 18GHz)	8/14/2024	Annual	8/15/2025	101648
Rohde & Schwarz	FSV40	Signal Analyzer (10Hz-40GHz)	5/29/2024	Annual	5/29/2025	101619
Rohde & Schwarz	ESW44	EMI Test Receiver	5/1/2024	Annual	5/1/2025	101867
Rohde & Schwarz	FSW67	Signal and Spectrum Analyzer (2Hz-67GHz)	7/5/2024	Annual	7/5/2025	101366
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz - 8GHz)	7/3/2024	Annual	7/3/2025	102356
Schwarzbeck	VULB 9162	Bilog Antenna (30MHz - 6GHz)	4/29/2024	Annual	4/29/2025	00304

Table 6-2. Annual Test Equipment Calibration Schedule – CA

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 15 of 124

7 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMS938U
 FCC Classification: 15E 6GHz Very Low Power Device (6VL)

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference	Test Lab Location
2.1046, 15.407(a)(12)	Maximum Conducted Output Power	N/A	CONDUCTED	PASS	Section 7.3	MD
15.407(a)(9)	Maximum Radiated Output Power	< 14dBm e.i.r.p.		PASS	Section 7.3	MD
2.1049, 15.407(a)(11)	Occupied Bandwidth/ 26dB Bandwidth	99% of the occupied bandwidth of any channel must be contained within each of its respective U-NII sub bands. The maximum transmitter channel bandwidth for U-NII devices in the 5.925-7.125 GHz band is 320 megahertz.		PASS	Section 7.2	MD
15.407(a)(9)	Maximum Power Spectral Density	< -5dBm/MHz e.i.r.p.		PASS	Section 7.4	MD
15.407(b)(7)	In-Band Emissions	EUT must meet the limits detailed in 15.407(b)(7)		PASS	Section 7.5	MD
15.407(d)(6)	Contention Based Protocol	EUT must detect AWGN signal with 90% (or better) certainty	RADIATED	PASS	Section 7.6	MD
15.407(d)(10)	Transmit Power Control	Must operate at least 6 dB below the maximum EIRP power spectral density (PSD) value of -5 dBm/MHz		PASS	Please see WiFi 6GHz (6VL) OFDM report	MD
15.407(b)(6)	Undesirable Emissions	< -27dBm/MHz e.i.r.p. outside of the 5.925 – 7.125GHz band		PASS	Section 7.7	CA
15.205, 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209		PASS	Section 7.7	CA
15.407(b)(9)	AC Conducted Emissions (150kHz – 30MHz)	< FCC 15.207 limits	LINE CONDUCTED	PASS	Please see WiFi 6GHz (6VL) OFDM report	MD

Table 7-1. Summary of Test Results

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 16 of 124

Notes:

- 1) All channels, modes, and modulations/data rates were investigated among all UNII bands. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "UNII Automation," Version 4.7.
- 5) For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "Chamber Automation," Version 1.3.1.
- 6) 802.11ax OFDMA testing was performed for all signal tone configurations as specified by the 802.11ax standard. Worst case results are determined and reported per the guidance provided at the October 2018 TCB Workshop.
- 7) Only one RU index could be selected at a time, so no contiguous or non-contiguous RUs were considered for testing.

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 17 of 124

7.2 26dB Bandwidth Measurement

Test Overview and Limit

The bandwidth at 26dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013, and at the appropriate frequencies. The spectrum analyzer's bandwidth measurement function is configured to measure the 26dB bandwidth.

Test Procedure Used

ANSI C63.10-2013 – Section 12.4

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 26$. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = max hold

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes

1. All cases were investigated; a subset of the taken plots were included to represent relevant settings and measurements.
2. In this section, the bandwidth data tables include mainly the 26dB bandwidth measurements. In case of 320MHz operation, an occupied bandwidth measurement was included in the table to demonstrate compliance. Thus, all measurements in the tables are 26dB bandwidth measurements except for the 320MHz bandwidth cases which are occupied bandwidth measurements.

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 18 of 124

	Frequency [MHz]	Channel	802.11 MODE	Antenna-1 26dB Bandwidth [MHz]	Antenna-2 26dB Bandwidth [MHz]
Band 5	5935	2	be (20MHz)	20.38	20.12
	6175	45	be (20MHz)	20.58	19.97
	6415	93	be (20MHz)	20.41	20.08
	5965	3	be (40MHz)	23.16	24.63
	6165	43	be (40MHz)	23.75	24.08
	6405	91	be (40MHz)	25.36	23.85
	5985	7	be (80MHz)	32.29	33.36
	6145	39	be (80MHz)	32.27	32.04
	6385	87	be (80MHz)	32.11	30.82
	6025	15	be (160MHz)	34.33	35.81
	6185	47	be (160MHz)	37.42	39.88
	6345	79	be (160MHz)	37.04	38.75
	6105	31	be (320MHz)	46.54	47.73
	6265	63	be (320MHz)	46.57	47.27
Band 7	6695	117	be (20MHz)	20.34	20.19
	6695	149	be (20MHz)	20.16	20.23
	6875	185	be (20MHz)	19.96	20.32
	6565	123	be (40MHz)	23.13	24.12
	6685	155	be (40MHz)	23.91	23.83
	6845	179	be (40MHz)	22.90	24.17
	6545	119	be (80MHz)	33.02	33.54
	6705	151	be (80MHz)	32.66	32.36
	6865	183	be (80MHz)	33.02	33.18
	6665	143	be (160MHz)	38.41	37.60
	6825	175	be (160MHz)	39.93	40.29

Table 7-2. 26dB Bandwidth Results – 26 Tones – VLP

	Frequency [MHz]	Channel	802.11 MODE	MRU Configuration	Antenna-1 26dB Bandwidth [MHz]	Antenna-2 26dB Bandwidth [MHz]	Antenna-1 Occupied Bandwidth [MHz]	Antenna-2 Occupied Bandwidth [MHz]
Band 5	6145	45	be (80MHz)	52+26T	18.85	18.52	-	-
	6175	45	be (20MHz)	106+26T	20.38	20.23	-	-
	6145	39	be (80MHz)	484+242T	89.63	89.93	-	-
	6185	47	be (160MHz)	996+484T	173.83	179.97	-	-
	6105	31	be (320MHz)	2x996+484T	-	-	237.69	237.38
	6105	31	be (320MHz)	3x996T	-	-	316.21	317.12
	6105	31	be (320MHz)	3x996+484T	-	-	316.04	315.84
Band 7	6695	149	be (20MHz)	52+26T	18.67	18.97	-	-
	6695	149	be (20MHz)	106+26T	20.46	20.33	-	-
	6705	151	be (80MHz)	484+242T	88.73	89.62	-	-
	6665	143	be (160MHz)	996+484T	176.72	177.15	-	-

Table 7-3. 26dB Bandwidth Results – MRU – VLP


FCC ID: A3LSMS938U	MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset		Page 19 of 124

	Frequency [MHz]	Channel	802.11 MODE	Antenna-1 26dB Bandwidth [MHz]	Antenna-2 26dB Bandwidth [MHz]	Antenna-1 Occupied Bandwidth [MHz]	Antenna-2 Occupied Bandwidth [MHz]
Band 5	5935	2	be (20MHz)	21.77	21.61	-	-
	6175	45	be (20MHz)	21.69	20.96	-	-
	6415	93	be (20MHz)	21.87	21.27	-	-
	5965	3	be (40MHz)	42.05	42.31	-	-
	6165	43	be (40MHz)	42.23	42.66	-	-
	6405	91	be (40MHz)	42.76	42.87	-	-
	5985	7	be (80MHz)	89.98	93.14	-	-
	6145	39	be (80MHz)	90.27	95.69	-	-
	6385	87	be (80MHz)	90.84	94.30	-	-
	6025	15	be (160MHz)	176.35	179.46	-	-
	6185	47	be (160MHz)	182.91	181.83	-	-
	6345	79	be (160MHz)	178.75	177.09	-	-
	6105	31	be (320MHz)	-	-	315.78	315.21
	6265	63	be (320MHz)	-	-	314.59	314.88
Band 7	6695	117	be (20MHz)	21.62	21.29	-	-
	6695	149	be (20MHz)	21.49	21.84	-	-
	6875	185	be (20MHz)	21.24	21.47	-	-
	6565	123	be (40MHz)	42.30	42.88	-	-
	6685	155	be (40MHz)	43.11	42.45	-	-
	6845	179	be (40MHz)	42.57	43.18	-	-
	6545	119	be (80MHz)	91.08	94.09	-	-
	6705	151	be (80MHz)	90.09	90.93	-	-
	6865	183	be (80MHz)	89.49	93.82	-	-
	6665	143	be (160MHz)	180.65	180.32	-	-

Table 7-4. 26dB Bandwidth Results – Full Tones – VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 20 of 124

7.2.1 MIMO Antenna-1 Bandwidth Measurements - (Partial Tones)




Plot 7-1. 26dB Bandwidth Plot MIMO ANT1 (20MHz 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 45) - VLP




Plot 7-2. 26dB Bandwidth Plot MIMO ANT1 (40MHz 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 43) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 21 of 124




Plot 7-3. 26dB Bandwidth Plot MIMO ANT1 (80MHz 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 39) - VLP




Plot 7-4. 26dB Bandwidth Plot MIMO ANT1 (160MHz 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 47) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 22 of 124




Plot 7-5. 26dB Bandwidth Plot MIMO ANT1 (320MHz 802.11be (26 Tones) (UNII Band 5) – Ch. 31) - VLP




Plot 7-6. 26dB Bandwidth Plot MIMO ANT1 (20MHz 802.11be (106+26 Tones) (UNII Band 5) – Ch. 45) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 23 of 124




Plot 7-7. 26dB Bandwidth Plot MIMO ANT1 (80MHz 802.11be (484+242 Tones) (UNII Band 5) – Ch. 39) VLP



Plot 7-8. 26dB Bandwidth Plot MIMO ANT1 (160MHz 802.11be (996+484 Tones) (UNII Band 5) – Ch. 47) VLP


FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 24 of 124




Plot 7-9. 26dB Bandwidth Plot MIMO ANT1 (320MHz 802.11be (3*996+484 Tones) (UNII Band 5) – Ch. 31) VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 25 of 124

7.2.2 MIMO Antenna-1 Bandwidth Measurements - (Full Tones)




Plot 7-10. 26dB Bandwidth Plot MIMO ANT1 (20MHz 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 45) - VLP




Plot 7-11. 26dB Bandwidth Plot MIMO ANT1 (40MHz 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 43) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 26 of 124




Plot 7-12. 26dB Bandwidth Plot MIMO ANT1 (80MHz 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 39) - VLP



Plot 7-13. 26dB Bandwidth Plot MIMO ANT1 (160MHz 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 47) - VLP


FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 27 of 124




Plot 7-14. 26dB Bandwidth Plot MIMO ANT1 (320MHz 802.11be (Full Tones) (UNII Band 5) – Ch. 31) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 28 of 124

7.2.3 MIMO Antenna-2 Bandwidth Measurements – (Partial Tones)




Plot 7-15. 26dB Bandwidth Plot MIMO ANT2 (20MHz 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 45) - VLP




Plot 7-16. 26dB Bandwidth Plot MIMO ANT2 (40MHz 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 43) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 29 of 124




Plot 7-17. 26dB Bandwidth Plot MIMO ANT2 (80MHz 802.11ax/be (26 Tones) (UNII Band 5) - Ch. 39) - VLP




Plot 7-18. 26dB Bandwidth Plot MIMO ANT2 (160MHz 802.11ax/be (26 Tones) (UNII Band 5) - Ch. 47) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 30 of 124




Plot 7-19. 26dB Bandwidth Plot MIMO ANT2 (320MHz 802.11be (26 Tones) (UNII Band 5) – Ch. 31) - VLP




Plot 7-20. 26dB Bandwidth Plot MIMO ANT2 (20MHz 802.11be (106+26 Tones) (UNII Band 5) – Ch. 45) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 31 of 124




Plot 7-21. 26dB Bandwidth Plot MIMO ANT2 (80MHz 802.11be (484+242 Tones) (UNII Band 5) – Ch. 39) VLP



Plot 7-22. 26dB Bandwidth Plot MIMO ANT2 (160MHz 802.11be (996+484 Tones) (UNII Band 5) – Ch. 47) VLP


FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 32 of 124




Plot 7-23. 26dB Bandwidth Plot MIMO ANT2 (320MHz 802.11be (3*996+484 Tones) (UNII Band 5) – Ch. 31) VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 33 of 124

7.2.4 MIMO Antenna-2 Bandwidth Measurements – (Full Tones)




Plot 7-24. 26dB Bandwidth Plot MIMO ANT2 (20MHz 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 45) - VLP




Plot 7-25. 26dB Bandwidth Plot MIMO ANT2 (40MHz 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 43) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 34 of 124




Plot 7-26. 26dB Bandwidth Plot MIMO ANT2 (80MHz 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 39) - VLP



Plot 7-27. 26dB Bandwidth Plot MIMO ANT2 (160MHz 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 47) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 35 of 124



Plot 7-28. 26dB Bandwidth Plot MIMO ANT2 (320MHz 802.11be (Full Tones) (UNII Band 5) – Ch. 31) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 36 of 124

7.3 UNII Output Power Measurement

Test Overview and Limits

A transmitter antenna terminal of the EUT is connected to the input of an RF pulse power sensor. Measurement is made using a broadband average power meter while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013, and at the appropriate frequencies.

For very low power devices operating in the 5.925-6.425 GHz and 6.525-6.875 GHz bands, the maximum power spectral density must not exceed -5 dBm e.i.r.p in any 1-megahertz band and the maximum e.i.r.p must not exceed 14 dBm.

Test Procedure Used

ANSI C63.10-2013 – Section 12.3.3.2 Method PM-G

ANSI C63.10-2013 – Section 14.2 Measure-and-Sum Technique

Test Settings

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-2. Test Instrument & Measurement Setup

Test Notes

None.

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 37 of 124

SISO Maximum Conducted Output Power Measurements (26 Tones)

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)			Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index						
					0	4	8				
	5	5935	2	26T	-4.04	-4.63	-5.08	-5.91	-9.95	14.0	-23.95
6175		45	26T	-4.47	-4.79	-4.04	-5.91	-9.95	14.0	-23.95	
6415		93	26T	-4.51	-4.58	-4.24	-5.91	-10.15	14.0	-24.15	
7	6535	117	26T	-4.22	-4.11	-4.04	-6.52	-10.56	14.0	-24.56	
	6695	149	26T	-4.36	-4.02	-4.22	-6.52	-10.54	14.0	-24.54	

Table 7-5. SISO ANT1 20MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power - VLP

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)			Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index						
					0	4	8				
	5	5935	2	26T	-4.07	-4.47	-4.24	-5.38	-9.45	14.0	-23.45
6175		45	26T	-4.07	-4.44	-4.11	-5.38	-9.45	14.0	-23.45	
6415		93	26T	-4.06	-4.29	-4.06	-5.38	-9.44	14.0	-23.44	
7	6535	117	26T	-4.35	-4.68	-4.29	-6.25	-10.54	14.0	-24.54	
	6695	149	26T	-4.60	-4.50	-4.52	-6.25	-10.75	14.0	-24.75	

Table 7-6. SISO ANT2 20MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 38 of 124

SISO Maximum Conducted Output Power Measurements (52 Tones)

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)			Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index						
					37	38	40				
	5	5935	2	52T	-1.73	-1.33	-1.73	-5.91	-7.24	14.0	-21.24
6175		45	52T	-1.98	-1.75	-1.45	-5.91	-7.36	14.0	-21.36	
6415		93	52T	-1.97	-1.73	-1.78	-5.91	-7.64	14.0	-21.64	
7	6535	117	52T	-1.53	-1.12	-1.04	-6.52	-7.56	14.0	-21.56	
	6695	149	52T	-1.24	-1.25	-1.04	-6.52	-7.56	14.0	-21.56	

Table 7-7. SISO ANT1 20MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power - VLP

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)			Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index						
					37	38	40				
	5	5935	2	52T	-1.17	-1.06	-1.29	-5.38	-6.44	14.0	-20.44
6175		45	52T	-1.48	-1.22	-1.06	-5.38	-6.44	14.0	-20.44	
6415		93	52T	-1.48	-1.14	-1.45	-5.38	-6.52	14.0	-20.52	
7	6535	117	52T	-1.60	-1.68	-1.45	-6.25	-7.70	14.0	-21.70	
	6695	149	52T	-1.68	-1.36	-1.57	-6.25	-7.61	14.0	-21.61	

Table 7-8. SISO ANT2 20MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 39 of 124

SISO Maximum Conducted Output Power Measurements (106 Tones)

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index					
					53	54				
		5935	2	106T	1.67	1.31	-5.91	-4.24	14.0	-18.24
		6175	45	106T	1.27	1.22	-5.91	-4.64	14.0	-18.64
		6415	93	106T	1.19	1.32	-5.91	-4.59	14.0	-18.59
	7	6535	117	106T	1.95	1.99	-6.52	-4.53	14.0	-18.53
		6695	149	106T	1.99	1.97	-6.52	-4.53	14.0	-18.53

Table 7-9. SISO ANT1 20MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power - VLP

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index					
					53	54				
7		5935	2	106T	1.83	1.67	-5.38	-3.55	14.0	-17.55
		6175	45	106T	1.47	1.33	-5.38	-3.91	14.0	-17.91
		6415	93	106T	1.50	1.40	-5.38	-3.88	14.0	-17.88
		6535	117	106T	1.01	1.06	-6.25	-5.19	14.0	-19.19
		6695	149	106T	1.25	1.31	-6.25	-4.94	14.0	-18.94

Table 7-10. SISO ANT2 20MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 40 of 124

SISO Maximum Conducted Output Power Measurements (242 Tones)

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)	Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index				
					61				
	5	5935	2	242T	5.50	-5.91	-0.41	14.0	-14.41
		6175	45	242T	5.92	-5.91	0.01	14.0	-13.99
		6415	93	242T	5.65	-5.91	-0.26	14.0	-14.26
	7	6535	117	242T	5.96	-6.52	-0.56	14.0	-14.56
		6695	149	242T	5.88	-6.52	-0.64	14.0	-14.64

Table 7-11. SISO ANT1 20MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power - VLP

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)	Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index				
					61				
	5	5935	2	242T	5.70	-5.38	0.32	14.0	-13.68
		6175	45	242T	5.75	-5.38	0.37	14.0	-13.63
		6415	93	242T	5.80	-5.38	0.42	14.0	-13.58
	7	6535	117	242T	5.38	-6.25	-0.87	14.0	-14.87
		6695	149	242T	5.05	-6.25	-1.20	14.0	-15.20

Table 7-12. SISO ANT2 20MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 41 of 124

SISO Maximum Conducted Output Power Measurements (484 Tones)

40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)	Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index				
					65				
	5	5965	3	484T	8.43	-5.91	2.52	14.0	-11.48
		6165	43	484T	8.86	-5.91	2.95	14.0	-11.05
		6405	91	484T	8.47	-5.91	2.56	14.0	-11.44
	7	6565	123	484T	8.99	-6.52	2.47	14.0	-11.53
		6725	155	484T	8.96	-6.52	2.44	14.0	-11.56
		6845	179	484T	8.87	-6.52	2.35	14.0	-11.65

Table 7-13. SISO ANT1 40MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power - VLP

40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)	Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index				
					65				
	5	5965	3	484T	8.49	-5.38	3.11	14.0	-10.89
		6165	43	484T	8.54	-5.38	3.16	14.0	-10.84
		6405	91	484T	8.77	-5.38	3.39	14.0	-10.61
	7	6565	123	484T	8.44	-6.25	2.19	14.0	-11.81
		6725	155	484T	8.36	-6.25	2.11	14.0	-11.89
		6845	179	484T	8.76	-6.25	2.51	14.0	-11.49

Table 7-14. SISO ANT2 40MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 42 of 124

SISO Maximum Conducted Output Power Measurements (996 Tones)

80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)	Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index				
					67				
	5	5985	7	996T	11.60	-5.91	5.69	14.0	-8.31
		6145	39	996T	11.01	-5.91	5.10	14.0	-8.90
		6385	87	996T	11.31	-5.91	5.40	14.0	-8.60
	7	6705	151	996T	11.95	-6.52	5.43	14.0	-8.57

Table 7-15. SISO ANT1 80MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power - VLP

80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)	Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index				
					67.00				
	5	5985	7	996T	11.33	-5.38	5.95	14.0	-8.05
		6145	39	996T	11.48	-5.38	6.10	14.0	-7.90
		6385	87	996T	11.77	-5.38	6.39	14.0	-7.61
	7	6705	151	996T	11.20	-6.25	4.95	14.0	-9.05

Table 7-16. SISO ANT2 80MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 43 of 124

SISO Maximum Conducted Output Power Measurements (2x996 Tones)

160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)	Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index				
					68				
	5	6025	15	2x996T	11.84	-5.91	5.93	14.0	-8.07
		6185	47	2x996T	11.01	-5.91	5.10	14.0	-8.90
		6345	79	2x996T	11.34	-5.91	5.43	14.0	-8.57
	7	6665	143	2x996T	11.99	-6.52	5.47	14.0	-8.53

Table 7-17. SISO ANT1 160MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power – VLP

160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)	Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index				
					68.00				
	5	6025	15	2x996T	11.57	-5.38	6.19	14.0	-7.81
		6185	47	2x996T	11.61	-5.38	6.23	14.0	-7.77
		6345	79	2x996T	11.88	-5.38	6.50	14.0	-7.50
	7	6665	143	2x996T	11.29	-6.25	5.04	14.0	-8.96

Table 7-18. SISO ANT2 160MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power – VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 44 of 124

SISO Maximum Conducted Output Power Measurements (4x996 Tones)

320MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)	Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index				
					69				
	5	6105	31	4x996T	11.6				
	7	6745	159	4x996T	11.9	-6.52	5.33	14.0	-8.67

Table 7-19. SISO ANT1 320MHz BW 802.11be (UNII) Maximum Conducted Output Power – VLP

320MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)	Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index				
					69.00				
	5	6105	31	4x996T	11.41				
	7	6745	159	4x996T	11.27	-6.25	5.02	14.0	-8.98

Table 7-20. SISO ANT2 320MHz BW 802.11be (UNII) Maximum Conducted Output Power – VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 45 of 124



MIMO Maximum Conducted Output Power Measurements (26 Tones)

20MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)									Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index												
					0			4			8						
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	ANT1	ANT2	MIMO				
5	5935	2	26T	-4.50	-4.02	-1.24	-5.47	-4.42	-1.90	-5.50	-4.19	-1.79	-2.63	-3.87	14.0	-17.87	
	6175	45	26T	-4.89	-4.02	-1.42	-5.21	-4.39	-1.77	-4.78	-4.06	-1.39	-2.63	-4.03	14.0	-18.03	
	6415	93	26T	-4.93	-4.01	-1.44	-5.21	-4.24	-1.69	-4.87	-4.01	-1.41	-2.63	-4.04	14.0	-18.04	
7	6535	117	26T	-4.10	-4.30	-1.19	-4.77	-4.63	-1.69	-4.24	-4.24	-1.23	-3.37	-4.56	14.0	-18.56	
	6695	149	26T	-4.38	-4.55	-1.45	-4.44	-4.45	-1.43	-4.24	-4.47	-1.34	-3.37	-4.72	14.0	-18.72	

Table 7-21. MIMO 20MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power – VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 46 of 124



MIMO Maximum Conducted Output Power Measurements (52 Tones)

20MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)									Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index												
					37			38			40						
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	ANT1	ANT2	MIMO				
5	5935	2	52T		-2.57	-1.12	1.23	-2.17	-1.01	1.46	-2.57	-1.24	1.16	-2.63	-1.17	14.0	-15.17
	6175	45	52T		-2.50	-1.43	1.08	-2.17	-1.17	1.37	-1.87	-1.01	1.59	-2.63	-1.04	14.0	-15.04
	6415	93	52T		-2.43	-1.43	1.11	-2.15	-1.09	1.42	-2.41	-1.40	1.13	-2.63	-1.21	14.0	-15.21
7	6535	117	52T		-1.37	-1.55	1.55	-1.54	-1.63	1.43	-1.35	-1.40	1.64	-3.37	-1.74	14.0	-15.74
	6695	149	52T		-1.41	-1.63	1.49	-1.07	-1.31	1.82	-1.34	-1.52	1.58	-3.37	-1.55	14.0	-15.55

Table 7-22. MIMO 20MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power – VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 47 of 124



MIMO Maximum Conducted Output Power Measurements (106 Tones)

20MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)						Dir. Ant. Gain [dB]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index									
					53			54						
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO				
7	5935	2	106T	0.83	1.88	4.40	0.89	1.72	4.34	-2.63	1.77	14.0	-12.23	
	6175	45	106T	0.43	1.52	4.02	0.59	1.38	4.01	-2.63	1.39	14.0	-12.61	
	6415	93	106T	0.77	1.55	4.19	0.90	1.45	4.19	-2.63	1.56	14.0	-12.44	
	6535	117	106T	1.32	1.06	4.20	1.38	1.11	4.26	-3.37	0.88	14.0	-13.12	
	6695	149	106T	1.56	1.30	4.44	1.55	1.36	4.47	-3.37	1.09	14.0	-12.91	

Table 7-23. MIMO 20MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power – VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 48 of 124

MIMO Maximum Conducted Output Power Measurements (242 Tones)

20MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)			Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index						
					61						
					ANT1	ANT2	MIMO				
	5	5935	2	242T	4.66	5.75	8.25	-2.63	5.62	14.0	-8.38
6175		45	242T	5.08	5.80	8.47	-2.63	5.83	14.0	-8.17	
6415		93	242T	5.23	5.85	8.56	-2.63	5.93	14.0	-8.07	
7	6535	117	242T	5.62	5.43	8.54	-3.37	5.16	14.0	-8.84	
	6695	149	242T	5.67	5.10	8.40	-3.37	5.03	14.0	-8.97	

Table 7-24. MIMO 20MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power – VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 49 of 124

MIMO Maximum Conducted Output Power Measurements (484 Tones)

40MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)			Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index						
					65						
					ANT1	ANT2	MIMO				
5	5965	3	484T	8.01	8.54	11.29	-2.63	8.66	14.0	-5.34	
	6165	43	484T	8.02	8.59	11.32	-2.63	8.69	14.0	-5.31	
	6405	91	484T	8.05	8.82	11.46	-2.63	8.83	14.0	-5.17	
	6565	123	484T	8.61	8.49	11.56	-3.37	8.19	14.0	-5.81	
	6725	155	484T	8.69	8.41	11.56	-3.37	8.19	14.0	-5.81	
	6845	179	484T	8.80	8.81	11.82	-3.37	8.44	14.0	-5.56	

Table 7-25. MIMO 40MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power – VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 50 of 124

MIMO Maximum Conducted Output Power Measurements (996 Tones)

80MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)			Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index						
					67						
					ANT1	ANT2	MIMO				
	5	5985	7	996T	10.97	11.38	14.19	-2.63	11.56	14.0	-2.44
	6145	39	996T	10.43	11.53	14.03	-2.63	11.39	14.0	-2.61	
	6385	87	996T	10.89	11.82	14.39	-2.63	11.76	14.0	-2.24	
7	6705	151	996T	11.53	11.25	14.40	-3.37	11.03	14.0	-2.97	

Table 7-26. MIMO 80MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power – VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 51 of 124

MIMO Maximum Conducted Output Power Measurements (2x996 Tones)

160MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)			Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index						
					68						
					ANT1	ANT2	MIMO				
	5	6025	15	2x996T	11.21	11.62	14.43	-2.63	11.80	14.0	-2.20
6185		47	2x996T	10.56	11.66	14.16	-2.63	11.52	14.0	-2.48	
6345		79	2x996T	10.71	11.93	14.37	-2.63	11.74	14.0	-2.26	
7	6665	143	2x996T	11.94	11.34	14.66	-3.37	11.29	14.0	-2.71	

Table 7-27. MIMO 160MHz BW 802.11ax/be (UNII) Maximum Conducted Output Power – VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 52 of 124



MIMO Maximum Conducted Output Power Measurements (4x996 Tones)

320MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)			Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index						
					69						
					ANT1	ANT2	MIMO				
	5	6105	31	4x996T	11.01	11.46	14.25	-2.63	11.62	14.0	-2.38
7	6745	159	4x996T	11.22	11.32	14.28	-3.37	10.91	14.0	-3.09	

Table 7-28. MIMO 320MHz BW 802.11be (UNII) Maximum Conducted Output Power – VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 53 of 124

MIMO Maximum Conducted Output Power Measurements (MRU)

20MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)									Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					MRU Index												
					70			71			72						
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	ANT1	ANT2	MIMO				
5	6175	45	52+26T	-3.21	-1.12	0.97	-3.30	-1.20	0.89	-3.17	-1.10	1.00	-2.63	-1.63	14.0	-15.63	
7	6695	149	52+26T	-1.33	-1.68	1.51	-1.44	-1.76	1.41	-1.28	-1.60	1.57	-3.37	-1.80	14.0	-15.80	

Table 7-29. MIMO 20MHz BW 802.11be (UNII) Maximum Conducted Output Power (52+26 Tones) – VLP

20MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)						Dir. Ant. Gain [dB]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					MRU Index									
					82			83						
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO				
5	6175	45	106+26T		-0.30	1.82	3.90	-0.26	1.85	3.93	-2.63	1.30	14.0	-12.70
7	6695	149	106+26T		1.71	1.36	4.55	1.73	1.39	4.57	-3.37	1.20	14.0	-12.80

Table 7-30. MIMO 20MHz BW 802.11be (UNII) Maximum Conducted Output Power (106+26 Tones) – VLP

80MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)									Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					MRU Index												
					90			91			93						
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	ANT1	ANT2	MIMO				
5	6145	39	242+484T	8.81	8.63	11.73	8.81	8.66	11.75	8.90	8.68	11.80	-2.63	9.17	14.0	-4.83	
7	6705	151	242+484T	8.67	7.22	11.02	8.71	7.22	11.04	8.68	7.33	11.07	-3.37	7.69	14.0	-6.31	

Table 7-31. MIMO 80MHz BW 802.11be (UNII) Maximum Conducted Output Power (484+242 Tones) – VLP

160MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)												Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					MRU Index															
					94			95			1094									
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	ANT1	ANT2	MIMO				
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	ANT1	ANT2	MIMO				
5	6185	47	996+484T	11.87	11.99	14.94	11.92	11.99	14.97	11.36	11.65	14.52	-2.63	12.33	14.0	-1.67				
7	6825	175	996+484T	11.99	10.45	14.30	11.99	10.35	14.26	11.99	10.42	14.29	-3.37	10.92	14.0	-3.08				

Table 7-32. MIMO 160MHz BW 802.11be (UNII) Maximum Conducted Output Power (996+484 Tones) – VLP

320MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)												Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					MRU Index															
					100			101			11102									
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	ANT1	ANT2	MIMO							
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	MIMO						
5	6105	31	2x996+484T	11.86	11.35	14.62	11.88	11.33	14.62	11.81	11.31	14.58	-2.63	11.99	14.0	-2.01				
7	6745	159	2x996+484T	11.99	10.42	14.29	11.98	10.42	14.28	11.96	10.37	14.25	-3.37	10.91	14.0	-3.09				

Table 7-33. MIMO 320MHz BW 802.11be (UNII) Maximum Conducted Output Power (2*996+484 Tones) – VLP

320 MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)									Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					MRU Index												
					104			10104			11104						
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	ANT1	ANT2	MIMO				
5	6105	31	3x996T	11.99	11.60	14.81	11.99	11.54	14.78	11.99	11.64	14.83	-2.63	12.20	14.0	-1.80	
7	6745	159	3x996T	11.81	10.21	14.09	11.91	10.25	14.17	11.87	10.28	14.16	-3.37	10.80	14.0	-3.20	

Table 7-34. MIMO 320MHz BW 802.11be (UNII) Maximum Conducted Output Power (3*996 Tones) – VLP

320 MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)												Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					MRU Index															
					105			106			11105									
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	ANT1	ANT2	MIMO							
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	ANT1	ANT2	MIMO							
5	6105	31	3x996+484T	11.72	11.21	14.48	11.73	11.19	14.48	11.76	11.23	14.51			-2.63	11.88	14.0	-2.12		
7	6745	159	3x996+484T	11.93	10.31	14.21	11.93	10.32	14.21	11.99	10.35	14.26			-3.37	10.88	14.0	-3.12		

Table 7-35. MIMO 320MHz BW 802.11be (UNII) Maximum Conducted Output Power (3*996+484 Tones) – VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 54 of 124



Sample MIMO Calculation:

At 5935MHz in 802.11ax (20MHz BW – 26 Tones) mode, the average conducted output power was measured to be -4.50 dBm for Antenna-1 and -4.02 dBm for Antenna-2.

Antenna 1 + Antenna 2 = MIMO

$$(-4.50 \text{ dBm} + -4.02 \text{ dBm}) = (0.355 \text{ mW} + 0.396 \text{ mW}) = 0.751 \text{ mW} = -1.24 \text{ dBm}$$

Sample Directional Gain Calculation:

Per ANSI C63.10-2013 Section 14.4.3, the directional gain is calculated using the following formula, where GN is the gain of the nth antenna and NANT, the total number of antennas used.

$$\text{Directional gain} = 10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{\text{ANT}}] \text{ dBi}$$

Sample e.i.r.p. Calculation:

At 5935MHz in 802.11ax (20MHz BW – 26 Tones) mode, the average MIMO conducted power was calculated to be -1.24 dBm with directional gain of -2.63 dBi.

$$\text{e.i.r.p. (dBm)} = \text{Conducted Power (dBm)} + \text{Ant gain (dBi)}$$

$$-1.24 \text{ dBm} + -2.63 \text{ dBi} = -3.87 \text{ dBm}$$

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 55 of 124

7.4 Maximum Power Spectral Density

Test Overview and Limit

The spectrum analyzer was connected to the antenna terminal while the EUT was operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013, and at the appropriate frequencies. Method SA-1, as defined in ANSI C63.10-2013, was used to measure the power spectral density.

For very low power devices operating in the 5.925-6.425 GHz and 6.525-6.875 GHz bands, the maximum power spectral density must not exceed -5 dBm e.i.r.p in any 1-megahertz band and the maximum e.i.r.p must not exceed 14 dBm.

Test Procedure Used

ANSI C63.10-2013 – Section 12.3.2.2

ANSI C63.10-2013 – Section 14.3.2.2 Measure-and-Sum Technique

Test Settings

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Span was set to encompass the entire emission bandwidth of the signal
3. RBW = 1MHz
4. VBW = 3MHz
5. Number of sweep points $\geq 2 \times (\text{span}/\text{RBW})$
6. Sweep time = auto
7. Detector = power averaging (RMS)
8. Trigger was set to free run for all modes
9. Trace was averaged over 100 sweeps
10. The peak search function of the spectrum analyzer was used to find the peak of the spectrum.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-3. Test Instrument & Measurement Setup

Test Notes

None.

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 56 of 124

MIMO Power Spectral Density Measurements

	Frequency [MHz]	Channel	802.11 MODE	Antenna-1 Power Density [dBm]	Antenna-2 Power Density [dBm]	Antenna-1 Gain [dBi]	Antenna-2 Gain [dBi]	Summed MIMO Power Density [dBm]	Directional Gain [dBi]	EIRP [dBm]	Max EIRP [dBm]	Margin [dB]
Band 5	5935	2	be (20MHz)	-6.98	-6.49	-5.91	-5.38	-3.72	-2.63	-6.35	-5	-1.35
	6175	45	be (20MHz)	-6.77	-7.05	-5.91	-5.38	-3.90	-2.63	-6.53	-5	-1.53
	6415	93	be (20MHz)	-7.55	-6.14	-5.91	-5.38	-3.78	-2.63	-6.41	-5	-1.41
	5965	3	be (40MHz)	-6.80	-7.12	-5.91	-5.38	-3.95	-2.63	-6.58	-5	-1.58
	6165	43	be (40MHz)	-7.18	-5.48	-5.91	-5.38	-3.24	-2.63	-5.87	-5	-0.87
	6405	91	be (40MHz)	-7.03	-6.59	-5.91	-5.38	-3.79	-2.63	-6.42	-5	-1.42
	5985	7	be (80MHz)	-6.63	-6.72	-5.91	-5.38	-3.66	-2.63	-6.29	-5	-1.29
	6145	39	be (80MHz)	-6.14	-6.46	-5.91	-5.38	-3.28	-2.63	-5.91	-5	-0.91
	6385	87	be (80MHz)	-6.04	-6.22	-5.91	-5.38	-3.12	-2.63	-5.75	-5	-0.75
	6025	15	be (160MHz)	-7.14	-6.83	-5.91	-5.38	-3.97	-2.63	-6.60	-5	-1.60
	6185	47	be (160MHz)	-7.40	-5.87	-5.91	-5.38	-3.55	-2.63	-6.18	-5	-1.18
	6345	79	be (160MHz)	-7.03	-5.20	-5.91	-5.38	-3.01	-2.63	-5.64	-5	-0.64
Band 7	6105	31	be (320MHz)	-6.26	-6.22	-5.91	-5.38	-3.23	-2.63	-5.86	-5	-0.86
	6265	63	be (320MHz)	-7.49	-4.74	-5.91	-5.38	-2.89	-2.63	-5.52	-5	-0.52
	6695	117	be (20MHz)	-8.07	-5.95	-6.52	-6.25	-3.87	-3.37	-7.24	-5	-2.24
	6695	149	be (20MHz)	-7.12	-7.02	-6.52	-6.25	-4.06	-3.37	-7.43	-5	-2.43
	6875	185	be (20MHz)	-6.97	-7.03	-6.52	-6.25	-3.99	-3.37	-7.36	-5	-2.36
	6565	123	be (40MHz)	-7.12	-7.16	-6.52	-6.25	-4.13	-3.37	-7.50	-5	-2.50
	6725	155	be (40MHz)	-6.94	-6.66	-6.52	-6.25	-3.79	-3.37	-7.16	-5	-2.16
	6845	179	be (40MHz)	-6.44	-6.49	-6.52	-6.25	-3.45	-3.37	-6.82	-5	-1.82
	6545	119	be (80MHz)	-5.92	-6.38	-6.52	-6.25	-3.14	-3.37	-6.51	-5	-1.51
	6705	151	be (80MHz)	-7.09	-6.43	-6.52	-6.25	-3.73	-3.37	-7.11	-5	-2.11
	6865	183	be (80MHz)	-6.20	-7.31	-6.52	-6.25	-3.71	-3.37	-7.08	-5	-2.08
	6665	143	be (160MHz)	-6.81	-6.41	-6.52	-6.25	-3.59	-3.37	-6.97	-5	-1.97
	6825	175	be (160MHz)	-6.14	-6.29	-6.52	-6.25	-3.20	-3.37	-6.58	-5	-1.58

Table 7-36. MIMO e.i.r.p. Conducted Power Spectral Density Measurements (26 Tones) – VLP

	Frequency [MHz]	Channel	802.11 MODE	MRU Cases	Antenna-1 Power Density [dBm]	Antenna-2 Power Density [dBm]	Antenna-1 Gain [dBi]	Antenna-2 Gain [dBi]	Summed MIMO Power Density [dBm]	Directional Gain [dBi]	DCCF [dB]	EIRP [dBm]	Max EIRP [dBm]	Margin [dB]
Band 5	6175	45	be (20MHz)	52+26T	-8.16	-7.28	-5.91	-5.38	-4.69	-2.63	0.00	-7.32	-5	-2.32
	6175	45	be (20MHz)	106+26T	-7.64	-6.70	-5.91	-5.38	-4.13	-2.63	0.00	-6.76	-5	-1.76
	6145	39	be (80MHz)	484+242T	-7.18	-7.23	-5.91	-5.38	-4.19	-2.63	0.16	-6.66	-5	-1.66
	6185	47	be (160MHz)	996+484T	-7.50	-6.77	-5.91	-5.38	-4.11	-2.63	0.17	-6.57	-5	-1.57
	6105	31	be (320MHz)	3x996+484T	-10.61	-10.43	-5.91	-5.38	-7.51	-2.63	0.12	-10.02	-5	-5.02
	6105	31	be (320MHz)	3x996T	-10.23	-9.37	-5.91	-5.38	-6.76	-2.63	0.19	-9.21	-5	-4.21
	6105	31	be (320MHz)	2x996+484T	-9.08	-8.30	-5.91	-5.38	-5.66	-2.63	0.16	-8.13	-5	-3.13
	6695	149	be (20MHz)	52+26T	-8.03	-8.44	-6.52	-6.25	-5.22	-3.37	0.00	-8.59	-5	-3.59
Band 7	6695	149	be (20MHz)	106+26T	-7.84	-7.17	-6.52	-6.25	-4.48	-3.37	0.00	-7.85	-5	-2.85
	6705	151	be (80MHz)	484+242T	-7.31	-7.75	-6.52	-6.25	-4.52	-3.37	0.16	-7.73	-5	-2.73
	6665	143	be (160MHz)	996+484T	-8.29	-7.68	-6.52	-6.25	-4.96	-3.37	0.17	-8.17	-5	-3.17

Table 7-37. MIMO e.i.r.p. Conducted Power Spectral Density Measurements (MRU Cases) – VLP


FCC ID: A3LSMS938U	MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset		Page 57 of 124

	Frequency [MHz]	Channel	802.11 MODE	Antenna-1 Power Density [dBm]	Antenna-2 Power Density [dBm]	Antenna-1 Gain [dBi]	Antenna-2 Gain [dBi]	Summed MIMO Power Density [dBm]	Directional Gain [dBi]	DCCF [dB]	EIRP [dBm]	Max EIRP [dBm]	Margin [dB]
Band 5	5935	2	be (20MHz)	-5.39	-5.77	-5.91	-5.38	-2.57	-2.63	0.13	-5.07	-5	-0.07
	6175	45	be (20MHz)	-5.59	-5.80	-5.91	-5.38	-2.68	-2.63	0.13	-5.18	-5	-0.18
	6415	93	be (20MHz)	-6.82	-5.88	-5.91	-5.38	-3.31	-2.63	0.13	-5.81	-5	-0.81
	5965	3	be (40MHz)	-6.84	-6.19	-5.91	-5.38	-3.49	-2.63	0.13	-5.99	-5	-0.99
	6165	43	be (40MHz)	-6.59	-5.73	-5.91	-5.38	-3.13	-2.63	0.13	-5.63	-5	-0.63
	6405	91	be (40MHz)	-6.34	-5.93	-5.91	-5.38	-3.12	-2.63	0.13	-5.62	-5	-0.62
	5985	7	be (80MHz)	-6.20	-5.63	-5.91	-5.38	-2.90	-2.63	0.21	-5.32	-5	-0.32
	6145	39	be (80MHz)	-5.97	-5.76	-5.91	-5.38	-2.85	-2.63	0.21	-5.28	-5	-0.28
	6385	87	be (80MHz)	-6.19	-5.73	-5.91	-5.38	-2.95	-2.63	0.21	-5.37	-5	-0.37
	6025	15	be (160MHz)	-8.37	-7.98	-5.91	-5.38	-5.16	-2.63	0.22	-7.57	-5	-2.57
	6185	47	be (160MHz)	-8.83	-7.78	-5.91	-5.38	-5.26	-2.63	0.22	-7.67	-5	-2.67
	6345	79	be (160MHz)	-9.37	-8.38	-5.91	-5.38	-5.83	-2.63	0.22	-8.24	-5	-3.24
Band 7	6105	31	be (320MHz)	-10.53	-11.03	-5.91	-5.38	-7.76	-2.63	0.14	-10.26	-5	-5.26
	6265	63	be (320MHz)	-11.89	-10.55	-5.91	-5.38	-8.16	-2.63	0.14	-10.65	-5	-5.65
	6695	117	be (20MHz)	-5.68	-5.69	-6.52	-6.25	-2.67	-3.37	0.13	-5.92	-5	-0.92
	6695	149	be (20MHz)	-6.15	-5.30	-6.52	-6.25	-2.69	-3.37	0.13	-5.93	-5	-0.93
	6875	185	be (20MHz)	-5.85	-5.82	-6.52	-6.25	-2.82	-3.37	0.13	-6.07	-5	-1.07
	6565	123	be (40MHz)	-6.97	-5.40	-6.52	-6.25	-3.10	-3.37	0.13	-6.35	-5	-1.35
	6725	155	be (40MHz)	-6.43	-5.68	-6.52	-6.25	-3.03	-3.37	0.13	-6.27	-5	-1.27
	6845	179	be (40MHz)	-6.17	-5.80	-6.52	-6.25	-2.97	-3.37	0.13	-6.22	-5	-1.22
	6545	119	be (80MHz)	-6.21	-5.16	-6.52	-6.25	-2.65	-3.37	0.21	-5.81	-5	-0.81
	6705	151	be (80MHz)	-6.26	-6.10	-6.52	-6.25	-3.17	-3.37	0.21	-6.33	-5	-1.33
	6865	183	be (80MHz)	-6.15	-6.66	-6.52	-6.25	-3.39	-3.37	0.21	-6.55	-5	-1.55
	6665	143	be (160MHz)	-9.86	-8.85	-6.52	-6.25	-6.31	-3.37	0.22	-9.47	-5	-4.47


Table 7-38. MIMO e.i.r.p. Conducted Power Spectral Density Measurements (Full Tones) – VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 58 of 124

7.4.1 MIMO Antenna-1 Power Spectral Density Measurements




Plot 7-29. Power Spectral Density Plot MIMO ANT1 (20MHz 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 45) - VLP




Plot 7-30. Power Spectral Density Plot MIMO ANT1 (40MHz 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 43) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 59 of 124




Plot 7-31. Power Spectral Density Plot MIMO ANT1 (80MHz 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 39) - VLP




Plot 7-32. Power Spectral Density Plot MIMO ANT1 (160MHz 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 47) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 60 of 124




Plot 7-33. Power Spectral Density Plot MIMO ANT1 (320MHz 802.11be (26 Tones) (UNII Band 5) – Ch. 31) - VLP




Plot 7-34. Power Spectral Density Plot MIMO ANT1 (20MHz 802.11be (52+26 Tones) (UNII Band 5) – Ch. 45) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 61 of 124




Plot 7-35. Power Spectral Density Plot MIMO ANT1 (80MHz 802.11be (484+242 Tones) (UNII Band 5) – Ch. 39) VLP




Plot 7-36. Power Spectral Density Plot MIMO ANT1 (160MHz 802.11be (996+484 Tones) (UNII Band 5) – Ch. 47) VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 62 of 124




Plot 7-37. Power Spectral Density Plot MIMO ANT1 (320MHz 802.11be (UNII Band 5) – Ch. 31) VLP




Plot 7-38. Power Spectral Density Plot MIMO ANT1 (20MHz 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 45) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 63 of 124




Plot 7-41. Power Spectral Density Plot MIMO ANT1 (160MHz 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 47) - VLP




Plot 7-42. Power Spectral Density Plot MIMO ANT1 (320MHz 802.11be (Full Tones) (UNII Band 5) – Ch. 31) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 65 of 124

7.4.2 MIMO Antenna-2 Power Spectral Density Measurements




Plot 7-43. Power Spectral Density Plot MIMO ANT2 (20MHz 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 45) - VLP




Plot 7-44. Power Spectral Density Plot MIMO ANT2 (40MHz 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 43) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 66 of 124




Plot 7-47. Power Spectral Density Plot MIMO ANT2 (320MHz 802.11be (26 Tones) (UNII Band 5) – Ch. 31) - VLP




Plot 7-48. Power Spectral Density Plot MIMO ANT2 (20MHz 802.11be (52+26 Tones) (UNII Band 5) – Ch. 45) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 68 of 124



Plot 7-49. Power Spectral Density Plot MIMO ANT2 (80MHz 802.11be (484+242 Tones) (UNII Band 5) – Ch. 39) VLP




Plot 7-50. Power Spectral Density Plot MIMO ANT2 (160MHz 802.11be (996+484 Tones) (UNII Band 5) – Ch. 47) VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 69 of 124




Plot 7-51. Power Spectral Density Plot MIMO ANT2 (320MHz 802.11be (UNII Band 5) – Ch. 31) VLP




Plot 7-52. Power Spectral Density Plot MIMO ANT2 (20MHz 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 45) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 70 of 124




Plot 7-53. Power Spectral Density Plot MIMO ANT2 (40MHz 802.11ax/be (Full Tones) (UNII Band 5) - Ch. 43) - VLP




Plot 7-54. Power Spectral Density Plot MIMO ANT2 (80MHz 802.11ax/be (Full Tones) (UNII Band 5) - Ch. 39) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 71 of 124



Plot 7-55. Power Spectral Density Plot MIMO ANT2 (160MHz 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 47) - VLP



Plot 7-56. Power Spectral Density Plot MIMO ANT2 (320MHz 802.11be (Full Tones) (UNII Band 5) – Ch. 31) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 72 of 124

Note:

Per ANSI C63.10-2013 Section 14.3.2.2 and KDB 662911 v02r01 Section E)2), the power spectral density at Antenna 1 and Antenna 2 were first measured separately as shown in the section above. The measured values were then summed in linear power units then converted back to dBm.

Per ANSI C63.10-2013 Section 14.4.3, the directional gain is calculated using the following formula, where GN is the gain of the nth antenna and NANT, the total number of antennas used.

$$\text{Directional gain} = 10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{\text{ANT}}] \text{ dBi}$$

Sample MIMO Calculation:

At 5935MHz in 802.11ax (20MHz BW) mode, the average conducted power spectral density was measured to be -6.98 dBm for Antenna-1 and -6.49 dBm for Antenna-2.

$$\text{Antenna 1} + \text{Antenna 2} = \text{MIMO}$$

$$(-6.98 \text{ dBm} + -6.49 \text{ dBm}) = (0.200 \text{ mW} + 0.224 \text{ mW}) = 0.424 \text{ mW} = -3.73 \text{ dBm}$$

Sample e.i.r.p Power Spectral Density Calculation:

At 5935 MHz in 802.11ax (20MHz BW) mode, the average MIMO power density was calculated to be -3.73 dBm with directional gain of -2.63 dBi.

$$\text{e.i.r.p. Power Spectral Density(dBm)} = \text{Power Spectral Density (dBm)} + \text{Ant gain (dBi)}$$

$$-3.73 \text{ dBm} + -2.63 \text{ dBi} = -6.36 \text{ dBm}$$

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 73 of 124

7.5 In-Band Emissions

Test Overview and Limit

The spectrum analyzer was connected to the antenna terminal while the EUT was operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013, and at the appropriate frequencies.

For transmitters operating within the 5.925-7.125 GHz bands: Power spectral density must be suppressed by 20 dB at 1 MHz outside of channel edge, by 28 dB at one channel bandwidth from the channel center, and by 40 dB at one- and one-half times the channel bandwidth away from channel center. At frequencies between one megahertz outside an unlicensed device's channel edge and one channel bandwidth from the center of the channel, the limits must be linearly interpolated between 20 dB and 28 dB suppression, and at frequencies between one and one- and one-half times an unlicensed device's channel bandwidth, the limits must be linearly interpolated between 28 dB and 40 dB suppression. Emissions removed from the channel center by more than one- and one-half times the channel bandwidth must be suppressed by at least 40 dB.

Test Procedure Used

KDB 987594 D02 v03

Test Settings

1. Connect output of the antenna port to a spectrum analyzer or EMI receiver, with appropriate attenuation, as to not damage the instrumentation.
2. Set the reference level of the measuring equipment in accordance with procedure 4.1.5.2 of ANSI C63.10-2013.
3. Measure the 26 dB EBW using the test procedure 12.4.1 of ANSI C63.10-2013. (This will be used to determine the channel edge.)
4. Measure the power spectral density (which will be used for emissions mask reference) using the following procedure:
 - a) Set the span to encompass the entire 26 dB EBW of the signal.
 - b) Set RBW = same RBW used for 26 dB EBW measurement.
 - c) Set VBW $\geq 3 \times$ RBW
 - d) Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$.
 - e) Sweep time = auto.
 - f) Detector = RMS (i.e., power averaging)
 - g) Trace average at least 100 traces in power averaging (rms) mode.
 - h) Use the peak search function on the instrument to find the peak of the spectrum.
5. For the purposes of developing the emission mask, the channel bandwidth is defined as the 26 dB EBW.
6. Using the measuring equipment limit line function, develop the emissions mask based on the following requirements. The emissions power spectral density must be reduced below the peak power spectral density (in dB) as follows:
 - a) Suppressed by 20 dB at 1 MHz outside of the channel edge. (The channel edge is defined as the 26-dB point on either side of the carrier center frequency.)
 - b) Suppressed by 28 dB at one channel bandwidth from the channel center.
 - c) Suppressed by 40 dB at one- and one-half times the channel bandwidth from the channel center.
7. Adjust the span to encompass the entire mask as necessary.
8. Clear trace.
9. Trace average at least 100 traces in power averaging (rms) mode.
10. Adjust the reference level as necessary so that the crest of the channel touches the top of the emission mask.

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 74 of 124

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-4. Test Instrument & Measurement Setup

Test Notes

None.

	Frequency [MHz]	Channel	802.11 MODE	Antenna-1 In-Band Emission	Antenna-2 In-Band Emission
Band 5	5935	2	be (20MHz)	PASS	PASS
	6175	45	be (20MHz)	PASS	PASS
	6415	93	be (20MHz)	PASS	PASS
	5965	3	be (40MHz)	PASS	PASS
	6165	43	be (40MHz)	PASS	PASS
	6405	91	be (40MHz)	PASS	PASS
	5985	7	be (80MHz)	PASS	PASS
	6145	39	be (80MHz)	PASS	PASS
	6385	87	be (80MHz)	PASS	PASS
	6025	15	be (160MHz)	PASS	PASS
	6185	47	be (160MHz)	PASS	PASS
	6345	79	be (160MHz)	PASS	PASS
	6105	31	be (320MHz)	PASS	PASS
	6265	63	be (320MHz)	PASS	PASS
Band 7	6695	117	be (20MHz)	PASS	PASS
	6695	149	be (20MHz)	PASS	PASS
	6875	185	be (20MHz)	PASS	PASS
	6565	123	be (40MHz)	PASS	PASS
	6725	155	be (40MHz)	PASS	PASS
	6845	179	be (40MHz)	PASS	PASS
	6545	119	be (80MHz)	PASS	PASS
	6705	151	be (80MHz)	PASS	PASS
	6865	183	be (80MHz)	PASS	PASS
	6665	143	be (160MHz)	PASS	PASS
	6825	175	be (160MHz)	PASS	PASS
Band 7/8	6745	159	be (320MHz)	PASS	PASS

Table 7-39. In Band Emission Results (26 Tones)

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 75 of 124

	Frequency [MHz]	Channel	802.11 MODE	Antenna-1 In-Band Emission	Antenna-2 In-Band Emission
Band 5	5935	2	be (20MHz)	PASS	PASS
	6175	45	be (20MHz)	PASS	PASS
	6415	93	be (20MHz)	PASS	PASS
	5965	3	be (40MHz)	PASS	PASS
	6165	43	be (40MHz)	PASS	PASS
	6405	91	be (40MHz)	PASS	PASS
	5985	7	be (80MHz)	PASS	PASS
	6145	39	be (80MHz)	PASS	PASS
	6385	87	be (80MHz)	PASS	PASS
	6025	15	be (160MHz)	PASS	PASS
	6185	47	be (160MHz)	PASS	PASS
	6345	79	be (160MHz)	PASS	PASS
	6105	31	be (320MHz)	PASS	PASS
	6265	63	be (320MHz)	PASS	PASS
Band 7	6695	117	be (20MHz)	PASS	PASS
	6695	149	be (20MHz)	PASS	PASS
	6875	185	be (20MHz)	PASS	PASS
	6565	123	be (40MHz)	PASS	PASS
	6725	155	be (40MHz)	PASS	PASS
	6845	179	be (40MHz)	PASS	PASS
	6545	119	be (80MHz)	PASS	PASS
	6705	151	be (80MHz)	PASS	PASS
	6865	183	be (80MHz)	PASS	PASS
	6665	143	be (160MHz)	PASS	PASS
	6825	175	be (160MHz)	PASS	PASS
	6585	127	be (320MHz)	PASS	PASS
	6745	159	be (320MHz)	PASS	PASS
	6745	159	be (320MHz)	PASS	PASS


Table 7-40. In Band Emission Results (Full Tones)

	Frequency [MHz]	Channel	802.11 MODE	MRU Cases	Antenna-1 In-Band Emission	Antenna-2 In-Band Emission
Band 5	6175	45	be (20MHz)	52+26T	PASS	PASS
	6175	45	be (20MHz)	106+26T	PASS	PASS
	6145	39	be (80MHz)	484+242T	PASS	PASS
	6185	47	be (160MHz)	996+484T	PASS	PASS
	6105	31	be (320MHz)	3x996+484T	PASS	PASS
	6105	31	be (320MHz)	3x996T	PASS	PASS
	6105	31	be (320MHz)	2x996+484T	PASS	PASS
Band 7	6695	149	be (20MHz)	52+26T	PASS	PASS
	6695	149	be (20MHz)	106+26T	PASS	PASS
	6705	151	be (80MHz)	484+242T	PASS	PASS
	6665	143	be (160MHz)	996+484T	PASS	PASS
Band 7/8	6745	159	be (320MHz)	3x996+484T	PASS	PASS
	6745	159	be (320MHz)	3x996T	PASS	PASS
	6745	159	be (320MHz)	2x996+484T	PASS	PASS


Table 7-41. In Band Emission Results (MRU)

FCC ID: A3LSMS938U	MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset		Page 76 of 124

7.5.1 MIMO Antenna-1 In-Band Emission Measurements




Plot 7-57. In Band Emissions Plot MIMO ANT1 (20MHz 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 45) - VLP




Plot 7-58. In Band Emissions Plot MIMO ANT1 (40MHz 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 43) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 77 of 124




Plot 7-59. In Band Emissions Plot MIMO ANT1 (80MHz 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 39) - VLP




Plot 7-60. In Band Emissions Plot MIMO ANT1 (160MHz 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 47) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 78 of 124




Plot 7-61. In Band Emissions Plot MIMO ANT1 (320MHz 802.11be (26 Tones) (UNII Band 5) – Ch. 31) - VLP




Plot 7-62. In Band Emissions Plot MIMO ANT1 (20MHz 802.11be (106+26 Tones) (UNII Band 5) – Ch. 45) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 79 of 124




Plot 7-63. In Band Emissions Plot MIMO ANT1 (80MHz 802.11be (484+242 Tones) (UNII Band 5) – Ch. 39) VLP




Plot 7-64. In Band Emissions Plot MIMO ANT1 (160MHz 802.11be (996+484 Tones) (UNII Band 5) – Ch. 47) VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 80 of 124




Plot 7-65. In Band Emissions Plot MIMO ANT1 (320MHz 802.11be (3*996+484 Tones) (UNII Band 5) – Ch. 31) VLP




Plot 7-66. In Band Emissions Plot MIMO ANT1 (20MHz 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 45) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 81 of 124




Plot 7-67. In Band Emissions Plot MIMO ANT1 (40MHz 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 43) - VLP




Plot 7-68. In Band Emissions Plot MIMO ANT1 (80MHz 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 39) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 82 of 124




Plot 7-69. In Band Emissions Plot MIMO ANT1 (160MHz 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 47) - VLP




Plot 7-70. In Band Emissions Plot MIMO ANT1 (320MHz 802.11be (Full Tones) (UNII Band 5) – Ch. 31) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 83 of 124

7.5.2 MIMO Antenna-2 In-Band Emission Measurements




Plot 7-71. In Band Emissions Plot MIMO ANT2 (20MHz 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 45) - VLP




Plot 7-72. In Band Emissions Plot MIMO ANT2 (40MHz 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 43) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 84 of 124




Plot 7-73. In Band Emissions Plot MIMO ANT2 (80MHz 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 39) - VLP



Plot 7-74. In Band Emissions Plot MIMO ANT2 (160MHz 802.11ax/be (26 Tones) (UNII Band 5) – Ch. 47) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 85 of 124




Plot 7-75. In Band Emissions Plot MIMO ANT2 (320MHz 802.11be (26 Tones) (UNII Band 5) – Ch. 31) - VLP




Plot 7-76. In Band Emissions Plot MIMO ANT2 (20MHz 802.11be (106+26 Tones) (UNII Band 5) – Ch. 45) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 86 of 124




Plot 7-77. In Band Emissions Plot MIMO ANT2 (80MHz 802.11be (484+242 Tones) (UNII Band 5) – Ch. 39) VLP




Plot 7-78. In Band Emissions Plot MIMO ANT2 (160MHz 802.11be (996+484 Tones) (UNII Band 5) – Ch. 47) VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 87 of 124




Plot 7-79. In Band Emissions Plot MIMO ANT2 (320MHz 802.11be (3*996+484 Tones) (UNII Band 5) – Ch. 31) VLP




Plot 7-80. In Band Emissions Plot MIMO ANT2 (20MHz 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 45) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 88 of 124




Plot 7-81. In Band Emissions Plot MIMO ANT2 (40MHz 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 43) - VLP




Plot 7-82. In Band Emissions Plot MIMO ANT2 (80MHz 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 39) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 89 of 124



Plot 7-83. In Band Emissions Plot MIMO ANT2 (160MHz 802.11ax/be (Full Tones) (UNII Band 5) – Ch. 47) - VLP



Plot 7-84. In Band Emissions Plot MIMO ANT2 (320MHz 802.11be (Full Tones) (UNII Band 5) – Ch. 31) - VLP

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 90 of 124

7.6 Contention Based Protocol

Test Overview and Limit

Indoor access points, subordinate devices and client devices operating in the 5.925-7.125 GHz band (herein referred to as unlicensed devices) are required to use technologies that include a contention-based protocol to avoid co-channel interference with incumbent devices sharing the band. To ensure incumbent co-channel operations are detected in a technology-agnostic manner, unlicensed devices are required to detect co-channel radio frequency energy (energy detect) and avoid simultaneous transmission.

Unlicensed indoor low-power devices must detect co-channel radio frequency power that is at least -62 dBm or lower. Upon detection of energy in the band, unlicensed low power indoor devices must vacate the channel and stay off the channel if detected radio frequency power is equal to or greater than the threshold (-62 dBm). The -62 dBm (or lower) threshold is referenced to a 0 dBi antenna gain.

To ensure incumbent operations are reliably detected in the band, low power indoor devices must detect RF energy throughout their intended operating channel.

Test Procedure Used

KDB 987594 D02 v03

Test Settings

1. Configure the EUT to transmit with a constant duty cycle.
2. Set the operating parameters of the EUT including power level, operating frequency, modulation, and bandwidth.
3. Set the signal analyzer center frequency to the nominal EUT channel center frequency. The span range of the signal analyzer shall be between two times and five times the OBW of the EUT. Connect the output port of the EUT to the signal analyzer 2. Ensure that the attenuator 2 provides enough attenuation to not overload the signal analyzer 2 receiver.
4. Monitoring the signal analyzer 2, verify the EUT is operating and transmitting with the parameters set at step two.
5. Using an AWGN signal source, generate (but do not transmit, i.e., RF OFF) a 10 MHz-wide AWGN signal. Use Table 1 to determine the center frequency of the 10 MHz AWGN signal relative to the EUT's channel bandwidth and center frequency.
6. Set the AWGN signal power to an extremely low level (more than 20 dB below the -62 dBm threshold). Connect the AWGN signal source, via a 3-dB splitter, to the signal analyzer 1 and the EUT as shown in Figure 2.
7. Transmit the AWGN signal (RF ON) and verify its characteristics on the signal analyzer 1.
8. Monitor the signal analyzer 2 to verify if the AWGN signal has been detected and the EUT has ceased transmission. If the EUT continues to transmit, then incrementally increase the AWGN signal power level until the EUT stops transmitting.
9. (Including all losses in the RF paths) Determine and record the AWGN signal power level (at the EUT's antenna port) at which the EUT ceased transmission. Repeat the procedure at least 10 times to verify the EUT can detect an AWGN signal with 90% (or better) level of certainty.
10. Refer to Table 1 of KDB 987594 D02 v01r01 to determine the number of times the detection threshold testing needs to be repeated. If testing is required more than once, then go back to step 5, choose a different center frequency for the AWGN signal, and repeat the process.

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 91 of 124

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Contention-based protocol test setup, conducted method

Test Notes

1. Per guidance from KDB 987594 D02 v01r01, contention based protocol was tested using an AWGN signal with a bandwidth of 10MHz (see Plot 7-85). The amplitude of the signal was increased until detected by the EUT, signaled by the ceasing of transmission (see Plot 7-86), M1 indicates the point at which the AWGN signal is introduced. D1 indicates where the AWGN signal is terminated, at least 10 seconds following M1.
2. 15 trials were run in order to ensure certainty of 90%
3. Per Guidance from KDB 987594 D04 v01, contention based protocol was tested with receiver with the lowest antenna gain.
4. All CBP Timing Plots shown are for the ceased condition. Some spikes that may be shown are from adjacent portions of the spectrum that are still transmitting.
5. In the presence of an AWGN signal, the EUT was shown to either completely move out of the channel or to reduce its bandwidth for the purpose of incumbent avoidance. Representative channel move plots are included for one sub-band to show how the channel reduces when the AWGN is injected at the lower edge, the center, and the upper edge of a channel.
6. This device only punctures to optimize network performance and never to avoid licensed incumbents.
7. For the channel move demonstration in Section 7.6.3, only plots from UNII-5 band are included. Additionally, the AWGN signal is not visible because the AWGN level is well below the noise floor.

$$\text{Detection Level} = \text{Injected AWGN Power (dBm)} - \text{Antenna Gain (dBi)} + \text{Path Loss (dB)}$$

Equation 7-1. Detection Level Calculation

Band	Channel	Channel Freq [MHz]	Channel BW [MHz]	Incumbent Freq [MHz]	Injected (AWGN) [dBm]	Antenna Gain [dBi]	Path Loss (dB)	Adjusted Power Level [dBm]	Detection Limit [dBm]	Margin [dB]
UNII Band 5	53	6215	20	6215	-74.74	-6.49	1.03	-67.22	-62.0	-5.22
				6270	-73.06	-6.49	1.03	-65.54	-62.0	-3.54
	95	6425	320	6425	-73.57	-6.49	1.03	-66.05	-62.0	-4.05
				6580	-73.05	-6.49	1.03	-65.53	-62.0	-3.53
UNII Band 7	149	6695	20	6695	-75.96	-6.97	1.03	-67.96	-62.0	-5.96
				6590	-75.66	-6.97	1.03	-67.66	-62.0	-5.66
	159	6745	320	6745	-75.96	-6.97	1.03	-67.96	-62.0	-5.96
				6900	-75.65	-6.97	1.03	-67.65	-62.0	-5.65

Table 7-42. Contention Based Protocol – Incumbent Detection Results

FCC ID: A3LSMS938U	MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset		Page 92 of 124

Band	Channel	Channel Freq [MHz]	Channel BW [MHz]	Incumbent Freq [MHz]	Antenna Gain [dBi]	EUT Transmission Status			Detection Limit [dBm]	Margin [dB]
						Adjusted AWGN Power (dBm)				
						Normal	Minimal	Ceased		
UNII Band 5	53	6215	20	6215	-6.49	-70.70	-68.62	-67.22	-62.0	-5.22
				6270	-6.49	-69.64	-66.57	-65.54	-62.0	-3.54
	95	6425	320	6425	-6.49	-68.50	-67.10	-66.05	-62.0	-4.05
				6580	-6.49	-67.78	-66.76	-65.53	-62.0	-3.53
UNII Band 7	149	6695	20	6695	-6.97	-70.01	-68.91	-67.96	-62.0	-5.96
				6590	-6.97	-71.52	-70.33	-67.66	-62.0	-5.66
	159	6745	320	6745	-6.97	-70.52	-69.35	-67.96	-62.0	-5.96
				6900	-6.97	-70.19	-68.84	-67.65	-62.0	-5.65


Table 7-43. Contention Based Protocol – Detection Results – All Tx Cases

CBP Detection (1 = Detection, Blank = No Detection)																				
Band	Channel	Channel Freq [MHz]	Channel BW [MHz]	Incumbent Freq [MHz]	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Detection Rate (%)
UNII Band 5	53	6215	20	6215	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
				6270	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
	95	6425	320	6425	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
				6580	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
UNII Band 7	149	6695	20	6695	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
				6590	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
	159	6745	320	6745	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100
				6900	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	100

Table 7-44. Contention Based Protocol – Incumbent Detection Trial Results

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 93 of 124


7.6.1 AWGN Plots



Plot 7-85. AWGN Signal (20MHz (UNII Band 5) – Mid)


FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 94 of 124

7.6.2 CBP Timing Plots



Date: 22.OCT.2024 06:55:53


Plot 7-86. Contention Based Protocol Timing Plot (20MHz (UNII Band 5) – Ch. 53)




Date: 29.OCT.2024 13:53:36

Plot 7-87. Contention Based Protocol Timing Plot (320MHz (UNII Band 5) – Ch. 47 Low)

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 95 of 124




Plot 7-88. Contention Based Protocol Timing Plot (320MHz (UNII Band 5) – Ch. 47 Mid)




Plot 7-89. Contention Based Protocol Timing Plot (320MHz (UNII Band 5) – Ch. 47 High)

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 96 of 124



Date: 22.OCT.2024 07:17:09

Plot 7-90. Contention Based Protocol Timing Plot (20MHz (UNII Band 7) – Ch. 149)



Date: 29.OCT.2024 13:50:29

Plot 7-91. Contention Based Protocol Timing Plot (320MHz (UNII Band 7) – Ch. 175 Low)

FCC ID: A3LSMS938U	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2408260067-33-R1.A3L	Test Dates: 09/03/2024 - 10/31/2024	EUT Type: Portable Handset	Page 97 of 124