

NR Band n12 Antenna A

NR Band n12 Antenna A Measured Pmax for RSI = 0 (Body-worn, or Phablet), RSI = 1 (Head), RSI = 2 (Hotspot) - 10 MHz Bandwidth							
NR Band n12 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	141500 (707.5 MHz)				
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.63			0	0.0
	1	26	23.71				0.0
	1	50	23.77				0.0
	25	0	22.67			0-1	1.0
	25	14	23.72			0	0.0
	25	27	22.76			0-1	1.0
50	0	22.72			1.0		
DFT-s-OFDM 16QAM	1	1	22.63			0-1	1.0
CP-OFDM QPSK	1	1	22.15			0-1.5	1.5

NR Band n12 Antenna A Measured Pmax for RSI = 0 (Body-worn, or Phablet), RSI = 1 (Head), RSI = 2 (Hotspot) - 5 MHz Bandwidth							
NR Band n12 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	140300 (701.5 MHz)				
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.73			0	0.0
	1	13	23.77				0.0
	1	23	23.71				0.0
	12	0	22.76			0-1	1.0
	12	7	23.77			0	0.0
	12	13	22.73			0-1	1.0
	25	0	22.76				1.0
DFT-s-OFDM 16QAM	1	1	22.84			0-1	1.0
CP-OFDM QPSK	1	1	22.37			0-1.5	1.5

NR Band n12 Antenna E

NR Band n12 Antenna E Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 10 MHz Bandwidth

NR Band n12 10 MHz Bandwidth								
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]	
Modulation	RB Size	RB Offset	141500 (707.5 MHz)					
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	20.39				0	0.0
	1	26	20.44					0.0
	1	50	20.41					0.0
	25	0	20.44				0-1	0.0
	25	14	20.48				0	0.0
	25	27	20.44				0-1	0.0
DFT-s-OFDM 16QAM	1	1	20.41				0-1	0.0
CP-OFDM QPSK	1	1	20.42				0-1.5	0.0

NR Band n12 Antenna E Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 5 MHz Bandwidth

NR Band n12 5 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	140300 (701.5 MHz)	141500 (707.5 MHz)	142700 (713.5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	20.41	20.48	20.43		0	0.0
	1	13	20.37	20.47	20.38			0.0
	1	23	20.44	20.46	20.46		0.0	
	12	0	20.48	20.47	20.47		0-1	0.0
	12	7	20.46	20.49	20.48		0	0.0
	12	13	20.45	20.46	20.48		0	0.0
	25	0	20.47	20.49	20.48		0-1	0.0
DFT-s-OFDM 16QAM	1	1	20.49	20.47	20.44		0-1	0.0
CP-OFDM QPSK	1	1	20.48	20.49	20.44		0-1.5	0.0

NR Band n12 Antenna E Measured Plimit for RSI = 1 (Head) - 10 MHz Bandwidth

NR Band n12 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	141500 (707.5 MHz)				
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18,24			0	0,0
	1	26	18,33				0,0
	1	50	18,31				0,0
	25	0	18,23			0-1	0,0
	25	14	18,30			0	0,0
	25	27	18,33			0	0,0
DFT-s-OFDM 16QAM	50	0	18,26			0-1	0,0
	1	1	18,20			0-1	0,0
CP-OFDM QPSK	1	1	18,29			0-1,5	0,0

NR Band n12 Antenna E Measured Plimit for RSI = 1 (Head) - 5 MHz Bandwidth

NR Band n12 5 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	140300 (701.5 MHz)	141500 (707.5 MHz)	142700 (713.5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	18.53	18.27	18.26		0	0.0
	1	13	18.20	18.25	18.32			0.0
	1	23	18.26	18.32	18.29		0-1	0.0
	12	0	18.32	18.33	18.32			0.0
	12	7	18.19	18.25	18.26		0	0.0
	12	13	18.24	18.31	18.35		0-1	0.0
	25	0	18.21	18.30	18.28			0.0
DFT-s-OFDM 16QAM	1	1	18.81	18.23	18.51		0-1	0.0
CP-OFDM QPSK	1	1	18.55	18.31	18.35		0-1.5	0.0

NR Band n26 Antenna A

NR Band n26 Antenna A Measured Pmax for RSI = 0 (Body-worn, or Phablet), RSI = 1 (Head), RSI = 2 (Hotspot) - 15 MHz Bandwidth

NR Band n26 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	164300 (821.5 MHz)	168300 (841.5 MHz)			
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.22	23.18		0	0.0
	1	40	23.21	23.10			0.0
	1	77	23.30	23.28			0.0
	36	0	22.22	22.54		0-1	0.0
	36	22	23.29	23.44		0	1.0
	36	43	22.32	22.46		0-1	1.0
DFT-s-OFDM 16QAM	75	0	22.37	22.41		0-1	1.0
	1	1	22.31	22.31			1.0
CP-OFDM QPSK	1	1	22.14	22.18		0-1.5	1.5

NR Band n26 Antenna A Measured Pmax for RSI = 0 (Body-worn, or Phablet), RSI = 1 (Head), RSI = 2 (Hotspot) - 10 MHz Bandwidth

NR Band n26 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	163800 (819 MHz)	166300 (831.5 MHz)	169800 (844 MHz)	Channel	
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.20	23.19	23.24		0.0
	1	26	23.24	23.24	23.35		0.0
	1	50	23.29	23.34	23.31		0.0
	25	0	22.54	22.54	22.22		0-1
	25	14	23.32	23.26	23.17		0
	25	27	22.30	22.23	22.16		0-1
DFT-s-OFDM 16QAM	50	0	22.26	22.26	22.22		1.0
	1	1	22.24	22.19	22.24		0-1
CP-OFDM QPSK	1	1	22.17	22.11	22.13		0-1.5

NR Band n26 Antenna A Measured Pmax for RSI = 0 (Body-worn, or Phablet), RSI = 1 (Head), RSI = 2 (Hotspot) - 5 MHz Bandwidth

NR Band n26 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	163300 (816.5 MHz)	166300 (831.5 MHz)	169300 (846.5 MHz)	Channel	
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.23	23.24	23.32		0.0
	1	13	23.34	23.19	23.17		0.0
	1	23	23.36	23.27	23.19		0.0
	12	0	22.24	22.16	22.21		0-1
	12	7	23.26	23.25	23.27		0
	12	13	22.27	22.19	22.16		0-1
DFT-s-OFDM 16QAM	25	0	22.21	22.18	22.24		1.0
	1	1	22.24	22.20	22.13		0-1
CP-OFDM QPSK	1	1	22.15	22.10	22.16		0-1.5

NR Band n26 Antenna E

NR Band n26 Antenna E Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 15 MHz Bandwidth									
NR Band n26 15 MHz Bandwidth									
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]	
Modulation	RB Size	RB Offset	164300 (821.5 MHz)	168300 (841.5 MHz)					
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	20.33	20.22				0	0.0
	1	40	20.25	20.25					0.0
	1	77	20.29	20.47				0.0	
	36	0	20.34	20.30				0-1	0.0
	36	22	20.31	20.36				0	0.0
	36	43	20.27	20.42				0-1	0.0
	75	0	20.33	20.33					0.0
DFT-s-OFDM 16QAM	1	1	20.28	20.27				0-1	0.0
CP-OFDM QPSK	1	1	20.36	20.28				0-1.5	0.0

NR Band n26 Antenna E Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 10 MHz Bandwidth								
NR Band n26 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163800 (819 MHz)	166300 (831.5 MHz)	168800 (844 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	20.38	20.24	20.44		0	0.0
	1	26	20.36	20.29	20.55			0.0
	1	50	20.29	20.38	20.53			0.0
	25	0	20.37	20.27	20.49		0-1	0.0
	25	14	20.38	20.30	20.54		0	0.0
	25	27	20.34	20.37	20.60		0-1	0.0
	50	0	20.35	20.32	20.47			0.0
DFT-s-OFDM 16QAM	1	1	20.37	20.22	20.42		0-1	0.0
CP-OFDM QPSK	1	1	20.37	20.25	20.43		0-1.5	0.0

NR Band n26 Antenna E Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 5 MHz Bandwidth								
NR Band n26 5 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163300 (816,5 MHz)	166300 (831,5 MHz)	169300 (846,5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	20,38	20,24	20,44			0,0
	1	13	20,36	20,29	20,55		0	0,0
	1	23	20,29	20,38	20,53			0,0
	12	0	20,37	20,27	20,49		0-1	0,0
	12	7	20,38	20,30	20,54		0	0,0
	12	13	20,34	20,37	20,60		0-1	0,0
	25	0	20,35	20,32	20,47			0,0
DFT-s-OFDM 16QAM	1	1	20,37	20,22	20,42		0-1	0,0
CP-OFDM QPSK	1	1	20,37	20,25	20,43		0-1,5	0,0

NR Band n26 Antenna E Measured Plimit for RSI = 1 (Head) - 15 MHz Bandwidth

NR Band n26 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	164300 (821.5 MHz)	168300 (841.5 MHz)			
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.02	18.17		0	0.0
	1	40	18.16	18.22			0.0
	1	77	18.18	18.32			0.0
	36	0	18.11	18.24		0-1	0.0
	36	22	18.14	18.33		0	0.0
	36	43	18.19	18.35		0-1	0.0
	75	0	18.14	18.31			0.0
DFT-s-OFDM 16QAM	1	1	18.03	18.16		0-1	0.0
CP-OFDM QPSK	1	1	18.03	18.20		0-1.5	0.0

NR Band n26 Antenna E Measured Plimit for RSI = 1 (Head) - 10 MHz Bandwidth

NR Band n26 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163800 (819 MHz)	166300 (831.5 MHz)	168800 (844 MHz)	Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.12	18.02	18.21		0	0.0
	1	26	18.14	18.16	18.31		0.0	
	1	50	18.07	18.18	18.27		0.0	
	25	0	18.16	18.11	18.30		0.0	
	25	14	18.16	18.14	18.34		0.0	
	25	27	18.16	18.19	18.34		0.0	
	50	0	18.15	18.14	18.32		0.0	
DFT-s-OFDM 16QAM	1	1	18.15	18.03	18.26		0-1	0.0
CP-OFDM QPSK	1	1	18.18	18.03	18.24		0-1.5	0.0

NR Band n26 Antenna E Measured Plimit for RSI = 1 (Head) - 5 MHz Bandwidth

NR Band n26 5 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163300 (816.5 MHz)	166300 (831.5 MHz)	169300 (846.5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	18.17	18.06	18.38		0	0.0
	1	13	18.12	18.05	18.54		0.0	
	1	23	18.17	18.12	18.39		0.0	
	12	0	18.22	18.10	18.49		0.0	
	12	7	18.20	18.11	18.43		0.0	
	12	13	18.18	18.14	18.40		0.0	
	25	0	18.19	18.13	18.42		0.0	
DFT-s-OFDM 16QAM	1	1	18.17	18.08	18.39		0-1	0.0
CP-OFDM QPSK	1	1	18.18	18.62	18.40		0-1.5	0.0

NR Band n66 Antenna A

NR Band n66 Antenna A Measured Pmax for RSI = 1 (Head) - 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	349000 (1745 MHz)				
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.19			0	0.0
	1	80	23.49				0.0
	1	156	23.53				0.0
	80	0	22.28			0-1	1.0
	80	40	23.44			0	0.0
	80	80	22.54			0-1	1.0
	160	0	22.60				1.0
DFT-s-OFDM 16QAM	1	1	22.17			0-1	1.0
CP-OFDM QPSK	1	1	21.72			0-1.5	1.5

NR Band n66 Antenna A Measured Pmax for RSI = 1 (Head) - 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth								
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]	
Modulation	RB Size	RB Offset	349000 (1745 MHz)					
				Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.20				0	0.0
	1	67	23.45					0.0
	1	131	23.55					0.0
	64	0	22.34				0-1	1.0
	64	35	23.52				0	0.0
	64	69	22.60				0-1	1.0
	128	0	22.49					1.0
DFT-s-OFDM 16QAM	1	1	22.17				0-1	1.0
CP-OFDM QPSK	1	1	21.74				0-1.5	1.5

NR Band n66 Antenna A Measured Pmax for RSI = 1 (Head) - 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	23.23	23.40	23.67		0	0.0
	1	53	23.48	23.65	23.82			0.0
	1	104	23.58	23.74	23.53			0.0
	50	0	22.37	22.47	22.61		0	0.0
	50	28	23.52	23.60	23.80		0	0.0
	50	56	22.59	22.72	22.59		0-1	1.0
	100	0	22.46	22.60	22.80		1.0	
DFT-s-OFDM 16QAM	1	1	22.20	22.40	22.85		0-1	1.0
CP-OFDM QPSK	1	1	21.73	21.91	22.19		0-1.5	1.5

NR Band n66 Antenna A Measured Pmax for RSI = 1 (Head) - 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	23.18	23.29	23.40		0	0.0
	1	40	23.15	23.42	23.32			0.0
	1	77	23.14	23.36	23.36			0.0
	36	0	22.24	22.37	22.39		0-1	1.0
	36	22	23.22	23.50	23.41		0	0.0
	36	43	22.19	22.57	22.37		0-1	1.0
	75	0	22.22	22.45	22.41			1.0
DFT-s-OFDM 16QAM	1	1	22.21	22.26	22.37		0-1	1.0
CP-OFDM QPSK	1	1	21.70	21.81	21.89		0-1.5	1.5

NR Band n66 Antenna A Measured Pmax for RSI = 1 (Head) - 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	23.23	23.33	23.47		0	0.0
	1	26	23.35	23.45	23.45			0.0
	1	50	23.20	23.55	23.42			0.0
	25	0	22.27	22.41	22.49		0-1	1.0
	25	14	23.27	23.49	23.47		0	0.0
	25	27	22.24	22.55	22.48		0-1	1.0
DFT-s-OFDM 16QAM	50	0	22.27	22.47	22.48		0-1	1.0
	1	1	22.20	22.33	22.47			1.0
CP-OFDM QPSK	1	1	21.72	21.85	22.01		0-1.5	1.5

NR Band n66 Antenna A Measured Pmax for RSI = 1 (Head) - 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)	Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.12	23.42	23.41		0	0.0
	1	13	23.11	23.41	23.35			0.0
	1	23	23.13	23.49	23.39			0.0
	12	0	22.16	22.43	22.43		0-1	1.0
	12	7	23.18	23.50	23.43		0	0.0
	12	13	22.18	22.51	22.42		0-1	1.0
	25	0	22.18	22.48	22.43		0-1	1.0
	DFT-s-OFDM 16QAM	1	1	22.13	22.35		22.42	
CP-OFDM QPSK	1	1	21.63	21.92	21.91		0-1.5	1.5

NR Band n66 Antenna A Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth								
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]	
Modulation	RB Size	RB Offset	349000 (1745 MHz)					
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.32				0	0.0
	1	80	17.36					0.0
	1	158	17.42					0.0
	80	0	17.19				0-1	0.0
	80	40	17.32				0	0.0
	80	80	17.48				0-1	0.0
	160	0	17.40				0-1	0.0
DFT-s-OFDM 16QAM	1	1	17.09				0-1	0.0
CP-OFDM QPSK	1	1	17.08				0-1.5	0.0

NR Band n66 Antenna A Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	349000 (1745 MHz)			
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.22		0	0.0
	1	67	17.30			0.0
	1	131	17.40			0.0
	64	0	17.20		0-1	0.0
	64	35	17.35		0	0.0
	64	69	17.49		0-1	0.0
	128	0	17.34		0-1	0.0
DFT-s-OFDM 16QAM	1	1	17.06		0-1	0.0
CP-OFDM QPSK	1	1	17.06		0-1.5	0.0

NR Band n66 Antenna A Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.06	17.18	17.43		0	0.0
	1	53	17.30	16.96	17.29			0.0
	1	104	17.45	16.95	17.34			0.0
	50	0	17.25	17.01	17.40		0-1	0.0
	50	28	17.33	17.03	17.39		0	0.0
	50	56	17.44	16.99	17.33		0-1	0.0
	100	0	17.34	17.02	17.38			0.0
DFT-s-OFDM 16QAM	1	1	17.12	16.96	17.38		0-1	0.0
CP-OFDM QPSK	1	1	17.07	17.02	17.44		0-1.5	0.0

NR Band n66 Antenna A Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.09	17.17	17.25		0	0.0
	1	40	17.05	17.30	17.19			0.0
	1	77	17.04	17.44	17.20			0.0
	36	0	17.13	17.30	17.29		0-1	0.0
	36	22	17.12	17.36	17.25		0	0.0
	36	43	17.11	17.46	17.23		0-1	0.0
	72	0	17.15	17.33	17.28			0.0
DFT-s-OFDM 16QAM	1	1	17.09	17.19	17.24		0-1	0.0
CP-OFDM QPSK	1	1	17.10	17.16	17.26		0-1.5	0.0

NR Band n66 Antenna A Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.09	17.21	17.36		0	0.0
	1	26	17.24	17.35	17.33			0.0
	1	50	17.09	17.43	17.30			0.0
	25	0	17.15	17.32	17.36		0-1	0.0
	25	14	17.14	17.38	17.36		0	0.0
	25	27	17.12	17.43	17.35		0-1	0.0
	50	0	17.17	17.36	17.38			0.0
DFT-s-OFDM 16QAM	1	1	17.14	17.26	17.42		0-1	0.0
CP-OFDM QPSK	1	1	17.15	17.23	17.36		0-1.5	0.0

NR Band n66 Antenna A Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.00	17.25	17.26		0	0.0
	1	13	16.93	17.26	17.20			0.0
	1	23	16.99	17.34	17.25			0.0
	12	0	17.01	17.28	17.29		0-1	0.0
	12	7	17.01	17.33	17.28		0	0.0
	12	13	17.04	17.35	17.27		0-1	0.0
	25	0	17.03	17.30	17.29			0.0
DFT-s-OFDM 16QAM	1	1	16.96	17.22	17.20		0-1	0.0
CP-OFDM QPSK	1	1	16.95	17.24	17.26		0-1.5	0.0