



**ELEMENT MATERIALS TECHNOLOGY,
Columbia MD**

(formerly PCTEST)

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.element.com>

**MEASUREMENT REPORT
FCC Part 15.247 Bluetooth (Low Energy)**

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

9/2/25 - 1/9/26

Test Report Issue Date:

1/13/2026

Test Site/Location:

Element Lab., Columbia, MD, USA

Test Report Serial No.:

1M2508270084-13-R1.A3L

FCC ID:

A3LSMS942B

APPLICANT:

Samsung Electronics Co., Ltd.

Application Type:

Certification

Model:

SM-S942B/DS

Additional Model(s):

SM-S942B

EUT Type:

Portable Handset

Max. RF Output Power:

48.328 mW (16.84 dBm) Peak Conducted

Frequency Range:

2402 – 2480MHz

FCC Classification:

Digital Transmission System (DTS)

FCC Rule Part(s):

Part 15 Subpart C (15.247)

Test Procedure(s):

ANSI C63.10:2020 + Cor. 1:2023, KDB 648474 D03 v01r04

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10:2020. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1M2508270084-13-R1.A3L) supersedes and replaces the previously issued test report (S/N: 1M2508270084-13.A3L) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

**RJ Ortanez
Executive Vice President**



FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 1 of 113

TEST REPORT REVISION HISTORY

Rev. No.	Description	Issue Date	Revised By
-	Initial Release	1/12/2026	WKR0000005883
1	Addressed comments made by TCB reviewer	1/13/2026	WKR0000005883

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 2 of 113

TABLE OF CONTENTS

1.0	INTRODUCTION	4
1.1	Scope.....	4
1.2	Element Test Location	4
1.3	Test Facility / Accreditations	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description	5
2.2	Device Capabilities	5
2.3	Antenna Description.....	5
2.4	Test Configuration.....	6
2.5	Software and Firmware	6
2.6	EMI Suppression Device(s)/Modifications.....	6
3.0	DESCRIPTION OF TESTS	7
3.1	Evaluation Procedure.....	7
3.2	AC Line Conducted Emissions.....	7
3.3	Radiated Emissions	8
3.4	Environmental Conditions	8
4.0	ANTENNA REQUIREMENTS	9
5.0	MEASUREMENT UNCERTAINTY	10
6.0	TEST EQUIPMENT CALIBRATION DATA	11
7.0	TEST RESULTS.....	14
7.1	Summary.....	14
7.2	6dB Bandwidth Measurement – Bluetooth (LE)	15
7.3	Output Power Measurement – Bluetooth (LE)	35
7.4	Power Spectral Density – Bluetooth (LE).....	54
7.5	Conducted Emissions at the Band Edge.....	73
7.6	Conducted Spurious Emissions	84
7.7	Radiated Spurious Emission Measurements	98
7.8	Line-Conducted Test Data	109
8.0	CONCLUSION.....	113

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 3 of 113

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Test Location

Measurements were conducted at the Element laboratory(ies) indicated in Section 1.3 below. All measurement facilities are compliant with the test site requirements specified in ANSI C63.4:2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at Element lab located in Columbia, MD 21046, U.S.A.

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Washington DC LLC facility is a registered test laboratory with the site description on file with ISED (Wireless Test Lab number 2451B) and FCC (Designation Number US1113).
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 4 of 113

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMS942B**. The data found in this test report was taken with the EUT operating in Bluetooth low energy mode. While in low energy mode, the Bluetooth transmitter hops pseudo-randomly between 40 channels, three of which are “advertising channels”. When the transmitter is hopping only between the three advertising channels, the EUT does not fall under the category of a “hopper” as defined in 15.247(a)(iii) which states that a “frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.” As operation on only the advertising channels does not qualify the EUT as a hopper, the EUT is certified as a DTS device in this mode. The data found in this report is representative of the device when it transmits on its advertising channels. Typical Bluetooth operation is covered under the DSS report found with this application.

Test Device Serial No.: 0282M, 0064M, 0111M, 0067M, 0001M, 0018M, 0086M, 0015M

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, Multi-band 5G NR (FR1), 802.11b/g/n/ac/ax/be WLAN, 802.11a/n/ac/ax/be UNII (5GHz and 6GHz), Bluetooth (1x, EDR, LE), NFC, Wireless Power Transfer

Ch.	Frequency (MHz)
37	2402
:	:
17	2440
:	:
39	2480

Table 2-1. Frequency / Channel Operations – 125/500kbps & 1Mbps

Ch.	Frequency (MHz)
0	2404
:	:
17	2440
:	:
36	2478

Table 2-2. Frequency / Channel Operations – 2Mbps

2.3 Antenna Description

The manufacturer provided the antenna gains which can affect the validity of test results used for determination of compliance. The following antenna gains are used in this device per the "Unlicensed Band Antenna Gain" document provided by the client. This document is also included in the filing as a public exhibit.

Frequency [GHz]	Antenna-1 Gain (dBi)	Antenna-2 Gain (dBi)	Directional Antenna Gain (dBi)
2.4	-2.88	-3.09	0.03

Table 2-3. Antenna Peak Gain

Note: This device is capable of operating in hopping and non-hopping mode. The EUT can hop between 79 different channels in the 2400 – 2483.5MHz band.

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 5 of 113

2.4 Test Configuration

The EUT was tested per the guidance of ANSI C63.10:2020. ANSI C63.10:2020 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5, and 7.6 for antenna port conducted emissions test setups.

The emissions below 1GHz and above 18GHz were tested with the highest transmitting power channel and the worst case configuration.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report. The worst orientation was found to be Y-orientation (landscape).

For AC line conducted and radiated test below 1GHz, following configuration were investigated and EUT powered by AC/DC was the worst case.

- EUT powered by AC/DC adaptor via USB cable with wire charger
- EUT powered by host PC via USB cable with wire charger

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on an authorized wireless charging pad (WCP) FCC ID: EP-2400 while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

2.5 Software and Firmware

The test was conducted with software/firmware version S942BXXU0AYI8 installed on the EUT.

2.6 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 6 of 113

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10:2020) and the guidance provided in KDB 558074 D01 v05r02 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that those cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.9. The EMI Receiver mode of the Agilent MXE was used to perform AC line conducted emissions testing.

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 7 of 113

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4:2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4:2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01 v01r01.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 8 of 113

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna(s) of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 9 of 113

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10:2020. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.13
Line Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

Table 5-1. Measurement Uncertainty Budget

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 10 of 113

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurement antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	MD 1M 40	EMC Cable and Switch System	2/25/2025	Annual	2/25/2026	MD 1M 40
-	AP1-002	EMC Cable and Switch System	2/25/2025	Annual	2/25/2026	AP1-002
-	AP2-001	EMC Cable and Switch System	2/25/2025	Annual	2/25/2026	AP2-001
-	AP2-002	EMC Cable and Switch System	2/25/2025	Annual	2/25/2026	AP2-002
-	ETS-001	EMC Cable and Switch System	2/25/2025	Annual	2/25/2026	ETS-001
-	ETS-002	EMC Cable and Switch System	2/25/2025	Annual	2/25/2026	ETS-002
-	WL25-1	Conducted Cable Set (25GHz)	2/25/2025	Annual	2/25/2026	WL25-1
-	WL25-2	Conducted Cable Set (25GHz)	2/25/2025	Annual	2/25/2026	WL25-2
-	WL40-1	Conducted Cable Set (40GHz)	2/25/2025	Annual	2/25/2026	WL40-1
Agilent	N9038A	MXE EMI Receiver	11/10/2025	Annual	11/10/2026	MY51210133
Anritsu	MA24408A	POWER SENSOR	2/11/2025	Annual	2/11/2026	12776
EMCO	3115	Horn Antenna (1-18GHz)	9/6/2024	Biennial	9/6/2026	9704-5182
Espec	ESX-2CA	Environmental Chamber	11/20/2024	Biennial	11/20/2026	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	6/4/2025	Biennial	6/4/2027	125518
ETS-Lindgren	3164-05	Quad Ridge Horn (Small) 2 - 18GHz	6/4/2025	Biennial	6/4/2027	208255
ETS-Lindgren	3816/2NM	Line Impedance Stabilization Network	4/21/2025	Biennial	4/21/2027	114451
Keysight Technologies	N9030A	PXA Signal Analyzer (44GHz)	6/6/2025	Annual	6/6/2026	MY52350166
Keysight Technologies	N9020A	MXA Signal Analyzer	6/4/2025	Annual	6/4/2026	MY54500644
Keysight Technologies	N9030A	PXA Signal Analyzer	11/3/2025	Annual	11/3/2026	MY54490576
Pasternack	NMLC-2	Line Conducted Emissions Cable (NM)	3/25/2025	Annual	3/25/2026	NMLC-2
Rohde & Schwarz	ESW44	EMI Test Receiver 2Hz to 44 GHz	3/25/2025	Annual	3/25/2026	101716
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	12/19/2025	Annual	12/19/2026	100342
Rohde & Schwarz	180-422-KF	Horn (18 - 40GHz)	10/9/2024	Biennial	10/9/2026	U157403-01
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	9/11/2024	Biennial	9/11/2026	A051107
Sunol	JB6	Bi-Log Antenna (30M - 5GHz)	3/24/2025	Biennial	3/24/2027	A082816

Table 6-1. Test Equipment Calibration Table

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

Equipment listed with "N/A under calibration information was not used to make calibrated measurements.

Component	Serial Number
MegaPhase Cable TM26-S1S1-36	18160103 003
Pasternack 6dB Attenuator PE7005-6	N/A

Table 6-2. WL25-1 Conducted Cable Set Components

Component	Serial Number
MiniCircuits Cable CBL-2FT-SMSM+	77743
MCL 6dB Attenuator BW-S6W2+	1314

Table 6-3. WL25-2 Conducted Cable Set Components

Component	Serial Number
MegaPhase Cable TM40K1K1-36	18160102 001
MCL 10dB Attenuator BW-K10 2W44+	1902

Table 6-4. WL40-1 Conducted Cable Set Components

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 11 of 113

Component	Serial Number
Pasternack Cable RG214/U	111815
MegaPhase (CAGE 1GVT4) Cable GR18-N5N5-24	14042714 001

Table 6-5. ETS-001 EMC Cable and Switch System Components

Component	Serial Number
MegaPhase (CAGE 1GVT4) Cable GR18-N5N5-24	14042714 001
MegaPhase (CAGE 1GVT4) Cable NC29-N1N1-324	20502201 001
Rohde & Schwarz SF Unit	102134
Minicircuits Cable CBL=0.5M-NMNM+	15440

Table 6-6. ETS-002 EMC Cable and Switch System Components

Component	Serial Number
Sucoflex 106A Cable	501992
MegaPhase Cable N29-N1N1-324	20335606 001
Rohde & Schwarz SF Unit	102133
MiniCircuits Cable CBL-2FT-SMSM+	77745
MegaPhase Cable 10511-1	15034701 001
MiniCircuits Switch RC 2SPDT-A18	11703270 041
Sucoflex 104 Cable	320259/4
Sucoflex 104 Cable	321999/4
Sucoflex 104 Cable	321995/4

Table 6-7. AP1-002 EMC Cable and Switch System Components

Component	Serial Number
Flex Cable	P2A-0001
Micro-Coax Utilifex Cable UFB311A-Q-3346-50U50U MFR 64639	231978-003
Chamber Passthrough	CP4/X12
Micro-Coax Utilifex Cable UFB311A-1-0629-50U50U MFR 64639	231986-003
Micro-Coax Utilifex Cable UFB142A-0-0629-5GU200 MFR 6463	232069-001
Rohde & Schwarz TS-PR8 Pre-Amplifier	102335
Rohde & Schwarz OSP130 Open Switch and Control Unit	101181

Table 6-8. AP2-001 EMC Cable and Switch System Components

Component	Serial Number
MiniCircuits Cable CBL-0.5M-SMNM+	47261
Micro-Coax Utilifex Cable UFB311A-Q-3346-50U50U MFR 64639	231978-001
Micro-Coax Utilifex Cable UFB311A-1-0629-50U50U MFR 64639	231986-002
MegaPhase (CAGE 1GVT4) Cable NC29-N1N1-324	19046401 001
Megaphase (CAGE 1GVT4) Flex Cable 10511-1	15044701-006
Micro-Coax Utilifex Cable UFB311A-Q-3346-50U50U MFR 64639	231978-002
Micro-Coax Utilifex Cable UFB311A-1-0629-50U50U MFR 64639	231986-004
Micro-Coax Utilifex Cable UFB142A-0-0629-5GU200 MFR 64639	232069-001
Rohde & Schwarz SF Unit	102138
Rohde & Schwarz OSP130 Open Switch and Control Unit	101181
Micro-Coax Utilifex Cable UFB311A-Q-3346-50U50U MFR 64639	231978-003
Micro-Coax Utilifex Cable UFB311A-1-0629-50U50U MFR 64639	231986-003
Rohde & Schwarz TS-PR8 Pre-Amplifier	102335

Table 6-9. AP2-002 EMC Cable and Switch System Components

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 12 of 113

Component	Serial Number
MegaPhase Cable TM40-K1K1-30	20233002-004
UTIPLEX Cable	64639 232063-001
Rohde & Schwarz Pre-amp RS-PR1840 18G-40G	9037.7670.02

Table 6-10. MD 1M 18-40 EMC Cable and Switch System Components

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 13 of 113

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMS942B
 FCC Classification: Digital Transmission System (DTS)
 Number of Channels: 40

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	6dB Bandwidth	> 500kHz	CONDUCTED	PASS	Section 7.2
15.247(b)(3)	Transmitter Output Power	< 1 Watt		PASS	Sections 7.3
15.247(e)	Transmitter Power Spectral Density	< 8dBm / 3kHz Band		PASS	Section 7.4
15.247(d)	Band Edge / Out-of-Band Emissions	≥ 20dBc		PASS	Sections 7.5, 7.6
15.205 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])	RADIATED	PASS	Sections 7.7, 7.8
15.207	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits (RSS-Gen[8.8])	LINE CONDUCTED	PASS	Section 7.9

Table 7-1. Summary of Test Results

Notes:

1. All modes of operation were investigated. The test results shown in the following sections represent the worst case emissions.
2. The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
3. All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
4. For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element “Bluetooth LE Automation,” Version 3.6.
5. For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element “Chamber Automation,” Version 1.3.1.

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 14 of 113

7.2 6dB Bandwidth Measurement – Bluetooth (LE)

Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the transmitter antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible 6dB bandwidth is 500 kHz.

Test Procedure Used

ANSI C63.10:2020 – Section 11.8.2 Option 2

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes


None

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 15 of 113


Frequency [MHz]	Data Rate	Channel No.	Bluetooth Mode	Measured Bandwidth [kHz]	Minimum Bandwidth [kHz]	Pass / Fail
2402	125 kbps	37	LE	608.0	500	Pass
2440	125 kbps	17	LE	611.8	500	Pass
2480	125 kbps	39	LE	608.3	500	Pass
2402	500 kbps	37	LE	660.0	500	Pass
2440	500 kbps	17	LE	664.9	500	Pass
2480	500 kbps	39	LE	661.4	500	Pass
2402	1 Mbps	37	LE	689.7	500	Pass
2440	1 Mbps	17	LE	699.8	500	Pass
2480	1 Mbps	39	LE	695.1	500	Pass
2404	2 Mbps	0	LE	1172.3	500	Pass
2440	2 Mbps	17	LE	1175.3	500	Pass
2478	2 Mbps	36	LE	1179.5	500	Pass

Table 7-2. Conducted 6dB Bandwidth Measurements – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 16 of 113




Plot 7-1. 6dB Bandwidth Plot (Bluetooth (LE), 125kbps – Ch. 37) – Ant 1




Plot 7-2. 6dB Bandwidth Plot (Bluetooth (LE), 125kbps – Ch. 17) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 17 of 113




Plot 7-3. 6dB Bandwidth Plot (Bluetooth (LE), 125kbps – Ch. 39) – Ant 1




Plot 7-4. 6dB Bandwidth Plot (Bluetooth (LE), 500kbps – Ch. 37) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 18 of 113



Plot 7-5. 6dB Bandwidth Plot (Bluetooth (LE), 500kbps – Ch. 17) – Ant 1




Plot 7-6. 6dB Bandwidth Plot (Bluetooth (LE), 500kbps – Ch. 39) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 19 of 113



Plot 7-7. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 37) – Ant 1



Plot 7-8. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 17) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 20 of 113



Plot 7-9. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 39) – Ant 1



Plot 7-10. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 0) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 21 of 113



Plot 7-11. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 17) – Ant 1




Plot 7-12. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 36) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 22 of 113

Frequency [MHz]	Data Rate	Channel No.	Bluetooth Mode	Measured Bandwidth [kHz]	Minimum Bandwidth [kHz]	Pass / Fail
2402	1 Mbps	37	LE	671.7	500	Pass
2440	1 Mbps	17	LE	670.5	500	Pass
2480	1 Mbps	39	LE	672.7	500	Pass
2404	2 Mbps	0	LE	1157.0	500	Pass
2440	2 Mbps	17	LE	1163.0	500	Pass
2478	2 Mbps	36	LE	1164.6	500	Pass

Table 7-3. Conducted 6dB Bandwidth Measurements – Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 23 of 113




Plot 7-13. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 37) – Ant 2




Plot 7-14. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 17) – Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 24 of 113



Plot 7-15. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 39) – Ant 2




Plot 7-16. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 0) – Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 25 of 113



Plot 7-17. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 17) – Ant 2



Plot 7-18. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 36) – Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 26 of 113

Frequency [MHz]	Data Rate	Channel No.	Bluetooth Mode	Measured Bandwidth [kHz]	Minimum Bandwidth [kHz]	Pass / Fail
2402	1 Mbps	37	LE	681.8	500	Pass
2440	1 Mbps	17	LE	669.8	500	Pass
2480	1 Mbps	39	LE	694.2	500	Pass
2404	2 Mbps	0	LE	1165.6	500	Pass
2440	2 Mbps	17	LE	1158.5	500	Pass
2478	2 Mbps	36	LE	1161.0	500	Pass

Table 7-4. Conducted 6dB Bandwidth Measurements – Dual Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 27 of 113




Plot 7-19. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 37) – Dual Ant 1




Plot 7-20. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 17) – Dual Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 28 of 113




Plot 7-21. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 39) – Dual Ant 1




Plot 7-22. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 0) – Dual Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 29 of 113



Plot 7-23. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 17) – Dual Ant 1




Plot 7-24. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 36) – Dual Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 30 of 113


Frequency [MHz]	Data Rate	Channel No.	Bluetooth Mode	Measured Bandwidth [kHz]	Minimum Bandwidth [kHz]	Pass / Fail
2402	1 Mbps	37	LE	665.2	500	Pass
2440	1 Mbps	17	LE	668.6	500	Pass
2480	1 Mbps	39	LE	678.8	500	Pass
2404	2 Mbps	0	LE	1155.7	500	Pass
2440	2 Mbps	17	LE	1151.7	500	Pass
2478	2 Mbps	36	LE	1148.0	500	Pass

Table 7-5. Conducted 6dB Bandwidth Measurements – Dual Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 31 of 113




Plot 7-25. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 37) – Dual Ant 2




Plot 7-26. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 17) – Dual Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 32 of 113




Plot 7-27. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 39) – Dual Ant 2




Plot 7-28. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 0) – Dual Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 33 of 113



Plot 7-29. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 17) – Dual Ant 2



Plot 7-30. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 36) – Dual Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 34 of 113

7.3 Output Power Measurement – Bluetooth (LE)

Test Overview and Limits

The transmitter antenna terminal of the EUT is connected to the input of a spectrum analyzer. Measurements are made while the EUT is operating at maximum power and at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

Test Procedure Used

ANSI C63.10:2020 – Section 11.9.1.1

Test Settings

1. RBW = 3MHz
2. VBW = 50MHz
3. Span $\geq 3 \times$ RBW
4. Sweep = auto couple
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-2. Test Instrument & Measurement Setup

Test Notes


None

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 35 of 113


Frequency [MHz]	Data Rate [Mbps]	Channel No.	Bluetooth Mode	Peak Conducted Power		Ant. Gain [dBi]	EIRP [dBm]	Limit [dBm]	Margin [dB]
				[dBm]	[mW]				
2402	125 kbps	37	LE	11.96	15.707	-2.88	9.08	36.02	-26.94
2440	125 kbps	17	LE	11.82	15.209	-2.88	8.94	36.02	-27.08
2480	125 kbps	39	LE	12.17	16.466	-2.88	9.29	36.02	-26.73
2402	500 kbps	37	LE	11.65	14.615	-2.88	8.77	36.02	-27.25
2440	500 kbps	17	LE	11.89	15.449	-2.88	9.01	36.02	-27.01
2480	500 kbps	39	LE	11.64	14.592	-2.88	8.76	36.02	-27.26
2402	1 Mbps	37	LE	16.58	45.478	-2.88	13.70	36.02	-22.32
2440	1 Mbps	17	LE	16.68	46.591	-2.88	13.80	36.02	-22.22
2480	1 Mbps	39	LE	16.87	48.641	-2.88	13.99	36.02	-22.03
2404	2 Mbps	0	LE	15.68	36.949	-2.88	12.80	36.02	-23.22
2440	2 Mbps	17	LE	16.61	45.772	-2.88	13.73	36.02	-22.29
2478	2 Mbps	36	LE	16.67	46.462	-2.88	13.79	36.02	-22.23

Table 7-6. Conducted Output Power Measurements (Bluetooth (LE)) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 36 of 113




Plot 7-31. Peak Power Plot (Bluetooth (LE), 125kbps – Ch. 37) – Ant 1




Plot 7-32. Peak Power Plot (Bluetooth (LE), 125kbps – Ch. 17) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 37 of 113




Plot 7-33. Peak Power Plot (Bluetooth (LE), 125kbps – Ch. 39) – Ant 1




Plot 7-34. Peak Power Plot (Bluetooth (LE), 500kbps – Ch. 37) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 38 of 113




Plot 7-35. Peak Power Plot (Bluetooth (LE), 500kbps – Ch. 17) – Ant 1




Plot 7-36. Peak Power Plot (Bluetooth (LE), 500kbps – Ch. 39) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 39 of 113




Plot 7-37. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 37) – Ant 1




Plot 7-38. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 17) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 40 of 113




Plot 7-39. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 39) – Ant 1




Plot 7-40. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 0) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 41 of 113



Plot 7-41. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 17) – Ant 1




Plot 7-42. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 36) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 42 of 113


Frequency [MHz]	Data Rate [Mbps]	Channel No.	Bluetooth Mode	Peak Conducted Power		Ant. Gain [dBi]	EIRP [dBm]	Limit [dBm]	Margin [dB]
				[dBm]	[mW]				
2402	1 Mbps	37	LE	16.42	43.863	-3.09	13.33	36.02	-22.69
2440	1 Mbps	17	LE	16.64	46.111	-3.09	13.55	36.02	-22.47
2480	1 Mbps	39	LE	15.19	32.999	-3.09	12.10	36.02	-23.93
2404	2 Mbps	0	LE	16.84	48.328	-3.09	13.75	36.02	-22.27
2440	2 Mbps	17	LE	16.69	46.644	-3.09	13.60	36.02	-22.42
2478	2 Mbps	36	LE	16.05	40.244	-3.09	12.96	36.02	-23.06

Table 7-7. Conducted Output Power Measurements (Bluetooth (LE)) – Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 43 of 113




Plot 7-43. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 37) – Ant 2




Plot 7-44. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 17) – Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 44 of 113




Plot 7-45. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 39) – Ant 2




Plot 7-46. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 0) – Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 45 of 113



Plot 7-47. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 17) – Ant 2




Plot 7-48. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 36) – Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 46 of 113


Frequency [MHz]	Data Rate [Mbps]	Channel No.	Bluetooth Mode	Peak Conducted Power - ANT 1		Peak Conducted Power - ANT 2		Peak Conducted Power - Dual		Ant. Gain [dBi]	EIRP [dBm]	Limit [dBm]	Margin [dB]
				[dBm]	[mW]	[dBm]	[mW]	[dBm]	[mW]				
2402	1 Mbps	37	LE	12.94	19.679	13.02	20.031	15.99	39.710	0.03	16.02	36.02	-20.00
2440	1 Mbps	17	LE	12.93	19.634	13.77	23.840	16.38	43.473	0.03	16.41	36.02	-19.61
2480	1 Mbps	39	LE	12.87	19.382	13.57	22.730	16.24	42.112	0.03	16.27	36.02	-19.75
2404	2 Mbps	0	LE	12.86	19.297	13.17	20.754	16.03	40.051	0.03	16.06	36.02	-19.96
2440	2 Mbps	17	LE	12.86	19.329	13.85	24.288	16.40	43.617	0.03	16.43	36.02	-19.59
2478	2 Mbps	36	LE	13.11	20.464	13.90	24.558	16.53	45.023	0.03	16.56	36.02	-19.46

Table 7-8. Conducted Output Power Measurements (Bluetooth (LE)) – Dual

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 47 of 113




Plot 7-49. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 37) – Dual Ant 1




Plot 7-50. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 17) – Dual Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 48 of 113




Plot 7-51. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 39) – Dual Ant 1




Plot 7-52. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 0) – Dual Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 49 of 113




Plot 7-53. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 17) – Dual Ant 1




Plot 7-54. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 36) – Dual Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 50 of 113




Plot 7-55. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 37) – Dual Ant 2




Plot 7-56. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 17) – Dual Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 51 of 113




Plot 7-57. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 39) – Dual Ant 2




Plot 7-58. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 0) – Dual Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 52 of 113



Plot 7-59. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 17) – Dual Ant 2



Plot 7-60. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 36) – Dual Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 53 of 113

7.4 Power Spectral Density – Bluetooth (LE)

Test Overview and Limit

The peak power density is measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies.

The maximum permissible power spectral density is 8 dBm in any 3 kHz band.

Test Procedure Used

ANSI C63.10:2020 – Section 11.10.2 Method PKPSD

Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3kHz
4. VBW = 1MHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-3. Test Instrument & Measurement Setup

Test Notes


None

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 54 of 113


Frequency [MHz]	Data Rate [Mbps]	Channel No.	Bluetooth Mode	Measured Power Spectral Density [dBm / 3kHz]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
2402	125 kbps	37	LE	5.55	8.0	-2.45
2440	125 kbps	17	LE	5.46	8.0	-2.54
2480	125 kbps	39	LE	5.71	8.0	-2.29
2402	500 kbps	37	LE	5.48	8.0	-2.52
2440	500 kbps	17	LE	5.44	8.0	-2.56
2480	500 kbps	39	LE	5.56	8.0	-2.44
2402	1 Mbps	37	LE	0.96	8.0	-7.04
2440	1 Mbps	17	LE	1.16	8.0	-6.84
2480	1 Mbps	39	LE	1.13	8.0	-6.87
2404	2 Mbps	0	LE	2.00	8.0	-6.00
2440	2 Mbps	17	LE	-0.76	8.0	-8.76
2478	2 Mbps	36	LE	-0.91	8.0	-8.91

Table 7-9. Conducted Power Density Measurements – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 55 of 113




Plot 7-61. Power Spectral Density Plot (Bluetooth (LE), 125kbps – Ch. 37) – Ant 1




Plot 7-62. Power Spectral Density Plot (Bluetooth (LE), 125kbps – Ch. 17) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 56 of 113




Plot 7-63. Power Spectral Density Plot (Bluetooth (LE), 125kbps – Ch. 39) – Ant 1




Plot 7-64. Power Spectral Density Plot (Bluetooth (LE), 500kbps – Ch. 37) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 57 of 113




Plot 7-65. Power Spectral Density Plot (Bluetooth (LE), 500kbps – Ch. 17) – Ant 1




Plot 7-66. Power Spectral Density Plot (Bluetooth (LE), 500kbps – Ch. 39) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 58 of 113




Plot 7-67. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 37) – Ant 1




Plot 7-68. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 17) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 59 of 113




Plot 7-69. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 39) – Ant 1




Plot 7-70. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 0) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 60 of 113



Plot 7-71. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 17) – Ant 1




Plot 7-72. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 36) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 61 of 113


Frequency [MHz]	Data Rate [Mbps]	Channel No.	Bluetooth Mode	Measured Power Spectral Density [dBm / 3kHz]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
2402	1 Mbps	37	LE	0.91	8.0	-7.09
2440	1 Mbps	17	LE	1.24	8.0	-6.76
2480	1 Mbps	39	LE	-0.36	8.0	-8.36
2404	2 Mbps	0	LE	-0.54	8.0	-8.54
2440	2 Mbps	17	LE	-0.64	8.0	-8.64
2478	2 Mbps	36	LE	-1.39	8.0	-9.39

Table 7-10. Conducted Power Density Measurements – Ant 2




Plot 7-73. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 37) – Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 62 of 113




Plot 7-74. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 17) – Ant 2




Plot 7-75. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 39) – Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 63 of 113



Plot 7-76. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 0) – Ant 2



Plot 7-77. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 17) – Ant 2


FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 64 of 113



© 2026 ELEMENT V11.3 5/14/2025
Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.


Frequency [MHz]	Data Rate [Mbps]	Channel No.	Bluetooth Mode	Measured Power Spectral Density [dBm / 3kHz]	Measured Power Spectral Density [dBm / 3kHz]	Measured Power Spectral Density [dBm / 3kHz]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
2402	1 Mbps	37	LE	-2.24	-2.25	0.77	8.0	-7.23
2440	1 Mbps	17	LE	-2.86	-2.12	0.54	8.0	-7.46
2480	1 Mbps	39	LE	-2.78	-1.94	0.67	8.0	-7.33
2404	2 Mbps	0	LE	-4.23	-3.91	-1.06	8.0	-9.06
2440	2 Mbps	17	LE	-4.76	-3.84	-1.27	8.0	-9.27
2478	2 Mbps	36	LE	-4.67	-3.66	-1.13	8.0	-9.13

Table 7-11. Conducted Power Density Measurements – DUAL




Plot 7-79. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 37) – Dual Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 66 of 113




Plot 7-80. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 17) – Dual Ant 1




Plot 7-81. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 39) – Dual Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 67 of 113




Plot 7-82. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 0) – Dual Ant 1




Plot 7-83. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 17) – Dual Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 68 of 113




Plot 7-84. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 36) – Dual Ant 1




Plot 7-85. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 37) – Dual Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 69 of 113




Plot 7-86. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 17) – Dual Ant 2




Plot 7-87. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 39) – Dual Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 70 of 113




Plot 7-88. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 0) – Dual Ant 2



Plot 7-89. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 17) – Dual Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 71 of 113



Plot 7-90. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 36) – Dual Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 72 of 113

7.5 Conducted Emissions at the Band Edge

Test Overview and Limit

For the following out of band conducted spurious emissions plots at the band edge, the EUT was set to transmit at maximum power with the largest packet size available. These settings produced the worst-case emissions.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth.

Test Procedure Used

ANSI C63.10:2020 – Section 11.11.3

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 300kHz
5. Detector = Peak
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-4. Test Instrument & Measurement Setup

Test Notes

None

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 73 of 113




Plot 7-91. Band Edge Plot (Bluetooth (LE), 125kbps – Ch. 37) – Ant 1



Plot 7-92. Band Edge Plot (Bluetooth (LE), 125kbps – Ch. 39) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 74 of 113




Plot 7-93. Band Edge Plot (Bluetooth (LE), 500kbps – Ch. 37) – Ant 1




Plot 7-94. Band Edge Plot (Bluetooth (LE), 500kbps – Ch. 39) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 75 of 113



Plot 7-95. Band Edge Plot (Bluetooth (LE), 1Mbps – Ch. 37) – Ant 1



Plot 7-96. Band Edge Plot (Bluetooth (LE), 1Mbps – Ch. 39) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 76 of 113




Plot 7-97. Band Edge Plot (Bluetooth (LE), 2Mbps – Ch. 0) – Ant 1



Plot 7-98. Band Edge Plot (Bluetooth (LE), 2Mbps – Ch. 36) – Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 77 of 113



Plot 7-99. Band Edge Plot (Bluetooth (LE), 1Mbps – Ch. 37) – Ant 2



Plot 7-100. Band Edge Plot (Bluetooth (LE), 1Mbps – Ch. 39) – Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 78 of 113




Plot 7-101. Band Edge Plot (Bluetooth (LE), 2Mbps – Ch. 0) – Ant 2



Plot 7-102. Band Edge Plot (Bluetooth (LE), 2Mbps – Ch. 36) – Ant 2

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 79 of 113



Plot 7-103. Band Edge Plot (Bluetooth (LE), 1Mbps – Ch. 37) – Dual Ant 1



Plot 7-104. Band Edge Plot (Bluetooth (LE), 1Mbps – Ch. 39) – Dual Ant 1

FCC ID: A3LSMS942B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2508270084-13-R1.A3L	Test Dates: 9/2/25 - 1/9/26	EUT Type: Portable Handset	Page 80 of 113