

APPENDIX F: POWER REDUCTION VERIFICATION

Per the May 2017 TCBC Workshop Notes, demonstration of proper functioning of the power reduction mechanisms is required to support the corresponding SAR configurations. The verification process included the evaluation of output power levels for individual or multiple triggering mechanisms.

F.1 Power Verification Procedure

The power verification was performed according to the following procedure:

1. A base station simulator was used to establish a conducted RF connection and the output power was monitored. The power measurements were confirmed to be within expected tolerances for all states before and after a power reduction mechanism was triggered.
2. Step 1 was repeated for all relevant modes and frequency bands for the mechanism being investigated.
3. Steps 1 and 2 were repeated for all individual power reduction mechanisms and combinations thereof. For the combination cases, one mechanism was switched to a 'triggered' state at a time; powers were confirmed to be within tolerances after each additional mechanism was activated.

FCC ID A3LSMS947B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX F: Page 1 of 3

F.2 Main Antenna Verification Summary

- Low band refers to: GSM850, UMTS B5, LTE B12/13/17/26/5, NR n12/26/5; Mid band refers to: GSM1900, UMTS B2/4, LTE B2/4/25/66, NR n66/25/2; High band refers to: LTE B41, NR n41; Ultra High band refers to: NR n77.
- This device uses different Radio State Indices (RSI) to configure different time averaged power levels based on certain exposure scenarios. For this device, RSI = 1 represents the case where the device is held-to-ear. RSI = 0 is configured when the device cannot detect the held-to-ear use conditions.

Table F-1
Power Measurement Verification for Main Antenna

Mode/Band	Radio State Index (RSI)	
	Free Space	Mechanism #1 (Head)
Low Band Ant A	0	1
Low Band Ant E	0	1
Mid Band Ant A	0	1
Mid Band Ant F	0	1
High Band Ant F	0	1
Ultra High Band Ant F	0	1

F.3 WIFI Verification Summary

- This device uses different Device State Indices (DSI) to configure different time averaged power levels based on certain exposure scenarios. For this device, DSI = 1 represents the case where the device is held-to-ear. DSI= 0 is configured when the device cannot detect the held-to-ear use conditions.

Table F-2
Power Measurement Verification WIFI

Mode/Band	Device State Index (DSI)	
	Un-triggered	Mechanism #1 (Head)
2.4 GHz WLAN Ant G	0	1
2.4 GHz WLAN Ant I	0	1

*Note: MIMO WIFI modes were not evaluated due to equipment limitations.

FCC ID A3LSMS947B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX F: Page 2 of 3

F.4 BT Verification Summary

Table F-3
Power Measurement Verification BT

Mode/Band	Conducted Power (dBm)		Target Power (dBm)	
	Un-triggered (Max)	Mechanism #1 RCV Active (Reduced)	Free Space	Mechanism #1 RCV Active (Reduced)
Bluetooth Ant G	15.76	13.62	15.5	14.0
Bluetooth LE Ant G	15.48	13.84	15.5	14.0
Bluetooth Ant I	17.35	15.49	17.5	15.0
Bluetooth LE Ant I	16.90	15.36	17.5	15.0