

NR Band n12 Antenna A

NR Band n12 Antenna A Measured Pmax for RSI = 0 (Body-worn, or Phablet), RSI = 1 (Head), RSI = 2 (Hotspot) - 10 MHz Bandwidth

NR Band n12 10 MHz Bandwidth						
			Channel			
Modulation	RB Size	RB Offset	141500 (707.5 MHz)		MPR Allowed per 3GPP [dB]	MPR [dB]
				Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.83		0	0.0
	1	26	23.77			0.0
	1	50	23.68			0.0
	25	0	22.80		0-1	1.0
	25	14	23.78		0	0.0
	25	27	22.78		0-1	1.0
	50	0	22.76			1.0
DFT-s-OFDM 16QAM	1	1	22.82		0-1	1.0
CP-OFDM QPSK	1	1	22.29		0-1.5	1.5

NR Band n12 Antenna A Measured Pmax for RSI = 0 (Body-worn, or Phablet), RSI = 1 (Head), RSI = 2 (Hotspot) - 5 MHz Bandwidth

NR Band n12 5 MHz Bandwidth						
			Channel			
Modulation	RB Size	RB Offset	140300 (701.5 MHz)		MPR Allowed per 3GPP [dB]	MPR [dB]
				Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.73		0	0.0
	1	13	23.71			0.0
	1	23	23.76			0.0
	12	0	22.78		0-1	1.0
	12	7	23.78		0	0.0
	12	13	22.79		0-1	1.0
	25	0	22.76			1.0
DFT-s-OFDM 16QAM	1	1	22.74		0-1	1.0
CP-OFDM QPSK	1	1	22.24		0-1.5	1.5

NR Band n12 Antenna E

NR Band n12 Antenna E Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 10 MHz Bandwidth

NR Band n12 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	141500 (707.5 MHz)				
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.85			0	0.0
	1	26	20.98				0.0
	1	50	20.86				0.0
	25	0	20.95			0-1	0.0
	25	14	21.00			0	0.0
	25	27	20.97			0-1	0.0
	50	0	20.99				0.0
DFT-s-OFDM 16QAM	1	1	20.92			0-1	0.0
CP-OFDM QPSK	1	1	20.84			0-1.5	0.0

NR Band n12 Antenna E Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 5 MHz Bandwidth

NR Band n12 5 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	140300 (701.5 MHz)	141500 (707.5 MHz)	142700 (713.5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	20.80	20.94	20.79		0	0.0
	1	13	20.73	20.91	20.69		0	0.0
	1	23	20.84	20.92	20.72		0-1	0.0
	12	0	20.83	20.99	20.80		0	0.0
	12	7	20.80	20.99	20.79		0	0.0
	12	13	20.81	20.98	20.78		0-1	0.0
	25	0	20.81	20.98	20.80			0.0
DFT-s-OFDM 16QAM	1	1	20.81	20.96	20.77		0-1	0.0
CP-OFDM QPSK	1	1	20.79	20.95	20.82		0-1.5	0.0

NR Band n12 Antenna E Measured Plimit for RSI = 1 (Head) - 10 MHz Bandwidth

NR Band n12 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	141500 (707.5 MHz)				
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.80			0	0.0
	1	26	18.79				0.0
	1	50	18.71				0.0
	25	0	18.85			0-1	0.0
	25	14	18.76			0	0.0
	25	27	18.75			0-1	0.0
	50	0	18.75				0.0
DFT-s-OFDM 16QAM	1	1	18.78			0-1	0.0
CP-OFDM QPSK	1	1	18.79			0-1.5	0.0

NR Band n12 Antenna E Measured Plimit for RSI = 1 (Head) - 5 MHz Bandwidth

NR Band n12 5 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	140300 (701.5 MHz)	141500 (707.5 MHz)	142700 (713.5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	18.46	18.46	18.43		0	0.0
	1	13	18.47	18.36	18.40			0.0
	1	23	18.45	18.43	18.49			0.0
	12	0	18.53	18.51	18.44		0-1	0.0
	12	7	18.55	18.45	18.48		0	0.0
	12	13	18.52	18.45	18.46		0-1	0.0
	25	0	18.56	18.45	18.47			0.0
DFT-s-OFDM 16QAM	1	1	18.46	18.44	18.39		0-1	0.0
CP-OFDM QPSK	1	1	18.47	18.47	18.40		0-1.5	0.0

NR Band n26 Antenna A

NR Band n26 Antenna A Measured Pmax for RSI = 0 (Body-worn, or Phablet), RSI = 1 (Head), RSI = 2 (Hotspot) - 15 MHz Bandwidth

NR Band n26 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	164300 (821.5 MHz)	168300 (841.5 MHz)			
Conducted Power [dBm]							
DFT-s-OFDM QPSK	1	1	23.54	23.74		0	0.0
	1	40	23.62	23.77			0.0
	1	77	23.63	23.78			0.0
	36	0	22.59	22.84		0-1	1.0
	36	22	23.71	23.86		0	0.0
	36	43	22.68	22.81		0-1	1.0
	75	0	22.61	22.84			1.0
DFT-s-OFDM 16QAM	1	1	22.55	22.73		0-1	1.0
CP-OFDM QPSK	1	1	22.04	22.35		0-1.5	1.5

NR Band n26 Antenna A Measured Pmax for RSI = 0 (Body-worn, or Phablet), RSI = 1 (Head), RSI = 2 (Hotspot) - 10 MHz Bandwidth

NR Band n26 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163800 (819 MHz)	166300 (831.5 MHz)	168800 (844 MHz)		
Conducted Power [dBm]							
DFT-s-OFDM QPSK	1	1	23.56	23.55	23.82	0	0.0
	1	26	23.61	23.64	23.81		0.0
	1	50	23.68	23.77	23.71		0.0
	25	0	22.56	22.56	22.78	0-1	1.0
	25	14	23.64	23.66	23.78	0	0.0
	25	27	22.66	22.74	22.77	0-1	1.0
	50	0	22.60	22.65	22.79		1.0
DFT-s-OFDM 16QAM	1	1	22.56	22.56	22.74	0-1	1.0
CP-OFDM QPSK	1	1	22.07	22.01	22.29	0-1.5	1.5

NR Band n26 Antenna A Measured Pmax for RSI = 0 (Body-worn, or Phablet), RSI = 1 (Head), RSI = 2 (Hotspot) - 5 MHz Bandwidth

NR Band n26 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163300 (816.5 MHz)	166300 (831.5 MHz)	169300 (846.5 MHz)		
Conducted Power [dBm]							
DFT-s-OFDM QPSK	1	1	23.57	23.56	23.86	0	0.0
	1	13	23.53	23.58	23.80		0.0
	1	23	23.63	23.73	23.88		0.0
	12	0	22.62	22.80	22.92	0-1	1.0
	12	7	23.62	23.67	23.89	0	0.0
	12	13	22.63	22.71	22.87	0-1	1.0
	25	0	22.60	22.66	22.91		1.0
DFT-s-OFDM 16QAM	1	1	22.59	22.54	22.79	0-1	1.0
CP-OFDM QPSK	1	1	22.11	22.05	22.36	0-1.5	1.5

NR Band n26 Antenna E

NR Band n26 Antenna E Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 15 MHz Bandwidth

NR Band n26 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	164300 (821.5 MHz)	168300 (841.5 MHz)			
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.45	19.48		0	0.0
	1	40	19.29	19.42			0.0
	1	77	19.18	19.43			0.0
	36	0	19.48	19.47		0-1	0.0
	36	22	19.41	19.43		0	0.0
	36	43	19.28	19.42		0-1	0.0
	75	0	19.39	19.44			
DFT-s-OFDM 16QAM	1	1	19.44	19.47		0-1	0.0
CP-OFDM QPSK	1	1	19.48	19.48		0-1.5	0.0

NR Band n26 Antenna E Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 10 MHz Bandwidth

NR Band n26 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163800 (819 MHz)	166300 (831.5 MHz)	168800 (844 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	19.44	19.43	19.10		0	0.0
	1	26	19.57	19.42	19.14			0.0
	1	50	19.51	19.26	19.10			0.0
	25	0	19.52	19.46	19.12		0-1	0.0
	25	14	19.54	19.42	19.10		0	0.0
	25	27	19.54	19.30	19.14		0-1	0.0
	50	0	19.54	19.41	19.11			0.0
DFT-s-OFDM 16QAM	1	1	19.45	19.50	19.12		0-1	0.0
CP-OFDM QPSK	1	1	19.47	19.46	19.15		0-1.5	0.0

NR Band n26 Antenna E Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 5 MHz Bandwidth

NR Band n26 5 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163300 (816.5 MHz)	166300 (831.5 MHz)	169300 (846.5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	19.45	19.42	19.20		0	0.0
	1	13	19.48	19.32	19.13		0.0	
	1	23	19.56	19.25	19.13		0.0	
	12	0	19.52	19.42	19.20		0-1	0.0
	12	7	19.51	19.41	19.21		0	0.0
	12	13	19.57	19.37	19.22		0-1	0.0
	25	0	19.57	19.39	19.22		0.0	
DFT-s-OFDM 16QAM	1	1	19.48	19.46	19.16		0-1	0.0
CP-OFDM QPSK	1	1	19.50	19.44	19.17		0-1.5	0.0

NR Band n26 Antenna E Measured Plimit for RSI = 1 (Head) - 15 MHz Bandwidth

NR Band n26 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	164300 (821.5 MHz)	166300 (841.5 MHz)			
Conducted Power [dBm]							
DFT-s-OFDM QPSK	1	1	19.71	19.40		0	0.0
	1	40	19.67	19.25			0.0
	1	77	19.63	19.33			0.0
	36	0	19.75	19.34		0-1	0.0
	36	22	19.72	19.21		0	0.0
	36	43	19.61	19.17		0-1	0.0
DFT-s-OFDM 16QAM	1	1	19.67	19.07		0-1	0.0
CP-OFDM QPSK	1	1	19.70	19.19		0-1.5	0.0

NR Band n26 Antenna E Measured Plimit for RSI = 1 (Head) - 10 MHz Bandwidth

NR Band n26 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163800 (819 MHz)	166300 (831.5 MHz)	168800 (844 MHz)		
Conducted Power [dBm]							
DFT-s-OFDM QPSK	1	1	19.70	19.74	19.60	0	0.0
	1	26	19.76	19.73	19.64		0.0
	1	50	19.77	19.63	19.63		0.0
	25	0	19.74	19.82	19.62	0-1	0.0
	25	14	19.78	19.74	19.64	0	0.0
	25	27	19.83	19.69	19.20	0-1	0.0
DFT-s-OFDM 16QAM	1	1	19.77	19.83	19.66	0-1	0.0
DFT-s-OFDM 16QAM	1	1	19.66	19.75	19.64	0-1	0.0
CP-OFDM QPSK	1	1	19.65	19.76	19.65	0-1.5	0.0

NR Band n26 Antenna E Measured Plimit for RSI = 1 (Head) - 5 MHz Bandwidth

NR Band n26 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163300 (816.5 MHz)	166300 (831.5 MHz)	169300 (846.5 MHz)		
Conducted Power [dBm]							
DFT-s-OFDM QPSK	1	1	19.68	19.76	19.65	0	0.0
	1	13	19.73	19.70	19.62		0.0
	1	23	19.80	19.67	19.67		0.0
	1	24	19.76	19.75	19.68	0-1	0.0
	12	0	19.78	19.72	19.65	0	0.0
	12	7	19.78	19.69	19.65	0	0.0
	12	13	19.80	19.71	19.66	0-1	0.0
	25	0	19.72	19.75	19.64	0-1	0.0
DFT-s-OFDM 16QAM	1	1	19.72	19.75	19.64	0-1	0.0
CP-OFDM QPSK	1	1	19.71	19.78	19.65	0-1.5	0.0

NR Band n66 Antenna A

NR Band n66 Antenna A Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth								
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]	
Modulation	RB Size	RB Offset	349000 (1745 MHz)					
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.85				0	0.0
	1	80	18.07					0.0
	1	158	18.09					0.0
	80	0	17.98				0-1	0.0
	80	40	17.99				0	0.0
	80	80	18.05				0-1	0.0
	160	0	17.99					0.0
DFT-s-OFDM 16QAM	1	1	17.81				0-1	0.0
CP-OFDM QPSK	1	1	17.88				0-1.5	0.0

NR Band n66 Antenna A Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth								
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]	
Modulation	RB Size	RB Offset	349000 (1745 MHz)					
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.84				0	0.0
	1	67	17.93					0.0
	1	131	18.10					0.0
	64	0	17.97				0-1	0.0
	64	35	18.03				0	0.0
	64	69	18.09				0-1	0.0
	128	0	18.04					0.0
DFT-s-OFDM 16QAM	1	1	17.85				0-1	0.0
CP-OFDM QPSK	1	1	17.89				0-1.5	0.0

NR Band n66 Antenna A Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth						
			Channel			MPR Allowed per 3GPP [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)	
Conducted Power [dBm]						MPR [dB]
DFT-s-OFDM QPSK	1	1	17.73	17.89	17.98	0.0
	1	53	17.83	18.00	17.84	0.0
	1	104	17.76	18.07	17.72	0.0
	50	0	17.77	17.99	17.97	0.0
	50	28	17.79	18.03	17.85	0.0
	50	56	17.77	18.09	17.77	0.0
DFT-s-OFDM 16QAM	1	1	17.73	17.89	17.97	0.0
	1	1	17.75	17.87	18.00	0.0
CP-OFDM QPSK	1	1	17.75	17.87	18.00	0.0

NR Band n66 Antenna A Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.81	17.93	17.87		0	0.0
	1	40	17.81	17.93	17.66		0	0.0
	1	77	17.83	18.06	17.68		0	0.0
	36	0	17.87	17.98	17.84		0-1	0.0
	36	22	17.88	18.00	17.77		0	0.0
	36	43	17.87	18.06	17.74		0-1	0.0
DFT-s-OFDM 16QAM	75	0	17.87	18.01	17.77		0-1	0.0
	1	1	17.79	17.90	17.88		0-1	0.0
CP-OFDM QPSK	1	1	17.79	17.93	17.92		0-1.5	0.0

NR Band n66 Antenna A Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)	Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.85	17.95	17.91		0	0.0
	1	26	17.96	18.06	17.84		0	0.0
	1	50	17.88	18.06	17.82		0	0.0
	25	0	17.89	17.99	17.81		0-1	0.0
	25	14	17.89	18.03	17.86		0	0.0
	25	27	17.90	18.05	17.86		0-1	0.0
DFT-s-OFDM 16QAM	50	0	17.88	18.03	17.86		0-1	0.0
	1	1	17.83	17.99	17.89		0-1	0.0
CP-OFDM QPSK	1	1	17.81	17.98	17.92		0-1.5	0.0

NR Band n66 Antenna A Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.64	17.97	17.80		0	0.0
	1	13	17.66	17.97	17.74		0	0.0
	1	23	17.70	17.97	17.77		0	0.0
	12	0	17.71	18.00	17.83		0-1	0.0
	12	7	17.72	18.00	17.82		0	0.0
	12	13	17.71	17.99	17.82		0-1	0.0
DFT-s-OFDM 16QAM	25	0	17.72	18.01	17.83		0-1	0.0
	1	1	17.66	17.95	17.80		0-1	0.0
CP-OFDM QPSK	1	1	17.70	17.99	17.83		0-1.5	0.0

NR Band n66 Antenna A Measured Plimit for RSI = 1 (Head) - 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	349000 (1745 MHz)					
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	23.28				0	0.0
	1	80	23.42					0.0
	1	158	23.39					0.0
	80	0	22.91				0-1	0.0
	80	40	23.38				0	0.0
	80	80	23.10				0-1	0.0
	160	0	23.05					0.0
DFT-s-OFDM 16QAM	1	1	22.95				0-1	0.0
CP-OFDM QPSK	1	1	22.35				0-1.5	0.5

NR Band n66 Antenna A Measured Plimit for RSI = 1 (Head) - 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	349000 (1745 MHz)			
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.25		0	0.0
	1	67	23.39			0.0
	1	131	23.44			0.0
	64	0	23.00		0-1	0.0
	64	35	23.43		0	0.0
	64	69	23.08		0-1	0.0
	128	0	23.05			0.0
DFT-s-OFDM 16QAM	1	1	23.02		0-1	0.0
CP-OFDM QPSK	1	1	22.40		0-1.5	0.5

NR Band n66 Antenna A Measured Plimit for RSI = 1 (Head) - 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	23.12	23.31	23.34		0	0.0
	1	53	23.13	23.39	23.18			0.0
	1	104	23.19	23.45	23.07			0.0
	50	0	22.76	22.97	22.84		0-1	0.0
	50	28	23.17	23.42	23.18		0	0.0
	50	56	22.76	23.10	22.72			0.0
	100	0	22.75	23.01	22.78		0-1	0.0
DFT-s-OFDM 16QAM	1	1	22.74	22.89	22.95		0-1	0.0
CP-OFDM QPSK	1	1	22.67	22.66	22.71		0-1.5	0.5

NR Band n66 Antenna A Measured Plimit for RSI = 1 (Head) - 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	23.16	23.28	23.16		0	0.0
	1	40	23.13	23.31	22.99			0.0
	1	77	23.15	23.47	23.01			0.0
	36	0	22.79	22.99	22.73		0-1	0.0
	36	22	23.20	23.44	23.08		0	0.0
	36	43	22.78	23.07	22.67		0-1	0.0
	75	0	22.79	23.01	22.67			0.0
DFT-s-OFDM 16QAM	1	1	22.79	22.91	22.79		0-1	0.0
CP-OFDM QPSK	1	1	22.56	22.64	22.70		0-1.5	0.5

NR Band n66 Antenna A Measured Plimit for RSI = 1 (Head) - 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	23.18	23.34	23.21		0	0.0
	1	26	23.28	23.40	23.17		0.0	
	1	50	23.18	23.44	23.12		0.0	
	25	0	22.83	22.99	22.79		0-1	0.0
	25	14	23.24	23.43	23.19		0	0.0
	25	27	22.82	23.04	22.77		0-1	0.0
	50	0	22.83	23.01	22.78			0.0
	DFT-s-OFDM 16QAM	1	1	22.91	22.76		22.80	0-1
CP-OFDM QPSK	1	1	22.67	22.77	22.76	0-1.5	0.5	

NR Band n66 Antenna A Measured Plimit for RSI = 1 (Head) - 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	23.06	23.37	23.11		0	0.0
	1	13	23.03	23.33	23.06			0.0
	1	23	23.08	23.40	23.08			0.0
	12	0	22.73	23.00	22.74		0-1	0.0
	12	7	23.15	23.42	23.14		0	0.0
	12	13	22.71	23.03	22.74			0.0
	25	0	22.71	23.00	22.73		0-1	0.0
DFT-s-OFDM 16QAM	1	1	22.69	22.95	22.68		0-1	0.0
CP-OFDM QPSK	1	1	22.69	22.76	22.79		0-1.5	0.5

NR Band n66 Antenna F

NR Band n66 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	349000 (1745 MHz)				
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.32			0	0.0
	1	80	19.57				0.0
	1	158	19.59				0.0
	80	0	19.50			0-1	0.0
	80	40	19.54			0	0.0
	80	80	19.73			0-1	0.0
	160	0	19.61				0.0
DFT-s-OFDM 16QAM	1	1	19.32			0-1	0.0
CP-OFDM QPSK	1	1	19.41			0-1.5	0.0

NR Band n66 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	349000 (1745 MHz)				
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.43			0	0.0
	1	67	19.59				0.0
	1	131	19.75				0.0
	64	0	19.54			0-1	0.0
	64	35	19.67			0	0.0
	64	69	19.76			0-1	0.0
	128	0	19.65				0.0
	DFT-s-OFDM 16QAM	1	1	19.45			0-1
CP-OFDM QPSK	1	1	19.47			0-1.5	0.0

NR Band n66 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth										
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]	
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)					
			Conducted Power [dBm]							
DFT-s-OFDM QPSK	1	1	19.42	19.50	19.59				0	0.0
	1	53	19.43	19.63	19.54					0.0
	1	104	19.44	19.68	19.45					0.0
	50	0	19.44	19.55	19.63				0-1	0.0
	50	28	19.42	19.64	19.63				0	0.0
	50	56	19.40	19.78	19.52				0	0.0
	100	0	19.43	19.66	19.60				0-1	0.0
DFT-s-OFDM 16QAM	1	1	19.48	19.49	19.64				0-1	0.0
CP-OFDM QPSK	1	1	19.46	19.50	19.60				0-1.5	0.0

NR Band n66 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	19.47	19.60	19.45		0	0.0
	1	40	19.29	19.59	19.40		0.0	
	1	77	19.43	19.75	19.41		0.0	
	36	0	19.50	19.60	19.56		0-1	0.0
	36	22	19.48	19.67	19.51		0	0.0
	36	43	19.42	19.72	19.46		0	0.0
	72	0	19.48	19.66	19.50		0-1	0.0
DFT-s-OFDM 16QAM	1	1	19.46	19.62	19.47		0-1	0.0
CP-OFDM QPSK	1	1	19.50	19.61	19.49		0-1.5	0.0

NR Band n66 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	19.50	19.61	19.55		0	0.0
	1	26	19.60	19.62	19.55			0.0
	1	50	19.41	19.65	19.51			0.0
	25	0	19.55	19.62	19.61		0-1	0.0
	25	14	19.51	19.65	19.57		0	0.0
	25	27	19.50	19.65	19.58		0-1	0.0
	50	0	19.50	19.65	19.58		0-1	0.0
DFT-s-OFDM 16QAM	1	1	19.50	19.61	19.55		0-1	0.0
CP-OFDM QPSK	1	1	19.48	19.64	19.56		0-1.5	0.0

NR Band n66 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	19.36	19.62	19.56		0	0.0
	1	13	19.45	19.57	19.43		0.0	
	1	23	19.38	19.57	19.46		0.0	
	12	0	19.42	19.62	19.55		0-1	0.0
	12	7	19.45	19.64	19.53		0	0.0
	12	13	19.38	19.62	19.56		0-1	0.0
	25	0	19.42	19.64	19.54		0-1	0.0
DFT-s-OFDM 16QAM	1	1	19.35	19.64	19.51		0-1	0.0
CP-OFDM QPSK	1	1	19.35	19.64	19.54		0-1.5	0.0

NR Band n66 Antenna F Measured Plimit for RSI = 1 (Head) - 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	349000 (1745 MHz)					
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	15.29				0	0.0
	1	80	15.66					0.0
	1	158	15.68					0.0
	80	0	15.52				0-1	0.0
	80	40	15.66				0	0.0
	80	80	15.72				0-1	0.0
	160	0	15.67				0-1	0.0
DFT-s-OFDM 16QAM	1	1	15.29				0-1	0.0
CP-OFDM QPSK	1	1	15.33				0-1.5	0.0

NR Band n66 Antenna F Measured Plimit for RSI = 1 (Head) - 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	349000 (1745 MHz)			
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	15.41		0	0.0
	1	67	15.61			0.0
	1	131	15.81			0.0
	64	0	15.56		0-1	0.0
	64	35	15.67		0	0.0
	64	69	15.74		0	0.0
	128	0	15.64		0-1	0.0
DFT-s-OFDM 16QAM	1	1	15.45		0-1	0.0
CP-OFDM QPSK	1	1	15.49		0-1.5	0.0

NR Band n66 Antenna F Measured Plimit for RSI = 1 (Head) - 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)	Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.45	15.46	15.64		0	0.0
	1	53	15.38	15.68	15.54			0.0
	1	104	15.43	15.77	15.47			0.0
	50	0	15.47	15.57	15.62		0-1	0.0
	50	28	15.44	15.66	15.56		0	0.0
	50	56	15.37	15.75	15.52		0-1	0.0
	100	0	15.44	15.65	15.56		0.0	
	DFT-s-OFDM 16QAM	1	1	15.42	15.46		15.66	
CP-OFDM QPSK	1	1	15.44	15.41	15.68		0-1.5	0.0

NR Band n66 Antenna F Measured Plimit for RSI = 1 (Head) - 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	15.42	15.58	15.48		0	0.0
	1	40	15.39	15.62	15.39		0.0	
	1	77	15.30	15.75	15.42		0.0	
	36	0	15.48	15.59	15.51		0-1	0.0
	36	22	15.48	15.68	15.49		0	0.0
	36	43	15.42	15.70	15.46		0-1	0.0
	75	0	15.45	15.65	15.50			
DFT-s-OFDM 16QAM	1	1	15.42	15.54	15.50		0-1	0.0
CP-OFDM QPSK	1	1	15.47	15.59	15.50		0-1.5	0.0

NR Band n66 Antenna F Measured Plimit for RSI = 1 (Head) - 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
			343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)	Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.50	15.65	15.45		0	0.0
	1	26	15.58	15.74	15.47		0.0	
	1	50	15.51	15.64	15.47		0.0	
	25	0	15.55	15.59	15.56		0-1	0.0
	25	14	15.53	15.63	15.57		0	0.0
	25	27	15.50	15.66	15.57		0-1	0.0
DFT-s-OFDM 16QAM	50	0	15.53	15.65	15.58		0-1	0.0
	1	1	15.49	15.65	15.48			
CP-OFDM QPSK	1	1	15.49	15.63	15.47		0-1.5	0.0

NR Band n66 Antenna F Measured Plimit for RSI = 1 (Head) - 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
			342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)	Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	15.32	15.69	15.45		0	0.0
	1	13	15.40	15.58	15.38			0.0
	1	23	15.35	15.57	15.45			0.0
	12	0	15.41	15.60	15.55		0-1	0.0
	12	7	15.42	15.61	15.53		0	0.0
	12	13	15.39	15.64	15.51		0-1	0.0
DFT-s-OFDM 16QAM	25	0	15.41	15.63	15.53		0-1	0.0
	1	1	15.34	15.70	15.47			0.0
CP-OFDM QPSK	1	1	15.39	15.70	15.49		0-1.5	0.0

NR Band n25 Antenna A

NR Band n25 Antenna A Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth								
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]	
Modulation	RB Size	RB Offset	376500 (1882.5 MHz)					
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.12				0	0.0
	1	80	17.13					0.0
	1	158	17.10					0.0
	80	0	17.08				0-1	0.0
	80	40	17.13				0	0.0
	80	80	17.14				0-1	0.0
	160	0	17.11				0	0.0
DFT-s-OFDM 16QAM	1	1	17.14				0-1	0.0
CP-OFDM QPSK	1	1	17.15				0-1.5	0.0

NR Band n25 Antenna A Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	376500 (1982.5 MHz)					
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.02				0	0.0
	1	67	17.01				0	0.0
	1	131	17.06				0	0.0
	64	0	17.04				0-1	0.0
	64	35	17.07				0	0.0
	64	69	17.12				0-1	0.0
	128	0	17.10				0	0.0
	DFT-s-OFDM 16QAM	1	1	17.05				0-1
CP-OFDM QPSK	1	1	17.07				0-1.5	0.0

NR Band n25 Antenna A Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.26	17.12	17.24		0	0.0
	1	53	17.23	17.16	17.37			0.0
	1	104	17.13	17.16	17.21			0.0
	50	0	17.27	17.11	17.29		0-1	0.0
	50	28	17.23	17.15	17.33		0	0.0
	50	56	17.21	17.17	17.26		0-1	0.0
DFT-s-OFDM 16QAM	100	0	17.25	17.15	17.33			0.0
	1	1	17.30	17.09	17.25		0-1	0.0
CP-OFDM QPSK	1	1	17.32	17.05	17.28		0-1,5	0.0

NR Band n25 Antenna A Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.34	17.07	17.19		0	0.0
	1	40	17.20	17.05	17.19		0-1	0.0
	1	77	17.20	17.15	17.13		0	0.0
	36	0	17.38	17.12	17.30		0	0.0
	36	22	17.32	17.14	17.28		0-1	0.0
	36	43	17.29	17.18	17.23		0	0.0
	75	0	17.33	17.14	17.30		0-1	0.0
DFT-s-OFDM 16QAM	1	1	17.39	17.06	17.22		0-1	0.0
CP-OFDM QPSK	1	1	17.36	17.07	17.23		0-1.5	0.0

NR Band n25 Antenna A Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.38	17.06	17.22		0	0.0
	1	26	17.45	17.11	17.27			0.0
	1	50	17.34	17.12	17.14			0.0
	25	0	17.42	17.10	17.28		0-1	0.0
	25	14	17.37	17.13	17.24		0	0.0
	25	27	17.34	17.15	17.20		0-1	0.0
	50	0	17.40	17.14	17.19			0.0
DFT-s-OFDM 16QAM	1	1	17.40	17.06	17.22		0-1	0.0
CP-OFDM QPSK	1	1	17.39	17.08	17.24		0-1.5	0.0

NR Band n25 Antenna A Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852,5 MHz)	376500 (1882,5 MHz)	382500 (1912,5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.21	17.08	17.15		0	0.0
	1	13	17.21	17.07	17.07		0.0	
	1	23	17.22	17.06	17.11		0.0	
	12	0	17.27	17.09	17.15		0-1	0.0
	12	7	17.26	17.10	17.14		0	0.0
	12	13	17.24	17.09	17.14		0-1	0.0
	25	0	17.28	17.11	17.13			
DFT-s-OFDM 16QAM	1	1	17.22	17.08	17.13		0-1	0.0
CP-OFDM QPSK	1	1	17.25	17.08	17.14		0-1.5	0.0

NR Band n25 Antenna A Measured Pmax for RSI = 1 (Head) - 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	376500 (1882.5 MHz)					
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	23.41				0	0.0
	1	80	23.34					0.0
	1	158	23.44					0.0
	80	0	22.77				0-1	1.0
	80	40	23.34				0	0.0
	80	80	22.85				0-1	1.0
	160	0	22.76					1.0
DFT-s-OFDM 16QAM	1	1	22.65				0-1	1.0
CP-OFDM QPSK	1	1	21.98				0-1.5	1.5

NR Band n25 Antenna A Measured Pmax for RSI = 1 (Head) - 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	376500 (1882.5 MHz)			
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.23		0	0.0
	1	67	23.36			0.0
	1	131	23.40			0.0
	64	0	22.78		0-1	1.0
	64	35	23.40		0	0.0
	64	69	22.77		0-1	1.0
	128	0	22.81			1.0
DFT-s-OFDM 16QAM	1	1	22.67		0-1	1.0
CP-OFDM QPSK	1	1	21.83		0-1.5	1.5

NR Band n25 Antenna A Measured Pmax for RSI = 1 (Head) - 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)	Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.55	23.45	23.34		0	0.0
	1	53	23.37	23.44	23.39			0.0
	1	104	23.41	23.53	23.41			0.0
	50	0	22.41	22.44	22.36		0-1	1.0
	50	28	23.45	23.51	23.36		0	0.0
	50	56	22.45	22.52	22.44		0-1	1.0
	100	0	22.42	22.52	22.43		1.0	
DFT-s-OFDM 16QAM	1	1	22.46	22.38	22.39		0-1	1.0
CP-OFDM QPSK	1	1	21.95	21.93	21.79		0-1.5	1.5

NR Band n25 Antenna A Measured Pmax for RSI = 1 (Head) - 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	23.55	23.43	23.63		0	0.0
	1	40	23.53	23.58	23.61		0.0	
	1	77	23.51	23.54	23.60		0.0	
	36	0	22.48	22.45	22.69		0-1	1.0
	36	22	23.56	23.52	23.62		0	0.0
	36	43	22.47	22.59	22.62		0-1	1.0
	75	0	22.49	22.49	22.60		1.0	
DFT-s-OFDM 16QAM	1	1	22.59	22.41	22.60		0-1	1.0
CP-OFDM QPSK	1	1	22.05	21.99	22.15		0-1.5	1.5

NR Band n25 Antenna A Measured Pmax for RSI = 1 (Head) - 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	23.59	23.48	23.67		0	0.0
	1	26	23.44	23.52	23.59			0.0
	1	50	23.53	23.57	23.63			0.0
	25	0	22.55	22.55	22.61		0-1	1.0
	25	14	23.57	23.58	23.60		0	0.0
	25	27	22.52	22.61	22.61		0-1	1.0
DFT-s-OFDM 16QAM	1	1	22.58	22.46	22.64		0-1	1.0
CP-OFDM QPSK	1	1	22.12	21.99	22.12		0-1.5	1.5

NR Band n25 Antenna A Measured Pmax for RSI = 1 (Head) - 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	23.62	23.51	23.61		0	0.0
	1	13	23.59	23.60	23.68		0.0	
	1	23	23.56	23.54	23.62		0.0	
	12	0	22.59	22.52	22.54		0-1	1.0
	12	7	23.61	23.58	23.65		0	0.0
	12	13	22.57	22.54	22.56		0-1	1.0
	25	0	22.56	22.53	22.56		0-1	1.0
DFT-s-OFDM 16QAM	1	1	22.59	22.46	22.57		0-1	1.0
CP-OFDM QPSK	1	1	22.14	22.04	22.02		0-1.5	1.5

NR Band n25 Antenna F

NR Band n25 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	376500 (1882.5 MHz)				
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.18			0	0.0
	1	80	19.14				0.0
	1	158	19.14				0.0
	80	0	19.22			0-1	0.0
	80	40	19.24			0	0.0
	80	80	19.28			0-1	0.0
	160	0	19.28			0	0.0
DFT-s-OFDM 16QAM	1	1	19.20			0-1	0.0
CP-OFDM QPSK	1	1	19.21			0-1.5	0.0

NR Band n25 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth								
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]	
Modulation	RB Size	RB Offset	376500 (1882.5 MHz)					
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	19.24				0	0.0
	1	67	19.09					0.0
	1	131	19.20					0.0
	64	0	19.24				0-1	0.0
	64	35	19.25				0	0.0
	64	69	19.26				0-1	0.0
	128	0	19.24					0.0
DFT-s-OFDM 16QAM	1	1	19.20				0-1	0.0
CP-OFDM QPSK	1	1	19.22				0-1.5	0.0

NR Band n25 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	19.38	19.17	19.23		0	0.0
	1	53	19.26	19.13	19.38			0.0
	1	104	19.19	19.26	19.48			0.0
	50	0	19.35	19.17	19.40		0-1	0.0
	50	28	19.30	19.22	19.54		0	0.0
	50	56	19.25	19.22	19.43		0-1	0.0
DFT-s-OFDM 16QAM	100	0	19.29	19.23	19.51			0.0
	1	1	19.40	19.15	19.25		0-1	0.0
CP-OFDM QPSK	1	1	19.40	19.21	19.24		0-1.5	0.0

NR Band n25 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)				
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	19.43	19.20	19.41			0	0.0
	1	40	19.25	19.15	19.37				0.0
	1	77	19.26	19.20	19.54				0.0
	36	0	19.42	19.25	19.39			0-1	0.0
	36	22	19.34	19.24	19.36			0	0.0
	36	43	19.34	19.20	19.45			0-1	0.0
	75	0	19.35	19.22	19.33				0.0
DFT-s-OFDM 16QAM	1	1	19.46	19.14	19.40			0-1	0.0
CP-OFDM QPSK	1	1	19.38	19.30	19.39			0-1.5	0.0

NR Band n25 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1862.5 MHz)	382000 (1910 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	19.47	19.28	19.37		0	0.0
	1	26	19.51	19.17	19.26			0.0
	1	50	19.35	19.24	19.56			0.0
	25	0	19.46	19.23	19.37		0-1	0.0
	25	14	19.42	19.25	19.31		0	0.0
	25	27	19.39	19.31	19.43		0-1	0.0
	50	0	19.45	19.28	19.35		0-1	0.0
DFT-s-OFDM 16QAM	1	1	19.45	19.26	19.45		0-1	0.0
CP-OFDM QPSK	1	1	19.43	19.31	19.38		0-1.5	0.0

NR Band n25 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852,5 MHz)	376500 (1862,5 MHz)	382500 (1912,5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	19.28	19.18	19.21		0	0.0
	1	13	19.58	19.10	19.25			0.0
	1	23	19.28	19.31	19.44			0.0
	12	0	19.33	19.23	19.27		0-1	0.0
	12	7	19.32	19.22	19.36		0	0.0
	12	13	19.32	19.28	19.46		0-1	0.0
	25	0	19.34	19.23	19.37		0-1	0.0
DFT-s-OFDM 16QAM	1	1	19.36	19.17	19.18		0-1	0.0
CP-OFDM QPSK	1	1	19.34	19.16	19.22		0-1.5	0.0

NR Band n25 Antenna F Measured Plimit for RSI = 1 (Head) - 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	376500 (1882.5 MHz)				
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.10			0	0.0
	1	80	17.12				0.0
	1	158	17.12				0.0
	80	0	17.19			0-1	0.0
	80	40	17.20			0	0.0
	80	80	17.22			0-1	0.0
	160	0	17.12			0-1	0.0
DFT-s-OFDM 16QAM	1	1	17.07			0-1	0.0
CP-OFDM QPSK	1	1	17.09			0-1.5	0.0

NR Band n25 Antenna F Measured Plimit for RSI = 1 (Head) - 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	376500 (1882.5 MHz)			
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.08		0	0.0
	1	67	17.07			0.0
	1	131	17.17			0.0
	64	0	17.21		0-1	0.0
	64	35	17.22		0	0.0
	64	69	17.24		0	0.0
	128	0	17.21		0-1	0.0
DFT-s-OFDM 16QAM	1	1	17.08		0-1	0.0
CP-OFDM QPSK	1	1	17.14		0-1.5	0.0

NR Band n25 Antenna F Measured Plimit for RSI = 1 (Head) - 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)	Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.35	17.17	17.22		0	0.0
	1	53	17.15	17.17	17.31			0.0
	1	104	17.19	17.23	17.42			0.0
	50	0	17.32	17.21	17.33		0-1	0.0
	50	28	17.21	17.24	17.39		0	0.0
	50	56	17.18	17.17	17.26		0-1	0.0
	100	0	17.26	17.21	17.36			
DFT-s-OFDM 16QAM	1	1	17.34	17.14	17.23		0-1	0.0
CP-OFDM QPSK	1	1	17.34	17.16	17.26		0-1.5	0.0

NR Band n25 Antenna F Measured Plimit for RSI = 1 (Head) - 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)	Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.36	17.16	17.33		0	0.0
	1	40	17.20	17.07	17.26		0.0	
	1	77	17.19	17.15	17.36		0.0	
	36	0	17.36	17.18	17.35		0-1	0.0
	36	22	17.27	17.20	17.28		0	0.0
	36	43	17.23	17.17	17.32		0-1	0.0
	75	0	17.28	17.18	17.36			
DFT-s-OFDM 16QAM	1	1	17.38	17.12	17.34		0-1	0.0
CP-OFDM QPSK	1	1	17.35	17.17	17.33		0-1.5	0.0

NR Band n25 Antenna F Measured Plimit for RSI = 1 (Head) - 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.36	17.21	17.29		0	0.0
	1	26	17.42	17.17	17.23			0.0
	1	50	17.27	17.16	17.43			0.0
	25	0	17.36	17.11	17.24		0-1	0.0
	25	14	17.34	17.15	17.26		0	0.0
	25	27	17.31	17.23	17.34		0-1	0.0
DFT-s-OFDM 16QAM	50	0	17.33	17.22	17.25		0-1	0.0
	1	1	17.35	17.12	17.36			0.0
CP-OFDM QPSK	1	1	17.38	17.15	17.29		0-1.5	0.0

NR Band n25 Antenna F Measured Plimit for RSI = 1 (Head) - 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.24	17.10	17.17		0	0.0
	1	13	17.22	17.08	17.24		0.0	
	1	23	17.18	17.25	17.42		0.0	
	12	0	17.27	17.12	17.24		0-1	0.0
	12	7	17.27	17.16	17.30		0	0.0
	12	13	17.23	17.18	17.36		0-1	0.0
	25	0	17.25	17.14	17.27		0.0	
DFT-s-OFDM 16QAM	1	1	17.19	17.12	17.12		0-1	0.0
CP-OFDM QPSK	1	1	17.28	17.11	17.13		0-1.5	0.0

NR Band n41 Antenna F Path 1

NR Band n41 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	508200 (2541 MHz)	528996 (2644.98 MHz)			
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.21	17.55		0	0.0
	1	123	17.17	17.34			0.0
	1	243	17.76	17.72			0.0
	120	0	17.29	17.56		0-1	0.0
	120	63	17.30	17.43		0	0.0
	120	125	17.45	17.51		0-1	0.0
	243	0	17.46	17.55		0.0	
DFT-s-OFDM 16QAM	1	1	17.33	17.56		0-1	0.0
CP-OFDM QPSK	1	1	17.31	17.63		0-1.5	0.0

NR Band n41 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)			
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.30	17.54		0	0.0
	1	95	17.23	17.39		0.0	
	1	109	17.23	17.39		0.0	
	1	215	17.62	17.76		0	
	108	0	17.29	17.54		0-1	
	108	55	17.30	17.45		0	
	108	109	17.37	17.54		0-1	
DFT-s-OFDM 16QAM	216	0	17.38	17.53		0	0.0
	1	1	17.29	17.58		0-1	0.0
CP-OFDM QPSK	1	1	17.32	17.55		0-1.5	0.0

NR Band n41 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)			
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.43	17.57		0	0.0
	1	95	17.24	17.44		0.0	
	1	187	17.46	17.62		0.0	
	90	0	17.32	17.50		0-1	0.0
	90	50	17.31	17.47		0	0.0
	90	99	17.42	17.55		0-1	0.0
	180	0	17.41	17.50		0.0	
DFT-s-OFDM 16QAM	1	1	17.44	17.64		0-1	0.0
CP-OFDM QPSK	1	1	17.49	17.65		0-1.5	0.0

NR Band n41 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.40	17.47	17.44		0	0.0
	1	81	17.22	17.65	17.41			0.0
	1	160	17.46	17.48	17.58			0.0
	81	0	17.34	17.56	17.43		0-1	0.0
	81	41	17.28	17.68	17.44		0	0.0
	81	81	17.35	17.60	17.54		0-1	0.0
	162	0	17.32	17.67	17.47		0	0.0
DFT-s-OFDM 16QAM	1	1	17.42	17.47	17.51		0-1	0.0
CP-OFDM QPSK	1	1	17.43	17.49	17.53		0-1.5	0.0

NR Band n41 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.39	17.49	17.48		0	0.0
	1	67	17.24	17.68	17.44			0.0
	1	131	17.38	17.52	17.58			0.0
	64	0	17.35	17.59	17.49		0-1	0.0
	64	35	17.31	17.70	17.47		0	0.0
	64	69	17.35	17.62	17.56		0-1	0.0
	128	0	17.36	17.69	17.48		0.0	
DFT-s-OFDM 16QAM	1	1	17.43	17.52	17.48		0-1	0.0
CP-OFDM QPSK	1	1	17.40	17.49	17.57		0-1.5	0.0

NR Band n41 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)			
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.33	17.30	17.65	17.45		0	0.0
	1	53	17.24	17.53	17.44	17.46		0	0.0
	1	104	17.30	17.55	17.35	17.53		0	0.0
	50	0	17.32	17.32	17.54	17.46		0-1	0.0
	50	28	17.26	17.34	17.43	17.50		0	0.0
	50	56	17.30	17.44	17.38	17.52		0-1	0.0
	100	0	17.31	17.34	17.46	17.49		0.0	
DFT-s-OFDM 16QAM	1	1	17.37	17.30	17.69	17.47		0-1	0.0
CP-OFDM QPSK	1	1	17.41	17.32	17.70	17.54		0-1.5	0.0

NR Band n41 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth										
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]	
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2592.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)			
			Conducted Power [dBm]							
DFT-s-OFDM QPSK	1	1	17.11	17.10	17.44	17.31	17.30	0	0.0	
	1	39	17.18	17.20	17.59	17.23	17.42		0.0	
	1	76	17.14	17.17	17.48	17.24	17.41		0.0	
	36	0	17.17	17.18	17.54	17.32	17.34		0-1	
	36	21	17.19	17.23	17.50	17.27	17.42		0.0	
	36	42	17.12	17.25	17.58	17.28	17.44		0.0	
	75	0	17.18	17.23	17.58	17.33	17.41		0-1	0.0
DFT-s-OFDM 16QAM	1	1	17.22	17.22	17.45	17.38	17.32	0-1	0.0	
CP-OFDM QPSK	1	1	17.28	17.27	17.21	17.41	17.36	0-1.5	0.0	

NR Band n41 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth										
			Channel						MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)			
			Conducted Power [dBm]							
DFT-s-OFDM QPSK	1	1	17.21	17.16	17.49	17.25	17.31		0	0.0
	1	26	17.13	17.18	17.56	17.18	17.34			0.0
	1	49	17.14	17.27	17.57	17.22	17.35			0.0
	25	0	17.19	17.20	17.54	17.25	17.37		0-1	0.0
	25	13	17.16	17.22	17.56	17.29	17.34		0	0.0
	25	26	17.19	17.24	17.57	17.28	17.38		0	0.0
	50	0	17.17	17.25	17.56	17.29	17.34	0-1	0.0	
DFT-s-OFDM 16QAM	1	1	17.26	17.17	17.51	17.30	17.31		0-1	0.0
CP-OFDM QPSK	1	1	17.24	17.16	17.58	17.25	17.33		0-1.5	0.0

NR Band n41 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.18	17.19	17.52	17.32	0	0.0	
	1	19	17.24	17.28	17.54	17.37		0.0	
	1	36	17.18	17.25	17.60	17.33		0.0	
	18	0	17.21	17.23	17.60	17.35		0-1	
	18	10	17.17	17.25	17.61	17.34		0.0	
	18	20	17.18	17.27	17.61	17.35		0-1	
DFT-s-OFDM 16QAM	1	1	17.25	17.26	17.53	17.34	17.50	0-1	0.0
CP-OFDM QPSK	1	1	17.27	17.25	17.60	17.35	17.61	0-1.5	0.0

NR Band n41 Antenna F Measured Plimit for RSI = 0 (Body-worn, or Phablet), RSI = 2 (Hotspot) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth										
			Channel						MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)			
			Conducted Power [dBm]							
DFT-s-OFDM QPSK	1	1	17.20	17.18	17.61	17.34	17.42		0	0.0
	1	12	17.21	17.24	17.66	17.35	17.48			0.0
	1	22	17.13	17.22	17.63	17.31	17.43			0.0
	12	0	17.21	17.23	17.62	17.37	17.49		0-1	0.0
	12	6	17.22	17.25	17.63	17.35	17.51		0	0.0
	12	12	17.15	17.27	17.64	17.36	17.50		0-1	0.0
	24	0	17.14	17.28	17.63	17.38	17.52		0.0	
DFT-s-OFDM 16QAM	1	1	17.14	17.18	17.61	17.41	17.44	0-1	0.0	
CP-OFDM QPSK	1	1	17.24	17.29	17.65	17.42	17.45	0-1.5	0.0	

NR Band n41 Antenna F Measured Plimit for RSI = 1 (Head) - 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth											
			Channel						MPR Allowed per 3GPP [dB]	MPR [dB]	
Modulation	RB Size	RB Offset	508200 (2541 MHz)	528996 (2644.98 MHz)							
			Conducted Power [dBm]								
DFT-s-OFDM QPSK	1	1	16.25	16.63						0	0.0
	1	123	16.26	16.39						0	0.0
	1	243	16.77	16.76						0-1	0.0
	120	0	16.33	16.53						0	0.0
	120	63	16.34	16.40						0	0.0
	120	125	16.41	16.49						0-1	0.0
DFT-s-OFDM 16QAM	243	0	16.43	16.52							0.0
DFT-s-OFDM 16QAM	1	1	16.36	16.57						0-1	0.0
CP-OFDM QPSK	1	1	16.29	16.60						0-1.5	0.0

NR Band n41 Antenna F Measured Plimit for RSI = 1 (Head) - 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth											
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]		
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)							
			Conducted Power [dBm]								
DFT-s-OFDM QPSK	1	1	16.24	16.54						0	0.0
	1	109	16.23	16.37						0	0.0
	1	215	16.58	16.64						0	0.0
	108	0	16.30	16.51						0-1	0.0
	108	55	16.33	16.43						0	0.0
	108	109	16.40	16.51						0	0.0
DFT-s-OFDM 16QAM	216	0	16.40	16.50						0-1	0.0
	1	1	16.29	16.57						0-1	0.0
CP-OFDM QPSK	1	1	16.37	16.56						0-1.5	0.0

NR Band n41 Antenna F Measured Plimit for RSI = 1 (Head) - 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth									
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]	
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)					
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	16.46	16.55				0	0.0
	1	95	16.26	16.39				0	0.0
	1	187	16.47	16.63				0	0.0
	90	0	16.34	16.48				0-1	0.0
	90	50	16.35	16.45				0	0.0
	90	99	16.41	16.53				0	0.0
DFT-s-OFDM 16QAM	180	0	16.40	16.50				0-1	0.0
	1	1	16.44	16.63				0-1	0.0
CP-OFDM QPSK	1	1	16.52	16.66				0-1.5	0.0

NR Band n41 Antenna F Measured Plimit for RSI = 1 (Head) - 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	16.37	16.44	16.48		0	0.0
	1	81	16.22	16.63	16.40			0.0
	1	160	16.42	16.46	16.59			0.0
	81	0	16.32	16.54	16.47		0-1	0.0
	81	41	16.27	16.65	16.45		0	0.0
	81	81	16.35	16.59	16.56		0	0.0
	162	0	16.32	16.64	16.50		0-1	0.0
DFT-s-OFDM 16QAM	1	1	16.41	16.45	16.58		0-1	0.0
CP-OFDM QPSK	1	1	16.39	16.47	16.56		0-1.5	0.0

NR Band n41 Antenna F Measured Plimit for RSI = 1 (Head) - 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)			
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	16.37	16.48	16.48		0	0.0
	1	67	16.23	16.67	16.40		0.0	
	1	131	16.39	16.56	16.57		0.0	
	64	0	16.34	16.59	16.48		0-1	0.0
	64	35	16.28	16.69	16.47		0	0.0
	64	69	16.33	16.61	16.54		0	0.0
	128	0	16.34	16.67	16.47		0-1	0.0
DFT-s-OFDM 16QAM	1	1	16.38	16.49	16.44		0-1	0.0
CP-OFDM QPSK	1	1	16.43	16.54	16.56		0-1.5	0.0

NR Band n41 Antenna F Measured Plimit for RSI = 1 (Head) - 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)	Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.38	16.37	16.63	16.45		0	0.0
	1	53	16.17	16.40	16.40	16.49			0.0
	1	104	16.27	16.63	16.37	16.61			0.0
	50	0	16.28	16.39	16.55	16.51		0-1	0.0
	50	28	16.23	16.36	16.44	16.56		0	0.0
	50	56	16.25	16.51	16.39	16.58		0-1	0.0
	100	0	16.21	16.37	16.47	16.56			0.0
DFT-s-OFDM 16QAM	1	1	16.37	16.36	16.66	16.54		0-1	0.0
CP-OFDM QPSK	1	1	16.40	16.49	16.75	16.56		0-1.5	0.0

NR Band n41 Antenna F Measured Plimit for RSI = 1 (Head) - 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth										
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]	
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)			
			Conducted Power [dBm]							
DFT-s-OFDM QPSK	1	1	16.19	16.16	16.44	16.32	16.29	0	0.0	
	1	39	16.21	16.25	16.56	16.25	16.36		0.0	
	1	76	16.11	16.26	16.45	16.22	16.41		0.0	
	36	0	16.18	16.22	16.52	16.33	16.31	0-1	0.0	
	36	21	16.19	16.24	16.58	16.28	16.39	0	0.0	
	36	42	16.18	16.27	16.57	16.30	16.40	0-1	0.0	
	75	0	16.20	16.25	16.58	16.31	16.37		0.0	
DFT-s-OFDM 16QAM	1	1	16.26	16.24	16.47	16.33	16.36	0-1	0.0	
CP-OFDM QPSK	1	1	16.24	16.22	16.52	16.36	16.32	0-1.5	0.0	

NR Band n41 Antenna F Measured Plimit for RSI = 1 (Head) - 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	16.13	16.12	16.53	16.31	16.37	0	0.0
	1	26	16.12	16.18	16.62	16.26	16.39		0.0
	1	49	16.11	16.27	16.61	16.24	16.45		0.0
	25	0	16.18	16.21	16.62	16.29	16.44	0-1	0.0
	25	13	16.13	16.23	16.58	16.27	16.43	0	0.0
	25	26	16.15	16.26	16.60	16.30	16.46	0-1	0.0
	50	0	16.15	16.27	16.62	16.27	16.42		0.0
DFT-s-OFDM 16QAM	1	1	16.21	16.16	16.50	16.35	16.36	0-1	0.0
CP-OFDM QPSK	1	1	16.26	16.19	16.56	16.35	16.41	0-1.5	0.0

NR Band n41 Antenna F Measured Plimit for RSI = 1 (Head) - 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth										
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]	
Modulation	RB Size	RB Offset	500700 (2503.5 MHz)	509652 (2546.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)			
			Conducted Power [dBm]							
DFT-s-OFDM QPSK	1	1	16.22	16.23	16.52	16.36	16.46	0	0.0	
	1	19	16.21	16.24	16.62	16.39	16.48		0.0	
	1	36	16.20	16.23	16.61	16.31	16.44		0.0	
	18	0	16.26	16.24	16.61	16.34	16.48	0-1	0.0	
	18	10	16.24	16.28	16.64	16.35	16.47	0	0.0	
	18	20	16.24	16.27	16.64	16.34	16.49	0-1	0.0	
	36	0	16.22	16.25	16.63	16.35	16.47		0.0	
DFT-s-OFDM 16QAM	1	1	16.30	16.28	16.58	16.40	16.51	0-1	0.0	
CP-OFDM QPSK	1	1	16.32	16.29	16.64	16.43	16.48	0-1.5	0.0	

NR Band n41 Antenna F Measured Plimit for RSI = 1 (Head) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501,01 MHz)	509400 (2547 MHz)	518598 (2592,99 MHz)	527802 (2639,01 MHz)	537000 (2685 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	16.20	16.26	16.60	16.37	16.46	0	0.0
	1	12	16.24	16.36	16.66	16.38	16.47		0.0
	1	22	16.12	16.31	16.64	16.33	16.48		0.0
	12	0	16.20	16.30	16.65	16.39	16.50	0-1	0.0
	12	6	16.22	16.31	16.65	16.38	16.53	0	0.0
	12	12	16.17	16.31	16.66	16.40	16.51	0-1	0.0
	24	0	16.19	16.31	16.67	16.33	16.51		0.0
DFT-s-OFDM 16QAM	1	1	16.23	16.31	16.67	16.40	16.48	0-1	0.0
CP-OFDM QPSK	1	1	16.31	16.33	16.69	16.45	16.53	0-1.5	0.0