

CERTIFICATION TEST REPORT

Report Number. : S-4791953314-E11V2

Applicant : SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA

Model : SC-52G, SCG38

FCC ID : A3LSMS947JPN

EUT Description : GSM/WCDMA/LTE/5G NR Phone + BT/BLE,
DTS/UNII a/b/g/n/ac/ax/be, NFC, WPT and UWB

Test Standard(s) : FCC 47 CFR PART 15 SUBPART C

Date Of Issue:
2026-01-09

Prepared by:
UL KOREA LTD.
26th floor, 152, Teheran-ro, Gangnam-gu Seoul, 06236, Korea

Suwon Test Site: UL KOREA LTD. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433

Revision History

Rev.	Issue Date	Revisions	Presented By
V1	2025-12-23	Initial issue	Jaejin Lee
V2	2026-01-09	Updated to address TCB's question	Jaejin Lee

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. DECISION RULES AND MEASUREMENT UNCERTAINTY	7
4.1. METROLOGICAL TRACEABILITY	7
4.2. SAMPLE CALCULATION	7
4.3. MEASUREMENT UNCERTAINTY	7
4.4. DECISION RULES	7
5. EQUIPMENT UNDER TEST	8
5.1. EUT DESCRIPTION	8
5.2. MAXIMUM OUTPUT POWER	8
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	9
5.4. WORST-CASE CONFIGURATION AND MODE	9
5.5. DESCRIPTION OF TEST SETUP	10
6. TEST AND MEASUREMENT EQUIPMENT	13
7. TEST RESULTS SUMMARY	14
8. MEASUREMENT METHODS	15
9. ANTENNA PORT TEST RESULTS	16
9.1. ON TIME AND DUTY CYCLE	16
9.2. 20 dB BANDWIDTH	17
9.2.1. CS_TONE_ASK MODULATION	17
9.3. HOPPING FREQUENCY SEPARATION	19
9.3.1. CS_TONE_ASK MODULATION	19
9.4. NUMBER OF HOPPING CHANNELS	20
9.4.1. CS_TONE_ASK MODULATION	20
9.5. AVERAGE TIME OF OCCUPANCY	21
9.5.1. CS_TONE_ASK MODULATION	22
9.6. OUTPUT POWER	23
9.6.1. CS_TONE_ASK MODULATION	23
9.6.2. OUTPUT POWER PLOTS	24
9.7. AVERAGE POWER	25
9.7.1. CS_TONE_ASK MODULATION	25

9.8.	CONDUCTED SPURIOUS EMISSIONS.....	26
9.8.1.	CS_TONE_ASK MODULATION	27
10.	RADIATED TEST RESULTS.....	31
10.1.	TRANSMITTER ABOVE 1 GHz.....	33
10.1.1.	CS_TONE_ASK MODULATION.....	33
10.2.	WORST CASE BELOW 1 GHz.....	37
11.	AC POWER LINE CONDUCTED EMISSIONS	38
11.1.	AC Power Line	39

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.

EUT DESCRIPTION: GSM/WCDMA/LTE/5G NR Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax/be, NFC, WPT and UWB

MODEL: SC-52G, SCG38

SERIAL NUMBER: R3CY90EPCDF, R3CY90EPDPN (CONDUCTED);
R3CY90EPFAN, R3CY90EPGSX (RADIATED);

DATE TESTED: 2025-11-26 ~ 2025-12-22

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
47 CFR Part 15 Subpart C	Complies

UL KOREA LTD. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL KOREA LTD. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.


Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL KOREA LTD. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL KOREA LTD. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL KOREA LTD. By:



Seokhwan Hong
Suwon Lab Engineer
UL KOREA LTD.

Tested By:



Jaejin Lee
Suwon Lab Engineer
UL KOREA LTD.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with following methods.

1. FCC 47 CFR Part 2.
2. FCC 47 CFR Part 15.
3. KDB 558074 D01 15.247 Meas Guidance v05r02.
4. KDB 662911 D01 v02r01
5. ANSI C63.10-2020.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
☒	Chamber 1(3m semi-anechoic chamber)
☒	Chamber 2(3m semi-anechoic chamber)
☒	Chamber 3(3m semi-anechoic chamber)
☐	Chamber 4(3m Full-anechoic chamber)
☐	Chamber 5(3m Full-anechoic chamber)

UL KOREA LTD. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <https://www.iasonline.org/wp-content/uploads/2017/05/TL-637-cert-New.pdf>.

4. DECISION RULES AND MEASUREMENT UNCERTAINTY

4.1. METROLOGICAL TRACEABILITY

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamplifier Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

$$\begin{aligned} \text{AC Corrected Reading (dBuV)} &= \text{Measured Voltage (dBuV)} + \text{Extension Cord} \\ &\text{Loss (dB)} + \text{Cable Loss (dB)} \\ 44.72 \text{ dBuV} &= 34.72 \text{ dBuV} + 9.9 \text{ dB} + 0.1 \text{ dB} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
RF Output Power	0.69 dB
Time	0.60 %
Occupied Bandwidth	0.04 %
Hopping Frequency Separation	2.9×10^3 Hz
Frequency Range	2.5×10^3 Hz
Conducted Spurious Emissions	1.40 dB
Conducted Disturbance, 0.15 to 30 MHz	1.84 dB
Radiated Disturbance, 9 kHz to 30 MHz	2.41 dB
Radiated Disturbance, 30 MHz to 1 GHz	3.69 dB
Radiated Disturbance, 1 GHz to 18 GHz	5.18 dB
Radiated Disturbance, 18 GHz to 40 GHz	5.07 dB

Uncertainty figures are valid to a confidence level of 95%.

4.4. DECISION RULES

Decision rule for statement(s) of conformity is based on Clause 4.4.3 in IEC Guide 115:2023.

5. EQUIPMENT UNDER TEST

5.1. EUT DESCRIPTION

The EUT is a GSM/WCDMA/LTE/5G NR Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax/be, NFC, WPT and UWB. This test report addresses the FHSS (BLE) operational mode.

Representative model	Comparison Criteria	Derivative model
		SCG38
SC-52G	Hardware	Identical
	Software	UI modified according to Service Provider specifications

The SC-52G model was used as the representative model for final testing. All test results in this report apply to both the representative model and its derivative variants.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range [MHz]	Mode	Power Mode	Output Power [dBm]	Output Power [mW]
2 404 ~ 2 478	CS_TONE_ASK	Peak	9.06	8.05
		Average	8.49	7.06

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

**The internal antenna was Permanently attached.
Therefore this E.U.T Complies with the requirement of §15.203.**

The radio utilizes a internal antenna, with a maximum gain of:

Frequency Band[MHz]	ANT1 Gain [dBi]	ANT2 Gain [dBi]
DSS 2400 – 2483.5	-4.06	-5.91

“SUB4” and “SUB6” as indicated in antenna specification are written as ANT1 and ANT2 in this report.

5.4. WORST-CASE CONFIGURATION AND MODE

Both Bluetooth LE ASK Diversity mode have been investigated and confirmed.

The fundamentals of the EUT were investigated in three orthogonal orientations X, Y and Z. It was determined that below table's orientation was the worst-case orientation.

Worst-case		ANT1	ANT2
Axis	Band-Edge	X	Z
	Spurious	Y	Y

For conducted power test, Diversity mode was tested and reported.

Radiated and power line conducted tests were performed with EUT connected to AC power adapter as the worst-case configuration. Radiated harmonics spurious 1~18 GHz Low/Mid/High channels, 18-26GHz were performed with the EUT set at the Diversity mode. Radiated emission below 1GHz and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

For Radiated band-edge and spurious test, tests were performed on Diversity mode. All radiated and power line conducted tests were performed attached with travel adapter for the worst-case condition mode.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-T2510	N/A	N/A
Data Cable	SAMSUNG	EP-DN980	N/A	N/A


I/O CABLE

I/O Cable List						
Cable No.	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	C Type	Shielded	1.0 m	N/A


TEST SETUP

The EUT is a stand-alone unit during the tests.
Test software in hidden menu exercised the EUT to enable BLE Channel Sounding mode.


SETUP DIAGRAM FOR TESTS (CONDUCTED TEST SETUP)



SETUP DIAGRAM FOR TESTS (RADIATED TEST SETUP)



SETUP DIAGRAM FOR TESTS (RADIATED TEST SETUP) Below 1GHz



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB 9163	750	2026-07-30
Antenna, Horn, 18 GHz	ETS	3117	00168717	2026-07-17
Antenna, Horn, 40 GHz	ETS	3116C	00166155	2026-07-23
Preamplifier	ETS	3116C-PA	00168841	2026-07-28
Preamplifier, 1000 MHz	Sonoma	310N	341282	2026-07-21
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	2029169	2026-07-21
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	2026-07-21
Spectrum Analyzer, 44 GHz	KEYSIGHT	N9030B	MY60070693	2026-01-02
RF Switching Unit	TA Engineering	TA-018S-16	SW-1	N/A
Average Power Sensor	Agilent / HP	U2000A	MY54270007	2026-07-22
Average Power Sensor	Agilent / HP	U2000A	MY54260010	2026-07-22
Attenuator	PASTERNAK	PE7087-10	A001	2026-07-22
Attenuator	PASTERNAK	PE7087-10	A008	2026-07-22
EMI Test Receive, 40 GHz	R&S	ESU40	100439	2026-07-21
EMI Test Receive, 40 GHz	R&S	ESU40	100457	2026-07-21
EMI Test Receive	R&S	ESW 8	101227	2026-07-17
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	009	2026-07-21
High Pass Filter 3GHz	Micro-Tronics	HPM17543	010	2026-07-21
High Pass Filter 6GHz	Micro-Tronics	HPS17542	21	2026-07-21
LISN	R&S	ENV216	101837	2026-07-22
Antenna, Loop, 9kHz-30MHz	R&S	HFH2-Z2E	100900	2027-07-24
UL Software				
Description	Manufacturer	Model	Version	
Radiated software	UL	UL EMC	Ver 9.5	
AC Line Conducted software	UL	UL EMC	Ver 9.5	

7. TEST RESULTS SUMMARY

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result
2.1051, 15.247(d)	Band Edge / Conducted Spurious Emission	-20 dBc	Conducted	Complies
15.247 (b)(1)	TX conducted output power	< 21 dBm		Complies
15.247 (a)(1)	Hopping frequency separation	> two-thirds of the 20 dB bandwidth		Complies
15.247 (a)(1)(iii)	Number of Hopping channels	More than 15 non-overlapping channels		Complies
15.247 (a)(1)(iii)	Avg Time of Occupancy	< 0.4 s		Complies
15.207(a)	AC Power Line conducted emissions	Section 11	Power Line conducted	Complies
15.205, 15.209	Radiated Spurious Emission	< 54dBuV/m(Av)	Radiated	Complies

8. MEASUREMENT METHODS

20dB BW : ANSI C63.10, Section 6.9.2

99% BW: ANSI C63.10, Section 6.9.3

HOPPING FREQUENCY SEPARATION: ANSI C63.10, Section 7.8.2

NUMBER OF HOPPING CHANNELS: ANSI C63.10, Section 7.8.3

AVERAGE TIME OF OCCUPANCY: ANSI C63.10, Section 7.8.4

OUTPUT POWER: ANSI C63.10, Section 7.8.5.

Out-of-band EMISSIONS (Conducted) : ANSI C63.10, Section 7.8.7

Out-of-band EMISSIONS IN NON-RESTRICTED BANDS: ANSI C63.10, Section 7.8.8

Out-of-band EMISSIONS IN RESTRICTED BANDS: ANSI C63.10, Section 7.8.8

AC Power Line Conducted Emission: ANSI C63.10-2020, Section 6.2.

9. ANTENNA PORT TEST RESULTS

9.1. ON TIME AND DUTY CYCLE


LIMITS

None; for reporting purposes only.

PROCEDURE

ANSI C63.10, Section 11.6 : Zero-Span Spectrum Analyzer Method.

ON TIME AND DUTY CYCLE RESULTS



Mode	On time [usec]	Period [usec]	Duty Cycle [%]	1/T Minimum VBW [kHz]
2 400 ~ 2 483.5 MHz Band				
CS_TONE_ASK	14	625	2.24	71.43

Note. Radiated band-edge and spurious emissions were measured with the duty cycle reduction factor (per customer declaration) applied in accordance with FCC Part 15.35(c).

9.2. 20 dB BANDWIDTH

LIMITS

None; for reporting purposes only.


TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement. The sweep time is coupled.

RESULTS

9.2.1. CS_TONE_ASK MODULATION

Antenna	Channel	Frequency [MHz]	20 dB Bandwidth [kHz]
ANT1	2	2 404	316.2
	38	2 440	314.8
	76	2 478	316.5
ANT2	2	2 404	315.3
	38	2 440	315.2
	76	2 478	315.4
Worst			314.8



9.3. HOPPING FREQUENCY SEPARATION

LIMITS

FCC §15.247 (a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel. The VBW is set to VBW $\geq$ RBW. The sweep time is coupled.

RESULTS

9.3.1. CS_TONE_ASK MODULATION



9.4. NUMBER OF HOPPING CHANNELS

LIMITS

FCC §15.247 (a) (1) (iii)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.


TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller. The analyzer is set to Max Hold.

RESULTS

Normal Mode: 72 channels are observed

9.4.1. CS_TONE_ASK MODULATION



9.5. AVERAGE TIME OF OCCUPANCY

LIMITS

FCC §15.247 (a) (1) (iii)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan.


The number of pulses is calculated based on the customer's declared operational cycle, in which CS_TONE_ASK operates twice per 205 ms period on a single channel.

The observation occupancy time is hopping channel $72 \times 400 \text{ ms} = 28.8 \text{ sec}$.
Since CS_TONE_ASK operates twice per 205 ms on a single channel, there are 281 occurrences (calculated as 280.98) within the 28.8-second period

RESULTS

9.5.1. CS_TONE_ASK MODULATION

Modulation	Pulse Width [msec]	Number of Pulses in 28.8 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
ASK	0.014	281	0.039	0.400	-0.361



9.6. OUTPUT POWER

LIMITS

§15.247 (b) (1)

The peak conducted output power limit is 0.125 W (21 dBm).

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.


RESULTS

9.6.1. CS_TONE_ASK MODULATION

Antenna	Channel	Frequency [MHz]	Peak Output Power [dBm]	Limit [dBm]	Margin [dB]
ANT1	2	2 404	8.80	21.00	-12.20
	38	2 440	9.03		-11.97
	76	2 478	9.06		-11.94
ANT2	2	2 404	8.08		-12.92
	38	2 440	7.88		-13.12
	76	2 478	9.37		-11.63
Worst			9.37		-11.63

9.6.2. OUTPUT POWER PLOTS

PEAK OUTPUT POWER



9.7. AVERAGE POWER

LIMITS

None; for reporting purposes only

TEST PROCEDURE

Measurements perform using a wideband gated RF power meter.
The cable assembly insertion loss was entered as an offset in the power meter to allow for direct reading of power.

RESULTS

9.7.1. CS_TONE_ASK MODULATION

Antenna	Channel	Frequency [MHz]	Average Output Power [dBm]	Average Output Power [mW]
ANT1	2	2 404	8.232	6.656
	38	2 440	8.488	7.059
	76	2 478	8.468	7.028
ANT2	2	2 404	7.637	5.804
	38	2 440	7.676	5.856
	76	2 478	9.067	8.067

9.8. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

Limit = -20 dBc

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

The band-edges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal hopping mode.


RESULTS

9.8.1. CS_TONE_ASK MODULATION


SPURIOUS EMISSIONS, NON-HOPPING – ANT1




SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON – ANT1



SPURIOUS EMISSIONS, NON-HOPPING – ANT2



SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON – ANT2



10. RADIATED TEST RESULTS

LIMITS

FCC §15.205 and §15.209

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (μV/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

FCC Part 15.205 (a) : Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.41425 ~ 8.41475	108 ~ 121.94	1300 ~ 1427	4.5 ~ 5.15	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1435 ~ 1626.5	5.35 ~ 5.46	15.35 ~ 16.2
2.1735 ~ 2.1905	12.51975 ~ 12.52025	149.9 ~ 150.05	1645.5 ~ 1646.5	7.25 ~ 7.75	17.7 ~ 21.4
4.125 ~ 4.128	12.57675 ~ 12.57725	156.52475 ~	1660 ~ 1710	8.025 ~ 8.5	22.01 ~ 23.12
4.17725 ~ 4.17775	13.36 ~ 13.41	156.52525	1718.8 ~ 1722.2	9.0 ~ 9.2	23.6 ~ 24.0
4.20725 ~ 4.20775	16.42 ~ 16.423	156.7 ~ 156.9	2200 ~ 2300	9.3 ~ 9.5	31.2 ~ 31.8
6.215 ~ 6.218	16.69475 ~ 16.69525	162.0125 ~	2310 ~ 2390	10.6 ~ 12.7	36.43 ~ 36.5
6.26775 ~ 6.26825	16.80425 ~ 16.80475	167.17	2483.5 ~ 2500	13.25 ~ 13.4	Above 38.6
6.31175 ~ 6.31225	25.5 ~ 25.67	167.72 ~ 173.2	2655 ~ 2900		
8.291 ~ 8.294	37.5 ~ 38.25	240 ~ 285	3260 ~ 3267		
8.362 ~ 8.366	73 ~ 74.6	322 ~ 335.4	3332 ~ 3339		
8.37625 ~ 8.38675	74.8 ~ 75.2	399.90 ~ 410	3345.8 ~ 3358		
		608 ~ 614	3600 ~ 4400		
		960 ~ 1240			

▪ FCC Part 15.205(b) : The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane for below 1GHz and 150 cm for above 1GHz. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz for peak measurements. (Pre-scans to detect harmonic and spurious emissions, the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 30 kHz for peak measurements.)

For band edge and spurious measurements above 1 GHz, the resolution bandwidth is set to 1 MHz, and the video bandwidth is set to 3 MHz for peak measurements. Radiated spurious emissions were measured with the duty cycle reduction factor (per customer declaration) applied in accordance with FCC Part 15.35(c).

Since CS_TONE_ASK operates twice per 205 ms on a single channel, this corresponds to approximately one occurrence (0.9756), 14us, per 100 ms. Because the reduction factor is greater than the 20 dB difference between the peak and average limits, average measurements were omitted.

The spectrum from 1GHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.
(From 30MHz to 1GHz, test was performed with the EUT set to transmit at the channel with highest output power)

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.


Note : Emission was pre-scanned from 9kHz to 30MHz; No emissions were detected which was at least 20dB below the specification limit (consider distance correction factor).
Per FCC part 15.31(o), test results were not reported.

Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open are test site.
Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the one of tests made in an open field based on KDB 414788.

10.1. TRANSMITTER ABOVE 1 GHz

10.1.1. CS_TONE_ASK MODULATION

BANDEDGE (WORST CASE: 76 CHANNEL, ANT1)



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	Antenna Factor (dB/m)	10dB Path Loss(dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.4835	53.39	Pk	32.4	-24.9	60.89	-	-	74	-13.11	129	100	H
2	* 2.48359	53.69	Pk	32.4	-24.9	61.19	-	-	74	-12.81	129	100	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
Pk - Peak detector

BANDEDGE TEST DATA


Freq. [MHz]	Antenna	Frequency [GHz]	Reading [dBuV]	Detector Mode	ANT Factor [dB/m]	Loss [dB]	DC Corr [dB]	Result [dBuV/m]	AV Limit [dBuV/m]	AV Margin [dB]	PK Limit [dBuV/m]	PK Margin [dB]	Azimuth [Degs]	Height [cm]	Polarit
2404	ANT1	* 2.39	42.51	Pk	32.10	-24.90	0.00	49.71	-	-	74.00	-24.29	124	164	H
		* 2.38958	45.13	Pk	32.10	-24.90	0.00	52.33	-	-	74.00	-21.67	124	164	H
		* 2.39	40.63	Pk	32.10	-24.90	0.00	47.83	-	-	74.00	-26.17	94	314	V
		* 2.38909	43.85	Pk	32.10	-24.90	0.00	51.05	-	-	74.00	-22.95	94	314	V
2478	ANT1	* 2.4835	53.39	Pk	32.40	-24.90	0.00	60.89	-	-	74.00	-13.11	129	100	H
		* 2.48359	53.69	Pk	32.40	-24.90	0.00	61.19	-	-	74.00	-12.81	129	100	H
		* 2.4835	53.01	Pk	32.40	-24.90	0.00	60.51	-	-	74.00	-13.49	87	108	V
		* 2.48354	53.36	Pk	32.40	-24.90	0.00	60.86	-	-	74.00	-13.14	87	108	V
Freq. [MHz]	Antenna	Frequency [GHz]	Reading [dBuV]	Detector Mode	ANT Factor [dB/m]	Loss [dB]	DC Corr [dB]	Result [dBuV/m]	AV Limit [dBuV/m]	AV Margin [dB]	PK Limit [dBuV/m]	PK Margin [dB]	Azimuth [Degs]	Height [cm]	Polarit
2404	ANT2	* 2.39	43.75	Pk	31.70	-26.20	0.00	49.25	-	-	74.00	-24.75	30	143	H
		* 2.38989	46.56	Pk	31.70	-26.20	0.00	52.06	-	-	74.00	-21.94	30	143	H
		* 2.39	43.31	Pk	31.70	-26.20	0.00	48.81	-	-	74.00	-25.19	171	100	V
		* 2.38635	46.29	Pk	31.70	-26.20	0.00	51.79	-	-	74.00	-22.21	171	100	V
2478	ANT2	* 2.48351	54.79	Pk	32.00	-26.20	0.00	60.59	-	-	74.00	-13.41	39	157	H
		* 2.48357	55.13	Pk	32.00	-26.20	0.00	60.93	-	-	74.00	-13.07	39	157	H
		* 2.48351	49.58	Pk	32.00	-26.20	0.00	55.38	-	-	74.00	-18.62	336	100	V
		* 2.48366	51.51	Pk	32.00	-26.20	0.00	57.31	-	-	74.00	-16.69	336	100	V

Note1. Pk - Peak detector


Note2. * - indicates frequency in 47 CFR Pt 15 / IC RSS-Restricted Band

HARMONICS AND SPURIOUS EMISSIONS(WORST CASE – ANT1)

76 CHANNEL RESULTS



HORIZONTAL



VERTICAL

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	Antenna_Factor (dB/m)	3GHz_HP_Path Loss(dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.95633	38.66	PK-U	34.3	-30.5	42.46	-	-	74	-31.54	0	100	H
* 4.9543	38.69	PK-U	34.3	-30.5	42.49	-	-	74	-31.51	0	100	V
* 7.43769	34.2	PK-U	35.7	-24.9	45	-	-	74	-29	0	100	V
* 7.43407	34.46	PK-U	35.7	-25	45.16	-	-	74	-28.84	0	100	H
9.91247	32.72	PK-U	37.1	-21.4	48.42	-	-	74	-25.58	0	100	H
9.90917	32.32	PK-U	37.1	-21.4	48.02	-	-	74	-25.98	0	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
PK2 - KDB558074 Method: Maximum Peak

HARMONICS AND SPURIOUS EMISSIONS TEST DATA


Freq. [MHz]	Antenna	Frequency [GHz]	Reading [dBuV]	Detector Mode	ANT Factor [dB/m]	Loss [dB]	DC Corr [dB]	Result [dBuV/m]	AV Limit [dBuV/m]	AV Margin [dB]	PK Limit [dBuV/m]	PK Margin [dB]	Azimuth [Degs]	Height [cm]	Polarity
2404	ANT1	* 4.8069	39.44	PK2	34.30	-30.10	0.00	43.64	-	-	74.00	-30.36	0	100	H
		* 4.80627	38.95	PK2	34.30	-30.10	0.00	43.15	-	-	74.00	-30.85	0	100	V
		7.209	34.41	PK2	35.80	-25.80	0.00	44.41	-	-	74.00	-29.59	0	100	H
		7.214	34.55	PK2	35.80	-25.70	0.00	44.65	-	-	74.00	-29.35	0	100	V
		9.614	32.85	PK2	36.70	-21.70	0.00	47.85	-	-	74.00	-26.15	0	100	H
		9.614	32.33	PK2	36.70	-21.70	0.00	47.33	-	-	74.00	-26.67	0	100	V
2440	ANT1	* 4.87889	39.21	PK2	34.20	-30.80	0.00	42.61	-	-	74.00	-31.39	0	100	H
		* 4.88178	39.21	PK2	34.20	-30.80	0.00	42.61	-	-	74.00	-31.39	0	100	V
		* 7.3241	34.28	PK2	35.80	-25.30	0.00	44.78	-	-	74.00	-29.22	0	100	H
		* 7.31818	34.49	PK2	35.80	-25.30	0.00	44.99	-	-	74.00	-29.01	0	100	V
		9.762	32.43	PK2	36.90	-21.40	0.00	47.93	-	-	74.00	-26.07	0	100	H
		9.765	32.54	PK2	36.90	-21.30	0.00	48.14	-	-	74.00	-25.86	0	100	V
2478	ANT1	* 4.95633	38.66	PK2	34.30	-30.50	0.00	42.46	-	-	74.00	-31.54	0	100	H
		* 4.9543	38.69	PK2	34.30	-30.50	0.00	42.49	-	-	74.00	-31.51	0	100	V
		* 7.43769	34.20	PK2	35.70	-24.90	0.00	45.00	-	-	74.00	-29.00	0	100	V
		* 7.43407	34.46	PK2	35.70	-25.00	0.00	45.16	-	-	74.00	-28.84	0	100	H
		9.912	32.72	PK2	37.10	-21.40	0.00	48.42	-	-	74.00	-25.58	0	100	H
		9.909	32.32	PK2	37.10	-21.40	0.00	48.02	-	-	74.00	-25.98	0	100	V
Freq. [MHz]	Antenna	Frequency [GHz]	Reading [dBuV]	Detector Mode	ANT Factor [dB/m]	Loss [dB]	DC Corr [dB]	Result [dBuV/m]	AV Limit [dBuV/m]	AV Margin [dB]	PK Limit [dBuV/m]	PK Margin [dB]	Azimuth [Degs]	Height [cm]	Polarity
2404	ANT2	* 4.80966	42.70	PK2	34.20	-33.00	0.00	43.90	-	-	74.00	-30.10	0	100	H
		* 4.80808	43.09	PK2	34.20	-33.00	0.00	44.29	-	-	74.00	-29.71	0	100	V
		7.213	41.06	PK2	35.60	-30.90	0.00	45.76	-	-	74.00	-28.24	0	100	H
		7.210	40.54	PK2	35.60	-30.90	0.00	45.24	-	-	74.00	-28.76	0	100	V
		9.618	37.71	PK2	37.00	-27.00	0.00	47.71	-	-	74.00	-26.29	0	100	H
		9.614	37.07	PK2	37.00	-27.00	0.00	47.07	-	-	74.00	-26.93	0	100	V
2440	ANT2	* 4.8776	42.49	PK2	34.20	-33.00	0.00	43.69	-	-	74.00	-30.31	0	100	H
		* 4.88132	42.76	PK2	34.20	-33.00	0.00	43.96	-	-	74.00	-30.04	0	100	V
		* 7.32106	41.03	PK2	35.50	-30.70	0.00	45.83	-	-	74.00	-28.17	0	100	H
		* 7.31777	40.69	PK2	35.50	-30.80	0.00	45.39	-	-	74.00	-28.61	0	100	V
		9.759	37.34	PK2	37.20	-26.40	0.00	48.14	-	-	74.00	-25.86	0	100	H
		9.760	37.08	PK2	37.20	-26.40	0.00	47.88	-	-	74.00	-26.12	0	100	V
2478	ANT2	* 4.9551	42.41	PK2	34.20	-32.90	0.00	43.71	-	-	74.00	-30.29	0	100	H
		* 4.95653	43.02	PK2	34.20	-33.00	0.00	44.22	-	-	74.00	-29.78	0	100	V
		* 7.43481	40.75	PK2	35.60	-30.30	0.00	46.05	-	-	74.00	-27.95	0	100	H
		* 7.43186	40.68	PK2	35.60	-30.40	0.00	45.88	-	-	74.00	-28.12	0	100	V
		9.910	37.51	PK2	37.40	-27.10	0.00	47.81	-	-	74.00	-26.19	0	100	H
		9.913	37.70	PK2	37.40	-27.10	0.00	48.00	-	-	74.00	-26.00	0	100	V

* - indicates frequency in 47 CFR Pt 15 / IC RSS-Restricted Band


PK2 - KDB558074 Method: Maximum Peak

10.2. WORST CASE BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION)



HORIZONTAL



VERTICAL

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Antenna_Factor (dB/m)	Below_1G_Path Loss(dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	96.833	45.75	Pk	16.9	-30.3	32.35	43.52	-11.17	0-360	200	H
2	287.341	40.46	Pk	18.9	-28.7	30.66	46.02	-15.36	0-360	100	H
3	598.42	33.05	Pk	25	-27.3	30.75	46.02	-15.27	0-360	100	H
4	39.409	41.41	Pk	18.3	-31.1	28.61	40	-11.39	0-360	200	V
5	87.133	41.7	Pk	14.7	-30.4	26	40	-14	0-360	300	V
6	598.129	38.52	Pk	25	-27.3	36.22	46.02	-9.8	0-360	200	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
Pk - Peak detector

11. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10:2020.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

11.1. AC Power Line

LINE 1 RESULTS



Trace Markers


Range 1: Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101836_Wit h EX_L1 [dB]	Cable Loss [dB]	Corrected Reading (dB(uVolts))	FCC 15 Class B QP [dBuV]	Margin (dB)	FCC 15 Class B AV [dBuV]	Margin (dB)
1	.183	38.81	Pk	9.9	.1	48.81	64.35	-15.54	-	-
2	.165	20.09	Av	9.9	.1	30.09	-	-	55.21	-25.12
3	.315	34.52	Pk	9.7	.1	44.32	59.84	-15.52	-	-
4	.315	20.61	Av	9.7	.1	30.41	-	-	49.84	-19.43
5	.567	33.72	Pk	9.8	.1	43.62	56	-12.38	-	-
6	.537	15.46	Av	9.9	.1	25.46	-	-	46	-20.54
7	1.014	34.35	Pk	9.7	.1	44.15	56	-11.85	-	-
8	1.014	14.55	Av	9.7	.1	24.35	-	-	46	-21.65
9	5.208	36.81	Pk	9.8	.2	46.81	60	-13.19	-	-
10	5.211	14.2	Av	9.8	.2	24.2	-	-	50	-25.8
11	15.273	27.66	Pk	10	.3	37.96	60	-22.04	-	-
12	15.252	15.46	Av	10	.3	25.76	-	-	50	-24.24

Pk - Peak detector

Av - Average detection

LINE 2 RESULTS



Trace Markers

Range 2: Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101836_Wit h EX_N [dB]	Cable Loss [dB]	Corrected Reading (dB(uVolts))	FCC 15 Class B QP [dBuV]	Margin (dB)	FCC 15 Class B AV [dBuV]	Margin (dB)
13	.291	37.48	Pk	9.7	.1	47.28	60.5	-13.22	-	-
14	.291	25.46	Av	9.7	.1	35.26	-	-	50.5	-15.24
15	.654	38.71	Pk	9.8	.1	48.61	56	-7.39	-	-
16	.654	18.19	Av	9.8	.1	28.09	-	-	46	-17.91
17	.903	39.46	Pk	9.8	.1	49.36	56	-6.64	-	-
18	.903	21.68	Av	9.8	.1	31.58	-	-	46	-14.42
19	2.763	39.44	Pk	9.7	.1	49.24	56	-6.76	-	-
20	2.763	19.65	Av	9.7	.1	29.45	-	-	46	-16.55
21	5.232	37.47	Pk	9.8	.2	47.47	60	-12.53	-	-
22	5.241	19.42	Av	9.8	.2	29.42	-	-	50	-20.58
23	14.616	29.89	Pk	10.1	.3	40.29	60	-19.71	-	-
24	14.616	12.79	Av	10.1	.3	23.19	-	-	50	-26.81

Pk - Peak detector
Av - Average detection

END OF TEST REPORT