

APPENDIX A: SAR TEST PLOTS

ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0546M

Communication System: UID:10021 - DAC, GSM; MAIA: Y; Frequency: 824.200 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 824.200 MHz; cond = 0.863 S/m; perm = 42.6; density = 1000 kg/m³

Phantom Section: LeftHead; Space: 0.00 mm

Test Date: 09/15/2025; Ambient Temp: 20.1°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7659; ConvF:(9.99,9.58,9.71); Calibrated: 2025-04-07

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1272; Calibrated: 2025-04-10

Phantom: Twin-SAM V8.0; Serial: 1966

Measurement SW: DASY Module SAR V16.4.0.5005

Mode: GSM 850, Antenna E, Exp: Head| Left Cheek, Ch. Low

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.33 W/kg; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.942 W/kg

SAR(1 g) = 0.453 W/kg

Smallest distance from peaks to all points 3 dB below is 9.7 mm

Ratio of SAR at M2 to SAR at M1 = 77.2 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0546M

Communication System: UID:10028 - DAC, GSM; MAIA: Y; Frequency: 836.600 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 836.600 MHz; cond = 0.867 S/m; perm = 42.6; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/15/2025; Ambient Temp: 20.1°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7659; ConvF:(9.99,9.58,9.71); Calibrated: 2025-04-07

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1272; Calibrated: 2025-04-10

Phantom: Twin-SAM V8.0; Serial: 1966

Measurement SW: DASY Module SAR V16.4.0.5005

Mode: GPRS 850, Antenna E, Exp: Body-worn/Hotspot| Back Side, Ch. Mid, 4 Tx Slots

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.51 W/kg; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.19 W/kg

SAR(1 g) = 0.604 W/kg

Smallest distance from peaks to all points 3 dB below is 9.6 mm

Ratio of SAR at M2 to SAR at M1 = 79.0 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0546M

Communication System: UID:10021 - DAC, GSM; MAIA: Y; Frequency: 1880.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 1880.000 MHz; cond = 1.38 S/m; perm = 41.1; density = 1000 kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 09/12/2025; Ambient Temp: 20.2°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN7659; ConvF:(8.38,8.04,8.14); Calibrated: 2025-04-07

Sensor-Surface: 1.4mm (All points)

Electronics: DAE4 Sn1272; Calibrated: 2025-04-10

Phantom: Twin-SAM V8.0; Serial: 1966

Measurement SW: DASY Module SAR V16.4.0.5005

Mode: GSM 1900, Antenna A, Exp: Head| Right Cheek, Ch. Mid

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.01 W/kg; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.067 W/kg

SAR(1 g) = 0.049 W/kg

Smallest distance from peaks to all points 3 dB below is 15.6 mm

Ratio of SAR at M2 to SAR at M1 = 90.7 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0546M

Communication System: UID:10028 - DAC, GSM; MAIA: Y; Frequency: 1850.200 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 1850.200 MHz; cond = 1.37 S/m; perm = 40.5; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/17/2025; Ambient Temp: 21.3°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN7659; ConvF:(8.38,8.04,8.14); Calibrated: 2025-04-07

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1272; Calibrated: 2025-04-10

Phantom: Twin-SAM V8.0; Serial: 1966

Measurement SW: DASY Module SAR V16.4.0.5005

Mode: GPRS 1900, Antenna A, Exp: Body-worn/Hotspot| Back Side, Ch. Low, 4 Tx Slots

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.01 W/kg; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 1.26 W/kg

SAR(1 g) = 0.705 W/kg

Smallest distance from peaks to all points 3 dB below is 8.4 mm

Ratio of SAR at M2 to SAR at M1 = 84.2 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0546M

Communication System: UID:10011 - CAC, WCDMA; MAIA: Y; Frequency: 846.600 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 846.600 MHz; cond = 0.870 S/m; perm = 42.6; density = 1000 kg/m³

Phantom Section: LeftHead; Space: 0.00 mm

Test Date: 09/15/2025; Ambient Temp: 20.1°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7659; ConvF:(9.99,9.58,9.71); Calibrated: 2025-04-07

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1272; Calibrated: 2025-04-10

Phantom: Twin-SAM V8.0; Serial: 1966

Measurement SW: DASY Module SAR V16.4.0.5005

Mode: UMTS 850, Antenna E, Exp: Head| Left Cheek, Ch. High

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.41 W/kg; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.41 W/kg

SAR(1 g) = 0.666 W/kg

Smallest distance from peaks to all points 3 dB below is 9.2 mm

Ratio of SAR at M2 to SAR at M1 = 75.9 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0546M

Communication System: UID:10011 - CAC, WCDMA; MAIA: Y; Frequency: 846.600 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 846.600 MHz; cond = 0.870 S/m; perm = 42.6; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/15/2025; Ambient Temp: 20.1°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7659; ConvF:(9.99,9.58,9.71); Calibrated: 2025-04-07

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1272; Calibrated: 2025-04-10

Phantom: Twin-SAM V8.0; Serial: 1966

Measurement SW: DASY Module SAR V16.4.0.5005

Mode: UMTS 850, Antenna E, Exp: Body-worn/Hotspot| Back Side, Ch. High

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.07 W/kg; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.58 W/kg

SAR(1 g) = 0.812 W/kg

Smallest distance from peaks to all points 3 dB below is 7.2 mm

Ratio of SAR at M2 to SAR at M1 = 81.3 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0546M

Communication System: UID:10011 - CAC, WCDMA; MAIA: Y; Frequency: 1752.600 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 1752.600 MHz; cond = 1.32 S/m; perm = 41.3; density = 1000 kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 09/12/2025; Ambient Temp: 20.2°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN7659; ConvF:(8.68,8.33,8.44); Calibrated: 2025-04-07

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1272; Calibrated: 2025-04-10

Phantom: Twin-SAM V8.0; Serial: 1966

Measurement SW: DASY Module SAR V16.4.0.5005

Mode: UMTS 1750, Antenna A, Exp: Head| Right Cheek, Ch. High

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.10 W/kg; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.150 W/kg

SAR(1 g) = 0.114 W/kg

Smallest distance from peaks to all points 3 dB below is 15.6 mm

Ratio of SAR at M2 to SAR at M1 = 94.7 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0564M

Communication System: UID:10011 - CAC, WCDMA; MAIA: Y; Frequency: 1732.400 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 1732.400 MHz; cond = 1.30 S/m; perm = 41.3; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/12/2025; Ambient Temp: 20.2°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN7659; ConvF:(8.68,8.33,8.44); Calibrated: 2025-04-07

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1272; Calibrated: 2025-04-10

Phantom: Twin-SAM V8.0; Serial: 1966

Measurement SW: DASY Module SAR V16.4.0.5005

Mode: UMTS 1750, Antenna A, Exp: Body-worn/Hotspot| Back Side, Ch. Mid

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.70 W/kg; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.43 W/kg

SAR(1 g) = 0.776 W/kg

Smallest distance from peaks to all points 3 dB below is 7.2 mm

Ratio of SAR at M2 to SAR at M1 = 83.1 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0546M

Communication System: UID:10011 - CAC, WCDMA; MAIA: Y; Frequency: 1852.400 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 1852.400 MHz; cond = 1.37 S/m; perm = 41.2; density = 1000 kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 09/12/2025; Ambient Temp: 20.2°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN7659; ConvF:(8.38,8.04,8.14); Calibrated: 2025-04-07

Sensor-Surface: 1.4mm (All points)

Electronics: DAE4 Sn1272; Calibrated: 2025-04-10

Phantom: Twin-SAM V8.0; Serial: 1966

Measurement SW: DASY Module SAR V16.4.0.5005

Mode: UMTS 1900, Antenna A, Exp: Head| Right Cheek, Ch. Low

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.09 W/kg; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.189 W/kg

SAR(1 g) = 0.136 W/kg

Smallest distance from peaks to all points 3 dB below is 12.5 mm

Ratio of SAR at M2 to SAR at M1 = 89.6 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0546M

Communication System: UID:10011 - CAC, WCDMA; MAIA: Y; Frequency: 1852.400 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 1852.400$ MHz; $\text{cond} = 1.37$ S/m; $\text{perm} = 41.2$; $\text{density} = 1000$ kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/12/2025; Ambient Temp: 20.2°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN7659; ConvF:(8.38,8.04,8.14); Calibrated: 2025-04-07

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1272; Calibrated: 2025-04-10

Phantom: Twin-SAM V8.0; Serial: 1966

Measurement SW: DASY Module SAR V16.4.0.5005

Mode: UMTS 1900, Antenna A, Exp: Body-worn/Hotspot| Back Side, Ch. Low

Area Scan (120.0 x 210.0): Measurement grid: $dx=15.0$ mm, $dy=15.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $dx=6.0$ mm, $dy=6.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5


Reference Value = 0.03 W/kg; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.40 W/kg

SAR(1 g) = 0.782 W/kg

Smallest distance from peaks to all points 3 dB below is 8.4 mm

Ratio of SAR at M2 to SAR at M1 = 84.9 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0546M

Communication System: UID:10169 - CAF, LTE-FDD; MAIA: Y; Frequency: 680.500 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 680.500 MHz; cond = 0.872 S/m; perm = 40.5; density = 1000 kg/m³

Phantom Section: LeftHead; Space: 0.00 mm

Test Date: 09/01/2025; Ambient Temp: 21.7°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7718; ConvF:(9.33,9.31,9.63); Calibrated: 2025-04-08

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1407; Calibrated: 2025-04-07

Phantom: Twin-SAM V8.0; Serial: 2060

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 71, Antenna E, Exp: Head| Left Cheek, Ch. Mid,
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.49 W/kg; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.34 W/kg

SAR(1 g) = 0.573 W/kg

Smallest distance from peaks to all points 3 dB below is 10.8 mm

Ratio of SAR at M2 to SAR at M1 = 71.8 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0546M

Communication System: UID:10169 - CAF, LTE-FDD; MAIA: Y; Frequency: 680.500 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 680.500 MHz; cond = 0.845 S/m; perm = 41.0; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/08/2025; Ambient Temp: 21.1°C; Tissue Temp: 20.8°C

Probe: EX3DV4 - SN7718; ConvF:(9.33,9.31,9.63); Calibrated: 2025-04-08

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1407; Calibrated: 2025-04-07

Phantom: Twin-SAM V8.0; Serial: 2060

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 71, Antenna E, Exp: Body-worn/Hotspot| Back Side, Ch. Mid,
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.58 W/kg; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.17 W/kg

SAR(1 g) = 0.576 W/kg

Smallest distance from peaks to all points 3 dB below is 7.2 mm

Ratio of SAR at M2 to SAR at M1 = 78.4 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0546M

Communication System: UID:10154 - CAH, LTE-FDD; MAIA: Y; Frequency: 707.500 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 707.500$ MHz; $\text{cond} = 0.885$ S/m; $\text{perm} = 40.5$; $\text{density} = 1000$ kg/m³

Phantom Section: LeftHead; Space: 0.00 mm

Test Date: 09/01/2025; Ambient Temp: 21.7°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7718; ConvF:(9.33,9.31,9.63); Calibrated: 2025-04-08

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1407; Calibrated: 2025-04-07

Phantom: Twin-SAM V8.0; Serial: 2060

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 12, Antenna E, Exp: Head| Left Cheek, Ch. Mid,
10 MHz Bandwidth, QPSK, 25 RB, 12 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: $dx=15.0$ mm, $dy=15.0$ mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: $dx=6.0$ mm, $dy=6.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5


Reference Value = 0.50 W/kg; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.35 W/kg

SAR(1 g) = 0.593 W/kg

Smallest distance from peaks to all points 3 dB below is 7.7 mm

Ratio of SAR at M2 to SAR at M1 = 73.8 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0546M

Communication System: UID:10154 - CAH, LTE-FDD; MAIA: Y; Frequency: 707.500 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 707.500 MHz; cond = 0.854 S/m; perm = 40.9; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/08/2025; Ambient Temp: 21.1°C; Tissue Temp: 20.8°C

Probe: EX3DV4 - SN7718; ConvF:(9.33,9.31,9.63); Calibrated: 2025-04-08

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1407; Calibrated: 2025-04-07

Phantom: Twin-SAM V8.0; Serial: 2060

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 12, Antenna E, Exp: Body-worn/Hotspot| Back Side, Ch. Mid,
10 MHz Bandwidth, QPSK, 25 RB, 0 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.70 W/kg; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.44 W/kg

SAR(1 g) = 0.711 W/kg

Smallest distance from peaks to all points 3 dB below is 8.4 mm

Ratio of SAR at M2 to SAR at M1 = 81.9 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0546M

Communication System: UID:10175 - CAH, LTE-FDD; MAIA: Y; Frequency: 782.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 782.000 MHz; cond = 0.904 S/m; perm = 40.2; density = 1000 kg/m³

Phantom Section: LeftHead; Space: 0.00 mm

Test Date: 09/01/2025; Ambient Temp: 21.7°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7718; ConvF:(9.33,9.31,9.63); Calibrated: 2025-04-08

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1407; Calibrated: 2025-04-07

Phantom: Twin-SAM V8.0; Serial: 2060

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 13, Antenna E, Exp: Head| Left Cheek, Ch. Mid,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.57 W/kg; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.49 W/kg

SAR(1 g) = 0.665 W/kg

Smallest distance from peaks to all points 3 dB below is 10.3 mm

Ratio of SAR at M2 to SAR at M1 = 73.0 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0546M

Communication System: UID:10175 - CAH, LTE-FDD; MAIA: Y; Frequency: 782.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 782.000 MHz; cond = 0.904 S/m; perm = 40.2; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/01/2025; Ambient Temp: 21.7°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7718; ConvF:(9.33,9.31,9.63); Calibrated: 2025-04-08

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1407; Calibrated: 2025-04-07

Phantom: Twin-SAM V8.0; Serial: 2060

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 13, Antenna A, Exp: Body-worn/Hotspot| Back Side, Ch. Mid,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.77 W/kg; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.55 W/kg

SAR(1 g) = 0.795 W/kg

Smallest distance from peaks to all points 3 dB below is 9.9 mm

Ratio of SAR at M2 to SAR at M1 = 78.9 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0546M

Communication System: UID:10175 - CAH, LTE-FDD; MAIA: Y; Frequency: 793.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 793.000 MHz; cond = 0.908 S/m; perm = 40.2; density = 1000 kg/m³

Phantom Section: LeftHead; Space: 0.00 mm

Test Date: 09/01/2025; Ambient Temp: 21.7°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7718; ConvF:(9.33,9.31,9.63); Calibrated: 2025-04-08

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1407; Calibrated: 2025-04-07

Phantom: Twin-SAM V8.0; Serial: 2060

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 14, Antenna E, Exp: Head| Left Cheek, Ch. Mid,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (42.0 x 42.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.55 W/kg; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.45 W/kg

SAR(1 g) = 0.642 W/kg

Smallest distance from peaks to all points 3 dB below is 10.2 mm

Ratio of SAR at M2 to SAR at M1 = 74.3 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0546M

Communication System: UID:10175 - CAH, LTE-FDD; MAIA: Y; Frequency: 793.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 793.000 MHz; cond = 0.908 S/m; perm = 40.2; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/01/2025; Ambient Temp: 21.7°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7718; ConvF:(9.33,9.31,9.63); Calibrated: 2025-04-08

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1407; Calibrated: 2025-04-07

Phantom: Twin-SAM V8.0; Serial: 2060

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 14, Antenna A, Exp: Body-worn/Hotspot| Back Side, Ch. Mid,
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.76 W/kg; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.58 W/kg

SAR(1 g) = 0.794 W/kg

Smallest distance from peaks to all points 3 dB below is 9.9 mm

Ratio of SAR at M2 to SAR at M1 = 78.5 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0546M

Communication System: UID:10181 - CAF, LTE-FDD; MAIA: Y; Frequency: 831.500 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 831.500 MHz; cond = 0.925 S/m; perm = 40.1; density = 1000 kg/m³

Phantom Section: LeftHead; Space: 0.00 mm

Test Date: 09/01/2025; Ambient Temp: 21.7°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7718; ConvF:(9.17,9.15,9.46); Calibrated: 2025-04-08

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1407; Calibrated: 2025-04-07

Phantom: Twin-SAM V8.0; Serial: 2060

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 26, Antenna E, Exp: Head| Left Cheek, Ch. Mid,
15 MHz Bandwidth, QPSK, 1 RB, 74 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.65 W/kg; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.57 W/kg

SAR(1 g) = 0.734 W/kg

Smallest distance from peaks to all points 3 dB below is 9.7 mm

Ratio of SAR at M2 to SAR at M1 = 79.2 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0546M

Communication System: UID:10181 - CAF, LTE-FDD; MAIA: Y; Frequency: 831.500 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 831.500 MHz; cond = 0.925 S/m; perm = 40.1; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/01/2025; Ambient Temp: 21.7°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7718; ConvF:(9.17,9.15,9.46); Calibrated: 2025-04-08

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1407; Calibrated: 2025-04-07

Phantom: Twin-SAM V8.0; Serial: 2060

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 26, Antenna A, Exp: Body-worn/Hotspot| Back Side, Ch. Mid,
15 MHz Bandwidth, QPSK, 1 RB, 74 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 36.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.63 W/kg; Power Drift = 0.20 dB

Peak SAR (extrapolated) = 1.13 W/kg

SAR(1 g) = 0.657 W/kg

Smallest distance from peaks to all points 3 dB below is 14.1 mm

Ratio of SAR at M2 to SAR at M1 = 82.9 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0708M

Communication System: UID:10169 - CAF, LTE-FDD; MAIA: Y; Frequency: 1745.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 1745.000 MHz; cond = 1.33 S/m; perm = 38.8; density = 1000 kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 09/08/2025; Ambient Temp: 21.3°C; Tissue Temp: 20.4°C

Probe: EX3DV4 - SN7410; ConvF:(7.81,7.7,8.15); Calibrated: 2024-12-05

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1213; Calibrated: 2024-12-04

Phantom: Twin-SAM V8.0; Serial: 1978

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 66, Antenna F, Exp: Head| Right Cheek, Ch. Mid,
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.40 W/kg; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 1.49 W/kg

SAR(1 g) = 0.726 W/kg

Smallest distance from peaks to all points 3 dB below is 7.3 mm

Ratio of SAR at M2 to SAR at M1 = 77.8 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0708M

Communication System: UID:10169 - CAF, LTE-FDD; MAIA: Y; Frequency: 1745.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 1745.000 MHz; cond = 1.33 S/m; perm = 38.8; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/08/2025; Ambient Temp: 21.3°C; Tissue Temp: 20.4°C

Probe: EX3DV4 - SN7410; ConvF:(7.81,7.7,8.15); Calibrated: 2024-12-05

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1213; Calibrated: 2024-12-04

Phantom: Twin-SAM V8.0; Serial: 1978

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 66, Antenna A, Exp: Body-worn/Hotspot| Front Side, Ch. Mid,
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.01 W/kg; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 1.52 W/kg

SAR(1 g) = 0.767 W/kg

Smallest distance from peaks to all points 3 dB below is 6.6 mm

Ratio of SAR at M2 to SAR at M1 = 81.1 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0708M

Communication System: UID:10169 - CAF, LTE-FDD; MAIA: Y; Frequency: 1905.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 1905.000 MHz; cond = 1.42 S/m; perm = 38.6; density = 1000 kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 09/08/2025; Ambient Temp: 21.3°C; Tissue Temp: 20.4°C

Probe: EX3DV4 - SN7410; ConvF:(7.58,7.48,7.91); Calibrated: 2024-12-05

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1213; Calibrated: 2024-12-04

Phantom: Twin-SAM V8.0; Serial: 1978

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 25, Antenna F, Exp: Head| Right Cheek, Ch. High,
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.42 W/kg; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.35 W/kg

SAR(1 g) = 0.663 W/kg

Smallest distance from peaks to all points 3 dB below is 7.3 mm

Ratio of SAR at M2 to SAR at M1 = 81.4 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0708M

Communication System: UID:10100 - CAF, LTE-FDD; MAIA: Y; Frequency: 1860.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 1860.000$ MHz; $\text{cond} = 1.40$ S/m; $\text{perm} = 38.8$; $\text{density} = 1000$ kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/04/2025; Ambient Temp: 21.0°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7410; ConvF:(7.58,7.48,7.91); Calibrated: 2024-12-05

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1213; Calibrated: 2024-12-04

Phantom: Twin-SAM V8.0; Serial: 1978

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 25, Antenna A, Exp: Body-worn| Back Side, Ch. Low,
20 MHz Bandwidth, QPSK, 100 RB, 0 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: $dx=15.0$ mm, $dy=15.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $dx=6.0$ mm, $dy=6.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5


Reference Value = 0.02 W/kg; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 1.33 W/kg

SAR(1 g) = 0.725 W/kg

Smallest distance from peaks to all points 3 dB below is 8.1 mm

Ratio of SAR at M2 to SAR at M1 = 83.2 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0708M

Communication System: UID:10169 - CAF, LTE-FDD; MAIA: Y; Frequency: 1860.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 1860.000 MHz; cond = 1.40 S/m; perm = 38.8; density = 1000 kg/m³

Phantom Section: Flat; Space: 10.00 mm

Test Date: 09/04/2025; Ambient Temp: 21.0°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7410; ConvF:(7.58,7.48,7.91); Calibrated: 2024-12-05

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1213; Calibrated: 2024-12-04

Phantom: Twin-SAM V8.0; Serial: 1978

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 25, Antenna A, Exp: Hotspot| Bottom Edge, Ch. Low,
20 MHz Bandwidth, QPSK, 1 RB, 50 RB Offset**

Area Scan (40.0 x 120.0): Measurement grid: dx=5.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.81 W/kg; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.37 W/kg

SAR(1 g) = 0.765 W/kg

Smallest distance from peaks to all points 3 dB below is 8.8 mm

Ratio of SAR at M2 to SAR at M1 = 82.7 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0510M

Communication System: UID:10175 - CAH, LTE-FDD; MAIA: Y; Frequency: 2310.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 2310.000 MHz; cond = 1.74 S/m; perm = 41.0; density = 1000 kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 09/18/2025; Ambient Temp: 20.5°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7640; ConvF:(8.11,7.54,8.1); Calibrated: 2025-02-12

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1645; Calibrated: 2025-02-11

Phantom: Twin-SAM V8.0; Serial: 1934

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 30, Antenna F, Exp: Head| Right Tilt, Ch. Mid,
10 MHz Bandwidth, QPSK, 1 RB, 49 RB Offset**

Area Scan (120.0 x 200.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.61 W/kg; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.59 W/kg

SAR(1 g) = 0.729 W/kg

Smallest distance from peaks to all points 3 dB below is 7.1 mm

Ratio of SAR at M2 to SAR at M1 = 79.5 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0510M

Communication System: UID:10154 - CAH, LTE-FDD; MAIA: Y; Frequency: 2310.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 2310.000$ MHz; $\text{cond} = 1.70$ S/m; $\text{perm} = 41.2$; $\text{density} = 1000$ kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/11/2025; Ambient Temp: 20.7°C; Tissue Temp: 20.2°C

Probe: EX3DV4 - SN7640; ConvF:(8.11,7.54,8.1); Calibrated: 2025-02-12

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1645; Calibrated: 2025-02-11

Phantom: Twin-SAM V8.0; Serial: 1934

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 30, Antenna A, Exp: Body-worn/Hotspot| Back Side, Ch. Mid,
10 MHz Bandwidth, QPSK, 25 RB, 12 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5


Reference Value = 0.66 W/kg; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.59 W/kg

SAR(1 g) = 0.766 W/kg

Smallest distance from peaks to all points 3 dB below is 8.0 mm

Ratio of SAR at M2 to SAR at M1 = 80.4 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0510M

Communication System: UID:10297 - AAE, LTE-FDD; MAIA: Y; Frequency: 2510.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 2510.000 MHz; cond = 1.90 S/m; perm = 40.7; density = 1000 kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 09/18/2025; Ambient Temp: 20.5°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7640; ConvF:(8.17,7.59,8.15); Calibrated: 2025-02-12

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1645; Calibrated: 2025-02-11

Phantom: Twin-SAM V8.0; Serial: 1934

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 7, Antenna F, Exp: Head| Right Tilt, Ch. Low,
20 MHz Bandwidth, QPSK, 50 RB, 0 RB Offset**

Area Scan (120.0 x 200.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.68 W/kg; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.89 W/kg

SAR(1 g) = 0.804 W/kg

Smallest distance from peaks to all points 3 dB below is 6.4 mm

Ratio of SAR at M2 to SAR at M1 = 76.7 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0510M

Communication System: UID:10100 - CAF, LTE-FDD; MAIA: Y; Frequency: 2560.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 2560.000$ MHz; $\text{cond} = 1.89$ S/m; $\text{perm} = 40.5$; $\text{density} = 1000$ kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/15/2025; Ambient Temp: 20.5°C; Tissue Temp: 20.3°C

Probe: EX3DV4 - SN7640; ConvF:(7.86,7.3,7.85); Calibrated: 2025-02-12

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1645; Calibrated: 2025-02-11

Phantom: Twin-SAM V8.0; Serial: 1934

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 7, Antenna B, Exp: Body-worn/Hotspot| Back Side, Ch. High,
20 MHz Bandwidth, QPSK, 100 RB, 0 RB Offset**

Area Scan (120.0 x 190.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5


Reference Value = 0.81 W/kg; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 2.05 W/kg

SAR(1 g) = 0.890 W/kg

Smallest distance from peaks to all points 3 dB below is 6.4 mm

Ratio of SAR at M2 to SAR at M1 = 76.2 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0510M

Communication System: UID:10435 - AAG, LTE-TDD; MAIA: Y; Frequency: 2506.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 2506.000 MHz; cond = 1.85 S/m; perm = 41.0; density = 1000 kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 09/11/2025; Ambient Temp: 20.7°C; Tissue Temp: 20.2°C

Probe: EX3DV4 - SN7640; ConvF:(8.17,7.59,8.15); Calibrated: 2025-02-12

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1645; Calibrated: 2025-02-11

Phantom: Twin-SAM V8.0; Serial: 1934

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 41, Antenna F, Exp: Head| Right Tilt, Ch. Low,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**

Area Scan (120.0 x 200.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.68 W/kg; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.91 W/kg

SAR(1 g) = 0.817 W/kg

Smallest distance from peaks to all points 3 dB below is 6.8 mm

Ratio of SAR at M2 to SAR at M1 = 77.8 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0510M

Communication System: UID:10435 - AAG, LTE-TDD; MAIA: Y; Frequency: 2636.500 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 2636.500 MHz; cond = 1.95 S/m; perm = 40.4; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/15/2025; Ambient Temp: 20.5°C; Tissue Temp: 20.3°C

Probe: EX3DV4 - SN7640; ConvF:(7.86,7.3,7.85); Calibrated: 2025-02-12

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1645; Calibrated: 2025-02-11

Phantom: Twin-SAM V8.0; Serial: 1934

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 41, Antenna F, Exp: Body-worn/Hotspot| Back Side, Ch. Mid-High,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**

Area Scan (120.0 x 200.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.75 W/kg; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 2.01 W/kg

SAR(1 g) = 0.887 W/kg

Smallest distance from peaks to all points 3 dB below is 6.8 mm

Ratio of SAR at M2 to SAR at M1 = 76.2 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0486M

Communication System: UID:10494 - AAG, LTE-TDD; MAIA: Y; Frequency: 3603.300 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 3603.300 MHz; cond = 3.03 S/m; perm = 37.7; density = 1000 kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 09/15/2025; Ambient Temp: 20.3°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7402; ConvF:(6.35,6.86,6.54); Calibrated: 2025-06-12

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1502; Calibrated: 2025-06-04

Phantom: Twin-SAM V5.0; Serial: 1868

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 48, ULCA 48C, Antenna F, Exp: Head| Right Tilt, Ch. Low-Mid,
PCC: 20 MHz Bandwidth, QPSK, Ch. 55773, 50 RB, 50 RB Offset
SCC: 20 MHz Bandwidth, QPSK, Ch. 55971, 50 RB, 0 RB Offset**

Area Scan (120.0 x 170.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (28.0 x 28.0 x 28.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.4 mm; Graded Ratio: 1.4


Reference Value = 0.59 W/kg; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 2.76 W/kg

SAR(1 g) = 0.840 W/kg

Smallest distance from peaks to all points 3 dB below is 5.3 mm

Ratio of SAR at M2 to SAR at M1 = 69.0 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0486M

Communication System: UID:10494 - AAG, LTE-TDD; MAIA: Y; Frequency: 3646.700 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 3646.700$ MHz; $\text{cond} = 3.07$ S/m; $\text{perm} = 37.6$; $\text{density} = 1000$ kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/15/2025; Ambient Temp: 20.3°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7402; ConvF:(6.35,6.86,6.54); Calibrated: 2025-06-12

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1502; Calibrated: 2025-06-04

Phantom: Twin-SAM V5.0; Serial: 1868

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: LTE Band 48, Antenna F, Exp: Body-worn/Hotspot| Back Side, Ch. Mid-High,
20 MHz Bandwidth, QPSK, 50 RB, 25 RB Offset**

Area Scan (120.0 x 200.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (28.0 x 28.0 x 28.0): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.4$ mm; Graded Ratio: 1.5


Reference Value = 0.73 W/kg; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 2.67 W/kg

SAR(1 g) = 0.935 W/kg

Smallest distance from peaks to all points 3 dB below is 6.1 mm

Ratio of SAR at M2 to SAR at M1 = 73.4 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0536M

Communication System: UID:10770 - AAE, CW; MAIA: Y; Frequency: 680.500 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 680.500$ MHz; $\text{cond} = 0.862$ S/m; $\text{perm} = 41.2$; $\text{density} = 1000$ kg/m³

Phantom Section: LeftHead; Space: 0.00 mm

Test Date: 09/15/2025; Ambient Temp: 22.7°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7488; ConvF:(10.15,9.9,9.87); Calibrated: 2025-03-07

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1415; Calibrated: 2025-03-11

Phantom: Twin-SAM V5.0; Serial: 1757

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n71, Antenna E, Exp: Head| Left Cheek, Ch. 136100, 35 MHz Bandwidth,
CP-OFDM QPSK, 1 RB, 1 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: $dx=15.0$ mm, $dy=15.0$ mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: $dx=6.0$ mm, $dy=6.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5


Reference Value = 0.43 W/kg; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 1.43 W/kg

SAR(1 g) = 0.566 W/kg

Smallest distance from peaks to all points 3 dB below is 8.7 mm

Ratio of SAR at M2 to SAR at M1 = 70.8 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0536M

Communication System: UID:10939 - AAC, 5G NR FR1 FDD; MAIA: Y; Frequency: 680.500 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 680.500 MHz; cond = 0.853 S/m; perm = 41.3; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/10/2025; Ambient Temp: 23.2°C; Tissue Temp: 19.6°C

Probe: EX3DV4 - SN7661; ConvF:(9.54,10.15,10.14); Calibrated: 2025-06-11

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1558; Calibrated: 2025-06-05

Phantom: Twin-SAM V8.0; Serial: 2065

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n71, Antenna E, Exp: Body-worn/Hotspot| Back Side, Ch. 136100,
35 MHz Bandwidth, DFT-s-OFDM QPSK, 90 RB, 0 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (35.4 x 35.4 x 31.2): Measurement grid: dx=5.9 mm, dy=5.9 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.53 W/kg; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 1.21 W/kg

SAR(1 g) = 0.574 W/kg

Smallest distance from peaks to all points 3 dB below is 8.4 mm

Ratio of SAR at M2 to SAR at M1 = 77.6 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0537M

Communication System: UID:10938 - AAC, 5G NR FR1 FDD; MAIA: Y; Frequency: 707.500 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 707.500 MHz; cond = 0.869 S/m; perm = 41.2; density = 1000 kg/m³

Phantom Section: LeftHead; Space: 0.00 mm

Test Date: 09/15/2025; Ambient Temp: 22.7°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7488; ConvF:(10.15,9.9,9.87); Calibrated: 2025-03-07

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1415; Calibrated: 2025-03-11

Phantom: Twin-SAM V5.0; Serial: 1757

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n12, Antenna E, Exp: Head| Left Cheek, Ch. 141500, 15 MHz Bandwidth,
DFT-s-OFDM QPSK, 36 RB, 0 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.52 W/kg; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.61 W/kg

SAR(1 g) = 0.640 W/kg

Smallest distance from peaks to all points 3 dB below is 8.7 mm

Ratio of SAR at M2 to SAR at M1 = 68.8 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0536M

Communication System: UID:10946 - AAC, 5G NR FR1 FDD; MAIA: Y; Frequency: 707.500 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 707.500$ MHz; $\text{cond} = 0.862$ S/m; $\text{perm} = 41.2$; $\text{density} = 1000$ kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/10/2025; Ambient Temp: 23.2°C; Tissue Temp: 19.6°C

Probe: EX3DV4 - SN7661; ConvF:(9.54,10.15,10.14); Calibrated: 2025-06-11

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1558; Calibrated: 2025-06-05

Phantom: Twin-SAM V8.0; Serial: 2065

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n12, Antenna E, Exp: Body-worn/Hotspot| Back Side, Ch. 141500,
15 MHz Bandwidth, DFT-s-OFDM QPSK, 75 RB, 0 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: $dx=15.0$ mm, $dy=15.0$ mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: $dx=6.0$ mm, $dy=6.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5


Reference Value = 0.80 W/kg; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.66 W/kg

SAR(1 g) = 0.786 W/kg

Smallest distance from peaks to all points 3 dB below is 7.2 mm

Ratio of SAR at M2 to SAR at M1 = 76.0 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0537M

Communication System: UID:10768 - AAE, CW; MAIA: Y; Frequency: 793.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 793.000 MHz; cond = 0.897 S/m; perm = 40.9; density = 1000 kg/m³

Phantom Section: LeftHead; Space: 0.00 mm

Test Date: 09/15/2025; Ambient Temp: 22.7°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7488; ConvF:(10.15,9.9,9.87); Calibrated: 2025-03-07

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1415; Calibrated: 2025-03-11

Phantom: Twin-SAM V5.0; Serial: 1757

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n14, Antenna E, Exp: Head| Left Cheek, Ch. 158600, 10 MHz Bandwidth,
CP-OFDM QPSK, 1 RB, 1 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.55 W/kg; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 1.67 W/kg

SAR(1 g) = 0.694 W/kg

Smallest distance from peaks to all points 3 dB below is 8.5 mm

Ratio of SAR at M2 to SAR at M1 = 71.9 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0531M

Communication System: UID:10937 - AAD, 5G NR FR1 FDD; MAIA: Y; Frequency: 793.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 793.000 MHz; cond = 0.895 S/m; perm = 40.7; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/02/2025; Ambient Temp: 22.0°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7488; ConvF:(10.15,9.9,9.87); Calibrated: 2025-03-07

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1415; Calibrated: 2025-03-11

Phantom: Twin-SAM V5.0; Serial: 1757

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n14, Antenna A, Exp: Body-worn/Hotspot| Back Side, Ch. 158600,
10 MHz Bandwidth, DFT-s-OFDM QPSK, 25 RB, 14 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (42.0 x 42.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.08 W/kg; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.31 W/kg

SAR(1 g) = 0.685 W/kg

Smallest distance from peaks to all points 3 dB below is 10.4 mm

Ratio of SAR at M2 to SAR at M1 = 82.8 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0537M

Communication System: UID:10939 - AAC, 5G NR FR1 FDD; MAIA: Y; Frequency: 831.500 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 831.500 MHz; cond = 0.908 S/m; perm = 40.8; density = 1000 kg/m³

Phantom Section: LeftHead; Space: 0.00 mm

Test Date: 09/15/2025; Ambient Temp: 22.7°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7488; ConvF:(9.92,9.67,9.65); Calibrated: 2025-03-07

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1415; Calibrated: 2025-03-11

Phantom: Twin-SAM V5.0; Serial: 1757

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n26, Antenna E, Exp: Head| Left Cheek, Ch. 166300, 20 MHz Bandwidth,
DFT-s-OFDM QPSK, 50 RB, 28 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.62 W/kg; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.68 W/kg

SAR(1 g) = 0.705 W/kg

Smallest distance from peaks to all points 3 dB below is 9.4 mm

Ratio of SAR at M2 to SAR at M1 = 73.0 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0536M

Communication System: UID:10947 - AAC, 5G NR FR1 FDD; MAIA: Y; Frequency: 831.500 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 831.500$ MHz; $\text{cond} = 0.903$ S/m; $\text{perm} = 40.8$; $\text{density} = 1000$ kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/10/2025; Ambient Temp: 23.2°C; Tissue Temp: 19.6°C

Probe: EX3DV4 - SN7661; ConvF:(9.28,9.87,9.86); Calibrated: 2025-06-11

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1558; Calibrated: 2025-06-05

Phantom: Twin-SAM V8.0; Serial: 2065

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n26, Antenna E, Exp: Body-worn/Hotspot| Back Side, Ch. 166300,
20 MHz Bandwidth, DFT-s-OFDM QPSK, 100 RB, 0 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: $dx=15.0$ mm, $dy=15.0$ mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: $dx=6.0$ mm, $dy=6.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5


Reference Value = 0.70 W/kg; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.35 W/kg

SAR(1 g) = 0.682 W/kg

Smallest distance from peaks to all points 3 dB below is 7.2 mm

Ratio of SAR at M2 to SAR at M1 = 81.6 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0735M

Communication System: UID:10930 - AAC, 5G NR FR1 FDD; MAIA: Y; Frequency: 1702.500 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 1702.500 MHz; cond = 1.32 S/m; perm = 40.2; density = 1000 kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 09/04/2025; Ambient Temp: 22.7°C; Tissue Temp: 20.9°C

Probe: EX3DV4 - SN7713; ConvF:(8.88,8.27,8.04); Calibrated: 2025-01-07

Sensor-Surface: 1.4mm (All points)

Electronics: DAE4 Sn1530; Calibrated: 2025-01-13

Phantom: Twin-SAM V8.0; Serial: 2064

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n70, Antenna F, Exp: Head| Right Tilt, Ch. 340500,
15 MHz Bandwidth, DFT-s-OFDM QPSK, 1 RB, 1 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.26 W/kg; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.44 W/kg

SAR(1 g) = 0.609 W/kg

Smallest distance from peaks to all points 3 dB below is 6.9 mm

Ratio of SAR at M2 to SAR at M1 = 75.2 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0735M

Communication System: UID:10930 - AAC, 5G NR FR1 FDD; MAIA: Y; Frequency: 1702.500 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 1702.500$ MHz; $\text{cond} = 1.32$ S/m; $\text{perm} = 41.0$; $\text{density} = 1000$ kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/01/2025; Ambient Temp: 20.3°C; Tissue Temp: 19.2°C

Probe: EX3DV4 - SN7713; ConvF:(8.88,8.27,8.04); Calibrated: 2025-01-07

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1530; Calibrated: 2025-01-13

Phantom: Twin-SAM V8.0; Serial: 2064

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n70, Antenna A, Exp: Body-worn/Hotspot| Back Side, Ch. 340500,
15 MHz Bandwidth, DFT-s-OFDM QPSK, 1 RB, 77 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: $dx=15.0$ mm, $dy=15.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $dx=6.0$ mm, $dy=6.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5


Reference Value = 0.70 W/kg; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.41 W/kg

SAR(1 g) = 0.781 W/kg

Smallest distance from peaks to all points 3 dB below is 8.4 mm

Ratio of SAR at M2 to SAR at M1 = 84.2 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0735M

Communication System: UID:10934 - AAC, 5G NR FR1 FDD; MAIA: Y; Frequency: 1745.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 1745.000$ MHz; $\text{cond} = 1.35$ S/m; $\text{perm} = 40.1$; $\text{density} = 1000$ kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 09/04/2025; Ambient Temp: 22.7°C; Tissue Temp: 20.9°C

Probe: EX3DV4 - SN7713; ConvF:(8.88,8.27,8.04); Calibrated: 2025-01-07

Sensor-Surface: 1.4mm (All points)

Electronics: DAE4 Sn1530; Calibrated: 2025-01-13

Phantom: Twin-SAM V8.0; Serial: 2064

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n66, Antenna F, Exp: Head| Right Tilt, Ch. 349000,
45 MHz Bandwidth, DFT-s-OFDM QPSK, 1 RB, 121 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: $dx=15.0$ mm, $dy=15.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $dx=6.0$ mm, $dy=6.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5


Reference Value = 0.45 W/kg; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.52 W/kg

SAR(1 g) = 0.663 W/kg

Smallest distance from peaks to all points 3 dB below is 7.2 mm

Ratio of SAR at M2 to SAR at M1 = 76.5 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0735M

Communication System: UID:10934 - AAC, 5G NR FR1 FDD; MAIA: Y; Frequency: 1745.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 1745.000 MHz; cond = 1.34 S/m; perm = 40.9; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/01/2025; Ambient Temp: 20.3°C; Tissue Temp: 19.2°C

Probe: EX3DV4 - SN7713; ConvF:(8.88,8.27,8.04); Calibrated: 2025-01-07

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1530; Calibrated: 2025-01-13

Phantom: Twin-SAM V8.0; Serial: 2064

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n66, Antenna A, Exp: Body-worn/Hotspot| Back Side, Ch. 349000,
45 MHz Bandwidth, DFT-s-OFDM QPSK, 1 RB, 121 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.68 W/kg; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.43 W/kg

SAR(1 g) = 0.779 W/kg

Smallest distance from peaks to all points 3 dB below is 7.2 mm

Ratio of SAR at M2 to SAR at M1 = 84.8 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0735M

Communication System: UID:10773 - AAF, CW; MAIA: Y; Frequency: 1882.500 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 1882.500$ MHz; $\text{cond} = 1.43$ S/m; $\text{perm} = 39.9$; $\text{density} = 1000$ kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 09/04/2025; Ambient Temp: 22.7°C; Tissue Temp: 20.9°C

Probe: EX3DV4 - SN7713; ConvF:(8.56,7.97,7.75); Calibrated: 2025-01-07

Sensor-Surface: 1.4mm (All points)

Electronics: DAE4 Sn1530; Calibrated: 2025-01-13

Phantom: Twin-SAM V8.0; Serial: 2064

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n25, Antenna F, Exp: Head| Right Tilt, Ch. 376500,
40 MHz Bandwidth, CP-OFDM QPSK, 1 RB, 1 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: $\text{dx}=15.0$ mm, $\text{dy}=15.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $\text{dx}=6.0$ mm, $\text{dy}=6.0$ mm, $\text{dz}=1.5$ mm; Graded Ratio: 1.5


Reference Value = 0.45 W/kg; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.51 W/kg

SAR(1 g) = 0.647 W/kg

Smallest distance from peaks to all points 3 dB below is 6.8 mm

Ratio of SAR at M2 to SAR at M1 = 76.1 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0735M

Communication System: UID:10773 - AAF, CW; MAIA: Y; Frequency: 1882.500 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 1882.500$ MHz; $\text{cond} = 1.43$ S/m; $\text{perm} = 39.9$; $\text{density} = 1000$ kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/04/2025; Ambient Temp: 22.7°C; Tissue Temp: 20.9°C

Probe: EX3DV4 - SN7713; ConvF:(8.56,7.97,7.75); Calibrated: 2025-01-07

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1530; Calibrated: 2025-01-13

Phantom: Twin-SAM V8.0; Serial: 2064

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n25, Antenna F, Exp: Body-worn/Hotspot| Back Side, Ch. 376500,
40 MHz Bandwidth, CP-OFDM QPSK, 1 RB, 1 RB Offset**

Area Scan (120.0 x 210.0): Measurement grid: $dx=15.0$ mm, $dy=15.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $dx=6.0$ mm, $dy=6.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5


Reference Value = 0.47 W/kg; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.24 W/kg

SAR(1 g) = 0.600 W/kg

Smallest distance from peaks to all points 3 dB below is 8.4 mm

Ratio of SAR at M2 to SAR at M1 = 78.3 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0510M

Communication System: UID:10945 - AAD, 5G NR FR1 FDD; MAIA: Y; Frequency: 2310.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 2310.000 MHz; cond = 1.73 S/m; perm = 39.7; density = 1000 kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 09/25/2025; Ambient Temp: 20.7°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7640; ConvF:(8.11,7.54,8.1); Calibrated: 2025-02-12

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1645; Calibrated: 2025-02-11

Phantom: Twin-SAM V8.0; Serial: 1934

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n30, Antenna F, Exp: Head| Right Cheek, Ch. 462000,
10 MHz Bandwidth, DFT-s-OFDM QPSK, 50 RB, 0 RB Offset**

Area Scan (120.0 x 180.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.47 W/kg; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.62 W/kg

SAR(1 g) = 0.736 W/kg

Smallest distance from peaks to all points 3 dB below is 7.1 mm

Ratio of SAR at M2 to SAR at M1 = 78.5 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0536M

Communication System: UID:10768 - AAE, CW; MAIA: Y; Frequency: 2310.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 2310.000 MHz; cond = 1.71 S/m; perm = 38.3; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/01/2025; Ambient Temp: 24.4°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN3914; ConvF:(7.44,6.97,6.99); Calibrated: 2025-05-13

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4ip Sn1639; Calibrated: 2025-02-05

Phantom: Twin-SAM V8.0; Serial: 2053

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n30, Antenna A, Exp: Body-worn/Hotspot| Front Side, Ch. 462000,
10 MHz Bandwidth, CP-OFDM QPSK, 1 RB, 1 RB Offset**

Area Scan (120.0 x 200.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.64 W/kg; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.32 W/kg

SAR(1 g) = 0.623 W/kg

Smallest distance from peaks to all points 3 dB below is 6.4 mm

Ratio of SAR at M2 to SAR at M1 = 81.6 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0536M

Communication System: UID:10935 - AAD, 5G NR FR1 FDD; MAIA: Y; Frequency: 2535.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 2535.000$ MHz; $\text{cond} = 1.86$ S/m; $\text{perm} = 38.7$; $\text{density} = 1000$ kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 09/15/2025; Ambient Temp: 23.1°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7661; ConvF:(7.17,7.63,7.62); Calibrated: 2025-06-11

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1558; Calibrated: 2025-06-05

Phantom: Twin-SAM V8.0; Serial: 2065

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n7, Antenna F, Exp: Head| Right Tilt, Ch. 507000,
50 MHz Bandwidth, CP-OFDM QPSK, 1 RB, 1 RB Offset**

Area Scan (120.0 x 200.0): Measurement grid: $\text{dx}=10.0$ mm, $\text{dy}=10.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $\text{dx}=5.0$ mm, $\text{dy}=5.0$ mm, $\text{dz}=1.5$ mm; Graded Ratio: 1.5


Reference Value = 0.77 W/kg; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.90 W/kg

SAR(1 g) = 0.815 W/kg

Smallest distance from peaks to all points 3 dB below is 7.1 mm

Ratio of SAR at M2 to SAR at M1 = 78.0 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0536M

Communication System: UID:10935 - AAD, 5G NR FR1 FDD; MAIA: Y; Frequency: 2535.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 2535.000$ MHz; $\text{cond} = 1.86$ S/m; $\text{perm} = 38.7$; $\text{density} = 1000$ kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/15/2025; Ambient Temp: 23.1°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7661; ConvF:(7.17,7.63,7.62); Calibrated: 2025-06-11

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1558; Calibrated: 2025-06-05

Phantom: Twin-SAM V8.0; Serial: 2065

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n7, Antenna B, Exp: Body-worn/Hotspot| Back Side, Ch. 507000,
50 MHz Bandwidth, DFT-s-OFDM QPSK, 270 RB, 0 RB Offset**

Area Scan (120.0 x 200.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5


Reference Value = 0.93 W/kg; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.91 W/kg

SAR(1 g) = 0.839 W/kg

Smallest distance from peaks to all points 3 dB below is 5.9 mm

Ratio of SAR at M2 to SAR at M1 = 78.6 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0510M

Communication System: UID:10866 - AAF, 5G NR FR1 TDD; MAIA: Y; Frequency: 2592.990 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 2592.990 MHz; cond = 1.92 S/m; perm = 40.4; density = 1000 kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 09/15/2025; Ambient Temp: 20.5°C; Tissue Temp: 20.3°C

Probe: EX3DV4 - SN7640; ConvF:(7.86,7.3,7.85); Calibrated: 2025-02-12

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1645; Calibrated: 2025-02-11

Phantom: Twin-SAM V8.0; Serial: 1934

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n41, Antenna F, Path 1, Exp: Head| Right Tilt, Ch. 518598,
100 MHz Bandwidth, DFT-s-OFDM QPSK, 1 RB, 271 RB Offset**

Area Scan (120.0 x 200.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.68 W/kg; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.79 W/kg

SAR(1 g) = 0.796 W/kg

Smallest distance from peaks to all points 3 dB below is 6.6 mm

Ratio of SAR at M2 to SAR at M1 = 81.2 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0510M

Communication System: UID:10868 - AAF, 5G NR FR1 TDD; MAIA: Y; Frequency: 2592.990 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 2592.990 MHz; cond = 1.94 S/m; perm = 39.3; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/25/2025; Ambient Temp: 20.7°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7640; ConvF:(7.86,7.3,7.85); Calibrated: 2025-02-12

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1645; Calibrated: 2025-02-11

Phantom: Twin-SAM V8.0; Serial: 1934

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n41, Antenna B, Path 2, Exp: Body-worn/Hotspot| Back Side, Ch. 518598,
100 MHz Bandwidth, CP-OFDM QPSK, 1 RB, 1 RB Offset**

Area Scan (120.0 x 200.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.5 mm; Graded Ratio: 1.4


Reference Value = 0.84 W/kg; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 2.33 W/kg

SAR(1 g) = 0.949 W/kg

Smallest distance from peaks to all points 3 dB below is 5.6 mm

Ratio of SAR at M2 to SAR at M1 = 79.0



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0486M

Communication System: UID:10913 - AAD, 5G NR FR1 TDD; MAIA: Y; Frequency: 3569.995 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 3569.995 MHz; cond = 2.86 S/m; perm = 39.3; density = 1000 kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 09/12/2025; Ambient Temp: 20.9°C; Tissue Temp: 20.2°C

Probe: EX3DV4 - SN7402; ConvF:(6.24,6.75,6.43); Calibrated: 2025-06-12

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1502; Calibrated: 2025-06-04

Phantom: Twin-SAM V5.0; Serial: 1868

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n48, Antenna F, Exp: Head| Right Tilt, Ch. 638000,
40 MHz Bandwidth, DFT-s-OFDM QPSK, 1 RB, 104 RB Offset**

Area Scan (120.0 x 200.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (28.0 x 28.0 x 28.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.4 mm; Graded Ratio: 1.5


Reference Value = 0.65 W/kg; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 2.72 W/kg

SAR(1 g) = 0.869 W/kg

Smallest distance from peaks to all points 3 dB below is 5.1 mm

Ratio of SAR at M2 to SAR at M1 = 72.7 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0486M

Communication System: UID:10913 - AAD, 5G NR FR1 TDD; MAIA: Y; Frequency: 3624.985 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 3624.985$ MHz; $\text{cond} = 2.91$ S/m; $\text{perm} = 39.3$; $\text{density} = 1000$ kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/12/2025; Ambient Temp: 20.9°C; Tissue Temp: 20.2°C

Probe: EX3DV4 - SN7402; ConvF:(6.35,6.86,6.54); Calibrated: 2025-06-12

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1502; Calibrated: 2025-06-04

Phantom: Twin-SAM V5.0; Serial: 1868

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n48, Antenna F, Exp: Body-worn/Hotspot| Back Side, Ch. 641666,
40 MHz Bandwidth, DFT-s-OFDM QPSK, 50 RB, 0 RB Offset**

Area Scan (120.0 x 200.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (28.0 x 28.0 x 28.0): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.4$ mm; Graded Ratio: 1.5


Reference Value = 0.79 W/kg; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 2.63 W/kg

SAR(1 g) = 0.974 W/kg

Smallest distance from peaks to all points 3 dB below is 6.1 mm

Ratio of SAR at M2 to SAR at M1 = 72.5 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0735M

Communication System: UID:10917 - AAD, 5G NR FR1 TDD; MAIA: Y; Frequency: 3500.010 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 3500.010$ MHz; $\text{cond} = 2.77$ S/m; $\text{perm} = 38.2$; $\text{density} = 1000$ kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 09/22/2025; Ambient Temp: 21.9°C; Tissue Temp: 20.6°C

Probe: EX3DV4 - SN7660; ConvF:(7.04,6.7,7.27); Calibrated: 2025-05-09

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1678; Calibrated: 2025-05-09

Phantom: Twin-SAM V8.0; Serial: 2056

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n77 DoD, Antenna F, Exp: Head| Right Tilt, Ch. 633334,
100 MHz Bandwidth, DFT-s-OFDM QPSK, 135 RB, 138 RB Offset**

Area Scan (120.0 x 200.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (28.0 x 28.0 x 28.0): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.4$ mm; Graded Ratio: 1.5


Reference Value = 0.43 W/kg; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 2.93 W/kg

SAR(1 g) = 0.942 W/kg

Smallest distance from peaks to all points 3 dB below is 5.6 mm

Ratio of SAR at M2 to SAR at M1 = 73.7 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0735M

Communication System: UID:10803 - AAF, 5G NR FR1 TDD; MAIA: Y; Frequency: 3930.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 3930.000 MHz; cond = 3.22 S/m; perm = 36.7; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/25/2025; Ambient Temp: 22.3°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN7660; ConvF:(6.92,6.59,7.15); Calibrated: 2025-05-09

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1678; Calibrated: 2025-05-09

Phantom: Twin-SAM V8.0; Serial: 2056

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NR Band n77, Antenna F, Exp: Body-worn/Hotspot| Back Side, Ch. 662000,
100 MHz Bandwidth, CP-OFDM QPSK, 1 RB, 1 RB Offset**

Area Scan (120.0 x 200.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (28.0 x 28.0 x 28.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.4 mm; Graded Ratio: 1.5


Reference Value = 0.49 W/kg; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 2.40 W/kg

SAR(1 g) = 0.883 W/kg

Smallest distance from peaks to all points 3 dB below is 6.8 mm

Ratio of SAR at M2 to SAR at M1 = 74.7 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0509M

Communication System: UID:10415 - AAA, WLAN; MAIA: Y; Frequency: 2437.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 2437.000 MHz; cond = 1.82 S/m; perm = 39.4; density = 1000 kg/m³

Phantom Section: LeftHead; Space: 0.00 mm

Test Date: 09/18/2025; Ambient Temp: 22.2°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN7565; ConvF:(7.88,6.52,6.33); Calibrated: 2025-01-09

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1466; Calibrated: 2025-01-14

Phantom: Twin-SAM V5.0; Serial: 1715

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: 2.4 GHz WIFI/ IEEE 802.11b, Antenna I, 22 MHz Bandwidth, Exp: Head| Left Cheek,
Ch. 6, 1Mbps**

Area Scan (130.0 x 180.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.55 W/kg; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.20 W/kg

SAR(1 g) = 0.614 W/kg

Smallest distance from peaks to all points 3 dB below is 7.8 mm

Ratio of SAR at M2 to SAR at M1 = 84.2 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0509M

Communication System: UID:10415 - AAA, WLAN; MAIA: Y; Frequency: 2437.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 2437.000 MHz; cond = 1.84 S/m; perm = 40.7; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/15/2025; Ambient Temp: 22.1°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7565; ConvF:(7.88,6.52,6.33); Calibrated: 2025-01-09

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1466; Calibrated: 2025-01-14

Phantom: Twin-SAM V5.0; Serial: 1715

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: 2.4 GHz WIFI/ IEEE 802.11b, Antenna I, 22 MHz Bandwidth,
Exp: Body-worn/Hotspot| Back Side, Ch. 6, 1Mbps**

Area Scan (120.0 x 200.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.08 W/kg; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 1.94 W/kg

SAR(1 g) = 0.938 W/kg

Smallest distance from peaks to all points 3 dB below is 8.6 mm

Ratio of SAR at M2 to SAR at M1 = 77.7 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0553M

Communication System: UID:10626 - AAD, WLAN; MAIA: Y; Frequency: 5530.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 5530.000 MHz; cond = 5.17 S/m; perm = 35.2; density = 1000 kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 10/20/2025; Ambient Temp: 20.8°C; Tissue Temp: 19.8°C

Probe: EX3DV4 - SN7546; ConvF:(5.37,5.0,5.33); Calibrated: 2025-04-11

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1368; Calibrated: 2025-04-07

Phantom: Twin-SAM V5.0; Serial: 1715

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: 5 GHz WIFI/ IEEE 802.11ac, Antenna MIMO, 80 MHz Bandwidth, U-NII-2C, Exp:
Head| Right Cheek, Ch. 106, 58.5 Mbps**

Area Scan (120.0 x 200.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (32.0 x 32.0 x 22.9): Measurement grid: dx=4.0 mm, dy=4.0 mm, dz=1.4 mm; Graded Ratio: 1.4


Reference Value = 0.33 W/kg; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 3.30 W/kg

SAR(1 g) = 0.774 W/kg

Smallest distance from peaks to all points 3 dB below is 7.2 mm

Ratio of SAR at M2 to SAR at M1 = 59.7 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0506M

Communication System: UID:10544 - AAD, WLAN; MAIA: Y; Frequency: 5530.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 5530.000 MHz; cond = 4.94 S/m; perm = 34.3; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/15/2025; Ambient Temp: 21.6°C; Tissue Temp: 20.3°C

Probe: EX3DV4 - SN7637; ConvF:(5.09,5.22,5.37); Calibrated: 2025-06-12

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1652; Calibrated: 2025-06-04

Phantom: Twin-SAM V5.0; Serial: 1797

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: 5 GHz WIFI/ IEEE 802.11ac, Antenna E, 80 MHz Bandwidth, U-NII-2C,
Exp: Body-worn| Back Side, Ch. 106, 29.3 Mbps**

Area Scan (120.0 x 200.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=4.0 mm, dy=4.0 mm, dz=1.4 mm; Graded Ratio: 1.4


Reference Value = 0.55 W/kg; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 3.60 W/kg

SAR(1 g) = 0.818 W/kg

Smallest distance from peaks to all points 3 dB below is 6.1 mm

Ratio of SAR at M2 to SAR at M1 = 60.8 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0506M

Communication System: UID:10544 - AAD, WLAN; MAIA: Y; Frequency: 5775.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 5775.000$ MHz; $\text{cond} = 5.25$ S/m; $\text{perm} = 33.8$; $\text{density} = 1000$ kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/15/2025; Ambient Temp: 21.6°C; Tissue Temp: 20.3°C

Probe: EX3DV4 - SN7637; ConvF:(5.14,5.27,5.42); Calibrated: 2025-06-12

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1652; Calibrated: 2025-06-04

Phantom: Twin-SAM V5.0; Serial: 1797

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: 5 GHz WIFI/ IEEE 802.11ac, Antenna E, 80 MHz Bandwidth, U-NII-3, Exp: Hotspot|
Back Side, Ch. 155, 29.3 Mbps**

Area Scan (120.0 x 200.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: $dx=4.0$ mm, $dy=4.0$ mm, $dz=1.4$ mm; Graded Ratio: 1.4


Reference Value = 0.25 W/kg; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.74 W/kg

SAR(1 g) = 0.394 W/kg

Smallest distance from peaks to all points 3 dB below is 7.4 mm

Ratio of SAR at M2 to SAR at M1 = 58.7 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0506M

Communication System: UID:10544 - AAD, CW; MAIA: Y; Frequency: 5855.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 5855.000 MHz; cond = 5.24 S/m; perm = 34.7; density = 1000 kg/m³

Phantom Section: Flat; Space: 0.00 mm

Test Date: 09/22/2025; Ambient Temp: 21.7°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7637; ConvF:(4.93,5.06,5.2); Calibrated: 2025-06-12

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1652; Calibrated: 2025-06-04

Phantom: Twin-SAM V5.0; Serial: 1797

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: 5 GHz WIFI/ IEEE 802.11ac, Antenna G, 80 MHz Bandwidth, U-NII-4, Exp: Phablet|
Left Edge, Ch. 171, 29.3 Mbps**

Area Scan (40.0 x 200.0): Measurement grid: dx=5.0 mm, dy=10.0 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=4.0 mm, dy=4.0 mm, dz=1.4 mm; Graded Ratio: 1.2


Reference Value = 2.93 W/kg; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 30.1 W/kg

SAR(10 g) = 1.03 W/kg

Smallest distance from peaks to all points 3 dB below is 4.1 mm

Ratio of SAR at M2 to SAR at M1 = 59.7 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0542M

Communication System: UID:10755 - AAC, WLAN; MAIA: Y; Frequency: 6025.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 6025.000 MHz; cond = 5.39 S/m; perm = 34.1; density = 1000 kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 09/17/2025; Ambient Temp: 24.4°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7570; ConvF:(5.35,5.65,5.29); Calibrated: 2025-02-10

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4ip Sn1638; Calibrated: 2025-02-07

Phantom: Twin-SAM V8.0; Serial: 1979

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: 6 GHz WIFI/ IEEE 802.11ax, Antenna MIMO, 160 MHz Bandwidth, U-NII-5, Exp:
Head| Right Cheek, Ch. 15, 136.1 Mbps**

Area Scan (119.0 x 204.0): Measurement grid: dx=8.5 mm, dy=8.5 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=3.4 mm, dy=3.4 mm, dz=1.4 mm; Graded Ratio: 1.4


Reference Value = 0.24 W/kg; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 1.95 W/kg

SAR(1 g) = 0.370 W/kg

Smallest distance from peaks to all points 3 dB below is 3.5 mm

Ratio of SAR at M2 to SAR at M1 = 51.3 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0542M

Communication System: UID:10755 - AAC, WLAN; MAIA: Y; Frequency: 6025.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 6025.000 MHz; cond = 5.36 S/m; perm = 35.0; density = 1000 kg/m³

Phantom Section: LeftHead; Space: 0.00 mm

Test Date: 09/04/2025; Ambient Temp: 22.6°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN7570; ConvF:(5.35,5.65,5.29); Calibrated: 2025-02-10

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4ip Sn1638; Calibrated: 2025-02-07

Phantom: Twin-SAM V8.0; Serial: 1979

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: 6 GHz WIFI/ IEEE 802.11ax, Antenna MIMO, 160 MHz Bandwidth, U-NII-5, Exp:
Head| Left Tilt, Ch. 15, 136.1 Mbps**

Area Scan (119.0 x 204.0): Measurement grid: dx=8.5 mm, dy=8.5 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=3.4 mm, dy=3.4 mm, dz=1.4 mm; Graded Ratio: 1.4


Reference Value = 0.37 W/kg; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.36 W/kg

APD(4cm²) = 2.49 W/m²

Smallest distance from peaks to all points 3 dB below is 4.1 mm

Ratio of SAR at M2 to SAR at M1 = 50.3 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0542M

Communication System: UID:10755 - AAC, WLAN; MAIA: Y; Frequency: 6025.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 6025.000 MHz; cond = 5.53 S/m; perm = 35.9; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/08/2025; Ambient Temp: 24.4°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN7570; ConvF:(5.35,5.65,5.29); Calibrated: 2025-02-10

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4ip Sn1638; Calibrated: 2025-02-07

Phantom: Twin-SAM V8.0; Serial: 1979

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: 6 GHz WIFI/ IEEE 802.11ax, Antenna MIMO, 160 MHz Bandwidth, U-NII-5, Exp:
Body-worn/Hotspot| Back Side, Ch. 15, 136.1 Mbps**

Area Scan (119.0 x 204.0): Measurement grid: dx=8.5 mm, dy=8.5 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=3.4 mm, dy=3.4 mm, dz=1.4 mm; Graded Ratio: 1.4


Reference Value = -0.01 W/kg; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.65 W/kg

SAR(1 g) = 0.355 W/kg; APD(4cm²) = 2.18 W/m²

Smallest distance from peaks to all points 3 dB below is 5.5 mm

Ratio of SAR at M2 to SAR at M1 = 55.5 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0542M

Communication System: UID:10755 - AAC, WLAN; MAIA: Y; Frequency: 6025.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 6025.000 MHz; cond = 5.53 S/m; perm = 35.9; density = 1000 kg/m³

Phantom Section: Flat; Space: 0.00 mm

Test Date: 09/08/2025; Ambient Temp: 24.4°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN7570; ConvF:(5.35,5.65,5.29); Calibrated: 2025-02-10

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4ip Sn1638; Calibrated: 2025-02-07

Phantom: Twin-SAM V8.0; Serial: 1979

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: 6 GHz WIFI/ IEEE 802.11ax, Antenna G, 160 MHz Bandwidth, U-NII-5, Exp:
Phablet| Left Edge, Ch. 15, 68.1 Mbps**

Area Scan (40.0 x 204.0): Measurement grid: dx=5.0 mm, dy=8.5 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=3.4 mm, dy=3.4 mm, dz=1.4 mm; Graded Ratio: 1.2


Reference Value = 0.04 W/kg; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 13.1 W/kg

SAR(10 g) = 0.543 W/kg; APD(4cm²) = 12.8 W/m²

Smallest distance from peaks to all points 3 dB below is 4.1 mm

Ratio of SAR at M2 to SAR at M1 = 58.5 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0520M

Communication System: UID:10032 - CAA, Bluetooth; MAIA: Y; Frequency: 2441.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 2441.000 MHz; cond = 1.77 S/m; perm = 39.0; density = 1000 kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 09/18/2025; Ambient Temp: 21.7°C; Tissue Temp: 20.6°C

Probe: EX3DV4 - SN7661; ConvF:(7.02,7.48,7.47); Calibrated: 2025-06-11

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1558; Calibrated: 2025-06-05

Phantom: Twin-SAM V8.0; Serial: 2065

Measurement SW: DASY Module SAR V16.4.0.5005

Mode: 2.4 GHz Bluetooth, Antenna G, Exp: Head| Right Cheek, Ch. 39, 1 Mbps

Area Scan (120.0 x 200.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 0.58 W/kg; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 1.58 W/kg

SAR(1 g) = 0.716 W/kg

Smallest distance from peaks to all points 3 dB below is 6.9 mm

Ratio of SAR at M2 to SAR at M1 = 78.4 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0520M

Communication System: UID:10032 - CAA, Bluetooth; MAIA: Y; Frequency: 2402.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 2402.000 MHz; cond = 1.74 S/m; perm = 39.0; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 09/18/2025; Ambient Temp: 21.7°C; Tissue Temp: 20.6°C

Probe: EX3DV4 - SN7661; ConvF:(7.02,7.48,7.47); Calibrated: 2025-06-11

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1558; Calibrated: 2025-06-05

Phantom: Twin-SAM V8.0; Serial: 2065

Measurement SW: DASY Module SAR V16.4.0.5005

Mode: 2.4 GHz Bluetooth, Antenna G, Exp: Body-worn/Hotspot| Back Side, Ch. 0, 1 Mbps

Area Scan (120.0 x 200.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 1.07 W/kg; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 2.10 W/kg

SAR(1 g) = 1.05 W/kg

Smallest distance from peaks to all points 3 dB below is 9.0 mm

Ratio of SAR at M2 to SAR at M1 = 82.0 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0520M

Communication System: UID:10032 - CAA, Bluetooth; MAIA: Y; Frequency: 2441.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 2441.000 MHz; cond = 1.77 S/m; perm = 39.0; density = 1000 kg/m³

Phantom Section: Flat; Space: 0.00 mm

Test Date: 09/18/2025; Ambient Temp: 21.7°C; Tissue Temp: 20.6°C

Probe: EX3DV4 - SN7661; ConvF:(7.02,7.48,7.47); Calibrated: 2025-06-11

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1558; Calibrated: 2025-06-05

Phantom: Twin-SAM V8.0; Serial: 2065

Measurement SW: DASY Module SAR V16.4.0.5005

Mode: 2.4 GHz Bluetooth, Antenna MIMO, Exp: Phablet| Left Edge, Ch. 39, 1 Mbps

Area Scan (40.0 x 200.0): Measurement grid: dx=5.0 mm, dy=10.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 1.68 W/kg; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 4.68 W/kg

SAR(10 g) = 0.527 W/kg

Smallest distance from peaks to all points 3 dB below is 5.9 mm

Ratio of SAR at M2 to SAR at M1 = 67.9 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0829M

Communication System: UID:0 - -, CW; MAIA: Y; Frequency: 7987.200 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 7987.200 MHz; cond = 7.91 S/m; perm = 31.9; density = 1000 kg/m³

Phantom Section: RightHead; Space: 0.00 mm

Test Date: 10/08/2025; Ambient Temp: 23.7°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7570; ConvF:(5.71,6.04,5.65); Calibrated: 2025-02-10

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4ip Sn1638; Calibrated: 2025-02-07

Phantom: Twin-SAM V8.0; Serial: 1979

Measurement SW: DASY Module SAR V16.4.0.5005

Mode: UWB, Antenna H, Exp: Head| Right Tilt, Ch. 9

Area Scan (142.5 x 210.0): Measurement grid: dx=7.5 mm, dy=7.5 mm

Zoom Scan (39.0 x 39.0 x 22.9): Measurement grid: dx=3.0 mm, dy=3.0 mm, dz=1.4 mm; Graded Ratio: 1.4


Reference Value = -0.01 W/kg; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.414 W/kg

SAR(1 g) = 0.003 W/kg

Smallest distance from peaks to all points 3 dB below is 0.9 mm

Ratio of SAR at M2 to SAR at M1 = N/A %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0829M

Communication System: UID:0 - -, CW; MAIA: Y; Frequency: 7987.200 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 7987.200 MHz; cond = 7.91 S/m; perm = 31.9; density = 1000 kg/m³

Phantom Section: LeftHead; Space: 0.00 mm

Test Date: 10/08/2025; Ambient Temp: 23.7°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7570; ConvF:(5.71,6.04,5.65); Calibrated: 2025-02-10

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4ip Sn1638; Calibrated: 2025-02-07

Phantom: Twin-SAM V8.0; Serial: 1979

Measurement SW: DASY Module SAR V16.4.0.5005

Mode: UWB, Antenna H, Exp: Head| Left Tilt, Ch. 9

Area Scan (135.0 x 210.0): Measurement grid: dx=7.5 mm, dy=7.5 mm

Zoom Scan (42.0 x 39.0 x 22.9): Measurement grid: dx=3.0 mm, dy=3.0 mm, dz=1.4 mm; Graded Ratio: 1.4


Reference Value = -0.01 W/kg; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.740 W/kg

APD(4cm²) = 0.023 W/m²

Smallest distance from peaks to all points 3 dB below is 0.9 mm

Ratio of SAR at M2 to SAR at M1 = 41.9 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0829M

Communication System: UID:0 - -, CW; MAIA: Y; Frequency: 6489.600 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 6489.600 MHz; cond = 6.07 S/m; perm = 34.4; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 10/08/2025; Ambient Temp: 23.7°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7570; ConvF:(5.35,5.65,5.29); Calibrated: 2025-02-10

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4ip Sn1638; Calibrated: 2025-02-07

Phantom: Twin-SAM V8.0; Serial: 1979

Measurement SW: DASY Module SAR V16.4.0.5005

Mode: UWB, Antenna H, Exp: Body-worn| Back Side, Ch. 5

Area Scan (144.5 x 204.0): Measurement grid: dx=8.5 mm, dy=8.5 mm

Zoom Scan (30.6 x 40.8 x 22.9): Measurement grid: dx=3.4 mm, dy=3.4 mm, dz=1.4 mm; Graded Ratio: 1.4


Reference Value = -0.01 W/kg; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.013 W/kg

SAR(1 g) = 0.002 W/kg; APD(4cm²) = 0.022 W/m²

Smallest distance from peaks to all points 3 dB below is 2.0 mm

Ratio of SAR at M2 to SAR at M1 = 36.9 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0829M

Communication System: UID:0 - -, CW; MAIA: Y; Frequency: 7987.200 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 7987.200 MHz; cond = 7.91 S/m; perm = 31.9; density = 1000 kg/m³

Phantom Section: Flat; Space: 0.00 mm

Test Date: 10/08/2025; Ambient Temp: 23.7°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7570; ConvF:(5.71,6.04,5.65); Calibrated: 2025-02-10

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4ip Sn1638; Calibrated: 2025-02-07

Phantom: Twin-SAM V8.0; Serial: 1979

Measurement SW: DASY Module SAR V16.4.0.5005

Mode: UWB, Antenna H, Exp: Phablet| Right Edge, Ch. 9

Area Scan (40.0 x 195.0): Measurement grid: dx=5.0 mm, dy=7.5 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=3.0 mm, dy=3.0 mm, dz=1.4 mm; Graded Ratio: 1.4


Reference Value = 0.00 W/kg; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.023 W/kg

SAR(10 g) = 0.002 W/kg; APD(4cm²) = 0.046 W/m²

Smallest distance from peaks to all points 3 dB below is 1.7 mm

Ratio of SAR at M2 to SAR at M1 = 64.1 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0735M

Communication System: UID:0 - -, CW; MAIA: Y; Frequency: 13.600 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 13.600$ MHz; $\text{cond} = 0.728$ S/m; $\text{perm} = 53.6$; $\text{density} = 1000$ kg/m³

Phantom Section: Flat; Space: 0.00 mm

Test Date: 08/27/2025; Ambient Temp: 21.6°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7539; ConvF:(18.32,18.43,20.5); Calibrated: 2024-11-11

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1415; Calibrated: 2025-03-11

Phantom: ELI V8.0; Serial: 2077

Measurement SW: DASY Module SAR V16.4.0.5005

Mode: NFC, Antenna NFC, Exp: Phablet| Back Side

Area Scan (120.0 x 210.0): Measurement grid: $dx=15.0$ mm, $dy=15.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $dx=6.0$ mm, $dy=6.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5


Reference Value = 0.02 W/kg; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.069 W/kg

SAR(10 g) = 0.007 W/kg

Smallest distance from peaks to all points 3 dB below is 6.3 mm

Ratio of SAR at M2 to SAR at M1 = 58.9 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0503M

Communication System: UID:0 - -, CW; MAIA: Y; Frequency: 1643.500 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 1643.500 MHz; cond = 1.26 S/m; perm = 38.3; density = 1000 kg/m³

Phantom Section: Flat; Space: 5.00 mm

Test Date: 10/06/2025; Ambient Temp: 20.3°C; Tissue Temp: 24.1°C

Probe: EX3DV4 - SN7539; ConvF:(7.83,7.57,8.43); Calibrated: 2024-11-11

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1415; Calibrated: 2025-03-11

Phantom: Twin-SAM V5.0; Serial: 1757

Measurement SW: DASY Module SAR V16.4.0.5005

**Mode: NTN Band 255, Antenna F, Exp: Body-worn| Back Side, Ch. 261674, 200 kHz
Bandwidth, QPSK, 1 Tone, 6 Tone Start**

Area Scan (120.0 x 210.0): Measurement grid: dx=15.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5


Reference Value = 1.13 W/kg; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 2.07 W/kg

SAR(1 g) = 1.18 W/kg

Smallest distance from peaks to all points 3 dB below is 9.6 mm

Ratio of SAR at M2 to SAR at M1 = 83.5 %



ELEMENT

DUT: A3LSMS948U; Type: Portable Handset; Serial: 0503M

Communication System: UID:0 - -, CW; MAIA: Y; Frequency: 1643.500 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 1643.500 MHz; cond = 1.26 S/m; perm = 38.3; density = 1000 kg/m³

Phantom Section: Flat; Space: 0.00 mm

Test Date: 10/06/2025; Ambient Temp: 20.3°C; Tissue Temp: 24.1°C

Probe: EX3DV4 - SN7539; ConvF:(7.83,7.57,8.43); Calibrated: 2024-11-11

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1415; Calibrated: 2025-03-11

Phantom: Twin-SAM V5.0; Serial: 1757

Measurement SW: DASY Module SAR V16.4.0.5005

Mode: NTN Band 255, Antenna F, Exp: Phablet| Top Edge, Ch. 261674, 200 kHz Bandwidth, QPSK, 1 Tone, 6 Tone Start

Area Scan (40.0 x 120.0): Measurement grid: dx=5.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.4


Reference Value = 6.77 W/kg; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 28.2 W/kg

SAR(10 g) = 3.19 W/kg

Smallest distance from peaks to all points 3 dB below is 5.2 mm

Ratio of SAR at M2 to SAR at M1 = 66.7 %



Date: 2025-10-01

Mode: 6GHz WIFI/ IEEE 802.11ax, Antenna G, 160 MHz Bandwidth, U-NII-5, Exp: Left Edge, Ch. 15, 68.1 Mbps

Device Under Test Properties

DUT	Serial Number	DUT Type
A3LSMS948U	0550M	Portable Handset

Exposure Conditions

Phantom Section	Position	Test Distance [mm]	Channel	Group, UID	Frequency [MHz]
5G	EDGE LEFT	2.00	15	10755	6025.0

Hardware Setup

Probe, Calibration Date	DAE, Calibration Date
EUmmWV3 - SN9389, 2025-01-08	DAE4ip - SN1639, 2025-02-05

Software Setup


Software	Software Version
cDASY6 Module mmWave	3.2.0.1840

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	100.0 x 100.0
Grid Steps [lambda]	0.05 x 0.05
Sensor Surface [mm]	2.0

Measurement Results

Scan Type	5G Scan
Avg. Area [cm²]	4.00
pS _{tot} avg [W/m²]	4.57
pS _n avg [W/m²]	3.53
E _{peak} [V/m]	80.3
Power Drift [dB]	-0.04



Date: 2025-10-11

UWB Ch. 5

Device Under Test Properties

DUT	Serial Number	DUT Type
A3LSMS948U	0829M	Portable Handset

Exposure Conditions

Phantom Section	Position	Test Distance [mm]	Channel	Group, UID	Frequency [MHz]
5G	EDGE LEFT	2.00	6489600	0	6489.6

Hardware Setup

Probe, Calibration Date	DAE, Calibration Date
EUmmWV3 – SN9389, 2025-01-08	DAE4ip – SN1639, 2025-02-05

Software Setup

Software	Software Version
cDASY6 Module mmWave	3.2.0.1840

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	100.0 x 100.0
Grid Steps [lambda]	0.067 x 0.067
Sensor Surface [mm]	2.0

Measurement Results

Scan Type	5G Scan
Avg. Area [cm²]	4.00
pS _{tot} avg [W/m²]	0.202
pS _n avg [W/m²]	0.194
E _{peak} [V/m]	10.6
Power Drift [dB]	-0.14

