

APPENDIX A: RF EXPOSURE TEST PLOTS

Plot A-1 Verification Test Data

cDASY6 Module WPT Measurement Report

Device under test

Info:
85kHz Verification

Serial number:
1011

Scenario:
10-2-2025

Tool info

DASY software version:
cDASY6 Module WPT 2.8.0.5184

Probe model, serial no. and configuration date:
MAGPy-8H3D+E3Dv2, WP000210, 2025/06/13

Software version:
2.8.8, backend: 2.2.36

Scan info

Center location:
x: 30.49 mm, y: -143.81 mm, z: 47.12 mm

Dimensions:
x: 389.0 mm, y: 477.0 mm, z: 36.7 mm

Resolution:
x: 7.33 mm, y: 7.33 mm, z: 7.33 mm

Completed on:
2025/10/02 17:33:25

Measurement results

Maximum H-field [rms]:
MAGNITUDE: 130.24 A/m
x: 7.62 A/m, y: 120.66 A/m, z: 48.44 A/m

Maximum H-field location relative to DUT:
x: 11.00 mm, y: -165.00 mm, z: 8.50 mm


Maximum E-field [rms]:
MAGNITUDE: 192.92 V/m
x: 6.11 V/m, y: 9.77 V/m, z: 192.57 V/m

Maximum E-field location relative to DUT:
x: 88.00 mm, y: 176.00 mm, z: 0.00 m


Distance to -20.0 dB boundary:
59.12 mm

Offset relative to DUT:
x: 0.00 m, y: 0.00 m, z: 1.00 mm

H-field magnitude [rms] at center location



H-field magnitude [rms] at lowest plane



Incident fields and induced fields in the homogeneous phantom at the peak frequency (f = 85.00 kHz, d = 0.750 S/m, tissue density = 1,000 kg/m³)

Distance [mm]	Peak incident fields [rms]		Peak E _{ind} [V/m, rms]			Peak J _{ind} [A/m², rms]		psSAR [mW/kg]		H-field extent		Warnings
	H _{inc} [A/m]	E _{inc} [V/m]	Cube avg.	Local	Line avg.	Surface avg.	1g avg.	10g avg.	-20 dB radius [mm]	Sign	Vector potential	
0.00	196	193	3.21	3.24	3.25	2.26	6.00	4.49	182	2%	89%	36%
2.00	180	177	3.03	3.05	3.06	2.13	5.38	4.07	184	2%	89%	38%

Compliance evaluation (Field values at the peak frequency) (f=85.00 kHz, total field evaluation, coverage evaluation)

Distance [mm]	ICNIRP 2010/2020				ICNIRP 1998				IEEE 2019				FCC				HC Code 6			
	RL [μs]	BR [μs]	RL [μs]	BR [μs]	RL [μs]	BR [μs]	RL [μs]	BR [μs]	RL [μs]	BR [μs]	RL [μs]	BR [μs]	RL [μs]	BR [μs]	RL [μs]	BR [μs]	RL [μs]	BR [μs]	RL [μs]	BR [μs]
0.00	196	193	24.2	4.49	196	193	2.26	4.49	196	193	12.6	4.49	196	193	N/A	6.00	196	193	34.5	6.00
2.00	180	177	22.9	4.07	180	177	2.13	4.07	180	177	11.9	4.07	180	177	N/A	5.38	180	177	32.6	5.38

Coverage factors: $w_{F_{ind, cube avg}} = [7.53, 7.57]$, $w_{F_{ind, local}} = [10.64, 10.69]$, $w_{F_{ind, line avg}} = [3.87, 3.89]$

Compliance evaluation (Exposure ratios) (with multi-frequency enhancement, total field evaluation, coverage evaluation)

Distance [mm]	ICNIRP 2010/2020				ICNIRP 1998				IEEE 2019				FCC				HC Code 6			
	RL [μs]	BR [μs]	RL [μs]	BR [μs]	RL [μs]	BR [μs]	RL [μs]	BR [μs]	RL [μs]	BR [μs]	RL [μs]	BR [μs]	RL [μs]	BR [μs]	RL [μs]	BR [μs]	RL [μs]	BR [μs]	RL [μs]	BR [μs]
0.00	9.35	N/A	5.27	N/A	2.11	N/A	39.3	4.7	13.3	N/A	1.2	N/A	0.71	N/A	0.71	N/A	2.18	3.33	N/A	N/A
2.00	8.55	N/A	4.85	N/A	2.0	N/A	35.9	4.32	12.6	N/A	1.1	N/A	0.67	N/A	0.67	N/A	2.0	3.07	N/A	N/A

Coverage factors: $w_{F_{ind, cube avg}} = [7.53, 7.57]$, $w_{F_{ind, local}} = [10.64, 10.69]$, $w_{F_{ind, line avg}} = [3.87, 3.89]$

Document generated at 2025/10/03 09:58:56, simulation performed at 2025/10/03 08:52:22 using Sim4Life version 8.0.1.15737

1/1

FCC ID: A3LSMS948B		WPT RF EXPOSURE EVALUATION REPORT	Reviewed by: Technical Manager
Test Dates: 10/2/2025	Apparatus/Device: Portable Handset		APPENDIX A: Page 1 of 2

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Plot A-2 Worst Case Test Data

cDASY6 Module WPT Measurement Report

Device under test

Info:
A3LSMS948B

Serial number:
0276M

Scenario:
Ping Signal Backside

Tool info

DASY software version:
cDASY6 Module WPT 2.8.0.5184

Probe model, serial no. and configuration date:
MAGPy-8H3D+E3Dv2, WP000210, 2025/06/13

Software version:
2.8.8, backend: 2.2.36

Scan info

Center location:
x: 12.29 mm, y: -110.45 mm, z: 24.67 mm

Dimensions:
x: 168.7 mm, y: 256.2 mm, z: 36.6 mm

Resolution:
x: 7.33 mm, y: 7.33 mm, z: 7.33 mm

Completed on:
2025/10/02 12:26:46

Measurement results

Maximum H-field [RMS]:

MAGNITUDE: 197.07 A/m

x: 23.82 A/m, y: 8.24 A/m, z: 195.45 A/m

Maximum H-field location relative to DUT:

x: -3.67 mm, y: 3.67 mm, z: 8.50 mm

Maximum E-field [RMS]:

MAGNITUDE: 37.47 V/m

x: 14.34 V/m, y: 15.08 V/m, z: 31.16 V/m

Maximum E-field location relative to DUT:

x: 0.00 m, y: -29.33 mm, z: 0.00 m


Distance to -20.0 dB boundary:

30.24 mm


Offset relative to DUT:

x: 0.00 m, y: 0.00 m, z: 1.00 mm

H-field magnitude [RMS] at center location



H-field magnitude [RMS] at lowest plane



Incident fields and induced fields in the homogeneous phantom at the peak frequency (f = 145.63 kHz, $\sigma = 0.750$ S/m, tissue density = 1,000 kg/m³)

Distance [mm]	Peak incident fields [rms]		Peak E _{ind} [V/m, rms]			Peak J _{ind} [A/m ² , rms]	psSAR [mW/kg]		H-field extent -20 dB radius [mm]	Sign	Vector potential	Warnings Boundary effect
	H _{inc} [A/m]	E _{inc} [V/m]	Cube avg.	Local	Line avg.		Surface avg.	1g avg.				
0.00	470	37.5	1.98	2.04	2.04	1.24	1.41	0.642	35.3	8%	21%	16%
2.00	404	35.8	1.67	1.73	1.73	1.02	0.966	0.444	36.0	8%	21%	16%

Compliance evaluation (Field values at the peak frequency) (f=145.63 kHz, total field evaluation, coverage evaluation)

Distance [mm]	ICNIRP 2010/2020				ICNIRP 1998				IEEE 2019				FCC				HC Code 6			
	RL [rms]	BR [rms]	RL [rms]	BR [rms]	ERL [rms]	DRL [rms]	MPE [rms]	BR [rms]	RL [rms]	BR [rms]	RL [rms]	BR [rms]	RL [rms]	BR [rms]	RL [rms]	BR [rms]	RL [rms]	BR [rms]	RL [rms]	BR [rms]
	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pJ _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR
	[A/m]	[V/m]	[V/m]	[mW/kg]	[A/m]	[V/m]	[A/m ²]	[mW/kg]	[A/m]	[V/m]	[V/m]	[mW/kg]	[A/m]	[V/m]	[V/m]	[mW/kg]	[A/m]	[V/m]	[V/m]	[mW/kg]
0.00	470	37.5	10.6	0.642	470	37.5	1.24	0.642	470	37.5	5.96	0.642	470	37.5	N/A	1.41	470	37.5	15.4	1.41
2.00	404	35.8	8.92	0.444	404	35.8	1.02	0.444	404	35.8	5.06	0.444	404	35.8	N/A	0.966	404	35.8	13.0	0.966

Coverage factors: $w_{E_{ind}, cube, avg} = [5.33, 5.34]$, $w_{E_{ind}, total} = [7.53, 7.54]$, $w_{E_{ind}, line, avg} = [2.93, 2.93]$

Compliance evaluation (Exposure ratios) (with multi-frequency enhancement, total field evaluation, coverage evaluation)

Distance [mm]	ICNIRP 2010/2020				ICNIRP 1998				IEEE 2019				FCC				HC Code 6									
	RL		BR		RL		BR		ERL		DRL		MPE		BR		RL		BR							
	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pJ _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR						
	NS	TH	NS	TH	NS	TH	N/A	N/A	NS	TH	NS	TH	NS	TH	N/A	N/A	NS	TH	NS	TH						
0.00	24.0	14.6	2.19	0.49	0.58	<0.01	98.4	3.22	4.6	<0.01	3.09	1.97	0.30	0.12	0.21	<0.01	290.0	0.67	N/A	<0.01	5.6	98.2	2.19	N/A	0.84	<0.01
2.00	20.7	12.6	2.09	0.47	0.49	<0.01	84.7	3.08	3.78	<0.01	2.66	1.69	0.28	0.11	0.18	<0.01	249.0	0.64	N/A	<0.01	4.82	84.5	2.09	N/A	0.71	<0.01

Coverage factors: $w_{E_{ind}, cube, avg} = [5.33, 5.34]$, $w_{E_{ind}, total} = [7.53, 7.54]$, $w_{E_{ind}, line, avg} = [2.93, 2.93]$

Document generated at 2025/10/02 12:29:40, simulation performed at 2025/10/02 12:29:36 using Sim4Life version 8.0.1.15737

1/1

FCC ID: A3LSMS948B		WPT RF EXPOSURE EVALUATION REPORT	Reviewed by: Technical Manager
Test Dates: 10/2/2025	Apparatus/Device: Portable Handset		APPENDIX A: Page 2 of 2

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.