

APPENDIX B: SAR DIPOLE VERIFICATION PLOTS

ELEMENT

DUT: Dipole 13.000 MHz; Type: CLA-13 - SN1002

Communication System: UID: 0, CW; Frequency: 13.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 13.000 MHz; cond = 0.728 S/m; perm = 53.5; density = 1000 kg/m³
Phantom Section: Flat; Space: 0 mm

Test Date: 08/27/2025; Ambient Temp: 21.6°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7539; ConvF:(18.32,18.43,20.5); Calibrated: 2024-11-11
Sensor-Surface: 1.4mm (All points)
Electronics: DAE4 Sn1415; Calibrated: 2025-03-11
Phantom: ELI V8.0; Serial: 2077
Measurement SW: DASY Module SAR V16.4.0.5005

13.0 MHz System Verification at 30.0 dBm (1000 mW)


Area Scan (40.0 x 90.0): Measurement grid: dx=10.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 0.989 W/kg

SAR(1 g) = 0.511 W/kg; SAR(10 g) = 0.321 W/kg

Deviation (1 g) = -1.73%; Deviation (10 g) = -1.23%



ELEMENT

DUT: Dipole 750.000 MHz; Type: D750V3 - SN1054

Communication System: UID: 0, CW; Frequency: 750.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 750.000 MHz; cond = 0.899 S/m; perm = 40.4; density = 1000 kg/m³

Phantom Section: Flat; Space: 15 mm

Test Date: 09/01/2025; Ambient Temp: 21.7°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7718; ConvF:(9.33,9.31,9.63); Calibrated: 2025-04-08

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1407; Calibrated: 2025-04-07

Phantom: Twin-SAM V8.0; Serial: 2060

Measurement SW: DASY Module SAR V16.4.0.5005

750.0 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (40.0 x 90.0): Measurement grid: dx=10.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 2.58 W/kg

SAR(1 g) = 1.71 W/kg; SAR(10 g) = 1.14 W/kg

Deviation (1 g) = -1.50%; Deviation (10 g) = 1.60%



ELEMENT

DUT: Dipole 750.000 MHz; Type: D750V3 - SN1054

Communication System: UID: 0, CW; Frequency: 750.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 750.000$ MHz; $\text{cond} = 0.883$ S/m; $\text{perm} = 40.9$; $\text{density} = 1000$ kg/m³

Phantom Section: Flat; Space: 15 mm

Test Date: 09/02/2025; Ambient Temp: 22.0°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7488; ConvF:(10.15,9.9,9.87); Calibrated: 2025-03-07

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1415; Calibrated: 2025-03-11

Phantom: Twin-SAM V5.0; Serial: 1757

Measurement SW: DASY Module SAR V16.4.0.5005

750.0 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (40.0 x 90.0): Measurement grid: $dx=10.0$ mm, $dy=15.0$ mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: $dx=6.0$ mm, $dy=6.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 2.41 W/kg

SAR(1 g) = 1.62 W/kg; SAR(10 g) = 1.09 W/kg

Deviation (1 g) = -6.68%; Deviation (10 g) = -2.85%



ELEMENT

DUT: Dipole 750.000 MHz; Type: D750V3 - SN1161

Communication System: UID: 0, CW; Frequency: 750.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 750.000$ MHz; $\text{cond} = 0.866$ S/m; $\text{perm} = 40.7$; $\text{density} = 1000$ kg/m³

Phantom Section: Flat; Space: 15 mm

Test Date: 09/08/2025; Ambient Temp: 21.1°C; Tissue Temp: 20.8°C

Probe: EX3DV4 - SN7718; ConvF:(9.33,9.31,9.63); Calibrated: 2025-04-08

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1407; Calibrated: 2025-04-07

Phantom: Twin-SAM V8.0; Serial: 2060

Measurement SW: DASY Module SAR V16.4.0.5005

750.0 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (40.0 x 90.0): Measurement grid: $dx=10.0$ mm, $dy=15.0$ mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: $dx=6.0$ mm, $dy=6.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 2.42 W/kg

SAR(1 g) = 1.63 W/kg; SAR(10 g) = 1.08 W/kg

Deviation (1 g) = -2.51%; Deviation (10 g) = -0.18%



ELEMENT

DUT: Dipole 750.000 MHz; Type: D750V3 - SN1161

Communication System: UID: 0, CW; Frequency: 750.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 750.000 MHz; cond = 0.876 S/m; perm = 41.1; density = 1000 kg/m³
Phantom Section: Flat; Space: 15 mm

Test Date: 09/10/2025; Ambient Temp: 23.2°C; Tissue Temp: 19.6°C

Probe: EX3DV4 - SN7661; ConvF:(9.54,10.15,10.14); Calibrated: 2025-06-11

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1558; Calibrated: 2025-06-05

Phantom: Twin-SAM V8.0; Serial: 2065

Measurement SW: DASY Module SAR V16.4.0.5005

750.0 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (40.0 x 90.0): Measurement grid: dx=10.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 2.53 W/kg

SAR(1 g) = 1.69 W/kg; SAR(10 g) = 1.13 W/kg

Deviation (1 g) = 1.08%; Deviation (10 g) = 4.44%



ELEMENT

DUT: Dipole 750.000 MHz; Type: D750V3 - SN1054

Communication System: UID: 0, CW; Frequency: 750.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 750.000$ MHz; $\text{cond} = 0.883$ S/m; $\text{perm} = 41.0$; $\text{density} = 1000$ kg/m³

Phantom Section: Flat; Space: 15 mm

Test Date: 09/15/2025; Ambient Temp: 22.7°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7488; ConvF:(10.15,9.9,9.87); Calibrated: 2025-03-07

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1415; Calibrated: 2025-03-11

Phantom: Twin-SAM V5.0; Serial: 1757

Measurement SW: DASY Module SAR V16.4.0.5005

750.0 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (40.0 x 90.0): Measurement grid: $dx=10.0$ mm, $dy=15.0$ mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: $dx=6.0$ mm, $dy=6.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 2.80 W/kg

SAR(1 g) = 1.85 W/kg; SAR(10 g) = 1.23 W/kg

Deviation (1 g) = 6.57%; Deviation (10 g) = 9.63%



ELEMENT

DUT: Dipole 835.000 MHz; Type: D835V2 - SN4d047

Communication System: UID: 0, CW; Frequency: 835.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 835.000 MHz; cond = 0.927 S/m; perm = 40.1; density = 1000 kg/m³

Phantom Section: Flat; Space: 15 mm

Test Date: 09/01/2025; Ambient Temp: 21.7°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN7718; ConvF:(9.17,9.15,9.46); Calibrated: 2025-04-08

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1407; Calibrated: 2025-04-07

Phantom: Twin-SAM V8.0; Serial: 2060

Measurement SW: DASY Module SAR V16.4.0.5005

835.0 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (40.0 x 90.0): Measurement grid: dx=10.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 2.96 W/kg

SAR(1 g) = 2.00 W/kg; SAR(10 g) = 1.31 W/kg

Deviation (1 g) = 5.93%; Deviation (10 g) = 7.55%



ELEMENT

DUT: Dipole 835.000 MHz; Type: D835V2 - SN4d133

Communication System: UID: 0, CW; Frequency: 835.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 835.000$ MHz; $\text{cond} = 0.904$ S/m; $\text{perm} = 40.8$; $\text{density} = 1000$ kg/m³

Phantom Section: Flat; Space: 15 mm

Test Date: 09/10/2025; Ambient Temp: 23.2°C; Tissue Temp: 19.6°C

Probe: EX3DV4 - SN7661; ConvF:(9.28,9.87,9.86); Calibrated: 2025-06-11

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1558; Calibrated: 2025-06-05

Phantom: Twin-SAM V8.0; Serial: 2065

Measurement SW: DASY Module SAR V16.4.0.5005

835.0 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (40.0 x 90.0): Measurement grid: $dx=10.0$ mm, $dy=15.0$ mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: $dx=6.0$ mm, $dy=6.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 3.01 W/kg

SAR(1 g) = 1.93 W/kg; SAR(10 g) = 1.28 W/kg

Deviation (1 g) = -2.92%; Deviation (10 g) = -1.39%



ELEMENT

DUT: Dipole 835.000 MHz; Type: D835V2 - SN4d133

Communication System: UID: 0, CW; Frequency: 835.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 835.000 MHz; cond = 0.866 S/m; perm = 42.6; density = 1000 kg/m³
Phantom Section: Flat; Space: 15 mm

Test Date: 09/15/2025; Ambient Temp: 20.1°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7659; ConvF:(9.99,9.58,9.71); Calibrated: 2025-04-07
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1272; Calibrated: 2025-04-10
Phantom: Twin-SAM V8.0; Serial: 1966
Measurement SW: DASY Module SAR V16.4.0.5005

835.0 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (40.0 x 90.0): Measurement grid: dx=10.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 2.94 W/kg

SAR(1 g) = 1.96 W/kg; SAR(10 g) = 1.32 W/kg

Deviation (1 g) = -1.41%; Deviation (10 g) = 1.69%



ELEMENT

DUT: Dipole 835.000 MHz; Type: D835V2 - SN4d133

Communication System: UID: 0, CW; Frequency: 835.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

$f = 835.000$ MHz; $\text{cond} = 0.909$ S/m; $\text{perm} = 40.8$; $\text{density} = 1000$ kg/m³

Phantom Section: Flat; Space: 15 mm

Test Date: 09/15/2025; Ambient Temp: 22.7°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7488; ConvF:(9.92,9.67,9.65); Calibrated: 2025-03-07

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1415; Calibrated: 2025-03-11

Phantom: Twin-SAM V5.0; Serial: 1757

Measurement SW: DASY Module SAR V16.4.0.5005

835.0 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (40.0 x 90.0): Measurement grid: $dx=10.0$ mm, $dy=15.0$ mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: $dx=6.0$ mm, $dy=6.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 3.08 W/kg

SAR(1 g) = 2.07 W/kg; SAR(10 g) = 1.37 W/kg

Deviation (1 g) = 4.12%; Deviation (10 g) = 5.55%



ELEMENT

DUT: Dipole 1640.000 MHz; Type: D1640V2 - SN321

Communication System: UID: 0, CW; Frequency: 1640.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 1640.000 MHz; cond = 1.26 S/m; perm = 38.3; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 10/06/2025; Ambient Temp: 20.3°C; Tissue Temp: 24.1°C

Probe: EX3DV4 - SN7539; ConvF:(7.83,7.57,8.43); Calibrated: 2024-11-11
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1415; Calibrated: 2025-03-11
Phantom: Twin-SAM V5.0; Serial: 1757
Measurement SW: DASY Module SAR V16.4.0.5005

1640.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 90.0): Measurement grid: dx=10.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 5.89 W/kg

SAR(1 g) = 3.38 W/kg; SAR(10 g) = 1.86 W/kg

Deviation (1 g) = -2.03%; Deviation (10 g) = 0.54%



ELEMENT

DUT: Dipole 1750.000 MHz; Type: D1750V2 - SN1150

Communication System: UID: 0, CW; Frequency: 1750.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 1750.000 MHz; cond = 1.34 S/m; perm = 40.9; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/01/2025; Ambient Temp: 20.3°C; Tissue Temp: 19.2°C

Probe: EX3DV4 - SN7713; ConvF:(8.88,8.27,8.04); Calibrated: 2025-01-07
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1530; Calibrated: 2025-01-13
Phantom: Twin-SAM V8.0; Serial: 2064
Measurement SW: DASY Module SAR V16.4.0.5005

1750.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 90.0): Measurement grid: dx=10.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 7.06 W/kg

SAR(1 g) = 3.93 W/kg; SAR(10 g) = 2.11 W/kg

Deviation (1 g) = 7.97%; Deviation (10 g) = 8.76%



ELEMENT

DUT: Dipole 1750.000 MHz; Type: D1750V2 - SN1148

Communication System: UID: 0, CW; Frequency: 1750.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 1750.000 MHz; cond = 1.35 S/m; perm = 40.1; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/04/2025; Ambient Temp: 22.7°C; Tissue Temp: 20.9°C

Probe: EX3DV4 - SN7713; ConvF:(8.88,8.27,8.04); Calibrated: 2025-01-07
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1530; Calibrated: 2025-01-13
Phantom: Twin-SAM V8.0; Serial: 2064
Measurement SW: DASY Module SAR V16.4.0.5005

1750.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 90.0): Measurement grid: dx=10.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 7.15 W/kg

SAR(1 g) = 3.98 W/kg; SAR(10 g) = 2.13 W/kg

Deviation (1 g) = 7.86%; Deviation (10 g) = 8.67%



ELEMENT

DUT: Dipole 1750.000 MHz; Type: D1750V2 - SN1150

Communication System: UID: 0, CW; Frequency: 1750.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 1750.000 MHz; cond = 1.34 S/m; perm = 38.8; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/08/2025; Ambient Temp: 21.3°C; Tissue Temp: 20.4°C

Probe: EX3DV4 - SN7410; ConvF:(7.81,7.7,8.15); Calibrated: 2024-12-05
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1213; Calibrated: 2024-12-04
Phantom: Twin-SAM V8.0; Serial: 1978
Measurement SW: DASY Module SAR V16.4.0.5005

1750.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 90.0): Measurement grid: dx=10.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 6.66 W/kg

SAR(1 g) = 3.67 W/kg; SAR(10 g) = 1.96 W/kg

Deviation (1 g) = 0.82%; Deviation (10 g) = 1.03%



ELEMENT

DUT: Dipole 1750.000 MHz; Type: D1750V2 - SN1150

Communication System: UID: 0, CW; Frequency: 1750.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 1750.000 MHz; cond = 1.31 S/m; perm = 41.3; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/12/2025; Ambient Temp: 20.2°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN7659; ConvF:(8.68,8.33,8.44); Calibrated: 2025-04-07
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1272; Calibrated: 2025-04-10
Phantom: Twin-SAM V8.0; Serial: 1966
Measurement SW: DASY Module SAR V16.4.0.5005

1750.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 90.0): Measurement grid: dx=10.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 6.40 W/kg

SAR(1 g) = 3.69 W/kg; SAR(10 g) = 2.02 W/kg

Deviation (1 g) = 1.37%; Deviation (10 g) = 4.12%



ELEMENT

DUT: Dipole 1900.000 MHz; Type: D1900V2 - SN5d148

Communication System: UID: 0, CW; Frequency: 1900.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 1900.000 MHz; cond = 1.43 S/m; perm = 38.7; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/04/2025; Ambient Temp: 21.0°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7410; ConvF:(7.58,7.48,7.91); Calibrated: 2024-12-05
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1213; Calibrated: 2024-12-04
Phantom: Twin-SAM V8.0; Serial: 1978
Measurement SW: DASY Module SAR V16.4.0.5005

1900.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 90.0): Measurement grid: dx=10.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 7.69 W/kg

SAR(1 g) = 4.21 W/kg; SAR(10 g) = 2.19 W/kg

Deviation (1 g) = 6.31%; Deviation (10 g) = 4.78%



ELEMENT

DUT: Dipole 1900.000 MHz; Type: D1900V2 - SN5d080

Communication System: UID: 0, CW; Frequency: 1900.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 1900.000 MHz; cond = 1.44 S/m; perm = 39.9; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/04/2025; Ambient Temp: 22.7°C; Tissue Temp: 20.9°C

Probe: EX3DV4 - SN7713; ConvF:(8.56,7.97,7.75); Calibrated: 2025-01-07
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1530; Calibrated: 2025-01-13
Phantom: Twin-SAM V8.0; Serial: 2064
Measurement SW: DASY Module SAR V16.4.0.5005

1900.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 90.0): Measurement grid: dx=10.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 7.64 W/kg

SAR(1 g) = 4.23 W/kg; SAR(10 g) = 2.26 W/kg

Deviation (1 g) = 5.22%; Deviation (10 g) = 6.60%



ELEMENT

DUT: Dipole 1900.000 MHz; Type: D1900V2 - SN5d148

Communication System: UID: 0, CW; Frequency: 1900.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 1900.000 MHz; cond = 1.42 S/m; perm = 38.6; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/08/2025; Ambient Temp: 21.3°C; Tissue Temp: 20.4°C

Probe: EX3DV4 - SN7410; ConvF:(7.58,7.48,7.91); Calibrated: 2024-12-05
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1213; Calibrated: 2024-12-04
Phantom: Twin-SAM V8.0; Serial: 1978
Measurement SW: DASY Module SAR V16.4.0.5005

1900.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 90.0): Measurement grid: dx=10.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 7.87 W/kg

SAR(1 g) = 4.25 W/kg; SAR(10 g) = 2.20 W/kg

Deviation (1 g) = 7.32%; Deviation (10 g) = 5.26%



ELEMENT

DUT: Dipole 1900.000 MHz; Type: D1900V2 - SN5d148

Communication System: UID: 0, CW; Frequency: 1900.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 1900.000 MHz; cond = 1.39 S/m; perm = 41.1; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/12/2025; Ambient Temp: 20.2°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN7659; ConvF:(8.38,8.04,8.14); Calibrated: 2025-04-07
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1272; Calibrated: 2025-04-10
Phantom: Twin-SAM V8.0; Serial: 1966
Measurement SW: DASY Module SAR V16.4.0.5005

1900.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 90.0): Measurement grid: dx=10.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 7.77 W/kg

SAR(1 g) = 4.33 W/kg; SAR(10 g) = 2.28 W/kg

Deviation (1 g) = 9.34%; Deviation (10 g) = 9.09%



ELEMENT

DUT: Dipole 1900.000 MHz; Type: D1900V2 - SN5d148

Communication System: UID: 0, CW; Frequency: 1900.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 1900.000 MHz; cond = 1.40 S/m; perm = 40.4; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/17/2025; Ambient Temp: 21.3°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN7659; ConvF:(8.38,8.04,8.14); Calibrated: 2025-04-07
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1272; Calibrated: 2025-04-10
Phantom: Twin-SAM V8.0; Serial: 1966
Measurement SW: DASY Module SAR V16.4.0.5005

1900.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 90.0): Measurement grid: dx=10.0 mm, dy=15.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=6.0 mm, dy=6.0 mm, dz=1.5 mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 7.97 W/kg

SAR(1 g) = 4.33 W/kg; SAR(10 g) = 2.28 W/kg

Deviation (1 g) = 9.34%; Deviation (10 g) = 9.09%



ELEMENT

DUT: Dipole 2300.000 MHz; Type: D2300V2 - SN1073

Communication System: UID: 0, CW; Frequency: 2300.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 2300.000$ MHz; $\text{cond} = 1.70$ S/m; $\text{perm} = 38.3$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/01/2025; Ambient Temp: 24.4°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN3914; ConvF:(7.44,6.97,6.99); Calibrated: 2025-05-13
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4ip Sn1639; Calibrated: 2025-02-05
Phantom: Twin-SAM V8.0; Serial: 2053
Measurement SW: DASY Module SAR V16.4.0.5005

2300.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 10.3 W/kg

SAR(1 g) = 5.20 W/kg; SAR(10 g) = 2.50 W/kg

Deviation (1 g) = 7.00%; Deviation (10 g) = 6.38%



ELEMENT

DUT: Dipole 2300.000 MHz; Type: D2300V2 - SN1117

Communication System: UID: 0, CW; Frequency: 2300.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 2300.000$ MHz; $\text{cond} = 1.69$ S/m; $\text{perm} = 41.2$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/11/2025; Ambient Temp: 20.7°C; Tissue Temp: 20.2°C

Probe: EX3DV4 - SN7640; ConvF:(8.11,7.54,8.1); Calibrated: 2025-02-12
Sensor-Surface: 1.4mm (All points)
Electronics: DAE4 Sn1645; Calibrated: 2025-02-11
Phantom: Twin-SAM V8.0; Serial: 1934
Measurement SW: DASY Module SAR V16.4.0.5005

2300.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 10.1 W/kg

SAR(1 g) = 4.95 W/kg; SAR(10 g) = 2.38 W/kg

Deviation (1 g) = 0.20%; Deviation (10 g) = -0.42%



ELEMENT

DUT: Dipole 2300.000 MHz; Type: D2300V2 - SN1008

Communication System: UID: 0, CW; Frequency: 2300.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 2300.000$ MHz; $\text{cond} = 1.73$ S/m; $\text{perm} = 41.0$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/18/2025; Ambient Temp: 20.5°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7640; ConvF:(8.11,7.54,8.1); Calibrated: 2025-02-12
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1645; Calibrated: 2025-02-11
Phantom: Twin-SAM V8.0; Serial: 1934
Measurement SW: DASY Module SAR V16.4.0.5005

2300.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 10.1 W/kg

SAR(1 g) = 5.12 W/kg; SAR(10 g) = 2.47 W/kg

Deviation (1 g) = 3.64%; Deviation (10 g) = 4.22%



ELEMENT

DUT: Dipole 2300.000 MHz; Type: D2300V2 - SN1008

Communication System: UID: 0, CW; Frequency: 2300.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 2300.000 MHz; cond = 1.72 S/m; perm = 39.8; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/25/2025; Ambient Temp: 20.7°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7640; ConvF:(8.11,7.54,8.1); Calibrated: 2025-02-12
Sensor-Surface: 1.4mm (All points)
Electronics: DAE4 Sn1645; Calibrated: 2025-02-11
Phantom: Twin-SAM V8.0; Serial: 1934
Measurement SW: DASY Module SAR V16.4.0.5005

2300.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.5 mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 10.4 W/kg

SAR(1 g) = 5.22 W/kg; SAR(10 g) = 2.51 W/kg

Deviation (1 g) = 5.67%; Deviation (10 g) = 5.91%



ELEMENT

DUT: Dipole 2450.000 MHz; Type: D2450V2 - SN882

Communication System: UID: 0, CW; Frequency: 2450.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 2450.000$ MHz; $\text{cond} = 1.81$ S/m; $\text{perm} = 41.1$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/11/2025; Ambient Temp: 20.7°C; Tissue Temp: 20.2°C

Probe: EX3DV4 - SN7640; ConvF:(8.17,7.59,8.15); Calibrated: 2025-02-12
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1645; Calibrated: 2025-02-11
Phantom: Twin-SAM V8.0; Serial: 1934
Measurement SW: DASY Module SAR V16.4.0.5005

2450.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 11.0 W/kg

SAR(1 g) = 5.49 W/kg; SAR(10 g) = 2.57 W/kg

Deviation (1 g) = 2.23%; Deviation (10 g) = 2.39%



ELEMENT

DUT: Dipole 2450.000 MHz; Type: D2450V2 - SN882

Communication System: UID: 0, CW; Frequency: 2450.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 2450.000$ MHz; $\text{cond} = 1.81$ S/m; $\text{perm} = 40.7$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/15/2025; Ambient Temp: 20.5°C; Tissue Temp: 20.3°C

Probe: EX3DV4 - SN7640; ConvF:(8.17,7.59,8.15); Calibrated: 2025-02-12
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1645; Calibrated: 2025-02-11
Phantom: Twin-SAM V8.0; Serial: 1934
Measurement SW: DASY Module SAR V16.4.0.5005

2450.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 11.0 W/kg

SAR(1 g) = 5.51 W/kg; SAR(10 g) = 2.59 W/kg

Deviation (1 g) = 2.61%; Deviation (10 g) = 3.19%



ELEMENT

DUT: Dipole 2450.000 MHz; Type: D2450V2 - SN882

Communication System: UID: 0, CW; Frequency: 2450.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 2450.000$ MHz; $\text{cond} = 1.85$ S/m; $\text{perm} = 40.7$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/15/2025; Ambient Temp: 22.1°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7565; ConvF:(7.88,6.52,6.33); Calibrated: 2025-01-09
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1466; Calibrated: 2025-01-14
Phantom: Twin-SAM V5.0; Serial: 1715
Measurement SW: DASY Module SAR V16.4.0.5005

2450.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 11.7 W/kg

SAR(1 g) = 5.66 W/kg; SAR(10 g) = 2.64 W/kg

Deviation (1 g) = 5.40%; Deviation (10 g) = 5.18%



ELEMENT

DUT: Dipole 2450.000 MHz; Type: D2450V2 - SN797

Communication System: UID: 0, CW; Frequency: 2450.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 2450.000 MHz; cond = 1.77 S/m; perm = 38.9; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/18/2025; Ambient Temp: 21.7°C; Tissue Temp: 20.6°C

Probe: EX3DV4 - SN7661; ConvF:(7.02,7.48,7.47); Calibrated: 2025-06-11
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1558; Calibrated: 2025-06-05
Phantom: Twin-SAM V8.0; Serial: 2065
Measurement SW: DASY Module SAR V16.4.0.5005

2450.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.5 mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 10.1 W/kg

SAR(1 g) = 4.99 W/kg; SAR(10 g) = 2.36 W/kg

Deviation (1 g) = -4.04%; Deviation (10 g) = -3.28%



ELEMENT

DUT: Dipole 2450.000 MHz; Type: D2450V2 - SN882

Communication System: UID: 0, CW; Frequency: 2450.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 2450.000$ MHz; $\text{cond} = 1.85$ S/m; $\text{perm} = 40.8$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/18/2025; Ambient Temp: 20.5°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7640; ConvF:(8.17,7.59,8.15); Calibrated: 2025-02-12
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1645; Calibrated: 2025-02-11
Phantom: Twin-SAM V8.0; Serial: 1934
Measurement SW: DASY Module SAR V16.4.0.5005

2450.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 11.5 W/kg

SAR(1 g) = 5.69 W/kg; SAR(10 g) = 2.66 W/kg

Deviation (1 g) = 5.96%; Deviation (10 g) = 5.98%



ELEMENT

DUT: Dipole 2450.000 MHz; Type: D2450V2 - SN945

Communication System: UID: 0, CW; Frequency: 2450.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 2450.000$ MHz; $\text{cond} = 1.83$ S/m; $\text{perm} = 39.4$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/18/2025; Ambient Temp: 22.2°C; Tissue Temp: 21.5°C

Probe: EX3DV4 - SN7565; ConvF:(7.88,6.52,6.33); Calibrated: 2025-01-09
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1466; Calibrated: 2025-01-14
Phantom: Twin-SAM V5.0; Serial: 1715
Measurement SW: DASY Module SAR V16.4.0.5005

2450.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 31.2): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 9.82 W/kg

SAR(1 g) = 4.83 W/kg; SAR(10 g) = 2.29 W/kg

Deviation (1 g) = -8.70%; Deviation (10 g) = -8.40%



ELEMENT

DUT: Dipole 2600.000 MHz; Type: D2600V2 - SN1009

Communication System: UID: 0, CW; Frequency: 2600.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 2600.000 MHz; cond = 1.93 S/m; perm = 40.8; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/11/2025; Ambient Temp: 20.7°C; Tissue Temp: 20.2°C

Probe: EX3DV4 - SN7640; ConvF:(7.86,7.3,7.85); Calibrated: 2025-02-12
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1645; Calibrated: 2025-02-11
Phantom: Twin-SAM V8.0; Serial: 1934
Measurement SW: DASY Module SAR V16.4.0.5005

2600.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.5 mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 12.4 W/kg

SAR(1 g) = 5.91 W/kg; SAR(10 g) = 2.66 W/kg

Deviation (1 g) = 4.60%; Deviation (10 g) = 4.72%



ELEMENT

DUT: Dipole 2600.000 MHz; Type: D2600V2 - SN1064

Communication System: UID: 0, CW; Frequency: 2600.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 2600.000$ MHz; $\text{cond} = 1.91$ S/m; $\text{perm} = 38.6$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/15/2025; Ambient Temp: 23.1°C; Tissue Temp: 21.0°C

Probe: EX3DV4 - SN7661; ConvF:(7.17,7.63,7.62); Calibrated: 2025-06-11
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1558; Calibrated: 2025-06-05
Phantom: Twin-SAM V8.0; Serial: 2065
Measurement SW: DASY Module SAR V16.4.0.5005

2600.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 11.1 W/kg

SAR(1 g) = 5.42 W/kg; SAR(10 g) = 2.49 W/kg

Deviation (1 g) = -3.39%; Deviation (10 g) = -1.19%



ELEMENT

DUT: Dipole 2600.000 MHz; Type: D2600V2 - SN1009

Communication System: UID: 0, CW; Frequency: 2600.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 2600.000 MHz; cond = 1.93 S/m; perm = 40.4; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/15/2025; Ambient Temp: 20.5°C; Tissue Temp: 20.3°C

Probe: EX3DV4 - SN7640; ConvF:(7.86,7.3,7.85); Calibrated: 2025-02-12
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1645; Calibrated: 2025-02-11
Phantom: Twin-SAM V8.0; Serial: 1934
Measurement SW: DASY Module SAR V16.4.0.5005

2600.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.5 mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 12.1 W/kg

SAR(1 g) = 5.85 W/kg; SAR(10 g) = 2.65 W/kg

Deviation (1 g) = 3.54%; Deviation (10 g) = 4.33%



ELEMENT

DUT: Dipole 2600.000 MHz; Type: D2600V2 - SN1009

Communication System: UID: 0, CW; Frequency: 2600.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 2600.000$ MHz; $\text{cond} = 1.98$ S/m; $\text{perm} = 40.6$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/18/2025; Ambient Temp: 20.5°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7640; ConvF:(7.86,7.3,7.85); Calibrated: 2025-02-12
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1645; Calibrated: 2025-02-11
Phantom: Twin-SAM V8.0; Serial: 1934
Measurement SW: DASY Module SAR V16.4.0.5005

2600.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 12.6 W/kg

SAR(1 g) = 6.06 W/kg; SAR(10 g) = 2.74 W/kg

Deviation (1 g) = 7.26%; Deviation (10 g) = 7.87%



ELEMENT

DUT: Dipole 2600.000 MHz; Type: D2600V2 - SN1009

Communication System: UID: 0, CW; Frequency: 2600.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 2600.000$ MHz; $\text{cond} = 1.95$ S/m; $\text{perm} = 39.3$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/25/2025; Ambient Temp: 20.7°C; Tissue Temp: 20.1°C

Probe: EX3DV4 - SN7640; ConvF:(7.86,7.3,7.85); Calibrated: 2025-02-12
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1645; Calibrated: 2025-02-11
Phantom: Twin-SAM V8.0; Serial: 1934
Measurement SW: DASY Module SAR V16.4.0.5005

2600.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 30.0): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.5$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 11.9 W/kg

SAR(1 g) = 5.79 W/kg; SAR(10 g) = 2.63 W/kg

Deviation (1 g) = 2.48%; Deviation (10 g) = 3.54%



ELEMENT

DUT: Dipole 3500.000 MHz; Type: D3500V2 - SN1068

Communication System: UID: 0, CW; Frequency: 3500.000 MHz

Medium: Head Simulating Liquid; Medium parameters used:

f = 3500.000 MHz; cond = 2.79 S/m; perm = 39.5; density = 1000 kg/m³

Phantom Section: Flat; Space: 10 mm

Test Date: 09/12/2025; Ambient Temp: 20.9°C; Tissue Temp: 20.2°C

Probe: EX3DV4 - SN7402; ConvF:(6.24,6.75,6.43); Calibrated: 2025-06-12

Sensor-Surface: 1.4mm (VMS + 6p)

Electronics: DAE4 Sn1502; Calibrated: 2025-06-04

Phantom: Twin-SAM V5.0; Serial: 1868

Measurement SW: DASY Module SAR V16.4.0.5005

3500.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (28.0 x 28.0 x 28.0): Measurement grid: dx=5.0 mm, dy=5.0 mm, dz=1.4 mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 16.5 W/kg

SAR(1 g) = 6.48 W/kg; SAR(10 g) = 2.49 W/kg

Deviation (1 g) = -0.46%; Deviation (10 g) = 0.81%



ELEMENT

DUT: Dipole 3500.000 MHz; Type: D3500V2 - SN1127

Communication System: UID: 0, CW; Frequency: 3500.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 3500.000$ MHz; $\text{cond} = 2.94$ S/m; $\text{perm} = 37.8$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/15/2025; Ambient Temp: 20.3°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7402; ConvF:(6.24,6.75,6.43); Calibrated: 2025-06-12
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1502; Calibrated: 2025-06-04
Phantom: Twin-SAM V5.0; Serial: 1868
Measurement SW: DASY Module SAR V16.4.0.5005

3500.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (28.0 x 28.0 x 28.0): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.4$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 18.6 W/kg

SAR(1 g) = 6.90 W/kg; SAR(10 g) = 2.57 W/kg

Deviation (1 g) = 6.32%; Deviation (10 g) = 4.05%



ELEMENT

DUT: Dipole 3500.000 MHz; Type: D3500V2 - SN1097

Communication System: UID: 0, CW; Frequency: 3500.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 3500.000$ MHz; $\text{cond} = 2.77$ S/m; $\text{perm} = 38.2$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/22/2025; Ambient Temp: 21.9°C; Tissue Temp: 20.6°C

Probe: EX3DV4 - SN7660; ConvF:(7.04,6.7,7.27); Calibrated: 2025-05-09
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1678; Calibrated: 2025-05-09
Phantom: Twin-SAM V8.0; Serial: 2056
Measurement SW: DASY Module SAR V16.4.0.5005

3500.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: $\text{dx}=10.0$ mm, $\text{dy}=10.0$ mm

Zoom Scan (30.0 x 30.0 x 29.1): Measurement grid: $\text{dx}=5.0$ mm, $\text{dy}=5.0$ mm, $\text{dz}=1.4$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 16.5 W/kg

SAR(1 g) = 6.45 W/kg; SAR(10 g) = 2.49 W/kg

Deviation (1 g) = -1.38%; Deviation (10 g) = 0.81%



ELEMENT

DUT: Dipole 3500.000 MHz; Type: D3500V2 - SN1097

Communication System: UID: 0, CW; Frequency: 3500.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 3500.000$ MHz; $\text{cond} = 2.78$ S/m; $\text{perm} = 37.5$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/25/2025; Ambient Temp: 22.3°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN7660; ConvF:(7.04,6.7,7.27); Calibrated: 2025-05-09
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1678; Calibrated: 2025-05-09
Phantom: Twin-SAM V8.0; Serial: 2056
Measurement SW: DASY Module SAR V16.4.0.5005

3500.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 29.1): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.4$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 17.1 W/kg

SAR(1 g) = 6.71 W/kg; SAR(10 g) = 2.59 W/kg

Deviation (1 g) = 2.60%; Deviation (10 g) = 4.86%



ELEMENT

DUT: Dipole 3700.000 MHz; Type: D3700V2 - SN1029

Communication System: UID: 0, CW; Frequency: 3700.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 3700.000$ MHz; $\text{cond} = 2.98$ S/m; $\text{perm} = 39.1$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/12/2025; Ambient Temp: 20.9°C; Tissue Temp: 20.2°C

Probe: EX3DV4 - SN7402; ConvF:(6.35,6.86,6.54); Calibrated: 2025-06-12
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1502; Calibrated: 2025-06-04
Phantom: Twin-SAM V5.0; Serial: 1868
Measurement SW: DASY Module SAR V16.4.0.5005

3700.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (28.0 x 28.0 x 28.0): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.4$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 17.1 W/kg

SAR(1 g) = 6.41 W/kg; SAR(10 g) = 2.39 W/kg

Deviation (1 g) = -6.83%; Deviation (10 g) = -5.53%



ELEMENT

DUT: Dipole 3700.000 MHz; Type: D3700V2 - SN1096

Communication System: UID: 0, CW; Frequency: 3700.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 3700.000$ MHz; $\text{cond} = 3.11$ S/m; $\text{perm} = 37.5$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/15/2025; Ambient Temp: 20.3°C; Tissue Temp: 20.0°C

Probe: EX3DV4 - SN7402; ConvF:(6.35,6.86,6.54); Calibrated: 2025-06-12
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1502; Calibrated: 2025-06-04
Phantom: Twin-SAM V5.0; Serial: 1868
Measurement SW: DASY Module SAR V16.4.0.5005

3700.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (28.0 x 28.0 x 28.0): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.4$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 18.3 W/kg

SAR(1 g) = 6.57 W/kg; SAR(10 g) = 2.38 W/kg

Deviation (1 g) = -5.60%; Deviation (10 g) = -7.03%



ELEMENT

DUT: Dipole 3700.000 MHz; Type: D3700V2 - SN1067

Communication System: UID: 0, CW; Frequency: 3700.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 3700.000$ MHz; $\text{cond} = 2.97$ S/m; $\text{perm} = 37.8$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/22/2025; Ambient Temp: 21.9°C; Tissue Temp: 20.6°C

Probe: EX3DV4 - SN7660; ConvF:(7.04,6.7,7.28); Calibrated: 2025-05-09
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1678; Calibrated: 2025-05-09
Phantom: Twin-SAM V8.0; Serial: 2056
Measurement SW: DASY Module SAR V16.4.0.5005

3700.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 29.1): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.4$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 17.0 W/kg

SAR(1 g) = 6.36 W/kg; SAR(10 g) = 2.36 W/kg

Deviation (1 g) = -4.93%; Deviation (10 g) = -2.88%



ELEMENT

DUT: Dipole 3700.000 MHz; Type: D3700V2 - SN1067

Communication System: UID: 0, CW; Frequency: 3700.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 3700.000$ MHz; $\text{cond} = 2.98$ S/m; $\text{perm} = 37.1$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/25/2025; Ambient Temp: 22.3°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN7660; ConvF:(7.04,6.7,7.28); Calibrated: 2025-05-09
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1678; Calibrated: 2025-05-09
Phantom: Twin-SAM V8.0; Serial: 2056
Measurement SW: DASY Module SAR V16.4.0.5005

3700.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 29.1): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.4$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 17.9 W/kg

SAR(1 g) = 6.67 W/kg; SAR(10 g) = 2.48 W/kg

Deviation (1 g) = -0.30%; Deviation (10 g) = 2.06%



ELEMENT

DUT: Dipole 3900.000 MHz; Type: D3900V2 - SN1056

Communication System: UID: 0, CW; Frequency: 3900.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 3900.000$ MHz; $\text{cond} = 3.17$ S/m; $\text{perm} = 37.3$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/22/2025; Ambient Temp: 21.9°C; Tissue Temp: 20.6°C

Probe: EX3DV4 - SN7660; ConvF:(6.92,6.59,7.15); Calibrated: 2025-05-09
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1678; Calibrated: 2025-05-09
Phantom: Twin-SAM V8.0; Serial: 2056
Measurement SW: DASY Module SAR V16.4.0.5005

3900.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 29.1): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.4$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 19.8 W/kg

SAR(1 g) = 6.97 W/kg; SAR(10 g) = 2.48 W/kg

Deviation (1 g) = 2.20%; Deviation (10 g) = 4.20%



ELEMENT

DUT: Dipole 3900.000 MHz; Type: D3900V2 - SN1073

Communication System: UID: 0, CW; Frequency: 3900.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 3900.000$ MHz; $\text{cond} = 3.20$ S/m; $\text{perm} = 36.7$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/25/2025; Ambient Temp: 22.3°C; Tissue Temp: 20.5°C

Probe: EX3DV4 - SN7660; ConvF:(6.92,6.59,7.15); Calibrated: 2025-05-09
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1678; Calibrated: 2025-05-09
Phantom: Twin-SAM V8.0; Serial: 2056
Measurement SW: DASY Module SAR V16.4.0.5005

3900.0 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (40.0 x 80.0): Measurement grid: $dx=10.0$ mm, $dy=10.0$ mm

Zoom Scan (30.0 x 30.0 x 29.1): Measurement grid: $dx=5.0$ mm, $dy=5.0$ mm, $dz=1.4$ mm; Graded Ratio: 1.5

Peak SAR (extrapolated) = 20.6 W/kg

SAR(1 g) = 7.28 W/kg; SAR(10 g) = 2.59 W/kg

Deviation (1 g) = 4.75%; Deviation (10 g) = 6.58%



ELEMENT

DUT: Dipole 5250.000 MHz; Type: D5GHzV2 - SN1237

Communication System: UID: 0, CW; Frequency: 5250.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 5250.000 MHz; cond = 4.65 S/m; perm = 34.8; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/15/2025; Ambient Temp: 21.6°C; Tissue Temp: 20.3°C

Probe: EX3DV4 - SN7637; ConvF:(5.67,5.81,5.98); Calibrated: 2025-06-12
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1652; Calibrated: 2025-06-04
Phantom: Twin-SAM V5.0; Serial: 1797
Measurement SW: DASY Module SAR V16.4.0.5005

5250.0 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (40.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=4.0 mm, dy=4.0 mm, dz=1.4 mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.6 W/kg

SAR(1 g) = 3.77 W/kg; SAR(10 g) = 1.07 W/kg

Deviation (1 g) = -5.16%; Deviation (10 g) = -5.31%



ELEMENT

DUT: Dipole 5250.000 MHz; Type: D5GHzV2 - SN1237

Communication System: UID: 0, CW; Frequency: 5250.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 5250.000 MHz; cond = 4.56 S/m; perm = 35.7; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/22/2025; Ambient Temp: 21.7°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7637; ConvF:(5.67,5.81,5.98); Calibrated: 2025-06-12
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1652; Calibrated: 2025-06-04
Phantom: Twin-SAM V5.0; Serial: 1797
Measurement SW: DASY Module SAR V16.4.0.5005

5250.0 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (40.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=4.0 mm, dy=4.0 mm, dz=1.4 mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.3 W/kg

SAR(1 g) = 3.99 W/kg; SAR(10 g) = 1.15 W/kg

Deviation (1 g) = 0.38%; Deviation (10 g) = 1.77%



ELEMENT

DUT: Dipole 5250.000 MHz; Type: D5GHzV2 - SN1237

Communication System: UID: 0, CW; Frequency: 5250.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 5250.000 MHz; cond = 4.82 S/m; perm = 35.8; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 10/20/2025; Ambient Temp: 20.8°C; Tissue Temp: 19.8°C

Probe: EX3DV4 - SN7546; ConvF:(6.0,5.59,5.96); Calibrated: 2025-04-11
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1368; Calibrated: 2025-04-07
Phantom: Twin-SAM V5.0; Serial: 1715
Measurement SW: DASY Module SAR V16.4.0.5005

5250.0 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (40.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=4.0 mm, dy=4.0 mm, dz=1.4 mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.9 W/kg

SAR(1 g) = 3.74 W/kg; SAR(10 g) = 1.06 W/kg

Deviation (1 g) = -5.91%; Deviation (10 g) = -6.19%



ELEMENT

DUT: Dipole 5600.000 MHz; Type: D5GHzV2 - SN1237

Communication System: UID: 0, CW; Frequency: 5600.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 5600.000 MHz; cond = 5.04 S/m; perm = 34.1; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/15/2025; Ambient Temp: 21.6°C; Tissue Temp: 20.3°C

Probe: EX3DV4 - SN7637; ConvF:(5.09,5.22,5.37); Calibrated: 2025-06-12
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1652; Calibrated: 2025-06-04
Phantom: Twin-SAM V5.0; Serial: 1797
Measurement SW: DASY Module SAR V16.4.0.5005

5600.0 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (40.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=4.0 mm, dy=4.0 mm, dz=1.4 mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 18.9 W/kg

SAR(1 g) = 4.25 W/kg; SAR(10 g) = 1.20 W/kg

Deviation (1 g) = 3.41%; Deviation (10 g) = 1.69%



ELEMENT

DUT: Dipole 5600.000 MHz; Type: D5GHzV2 - SN1237

Communication System: UID: 0, CW; Frequency: 5600.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 5600.000 MHz; cond = 4.95 S/m; perm = 35.1; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/22/2025; Ambient Temp: 21.7°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7637; ConvF:(5.09,5.22,5.37); Calibrated: 2025-06-12
Sensor-Surface: 1.4mm (All points)
Electronics: DAE4 Sn1652; Calibrated: 2025-06-04
Phantom: Twin-SAM V5.0; Serial: 1797
Measurement SW: DASY Module SAR V16.4.0.5005

5600.0 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (40.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=4.0 mm, dy=4.0 mm, dz=1.4 mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 19.2 W/kg

SAR(1 g) = 4.30 W/kg; SAR(10 g) = 1.21 W/kg

Deviation (1 g) = 4.62%; Deviation (10 g) = 2.54%



ELEMENT

DUT: Dipole 5600.000 MHz; Type: D5GHzV2 - SN1237

Communication System: UID: 0, CW; Frequency: 5600.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 5600.000 MHz; cond = 5.25 S/m; perm = 35.1; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 10/20/2025; Ambient Temp: 20.8°C; Tissue Temp: 19.8°C

Probe: EX3DV4 - SN7546; ConvF:(5.37,5.0,5.33); Calibrated: 2025-04-11
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1368; Calibrated: 2025-04-07
Phantom: Twin-SAM V5.0; Serial: 1715
Measurement SW: DASY Module SAR V16.4.0.5005

5600.0 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (40.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=4.0 mm, dy=4.0 mm, dz=1.4 mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 18.9 W/kg

SAR(1 g) = 4.16 W/kg; SAR(10 g) = 1.18 W/kg

Deviation (1 g) = 1.22%; Deviation (10 g) = 0.00%



ELEMENT

DUT: Dipole 5750.000 MHz; Type: D5GHzV2 - SN1237

Communication System: UID: 0, CW; Frequency: 5750.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 5750.000 MHz; cond = 5.21 S/m; perm = 33.8; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/15/2025; Ambient Temp: 21.6°C; Tissue Temp: 20.3°C

Probe: EX3DV4 - SN7637; ConvF:(5.14,5.27,5.42); Calibrated: 2025-06-12
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1652; Calibrated: 2025-06-04
Phantom: Twin-SAM V5.0; Serial: 1797
Measurement SW: DASY Module SAR V16.4.0.5005

5750.0 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (40.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=4.0 mm, dy=4.0 mm, dz=1.4 mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 17.7 W/kg

SAR(1 g) = 3.83 W/kg; SAR(10 g) = 1.09 W/kg

Deviation (1 g) = -3.04%; Deviation (10 g) = -2.68%



ELEMENT

DUT: Dipole 5750.000 MHz; Type: D5GHzV2 - SN1237

Communication System: UID: 0, CW; Frequency: 5750.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 5750.000 MHz; cond = 5.13 S/m; perm = 34.9; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/22/2025; Ambient Temp: 21.7°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7637; ConvF:(5.14,5.27,5.42); Calibrated: 2025-06-12
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1652; Calibrated: 2025-06-04
Phantom: Twin-SAM V5.0; Serial: 1797
Measurement SW: DASY Module SAR V16.4.0.5005

5750.0 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (40.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=4.0 mm, dy=4.0 mm, dz=1.4 mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 18.8 W/kg

SAR(1 g) = 4.12 W/kg; SAR(10 g) = 1.18 W/kg

Deviation (1 g) = 4.30%; Deviation (10 g) = 5.36%



ELEMENT

DUT: Dipole 5750.000 MHz; Type: D5GHzV2 - SN1237

Communication System: UID: 0, CW; Frequency: 5750.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 5750.000 MHz; cond = 5.44 S/m; perm = 34.8; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 10/20/2025; Ambient Temp: 20.8°C; Tissue Temp: 19.8°C

Probe: EX3DV4 - SN7546; ConvF:(5.29,4.93,5.26); Calibrated: 2025-04-11
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1368; Calibrated: 2025-04-07
Phantom: Twin-SAM V5.0; Serial: 1715
Measurement SW: DASY Module SAR V16.4.0.5005

5750.0 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (40.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=4.0 mm, dy=4.0 mm, dz=1.4 mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 17.6 W/kg

SAR(1 g) = 3.73 W/kg; SAR(10 g) = 1.06 W/kg

Deviation (1 g) = -5.57%; Deviation (10 g) = -5.36%



ELEMENT

DUT: Dipole 5850.000 MHz; Type: D5GHzV2 - SN1237

Communication System: UID: 0, CW; Frequency: 5850.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 5850.000 MHz; cond = 5.34 S/m; perm = 33.6; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/15/2025; Ambient Temp: 21.6°C; Tissue Temp: 20.3°C

Probe: EX3DV4 - SN7637; ConvF:(4.93,5.06,5.2); Calibrated: 2025-06-12
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1652; Calibrated: 2025-06-04
Phantom: Twin-SAM V5.0; Serial: 1797
Measurement SW: DASY Module SAR V16.4.0.5005

5850.0 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (40.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=4.0 mm, dy=4.0 mm, dz=1.4 mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 19.7 W/kg

SAR(1 g) = 4.17 W/kg; SAR(10 g) = 1.17 W/kg

Deviation (1 g) = 1.71%; Deviation (10 g) = 0.00%



ELEMENT

DUT: Dipole 5850.000 MHz; Type: D5GHzV2 - SN1237

Communication System: UID: 0, CW; Frequency: 5850.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 5850.000 MHz; cond = 5.24 S/m; perm = 34.7; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 09/22/2025; Ambient Temp: 21.7°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7637; ConvF:(4.93,5.06,5.2); Calibrated: 2025-06-12
Sensor-Surface: 1.4mm (All points)
Electronics: DAE4 Sn1652; Calibrated: 2025-06-04
Phantom: Twin-SAM V5.0; Serial: 1797
Measurement SW: DASY Module SAR V16.4.0.5005

5850.0 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (40.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=4.0 mm, dy=4.0 mm, dz=1.4 mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 19.8 W/kg

SAR(1 g) = 4.23 W/kg; SAR(10 g) = 1.20 W/kg

Deviation (1 g) = 3.17%; Deviation (10 g) = 2.56%



ELEMENT

DUT: Dipole 5850.000 MHz; Type: D5GHzV2 - SN1237

Communication System: UID: 0, CW; Frequency: 5850.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 5850.000 MHz; cond = 5.56 S/m; perm = 34.6; density = 1000 kg/m³
Phantom Section: Flat; Space: 10 mm

Test Date: 10/20/2025; Ambient Temp: 20.8°C; Tissue Temp: 19.8°C

Probe: EX3DV4 - SN7546; ConvF:(5.3,4.94,5.26); Calibrated: 2025-04-11
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4 Sn1368; Calibrated: 2025-04-07
Phantom: Twin-SAM V5.0; Serial: 1715
Measurement SW: DASY Module SAR V16.4.0.5005

5850.0 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (40.0 x 80.0): Measurement grid: dx=10.0 mm, dy=10.0 mm

Zoom Scan (22.0 x 22.0 x 22.0): Measurement grid: dx=4.0 mm, dy=4.0 mm, dz=1.4 mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 18.8 W/kg

SAR(1 g) = 3.89 W/kg; SAR(10 g) = 1.09 W/kg

Deviation (1 g) = -5.12%; Deviation (10 g) = -6.84%



ELEMENT

DUT: Dipole 6500.000 MHz; Type: D6.5GHzV2 - SN1018

Communication System: UID: 0, CW; Frequency: 6500.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 6500.000 MHz; cond = 5.96 S/m; perm = 34.3; density = 1000 kg/m³
Phantom Section: Flat; Space: 5 mm

Test Date: 09/04/2025; Ambient Temp: 22.6°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN7570; ConvF:(5.35,5.65,5.29); Calibrated: 2025-02-10
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4ip Sn1638; Calibrated: 2025-02-07
Phantom: Twin-SAM V8.0; Serial: 1979
Measurement SW: DASY Module SAR V16.4.0.5005

6500.0 MHz System Verification at 14.0 dBm (25 mW)


Area Scan (51.0 x 85.0): Measurement grid: dx=8.5 mm, dy=8.5 mm

Zoom Scan (27.2 x 27.2 x 22.9): Measurement grid: dx=3.4 mm, dy=3.4 mm, dz=1.4 mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 46.1 W/kg

SAR(1 g) = 7.29 W/kg; SAR(10 g) = 1.33 W/kg; APD(4cm²) = 32.3 W/m²

Deviation (1 g) = -0.14%; Deviation (10 g) = -1.30%; Deviation (APD) = -1.37%



ELEMENT

DUT: Dipole 6500.000 MHz; Type: D6.5GHzV2 - SN1018

Communication System: UID: 0, CW; Frequency: 6500.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 6500.000 MHz; cond = 6.18 S/m; perm = 35.1; density = 1000 kg/m³
Phantom Section: Flat; Space: 5 mm

Test Date: 09/08/2025; Ambient Temp: 24.4°C; Tissue Temp: 22.1°C

Probe: EX3DV4 - SN7570; ConvF:(5.35,5.65,5.29); Calibrated: 2025-02-10
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4ip Sn1638; Calibrated: 2025-02-07
Phantom: Twin-SAM V8.0; Serial: 1979
Measurement SW: DASY Module SAR V16.4.0.5005

6500.0 MHz System Verification at 14.0 dBm (25 mW)


Area Scan (51.0 x 85.0): Measurement grid: dx=8.5 mm, dy=8.5 mm

Zoom Scan (23.8 x 27.2 x 22.9): Measurement grid: dx=3.4 mm, dy=3.4 mm, dz=1.4 mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 44.7 W/kg

SAR(1 g) = 7.09 W/kg; SAR(10 g) = 1.32 W/kg; APD(4cm²) = 31.8 W/m²

Deviation (1 g) = -2.88%; Deviation (10 g) = -2.04% Deviation (APD) = -2.90%



ELEMENT

DUT: Dipole 6500.000 MHz; Type: D6.5GHzV2 - SN1018

Communication System: UID: 0, CW; Frequency: 6500.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
 $f = 6500.000$ MHz; $\text{cond} = 5.98$ S/m; $\text{perm} = 33.3$; $\text{density} = 1000$ kg/m³
Phantom Section: Flat; Space: 5 mm

Test Date: 09/17/2025; Ambient Temp: 24.4°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7570; ConvF:(5.35,5.65,5.29); Calibrated: 2025-02-10
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4ip Sn1638; Calibrated: 2025-02-07
Phantom: Twin-SAM V8.0; Serial: 1979
Measurement SW: DASY Module SAR V16.4.0.5005

6500.0 MHz System Verification at 14.0 dBm (25 mW)


Area Scan (51.0 x 85.0): Measurement grid: $dx=8.5$ mm, $dy=8.5$ mm

Zoom Scan (23.8 x 23.8 x 22.9): Measurement grid: $dx=3.4$ mm, $dy=3.4$ mm, $dz=1.4$ mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 48.3 W/kg

SAR(1 g) = 7.59 W/kg; SAR(10 g) = 1.39 W/kg; APD(4cm²) = 33.6 W/m²

Deviation (1 g) = 3.97%; Deviation (10 g) = 3.15%; Deviation (APD) = 2.60%



ELEMENT

DUT: Dipole 8000.000 MHz; Type: D8GHzV2 - SN1007

Communication System: UID: 0, CW; Frequency: 8000.000 MHz
Medium: Head Simulating Liquid; Medium parameters used:
f = 8000.000 MHz; cond = 7.92 S/m; perm = 32.0; density = 1000 kg/m³
Phantom Section: Flat; Space: 5 mm

Test Date: 10/08/2025; Ambient Temp: 23.7°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7570; ConvF:(5.71,6.04,5.65); Calibrated: 2025-02-10
Sensor-Surface: 1.4mm (VMS + 6p)
Electronics: DAE4ip Sn1638; Calibrated: 2025-02-07
Phantom: Twin-SAM V8.0; Serial: 1979
Measurement SW: DASY Module SAR V16.4.0.5005

8000.0 MHz System Verification at 14.0 dBm (25 mW)


Area Scan (52.0 x 91.0): Measurement grid: dx=6.5 mm, dy=6.5 mm

Zoom Scan (24.3 x 24.3 x 31.0): Measurement grid: dx=2.7 mm, dy=2.7 mm, dz=1.3 mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 64.7 W/kg

SAR(1 g) = 7.17 W/kg; SAR(10 g) = 1.20 W/kg; APD(4.0 cm²) = 29.1 W/m

Deviation (1 g) = 9.47%; Deviation (10 g) = 7.38%; Deviation (APD) = 6.79%



Date: 2025-10-01

Measurement Group

Device Under Test Properties

DUT	Serial Number
10 GHz Verification Source	1 002

Exposure Conditions

Phantom Section	Position	Test Distance [mm]	Band	Frequency [MHz]
5G	FRONT	10.00	Validation band	10000.0

Hardware Setup

Probe, Calibration Date	DAE, Calibration Date
EUmmWV3 – SN9389, 2025-01-08	DAE4ip – SN1639, 2025-02-05

Software Setup


Software	Software Version
cDASY6 Module mmWave	3.2.0.1840

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	120.0 x 120.0
Grid Steps [lambda]	0.125 x 0.125
Sensor Surface [mm]	10.0

Measurement Results

Scan Type	5G Scan
Avg. Area [cm²]	4.00
pS _{tot} avg [W/m²]	50.0
pS _n avg [W/m²]	49.8
E _{peak} [V/m]	145
Deviation [dB] pS _{tot}	-0.33
Deviation [dB] pS _n	-0.34



Date: 2025-10-11

Measurement Group

Device Under Test Properties

DUT	Serial Number
10 GHz Verification Source	1 002

Exposure Conditions

Phantom Section	Position	Test Distance [mm]	Band	Frequency [MHz]
5G	FRONT	10.00	Validation band	10000.0

Hardware Setup

Probe, Calibration Date	DAE, Calibration Date
EUmmWV3 – SN9389, 2025-01-08	DAE4ip – SN1639, 2025-02-05

Software Setup

Software	Software Version
cDASY6 Module mmWave	3.2.0.1840

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	120.0 x 120.0
Grid Steps [lambda]	0.125 x 0.125
Sensor Surface [mm]	10.0

Measurement Results

Scan Type	5G Scan
Avg. Area [cm²]	4.00
pS _{tot} avg [W/m²]	51.8
pS _n avg [W/m²]	51.4
E _{peak} [V/m]	146
Deviation [dB] pS _{tot}	-0.18
Deviation [dB] pS _n	-0.18

