

EMC TEST REPORT

Project No.	LBE20250328	Issue No.	0
Applicant	Name of organization	Samsung Electronics Co., Ltd.	
	Address	(Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea	
	Date of receipt	September 8, 2025	
EUT	Type of device	☒ All other receivers subject to Part 15 ☒ Class B personal computers and peripherals ☒ Other Class B digital devices and peripherals ☐ FM Broadcast Receiver	
	Equipment authorization	☒ Certification ☐ Supplier's Declaration of Conformity	
	FCC ID	A3LSMS948U	
	Kind of product	Mobile Phone	
	Model No.	SM-S948U	
	Variant Model No.	Refer to clause 4.6	
	Manufacturer	Samsung Electronics Co.,Ltd. 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea	
Applied Standards		FCC 47 CFR Part 15, Subpart B, Class B / ANSI C63.4-2014	
Test Period		September 16, 2025 ~ September 18, 2025	
Issue date		September 30, 2025	
Test result : Complied The equipment under test has found to be compliant with the applied standards. (Refer to the attached test result for more detail.)			
Tested by : Jin-Yi Kang 76 21 01		Reviewed by : Young-Ju Ryu Y. T. Ryu	
The test results in this report only apply to the tested sample. This report must not be reproduced, except in full, without written permission from Global CS center. * Not KOLAS report			
Samsung Electronics Co., Ltd., Global CS Center (Maetan dong) 129, Samsung-ro, Yeongtong-Gu, Suwon-Si, Gyeonggi-Do 16677, Korea			

Table of Contents

1. Report Information	3
1.1 Revision history	3
2. Summary of test results	3
2.1 Emission	3
3. General Information	3
3.1 Test facility	3
4. Test Setup configuration	4
4.1 Test Peripherals	4
4.2 EUT operating mode	5
4.3 Details of Sampling	5
4.4 Used cable description	6
4.5 Test arrangement	7
4.6 EUT Description	10
4.7 EUT Frequencies	10
4.8 Test configuration and condition	11
4.9 Measurement uncertainty	11
5. Results of individual test	12
5.1 Conducted Emission	12
5.2 Radiated Emission	17

1. Report Information

1.1 Revision history

No.	Date of Issue	Revised detailed information
Issue 0	September 30, 2025	There are no revisions and this version is basic test report.

※ Remark

Only compliance with Part 15B (Section 15.107 Conducted limits) requirements for the receiver part of the licensed transmitter (equipment code CXX) is covered by this report.

2. Summary of test results

2.1 Emission

The EUT has been tested according to the following specifications:

Applied	Test type	Applied standard	Result
■	Conducted Emission (Mains port)	FCC 47 CFR Part 15 Subpart B / ANSI C63.4-2014 (Class B)	Complied
■	Radiated Emission		Complied

3. General Information

3.1 Test facility

The Global CS Center is located on Samsung Electronics Co., Ltd. at (Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea.

All testing are performed in Semi-anechoic chambers conforming to the site attenuation characteristics defined by ANSI C63.4, CISPR 32, CISPR 16-1-4 and Shielded rooms.

And all antennas are properly calibrated using ANSI C63.5:2017.

The Global CS Center is an ISO/IEC 17025 accredited testing laboratory by the National Radio Research Agency with designation No. KR0004. for EMC testing.

4. Test Setup configuration

4.1 Test Peripherals

The cables used for these peripherals are either permanently attached by the peripheral manufacturer or coupled with an assigned cable as defined below.

The following is a listing of the EUT and peripherals utilized during the performance of EMC test:

Description	Model No.	Serial No.	Manufacturer / Trademark	FCC ID
Mobile Phone	SM-S948U	-	SAMSUNG	A3LSMS948U
Headset	EO-IC100	-	CRESYN	-
Data Link Cable	EP-DN980	-	RFTECH	-
Laptop Computer	Latitude5580	1WYRYM2	Dell	SDoC
Laptop Computer	Latitude5580	D3HRYM2	Dell	SDoC
Laptop AC Adapter	LA65NM130	5DEA	Dell	SDoC
Laptop AC Adapter	LA65NM130	5B3C	Dell	SDoC
Mouse	AA-SM7PCPB	CN57BA5903634ADV 8JJCD4371	SAMSUNG	SDoC
Mouse	SMH-210UB	TAKGA05788 Z	SAMSUNG	SDoC
Router	DIR-806A	RF0F1D8018454	D-Link	SDoC
Router	DIR-806A	RF0F1D8011504	D-Link	SDoC
Travel Adapter	EP-T6010	R37Y8S23M91RTA	RFTECH	-
Monitor	27UD88	711NTQD8H004	LG	SDoC
Monitor AC Adapter	LCAP31	EH8NN629490055062	LG	SDoC
DP Cable	CDP01	-	KBEST	-
S-Pen	EJ-PS938	-	WACOM	-

4.2 EUT operating mode

To achieve compliance applied standard specification including CXX, JAB and JBP requirement, the following mode(s) were made during compliance testing:

4.2.1 Conducted Emission

No.	Operating mode
1	Camera (Rear) + Charging (w/TA) + Cellular receiver (LTE FDD26 Center Frequency)
2	Camera (Front) + Charging (w/TA)
3	Video + Audio playback from internal memory + Charging (w/TA)
4	USB data communication with PC (from internal memory)

4.2.2 Radiated Emission

No.	Operating mode
1	Camera (Rear) + Charging (w/TA)
2	Camera (Front) (w/Headset)
3	Video + Audio playback from internal memory (w/Headset)
4	Video + Audio playback from internal memory + Display out (w/ USB to Direct DP cable)
5	USB data communication with PC (from internal memory)

4.3 Details of Sampling

Customer selected, single unit.


4.4 Used cable description

The EUT is configured, installed, arranged and operated in a manner consistent with typical applications. Interface cables/loads/devices are connected to at least one of each type of interface port of the EUT, and where practical, each cable shall be terminated in a device typical of actual usage. The type(s) of interconnecting cables to be used and the interface port (of the EUT) to which these were connected:


Connected cable	Length [m]	Shielded [Y/N]	Note
Data Link Cable	1.0	Y	From EUT to Laptop Computer or Travel Adapter
Headset	1.2	N	For EUT
Power(DC)	1.8	N	From Laptop Computer to AC Adapter
Power(AC)	1.5	N	For Laptop AC Adapter
LAN	1.5	N	From Laptop Computer to Router
USB	0.8	Y	From Laptop Computer to Router for DC Power
USB	1.8	Y	From Laptop Computer to Mouse
DP Cable	2	Y	From EUT to Monitor
Power(DC)	1.2	N	From Monitor to AC Adapter
Power(AC)	2.2	N	For Monitor AC Adapter

4.5 Test arrangement

4.5.1 Conducted Emission




[Mode 1 – 3]




[Mode 4]


4.5.2 Radiated Emission




[Mode 1]



[Mode 2 – 3]



[Mode 4]



[Mode 5]

4.6 EUT Description

The EUT is a bar type mobile phone which can operate on GSM 850/900/1800/1900, WCDMA FDD 1/2/4/5/8, LTE FDD 1/2/3/4/5/7/8/12/13/14/18/19/20/25/26/28/29/30/66/71, LTE TDD 38/39/40/41/48, 5G NR n1/2/3/5/7/8/12/14/20/25/26/28/29/30/38/41/48/66/70/71/77/78/257/258/260/261 and incorporates a Bluetooth, Wi-Fi (802.11 b/g/n/a/ac/ax/be), Camera, Audio, Video, GNSS, UWB, DP, S-Pen, NFC, USB, Wireless Charging and Wireless power sharing.

4.6.1 The variant models

- SM-S948U1

4.7 EUT Frequencies

The highest frequencies (Generated and used)	Frequency [MHz]
NR n260	40 000

4.8 Test configuration and condition

The system was configured for testing in a typical fashion that a customer would normally use. Cables were attached to each of the available I/O Ports. Where applicable, peripherals were attached to the I/O cables.

All the external I/O ports are exercised, as well as internal and the external microSD card(if available), by writing and reading arbitrary data or charging with TA.

The EUT was investigated in three orientations and the worst case orientation is reported.

For the AC conducted emissions test, the conducted emissions of receiver modes which operate within the frequency range of 30-960 MHz were compared through preliminary tests. However, no significant differences were found to affect the conducted emission, so the test result for one representative receiver frequency band (LTE FDD26) were reported.

The video and audio(1 kHz sound) were repetitively played with the headset connected.

The video and audio(1 kHz sound) were played on monitor through display out function using direct DP cable.

The camera of the EUT was operated continuously.

Power source for the EUT operating was supplied by CVCF.

- Test Voltage : AC 120 V, 60 Hz

4.9 Measurement uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus : (According to CISPR 16-4-2 and UKAS M3003)

Test type		Measurement uncertainty (C.L. approximately 95 %, $k = 2$)
Conducted Emission	AC Mains	2.8 dB
Radiated Emission (Below 1 GHz)	Horizontal	4.2 dB
	Vertical	6.1 dB
Radiated Emission (Above 1 GHz)	Horizontal	5.0 dB
	Vertical	5.0 dB

* Remark

- 1) The values for uncertainty of conducted and radiated emissions are less than the Corresponding values of U_{cispr} given in CISPR 16-4-2. Therefore no adjustment of measurement results is necessary when comparing them with the relevant limits.

5. Results of individual test

5.1 Conducted Emission

The EUT is connected to a LISN via travel adapter. If the EUT is connected to the Laptop Computer USB port, the Laptop AC adapter is connected to a LISN.

Both conducted lines are measured in Quasi-Peak and CISPR-Average mode, including the worst-case data points for each tested configuration. The EUT measured in accordance with the methods described in standards.

Limits for Conducted emission at the mains ports of Class B

Frequency range Limits [MHz]	Resolution Bandwidth [kHz]	Limits [dB(μV)]	
		Quasi-peak	Average
0.15 to 0.50	9	66 to 56	56 to 46
0.50 to 5	9	56	46
5 to 30	9	60	50

NOTE 1 The lower limit shall apply at the transition frequency.

NOTE 2 The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

5.1.1 Test instrumentation


EMC No.	Test Instrument	Model name	Manufacturer	Serial No.	Next Calibration	
					Date	Interval (Month)
E5I-C-008	LTE Communicator	CMW500	R&S	132728	2026-04-09	12
E5I-G-003	Two-Line V-Network	ENV216	R&S	102061	2026-02-07	12
E5I-B-007	EMI Test Receiver	ESW8	R&S	103124	2026-07-14	12
-	Test software	EMC32	R&S	Ver 10.60.20	-	-

5.1.2 Temperature and humidity condition

Test date	2025-09-16	Test engineer	Jin-Yi Kang
Climate condition	Ambient temperature	(23.2 ± 1.0) °C	Limit (15.0 to 35.0) °C
	Humidity	(52.3 ± 1.0) % R.H.	Limit (25.0 to 75.0) % R.H.
	Atmospheric pressure	(101.1 ± 1.0) kPa	Limit (86.0 to 106.0) kPa
Test place	Shield Room (SR8)		

5.1.3 Test Results

□ Operating Mode 1: AC Mains



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:


Frequency (MHz)	QP (dBμV)	CAV (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.161	---	35.8	55.4	19.6	N	9.9
0.161	58.0	---	65.4	7.4	L1	9.9
0.220	---	29.1	52.8	23.8	N	10.0
0.222	53.4	---	62.7	9.4	N	10.0
0.321	---	24.1	49.7	25.5	N	10.0
0.328	48.1	---	59.5	11.5	L1	10.0
0.492	41.9	---	56.1	14.3	N	10.2
0.566	---	24.3	46.0	21.7	N	10.1
0.607	---	27.3	46.0	18.7	N	10.1
0.695	29.8	---	56.0	26.2	N	10.1
4.965	27.0	---	56.0	29.0	N	10.1
4.992	---	18.8	46.0	27.2	N	10.1

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

Note 3) A 0.1 dB deviation can occur in the margin calculation because of rounding the decimal point in the data.

□ Operating Mode 2: AC Mains



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:


Frequency (MHz)	QP (dBμV)	CAV (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.152	---	39.5	55.9	16.4	L1	9.9
0.152	50.6	---	65.9	15.2	L1	9.9
0.220	52.5	---	62.8	10.3	N	10.0
0.231	---	32.7	52.4	19.7	N	9.9
0.321	---	25.9	49.7	23.8	N	10.0
0.323	42.7	---	59.6	16.9	L1	10.0
0.611	---	26.6	46.0	19.4	N	10.1
0.614	38.4	---	56.0	17.6	N	10.1
4.409	27.5	---	56.0	28.5	N	10.0
4.634	25.9	---	56.0	30.1	N	10.0
4.994	---	18.9	46.0	27.1	N	10.1
10.003	---	19.2	50.0	30.8	N	10.3

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
 Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

Note 3) A 0.1 dB deviation can occur in the margin calculation because of rounding the decimal point in the data.

□ Operating Mode 3: AC Mains



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:

Frequency (MHz)	QP (dBμV)	CAV (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.150	---	33.6	56.0	22.4	L1	9.9
0.152	56.1	---	65.9	9.8	N	9.9
0.220	51.4	---	62.8	11.5	L1	10.0
0.227	---	25.2	52.6	27.4	L1	9.9
0.330	45.4	---	59.5	14.0	L1	10.0
0.456	---	18.2	46.8	28.5	L1	10.2
0.467	39.2	---	56.6	17.3	L1	10.2
0.578	---	26.7	46.0	19.3	L1	10.1
0.605	---	27.6	46.0	18.4	L1	10.1
0.683	31.0	---	56.0	25.0	N	10.1
4.610	26.8	---	56.0	29.2	L1	10.0
4.958	---	18.7	46.0	27.3	L1	10.0


Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)

Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

Note 3) A 0.1 dB deviation can occur in the margin calculation because of rounding the decimal point in the data.

□ Operating Mode 4: AC Mains



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:

Frequency (MHz)	QP (dBμV)	CAV (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.150	57.8	---	66.0	8.2	N	9.8
0.152	---	40.2	55.9	15.7	N	9.8
0.220	42.5	---	62.8	20.3	N	9.9
0.499	31.6	---	56.0	24.4	L1	10.1
3.091	---	21.1	46.0	24.9	L1	9.8
3.831	35.5	---	56.0	20.5	N	9.8
3.836	---	26.2	46.0	19.8	N	9.8
4.526	---	24.2	46.0	21.8	L1	9.8
4.531	32.7	---	56.0	23.3	N	9.8
9.632	---	29.9	50.0	20.1	L1	9.9
9.767	---	30.2	50.0	19.8	L1	9.9
9.852	36.1	---	60.0	23.9	L1	9.9

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
 Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)

QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

Note 3) A 0.1 dB deviation can occur in the margin calculation because of rounding the decimal point in the data.

5.2 Radiated Emission

The following data lists the significant emission frequencies, measured levels, correction factors (for antenna and cables), orientation of table, polarization and height of antenna, the corrected reading, the limit, and the amount of margin.

Peak measurements were made over the changeable frequency range 30 MHz to 1 GHz at a measurement distance of 10 m for the following antenna and turntable arrangements:

Antenna Height [cm]	Antenna Polarization	Resolution Bandwidth [kHz]	Video Bandwidth [kHz]	Turntable position [degrees]
100 ~ 400	Horizontal, Vertical	120	300	Continuous

Measurements within 6 dB of the limit were then maximized by adjusting turntable position.

Final measurements were made using quasi-peak detector.

Peak/CISPR-Average measurements were made over the changeable frequency range 1 GHz to 40 GHz or 5th harmonics of the highest frequency generated or used in the device or on which the device operates or tunes at a measurement distance of 3 m for the following antenna and turntable arrangements. The measurements above 1 GHz were performed with the bore-sighting antenna aimed at the EUT.

Antenna Height [cm]	Antenna Polarization	Resolution Bandwidth [MHz]	Video Bandwidth [MHz]	Turntable position [degrees]
100 ~ 400	Horizontal, Vertical	1	3	Continuous

Measurements within 6 dB of the limit were then maximized by adjusting turntable position.

Final measurements were made using peak and CISPR-average detectors.

Limits for Radiated emission of Class B at a measuring distance of 3 m and 10 m

Frequency range Limits [MHz]	Field Strength		
	3 m [$\mu\text{V/m}$]	3 m [$\text{dB}(\mu\text{V/m})$]	10 m [$\text{dB}(\mu\text{V/m})$]
30 to 88	100	40.0	29.5
88 to 216	150	43.5	33.0
216 to 960	200	46.0	35.5
Above 960	500	54.0	43.5

Note) Distance correction formula from D1(3m) to D2(10m)

: Limit at D2 = Limit at D1 + $20\text{Log}(D1/D2)$

Results checked manually; and points close to the limit line were re-measured.

5.2.1 Test instrumentation

EMC No.	Test Instrument	Model name	Manufacturer	Serial No.	Next Calibration	
					Date	Interval (Month)
E5I-B-005	EMI Test Receiver	ESU40	R&S	100375	2025-10-16	12
E5I-B-002	EMI Test Receiver	ESU8	R&S	100482	2026-06-09	12
E5I-B-008	EMI Test Receiver	ESW44	R&S	103129	2026-07-14	12
E5I-A-005	BiLog Antenna	CBL6112D	TESEQ	36997	2026-05-29	24
E5I-A-004	BiLog Antenna	CBL6112D	TESEQ	36009	2026-05-29	24
E5I-E-005	Preamplifier	310N	SONOMA	273122	2026-01-22	12
E5I-E-006	Preamplifier	310N	SONOMA	282363	2026-01-22	12
E5I-A-007	Horn Antenna	HF907	R&S	102525	2026-03-28	24
E5I-E-007	Signal Conditioning Unit	SCU-18	R&S	10211	2026-04-10	12
E5I-A-013	WideBand Horn Antenna	QMS-00880	STEATITE	25187	2025-12-05	24
E5I-E-010	Signal Conditioning Unit	SCU-40A	R&S	10003	2026-01-22	12
-	Test software	EP7RE	TOYO	Ver 8.0.20	-	-
-	Test software	EMC32	R&S	Ver 10.60.20	-	-


5.2.2 Temperature and humidity condition

Test date	2025-09-17 ~ 2025-09-18	Test engineer	Jin-Yi Kang
Climate condition	Ambient temperature	(21.4 ± 1.0) °C (21.3 ± 1.0) °C	Limit (15.0 to 35.0) °C
	Humidity	(47.9 ± 1.0) % R.H. (48.9 ± 1.0) % R.H.	Limit (25.0 to 75.0) % R.H.
	Atmospheric pressure	(100.9 ± 1.0) kPa (100.2 ± 1.0) kPa	Limit (86.0 to 106.0) kPa
Test place	Semi-Anechoic Chamber (SAC5)		

5.2.3 Test Results

□ Operating Mode 1

- Frequencies below 1 GHz




Note1) Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz



Note 1) We have also tested from 18 GHz to 40 GHz and found no emissions.


Note 2) Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 2

- Frequencies below 1 GHz




Note1) Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz



Note 1) We have also tested from 18 GHz to 40 GHz and found no emissions.


Note 2) Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 3

- Frequencies below 1 GHz




Note1) Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz



Note 1) We have also tested from 18 GHz to 40 GHz and found no emissions.


Note 2) Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 4


- Frequencies below 1 GHz



Note1) Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz

Frequency (MHz)	PK (dB μ V/m)	CAV (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1 076.400	45.6	---	74.0	28.4	101.0	H	347.0	8.0
1 077.200	---	35.7	54.0	18.3	101.0	H	0.0	8.0
1 349.200	48.7	---	74.0	25.3	102.0	H	24.0	9.3
1 349.200	---	39.3	54.0	14.7	101.0	H	24.0	9.3
2 942.200	50.1	---	74.0	23.9	102.0	H	158.0	19.0
2 950.400	---	38.9	54.0	15.1	102.0	H	152.0	19.3
5 400.000	---	47.7	54.0	6.3	101.0	H	127.0	8.9
5 400.000	49.7	---	74.0	24.3	101.0	H	127.0	8.9
11 145.000	48.2	---	74.0	25.8	103.0	V	196.0	24.8
11 165.000	---	43.0	54.0	11.0	100.0	H	98.0	24.5
17 707.500	49.7	---	74.0	24.3	102.0	H	58.0	35.3
17 787.500	---	46.2	54.0	7.8	101.0	H	20.0	37.1

Note 1) We have also tested from 18 GHz to 40 GHz and found no emissions.


Note 2) Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 5


- Frequencies below 1 GHz



Note1) Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz

Frequency (MHz)	PK (dB μ V/m)	CAV (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1 861.000	45.3	---	74.0	28.7	101.0	V	0.0	13.6
1 865.600	---	33.6	54.0	20.4	100.0	V	13.0	13.6
2 130.400	---	45.5	54.0	8.5	102.0	V	28.0	15.4
2 133.400	58.3	---	74.0	15.7	101.0	V	28.0	15.3
2 981.800	---	36.6	54.0	17.4	101.0	H	247.0	19.3
2 988.600	47.0	---	74.0	27.0	103.0	V	147.0	19.6
5 249.500	---	38.0	54.0	16.0	102.0	H	1.0	10.9
5 249.500	43.7	---	74.0	30.3	101.0	H	1.0	10.9
11 681.000	---	43.4	54.0	10.6	102.0	H	200.0	25.3
11 697.000	49.1	---	74.0	24.9	101.0	V	57.0	25.9
17 776.500	---	44.3	54.0	9.7	102.0	H	297.0	36.6
17 800.000	49.6	---	74.0	24.4	104.0	V	305.0	37.1

Note 1) We have also tested from 18 GHz to 40 GHz and found no emissions.

Note 2) Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor