

EMC TEST REPORT

Project No.	LBE20135086	Issue No.	0
Applicant	Name of organization	Samsung Electronics Co., Ltd.	
	Address	(Maetan dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 443-742, Republic of Korea	
	Date of application	October 16, 2013	
EUT	Type of device	☒ Class B personal computers and peripherals ☐ All other devices	
	Equipment authorization	☐ Declaration of Conformity ☒ Certification ☐ Verification	
	FCC ID	A3LSMT217T	
	Kind of product	Portable Device	
	Model No.	SM-T217T	
	Variant Model No.	Refer to clause 4.6	
	Manufacturer	SAMSUNG ELECTRONICS CO., LTD. 94-1, Imsu-dong, Gumi-si, Gyengsangbuk-do, 730-722, Republic of Korea	
Applied Standards		FCC Part 15, Subpart B, Class B / ANSI C63.4-2009	
Test Period		October 21, 2013 ~ October 24, 2013	
Issue date		October 28, 2013	
Test result : Complied The equipment under test has found to be compliant with the applied standards. (Refer to the attached test result for more detail.)			
Tested by : Hee-Sung Kim 		Reviewed by : Jong-Sup Jeong 	
The test results in this report only apply to the tested sample. This report must not be reproduced, except in full, without written permission from CS & Environment center.			
			
(Maetan dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-so, 443-742, Republic of Korea Tel: 82 31 279 1750, Fax: 82 31 279 1745			

Table of contents

1. Report Information

1.1 Revision history	3
----------------------------	---

2. Summary of test results

2.1 Emission	3
--------------------	---

3. General Information

3.1 Test facility	3
-------------------------	---

4. Test Configuration

4.1 Test Peripherals	4
4.2 EUT operating mode	4
4.3 Details of Sampling	4
4.4 Used cable description	5
4.5 Test arrangement	5
4.6 EUT Description	6
4.7 Clock Frequencies	6
4.8 Test configuration and condition	7
4.9 Measurement uncertainty	7

5. Result of individual tests

5.1 Conducted disturbance	8
5.2 Radiated disturbance	10

1. Report Information

1.1 Revision history

No.	Revised detailed information
Issue 0	- LBE20135086 (SAMSUNG)

2. Summary of test results

1.1 Emission

The EUT has been tested according to the following specifications:

Applied	Test type	Applied standard	Result
☒	Conducted Disturbance (Mains port)	FCC Part 15 Subpart B / ANSI C63.4-2009 (Class B)	Complied
☒	Radiated Disturbance		Complied

3. General Information

3.1 Test facility

The CS & Environment center is located on Samsung Electronics Co., Ltd. at (Maetan dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, Republic of Korea.

All testing are performed in Semi-anechoic chambers conforming to the site attenuation characteristics defined by ANSI C63.4, CISPR 22, 16-1 and 16-2. and Shielded rooms.

The CS & Environment center is operated as testing laboratory in accordance with the requirements of ISO/IEC 17025:2005.

4. Test Setup configuration

4.1 Test Peripherals

The cables used for these peripherals are either permanently attached by the peripheral manufacturer or coupled with an assigned cable as defined below.

The following is a listing of the EUT and peripherals utilized during the performance of EMC test:

Mark	Description	Model No.	Serial No.	Manufacturer / Trademark	FCC ID / DoC
A	Portable Device	SM-T217T	-	SAMSUNG	A3LSMT217T
B	Battery	SP4960C3C	-	SAMSUNG	-
C	Headset	EHS64ASFWE	-	SAMSUNG	-
D	Data Cable	ECB-DU4EBE	-	SAMSUNG	-
E	Micro SD Card	16GB	-	SANDISK	-
F	Desk-Top Computer	DM300S3A	EBDEDC6FFD	SAMSUNG	DoC
			-	SAMSUNG	DoC
G	LCD TV Monitor	CF19MS	CF19H1LS700048Y	SAMSUNG	DoC
		EF23TS	EM23H1LS300070L	SAMSUNG	DoC
H	Mouse	SML-210PB	TAKD125021R	SAMSUNG	DoC
I	Keyboard	SDM8500P	8M001183	SAMSUNG	DoC
J	Router	J9794A	CN33FQ71XK	HP	DoC
K	Power Supply	EADP-15DC A	DIKD1245096576	HP	DoC

This portable device does not contain the minimum number of ports required for personal computer testing per ANSI C63.4, but the EUT is attached to a computer through its only available port, which represents worst case emissions. All other aspects of C63.4 testing requirements were maintained.

4.2 EUT operating mode

To achieve compliance applied standard specification, the following mode(s) were made during compliance testing:

Operating Mode 1	USB Mode (Data Communication)
-------------------------	-------------------------------

4.3 Details of Sampling

Customer selected, single unit.

The EUT is configured, installed, arranged and operated in a manner consistent with typical applications. Interface cables/loads/devices are connected to at least one of each type of interface port of the EUT, and where practical, each cable shall be terminated in a device typical of actual usage. The type(s) of interconnecting cables to be used and the interface port (of the EUT) to which these were connected:

No.	Connected cable	Length [m]	Shielded [Y/N]	Note
1	USB	1.5	Yes	From EUT to Desk-Top Computer
2	Headset	1.2	No	For EUT
3	Power	1.8	No	For Desk-Top Computer
4	Power	1.8	No	For LCD TV Monitor
5	Power	1.8	No	For Power Supply
6	Power	1.8	No	From Router to Power Supply
7	LAN	1.5	No	From Desk-Top Computer to Router
8	LAN	1.5	No	From Router to Local Area Network
9	RGB	1.8	Yes	From Desk-Top Computer to LCD TV Monitor
10	PS/2	1.8	Yes	From Desk-Top Computer to Mouse
11	PS/2	1.8	Yes	From Desk-Top Computer to Keyboard

The diagram illustrates a computer system with the following components and connections:

- Components:**
 - F:** A black and blue desktop computer tower.
 - G:** A black computer monitor.
 - J:** A white wireless router.
 - K:** A silver wireless access point or antenna.
 - H:** A black computer mouse.
 - I:** A blue keyboard.
 - C:** A black cable with multiple connectors.
 - A&B&E:** A smartphone.
- Connections:**
 - 1:** A cable connecting the smartphone (A&B&E) to the desktop tower (F).
 - 2:** A cable connecting the smartphone (A&B&E) to the desktop tower (F).
 - 3:** A cable connecting the desktop tower (F) to an external device (represented by a mouse icon).
 - 4:** A cable connecting the monitor (G) to an external device (represented by a mouse icon).
 - 5:** A cable connecting the wireless access point (K) to an external device (represented by a mouse icon).
 - 6:** A cable connecting the wireless router (J) to the wireless access point (K).
 - 7:** A cable connecting the desktop tower (F) to the wireless router (J).
 - 8:** A cable connecting the wireless router (J) to an external device (represented by a mouse icon).
 - 9:** A cable connecting the desktop tower (F) to the monitor (G).
 - 10:** A cable connecting the desktop tower (F) to the mouse (H).
 - 11:** A cable connecting the desktop tower (F) to the keyboard (I).

4.6 EUT Description

4.6.1 The following features describe EUT represented by this report:

Item	Specification	
Operating Temperature (°C)	-20 ~ +60	
Operating Humidity (%)	0 ~ 95	
Frequency Range	WCDMA B2	TX : 1 850 ~ 1 910 MHz RX : 1 930 ~ 1 990 MHz
	WCDMA B5	TX : 824 ~ 849 MHz RX : 869 ~ 894 MHz
	LTE B2	TX : 1 850 ~ 1 910 MHz RX : 1 930 ~ 1 990 MHz
	LTE B4	TX : 1 710 ~ 1 755 MHz RX : 2 110 ~ 2 155 MHz
	LTE B5	TX : 824 ~ 849 MHz RX : 869 ~ 894 MHz
	LTE B17	TX : 704 ~ 716 MHz RX : 734 ~ 746 MHz

4.6.2 The variant models

- None

4.7 Clock Frequencies

Kind of Clocks	Frequency [MHz]
CPU	1 600

4.8 Test configuration and condition

- ☐ The EUT exercise program which is the samsung standardized emission test program for Windows was used during all EMC measurements were tested. This program was contained on the PC hard disk drive. Once loaded, the program sequentially exercises each system component in turn.
- ☒ The EUT was exercised during the testing by data read and write cycles repeated with internal storage devices. At the end of the test, the copied back data was compared with original.
- ☐ The EUT was connected to the PC by using USB data cable to charge.
- ☐ The system was configured for testing in a typical fashion that a customer would normally use, and was tested while in an automated non-attendant mode.

Power source for the EUT operating was supplied by CVCF made by the Pacific Power Source Corp.

- Test Voltage : AC 120 V, 60 Hz

4.9 Measurement uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus: (According to CISPR 16-4 and UKAS Lab 34.)

4.9.1 Emission

Test type		Measurement uncertainty (C.L. 95 %, k = 2)
Conducted disturbance	AC Mains	±3.12 dB
Radiated Disturbance (30 MHz ~ 1 GHz)	Horizontal	±4.03 dB
	Vertical	±4.13 dB
Radiated Disturbance (1 GHz ~ 6 GHz)	Horizontal	±4.53 dB
	Vertical	±4.51 dB

5. Results of individual test

5.1 Conducted disturbance

The EUT was connected to the Desk-Top Computer which was powered from one LISN for the measurements. The support equipment power cables were connected to a second LISN.

Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration. The EUT measured in accordance with the methods described in standards.

Limits for conducted disturbance at the mains ports of Class B ITE

Frequency range Limits [MHz]	Resolution Bandwidth [kHz]	Limits [dB(μV)]	
		Quasi-peak	Average
0,15 to 0,50	9	66 to 56	56 to 46
0,50 to 5	9	56	46
5 to 30	9	60	50

NOTE 1 The lower limit shall apply at the transition frequency.
NOTE 2 The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

5.1.1 Test instrumentation


EMC No.	Test Instrument	Model name	Manufacturer	Serial No.	Calibration	
					Date	Interval (Month)
E5I-010	LISN	ESH3-Z5	R&S	100263	2013-10-17	12
E5I-016	EMI Test Receiver	ESU8	R&S	100482	2013-06-11	12
E5I-043	LISN	ENV216	R&S	101630	2013-06-07	12

5.1.2 Temperature and humidity condition

Test date	2013-10-24	Test engineer	Hee-Sung Kim
Climate condition	Ambient temperature	23.3 °C	Limit (15.0 to 35.0) °C
	relative humidity	41.2 % R.H.	Limit (25.0 to 75.0) % R.H.
	Atmospheric pressure	101.3 kPa	Limit (86.0 to 106.0) kPa
Test place	Shield Room (SR14)		

5.1.3 Test results

□ Operating Mode 1: AC Mains



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

Quasi-peak /Average final measurement results table:

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.472	---	28.4	46.5	18.1	L1	9.9
2.674	25.1	---	56.0	30.9	L1	9.7
2.795	26.1	---	56.0	29.9	L1	9.7
3.525	35.8	---	56.0	20.2	L1	9.7
3.525	---	29.1	46.0	16.9	L1	9.7
3.680	33.6	---	56.0	22.4	N	9.7
22.971	---	35.9	50.0	14.2	L1	9.9
23.318	37.8	---	60.0	22.3	L1	10.0
23.970	---	36.4	50.0	13.6	L1	10.0

Note 2) Level (QP and/or AV) = Meter Reading (QP and/or AV) + Corr. (LISN Insertion Loss + Cable Loss)
 Margin (QP and/or AV) = Limit – Level (QP and/or AV)
 QP = Quasi-Peak, AV = Average

5.2 Radiated disturbance

The following data lists the significant emission frequencies, measured levels, correction factors (for antenna and cables), orientation of table, polarization and height of antenna, the corrected reading, the limit, and the amount of margin.

Peak measurements were made over the changeable frequency range 30 MHz to 1 GHz at a measurement distance of 10 m for the following antenna and turntable arrangements:

Antenna Height [cm]	Antenna Polarisation	Resolution Bandwidth [kHz]	Video Bandwidth [kHz]	Turntable position [degrees]
100 ~ 400	Horizontal, Vertical	120	300	Continuous

Measurements within 6 dB of the limit were then maximized by adjusting turntable position. Final measurements were made using quasi-peak detectors.

Peak/RMS-Average measurements were made over the changeable frequency range 1 GHz to 40 GHz or 5th harmonics of the highest frequency in accordance with internal maximum operating frequency at a measurement distance of 3 m for the following antenna and turntable arrangements:

Antenna Height [cm]	Antenna Polarisation	Resolution Bandwidth [MHz]	Video Bandwidth [MHz]	Turntable position [degrees]
100 ~ 400	Horizontal, Vertical	1	3	0 ~ 345 (Step size: 15 degrees)

Measurements within 6 dB of the limit were then maximized by adjusting turntable position. Final measurements were made using peak and rms-average detectors.

Limits for radiated disturbance of Class B ITE at a measuring distance of 3 m and 10 m

Frequency range Limits [MHz]	Field Strength		
	3 m [$\mu\text{V/m}$]	3 m [dB($\mu\text{V/m}$)]	10 m [dB($\mu\text{V/m}$)]
30 to 88	100	40.0	29.5
88 to 216	150	43.5	33.0
216 to 960	200	46.0	35.5
Above 960	500	54.0	43.5

Results checked manually; and points close to the limit line were re-measured.

5.2.1 Test instrumentation

EMC No.	Test Instrument	Model name	Manufacturer	Serial No.	Calibration	
					Date	Interval (Month)
E5I-015	EMI Test Receiver	ESU8	R&S	100481	2013-06-11	12
E5I-020	EMI Test Receiver	ESU40	R&S	100375	2013-06-13	12
E5I-036	Double-Ridged Waveguide Horn Antenna	HF907	R&S	100507	2013-04-02	24
E5I-069	BiLOG Antenna	CBL6112D	Teseq	35382	2013-05-21	24
E5I-070	BiLOG Antenna	CBL6112D	Teseq	35383	2013-05-22	24
E5I-073	Preamplifier	310N	Sonoma	332016	2013-06-10	12
E5I-074	Preamplifier	310N	Sonoma	332017	2013-06-10	12


5.2.2 Temperature and humidity condition

Test date	2013-10-21	Test engineer	Hee-Sung Kim
Climate condition	Ambient temperature	23.0 °C	Limit (15.0 to 35.0) °C
	Relative humidity	47.1 % R.H.	Limit (25.0 to 75.0) % R.H.
	Atmospheric pressure	101.4 kPa	Limit (86.0 to 106.0) kPa
Test place	Semi-Anechoic Chamber (SAC8)		

5.2.3 Test results

☐ Operating Mode 1

- Frequency range: 30 ~ 1 000 MHz



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	System
1	40.496	V	34.7	-18.6	16.1	29.5	13.4	104	253	2
2	47.420	V	38.9	-22.2	16.7	29.5	12.8	100	241	2
3	92.675	V	38.9	-21.5	17.4	33.0	15.6	194	237	2
4	126.753	V	33.1	-18.5	14.6	33.0	18.4	108	33	2
5	141.989	V	31.8	-19.2	12.6	33.0	20.4	100	336	2
6	733.371	H	36.0	-8.7	27.3	35.5	8.2	100	221	1


Note) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 10 m, Antenna Height : 1 to 4 meters

Level (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak

- Frequency range: 1 000 ~ 8 000 MHz

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1 392.0	50.9	---	74.0	23.1	100.0	V	180.0	-7.8
1 560.0	49.6	---	74.0	24.4	100.0	V	180.0	-6.0
1 620.0	---	28.8	54.0	25.2	100.0	H	270.0	-6.1
2 151.5	---	32.5	54.0	21.5	100.0	H	270.0	-2.8
2 221.5	48.4	---	74.0	25.6	100.0	H	0.0	-2.7
2 296.0	---	31.0	54.0	23.0	100.0	V	90.0	-2.1
2 419.5	49.3	---	74.0	24.7	100.0	H	180.0	-1.4
2 494.5	---	35.3	54.0	18.7	100.0	H	270.0	-1.0
2 494.5	52.7	---	74.0	21.4	100.0	H	270.0	-1.0
5 459.5	49.9	---	74.0	24.1	100.0	H	270.0	11.1
7 621.0	52.2	---	74.0	21.8	100.0	H	270.0	16.7

Note) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or AV) = Reading (PK and/or AV) + corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or AV) = Limit – Level (PK and/or AV)

PK = Peak, AV = Average