



**FCC 47 CFR PART 15 SUBPART C
INDUSTRY CANADA RSS-210 ISSUE 8**

**CERTIFICATION TEST REPORT
FOR
Tablet with Bluetooth, DTS/UNII a/b/g/n, and ANT+**

MODEL NUMBER: SM-T350

FCC ID: A3LSMT350

IC ID: 649E-SMT350

**REPORT NUMBER: 15I19924-E1
ISSUE DATE: FEBRUARY 16, 2015**

Prepared for
**SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU
SUWON-CITY, GYEONGGI-DO 443-742, SOUTH KOREA**

Prepared by
**UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

Revision History

Issue			
Rev.	Date	Revisions	Revised By
--	2/16/15	Initial Issue	P. Zhang

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. MEASURING INSTRUMENT CALIBRATION	6
4.2. SAMPLE CALCULATION	7
4.3. MEASUREMENT UNCERTAINTY	7
5. EQUIPMENT UNDER TEST	8
5.1. DESCRIPTION OF EUT	8
5.2. MAXIMUM OUTPUT POWER.....	8
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	8
5.4. WORST-CASE CONFIGURATION AND MODE	9
5.5. DESCRIPTION OF TEST SETUP.....	10
6. TEST AND MEASUREMENT EQUIPMENT	12
7. SUMMARY TABLE	13
8. ANTENNA PORT TEST RESULTS	14
8.1. 20 dB AND 99% BANDWIDTH	14
8.1.1. BASIC DATA RATE GFSK MODULATION	14
8.1.2. ENHANCED DATA RATE 8PSK MODULATION	15
20 dB AND 99% BANDWIDTH PLOTS	16
8.2. HOPPING FREQUENCY SEPARATION	28
8.3. NUMBER OF HOPPING CHANNELS	30
8.4. AVERAGE TIME OF OCCUPANCY	35
8.5. OUTPUT POWER	43
8.5.1. BASIC DATA RATE GFSK MODULATION	43
8.5.2. ENHANCED DATA RATE 8PSK MODULATION	44
8.5.3. OUTPUT POWER PLOTS	45
8.6. AVERAGE POWER	51
8.6.1. BASIC DATA RATE GFSK MODULATION	51
8.6.2. DATA RATE PI/4-DQPSK MODULATION	52
8.6.3. ENHANCED DATA RATE 8PSK MODULATION	52
8.7. CONDUCTED SPURIOUS EMISSIONS	53
8.7.1. BASIC DATA RATE GFSK MODULATION	54

ENHANCED DATA RATE 8PSK MODULATION	62
9. RADIATED TEST RESULTS.....	70
9.1. LIMITS AND PROCEDURE	70
9.2. TRANSMITTER ABOVE 1 GHz	72
9.2.1. BASIC DATA RATE GFSK MODULATION	72
9.2.2. ENHANCED DATA RATE 8PSK MODULATION	85
9.3. WORST-CASE BELOW 1 GHz.....	98
10. AC POWER LINE CONDUCTED EMISSIONS	101
11. SETUP PHOTOS	106

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.

EUT DESCRIPTION: Tablet with Bluetooth, DTS/UNII a/b/g/n, and ANT+

MODEL: SM-T350

SERIAL NUMBER: 2044001 (Radiated), 2044002 (Conducted)

DATE TESTED: JANUARY 29 – FEBRUARY 6, 2015

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass
INDUSTRY CANADA RSS-210 ISSUE 8	Pass
INDUSTRY CANADA RSS-GEN ISSUE 4	Pass

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For

UL Verification Services Inc. By:

Tested By:



PENG ZHANG
CONSUMER TECHNOLOGY DIVISION
PROJECT LEAD
UL Verification Services Inc.

JONATHAN HSU
CONSUMER TECHNOLOGY DIVISION
LAB ENGINEER
UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15, RSS-GEN Issue 4, and RSS-210 Issue 8.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street
☐ Chamber A(IC: 2324B-1)	☐ Chamber D(IC: 2324B-4)
☒ Chamber B(IC: 2324B-2)	☐ Chamber E(IC: 2324B-5)
☐ Chamber C(IC: 2324B-3)	☐ Chamber F(IC: 2324B-6)
	☐ Chamber G(IC: 2324B-7)
	☐ Chamber H(IC: 2324B-8)

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://ts.nist.gov/standards/scopes/2000650.htm>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB)

36.5 dBuV + 18.7 dB/m + 0.6 dB – 26.9 dB = 28.9 dBuV/m

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 26000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a Tablet with Bluetooth, DTS/UNII a/b/g/n, and ANT+

The model FCC ID: A3LSMT350 shares the same enclosure and circuit board as mode FCC ID: A3LSMT355. The WLAN/Bluetooth circuitry and layout, including antenna, are almost identical between the two units. The WLAN/Bluetooth antenna and surrounding circuitry is the same between these two units.

Only Difference is WWAN antenna and surrounding circuitry is being removed.

After confirming through preliminary radiated emissions that the performance of the A3LSMT350 WLAN/Bluetooth data remains representative of this model (FCC ID: A3LSMT355). Test data for FCC ID: A3LSMT355 is being submitted for this application.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2402 - 2480	Basic GFSK	9.27	8.45
2402 - 2480	Enhanced 8PSK	9.68	9.29

Note: GFSK, Pi/4-DQPSK, 8PSK average Power are all investigated, The GFSK & 8PSK Power are the worst case. Testing is based on this mode to showing compliance. For average power data please refer to section 8.6.

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antenna, with a maximum gain of -0.5 dBi.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X,Y,Z, it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	SAMSUNG	SM-T355	N/A	N/A
Earphone	SAMSUNG	SM-T355	N/A	N/A

I/O CABLES


I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	1.2m	N/A
2	Audio	1	Mini-Jack	Unshielded	1m	N/A

TEST SETUP

The EUT is continuously communicating to the Bluetooth tester during the tests.

EUT was set in the Hidden menu mode to enable BT communications.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	Asset	Cal Due
Antenna, Biconolog, 30MHz-1 GHz	Sunol Sciences	JB1	C01171	02/13/15
Antenna, Horn, 18GHz	EMCO	3115	C00783	10/25/15
Antenna, Horn, 26.5 GHz	ARA	MWH-1826/B	C00980	11/14/15
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00580	04/03/15
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01052	10/22/15
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01069	12/20/15
CBT Bluetooth Tester	R & S	CBT	None	07/12/15
Peak Power Meter	Agilent / HP	E4416A	C00963	12/13/15
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	12/13/15
LISN, 30 MHz	FCC	50/250-25-2	C00626	01/14/16
Reject Filter, 2.4GHz	Micro-Tronics	BRM50702	N02684	CNR
Peak Power Meter	Agilent / HP	E4416A	C00963	12/13/15
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	12/13/15

Test Equipment List			
Description	Manufacturer	Model	Version
Radiated Software	UL	UL EMC	Version 9.5, 07/22/14
Conducted Software	UL	UL EMC	Version 9.5, 05/17/14
CLT Software	UL	UL RF	Version 1.0, 02/02/15
Antenna Port Software	UL	UL RF	Version 2.1.1.1, 1/20/15

7. SUMMARY TABLE

FCC Part Section	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Worst Case
2.1049	RSS-GEN 4.6	Occupied Band width (99%)	N/A	Conducted	Pass	1.1976 MHz
2.1051, 15.247 (d)	RSS-210 A8.5	Band Edge / Conducted Spurious Emission	-20dBc		Pass	-38.56 dBm
15.247 (b)(1)	RSS-210 A8.4	TX conducted output power	<21dBm		Pass	9.68 dBm
15.247 (a)(1)	RSS-210 A8.1(b)	Hopping frequency separation	> 25KHz		Pass	1 MHz
15.247 (a)(1)(iii)	RSS-210 A8.1(d)	Number of Hopping channels	More than 15 non-overlapping channels		Pass	79
15.247 (a)(1)(iii)	RSS-210 A8.1(d)	Avg Time of Occupancy	< 0.4sec		Pass	0.3731 sec
15.207 (a)	RSS-GEN 7.2.2	AC Power Line conducted emissions	Section 10	Radiated	Pass	48.48dBuV(PK)
15.205, 15.209	RSS-210 Clause 2.6, RSS-210 Clause 6	Radiated Spurious Emission	< 54dBuV/m		Pass	39.44 dBuV/m

8. ANTENNA PORT TEST RESULTS

8.1. 20 dB AND 99% BANDWIDTH

LIMIT

None; for reporting purposes only.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer. The RBW is set to $\geq 1\%$ of the 20 dB bandwidth. The VBW is set to $\geq$ RBW. The sweep time is coupled.

RESULTS

8.1.1. BASIC DATA RATE GFSK MODULATION


Channel	Frequency (MHz)	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	2402	0.919	0.864
Middle	2441	0.923	0.909
High	2480	0.924	0.885
Worst		0.924	0.909

8.1.2. ENHANCED DATA RATE 8PSK MODULATION


Channel	Frequency (MHz)	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	2402	1.208	1.162
Middle	2441	1.262	1.1858
High	2480	1.263	1.1976
Worst		1.263	1.1976

20 dB AND 99% BANDWIDTH PLOTS


GFSK 20 dB BANDWIDTH



MID CHANNEL




HIGH CHANNEL




GFSK 99% BANDWIDTH


LOW CHANNEL



MID CHANNEL




HIGH CHANNEL




8PSK 20 dB BANDWIDTH


LOW CHANNEL



MID CHANNEL




HIGH CHANNEL




8PSK 99% BANDWIDTH


LOW CHANNEL



MID CHANNEL



HIGH CHANNEL



8.2. HOPPING FREQUENCY SEPARATION

LIMIT

FCC §15.247 (a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer. The RBW is set to 300 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

RESULTS

HOPPING FREQUENCY SEPARATION PLOT



8.3. NUMBER OF HOPPING CHANNELS

LIMIT

FCC §15.247 (a) (1) (iii)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.

TEST PROCEDURE


DA 00-705: The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to a maximum of 1 % of the span. The analyzer is set to Max Hold.

RESULTS


Normal Mode: 79 Channels observed.

NUMBER OF HOPPING CHANNELS PLOTS


NUMBER OF HOPPING CHANNELS (100 MHZ SPAN)




NUMBER OF HOPPING CHANNELS (30 MHZ SPAN, FIRST SEGMENT)



NUMBER OF HOPPING CHANNELS (30 MHZ SPAN, SECOND SEGMENT)



NUMBER OF HOPPING CHANNELS (30 MHZ SPAN, THIRD SEGMENT)



8.4. AVERAGE TIME OF OCCUPANCY

LIMIT

FCC §15.247 (a) (1) (iii)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.


The average time of occupancy in the specified 31.6 second period (79 channels * 0.4 s) is equal to 10 * (# of pulses in 3.16 s) * pulse width.

For AFH mode, the average time of occupancy in the specified 8 second period (20 channels * 0.4 seconds) is equal to 10 * (# of pulses in 0.8 s) * pulse width.


RESULTS

DH Packet	Pulse Width (msec)	Number of Pulses in 3.16 seconds	Average Time of Occupancy (sec)	Limit (sec)	Margin (sec)
GFSK Normal Mode					
DH1	0.378	30	0.1134	0.4	-0.2866
DH3	1.635	16	0.2616	0.4	-0.1384
DH5	2.87	13	0.3731	0.4	-0.0269
DH Packet	Pulse Width (msec)	Number of Pulses in 0.8 seconds	Average Time of Occupancy (sec)	Limit (sec)	Margin (sec)
GFSK AFH Mode					
DH1	0.378	7.5	0.02835	0.4	-0.37165
DH3	1.635	4	0.0654	0.4	-0.3346
DH5	2.87	3.25	0.093275	0.4	-0.30673


PULSE WIDTH - DH1




NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD - DH1




PULSE WIDTH - DH3




NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD - DH3



PULSE WIDTH - DH5



NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD - DH5



8.5. OUTPUT POWER

LIMIT

§15.247 (b) (1)

The maximum antenna gain is less than 6 dBi, therefore the limit is 21 dBm.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.

RESULTS

8.5.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Margin (dB)
Low	2402	9.27	21	-11.73
Middle	2441	8.77	21	-12.23
High	2480	9.18	21	-11.82
Worst		9.27		-11.73


8.5.2. ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Margin (dB)
Low	2402	9.68	21	-11.32
Middle	2441	9	21	-12
High	2480	9.59	21	-11.41
Worst		9.68		-11.32


8.5.3. OUTPUT POWER PLOTS

GFSK OUTPUT POWER


LOW CHANNEL



MID CHANNEL




HIGH CHANNEL




8PSK OUTPUT POWER


LOW CHANNEL



MID CHANNEL



HIGH CHANNEL



8.6. AVERAGE POWER

LIMIT

None; for reporting purposes only.

TEST PROCEDURE

DA 00-705: The transmitter output is connected to a power meter.

RESULTS

The cable assembly insertion loss of 10.7 dB (including 10 dB pad and 0.7 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

8.6.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency (MHz)	Average Power (dBm)
Low	2402	9.2
Middle	2441	8.6
High	2480	9.1
Worst		9.2

8.6.2. DATA RATE PI/4-DQPSK MODULATION

Channel	Frequency (MHz)	Average Power (dBm)
Low	2402	8.20
Middle	2441	7.60
High	2480	7.80
Worst		8.20

8.6.3. ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency (MHz)	Average Power (dBm)
Low	2402	8.2
Middle	2441	7.6
High	2480	7.8
Worst		8.2

8.7. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

Limit = -20 dBc

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

The bandedges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal hopping mode.


RESULTS

8.7.1. BASIC DATA RATE GFSK MODULATION


SPURIOUS EMISSIONS, LOW CHANNEL




LOW CHANNEL SPURIOUS




SPURIOUS EMISSIONS, MID CHANNEL




MID CHANNEL SPURIOUS



SPURIOUS EMISSIONS, HIGH CHANNEL




HIGH CHANNEL SPURIOUS




SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON

LOW BANDEDGE WITH HOPPING ON




HIGH BANDEDGE WITH HOPPING ON




ENHANCED DATA RATE 8PSK MODULATION

SPURIOUS EMISSIONS, LOW CHANNEL

LOW CHANNEL BANDEDGE




LOW CHANNEL SPURIOUS




SPURIOUS EMISSIONS, MID CHANNEL


MID CHANNEL BANDEDGE




MID CHANNEL SPURIOUS



SPURIOUS EMISSIONS, HIGH CHANNEL




HIGH CHANNEL SPURIOUS




SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON

LOW BANDEDGE WITH HOPPING ON



HIGH BANDEDGE WITH HOPPING ON



9. RADIATED TEST RESULTS

9.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

IC RSS-GEN Clause 8.9 (Transmitter)

IC RSS-GEN Clause 7 (Receiver)

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For band edge measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 1/T (on time) for average measurement.

GFSK = $1/T = 1 / 0.001633 \text{ S} = 612\text{Hz}$.

The spectrum from 1GHzHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.


The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

9.2. TRANSMITTER ABOVE 1 GHz

9.2.1. BASIC DATA RATE GFSK MODULATION

RESTRICTED BANDEDGE (LOW CHANNEL)


HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/ Fitr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	38.94	PK	32.1	-22.6	48.44	-	-	74	-25.56	164	108	H
2	* 2.322	41.72	PK	31.7	-22.7	50.72	-	-	74	-23.28	164	108	H
3	* 2.39	28.32	VB1T	32.1	-22.6	37.82	54	-16.18	-	-	164	108	H
4	* 2.388	28.82	VB1T	32.1	-22.6	38.32	54	-15.68	-	-	164	108	H

VERTICAL PEAK AND AVERAGE PLOT




VERTICAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/ Filt/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	38	PK	32.1	-22.6	47.5	-	-	74	-26.5	297	207	V
2	* 2.377	41.21	PK	32	-22.6	50.61	-	-	74	-23.39	297	207	V
3	* 2.39	28.5	VB1T	32.1	-22.6	38	54	-16	-	-	297	207	V
4	* 2.387	28.81	VB1T	32.1	-22.6	38.31	54	-15.69	-	-	297	207	V

AUTHORIZED BANDEDGE (HIGH CHANNEL)


HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/ Filt/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	38.88	PK	32.4	-22.4	48.88	-	-	74	-25.12	336	272	H
2	* 2.484	43.01	PK	32.4	-22.4	53.01	-	-	74	-20.99	336	272	H
3	* 2.484	29.4	VB1T	32.4	-22.4	39.4	54	-14.6	-	-	336	272	H
4	* 2.484	29.44	VB1T	32.4	-22.4	39.44	54	-14.56	-	-	336	272	H


VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/ Filt/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	38.45	PK	32.4	-22.4	48.45	-	-	74	-25.55	336	274	V
3	* 2.484	28.78	VB1T	32.4	-22.4	38.78	54	-15.22	-	-	336	274	V
2	* 2.499	41.26	PK	32.4	-22.4	51.26	-	-	74	-22.74	336	274	V
4	2.515	28.77	VB1T	32.5	-22.3	38.97	54	-15.03	-	-	336	274	V

HARMONICS AND SPURIOUS EMISSIONS



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA


TRACE MARKERS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.781	35.26	PK	30	-23.3	41.96	-	-	-	-	0-360	101	H
2	1.946	34.99	PK	31.2	-23.2	42.99	-	-	-	-	0-360	200	H
3	2.123	34.83	PK	31.3	-23	43.13	-	-	-	-	0-360	101	V
4	3.175	33.27	PK	32.8	-30.8	35.27	-	-	-	-	0-360	101	H
5	6.51	31.28	PK	35.7	-28.3	38.68	-	-	-	-	0-360	199	V
6	9.687	28.39	PK	36.9	-23.6	41.69	-	-	-	-	0-360	199	V

PK - Peak detector


FCC Part15 Subpart C T186 2400MHz Spurious Emissions.TST 12746Rev 9.5 12 Jun 2013

MID CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA


TRACE MARKERS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.157	37.8	PK	27.8	-24.3	41.3	-	-	74	-32.7	0-360	200	V
4	* 3.521	34.66	PK	32.9	-31.1	36.46	-	-	74	-37.54	0-360	199	H
2	1.814	36.64	PK	30.3	-23.3	43.64	-	-	-	-	0-360	200	V
3	2.072	35.17	PK	31.3	-23.1	43.37	-	-	-	-	0-360	200	H
5	6.639	32.07	PK	35.7	-28.2	39.57	-	-	-	-	0-360	101	V
6	9.68	29.16	PK	36.8	-23.6	42.36	-	-	-	-	0-360	101	V

PK - Peak detector


FCC Part15 Subpart C T186 2400MHz Spurious Emissions.TST 12746Rev 9.5 12 Jun 2013

HIGH CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

TRACE MARKERS


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.277	35.24	PK	28.7	-24.2	39.74	-	-	74	-34.26	0-360	200	V
2	* 1.719	34.89	PK	29.3	-23.4	40.79	-	-	74	-33.21	0-360	101	V
3	2.082	35.4	PK	31.3	-23.1	43.6	-	-	-	-	0-360	101	H
4	3.467	32.31	PK	32.8	-30.7	34.41	-	-	-	-	0-360	199	H
5	6.004	32.64	PK	35.3	-28.8	39.14	-	-	-	-	0-360	199	H
6	10.18	28.21	PK	37.1	-23.4	41.91	-	-	-	-	0-360	199	V

PK - Peak detector

FCC Part15 Subpart C T186 2400MHz Spurious Emissions.TST 12746Rev 9.5 12 Jun 2013

9.2.2. ENHANCED DATA RATE 8PSK MODULATION RESTRICTED BANDEDGE (LOW CHANNEL)


HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cb/ Fitr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	38.67	PK	32.1	-22.6	48.17	-	-	74	-25.83	164	108	H
2	* 2.361	41.42	PK	31.9	-22.6	50.72	-	-	74	-23.28	164	108	H
3	* 2.39	28.28	VB1T	32.1	-22.6	37.78	54	-16.22	-	-	164	108	H
4	* 2.386	28.75	VB1T	32.1	-22.6	38.25	54	-15.75	-	-	164	108	H

VERTICAL PEAK AND AVERAGE PLOT




VERTICAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/ Fitr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	38.55	PK	32.1	-22.6	48.05	-	-	74	-25.95	297	207	V
2	* 2.338	42.02	PK	31.8	-22.7	51.12	-	-	74	-22.88	297	207	V
3	* 2.39	28.43	VB1T	32.1	-22.6	37.93	54	-16.07	-	-	297	207	V
4	* 2.388	28.85	VB1T	32.1	-22.6	38.35	54	-15.65	-	-	297	207	V

AUTHORIZED BANDEDGE (HIGH CHANNEL)


HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cb/ Fitr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	40.21	PK	32.4	-22.4	50.21	-	-	74	-23.79	336	272	H
3	* 2.484	29.14	VB1T	32.4	-22.4	39.14	54	-14.86	-	-	336	272	H
4	2.521	28.92	VB1T	32.5	-22.3	39.12	54	-14.88	-	-	336	272	H
2	2.522	41.57	PK	32.5	-22.3	51.77	-	-	74	-22.23	336	272	H


VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/ Fitr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	38.23	PK	32.4	-22.4	48.23	-	-	74	-25.77	336	274	V
3	* 2.484	28.71	VB1T	32.4	-22.4	38.71	54	-15.29	-	-	336	274	V
4	* 2.484	29.16	VB1T	32.4	-22.4	39.16	54	-14.84	-	-	336	274	V
2	2.56	41.84	PK	32.5	-22.4	51.94	-	-	74	-22.06	336	274	V

HARMONICS AND SPURIOUS EMISSIONS



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

TRACE MARKERS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.266	35.83	PK	28.6	-24.2	40.23	-	-	74	-33.77	0-360	101	V
2	1.716	41.03	PK	29.2	-23.4	46.83	-	-	-	-	0-360	101	V
3	2.111	35.43	PK	31.3	-23	43.73	-	-	-	-	0-360	101	V
4	3.282	32.84	PK	32.8	-30.9	34.74	-	-	-	-	0-360	199	V
5	5.798	32.1	PK	34.7	-29.7	37.1	-	-	-	-	0-360	101	V
6	9.726	28.38	PK	36.9	-23.7	41.58	-	-	-	-	0-360	199	V


PK - Peak detector

RADIATED EMISSIONS

Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/Filtr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1.716	30.58	VB1T	29.2	-23.4	36.38	-	-	-	-	17	102	V
1.718	43.22	PK3	29.2	-23.4	49.02	-	-	-	-	17	102	V


FCC Part15 Subpart C T186 2400MHz Spurious Emissions.TST 12746Rev 9.5 12 Jun 2013

MID CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA


TRACE MARKERS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.314	36.09	PK	28.8	-24.2	40.69	-	-	74	-33.31	0-360	199	H
2	1.736	35.13	PK	29.4	-23.4	41.13	-	-	-	-	0-360	101	H
3	2.107	34.76	PK	31.2	-23	42.96	-	-	-	-	0-360	199	H
4	3.282	32.84	PK	32.8	-30.9	34.74	-	-	-	-	0-360	199	V
5	5.798	32.1	PK	34.7	-29.7	37.1	-	-	-	-	0-360	101	V
6	9.726	28.38	PK	36.9	-23.7	41.58	-	-	-	-	0-360	199	V

PK - Peak detector


FCC Part15 Subpart C T186 2400MHz Spurious Emissions.TST 12746Rev 9.5 12 Jun 2013

HIGH CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

TRACE MARKERS


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.141	36.79	PK	27.7	-24.3	40.19	-	-	74	-33.81	0-360	101	V
2	* 1.681	36.1	PK	28.9	-23.5	41.5	-	-	74	-32.5	0-360	101	V
3	2.1	35.47	PK	31.2	-23.1	43.57	-	-	-	-	0-360	101	H
4	3.324	33.51	PK	32.8	-30.9	35.41	-	-	-	-	0-360	199	V
5	5.924	31.39	PK	35	-28.5	37.89	-	-	-	-	0-360	101	V
6	10.282	28.37	PK	37.2	-23.3	42.27	-	-	-	-	0-360	199	H

PK - Peak detector


FCC Part15 Subpart C T186 2400MHz Spurious Emissions.TST 12746Rev 9.5 12 Jun 2013

9.3. WORST-CASE BELOW 1 GHz

GFSK SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)



VERTICAL PLOT



BELOW 1 GHz TABLE

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	AF T243 (dB/m)	Amp/Cbl (dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
3	* 108.54	36.71	PK	12.3	-28	21.01	43.52	-22.51	0-360	300	H
6	* 243.4	39.27	PK	11.6	-26.5	24.37	46.02	-21.65	0-360	200	V
4	157.5	38.19	PK	12.3	-27.4	23.09	43.52	-20.43	0-360	100	H
5	186.145	38.95	PK	11.3	-27.1	23.15	43.52	-20.37	0-360	400	H
1	41.135	41.81	PK	13.2	-28.8	26.21	40	-13.79	0-360	101	V
7	556	35.3	PK	18.6	-25.5	28.4	46.02	-17.62	0-360	200	H
2	56.01	54.22	PK	7.3	-28.6	32.92	40	-7.08	0-360	101	V
8	705.2	42.4	PK	20.2	-24.5	38.1	46.02	-7.92	0-360	101	V

PK - Peak detector

10. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

RSS-Gen 8.8

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 [*]	56 to 46 [*]
0.5-5	56	46
5-30	60	50

^{*} Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.4.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

6 WORST EMISSIONS

LINE 1 PLOT




LINE 1 RESULTS

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	T24 IL L1 (dB)	LC Cables 1&3 (dB)	Corrected Reading dBuV	CISPR 22 Class B QP	Margin to Limit (dB)	CISPR 22 Class B Avg	Margin to Limit (dB)
1	.168	32.42	PK	1.2	0	33.62	65.1	-31.48	-	-
2	.168	13.17	Av	1.2	0	14.37	-	-	55.1	-40.73
3	.3165	31.97	PK	.5	0	32.47	59.8	-27.33	-	-
4	.3165	16.65	Av	.5	0	17.15	-	-	49.8	-32.65
5	.474	37.91	PK	.4	0	38.31	56.4	-18.09	-	-
6	.474	27.87	Av	.4	0	28.27	-	-	46.4	-18.13
7	.897	40.68	PK	.3	.1	41.08	56	-14.92	-	-
8	.897	21.23	Av	.3	.1	21.63	-	-	46	-24.37
9	1.284	36.35	PK	.2	.1	36.65	56	-19.35	-	-
10	1.284	18.45	Av	.2	.1	18.75	-	-	46	-27.25
11	3.9345	41.33	PK	.2	.1	41.63	56	-14.37	-	-
12	3.9345	28.46	Av	.2	.1	28.76	-	-	46	-17.24
13	6.27	42.51	PK	.2	.1	42.81	60	-17.19	-	-
14	6.27	26.15	Av	.2	.1	26.45	-	-	50	-23.55
15	12.408	35.35	PK	.2	.2	35.75	60	-24.25	-	-
16	12.408	19.77	Av	.2	.2	20.17	-	-	50	-29.83
17	17.8215	36.22	PK	.3	.2	36.72	60	-23.28	-	-
18	17.8215	22.41	Av	.3	.2	22.91	-	-	50	-27.09

LINE 2 PLOT



LINE 2 RESULTS

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	T24 IL L2 (dB)	LC Cables 2&3 (dB)	Corrected Reading dBuV	CISPR 22 Class B QP	Margin to Limit (dB)	CISPR 22 Class B Avg	Margin to Limit (dB)
19	.1725	36.71	PK	1.2	0	37.91	64.8	-26.89	-	-
20	.1725	13.66	Av	1.2	0	14.86	-	-	54.8	-39.94
21	.285	31.35	PK	.6	0	31.95	60.7	-28.75	-	-
22	.285	11.18	Av	.6	0	11.78	-	-	50.7	-38.92
23	.3435	33.41	PK	.5	0	33.91	59.1	-25.19	-	-
24	.3435	13.52	Av	.5	0	14.02	-	-	49.1	-35.08
25	.5145	37.36	PK	.4	0	37.76	56	-18.24	-	-
26	.5145	14.66	Av	.4	0	15.06	-	-	46	-30.94
27	.7485	48.18	PK	.3	0	48.48	56	-7.52	-	-
28	.7485	14.97	Av	.3	0	15.27	-	-	46	-30.73
29	3.3135	37.66	PK	.2	.1	37.96	56	-18.04	-	-
30	3.3135	20.68	Av	.2	.1	20.98	-	-	46	-25.02
31	8.079	40.91	PK	.2	.1	41.21	60	-18.79	-	-
32	8.079	21.55	Av	.2	.1	21.85	-	-	50	-28.15
33	13.506	36.02	PK	.2	.2	36.42	60	-23.58	-	-
34	13.506	19.6	Av	.2	.2	20	-	-	50	-30
35	16.3095	39.13	PK	.3	.2	39.63	60	-20.37	-	-
36	16.3095	19.57	Av	.3	.2	20.07	-	-	50	-29.93