GSM 1900

GSM

GSM1900
GPRS

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-13-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Earphone, Z Position
Mode: GPRS 1900 MHz

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 24

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1850.2MHz									
3.7004	-11.9	V	3.0	39.7	1.0	-50.6	-13.0	-37.6	
5.5506	0.0	V	3.0	39.9	1.0	-39.0	-13.0	-26.0	
7.4008	-10.0	V	3.0	39.4	1.0	-48.4	-13.0	-35.4	
3.7004	-13.9	H	3.0	39.7	1.0	-52.5	-13.0	-39.5	
5.5506	-3.6	H	3.0	39.9	1.0	-42.6	-13.0	-29.6	
7.4008	-7.6	H	3.0	39.4	1.0	-46.1	-13.0	-33.1	
Mid Ch, 1880.0MHz									
3.7600	-10.9	V	3.0	39.7	1.0	-49.6	-13.0	-36.6	
5.6400	-1.0	V	3.0	40.0	1.0	-40.0	-13.0	-27.0	
7.5200	-8.7	V	3.0	39.4	1.0	-47.1	-13.0	-34.1	
3.7600	-10.7	H	3.0	39.7	1.0	-49.4	-13.0	-36.4	
5.6400	-6.9	H	3.0	40.0	1.0	-45.9	-13.0	-32.9	
7.5200	-7.8	H	3.0	39.4	1.0	-46.2	-13.0	-33.2	
High Ch, 1909.8 MHz									
3.8196	-9.9	V	3.0	39.7	1.0	-48.6	-13.0	-35.6	
5.7294	-4.8	V	3.0	40.0	1.0	-43.8	-13.0	-30.8	
7.6392	-7.0	V	3.0	39.3	1.0	-45.3	-13.0	-32.3	
3.8196	-10.9	H	3.0	39.7	1.0	-49.7	-13.0	-36.7	
5.7294	-6.3	H	3.0	40.0	1.0	-45.3	-13.0	-32.3	
7.6392	-7.9	H	3.0	39.3	1.0	-46.2	-13.0	-33.2	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

GSM

GSM1900
EGPRS

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-13-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Earphone, Z Position
Mode: EGPRS 1900 MHz

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 24

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1850.2MHz									
3.7004	-12.4	V	3.0	39.7	1.0	-51.1	-13.0	-38.1	
5.5506	0.3	V	3.0	39.9	1.0	-38.6	-13.0	-25.6	
7.4008	-10.2	V	3.0	39.4	1.0	-48.6	-13.0	-35.6	
3.7004	-14.8	H	3.0	39.7	1.0	-53.5	-13.0	-40.5	
5.5506	-5.0	H	3.0	39.9	1.0	-43.9	-13.0	-30.9	
7.4008	-8.4	H	3.0	39.4	1.0	-46.8	-13.0	-33.8	
Mid Ch, 1880.0MHz									
3.7600	-11.6	V	3.0	39.7	1.0	-50.3	-13.0	-37.3	
5.6400	-3.0	V	3.0	40.0	1.0	-42.0	-13.0	-29.0	
7.5200	-10.4	V	3.0	39.4	1.0	-48.8	-13.0	-35.8	
3.7600	-11.6	H	3.0	39.7	1.0	-50.3	-13.0	-37.3	
5.6400	-6.3	H	3.0	40.0	1.0	-45.2	-13.0	-32.2	
7.5200	-8.4	H	3.0	39.4	1.0	-46.7	-13.0	-33.7	
High Ch, 1909.8 MHz									
3.8196	-11.1	V	3.0	39.7	1.0	-49.8	-13.0	-36.8	
5.7294	-6.3	V	3.0	40.0	1.0	-45.3	-13.0	-32.3	
7.6392	-7.8	V	3.0	39.3	1.0	-46.1	-13.0	-33.1	
3.8196	-12.6	H	3.0	39.7	1.0	-51.3	-13.0	-38.3	
5.7294	-7.1	H	3.0	40.0	1.0	-46.1	-13.0	-33.1	
7.6392	-9.2	H	3.0	39.3	1.0	-47.5	-13.0	-34.5	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

WCDMA Band 5

WCDMA

Band 5
REL99

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-20-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Earphone / X Position
Mode: Tx, REL99,850MHz

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 22

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 826.40MHz									
1.6520	-16.7	V	3.0	38.2	1.0	-54.0	-13.0	-41.0	
2.4790	-14.2	V	3.0	38.8	1.0	-52.0	-13.0	-39.0	
3.3056	-12.3	V	3.0	39.4	1.0	-50.7	-13.0	-37.7	
1.6520	-15.7	H	3.0	38.2	1.0	-53.0	-13.0	-40.0	
2.4790	-14.1	H	3.0	38.8	1.0	-51.9	-13.0	-38.9	
3.3056	-13.4	H	3.0	39.4	1.0	-51.8	-13.0	-38.8	
Mid Ch, 836.6MHz									
1.6732	-16.5	V	3.0	38.2	1.0	-53.8	-13.0	-40.8	
2.5098	-15.1	V	3.0	38.8	1.0	-52.9	-13.0	-39.9	
3.3464	-13.2	V	3.0	39.5	1.0	-51.7	-13.0	-38.7	
1.6732	-15.2	H	3.0	38.2	1.0	-52.4	-13.0	-39.4	
2.5098	-14.8	H	3.0	38.8	1.0	-52.6	-13.0	-39.6	
3.3464	-12.7	H	3.0	39.5	1.0	-51.2	-13.0	-38.2	
High Ch, 846.6MHz									
1.6932	-17.0	V	3.0	38.2	1.0	-54.3	-13.0	-41.3	
2.5390	-15.5	V	3.0	38.9	1.0	-53.4	-13.0	-40.4	
3.3860	-13.9	V	3.0	39.5	1.0	-52.4	-13.0	-39.4	
1.6932	-14.7	H	3.0	38.2	1.0	-51.9	-13.0	-38.9	
2.5390	-15.7	H	3.0	38.9	1.0	-53.5	-13.0	-40.5	
3.3860	-13.1	H	3.0	39.5	1.0	-51.6	-13.0	-38.6	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

WCDMA

Band 5
HSDPA

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-20-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Earphone / X Position
Mode: Tx, HSDPA,850MHz

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 22

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 826.40MHz									
1.6520	-17.1	V	3.0	38.2	1.0	-54.3	-13.0	-41.3	
2.4790	-14.8	V	3.0	38.8	1.0	-52.6	-13.0	-39.6	
3.3056	-13.2	V	3.0	39.4	1.0	-51.7	-13.0	-38.7	
1.6520	-15.9	H	3.0	38.2	1.0	-53.2	-13.0	-40.2	
2.4790	-15.2	H	3.0	38.8	1.0	-53.0	-13.0	-40.0	
3.3056	-13.7	H	3.0	39.4	1.0	-52.1	-13.0	-39.1	
Mid Ch, 836.6MHz									
1.6732	-16.7	V	3.0	38.2	1.0	-54.0	-13.0	-41.0	
2.5098	-14.2	V	3.0	38.8	1.0	-52.0	-13.0	-39.0	
3.3464	-13.0	V	3.0	39.5	1.0	-51.5	-13.0	-38.5	
1.6732	-15.3	H	3.0	38.2	1.0	-52.5	-13.0	-39.5	
2.5098	-14.5	H	3.0	38.8	1.0	-52.4	-13.0	-39.4	
3.3464	-12.9	H	3.0	39.5	1.0	-51.3	-13.0	-38.3	
High Ch, 846.6MHz									
1.6932	-16.0	V	3.0	38.2	1.0	-53.2	-13.0	-40.2	
2.5390	-15.5	V	3.0	38.9	1.0	-53.4	-13.0	-40.4	
3.3860	-13.6	V	3.0	39.5	1.0	-52.1	-13.0	-39.1	
1.6932	-14.7	H	3.0	38.2	1.0	-52.0	-13.0	-39.0	
2.5390	-15.7	H	3.0	38.9	1.0	-53.6	-13.0	-40.6	
3.3860	-13.7	H	3.0	39.5	1.0	-52.2	-13.0	-39.2	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

WCDMA Band 2

WCDMA

Band 2
REL99

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-14-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Earphone / Z Position
Mode: Tx, REL99,1900MHz

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 24

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1852.4MHz									
3.7048	-10.8	V	3.0	39.7	1.0	-49.4	-13.0	-36.4	
5.5572	-11.5	V	3.0	39.9	1.0	-50.4	-13.0	-37.4	
7.4096	-8.3	V	3.0	39.4	1.0	-46.7	-13.0	-33.7	
3.7048	-3.4	H	3.0	39.7	1.0	-42.1	-13.0	-29.1	
5.5572	-12.0	H	3.0	39.9	1.0	-50.9	-13.0	-37.9	
7.4096	-1.6	H	3.0	39.4	1.0	-40.0	-13.0	-27.0	
Mid Ch, 1880MHz									
3.7600	-9.5	V	3.0	39.7	1.0	-48.2	-13.0	-35.2	
5.6400	-11.8	V	3.0	40.0	1.0	-50.8	-13.0	-37.8	
7.5200	-1.7	V	3.0	39.4	1.0	-40.1	-13.0	-27.1	
3.7600	-5.7	H	3.0	39.7	1.0	-44.4	-13.0	-31.4	
5.6400	-10.1	H	3.0	40.0	1.0	-49.1	-13.0	-36.1	
7.5200	-2.2	H	3.0	39.4	1.0	-40.6	-13.0	-27.6	
High Ch, 1907.6MHz									
3.8152	-7.6	V	3.0	39.7	1.0	-46.3	-13.0	-33.3	
5.7228	-11.0	V	3.0	40.0	1.0	-50.0	-13.0	-37.0	
7.6304	-9.6	V	3.0	39.3	1.0	-48.0	-13.0	-35.0	
3.8152	-5.2	H	3.0	39.7	1.0	-43.9	-13.0	-30.9	
5.7228	-5.5	H	3.0	40.0	1.0	-44.5	-13.0	-31.5	
7.6304	-3.0	H	3.0	39.3	1.0	-41.4	-13.0	-28.4	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

WCDMA

Band 2
HSDPA

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-14-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Earphone / Z Position
Mode: Tx, HSDPA,1900MHz

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 24

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1852.4MHz									
3.7048	-9.9	V	3.0	39.7	1.0	-48.6	-13.0	-35.6	
5.5572	-11.2	V	3.0	39.9	1.0	-50.2	-13.0	-37.2	
7.4096	-8.0	V	3.0	39.4	1.0	-46.4	-13.0	-33.4	
3.7048	-1.8	H	3.0	39.7	1.0	-40.5	-13.0	-27.5	
5.5572	-11.5	H	3.0	39.9	1.0	-50.4	-13.0	-37.4	
7.4096	-1.6	H	3.0	39.4	1.0	-40.0	-13.0	-27.0	
Mid Ch, 1880MHz									
3.7600	-10.7	V	3.0	39.7	1.0	-49.4	-13.0	-36.4	
5.6400	-10.9	V	3.0	40.0	1.0	-49.9	-13.0	-36.9	
7.5200	-3.5	V	3.0	39.4	1.0	-41.8	-13.0	-28.8	
3.7600	-4.5	H	3.0	39.7	1.0	-43.2	-13.0	-30.2	
5.6400	-9.4	H	3.0	40.0	1.0	-48.4	-13.0	-35.4	
7.5200	-2.0	H	3.0	39.4	1.0	-40.4	-13.0	-27.4	
High Ch, 1907.6MHz									
3.8152	-9.7	V	3.0	39.7	1.0	-48.4	-13.0	-35.4	
5.7228	-10.6	V	3.0	40.0	1.0	-49.6	-13.0	-36.6	
7.6304	-10.1	V	3.0	39.3	1.0	-48.5	-13.0	-35.5	
3.8152	-5.1	H	3.0	39.7	1.0	-43.9	-13.0	-30.9	
5.7228	-6.8	H	3.0	40.0	1.0	-45.8	-13.0	-32.8	
7.6304	-3.0	H	3.0	39.3	1.0	-41.3	-13.0	-28.3	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 5

LTE

Band 5

10MHz

QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-25-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Earphone, X Position
Mode: TX, LTE BAND 5, 10MHz BW,QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 22

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Channel (829MHz)									
1.6580	-2.6	V	3.0	38.2	1.0	-39.8	-13.0	-26.8	
2.4870	-14.1	V	3.0	38.8	1.0	-51.9	-13.0	-38.9	
3.3160	-8.7	V	3.0	39.4	1.0	-47.1	-13.0	-34.1	
4.1450	-3.4	V	3.0	39.8	1.0	-42.2	-13.0	-29.2	
4.9740	-10.1	V	3.0	39.8	1.0	-48.9	-13.0	-35.9	
1.6580	-8.6	H	3.0	38.2	1.0	-45.8	-13.0	-32.8	
2.4870	-14.8	H	3.0	38.8	1.0	-52.6	-13.0	-39.6	
3.3160	-10.0	H	3.0	39.4	1.0	-48.4	-13.0	-35.4	
4.1450	-5.5	H	3.0	39.8	1.0	-44.3	-13.0	-31.3	
4.9740	-12.1	H	3.0	39.8	1.0	-50.9	-13.0	-37.9	
Mid Channel (836.5MHz)									
1.6730	-2.6	V	3.0	38.2	1.0	-39.8	-13.0	-26.8	
2.5095	-11.7	V	3.0	38.8	1.0	-49.5	-13.0	-36.5	
3.3460	-9.3	V	3.0	39.5	1.0	-47.7	-13.0	-34.7	
4.1825	-1.5	V	3.0	39.8	1.0	-40.3	-13.0	-27.3	
5.0190	-9.2	V	3.0	39.8	1.0	-48.0	-13.0	-35.0	
1.6730	-14.2	H	3.0	38.2	1.0	-51.5	-13.0	-38.5	
2.5095	-12.9	H	3.0	38.8	1.0	-50.7	-13.0	-37.7	
3.3460	-10.3	H	3.0	39.5	1.0	-48.7	-13.0	-35.7	
4.1825	-6.3	H	3.0	39.8	1.0	-45.1	-13.0	-32.1	
5.0190	-10.6	H	3.0	39.8	1.0	-49.3	-13.0	-36.3	
High Channel (844MHz)									
1.6880	-4.1	V	3.0	38.2	1.0	-41.3	-13.0	-28.3	
2.5320	-13.1	V	3.0	38.9	1.0	-50.9	-13.0	-37.9	
3.3760	-10.0	V	3.0	39.5	1.0	-48.4	-13.0	-35.4	
4.2200	-5.1	V	4.0	39.8	2.0	-40.4	-13.0	-27.4	
5.0640	-10.3	V	5.0	39.8	3.0	-42.7	-13.0	-29.7	
1.6880	-12.1	H	3.0	38.2	1.0	-49.4	-13.0	-36.4	
2.5320	-13.6	H	3.0	38.9	1.0	-51.5	-13.0	-38.5	
3.3760	-11.4	H	3.0	39.5	1.0	-49.8	-13.0	-36.8	
4.2200	-9.8	H	3.0	39.8	1.0	-48.6	-13.0	-35.6	
5.0640	-11.8	H	3.0	39.8	1.0	-50.5	-13.0	-37.5	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE

Band 5

10MHz

16QAM

UL Korea, Ltd Suwon Laboratory

Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-25-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Earphone, X Position
Mode: TX, LTE BAND 5, 10MHz BW, 16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 22

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Channel (829MHz)									
1.6580	-2.6	V	3.0	38.2	1.0	-39.9	-13.0	-26.9	
2.4870	-14.5	V	3.0	38.8	1.0	-52.3	-13.0	-39.3	
3.3160	-8.7	V	3.0	39.4	1.0	-47.1	-13.0	-34.1	
4.1450	-3.3	V	3.0	39.8	1.0	-42.1	-13.0	-29.1	
4.9740	-9.7	V	3.0	39.8	1.0	-48.5	-13.0	-35.5	
1.6580	-8.1	H	3.0	38.2	1.0	-45.3	-13.0	-32.3	
2.4870	-15.6	H	3.0	38.8	1.0	-53.4	-13.0	-40.4	
3.3160	-10.6	H	3.0	39.4	1.0	-49.0	-13.0	-36.0	
4.1450	-6.1	H	3.0	39.8	1.0	-44.9	-13.0	-31.9	
4.9740	-12.3	H	3.0	39.8	1.0	-51.1	-13.0	-38.1	
Mid Channel (836.5MHz)									
1.6730	-2.2	V	3.0	38.2	1.0	-39.4	-13.0	-26.4	
2.5095	-12.0	V	3.0	38.8	1.0	-49.8	-13.0	-36.8	
3.3460	-9.1	V	3.0	39.5	1.0	-47.6	-13.0	-34.6	
4.1825	-1.7	V	3.0	39.8	1.0	-40.5	-13.0	-27.5	
5.0190	-9.2	V	3.0	39.8	1.0	-48.0	-13.0	-35.0	
1.6730	-14.2	H	3.0	38.2	1.0	-51.4	-13.0	-38.4	
2.5095	-12.9	H	3.0	38.8	1.0	-50.8	-13.0	-37.8	
3.3460	-10.4	H	3.0	39.5	1.0	-48.8	-13.0	-35.8	
4.1825	-6.2	H	3.0	39.8	1.0	-45.0	-13.0	-32.0	
5.0190	-10.4	H	3.0	39.8	1.0	-49.2	-13.0	-36.2	
High Channel (844MHz)									
1.6880	-4.8	V	3.0	38.2	1.0	-42.1	-13.0	-29.1	
2.5320	-13.0	V	3.0	38.9	1.0	-50.8	-13.0	-37.8	
3.3760	-10.4	V	3.0	39.5	1.0	-48.8	-13.0	-35.8	
4.2200	-5.2	V	4.0	39.8	2.0	-40.6	-13.0	-27.6	
5.0640	-11.0	V	5.0	39.8	3.0	-43.4	-13.0	-30.4	
1.6880	-12.0	H	3.0	38.2	1.0	-49.3	-13.0	-36.3	
2.5320	-13.9	H	3.0	38.9	1.0	-51.8	-13.0	-38.8	
3.3760	-11.3	H	3.0	39.5	1.0	-49.8	-13.0	-36.8	
4.2200	-10.1	H	3.0	39.8	1.0	-48.9	-13.0	-35.9	
5.0640	-12.3	H	3.0	39.8	1.0	-51.1	-13.0	-38.1	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE
Band 5
5MHz
QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-22-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Earphone, X Position
Mode: TX, LTE BAND 5, 5MHz BW,QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 22

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Channel (826.5MHz)									
1.6530	-2.3	V	3.0	38.2	1.0	-39.5	-13.0	-26.5	
2.4795	-15.3	V	3.0	38.8	1.0	-53.1	-13.0	-40.1	
3.3060	-10.1	V	3.0	39.4	1.0	-48.6	-13.0	-35.6	
4.1325	-5.6	V	3.0	39.8	1.0	-44.4	-13.0	-31.4	
4.9590	-9.7	V	3.0	39.8	1.0	-48.5	-13.0	-35.5	
1.6530	-11.2	H	3.0	38.2	1.0	-48.5	-13.0	-35.5	
2.4795	-15.7	H	3.0	38.8	1.0	-53.5	-13.0	-40.5	
3.3060	-12.4	H	3.0	39.4	1.0	-50.9	-13.0	-37.9	
4.1325	-9.4	H	3.0	39.8	1.0	-48.2	-13.0	-35.2	
4.9590	-11.2	H	3.0	39.8	1.0	-50.0	-13.0	-37.0	
Mid Channel (836.5MHz)									
1.6730	-2.4	V	3.0	38.2	1.0	-39.7	-13.0	-26.7	
2.5095	-11.6	V	3.0	38.8	1.0	-49.5	-13.0	-36.5	
3.3460	-9.2	V	3.0	39.5	1.0	-47.7	-13.0	-34.7	
4.1825	-3.8	V	3.0	39.8	1.0	-42.6	-13.0	-29.6	
5.0190	-9.2	V	3.0	39.8	1.0	-48.0	-13.0	-35.0	
1.6730	-14.1	H	3.0	38.2	1.0	-51.4	-13.0	-38.4	
2.5095	-12.5	H	3.0	38.8	1.0	-50.3	-13.0	-37.3	
3.3460	-10.1	H	3.0	39.5	1.0	-48.5	-13.0	-35.5	
4.1825	-6.1	H	3.0	39.8	1.0	-45.0	-13.0	-32.0	
5.0190	-10.6	H	3.0	39.8	1.0	-49.4	-13.0	-36.4	
High Channel (846.5MHz)									
1.6930	-2.4	V	3.0	38.2	1.0	-39.7	-13.0	-26.7	
2.5395	-11.5	V	3.0	38.9	1.0	-49.4	-13.0	-36.4	
3.3860	-9.4	V	3.0	39.5	1.0	-47.9	-13.0	-34.9	
4.2325	-3.4	V	4.0	39.8	2.0	-38.7	-13.0	-25.7	
5.0790	-8.1	V	5.0	39.8	3.0	-40.5	-13.0	-27.5	
1.6930	-10.5	H	3.0	38.2	1.0	-47.8	-13.0	-34.8	
2.5395	-13.9	H	3.0	38.9	1.0	-51.8	-13.0	-38.8	
3.3860	-11.5	H	3.0	39.5	1.0	-50.0	-13.0	-37.0	
4.2325	-6.8	H	3.0	39.8	1.0	-45.6	-13.0	-32.6	
5.0790	-9.8	H	3.0	39.8	1.0	-48.6	-13.0	-35.6	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE

Band 5

5MHz

16QAM

UL Korea, Ltd Suwon Laboratory

Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-22-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Earphone, X Position
Mode: TX, LTE BAND 5, 5MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 22

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Channel (826.5MHz)									
1.6530	-2.2	V	3.0	38.2	1.0	-39.4	-13.0	-26.4	
2.4795	-15.4	V	3.0	38.8	1.0	-53.3	-13.0	-40.3	
3.3060	-10.2	V	3.0	39.4	1.0	-48.7	-13.0	-35.7	
4.1325	-5.9	V	3.0	39.8	1.0	-44.7	-13.0	-31.7	
4.9590	-9.6	V	3.0	39.8	1.0	-48.4	-13.0	-35.4	
1.6530	-12.1	H	3.0	38.2	1.0	-49.4	-13.0	-36.4	
2.4795	-16.1	H	3.0	38.8	1.0	-53.9	-13.0	-40.9	
3.3060	-12.5	H	3.0	39.4	1.0	-50.9	-13.0	-37.9	
4.1325	-9.6	H	3.0	39.8	1.0	-48.4	-13.0	-35.4	
4.9590	-11.5	H	3.0	39.8	1.0	-50.3	-13.0	-37.3	
Mid Channel (836.5MHz)									
1.6730	-2.6	V	3.0	38.2	1.0	-39.8	-13.0	-26.8	
2.5095	-11.9	V	3.0	38.8	1.0	-49.7	-13.0	-36.7	
3.3460	-10.2	V	3.0	39.5	1.0	-48.7	-13.0	-35.7	
4.1825	-4.8	V	3.0	39.8	1.0	-43.6	-13.0	-30.6	
5.0190	-9.4	V	3.0	39.8	1.0	-48.2	-11.0	-37.2	
1.6730	-14.4	H	3.0	38.2	1.0	-51.6	-13.0	-38.6	
2.5095	-12.6	H	3.0	38.8	1.0	-50.5	-13.0	-37.5	
3.3460	-10.3	H	3.0	39.5	1.0	-48.7	-13.0	-35.7	
4.1825	-6.3	H	3.0	39.8	1.0	-45.1	-13.0	-32.1	
5.0190	-10.9	H	3.0	39.8	1.0	-49.7	-13.0	-36.7	
High Channel (846.5MHz)									
1.6930	-2.7	V	3.0	38.2	1.0	-39.9	-13.0	-26.9	
2.5395	-12.5	V	3.0	38.9	1.0	-50.4	-13.0	-37.4	
3.3860	-10.1	V	3.0	39.5	1.0	-48.6	-13.0	-35.6	
4.2325	-3.3	V	4.0	39.8	2.0	-38.6	-13.0	-25.6	
5.0790	-9.0	V	5.0	39.8	3.0	-41.3	-13.0	-28.3	
1.6930	-11.3	H	3.0	38.2	1.0	-48.5	-13.0	-35.5	
2.5395	-14.2	H	3.0	38.9	1.0	-52.1	-13.0	-39.1	
3.3860	-12.2	H	3.0	39.5	1.0	-50.7	-13.0	-37.7	
4.2325	-6.8	H	3.0	39.8	1.0	-45.6	-13.0	-32.6	
5.0790	-9.8	H	3.0	39.8	1.0	-48.6	-13.0	-35.6	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE
Band 5
3MHz
QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-22-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Earphone, X Position
Mode: TX, LTE BAND 5, 3MHz BW,QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 22

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Channel (825.5MHz)									
1.6510	-2.6	V	3.0	38.2	1.0	-39.8	-13.0	-26.8	
2.4765	-15.1	V	3.0	38.8	1.0	-52.9	-13.0	-39.9	
3.3020	-11.8	V	3.0	39.4	1.0	-50.2	-13.0	-37.2	
4.1275	-8.2	V	3.0	39.8	1.0	-47.0	-13.0	-34.0	
4.9530	-9.6	V	3.0	39.8	1.0	-48.4	-13.0	-35.4	
1.6510	-11.0	H	3.0	38.2	1.0	-48.2	-13.0	-35.2	
2.4765	-15.8	H	3.0	38.8	1.0	-53.6	-13.0	-40.6	
3.3020	-13.2	H	3.0	39.4	1.0	-51.6	-13.0	-38.6	
4.1275	-9.8	H	3.0	39.8	1.0	-48.7	-13.0	-35.7	
4.9530	-11.1	H	3.0	39.8	1.0	-49.9	-13.0	-36.9	
Mid Channel (836.5MHz)									
1.6730	-3.5	V	3.0	38.2	1.0	-40.7	-13.0	-27.7	
2.5095	-11.7	V	3.0	38.8	1.0	-49.5	-13.0	-36.5	
3.3460	-9.7	V	3.0	39.5	1.0	-48.1	-13.0	-35.1	
4.1825	-3.3	V	3.0	39.8	1.0	-42.1	-13.0	-29.1	
5.0190	-8.6	V	3.0	39.8	1.0	-47.4	-13.0	-34.4	
1.6730	-14.2	H	3.0	38.2	1.0	-51.5	-13.0	-38.5	
2.5095	-13.2	H	3.0	38.8	1.0	-51.1	-13.0	-38.1	
3.3460	-10.7	H	3.0	39.5	1.0	-49.2	-13.0	-36.2	
4.1825	-7.2	H	3.0	39.8	1.0	-46.0	-13.0	-33.0	
5.0190	-10.1	H	3.0	39.8	1.0	-48.9	-13.0	-35.9	
High Channel (847.5MHz)									
1.6950	-4.1	V	3.0	38.2	1.0	-41.4	-13.0	-28.4	
2.5425	-12.6	V	3.0	38.9	1.0	-50.5	-13.0	-37.5	
3.3900	-9.1	V	3.0	39.5	1.0	-47.5	-13.0	-34.5	
4.2375	-3.5	V	3.0	39.8	1.0	-42.3	-13.0	-29.3	
5.0850	-8.8	V	3.0	39.8	1.0	-47.6	-13.0	-34.6	
1.6950	-9.7	H	3.0	38.2	1.0	-47.0	-13.0	-34.0	
2.5425	-13.9	H	3.0	38.9	1.0	-51.8	-13.0	-38.8	
3.3900	-11.2	H	3.0	39.5	1.0	-49.7	-13.0	-36.7	
4.2375	-7.0	H	3.0	39.8	1.0	-45.8	-13.0	-32.8	
5.0850	-9.4	H	3.0	39.8	1.0	-48.1	-13.0	-35.1	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE

Band 5

3MHz

16QAM

UL Korea, Ltd Suwon Laboratory

Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-22-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Earphone, X Position
Mode: TX, LTE BAND 5, 3MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 22

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Channel (825.5MHz)									
1.6510	-2.5	V	3.0	38.2	1.0	-39.7	-13.0	-26.7	
2.4765	-15.4	V	3.0	38.8	1.0	-53.2	-13.0	-40.2	
3.3020	-11.8	V	3.0	39.4	1.0	-50.2	-13.0	-37.2	
4.1275	-7.7	V	3.0	39.8	1.0	-46.6	-13.0	-33.6	
4.9530	-10.1	V	3.0	39.8	1.0	-48.9	-13.0	-35.9	
1.6510	-11.4	H	3.0	38.2	1.0	-48.7	-13.0	-35.7	
2.4765	-15.8	H	3.0	38.8	1.0	-53.6	-13.0	-40.6	
3.3020	-13.0	H	3.0	39.4	1.0	-51.5	-13.0	-38.5	
4.1275	-10.2	H	3.0	39.8	1.0	-49.0	-13.0	-36.0	
4.9530		H	3.0	39.8	1.0	-38.8	-13.0	-25.8	
Mid Channel (836.5MHz)									
1.6730	-4.1	V	3.0	38.2	1.0	-41.3	-13.0	-28.3	
2.5095	-12.3	V	3.0	38.8	1.0	-50.2	-13.0	-37.2	
3.3460	-9.7	V	3.0	39.5	1.0	-48.2	-13.0	-35.2	
4.1825	-2.9	V	3.0	39.8	1.0	-41.7	-13.0	-28.7	
5.0190	-8.6	V	3.0	39.8	1.0	-47.4	-13.0	-34.4	
1.6730	-14.3	H	3.0	38.2	1.0	-51.5	-13.0	-38.5	
2.5095	-13.7	H	3.0	38.8	1.0	-51.6	-13.0	-38.6	
3.3460	-10.9	H	3.0	39.5	1.0	-49.4	-13.0	-36.4	
4.1825	-7.3	H	3.0	39.8	1.0	-46.1	-13.0	-33.1	
5.0190	-10.8	H	3.0	39.8	1.0	-49.6	-13.0	-36.6	
High Channel (847.5MHz)									
1.6950	-3.2	V	3.0	38.2	1.0	-40.5	-13.0	-27.5	
2.5425	-12.3	V	3.0	38.9	1.0	-50.2	-13.0	-37.2	
3.3900	-9.5	V	4.0	39.5	2.0	-44.5	-13.0	-31.5	
4.2375	-3.4	V	5.0	39.8	3.0	-35.8	-13.0	-22.8	
5.0850	-9.2	V	6.0	39.8	4.0	-39.0	-13.0	-26.0	
1.6950	-10.7	H	3.0	38.2	1.0	-48.0	-13.0	-35.0	
2.5425	-14.1	H	3.0	38.9	1.0	-51.9	-13.0	-38.9	
3.3900	-11.6	H	3.0	39.5	1.0	-50.1	-13.0	-37.1	
4.2375	-6.3	H	3.0	39.8	1.0	-45.1	-13.0	-32.1	
5.0850	-9.8	H	3.0	39.8	1.0	-48.5	-13.0	-35.5	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE

Band 5

1.4MHz

QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-22-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Earphone, X Position
Mode: TX, LTE BAND 5, 1.4MHz BW,QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 22

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Channel (824.7MHz)									
1.6494	-2.6	V	3.0	38.2	1.0	-39.8	-13.0	-26.8	
2.4741	-15.3	V	3.0	38.8	1.0	-53.1	-13.0	-40.1	
3.2988	-12.2	V	3.0	39.4	1.0	-50.6	-13.0	-37.6	
4.1235	-10.2	V	3.0	39.8	1.0	-49.0	-13.0	-36.0	
4.9482	-11.3	V	3.0	39.8	1.0	-50.1	-13.0	-37.1	
1.6494	-10.3	H	3.0	38.2	1.0	-47.5	-13.0	-34.5	
2.4741	-15.8	H	3.0	38.8	1.0	-53.6	-13.0	-40.6	
3.2988	-13.9	H	3.0	39.4	1.0	-52.3	-13.0	-39.3	
4.1235	-11.1	H	3.0	39.8	1.0	-50.0	-13.0	-37.0	
4.9482	-11.2	H	3.0	39.8	1.0	-49.9	-13.0	-36.9	
Mid Channel (836.5MHz)									
1.6730	-2.8	V	3.0	38.2	1.0	-40.0	-13.0	-27.0	
2.5095	-12.5	V	3.0	38.8	1.0	-50.4	-13.0	-37.4	
3.3460	-9.7	V	3.0	39.5	1.0	-48.1	-13.0	-35.1	
4.1825	-2.2	V	3.0	39.8	1.0	-41.0	-13.0	-28.0	
5.0190	-8.9	V	3.0	39.8	1.0	-47.7	-13.0	-34.7	
1.6730	-13.9	H	3.0	38.2	1.0	-51.1	-13.0	-38.1	
2.5095	-13.8	H	3.0	38.8	1.0	-51.7	-13.0	-38.7	
3.3460	-9.7	H	3.0	39.5	1.0	-48.2	-13.0	-35.2	
4.1825	-7.8	H	3.0	39.8	1.0	-46.6	-13.0	-33.6	
5.0190	-10.6	H	3.0	39.8	1.0	-49.4	-13.0	-36.4	
High Channel (848.3MHz)									
1.6966	-5.2	V	3.0	38.2	1.0	-42.5	-13.0	-29.5	
2.5449	-11.6	V	3.0	38.9	1.0	-49.5	-13.0	-36.5	
3.3932	-9.5	V	3.0	39.5	1.0	-47.9	-13.0	-34.9	
4.2415	-4.6	V	4.0	39.8	1.0	-40.9	-13.0	-27.9	
5.0898	-9.9	V	5.0	39.8	1.0	-44.2	-13.0	-31.2	
1.6966	-11.3	H	3.0	38.2	1.0	-48.6	-13.0	-35.6	
2.5449	-12.5	H	3.0	38.9	1.0	-50.4	-13.0	-37.4	
3.3932	-11.8	H	3.0	39.5	1.0	-50.3	-13.0	-37.3	
4.2415	-7.7	H	3.0	39.8	1.0	-46.5	-13.0	-33.5	
5.0898	-11.3	H	3.0	39.8	1.0	-50.1	-13.0	-37.1	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE

Band 5

1.4MHz

16QAM

UL Korea, Ltd Suwon Laboratory

Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-22-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Earphone, X Position
Mode: TX, LTE BAND 5, 1.4MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 22

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Channel (824.7MHz)									
1.6494	-2.9	V	3.0	38.2	1.0	-40.1	-13.0	-27.1	
2.4741	-15.3	V	3.0	38.8	1.0	-53.1	-13.0	-40.1	
3.2988	-13.0	V	3.0	39.4	1.0	-51.5	-13.0	-38.5	
4.1235	-10.0	V	3.0	39.8	1.0	-48.8	-13.0	-35.8	
4.9482	-11.3	V	3.0	39.8	1.0	-50.1	-13.0	-37.1	
1.6494	-10.3	H	3.0	38.2	1.0	-47.5	-13.0	-34.5	
2.4741	-16.2	H	3.0	38.8	1.0	-54.0	-13.0	-41.0	
3.2988	-14.2	H	3.0	39.4	1.0	-52.6	-13.0	-39.6	
4.1235	-11.1	H	3.0	39.8	1.0	-49.9	-13.0	-36.9	
4.9482	-11.4	H	3.0	39.8	1.0	-50.2	-13.0	-37.2	
Mid Channel (836.5MHz)									
1.6730	-4.0	V	3.0	38.2	1.0	-41.2	-13.0	-28.2	
2.5095	-12.7	V	3.0	38.8	1.0	-50.5	-13.0	-37.5	
3.3460	-10.1	V	3.0	39.5	1.0	-48.6	-13.0	-35.6	
4.1825	-2.2	V	3.0	39.8	1.0	-41.0	-13.0	-28.0	
5.0190	-8.3	V	3.0	39.8	1.0	-47.1	-13.0	-34.1	
1.6730	-15.0	H	3.0	38.2	1.0	-52.2	-13.0	-39.2	
2.5095	-14.1	H	3.0	38.8	1.0	-51.9	-13.0	-38.9	
3.3460	-10.3	H	3.0	39.5	1.0	-48.7	-13.0	-35.7	
4.1825	-8.1	H	3.0	39.8	1.0	-46.9	-13.0	-33.9	
5.0190	-10.6	H	3.0	39.8	1.0	-49.4	-13.0	-36.4	
High Channel (848.3MHz)									
1.6966	-4.7	V	3.0	38.2	1.0	-41.9	-13.0	-28.9	
2.5449	-12.7	V	3.0	38.9	1.0	-50.6	-13.0	-37.6	
3.3932	-10.1	V	3.0	39.5	1.0	-48.6	-13.0	-35.6	
4.2415	-4.4	V	4.0	39.8	2.0	-39.7	-13.0	-26.7	
5.0898	-10.2	V	5.0	39.8	3.0	-42.5	-13.0	-29.5	
1.6966	-11.5	H	3.0	38.2	1.0	-48.7	-13.0	-35.7	
2.5449	-13.4	H	3.0	38.9	1.0	-51.3	-13.0	-38.3	
3.3932	-11.9	H	3.0	39.5	1.0	-50.4	-13.0	-37.4	
4.2415	-8.1	H	3.0	39.8	1.0	-46.9	-13.0	-33.9	
5.0898	-11.7	H	3.0	39.8	1.0	-50.5	-13.0	-37.5	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 7

LTE Band 7 20MHz QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-15-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 7, 20MHz BW, QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2510 MHz)									
5.0200	-7.3	V	3.0	39.8	1.0	-46.1	-25.0	-21.1	
7.5300	5.4	V	3.0	39.4	1.0	-33.0	-25.0	-8.0	
10.0400	-0.7	V	3.0	38.6	1.0	-38.3	-25.0	-13.3	
5.0200	0.0	H	3.0	39.8	1.0	-38.8	-25.0	-13.8	
7.5300	4.7	H	3.0	39.4	1.0	-33.6	-25.0	-8.6	
10.0400	-8.8	H	3.0	38.6	1.0	-46.4	-25.0	-21.4	
Mid Ch, (2535 MHz)									
5.0700	-1.7	V	3.0	39.8	1.0	-40.5	-25.0	-15.5	
7.6050	0.4	V	3.0	39.3	1.0	-37.9	-25.0	-12.9	
10.1400	-5.2	V	3.0	38.6	1.0	-42.7	-25.0	-17.7	
5.0700	3.4	H	3.0	39.8	1.0	-35.4	-25.0	-10.4	
7.6050	0.6	H	3.0	39.3	1.0	-37.8	-25.0	-12.8	
10.1400	-9.1	H	3.0	38.6	1.0	-46.7	-25.0	-21.7	
High Ch, (2560 MHz)									
5.1200	-5.7	V	3.0	39.8	1.0	-44.5	-25.0	-19.5	
7.6800	-1.4	V	3.0	39.3	1.0	-39.7	-25.0	-14.7	
10.2400	-7.2	V	3.0	38.6	1.0	-44.8	-25.0	-19.8	
5.1200	0.3	H	3.0	39.8	1.0	-38.6	-25.0	-13.6	
7.6800	-1.3	H	3.0	39.3	1.0	-39.6	-25.0	-14.6	
10.2400	-8.7	H	3.0	38.6	1.0	-46.2	-25.0	-21.2	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

LTE Band 7 20MHz 16QAM

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-15-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 7, 20MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2510 MHz)									
5.0200	-7.2	V	3.0	39.8	1.0	-45.9	-25.0	-20.9	
7.5300	5.4	V	3.0	39.4	1.0	-33.0	-25.0	-8.0	
10.0400	-1.0	V	3.0	38.6	1.0	-38.6	-25.0	-13.6	
5.0200	0.0	H	3.0	39.8	1.0	-38.7	-25.0	-13.7	
7.5300	5.9	H	3.0	39.4	1.0	-32.4	-25.0	-7.4	
10.0400	-9.3	H	3.0	38.6	1.0	-46.9	-25.0	-21.9	
Mid Ch, (2535 MHz)									
5.0700	-1.1	V	3.0	39.8	1.0	-39.8	-25.0	-14.8	
7.6050	0.6	V	3.0	39.3	1.0	-37.7	-25.0	-12.7	
10.1400	-4.4	V	3.0	38.6	1.0	-42.0	-25.0	-17.0	
5.0700	3.2	H	3.0	39.8	1.0	-35.6	-25.0	-10.6	
7.6050	0.5	H	3.0	39.3	1.0	-37.8	-25.0	-12.8	
10.1400	-9.6	H	3.0	38.6	1.0	-47.2	-25.0	-22.2	
High Ch, (2560 MHz)									
5.1200	-6.3	V	3.0	39.8	1.0	-45.1	-25.0	-20.1	
7.6800	-2.1	V	3.0	39.3	1.0	-40.4	-25.0	-15.4	
10.2400	-7.2	V	3.0	38.6	1.0	-44.7	-25.0	-19.7	
5.1200	0.3	H	3.0	39.8	1.0	-38.6	-25.0	-13.6	
7.6800	-1.2	H	3.0	39.3	1.0	-39.6	-25.0	-14.6	
10.2400	-9.0	H	3.0	38.6	1.0	-46.6	-25.0	-21.6	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE

Band 7

15MHz

QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-15-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 7, 15MHz BW, QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2507.5 MHz)									
5.0150	-5.1	V	3.0	39.8	1.0	-43.9	-25.0	-18.9	
7.5225	5.7	V	3.0	39.4	1.0	-32.7	-25.0	-7.7	
10.0300	-0.2	V	3.0	38.6	1.0	-37.7	-25.0	-12.7	
5.0150	0.2	H	3.0	39.8	1.0	-38.5	-25.0	-13.5	
7.5225	7.9	H	3.0	39.4	1.0	-30.5	-25.0	-5.5	
10.0300	-2.2	H	3.0	38.6	1.0	-39.8	-25.0	-14.8	
Mid Ch, (2535 MHz)									
5.0700	-0.8	V	3.0	39.8	1.0	-39.6	-25.0	-14.6	
7.6050	0.9	V	3.0	39.3	1.0	-37.5	-25.0	-12.5	
10.1400	-4.8	V	3.0	38.6	1.0	-42.3	-25.0	-17.3	
5.0700	3.7	H	3.0	39.8	1.0	-35.0	-25.0	-10.0	
7.6050	-0.3	H	3.0	39.3	1.0	-38.6	-25.0	-13.6	
10.1400	-8.9	H	3.0	38.6	1.0	-46.5	-25.0	-21.5	
High Ch, (2562.5 MHz)									
5.1250	-3.5	V	3.0	39.8	1.0	-42.3	-25.0	-17.3	
7.6875	-2.2	V	3.0	39.3	1.0	-40.5	-25.0	-15.5	
10.2500	-7.4	V	3.0	38.6	1.0	-45.0	-25.0	-20.0	
5.1250	2.1	H	3.0	39.8	1.0	-36.8	-25.0	-11.8	
7.6875	-3.4	H	3.0	39.3	1.0	-41.7	-25.0	-16.7	
10.2500	-9.2	H	3.0	38.6	1.0	-46.7	-25.0	-21.7	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

LTE

Band 7

15MHz

16QAM

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-15-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 7, 15MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2507.5 MHz)									
5.0150	-4.6	V	3.0	39.8	1.0	-43.4	-25.0	-18.4	
7.5225	5.2	V	3.0	39.4	1.0	-33.2	-25.0	-8.2	
10.0300	0.9	V	3.0	38.6	1.0	-36.7	-25.0	-11.7	
5.0150	0.3	H	3.0	39.8	1.0	-38.4	-25.0	-13.4	
7.5225	8.1	H	3.0	39.4	1.0	-30.3	-25.0	-5.3	
10.0300	-2.6	H	3.0	38.6	1.0	-40.2	-25.0	-15.2	
Mid Ch, (2535 MHz)									
5.0700	-0.4	V	3.0	39.8	1.0	-39.2	-25.0	-14.2	
7.6050	0.6	V	3.0	39.3	1.0	-37.8	-25.0	-12.8	
10.1400	-7.4	V	3.0	38.6	1.0	-44.9	-25.0	-19.9	
5.0700	3.9	H	3.0	39.8	1.0	-34.9	-25.0	-9.9	
7.6050	-1.5	H	3.0	39.3	1.0	-39.9	-25.0	-14.9	
10.1400	-9.8	H	3.0	38.6	1.0	-47.4	-25.0	-22.4	
High Ch, (2562.5 MHz)									
5.1250	-3.6	V	3.0	39.8	1.0	-42.4	-25.0	-17.4	
7.6875	-2.3	V	3.0	39.3	1.0	-40.6	-25.0	-15.6	
10.2500	-7.6	V	3.0	38.6	1.0	-45.2	-25.0	-20.2	
5.1250	1.9	H	3.0	39.8	1.0	-36.9	-25.0	-11.9	
7.6875	-3.1	H	3.0	39.3	1.0	-41.5	-25.0	-16.5	
10.2500	-9.4	H	3.0	38.6	1.0	-47.0	-25.0	-22.0	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE
Band 7
10MHz
QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-15-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 7, 10MHz BW, QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2505 MHz)									
5.0100	-4.5	V	3.0	39.8	1.0	-43.2	-25.0	-18.2	
7.5150	4.9	V	3.0	39.4	1.0	-33.5	-25.0	-8.5	
10.0200	-0.9	V	3.0	38.6	1.0	-38.5	-25.0	-13.5	
5.0100	1.1	H	3.0	39.8	1.0	-37.7	-25.0	-12.7	
7.5150	-8.1	H	3.0	39.4	1.0	-46.5	-25.0	-21.5	
10.0200	-2.9	H	3.0	38.6	1.0	-40.5	-25.0	-15.5	
Mid Ch, (2535 MHz)									
5.0700	-5.2	V	3.0	39.8	1.0	-44.0	-25.0	-19.0	
7.6050	-0.1	V	3.0	39.3	1.0	-38.5	-25.0	-13.5	
10.1400	-5.5	V	3.0	38.6	1.0	-43.0	-25.0	-18.0	
5.0700	3.3	H	3.0	39.8	1.0	-35.5	-25.0	-10.5	
7.6050	-1.1	H	3.0	39.3	1.0	-39.4	-25.0	-14.4	
10.1400	-9.2	H	3.0	38.6	1.0	-46.8	-25.0	-21.8	
High Ch, (2565 MHz)									
5.1300	-3.4	V	3.0	39.8	1.0	-42.2	-25.0	-17.2	
7.6950	-6.9	V	3.0	39.3	1.0	-45.2	-25.0	-20.2	
10.2600	-8.8	V	3.0	38.6	1.0	-46.4	-25.0	-21.4	
5.1300	2.6	H	3.0	39.8	1.0	-36.2	-25.0	-11.2	
7.6950	-4.4	H	3.0	39.3	1.0	-42.7	-25.0	-17.7	
10.2600	-9.3	H	3.0	38.6	1.0	-46.8	-25.0	-21.8	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

LTE
Band 7
10MHz
16QAM

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-15-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 7, 10MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2505 MHz)									
5.0100	-3.7	V	3.0	39.8	1.0	-42.5	-25.0	-17.5	
7.5150	6.0	V	3.0	39.4	1.0	-32.3	-25.0	-7.3	
10.0200	-1.0	V	3.0	38.6	1.0	-38.6	-25.0	-13.6	
5.0100	1.3	H	3.0	39.8	1.0	-37.4	-25.0	-12.4	
7.5150	-8.1	H	3.0	39.4	1.0	-46.5	-25.0	-21.5	
10.0200	-2.6	H	3.0	38.6	1.0	-40.1	-25.0	-15.1	
Mid Ch, (2535 MHz)									
5.0700	-4.1	V	3.0	39.8	1.0	-42.9	-25.0	-17.9	
7.6050	2.2	V	3.0	39.3	1.0	-36.1	-25.0	-11.1	
10.1400	-3.8	V	3.0	38.6	1.0	-41.4	-25.0	-16.4	
5.0700	3.5	H	3.0	39.8	1.0	-35.3	-25.0	-10.3	
7.6050	-0.2	H	3.0	39.3	1.0	-38.5	-25.0	-13.5	
10.1400	-8.5	H	3.0	38.6	1.0	-46.1	-25.0	-21.1	
High Ch, (2565 MHz)									
5.1300	-2.5	V	3.0	39.8	1.0	-41.3	-25.0	-16.3	
7.6950	-6.3	V	3.0	39.3	1.0	-44.6	-25.0	-19.6	
10.2600	-8.2	V	3.0	38.6	1.0	-45.8	-25.0	-20.8	
5.1300	2.5	H	3.0	39.8	1.0	-36.3	-25.0	-11.3	
7.6950	-4.0	H	3.0	39.3	1.0	-42.3	-25.0	-17.3	
10.2600	-9.5	H	3.0	38.6	1.0	-47.1	-25.0	-22.1	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE
Band 7
5MHz
QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-15-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 7, 5MHz BW, QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2502.5 MHz)									
5.0050	-5.9	V	3.0	39.8	1.0	-44.7	-25.0	-19.7	
7.5075	2.4	V	3.0	39.4	1.0	-36.0	-25.0	-11.0	
10.0100	-2.8	V	3.0	38.6	1.0	-40.3	-25.0	-15.3	
5.0050	1.1	H	3.0	39.8	1.0	-37.6	-25.0	-12.6	
7.5075	8.1	H	3.0	39.4	1.0	-30.3	-25.0	-5.3	
10.0100	-4.5	H	3.0	38.6	1.0	-42.1	-25.0	-17.1	
Mid Ch, (2535 MHz)									
5.0700	-1.6	V	3.0	39.8	1.0	-40.3	-25.0	-15.3	
7.6050	0.6	V	3.0	39.3	1.0	-37.7	-25.0	-12.7	
10.1400	-5.4	V	3.0	38.6	1.0	-42.9	-25.0	-17.9	
5.0700	3.5	H	3.0	39.8	1.0	-35.3	-25.0	-10.3	
7.6050	0.6	H	3.0	39.3	1.0	-37.8	-25.0	-12.8	
10.1400	-9.0	H	3.0	38.6	1.0	-46.5	-25.0	-21.5	
High Ch, (2567.5 MHz)									
5.1350	-1.9	V	3.0	39.8	1.0	-40.7	-25.0	-15.7	
7.7025	-8.6	V	3.0	39.3	1.0	-46.9	-25.0	-21.9	
10.2700	-9.5	V	3.0	38.6	1.0	-47.0	-25.0	-22.0	
5.1350	2.8	H	3.0	39.8	1.0	-36.0	-25.0	-11.0	
7.7025	-2.1	H	3.0	39.3	1.0	-40.4	-25.0	-15.4	
10.2700	-9.1	H	3.0	38.6	1.0	-46.6	-25.0	-21.6	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

LTE
Band 7
5MHz
16QAM

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-15-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 7, 5MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2502.5 MHz)									
5.0050	-4.6	V	3.0	39.8	1.0	-43.4	-25.0	-18.4	
7.5075	2.9	V	3.0	39.4	1.0	-35.5	-25.0	-10.5	
10.0100	-2.5	V	3.0	38.6	1.0	-40.1	-25.0	-15.1	
5.0050	1.4	H	3.0	39.8	1.0	-37.4	-25.0	-12.4	
7.5075	8.2	H	3.0	39.4	1.0	-30.2	-25.0	-5.2	
10.0100	-5.4	H	3.0	38.6	1.0	-42.9	-25.0	-17.9	
Mid Ch, (2535 MHz)									
5.0700	-0.6	V	3.0	39.8	1.0	-39.4	-25.0	-14.4	
7.6050	0.1	V	3.0	39.3	1.0	-38.3	-25.0	-13.3	
10.1400	-4.9	V	3.0	38.6	1.0	-42.5	-25.0	-17.5	
5.0700	3.8	H	3.0	39.8	1.0	-35.0	-25.0	-10.0	
7.6050	0.1	H	3.0	39.3	1.0	-38.3	-25.0	-13.3	
10.1400	-9.5	H	3.0	38.6	1.0	-47.1	-25.0	-22.1	
High Ch, (2567.5 MHz)									
5.1350	-1.7	V	3.0	39.8	1.0	-40.5	-25.0	-15.5	
7.7025	-7.8	V	3.0	39.3	1.0	-46.1	-25.0	-21.1	
10.2700	-8.7	V	3.0	38.6	1.0	-46.3	-25.0	-21.3	
5.1350	3.1	H	3.0	39.8	1.0	-35.8	-25.0	-10.8	
7.7025	-2.5	H	3.0	39.3	1.0	-40.8	-25.0	-15.8	
10.2700	-9.5	H	3.0	38.6	1.0	-47.1	-25.0	-22.1	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 7(with Protective cover)

LTE Band 7 20MHz QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 10-12-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 7, 20MHz BW, QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2510 MHz)									
5.0200	-3.0	V	3.0	39.8	1.0	-41.8	-25.0	-16.8	
7.5300	2.1	V	3.0	39.4	1.0	-36.3	-25.0	-11.3	
10.0400	-0.5	V	3.0	38.6	1.0	-38.0	-25.0	-13.0	
5.0200	-0.9	H	3.0	39.8	1.0	-39.7	-25.0	-14.7	
7.5300	5.4	H	3.0	39.4	1.0	-33.0	-25.0	-8.0	
10.0400	-6.1	H	3.0	38.6	1.0	-43.7	-25.0	-18.7	
Mid Ch, (2535 MHz)									
5.0700	-0.6	V	3.0	39.8	1.0	-39.4	-25.0	-14.4	
7.6050	0.9	V	3.0	39.3	1.0	-37.5	-25.0	-12.5	
10.1400	-3.7	V	3.0	38.6	1.0	-41.2	-25.0	-16.2	
5.0700	2.8	H	3.0	39.8	1.0	-36.0	-25.0	-11.0	
7.6050	4.7	H	3.0	39.3	1.0	-33.6	-25.0	-8.6	
10.1400	-5.5	H	3.0	38.6	1.0	-43.1	-25.0	-18.1	
High Ch, (2560 MHz)									
5.1200	-1.4	V	3.0	39.8	1.0	-40.2	-25.0	-15.2	
7.6800	-4.9	V	3.0	39.3	1.0	-43.2	-25.0	-18.2	
10.2400	-5.0	V	3.0	38.6	1.0	-42.6	-25.0	-17.6	
5.1200	2.7	H	3.0	39.8	1.0	-36.1	-25.0	-11.1	
7.6800	-1.8	H	3.0	39.3	1.0	-40.1	-25.0	-15.1	
10.2400	-9.3	H	3.0	38.6	1.0	-46.9	-25.0	-21.9	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

LTE Band 7 20MHz 16QAM

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 10-12-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 7, 20MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2510 MHz)									
5.0200	-2.7	V	3.0	39.8	1.0	-41.4	-25.0	-16.4	
7.5300	2.4	V	3.0	39.4	1.0	-36.0	-25.0	-11.0	
10.0400	-0.7	V	3.0	38.6	1.0	-38.3	-25.0	-13.3	
5.0200	-0.8	H	3.0	39.8	1.0	-39.5	-25.0	-14.5	
7.5300	4.9	H	3.0	39.4	1.0	-33.5	-25.0	-8.5	
10.0400	-5.9	H	3.0	38.6	1.0	-43.5	-25.0	-18.5	
Mid Ch, (2535 MHz)									
5.0700	-0.2	V	3.0	39.8	1.0	-39.0	-25.0	-14.0	
7.6050	0.0	V	3.0	39.3	1.0	-38.4	-25.0	-13.4	
10.1400	-5.8	V	3.0	38.6	1.0	-43.4	-25.0	-18.4	
5.0700	2.9	H	3.0	39.8	1.0	-35.9	-25.0	-10.9	
7.6050	3.7	H	3.0	39.3	1.0	-34.7	-25.0	-9.7	
10.1400	-6.1	H	3.0	38.6	1.0	-43.7	-25.0	-18.7	
High Ch, (2560 MHz)									
5.1200	-1.2	V	3.0	39.8	1.0	-40.0	-25.0	-15.0	
7.6800	-4.7	V	3.0	39.3	1.0	-43.0	-25.0	-18.0	
10.2400	-4.6	V	3.0	38.6	1.0	-42.1	-25.0	-17.1	
5.1200	2.7	H	3.0	39.8	1.0	-36.1	-25.0	-11.1	
7.6800	-2.5	H	3.0	39.3	1.0	-40.8	-25.0	-15.8	
10.2400	-9.5	H	3.0	38.6	1.0	-47.1	-25.0	-22.1	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 7 15MHz QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 10-12-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 7, 15MHz BW, QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2507.5 MHz)									
5.0150	-3.9	V	3.0	39.8	1.0	-42.7	-25.0	-17.7	
7.5225	-0.1	V	3.0	39.4	1.0	-38.5	-25.0	-13.5	
10.0300	-1.2	V	3.0	38.6	1.0	-38.8	-25.0	-13.8	
5.0150	2.0	H	3.0	39.8	1.0	-36.8	-25.0	-11.8	
7.5225	7.3	H	3.0	39.4	1.0	-31.1	-25.0	-6.1	
10.0300	-5.8	H	3.0	38.6	1.0	-43.4	-25.0	-18.4	
Mid Ch, (2535 MHz)									
5.0700	0.0	V	3.0	39.8	1.0	-38.8	-25.0	-13.8	
7.6050	0.6	V	3.0	39.3	1.0	-37.8	-25.0	-12.8	
10.1400	-3.2	V	3.0	38.6	1.0	-40.7	-25.0	-15.7	
5.0700	3.2	H	3.0	39.8	1.0	-35.6	-25.0	-10.6	
7.6050	5.5	H	3.0	39.3	1.0	-32.8	-25.0	-7.8	
10.1400	-3.7	H	3.0	38.6	1.0	-41.3	-25.0	-16.3	
High Ch, (2562.5 MHz)									
5.1250	-2.7	V	3.0	39.8	1.0	-41.5	-25.0	-16.5	
7.6875	-3.6	V	3.0	39.3	1.0	-41.9	-25.0	-16.9	
10.2500	-6.0	V	3.0	38.6	1.0	-43.5	-25.0	-18.5	
5.1250	2.8	H	3.0	39.8	1.0	-36.0	-25.0	-11.0	
7.6875	-0.4	H	3.0	39.3	1.0	-38.7	-25.0	-13.7	
10.2500	-8.9	H	3.0	38.6	1.0	-46.5	-25.0	-21.5	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

LTE Band 7 15MHz 16QAM

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 10-12-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 7, 15MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2507.5 MHz)									
5.0150	-3.0	V	3.0	39.8	1.0	-41.8	-25.0	-16.8	
7.5225	0.9	V	3.0	39.4	1.0	-37.5	-25.0	-12.5	
10.0300	-1.6	V	3.0	38.6	1.0	-39.1	-25.0	-14.1	
5.0150	2.1	H	3.0	39.8	1.0	-36.7	-25.0	-11.7	
7.5225	6.9	H	3.0	39.4	1.0	-31.5	-25.0	-6.5	
10.0300	-6.0	H	3.0	38.6	1.0	-43.6	-25.0	-18.6	
Mid Ch, (2535 MHz)									
5.0700	0.8	V	3.0	39.8	1.0	-38.0	-25.0	-13.0	
7.6050	0.9	V	3.0	39.3	1.0	-37.4	-25.0	-12.4	
10.1400	-3.4	V	3.0	38.6	1.0	-41.0	-25.0	-16.0	
5.0700	3.4	H	3.0	39.8	1.0	-35.4	-25.0	-10.4	
7.6050	5.8	H	3.0	39.3	1.0	-32.5	-25.0	-7.5	
10.1400	-5.1	H	3.0	38.6	1.0	-42.6	-25.0	-17.6	
High Ch, (2562.5 MHz)									
5.1250	-2.1	V	3.0	39.8	1.0	-40.9	-25.0	-15.9	
7.6875	-4.6	V	3.0	39.3	1.0	-42.9	-25.0	-17.9	
10.2500	-7.2	V	3.0	38.6	1.0	-44.7	-25.0	-19.7	
5.1250	3.4	H	3.0	39.8	1.0	-35.4	-25.0	-10.4	
7.6875	-0.8	H	3.0	39.3	1.0	-39.1	-25.0	-14.1	
10.2500	-9.2	H	3.0	38.6	1.0	-46.7	-25.0	-21.7	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 7 10MHz QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 10-12-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 7, 10MHz BW, QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2505 MHz)									
5.0100	-2.6	V	3.0	39.8	1.0	-41.4	-25.0	-16.4	
7.5150	5.1	V	3.0	39.4	1.0	-33.3	-25.0	-8.3	
10.0200	-0.1	V	3.0	38.6	1.0	-37.6	-25.0	-12.6	
5.0100	0.9	H	3.0	39.8	1.0	-37.9	-25.0	-12.9	
7.5150	8.5	H	3.0	39.4	1.0	-29.9	-25.0	-4.9	
10.0200	-3.2	H	3.0	38.6	1.0	-40.8	-25.0	-15.8	
Mid Ch, (2535 MHz)									
5.0700	-0.8	V	3.0	39.8	1.0	-39.6	-25.0	-14.6	
7.6050	2.7	V	3.0	39.3	1.0	-35.7	-25.0	-10.7	
10.1400	-3.1	V	3.0	38.6	1.0	-40.7	-25.0	-15.7	
5.0700	1.9	H	3.0	39.8	1.0	-36.9	-25.0	-11.9	
7.6050	6.2	H	3.0	39.3	1.0	-32.1	-25.0	-7.1	
10.1400	-4.6	H	3.0	38.6	1.0	-42.2	-25.0	-17.2	
High Ch, (2565 MHz)									
5.1300	-1.4	V	3.0	39.8	1.0	-40.2	-25.0	-15.2	
7.6950	-1.1	V	3.0	39.3	1.0	-39.4	-25.0	-14.4	
10.2600	-4.9	V	3.0	38.6	1.0	-42.5	-25.0	-17.5	
5.1300	4.1	H	3.0	39.8	1.0	-34.7	-25.0	-9.7	
7.6950	1.6	H	3.0	39.3	1.0	-36.7	-25.0	-11.7	
10.2600	-9.0	H	3.0	38.6	1.0	-46.6	-25.0	-21.6	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

LTE Band 7 10MHz 16QAM

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 10-12-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 7, 10MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2505 MHz)									
5.0100	-2.2	V	3.0	39.8	1.0	-41.0	-25.0	-16.0	
7.5150	4.8	V	3.0	39.4	1.0	-33.6	-25.0	-8.6	
10.0200	-0.4	V	3.0	38.6	1.0	-38.0	-25.0	-13.0	
5.0100	1.3	H	3.0	39.8	1.0	-37.5	-25.0	-12.5	
7.5150	8.0	H	3.0	39.4	1.0	-30.4	-25.0	-5.4	
10.0200	-3.6	H	3.0	38.6	1.0	-41.1	-25.0	-16.1	
Mid Ch, (2535 MHz)									
5.0700	-0.9	V	3.0	39.8	1.0	-39.7	-25.0	-14.7	
7.6050	2.2	V	3.0	39.3	1.0	-36.2	-25.0	-11.2	
10.1400	-3.5	V	3.0	38.6	1.0	-41.0	-25.0	-16.0	
5.0700	2.7	H	3.0	39.8	1.0	-36.1	-25.0	-11.1	
7.6050	6.2	H	3.0	39.3	1.0	-32.1	-25.0	-7.1	
10.1400	-4.6	H	3.0	38.6	1.0	-42.1	-25.0	-17.1	
High Ch, (2565 MHz)									
5.1300	-1.0	V	3.0	39.8	1.0	-39.8	-25.0	-14.8	
7.6950	-2.1	V	3.0	39.3	1.0	-40.4	-25.0	-15.4	
10.2600	-6.3	V	3.0	38.6	1.0	-43.8	-25.0	-18.8	
5.1300	4.6	H	3.0	39.8	1.0	-34.2	-25.0	-9.2	
7.6950	1.5	H	3.0	39.3	1.0	-36.8	-25.0	-11.8	
10.2600	-9.2	H	3.0	38.6	1.0	-46.8	-25.0	-21.8	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE

Band 7

5MHz

QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 10-11-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 7, 5MHz BW, QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2502.5 MHz)									
5.0050	-1.4	V	3.0	39.8	1.0	-40.2	-25.0	-15.2	
7.5075	7.2	V	3.0	39.4	1.0	-31.2	-25.0	-6.2	
10.0100	-3.1	V	3.0	38.6	1.0	-40.7	-25.0	-15.7	
5.0050	0.4	H	3.0	39.8	1.0	-38.3	-25.0	-13.3	
7.5075	9.4	H	3.0	39.4	1.0	-29.0	-25.0	-4.0	
10.0100	-5.5	H	3.0	38.6	1.0	-43.1	-25.0	-18.1	
Mid Ch, (2535 MHz)									
5.0700	-0.6	V	3.0	39.8	1.0	-39.4	-25.0	-14.4	
7.6050	2.4	V	3.0	39.3	1.0	-36.0	-25.0	-11.0	
10.1400	-4.1	V	3.0	38.6	1.0	-41.6	-25.0	-16.6	
5.0700	1.7	H	3.0	39.8	1.0	-37.1	-25.0	-12.1	
7.6050	5.3	H	3.0	39.3	1.0	-33.1	-25.0	-8.1	
10.1400	-5.9	H	3.0	38.6	1.0	-43.4	-25.0	-18.4	
High Ch, (2567.5 MHz)									
5.1350	-3.4	V	3.0	39.8	1.0	-42.2	-25.0	-17.2	
7.7025	0.5	V	3.0	39.3	1.0	-37.8	-25.0	-12.8	
10.2700	-6.1	V	3.0	38.6	1.0	-43.6	-25.0	-18.6	
5.1350	3.9	H	3.0	39.8	1.0	-34.9	-25.0	-9.9	
7.7025	0.0	H	3.0	39.3	1.0	-38.3	-25.0	-13.3	
10.2700	-7.4	H	3.0	38.6	1.0	-44.9	-25.0	-19.9	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

LTE

Band 7

5MHz

16QAM

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 10-11-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 7, 5MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2502.5 MHz)									
5.0050	-2.5	V	3.0	39.8	1.0	-41.3	-25.0	-16.3	
7.5075	7.0	V	3.0	39.4	1.0	-31.4	-25.0	-6.4	
10.0100	-1.7	V	3.0	38.6	1.0	-39.3	-25.0	-14.3	
5.0050	0.5	H	3.0	39.8	1.0	-38.2	-25.0	-13.2	
7.5075	9.4	H	3.0	39.4	1.0	-29.0	-25.0	-4.0	
10.0100	-6.1	H	3.0	38.6	1.0	-43.7	-25.0	-18.7	
Mid Ch, (2535 MHz)									
5.0700	-0.9	V	3.0	39.8	1.0	-39.7	-25.0	-14.7	
7.6050	3.1	V	3.0	39.3	1.0	-35.3	-25.0	-10.3	
10.1400	-4.3	V	3.0	38.6	1.0	-41.9	-25.0	-16.9	
5.0700	1.6	H	3.0	39.8	1.0	-37.2	-25.0	-12.2	
7.6050	4.9	H	3.0	39.3	1.0	-33.5	-25.0	-8.5	
10.1400	-6.3	H	3.0	38.6	1.0	-43.9	-25.0	-18.9	
High Ch, (2567.5 MHz)									
5.1350	-3.1	V	3.0	39.8	1.0	-41.9	-25.0	-16.9	
7.7025	0.3	V	3.0	39.3	1.0	-38.1	-25.0	-13.1	
10.2700	-6.5	V	3.0	38.6	1.0	-44.1	-25.0	-19.1	
5.1350	3.9	H	3.0	39.8	1.0	-34.9	-25.0	-9.9	
7.7025	0.0	H	3.0	39.3	1.0	-38.3	-25.0	-13.3	
10.2700	-8.5	H	3.0	38.6	1.0	-46.1	-25.0	-21.1	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 41

LTE Band 41 20MHz QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-18-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 41, 20MHz BW, QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2565 MHz)									
5.1300	-3.7	V	3.0	39.8	1.0	-42.5	-25.0	-17.5	
7.6950	-0.3	V	3.0	39.3	1.0	-38.6	-25.0	-13.6	
10.2600	-9.0	V	3.0	38.6	1.0	-46.5	-25.0	-21.5	
5.1300	2.1	H	3.0	39.8	1.0	-36.7	-25.0	-11.7	
7.6950	-0.8	H	3.0	39.3	1.0	-39.1	-25.0	-14.1	
10.2600	-8.6	H	3.0	38.6	1.0	-46.2	-25.0	-21.2	
Mid Ch, (2605 MHz)									
5.2100	-5.2	V	3.0	39.8	1.0	-44.1	-25.0	-19.1	
7.8150	-5.4	V	3.0	39.3	1.0	-43.6	-25.0	-18.6	
10.4200	-7.1	V	3.0	38.5	1.0	-44.6	-25.0	-19.6	
5.2100	0.7	H	3.0	39.8	1.0	-38.1	-25.0	-13.1	
7.8150	-2.4	H	3.0	39.3	1.0	-40.7	-25.0	-15.7	
10.4200	-9.8	H	3.0	38.5	1.0	-47.3	-25.0	-22.3	
High Ch, (2645 MHz)									
5.2900	-5.7	V	3.0	39.9	1.0	-44.6	-25.0	-19.6	
7.9350	-4.6	V	3.0	39.2	1.0	-42.8	-25.0	-17.8	
10.5800	-3.9	V	3.0	38.5	1.0	-41.4	-25.0	-16.4	
5.2900	1.1	H	3.0	39.9	1.0	-37.8	-25.0	-12.8	
7.9350	0.3	H	3.0	39.2	1.0	-37.9	-25.0	-12.9	
10.5800	-9.1	H	3.0	38.5	1.0	-46.7	-25.0	-21.7	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

LTE Band 41 20MHz 16QAM

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-18-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 41, 20MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2565 MHz)									
5.1300	-3.1	V	3.0	39.8	1.0	-41.9	-25.0	-16.9	
7.6950	-2.0	V	3.0	39.3	1.0	-40.3	-25.0	-15.3	
10.2600	-9.0	V	3.0	38.6	1.0	-46.6	-25.0	-21.6	
5.1300	1.8	H	3.0	39.8	1.0	-37.0	-25.0	-12.0	
7.6950	-1.3	H	3.0	39.3	1.0	-39.6	-25.0	-14.6	
10.2600	-9.3	H	3.0	38.6	1.0	-46.8	-25.0	-21.8	
Mid Ch, (2605 MHz)									
5.2100	-4.7	V	3.0	39.8	1.0	-43.5	-25.0	-18.5	
7.8150	-5.0	V	3.0	39.3	1.0	-43.3	-25.0	-18.3	
10.4200	-8.9	V	3.0	38.5	1.0	-46.4	-25.0	-21.4	
5.2100	0.4	H	3.0	39.8	1.0	-38.4	-25.0	-13.4	
7.8150	-2.7	H	3.0	39.3	1.0	-40.9	-25.0	-15.9	
10.4200	-9.5	H	3.0	38.5	1.0	-47.1	-25.0	-22.1	
High Ch, (2645 MHz)									
5.2900	-5.5	V	3.0	39.9	1.0	-44.4	-25.0	-19.4	
7.9350	-4.4	V	3.0	39.2	1.0	-42.6	-25.0	-17.6	
10.5800	-3.3	V	3.0	38.5	1.0	-40.8	-25.0	-15.8	
5.2900	1.2	H	3.0	39.9	1.0	-37.6	-25.0	-12.6	
7.9350	0.5	H	3.0	39.2	1.0	-37.7	-25.0	-12.7	
10.5800	-9.3	H	3.0	38.5	1.0	-46.8	-25.0	-21.8	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE

Band 41

15MHz

QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-18-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 41, 15MHz BW,QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2562.5 MHz)									
5.1250	-3.6	V	3.0	39.8	1.0	-42.4	-25.0	-17.4	
7.6875	-0.2	V	3.0	39.3	1.0	-38.5	-25.0	-13.5	
10.2500	-8.7	V	3.0	38.6	1.0	-46.2	-25.0	-21.2	
5.1250	2.2	H	3.0	39.8	1.0	-36.6	-25.0	-11.6	
7.6875	1.9	H	3.0	39.3	1.0	-36.4	-25.0	-11.4	
10.2500	-9.2	H	3.0	38.6	1.0	-46.7	-25.0	-21.7	
Mid Ch, (2605 MHz)									
5.2100	-6.4	V	3.0	39.8	1.0	-45.2	-25.0	-20.2	
7.8150	-1.8	V	3.0	39.3	1.0	-40.1	-25.0	-15.1	
10.4200	-5.5	V	3.0	38.5	1.0	-43.0	-25.0	-18.0	
5.2100	2.4	H	3.0	39.8	1.0	-36.4	-25.0	-11.4	
7.8150	-1.9	H	3.0	39.3	1.0	-40.2	-25.0	-15.2	
10.4200	-9.4	H	3.0	38.5	1.0	-47.0	-25.0	-22.0	
High Ch, (2647.5 MHz)									
5.2950	-5.9	V	3.0	39.9	1.0	-44.8	-25.0	-19.8	
7.9425	-4.6	V	3.0	39.2	1.0	-42.8	-25.0	-17.8	
10.5900	-3.6	V	3.0	38.5	1.0	-41.1	-25.0	-16.1	
5.2950	2.4	H	3.0	39.9	1.0	-36.5	-25.0	-11.5	
7.9425	-2.8	H	3.0	39.2	1.0	-41.0	-25.0	-16.0	
10.5900	-9.1	H	3.0	38.5	1.0	-46.6	-25.0	-21.6	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

LTE

Band 41

15MHz

16QAM

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-18-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 41, 15MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2562.5 MHz)									
5.1250	-2.2	V	3.0	39.8	1.0	-41.0	-25.0	-16.0	
7.6875	0.2	V	3.0	39.3	1.0	-38.1	-25.0	-13.1	
10.2500	-8.7	V	3.0	38.6	1.0	-46.2	-25.0	-21.2	
5.1250	2.5	H	3.0	39.8	1.0	-36.3	-25.0	-11.3	
7.6875	1.6	H	3.0	39.3	1.0	-36.7	-25.0	-11.7	
10.2500	-8.9	H	3.0	38.6	1.0	-46.5	-25.0	-21.5	
Mid Ch, (2605 MHz)									
5.2100	-6.3	V	3.0	39.8	1.0	-45.1	-25.0	-20.1	
7.8150	-2.5	V	3.0	39.3	1.0	-40.7	-25.0	-15.7	
10.4200	-5.6	V	3.0	38.5	1.0	-43.1	-25.0	-18.1	
5.2100	2.1	H	3.0	39.8	1.0	-36.7	-25.0	-11.7	
7.8150	-2.0	H	3.0	39.3	1.0	-40.3	-25.0	-15.3	
10.4200	-9.1	H	3.0	38.5	1.0	-46.6	-25.0	-21.6	
High Ch, (2647.5 MHz)									
5.2950	-5.7	V	3.0	39.9	1.0	-44.5	-25.0	-19.5	
7.9425	-4.6	V	3.0	39.2	1.0	-42.8	-25.0	-17.8	
10.5900	-4.3	V	3.0	38.5	1.0	-41.8	-25.0	-16.8	
5.2950	1.9	H	3.0	39.9	1.0	-36.9	-25.0	-11.9	
7.9425	-2.4	H	3.0	39.2	1.0	-40.6	-25.0	-15.6	
10.5900	-8.9	H	3.0	38.5	1.0	-46.4	-25.0	-21.4	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE

Band 41

10MHz

QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-18-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 41, 10MHz BW, QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2560 MHz)									
5.1200	-4.5	V	3.0	39.8	1.0	-43.3	-25.0	-18.3	
7.6800	-1.4	V	3.0	39.3	1.0	-39.7	-25.0	-14.7	
10.2400	-3.8	V	3.0	38.6	1.0	-41.4	-25.0	-16.4	
5.1200	0.0	H	3.0	39.8	1.0	-38.9	-25.0	-13.9	
7.6800	-0.9	H	3.0	39.3	1.0	-39.2	-25.0	-14.2	
10.2400	-8.2	H	3.0	38.6	1.0	-45.8	-25.0	-20.8	
Mid Ch, (2605 MHz)									
5.2100	-7.0	V	3.0	39.8	1.0	-45.8	-25.0	-20.8	
7.8150	-2.5	V	3.0	39.3	1.0	-40.7	-25.0	-15.7	
10.4200	-5.6	V	3.0	38.5	1.0	-43.2	-25.0	-18.2	
5.2100	0.2	H	3.0	39.8	1.0	-38.7	-25.0	-13.7	
7.8150	-4.2	H	3.0	39.3	1.0	-42.5	-25.0	-17.5	
10.4200	-8.4	H	3.0	38.5	1.0	-46.0	-25.0	-21.0	
High Ch, (2650 MHz)									
5.3000	-5.3	V	3.0	39.9	1.0	-44.1	-25.0	-19.1	
7.9500	-3.2	V	3.0	39.2	1.0	-41.4	-25.0	-16.4	
10.6000	-5.0	V	3.0	38.5	1.0	-42.5	-25.0	-17.5	
5.3000	2.0	H	3.0	39.9	1.0	-36.8	-25.0	-11.8	
7.9500	0.0	H	3.0	39.2	1.0	-38.2	-25.0	-13.2	
10.6000	-8.6	H	3.0	38.5	1.0	-46.1	-25.0	-21.1	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

LTE

Band 41

10MHz

16QAM

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-18-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 41, 10MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2560 MHz)									
5.1200	-4.6	V	3.0	39.8	1.0	-43.4	-25.0	-18.4	
7.6800	-2.6	V	3.0	39.3	1.0	-40.9	-25.0	-15.9	
10.2400	-5.4	V	3.0	38.6	1.0	-43.0	-25.0	-18.0	
5.1200	-0.2	H	3.0	39.8	1.0	-39.0	-25.0	-14.0	
7.6800	-1.2	H	3.0	39.3	1.0	-39.6	-25.0	-14.6	
10.2400	-8.2	H	3.0	38.6	1.0	-45.8	-25.0	-20.8	
Mid Ch, (2605 MHz)									
5.2100	-6.8	V	3.0	39.8	1.0	-45.7	-25.0	-20.7	
7.8150	-1.7	V	3.0	39.3	1.0	-40.0	-25.0	-15.0	
10.4200	-6.2	V	3.0	38.5	1.0	-43.7	-25.0	-18.7	
5.2100	0.5	H	3.0	39.8	1.0	-38.3	-25.0	-13.3	
7.8150	-3.8	H	3.0	39.3	1.0	-42.0	-25.0	-17.0	
10.4200	-9.4	H	3.0	38.5	1.0	-47.0	-25.0	-22.0	
High Ch, (2650 MHz)									
5.3000	-5.2	V	3.0	39.9	1.0	-44.1	-25.0	-19.1	
7.9500	-4.1	V	3.0	39.2	1.0	-42.3	-25.0	-17.3	
10.6000	-4.8	V	3.0	38.5	1.0	-42.3	-25.0	-17.3	
5.3000	2.7	H	3.0	39.9	1.0	-36.2	-25.0	-11.2	
7.9500	-0.1	H	3.0	39.2	1.0	-38.3	-25.0	-13.3	
10.6000	-8.1	H	3.0	38.5	1.0	-45.6	-25.0	-20.6	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE

Band 41

5MHz

QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-18-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 41, 5MHz BW, QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2557.5 MHz)									
5.1150	-5.3	V	3.0	39.8	1.0	-44.1	-25.0	-19.1	
7.6725	-2.0	V	3.0	39.3	1.0	-40.3	-25.0	-15.3	
10.2300	-8.6	V	3.0	38.6	1.0	-46.1	-25.0	-21.1	
5.1150	-0.1	H	3.0	39.8	1.0	-38.9	-25.0	-13.9	
7.6725	1.5	H	3.0	39.3	1.0	-36.8	-25.0	-11.8	
10.2300	-9.5	H	3.0	38.6	1.0	-47.1	-25.0	-22.1	
Mid Ch, (2605 MHz)									
5.2100	-5.2	V	3.0	39.8	1.0	-44.0	-25.0	-19.0	
7.8150	-3.6	V	3.0	39.3	1.0	-41.8	-25.0	-16.8	
10.4200	-6.9	V	3.0	38.5	1.0	-44.4	-25.0	-19.4	
5.2100	1.0	H	3.0	39.8	1.0	-37.9	-25.0	-12.9	
7.8150	-2.4	H	3.0	39.3	1.0	-40.7	-25.0	-15.7	
10.4200	-8.8	H	3.0	38.5	1.0	-46.3	-25.0	-21.3	
High Ch, (2652.5 MHz)									
5.3050	-4.5	V	3.0	39.9	1.0	-43.4	-25.0	-18.4	
7.9575	-3.2	V	3.0	39.2	1.0	-41.4	-25.0	-16.4	
10.6100	-4.9	V	3.0	38.5	1.0	-42.5	-25.0	-17.5	
5.3050	1.6	H	3.0	39.9	1.0	-37.3	-25.0	-12.3	
7.9575	-0.5	H	3.0	39.2	1.0	-38.7	-25.0	-13.7	
10.6100	-8.4	H	3.0	38.5	1.0	-46.0	-25.0	-21.0	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

LTE

Band 41

5MHz

16QAM

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 09-18-17
Test Engineer: JH Park
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 41, 5MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2557.5 MHz)									
5.1150	-4.7	V	3.0	39.8	1.0	-43.5	-25.0	-18.5	
7.6725	-3.1	V	3.0	39.3	1.0	-41.4	-25.0	-16.4	
10.2300	-9.4	V	3.0	38.6	1.0	-47.0	-25.0	-22.0	
5.1150	-0.3	H	3.0	39.8	1.0	-39.1	-25.0	-14.1	
7.6725	1.6	H	3.0	39.3	1.0	-36.7	-25.0	-11.7	
10.2300	-9.1	H	3.0	38.6	1.0	-46.7	-25.0	-21.7	
Mid Ch, (2605 MHz)									
5.2100	-5.4	V	3.0	39.8	1.0	-44.2	-25.0	-19.2	
7.8150	-3.5	V	3.0	39.3	1.0	-41.8	-25.0	-16.8	
10.4200	-7.5	V	3.0	38.5	1.0	-45.0	-25.0	-20.0	
5.2100	1.1	H	3.0	39.8	1.0	-37.7	-25.0	-12.7	
7.8150	-1.3	H	3.0	39.3	1.0	-39.5	-25.0	-14.5	
10.4200	-8.7	H	3.0	38.5	1.0	-46.2	-25.0	-21.2	
High Ch, (2652.5 MHz)									
5.3050	-4.6	V	3.0	39.9	1.0	-43.5	-25.0	-18.5	
7.9575	-3.5	V	3.0	39.2	1.0	-41.7	-25.0	-16.7	
10.6100	-5.4	V	3.0	38.5	1.0	-42.9	-25.0	-17.9	
5.3050	1.1	H	3.0	39.9	1.0	-37.8	-25.0	-12.8	
7.9575	-0.9	H	3.0	39.2	1.0	-39.1	-25.0	-14.1	
10.6100	-8.0	H	3.0	38.5	1.0	-45.5	-25.0	-20.5	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 41 (with Protective cover)

LTE Band 41 20MHz QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 10-11-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 41, 20MHz BW, QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2565 MHz)									
5.1300	-3.1	V	3.0	39.8	1.0	-41.9	-25.0	-16.9	
7.6950	1.2	V	3.0	39.3	1.0	-37.1	-25.0	-12.1	
10.2600	-3.3	V	3.0	38.6	1.0	-40.9	-25.0	-15.9	
5.1300	4.1	H	3.0	39.8	1.0	-34.7	-25.0	-9.7	
7.6950	-1.8	H	3.0	39.3	1.0	-40.1	-25.0	-15.1	
10.2600	-6.0	H	3.0	38.6	1.0	-43.6	-25.0	-18.6	
Mid Ch, (2605 MHz)									
5.2100	-4.3	V	3.0	39.8	1.0	-43.2	-25.0	-18.2	
7.8150	-3.4	V	3.0	39.3	1.0	-41.7	-25.0	-16.7	
10.4200	-6.4	V	3.0	38.5	1.0	-43.9	-25.0	-18.9	
5.2100	2.9	H	3.0	39.8	1.0	-35.9	-25.0	-10.9	
7.8150	-3.1	H	3.0	39.3	1.0	-41.4	-25.0	-16.4	
10.4200	-8.0	H	3.0	38.5	1.0	-45.5	-25.0	-20.5	
High Ch, (2645 MHz)									
5.2900	-5.9	V	3.0	39.9	1.0	-44.8	-25.0	-19.8	
7.9350	-0.8	V	3.0	39.2	1.0	-39.0	-25.0	-14.0	
10.5800	-3.9	V	3.0	38.5	1.0	-41.4	-25.0	-16.4	
5.2900	1.7	H	3.0	39.9	1.0	-37.2	-25.0	-12.2	
7.9350	-2.5	H	3.0	39.2	1.0	-40.7	-25.0	-15.7	
10.5800	-6.7	H	3.0	38.5	1.0	-44.2	-25.0	-19.2	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

LTE Band 41 20MHz 16QAM

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 10-11-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 41, 20MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2565 MHz)									
5.1300	-3.0	V	3.0	39.8	1.0	-41.8	-25.0	-16.8	
7.6950	0.9	V	3.0	39.3	1.0	-37.4	-25.0	-12.4	
10.2600	-3.9	V	3.0	38.6	1.0	-41.4	-25.0	-16.4	
5.1300	4.0	H	3.0	39.8	1.0	-34.8	-25.0	-9.8	
7.6950	-2.3	H	3.0	39.3	1.0	-40.6	-25.0	-15.6	
10.2600	-6.6	H	3.0	38.6	1.0	-44.1	-25.0	-19.1	
Mid Ch, (2605 MHz)									
5.2100	-4.2	V	3.0	39.8	1.0	-43.0	-25.0	-18.0	
7.8150	-3.9	V	3.0	39.3	1.0	-42.1	-25.0	-17.1	
10.4200	-7.7	V	3.0	38.5	1.0	-45.2	-25.0	-20.2	
5.2100	3.0	H	3.0	39.8	1.0	-35.8	-25.0	-10.8	
7.8150	-3.7	H	3.0	39.3	1.0	-41.9	-25.0	-16.9	
10.4200	-7.8	H	3.0	38.5	1.0	-45.4	-25.0	-20.4	
High Ch, (2645 MHz)									
5.2900	-6.2	V	3.0	39.9	1.0	-45.0	-25.0	-20.0	
7.9350	-0.3	V	3.0	39.2	1.0	-38.5	-25.0	-13.5	
10.5800	-3.5	V	3.0	38.5	1.0	-41.0	-25.0	-16.0	
5.2900	1.9	H	3.0	39.9	1.0	-36.9	-25.0	-11.9	
7.9350	-2.9	H	3.0	39.2	1.0	-41.1	-25.0	-16.1	
10.5800	-7.4	H	3.0	38.5	1.0	-44.9	-25.0	-19.9	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE

Band 41

15MHz

QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 10-11-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 41, 15MHz BW,QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2562.5 MHz)									
5.1250	-3.3	V	3.0	39.8	1.0	-42.1	-25.0	-17.1	
7.6875	3.1	V	3.0	39.3	1.0	-35.2	-25.0	-10.2	
10.2500	-4.4	V	3.0	38.6	1.0	-42.0	-25.0	-17.0	
5.1250	4.9	H	3.0	39.8	1.0	-33.9	-25.0	-8.9	
7.6875	-0.5	H	3.0	39.3	1.0	-38.9	-25.0	-13.9	
10.2500	-6.8	H	3.0	38.6	1.0	-44.3	-25.0	-19.3	
Mid Ch, (2605 MHz)									
5.2100	-3.4	V	3.0	39.8	1.0	-42.2	-25.0	-17.2	
7.8150	-4.5	V	3.0	39.3	1.0	-42.7	-25.0	-17.7	
10.4200	-5.5	V	3.0	38.5	1.0	-43.1	-25.0	-18.1	
5.2100	3.1	H	3.0	39.8	1.0	-35.7	-25.0	-10.7	
7.8150	-3.0	H	3.0	39.3	1.0	-41.3	-25.0	-16.3	
10.4200	-7.7	H	3.0	38.5	1.0	-45.3	-25.0	-20.3	
High Ch, (2647.5 MHz)									
5.2950	-5.4	V	3.0	39.9	1.0	-44.3	-25.0	-19.3	
7.9425	-0.1	V	3.0	39.2	1.0	-38.3	-25.0	-13.3	
10.5900	-4.6	V	3.0	38.5	1.0	-42.1	-25.0	-17.1	
5.2950	2.4	H	3.0	39.9	1.0	-36.5	-25.0	-11.5	
7.9425	-1.5	H	3.0	39.2	1.0	-39.7	-25.0	-14.7	
10.5900	-7.9	H	3.0	38.5	1.0	-45.4	-25.0	-20.4	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

LTE

Band 41

15MHz

16QAM

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 10-11-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 41, 15MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2562.5 MHz)									
5.1250	-2.5	V	3.0	39.8	1.0	-41.3	-25.0	-16.3	
7.6875	2.8	V	3.0	39.3	1.0	-35.5	-25.0	-10.5	
10.2500	-3.5	V	3.0	38.6	1.0	-41.1	-25.0	-16.1	
5.1250	4.3	H	3.0	39.8	1.0	-34.5	-25.0	-9.5	
7.6875	-0.5	H	3.0	39.3	1.0	-38.8	-25.0	-13.8	
10.2500	-6.4	H	3.0	38.6	1.0	-43.9	-25.0	-18.9	
Mid Ch, (2605 MHz)									
5.2100	-4.0	V	3.0	39.8	1.0	-42.9	-25.0	-17.9	
7.8150	-4.6	V	3.0	39.3	1.0	-42.8	-25.0	-17.8	
10.4200	-5.4	V	3.0	38.5	1.0	-43.0	-25.0	-18.0	
5.2100	3.6	H	3.0	39.8	1.0	-35.2	-25.0	-10.2	
7.8150	-3.2	H	3.0	39.3	1.0	-41.5	-25.0	-16.5	
10.4200	-8.4	H	3.0	38.5	1.0	-45.9	-25.0	-20.9	
High Ch, (2647.5 MHz)									
5.2950	-5.5	V	3.0	39.9	1.0	-44.4	-25.0	-19.4	
7.9425	-0.5	V	3.0	39.2	1.0	-38.7	-25.0	-13.7	
10.5900	-4.3	V	3.0	38.5	1.0	-41.9	-25.0	-16.9	
5.2950	2.5	H	3.0	39.9	1.0	-36.4	-25.0	-11.4	
7.9425	-1.4	H	3.0	39.2	1.0	-39.6	-25.0	-14.6	
10.5900	-8.1	H	3.0	38.5	1.0	-45.7	-25.0	-20.7	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE

Band 41

10MHz

QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 10-11-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 41, 10MHz BW, QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2560 MHz)									
5.1200	-4.7	V	3.0	39.8	1.0	-43.5	-25.0	-18.5	
7.6800	3.8	V	3.0	39.3	1.0	-34.5	-25.0	-9.5	
10.2400	-3.7	V	3.0	38.6	1.0	-41.3	-25.0	-16.3	
5.1200	4.1	H	3.0	39.8	1.0	-34.7	-25.0	-9.7	
7.6800	1.9	H	3.0	39.3	1.0	-36.4	-25.0	-11.4	
10.2400	-7.0	H	3.0	38.6	1.0	-44.5	-25.0	-19.5	
Mid Ch, (2605 MHz)									
5.2100	-5.0	V	3.0	39.8	1.0	-43.8	-25.0	-18.8	
7.8150	-3.7	V	3.0	39.3	1.0	-42.0	-25.0	-17.0	
10.4200	-5.8	V	3.0	38.5	1.0	-43.4	-25.0	-18.4	
5.2100	3.7	H	3.0	39.8	1.0	-35.1	-25.0	-10.1	
7.8150	-2.4	H	3.0	39.3	1.0	-40.6	-25.0	-15.6	
10.4200	-7.9	H	3.0	38.5	1.0	-45.5	-25.0	-20.5	
High Ch, (2650 MHz)									
5.3000	-3.7	V	3.0	39.9	1.0	-42.5	-25.0	-17.5	
7.9500	-2.5	V	3.0	39.2	1.0	-40.7	-25.0	-15.7	
10.6000	-2.8	V	3.0	38.5	1.0	-40.3	-25.0	-15.3	
5.3000	5.6	H	3.0	39.9	1.0	-33.3	-25.0	-8.3	
7.9500	-3.8	H	3.0	39.2	1.0	-42.0	-25.0	-17.0	
10.6000	-7.6	H	3.0	38.5	1.0	-45.1	-25.0	-20.1	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

LTE

Band 41

10MHz

16QAM

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 10-11-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 41, 10MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2560 MHz)									
5.1200	-5.2	V	3.0	39.8	1.0	-44.0	-25.0	-19.0	
7.6800	3.2	V	3.0	39.3	1.0	-35.1	-25.0	-10.1	
10.2400	-3.7	V	3.0	38.6	1.0	-41.3	-25.0	-16.3	
5.1200	3.9	H	3.0	39.8	1.0	-34.9	-25.0	-9.9	
7.6800	1.1	H	3.0	39.3	1.0	-37.2	-25.0	-12.2	
10.2400	-7.2	H	3.0	38.6	1.0	-44.8	-25.0	-19.8	
Mid Ch, (2605 MHz)									
5.2100	-4.9	V	3.0	39.8	1.0	-43.7	-25.0	-18.7	
7.8150	-3.9	V	3.0	39.3	1.0	-42.1	-25.0	-17.1	
10.4200	-5.2	V	3.0	38.5	1.0	-42.7	-25.0	-17.7	
5.2100	4.1	H	3.0	39.8	1.0	-34.7	-25.0	-9.7	
7.8150	-2.7	H	3.0	39.3	1.0	-40.9	-25.0	-15.9	
10.4200	-7.5	H	3.0	38.5	1.0	-45.1	-25.0	-20.1	
High Ch, (2650 MHz)									
5.3000	-4.2	V	3.0	39.9	1.0	-43.1	-25.0	-18.1	
7.9500	-2.9	V	3.0	39.2	1.0	-41.1	-25.0	-16.1	
10.6000	-3.3	V	3.0	38.5	1.0	-40.8	-25.0	-15.8	
5.3000	5.2	H	3.0	39.9	1.0	-33.6	-25.0	-8.6	
7.9500	-4.3	H	3.0	39.2	1.0	-42.5	-25.0	-17.5	
10.6000	-8.3	H	3.0	38.5	1.0	-45.8	-25.0	-20.8	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE

Band 41

5MHz

QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 10-11-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 41, 5MHz BW, QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2557.5 MHz)									
5.1150	-3.1	V	3.0	39.8	1.0	-41.9	-25.0	-16.9	
7.6725	2.0	V	3.0	39.3	1.0	-36.3	-25.0	-11.3	
10.2300	-4.8	V	3.0	38.6	1.0	-42.4	-25.0	-17.4	
5.1150	4.6	H	3.0	39.8	1.0	-34.2	-25.0	-9.2	
7.6725	2.4	H	3.0	39.3	1.0	-35.9	-25.0	-10.9	
10.2300		H	3.0	38.6	1.0	-37.6	-25.0	-12.6	
Mid Ch, (2605 MHz)									
5.2100	-5.0	V	3.0	39.8	1.0	-43.9	-25.0	-18.9	
7.8150	-3.0	V	3.0	39.3	1.0	-41.3	-25.0	-16.3	
10.4200	-4.7	V	3.0	38.5	1.0	-42.2	-25.0	-17.2	
5.2100	4.6	H	3.0	39.8	1.0	-34.2	-25.0	-9.2	
7.8150	-2.8	H	3.0	39.3	1.0	-41.0	-25.0	-16.0	
10.4200	-7.9	H	3.0	38.5	1.0	-45.5	-25.0	-20.5	
High Ch, (2652.5 MHz)									
5.3050	-3.2	V	3.0	39.9	1.0	-42.0	-25.0	-17.0	
7.9575	-1.7	V	3.0	39.2	1.0	-39.9	-25.0	-14.9	
10.6100	-2.7	V	3.0	38.5	1.0	-40.2	-25.0	-15.2	
5.3050	6.0	H	3.0	39.9	1.0	-32.9	-25.0	-7.9	
7.9575	-1.9	H	3.0	39.2	1.0	-40.1	-25.0	-15.1	
10.6100	-7.5	H	3.0	38.5	1.0	-45.0	-25.0	-20.0	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

LTE

Band 41

5MHz

16QAM

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788148881
Date: 10-11-17
Test Engineer: YH Lim
Configuration: EUT / AC Adapter / Ear Phone / Z-Position
Mode: TX, LTE BAND 41, 5MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2557.5 MHz)									
5.1150	-3.3	V	3.0	39.8	1.0	-42.1	-25.0	-17.1	
7.6725	1.8	V	3.0	39.3	1.0	-36.5	-25.0	-11.5	
10.2300	-5.9	V	3.0	38.6	1.0	-43.5	-25.0	-18.5	
5.1150	4.4	H	3.0	39.8	1.0	-34.4	-25.0	-9.4	
7.6725	2.6	H	3.0	39.3	1.0	-35.7	-25.0	-10.7	
10.2300	-7.6	H	3.0	38.6	1.0	-45.2	-25.0	-20.2	
Mid Ch, (2605 MHz)									
5.2100	-4.3	V	3.0	39.8	1.0	-43.1	-25.0	-18.1	
7.8150	-3.5	V	3.0	39.3	1.0	-41.8	-25.0	-16.8	
10.4200	-4.8	V	3.0	38.5	1.0	-42.3	-25.0	-17.3	
5.2100	4.2	H	3.0	39.8	1.0	-34.7	-25.0	-9.7	
7.8150	-3.0	H	3.0	39.3	1.0	-41.3	-25.0	-16.3	
10.4200	-8.3	H	3.0	38.5	1.0	-45.8	-25.0	-20.8	
High Ch, (2652.5 MHz)									
5.3050	-3.0	V	3.0	39.9	1.0	-41.9	-25.0	-16.9	
7.9575	-2.4	V	3.0	39.2	1.0	-40.6	-25.0	-15.6	
10.6100	-2.2	V	3.0	38.5	1.0	-39.8	-25.0	-14.8	
5.3050	6.0	H	3.0	39.9	1.0	-32.9	-25.0	-7.9	
7.9575	-1.6	H	3.0	39.2	1.0	-39.8	-25.0	-14.8	
10.6100	-8.2	H	3.0	38.5	1.0	-45.7	-25.0	-20.7	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.