FCC CFR47 PART 15 SUBPART C

ANT+
CERTIFICATION TEST REPORT

FOR

GSM/WCDMA/LTE Tablet with Bluetooth, DTS/UNII a/b/g/n and ANT+

MODEL NUMBER: SM-T555

FCC ID: A3LSMT555

REPORT NUMBER: 15I19862-E6

ISSUE DATE: JANUARY 30, 2015

Prepared for
SAMSUNG ELECTRONICS CO., LTD.
129 Samsung-ro, Yeongtong-gu, Suwon-si,
Gyeonggi-do, 443-742, Korea

Prepared by
UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888

NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	01/30/15	Initial Issue	P. Zhang

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS 4

2. TEST METHODOLOGY 5

3. FACILITIES AND ACCREDITATION 5

4. CALIBRATION AND UNCERTAINTY 5

4.1. MEASURING INSTRUMENT CALIBRATION 5

4.2. SAMPLE CALCULATION 5

4.3. MEASUREMENT UNCERTAINTY 5

5. EQUIPMENT UNDER TEST 6

5.1. DESCRIPTION OF EUT 6

5.2. MAXIMUM OUTPUT FUNDAMENTAL FIELD STRENGTH 6

5.3. DESCRIPTION OF AVAILABLE ANTENNAS 6

5.4. WORST-CASE CONFIGURATION AND MODE 6

5.5. DESCRIPTION OF TEST SETUP 7

6. TEST AND MEASUREMENT EQUIPMENT 9

7. LIMITS AND RESULTS 10

7.1. 99% BANDWIDTH 10

7.2. TRANSMITTER RADIATED EMISSIONS 13

7.2.1. DUTY CYCLE 15

7.2.2. FUNDAMENTAL FREQUENCY RADIATED EMISSION 16

7.2.3. TRANSMITTER RESTRICTED BAND EDGES 17

7.2.4. SPURIOUS BELOW 1 GHz 22

8. AC POWER LINE CONDUCTED EMISSIONS 25

9. SETUP PHOTOS 30

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

1. ATTESTATION OF TEST RESULTS

COMPANY NAME:	**SAMSUNG ELECTRONICS CO., LTD.**
EUT DESCRIPTION:	**GSM/WCDMA/LTE Tablet with Bluetooth, WLAN 2.4GHz b/g/n, and ANT+**
MODEL:	**SM-T555**
SERIAL NUMBER:	**R32G1032KGK (Conducted), R32G1032KDZ (Radiated)**
DATE TESTED:	**JANUARY 24 - 26, 2015**

APPLICABLE STANDARDS	
STANDARD	**TEST RESULTS**
CFR 47 Part 15 Subpart C	Pass

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Verification Services Inc. By:

PENG ZHANG
CONSUMER TECHNOLOGY DIVISION
PROJECT LEAD
UL Verification Services Inc.

Tested By:

CHARLES VERGONIO
CONSUMER TECHNOLOGY DIVISION
LAB ENGINEER
UL Verification Services Inc.

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street
☐ Chamber A	☐ Chamber D
☒ Chamber B	☐ Chamber E
☒ Chamber C	☐ Chamber F

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at http://ts.nist.gov/standards/scopes/2000650.htm.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB)

36.5 dBuV + 18.7 dB/m + 0.6 dB – 26.9 dB = 28.9 dBuV/m

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 26000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE Tablet with Bluetooth, DTS/UNII a/b/g/n, and ANT+.

5.2. MAXIMUM OUTPUT FUNDAMENTAL FIELD STRENGTH

The ANT+ mode has maximum output fundamental field strength as follows:

Frequency Range (MHz)	Mode	Peak E-field Strength (dBuV/m)	Avg E-field Strength (dBuV/m)	Distance (m)
2402 - 2480	ANT +	73.34	72.70	3.00

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antenna, with a maximum gain of -1.6 dBi.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y, Z it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	**Manufacturer**	**Model**	**Serial Number**	**FCC ID**
AC Adapter	SAMSUNG	EP-TA12EWE	N/A	N/A
Earphone	SAMSUNG	N/A	N/A	N/A

I/O CABLES

I/O Cable List						
Cable No	**Port**	**# of identical ports**	**Connector Type**	**Cable Type**	**Cable Length (m)**	**Remarks**
1	DC Power	1	Mini-USB	Shielded	80cm	N/A
2	Audio	1	Mini-Jack	Unshielded	1m	N/A

TEST SETUP

The EUT is set to continuously transmit in ANT + test mode

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

SETUP DIAGRAM FOR TESTS



This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	**Manufacturer**	**Model**	**Asset**	**Cal Due**
Antenna, Biconolog, 30MHz-1 GHz	Sunol Sciences	JB1	C01171	02/13/15
Antenna, Horn, 18GHz	EMCO	3115	C00783	10/25/15
Antenna, Horn, 26.5 GHz	ARA	MWH-1826/B	C00980	11/14/15
RF Preamplifier, 100KHz -> 1300MHz	HP	TBD	C00825	06/01/15
RF Preamplifier, 1GHz - 18GHz	Miteq	NSP4000-SP2	924343	03/23/15
RF Preamplifier, 1GHz - 26.5GHz	HP	8449B	F00351	06/27/15
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01069	12/20/15
CBT Bluetooth Tester	R & S	CBT	None	07/12/15
Peak Power Meter	Agilent / HP	E4416A	C00963	12/13/15
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	12/13/15
LISN, 30 MHz	FCC	50/250-25-2	C00626	01/14/16

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

7. LIMITS AND RESULTS

7.1. 99% BANDWIDTH

LIMIT

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

RESULTS

Channel	Frequency (MHz)	99% Bandwidth (kHz)
Low	2402	833.8
Middle	2442	832.3
High	2480	877.7

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

99% BANDWIDTH

99% BANDWIDTH LOW CH



99% BANDWIDTH MID CH



This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

99% BANDWIDTH HIGH CH



This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

7.2. TRANSMITTER RADIATED EMISSIONS

TEST PROCEDURE

ANSI C63.4: 2009

LIMIT

FCC 15.249

Operation within the bands 902–928 MHz, 2400–2483.5 MHz, 5725–5875 MHZ, and 24.0–24.25 GHz.
(a) Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.

(e) As shown in Sec. 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009–0.490	2400/F(kHz)	300
0.490–1.705	24000/F(kHz)	30
1.705–30.0	30	30
30–88	100 **	3
88–216	150 **	3
216–960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

RESULTS

7.2.1. DUTY CYCLE



Duty Cycle = ON time / Period = 0.133 / 62.47 = 0.21%
Duty Cycle Factor= 20log(0.0021) = -53.56 dB
VBW=1/(0.133ms)= 7.518kHz

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

7.2.2. FUNDAMENTAL FREQUENCY RADIATED EMISSION

FCC, VCCI, CISPR, CE, AUSTEL, NZ
UL, CSA, TUV, BSMI, DHHS, NVLAP

47173 BENICIA STREET, FREMONT, CA 94538, USA

Project #:	15I19862
Report #:	15I19862
Date& Time:	01/25/15
Test Engr:	R. Alegre

Company:	Samsung
EUT Description:	GSM/WCDMA/LTE Tablet + Bluetooth, DTS/UNll a/b/g/n & ANT+
Test Configuration :	X POSITION
Type of Test:	FCC
Mode of Operation:	Transmitting : ANT+ mode

M% = ((t1+t2+t3+...)/T) * 66.83% = 0.21%

Av Reading = Pk Reading + 20*log(M%)
20 * log (M%) = -53.56

Freq. (MHz)	Pk Rdg (dBuV)	Av Rdg (dBuV)	AF (dB)	Closs (dB)	Pre-amp (dB)	Pk Level (dBuV/m)	Av Level (dBuV/m)	Pk Limit FCC_B	Av Limit FCC_B	Pk Margin (dB)	Avg Margin (dB)	Pol (H/V)	Az (Deg)	Height (Meter)
Low channel														
2402.00	70.45	68.85	32.10	-33.00	0.00	69.55	67.95	114.00	94.00	-44.45	-26.05	3mV	0.00	1.00
2402.00	74.24	73.60	32.10	-33.00	0.00	73.34	72.70	114.00	94.00	-40.66	-21.30	3mH	0.00	2.00
Mid channel														
2442.00	70.39	69.28	32.10	-33.00	0.00	69.49	68.38	114.00	94.00	-44.51	-25.62	3mV	0.00	1.00
2442.00	73.59	73.12	32.10	-33.00	0.00	72.69	72.22	114.00	94.00	-41.31	-21.78	3mH	0.00	2.00
High channel														
2480.00	69.53	68.40	32.10	-33.00	0.00	68.63	67.50	114.00	94.00	-45.37	-26.50	3mV	0.00	1.00
2480.00	73.48	72.67	32.10	-33.00	0.00	72.58	71.77	114.00	94.00	-41.42	-22.23	3mH	0.00	2.00

AVG VB=1/Ton, Voltage Averaging Max Hold where: Ton is the duration of the packet

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

7.2.3. TRANSMITTER RESTRICTED BAND EDGES

BANDEDGE (LOW CHANNEL, HORIZONTAL)



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/ Fltr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	2.354	43.34	PK	31.8	-23.1	52.04	-	-	74	-21.96	316	234	H
4	2.396	29.78	VB1T	32	-23.1	38.68	54	-15.32	-	-	316	234	H
1	2.4	41.28	PK	32	-23.1	50.18	-	-	74	-23.82	316	234	H
3	2.4	29.64	VB1T	32	-23.1	38.54	54	-15.46	-	-	316	234	H

PK - Peak detector

VB1T - FHSS Method: VB=1/Ton, Voltage Averaging Max Hold where: Ton is the duration of the packet

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

BANDEDGE (LOW CHANNEL, VERTICAL)



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/ Fltr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	2.364	43.83	PK	31.9	-23.1	52.63	-	-	74	-21.37	177	398	V
4	2.397	29.88	VB1T	32	-23.1	38.78	54	-15.22	-	-	177	398	V
1	2.4	40.89	PK	32	-23.1	49.79	-	-	74	-24.21	177	398	V
3	2.4	29.78	VB1T	32	-23.1	38.68	54	-15.32	-	-	177	398	V

PK - Peak detector

VB1T - FHSS Method: VB=1/Ton, Voltage Averaging Max Hold where: Ton is the duration of the packet

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

BANDEDGE (HIGH CHANNEL, VERTICAL)



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/ Fltr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	2.484	40.49	PK	32.3	-22.8	49.99	-	-	74	-24.01	344	237	H
3	2.484	29.56	VB1T	32.3	-22.8	39.06	54	-14.94	-	-	344	237	H
4	2.507	29.82	VB1T	32.3	-22.8	39.32	54	-14.68	-	-	344	237	H
2	2.548	43.02	PK	32.4	-22.7	52.72	-	-	74	-21.28	344	237	H

PK - Peak detector

VB1T - FHSS Method: VB=1/Ton, Voltage Averaging Max Hold where: Ton is the duration of the packet

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/ Fltr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	2.484	40.04	PK	32.3	-22.8	49.54	-	-	74	-24.46	215	336	V
3	2.484	29.63	VB1T	32.3	-22.8	39.13	54	-14.87	-	-	215	336	V
2	2.531	42.96	PK	32.4	-22.7	52.66	-	-	74	-21.34	215	336	V
4	2.532	29.68	VB1T	32.4	-22.7	39.38	54	-14.62	-	-	215	336	V

PK - Peak detector

VB1T - FHSS Method: VB=1/Ton, Voltage Averaging Max Hold where: Ton is the duration of the packet

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

HARMONICS AND SPURIOUS EMISSIONS ABOVE 1GHz

HARMONICS

FCC, VCCI, CISPR, CE, AUSTEL, NZ
UL, CSA, TUV, BSMI, DHHS, NVLAP

47173 BENICIA STREET, FREMONT, CA 94538, USA

Project #:	15I19862
Report #:	15I19862
Date& Time:	01/25/15
Test Engr:	R. Alegre

Company:	Samsung
EUT Description:	GSM/WCDMA/LTE Tablet + Bluetooth, DTS/UNll a/b/g/n & ANT+
Test Configuration :	X POSITION
Type of Test:	FCC
Mode of Operation:	Transmitting : ANT+ mode

M% = ((t1+t2+t3+...)/T) * 66.83% = 0.21%

Av Reading = Pk Reading + 20*log(M%)
20 * log (M%) = -53.56

Freq.	Pk Rdg	Av Rdg	AF	Closs	Pre-amp	Pk Level	Av Level	Pk Limit	Av Limit	Pk Margin	Avg Margin	Pol	Az	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	FCC_B	FCC_B	(dB)	(dB)	(H/V)	(Deg)	(Meter)
Low channel														
4804.00	43.38	33.36	34.00	-31.00	0.00	46.38	36.36	74.00	54.00	-27.62	-17.64	3mV	0.00	1.00
4804.00	43.54	33.85	34.00	-31.00	0.00	46.54	36.85	74.00	54.00	-27.46	-17.15	3mH	0.00	2.00
Mid channel														
4884.00	43.26	33.74	34.00	-31.00	0.00	46.26	36.74	74.00	54.00	-27.74	-17.26	3mV	0.00	1.00
4884.00	43.11	33.90	34.00	-31.00	0.00	46.11	36.90	74.00	54.00	-27.89	-17.10	3mH	0.00	2.00
High channel														
4960.00	43.24	32.89	34.00	-31.00	0.00	46.24	35.89	74.00	54.00	-27.76	-18.11	3mV	0.00	1.00
4960.00	43.30	33.10	34.00	-31.00	0.00	46.30	36.10	74.00	54.00	-27.70	-17.90	3mH	0.00	2.00

AVG VB=1/Ton, Voltage Averaging Max Hold where: Ton is the duration of the packet

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

7.2.4. SPURIOUS BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (HORIZONTAL)



This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

SPURIOUS EMISSIONS 30 TO 1000 MHz (VERTICAL)



This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	AF T243 (dB/m)	Amp/Cbl (dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
5	* 243.4	38.97	PK	11.6	-26.5	24.07	46.02	-21.95	0-360	101	V
3	30.085	35.99	PK	20.7	-28.9	27.79	40	-12.21	0-360	101	V
1	47.255	46.54	PK	9.4	-28.7	27.24	40	-12.76	0-360	101	V
2	55.5425	54.63	PK	7.3	-28.6	33.33	40	-6.67	0-360	101	V
4	93.07	45.28	PK	8.4	-28.1	25.58	43.52	-17.94	0-360	101	V
6	357.95	35.97	PK	14.8	-25.9	24.87	46.02	-21.15	0-360	300	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

8. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

RSS-Gen 8.9

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST PROCEDURE

ANSI C63.4 - 2009

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

6 WORST EMISSIONS

Line-L1 .15 - 30MHz

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	T24 IL L1 (dB)	LC Cables 1&3 (dB)	Corrected Reading dBuV	CISPR 22 Class B QP	Margin to Limit (dB)	CISPR 22 Class B Avg	Margin to Limit (dB)
1	.2895	42	PK	.6	0	42.6	60.5	-17.9	-	-
2	.2895	25	Av	.6	0	25.6	-	-	50.5	-24.9
3	.411	40.7	PK	.4	0	41.1	57.6	-16.5	-	-
4	.411	21.42	Av	.4	0	21.82	-	-	47.6	-25.78
5	.825	44.7	PK	.3	0	45	56	-11	-	-
6	.825	23.85	Av	.3	0	24.15	-	-	46	-21.85
7	1.302	42.16	PK	.2	.1	42.46	56	-13.54	-	-
8	1.302	19.68	Av	.2	.1	19.98	-	-	46	-26.02
9	5.7075	38.58	PK	.2	.1	38.88	60	-21.12	-	-
10	5.7075	18.74	Av	.2	.1	19.04	-	-	50	-30.96
11	7.9485	38.36	PK	.2	.1	38.66	60	-21.34	-	-
12	7.9485	18.86	Av	.2	.1	19.16	-	-	50	-30.84

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

Line-L2 .15 - 30MHz

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	T24 IL L2 (dB)	LC Cables 2&3 (dB)	Corrected Reading dBuV	CISPR 22 Class B QP	Margin to Limit (dB)	CISPR 22 Class B Avg	Margin to Limit (dB)
13	.2895	36.8	PK	.6	0	37.4	60.5	-23.1	-	-
14	.2895	12.22	Av	.6	0	12.82	-	-	50.5	-37.68
15	.4245	39.81	PK	.4	0	40.21	57.4	-17.19	-	-
16	.4245	18.59	Av	.4	0	18.99	-	-	47.4	-28.41
17	.708	40.2	PK	.3	0	40.5	56	-15.5	-	-
18	.708	16.76	Av	.3	0	17.06	-	-	46	-28.94
19	.942	41.69	PK	.3	0	41.99	56	-14.01	-	-
20	.942	17.12	Av	.3	0	17.42	-	-	46	-28.58
21	3.381	42.48	PK	.2	.1	42.78	56	-13.22	-	-
22	3.381	30.9	Av	.2	.1	31.2	-	-	46	-14.8
23	7.3545	35.77	PK	.2	.1	36.07	60	-23.93	-	-
24	7.3545	17.46	Av	.2	.1	17.76	-	-	50	-32.24
25	13.8885	38.46	PK	.2	.2	38.86	60	-21.14	-	-
26	13.8885	23.27	Av	.2	.2	23.67	-	-	50	-26.33

PK - Peak detector

Av - average detection

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

LINE 1 RESULTS



This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

LINE 2 RESULTS



This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.