


Antenna-2 Power Spectral Density Measurements


	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Power Density [dBm]	Max Permissible Power Density [dBm/MHz]	Margin [dB]	Pass / Fail
Band 1	5180	36	a	6	-3.47	4.0	-7.47	Pass
	5200	40	a	6	-3.26	4.0	-7.26	Pass
	5240	48	a	6	-2.65	4.0	-6.65	Pass
	5180	36	n (20MHz)	6.5/7.2 (MCS0)	-3.02	4.0	-7.02	Pass
	5200	40	n (20MHz)	6.5/7.2 (MCS0)	-3.22	4.0	-7.22	Pass
	5240	48	n (20MHz)	6.5/7.2 (MCS0)	-3.05	4.0	-7.05	Pass
	5190	38	n (40MHz)	13.5/15 (MCS0)	-5.55	4.0	-9.55	Pass
	5230	46	n (40MHz)	13.5/15 (MCS0)	-5.49	4.0	-9.49	Pass
	5210	42	ac (80MHz)	29.3/32.5 (MCS0)	-10.96	4.0	-14.96	Pass
Band 2A	5260	52	a	6	-2.55	11.0	-13.55	Pass
	5280	56	a	6	-2.65	11.0	-13.65	Pass
	5320	64	a	6	-2.74	11.0	-13.74	Pass
	5260	52	n (20MHz)	6.5/7.2 (MCS0)	-2.73	11.0	-13.73	Pass
	5280	56	n (20MHz)	6.5/7.2 (MCS0)	-2.98	11.0	-13.98	Pass
	5320	64	n (20MHz)	6.5/7.2 (MCS0)	-3.02	11.0	-14.02	Pass
	5270	54	n (40MHz)	13.5/15 (MCS0)	-5.35	11.0	-16.35	Pass
	5310	62	n (40MHz)	13.5/15 (MCS0)	-5.60	11.0	-16.60	Pass
	5290	58	ac (80MHz)	29.3/32.5 (MCS0)	-11.32	11.0	-22.32	Pass
Band 2C	5500	100	a	6	-2.22	11.0	-13.22	Pass
	5580	116	a	6	-2.13	11.0	-13.13	Pass
	5700	140	a	6	-2.19	11.0	-13.19	Pass
	5500	100	n (20MHz)	6.5/7.2 (MCS0)	-2.76	11.0	-13.76	Pass
	5580	116	n (20MHz)	6.5/7.2 (MCS0)	-2.60	11.0	-13.60	Pass
	5700	140	n (20MHz)	6.5/7.2 (MCS0)	-2.65	11.0	-13.65	Pass
	5510	102	n (40MHz)	13.5/15 (MCS0)	-5.21	11.0	-16.21	Pass
	5550	110	n (40MHz)	13.5/15 (MCS0)	-5.01	11.0	-16.01	Pass
	5670	134	n (40MHz)	13.5/15 (MCS0)	-4.93	11.0	-15.93	Pass
	5530	106	ac (80MHz)	29.3/32.5 (MCS0)	-11.25	11.0	-22.25	Pass

Table 6-19. Conducted Power Spectral Density Measurements

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer	Page 72 of 182	




Plot 6-97. Peak Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 36)




Plot 6-98. Peak Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 40)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 73 of 182




Plot 6-99. Peak Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 48)




Plot 6-100. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 36)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 74 of 182




Plot 6-101. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 40)




Plot 6-102. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 48)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 75 of 182





Plot 6-103. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 38)




Plot 6-104. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 46)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 76 of 182






Plot 6-107. Peak Power Spectral Density Plot (802.11a (UNII Band 2A) – Ch. 56)




Plot 6-108. Peak Power Spectral Density Plot (802.11a (UNII Band 2A) – Ch. 64)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 78 of 182




Plot 6-109. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 52)




Plot 6-110. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 56)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 79 of 182




Plot 6-111. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 64)




Plot 6-112. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2A) – Ch. 54)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 80 of 182




Plot 6-113. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2A) – Ch. 62)




Plot 6-114. Peak Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 2A) – Ch. 58)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 81 of 182




Plot 6-115. Peak Power Spectral Density Plot (802.11a (UNII Band 2C) – Ch. 100)




Plot 6-116. Peak Power Spectral Density Plot (802.11a (UNII Band 2C) – Ch. 116)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 82 of 182




Plot 6-117. Peak Power Spectral Density Plot (802.11a (UNII Band 2C) – Ch. 140)




Plot 6-118. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 100)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 83 of 182




Plot 6-119. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 116)




Plot 6-120. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 140)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 84 of 182




Plot 6-121. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 102)




Plot 6-122. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 110)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 85 of 182



Plot 6-123. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 134)



Plot 6-124. Peak Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 106)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 86 of 182

Summed MIMO Power Spectral Density Measurements

	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Antenn-1 Power Density [dBm]	Antenn-2 Power Density [dBm]	Summed MIMO Power Density [dBm]	Max Permissible Power Density [dBm/MHz]	Margin [dB]	Pass / Fail
Band 1	5180	36	n (20MHz)	6.5/7.2 (MCS0)	-2.91	-3.02	0.05	4.0	-3.95	Pass
	5200	40	n (20MHz)	6.5/7.2 (MCS0)	-2.95	-3.22	-0.08	4.0	-4.08	Pass
	5240	48	n (20MHz)	6.5/7.2 (MCS0)	-2.78	-3.05	0.09	4.0	-3.91	Pass
	5190	38	n (40MHz)	13.5/15 (MCS0)	-4.27	-5.55	-1.85	4.0	-5.85	Pass
	5230	46	n (40MHz)	13.5/15 (MCS0)	-5.37	-5.49	-2.42	4.0	-6.42	Pass
	5210	42	ac (80MHz)	29.3/32.5 (MCS0)	-11.65	-10.96	-8.28	4.0	-12.28	Pass
Band 2A	5260	52	n (20MHz)	6.5/7.2 (MCS0)	-2.90	-2.73	0.20	11.0	-10.80	Pass
	5280	56	n (20MHz)	6.5/7.2 (MCS0)	-3.26	-2.98	-0.11	11.0	-11.11	Pass
	5320	64	n (20MHz)	6.5/7.2 (MCS0)	-2.83	-3.02	0.08	11.0	-10.92	Pass
	5270	54	n (40MHz)	13.5/15 (MCS0)	-5.18	-5.35	-2.25	11.0	-13.25	Pass
	5310	62	n (40MHz)	13.5/15 (MCS0)	-5.20	-5.60	-2.39	11.0	-13.39	Pass
	5290	58	ac (80MHz)	29.3/32.5 (MCS0)	-12.00	-11.32	-8.64	11.0	-19.64	Pass
Band 2C	5500	100	n (20MHz)	6.5/7.2 (MCS0)	-2.80	-2.76	0.23	11.0	-10.77	Pass
	5580	116	n (20MHz)	6.5/7.2 (MCS0)	-2.87	-2.60	0.28	11.0	-10.72	Pass
	5700	140	n (20MHz)	6.5/7.2 (MCS0)	-2.55	-2.65	0.41	11.0	-10.59	Pass
	5510	102	n (40MHz)	13.5/15 (MCS0)	-4.99	-5.21	-2.09	11.0	-13.09	Pass
	5550	110	n (40MHz)	13.5/15 (MCS0)	-4.85	-5.01	-1.92	11.0	-12.92	Pass
	5670	134	n (40MHz)	13.5/15 (MCS0)	-5.12	-4.93	-2.02	11.0	-13.02	Pass
	5530	106	ac (80MHz)	29.3/32.5 (MCS0)	-11.27	-11.25	-8.25	11.0	-19.25	Pass

Table 6-20. MIMO Conducted Power Spectral Density Measurements

Note:

Per KDB 662911 v02r01 Section E)2), the power spectral density at Antenna 1 and Antenna 2 were first measured separately as shown in the section above. The measured values were then summed in linear power units then converted back to dBm.

Sample MIMO Calculation:

At 2412MHz the average conducted power spectral density was measured to be -2.57 dBm for Antenna-1 and -3.47 dBm for Antenna-2.

$$\text{Antenna 1} + \text{Antenna 2} = \text{MIMO}$$

$$(-2.57 \text{ dBm} + -3.47 \text{ dBm}) = (0.55 \text{ mW} + 0.45 \text{ mW}) = 1.00 \text{ mW} = 0.02 \text{ dBm}$$

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 87 of 182

6.5 Peak Excursion Ratio – 802.11a/n/ac §15.407(a.6)

Test Overview and Limit

The spectrum analyzer was connected to the antenna terminal while the EUT was operating at its maximum duty cycle (>98%), at its maximum power control level, as defined in KDB 789033 v01r03, and at the appropriate frequencies. Method SA-1, as defined in KDB 789033 v01r03, was used to capture the average trace used to make the peak excursion measurement.

The largest permissible difference between the modulation envelope (measured using a peak hold function) and the maximum power spectral density is 13 dBm/MHz.

Test Procedure Used

KDB 789033 v01r03 – Section G

Test Settings

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Span was set to encompass the entire emission bandwidth of the signal
3. RBW = 1MHz
4. VBW = 3MHz
5. Detector = peak
6. Trace mode = max hold
7. Trace was allowed to stabilize
8. The peak search function of the spectrum analyzer was used to find the peak of the spectrum. This level was compared to the peak power density level found from the previous section to determine the peak excursion.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-4. Test Instrument & Measurement Setup

Test Notes


The peak excursion was investigated for all signal types, modulation types, channel bandwidths, and variations in signal parameters and the worst case data is shown below. Only the worst case modulation mode on a single channel among all bands is reported since that is sufficient to demonstrate compliance to the peak excursion requirement per KDB 789033 v01r03.

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 88 of 182

Antenna-1 Peak Excursion Ratio – 802.11a/n/ac


Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Peak Excursion Ratio [dBm]	Max Permissible Peak Excursion Ratio [dBm/MHz]	Margin [dB]	Pass / Fail
5180	36	a	6	7.81	13.0	-5.19	Pass
5180	36	n (20MHz)	6.5/7.2 (MCS0)	7.99	13.0	-5.01	Pass
5190	38	n (40MHz)	13.5/15 (MCS0)	7.13	13.0	-5.87	Pass
5210	42	ac (80MHz)	58.5/65 (MCS0)	8.09	13.0	-4.91	Pass

Table 6-21. Conducted Peak Excursion Ratio Measurements




Plot 6-125. Peak Excursion Ratio Plot (802.11a (UNII Band 1) – Ch. 36)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 89 of 182




Plot 6-126. Peak Excursion Ratio Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 36)



Plot 6-127. Peak Excursion Ratio Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 38)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 90 of 182




Plot 6-128. Peak Excursion Ratio Plot (80MHz BW 802.11ac (UNII Band 1) – Ch. 42)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 91 of 182

Antenna-2 Peak Excursion Ratio – 802.11a/n/ac


Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Peak Excursion Ratio [dBm]	Max Permissible Peak Excursion Ratio [dBm/MHz]	Margin [dB]	Pass / Fail
5180	36	a	6	7.89	13.0	-5.11	Pass
5180	36	n (20MHz)	6.5/7.2 (MCS0)	7.89	13.0	-5.11	Pass
5190	38	n (40MHz)	13.5/15 (MCS0)	8.39	13.0	-4.61	Pass
5210	42	ac (80MHz)	29.3/32.5 (MCS0)	8.78	13.0	-4.23	Pass

Table 6-22. Conducted Peak Excursion Ratio Measurements




Plot 6-129. Peak Excursion Ratio Plot (802.11a (UNII Band 1) – Ch. 36)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 92 of 182




Plot 6-130. Peak Excursion Ratio Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 36)



Plot 6-131. Peak Excursion Ratio Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 38)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 93 of 182



Plot 6-132. Peak Excursion Ratio Plot (80MHz BW 802.11ac (UNII Band 1) – Ch. 42)

FCC ID: A3LSMT707A	 FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer	Page 94 of 182

6.6 Frequency Stability

§15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.

OPERATING FREQUENCY: 5,180,000,000 Hz
 CHANNEL: 36
 REFERENCE VOLTAGE: 3.80 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	5,179,999,980	-20	-0.00000039
100 %		- 30	5,180,000,011	11	0.00000021
100 %		- 20	5,179,999,996	-4	-0.00000008
100 %		- 10	5,179,999,988	-12	-0.00000023
100 %		0	5,179,999,995	-5	-0.00000010
100 %		+ 10	5,180,000,019	19	0.00000037
100 %		+ 20	5,179,999,999	-1	-0.00000002
100 %		+ 30	5,180,000,020	20	0.00000039
100 %		+ 40	5,179,999,997	-3	-0.00000006
100 %		+ 50	5,180,000,021	21	0.00000041
BATT. ENDPOINT	3.40	+ 20	5,179,999,987	-13	-0.00000025

Table 6-23. Frequency Stability Measurements for UNII Band 1 (Ch. 36)

Note:

Based on the results of the frequency stability test shown above the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 95 of 182

Frequency Stability

§15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.

OPERATING FREQUENCY: 5,260,000,000 Hz
 CHANNEL: 52
 REFERENCE VOLTAGE: 3.80 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	5,259,999,991	-9	-0.00000017
100 %		- 30	5,260,000,014	14	0.00000027
100 %		- 20	5,259,999,988	-12	-0.00000023
100 %		- 10	5,260,000,002	2	0.00000004
100 %		0	5,259,999,993	-7	-0.00000013
100 %		+ 10	5,260,000,018	18	0.00000034
100 %		+ 20	5,260,000,016	16	0.00000030
100 %		+ 30	5,260,000,012	12	0.00000023
100 %		+ 40	5,259,999,976	-24	-0.00000046
100 %		+ 50	5,260,000,027	27	0.00000051
BATT. ENDPOINT	3.40	+ 20	5,259,999,986	-14	-0.00000027

Table 6-24. Frequency Stability Measurements for UNII Band 2A (Ch. 52)

Note:

Based on the results of the frequency stability test shown above the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 96 of 182

Frequency Stability

§15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.

OPERATING FREQUENCY: 5,500,000,000 Hz
 CHANNEL: 100
 REFERENCE VOLTAGE: 3.80 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	5,499,999,999	-1	-0.00000002
100 %		- 30	5,499,999,984	-16	-0.00000029
100 %		- 20	5,499,999,998	-2	-0.00000004
100 %		- 10	5,500,000,010	10	0.00000018
100 %		0	5,500,000,004	4	0.00000007
100 %		+ 10	5,499,999,998	-2	-0.00000004
100 %		+ 20	5,499,999,994	-6	-0.00000011
100 %		+ 30	5,500,000,003	3	0.00000005
100 %		+ 40	5,500,000,018	18	0.00000033
100 %		+ 50	5,499,999,984	-16	-0.00000029
BATT. ENDPOINT	3.40	+ 20	5,499,999,982	-18	-0.00000033

Table 6-25. Frequency Stability Measurements for UNII Band 2C (Ch. 100)

Note:

Based on the results of the frequency stability test shown above the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 97 of 182

6.7 Radiated Spurious Emission Measurements

§15.407(b.1)(b.6) §15.205 §15.209

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle (>98%), at its maximum power control level, as defined in KDB 789033 v01r04, and at the appropriate frequencies. All channels, modes (e.g. 802.11a, 802.11n (20MHz BW) and 802.11n (40MHz BW)), and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 6-26 per Section 15.209.

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 6-26. Radiated Limits

Test Procedures Used

KDB 789033 v01r04 – Section H

Test Settings

Average Measurements above 1GHz (Method AD)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
6. Averaging type = power (RMS)
7. Sweep time = auto couple
8. Trace was averaged over 100 sweeps

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 98 of 182

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = 120kHz
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-5. Test Instrument & Measurement Setup

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 99 of 182

Test Notes

1. All radiated spurious emissions levels were measured in a radiated test setup per the guidance of KDB 789033 v01r04 Section H.
2. All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 are below the limit shown in Table 6-26.
3. All spurious emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 6-11. All spurious emissions that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBμV/m can be determined by adding a “conversion” factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dBμV/m.
4. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
5. This unit was tested with its standard battery.
6. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
7. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.

Sample Calculations

Determining Spurious Emissions Levels

- o Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level}_{[dBm]} + 107 + \text{AFCL}_{[dB/m]}$
- o $\text{AFCL}_{[dB/m]} = \text{Antenna Factor}_{[dB/m]} + \text{Cable Loss}_{[dB]}$
- o $\text{Margin}_{[dB]} = \text{Field Strength Level}_{[dB\mu V/m]} - \text{Limit}_{[dB\mu V/m]}$

Radiated Band Edge Measurement Offset

- o The amplitude offset shown in the radiated restricted band edge plots in Section 6.8 was calculated using the formula:
Offset (dB) = (Antenna Factor + Cable Loss + 10 dB Attenuator) – Preamplifier Gain

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 100 of 182

Antenna-1 Radiated Spurious Emission Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10360.00	-97.08	Peak	H	H	46.86	0.00	56.78	68.20	-11.42
* 15540.00	-117.70	Average	H	H	50.97	0.00	40.27	53.98	-13.71
* 15540.00	-105.10	Peak	H	H	50.97	0.00	52.87	73.98	-21.11
* 20720.00	-99.64	Average	V	V	44.00	-9.54	41.82	53.98	-12.16
* 20720.00	-96.31	Peak	V	V	44.00	-9.54	45.15	73.98	-28.83
25900.00	-103.25	Peak	V	V	44.87	-9.54	39.08	68.20	-29.12

Table 6-27. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5200MHz
 Channel: 40

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10400.00	-97.65	Peak	H	H	46.81	0.00	56.17	68.20	-12.03
* 15600.00	-117.84	Average	H	H	51.01	0.00	40.18	53.98	-13.80
* 15600.00	-104.85	Peak	H	H	51.01	0.00	53.17	73.98	-20.81
* 20800.00	-97.63	Average	V	V	43.99	-9.54	43.81	53.98	-10.17
* 20800.00	-94.41	Peak	V	V	43.99	-9.54	47.03	73.98	-26.95
26000.00	-103.31	Peak	V	V	44.97	-9.54	39.12	68.20	-29.08

Table 6-28. Radiated Measurements

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 101 of 182

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5240MHz
 Channel: 48

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10480.00	-99.64	Peak	H	H	46.73	0.00	54.09	68.20	-14.11
* 15720.00	-117.62	Average	H	H	49.90	0.00	39.28	53.98	-14.70
* 15720.00	-105.48	Peak	H	H	49.90	0.00	51.42	73.98	-22.56
* 20960.00	-100.28	Average	V	V	43.90	-9.54	41.07	53.98	-12.91
* 20960.00	-97.07	Peak	V	V	43.90	-9.54	44.28	73.98	-29.70
26200.00	-102.66	Peak	V	V	44.76	-9.54	39.55	68.20	-28.65

Table 6-29. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5260MHz
 Channel: 52

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10520.00	-100.81	Peak	H	H	46.70	0.00	52.89	68.20	-15.31
* 15780.00	-118.26	Average	H	H	49.90	0.00	38.65	53.98	-15.33
* 15780.00	-105.36	Peak	H	H	49.90	0.00	51.55	73.98	-22.43
* 21040.00	-101.98	Average	V	V	43.84	-9.54	39.32	53.98	-14.66
* 21040.00	-99.05	Peak	V	V	43.84	-9.54	42.25	73.98	-31.73
26300.00	-102.93	Peak	V	V	44.78	-9.54	39.31	68.20	-28.89

Table 6-30. Radiated Measurements

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 102 of 182

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5280MHz
 Channel: 56

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10560.00	-98.30	Peak	H	H	46.84	0.00	55.54	68.20	-12.66
* 15840.00	-118.48	Average	H	H	50.07	0.00	38.58	53.98	-15.40
* 15840.00	-105.78	Peak	H	H	50.07	0.00	51.28	73.98	-22.70
* 21120.00	-102.43	Average	V	V	43.74	-9.54	38.77	53.98	-15.21
* 21120.00	-100.06	Peak	V	V	43.74	-9.54	41.14	73.98	-32.84
26400.00	-102.15	Peak	V	V	44.72	-9.54	40.02	68.20	-28.18

Table 6-31. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 10640.00	-112.66	Average	H	H	47.16	0.00	41.50	53.98	-12.48
* 10640.00	-100.66	Peak	H	H	47.16	0.00	53.50	73.98	-20.48
* 15960.00	-119.34	Average	H	H	49.71	0.00	37.37	53.98	-16.61
* 15960.00	-107.34	Peak	H	H	49.71	0.00	49.37	73.98	-24.61
* 21280.00	-104.22	Average	V	V	43.64	-9.54	36.88	53.98	-17.10
* 21280.00	-100.79	Peak	V	V	43.64	-9.54	40.31	73.98	-33.67
26600.00	-124.77	Peak	V	V	47.28	-9.54	19.97	68.20	-48.23

Table 6-32. Radiated Measurements

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 103 of 182

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6 Mbps
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5500MHz
Channel: 100

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11000.00	-114.03	Average	H	H	47.11	0.00	40.08	53.98	-13.90
* 11000.00	-101.36	Peak	H	H	47.11	0.00	52.75	73.98	-21.23
16500.00	-107.23	Peak	H	H	51.60	0.00	51.37	68.20	-16.83
22000.00	-97.98	Peak	V	V	43.92	-9.54	43.39	68.20	-24.81
27500.00	-126.05	Peak	V	V	48.51	-9.54	19.92	68.20	-48.28

Table 6-33. Radiated Measurements

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6 Mbps
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5580MHz
Channel: 116

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11160.00	-114.09	Average	H	H	47.43	0.00	40.35	53.98	-13.63
* 11160.00	-101.38	Peak	H	H	47.43	0.00	53.06	73.98	-20.92
16740.00	-107.51	Peak	H	H	52.71	0.00	52.20	68.20	-16.00
* 22320.00	-102.06	Average	V	V	44.40	-9.54	39.80	53.98	-14.18
* 22320.00	-98.71	Peak	V	V	44.40	-9.54	43.15	73.98	-30.83
27900.00	-126.44	Peak	V	V	48.13	-9.54	19.15	68.20	-49.05

Table 6-34. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5700MHz
 Channel: 140

	Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	11400.00	-112.80	Average	H	H	47.68	0.00	41.89	53.98	-12.09
*	11400.00	-100.64	Peak	H	H	47.68	0.00	54.05	73.98	-19.93
	17100.00	-108.27	Peak	H	H	54.03	0.00	52.76	68.20	-15.44
*	22800.00	-104.35	Average	V	V	44.39	-9.54	37.50	53.98	-16.48
*	22800.00	-100.69	Peak	V	V	44.39	-9.54	41.16	73.98	-32.82
	28500.00	-125.76	Peak	V	V	48.03	-9.54	19.73	68.20	-48.47

Table 6-35. Radiated Measurements

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 105 of 182

Antenna-2 Radiated Spurious Emission Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10360.00	-93.83	Peak	H	H	46.86	0.00	60.03	68.20	-8.17
* 15540.00	-118.12	Average	H	H	50.97	0.00	39.85	53.98	-14.13
* 15540.00	-106.10	Peak	H	H	50.97	0.00	51.87	73.98	-22.11
* 20720.00	-102.87	Average	V	V	44.00	-9.54	38.59	53.98	-15.39
* 20720.00	-99.52	Peak	V	V	44.00	-9.54	41.94	73.98	-32.04
25900.00	-102.83	Peak	V	V	44.87	-9.54	39.50	68.20	-28.70

Table 6-36. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5200MHz
 Channel: 40

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10400.00	-91.85	Peak	H	H	46.81	0.00	61.97	68.20	-6.23
* 15600.00	-117.64	Average	H	H	51.01	0.00	40.38	53.98	-13.60
* 15600.00	-106.48	Peak	H	H	51.01	0.00	51.54	73.98	-22.44
* 20800.00	-101.30	Average	V	V	43.99	-9.54	40.14	53.98	-13.84
* 20800.00	-98.07	Peak	V	V	43.99	-9.54	43.37	73.98	-30.61
26000.00	-103.58	Peak	V	V	44.97	-9.54	38.85	68.20	-29.35

Table 6-37. Radiated Measurements

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 106 of 182

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5240MHz
 Channel: 48

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10480.00	-92.61	Peak	H	H	46.73	0.00	61.12	68.20	-7.08
* 15720.00	-118.32	Average	H	H	49.90	0.00	38.58	53.98	-15.40
* 15720.00	-106.77	Peak	H	H	49.90	0.00	50.13	73.98	-23.85
* 20960.00	-104.10	Average	V	V	43.90	-9.54	37.25	53.98	-16.73
* 20960.00	-100.68	Peak	V	V	43.90	-9.54	40.67	73.98	-33.31
26200.00	-102.39	Peak	V	V	44.76	-9.54	39.82	68.20	-28.38

Table 6-38. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5260MHz
 Channel: 52

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10520.00	-92.22	Peak	H	H	46.70	0.00	61.48	68.20	-6.72
* 15780.00	-119.86	Average	H	H	49.90	0.00	37.05	53.98	-16.93
* 15780.00	-107.61	Peak	H	H	49.90	0.00	49.30	73.98	-24.68
* 21040.00	-103.95	Average	V	V	43.84	-9.54	37.35	53.98	-16.63
* 21040.00	-100.19	Peak	V	V	43.84	-9.54	41.11	73.98	-32.87
26300.00	-103.18	Peak	V	V	44.78	-9.54	39.06	68.20	-29.14

Table 6-39. Radiated Measurements

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 107 of 182

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5280MHz
 Channel: 56

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10560.00	-92.31	Peak	H	H	46.84	0.00	61.53	68.20	-6.67
* 15840.00	-118.73	Average	H	H	50.07	0.00	38.33	53.98	-15.65
* 15840.00	-107.07	Peak	H	H	50.07	0.00	49.99	73.98	-23.99
* 21120.00	-104.62	Average	V	V	43.74	-9.54	36.58	53.98	-17.40
* 21120.00	-101.09	Peak	V	V	43.74	-9.54	40.11	73.98	-33.87
26400.00	-102.85	Peak	V	V	44.72	-9.54	39.32	68.20	-28.88

Table 6-40. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 10640.00	-105.66	Average	H	H	47.16	0.00	48.50	53.98	-5.48
* 10640.00	-92.26	Peak	H	H	47.16	0.00	61.90	73.98	-12.08
* 15960.00	-116.76	Average	H	H	49.71	0.00	39.95	53.98	-14.03
* 15960.00	-107.34	Peak	H	H	49.71	0.00	49.37	73.98	-24.61
* 21280.00	-106.20	Average	V	V	43.64	-9.54	34.90	53.98	-19.08
* 21280.00	-102.84	Peak	V	V	43.64	-9.54	38.26	73.98	-35.72
26600.00	-124.97	Peak	V	V	47.28	-9.54	19.77	68.20	-48.43

Table 6-41. Radiated Measurements

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 108 of 182

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11000.00	-108.53	Average	H	H	47.11	0.00	45.58	53.98	-8.40
* 11000.00	-95.91	Peak	H	H	47.11	0.00	58.20	73.98	-15.78
16500.00	-107.93	Peak	H	H	51.60	0.00	50.67	68.20	-17.53
22000.00	-98.30	Peak	V	V	43.92	-9.54	43.07	68.20	-25.13
27500.00	-126.39	Peak	V	V	48.51	-9.54	19.58	68.20	-48.62

Table 6-42. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5580MHz
 Channel: 116

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11160.00	-110.15	Average	H	H	47.43	0.00	44.29	53.98	-9.69
* 11160.00	-97.75	Peak	H	H	47.43	0.00	56.69	73.98	-17.29
16740.00	-108.71	Peak	H	H	52.71	0.00	51.00	68.20	-17.20
* 22320.00	-102.23	Average	V	V	44.40	-9.54	39.63	53.98	-14.35
* 22320.00	-99.03	Peak	V	V	44.40	-9.54	42.83	73.98	-31.15
27900.00	-126.57	Peak	V	V	48.13	-9.54	19.02	68.20	-49.18

Table 6-43. Radiated Measurements

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 109 of 182

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5700MHz
 Channel: 140

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11400.00	-109.04	Average	H	H	47.68	0.00	45.65	53.98	-8.33
* 11400.00	-96.14	Peak	H	H	47.68	0.00	58.55	73.98	-15.43
17100.00	-108.37	Peak	H	H	54.03	0.00	52.66	68.20	-15.54
* 22800.00	-105.02	Average	V	V	44.39	-9.54	36.83	53.98	-17.15
* 22800.00	-101.93	Peak	V	V	44.39	-9.54	39.92	73.98	-34.06
28500.00	-127.39	Peak	V	V	48.03	-9.54	18.10	68.20	-50.10

Table 6-44. Radiated Measurements

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 110 of 182

MIMO Radiated Spurious Emission Measurements

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10360.00	-105.79	Peak	H	H	46.86	0.00	48.07	68.20	-20.13
* 15540.00	-118.40	Average	H	H	50.97	0.00	39.57	53.98	-14.41
* 15540.00	-106.74	Peak	H	H	50.97	0.00	51.23	73.98	-22.75
* 20720.00	-97.27	Average	V	V	44.00	-9.54	44.19	53.98	-9.79
* 20720.00	-93.76	Peak	V	V	44.00	-9.54	47.70	73.98	-26.28
25900.00	-103.83	Peak	V	V	44.87	-9.54	38.50	68.20	-29.70

Table 6-45. Radiated Measurements

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5200MHz
 Channel: 40

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10400.00	-105.42	Peak	H	H	46.81	0.00	48.40	68.20	-19.80
* 15600.00	-118.35	Average	H	H	51.01	0.00	39.67	53.98	-14.31
* 15600.00	-106.67	Peak	H	H	51.01	0.00	51.35	73.98	-22.63
* 20800.00	-97.11	Average	V	V	43.99	-9.54	44.33	53.98	-9.65
* 20800.00	-93.60	Peak	V	V	43.99	-9.54	47.84	73.98	-26.14
26000.00	-103.70	Peak	V	V	44.97	-9.54	38.73	68.20	-29.47

Table 6-46. Radiated Measurements

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 111 of 182

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS8
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5240MHz
Channel: 48

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10480.00	-105.26	Peak	H	H	46.73	0.00	48.47	68.20	-19.73
* 15720.00	-118.56	Average	H	H	49.90	0.00	38.34	53.98	-15.64
* 15720.00	-106.43	Peak	H	H	49.90	0.00	50.47	73.98	-23.51
* 20960.00	-100.71	Average	V	V	43.90	-9.54	40.64	53.98	-13.34
* 20960.00	-97.20	Peak	V	V	43.90	-9.54	44.15	73.98	-29.83
26200.00	-102.39	Peak	V	V	44.76	-9.54	39.82	68.20	-28.38

Table 6-47. Radiated Measurements

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS8
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5260MHz
Channel: 52

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10520.00	-104.54	Peak	H	H	46.70	0.00	49.16	68.20	-19.04
* 15780.00	-120.06	Average	H	H	49.90	0.00	36.85	53.98	-17.13
* 15780.00	-106.96	Peak	H	H	49.90	0.00	49.95	73.98	-24.03
* 21040.00	-98.97	Average	V	V	43.84	-9.54	42.33	53.98	-11.65
* 21040.00	-96.42	Peak	V	V	43.84	-9.54	44.88	73.98	-29.10
26300.00	-103.05	Peak	V	V	44.78	-9.54	39.19	68.20	-29.01

Table 6-48. Radiated Measurements

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 112 of 182

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5280MHz
 Channel: 56

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10560.00	-106.32	Peak	H	H	46.84	0.00	47.52	68.20	-20.68
* 15840.00	-119.48	Average	H	H	50.07	0.00	37.58	53.98	-16.40
* 15840.00	-109.28	Peak	H	H	50.07	0.00	47.78	73.98	-26.20
* 21120.00	-99.44	Average	V	V	43.74	-9.54	41.76	53.98	-12.22
* 21120.00	-96.13	Peak	V	V	43.74	-9.54	45.07	73.98	-28.91
26400.00	-102.65	Peak	V	V	44.72	-9.54	39.52	68.20	-28.68

Table 6-49. Radiated Measurements

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 10640.00	-116.16	Average	H	H	47.16	0.00	38.00	53.98	-15.98
* 10640.00	-104.94	Peak	H	H	47.16	0.00	49.22	73.98	-24.76
* 15960.00	-120.24	Average	H	H	49.71	0.00	36.47	53.98	-17.51
* 15960.00	-107.94	Peak	H	H	49.71	0.00	48.77	73.98	-25.21
* 21280.00	-101.21	Average	V	V	43.64	-9.54	39.89	53.98	-14.09
* 21280.00	-98.07	Peak	V	V	43.64	-9.54	43.03	73.98	-30.95
26600.00	-124.78	Peak	V	V	47.28	-9.54	19.96	68.20	-48.24

Table 6-50. Radiated Measurements

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 113 of 182

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11000.00	-116.25	Average	H	H	47.11	0.00	37.86	53.98	-16.12
* 11000.00	-105.06	Peak	H	H	47.11	0.00	49.05	73.98	-24.93
16500.00	-108.63	Peak	H	H	51.60	0.00	49.97	68.20	-18.23
22000.00	-96.54	Peak	V	V	43.92	-9.54	44.83	68.20	-23.37
27500.00	-125.95	Peak	V	V	48.51	-9.54	20.02	68.20	-48.18

Table 6-51. Radiated Measurements

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5580MHz
 Channel: 116

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11160.00	-117.04	Average	H	H	47.43	0.00	37.40	53.98	-16.58
* 11160.00	-105.02	Peak	H	H	47.43	0.00	49.42	73.98	-24.56
16740.00	-108.80	Peak	H	H	52.71	0.00	50.91	68.20	-17.29
* 22320.00	-100.47	Average	V	V	44.40	-9.54	41.39	53.98	-12.59
* 22320.00	-97.10	Peak	V	V	44.40	-9.54	44.76	73.98	-29.22
27900.00	-126.24	Peak	V	V	48.13	-9.54	19.35	68.20	-48.85

Table 6-52. Radiated Measurements

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 114 of 182

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS8
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5700MHz
 Channel: 140

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11400.00	-117.68	Average	H	H	47.68	0.00	37.01	53.98	-16.97
* 11400.00	-105.89	Peak	H	H	47.68	0.00	48.80	73.98	-25.18
17100.00	-108.37	Peak	H	H	54.03	0.00	52.66	68.20	-15.54
* 22800.00	-102.35	Average	V	V	44.39	-9.54	39.50	53.98	-14.48
* 22800.00	-98.99	Peak	V	V	44.39	-9.54	42.86	73.98	-31.12
28500.00	-127.08	Peak	V	V	48.03	-9.54	18.41	68.20	-49.79

Table 6-53. Radiated Measurements

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 115 of 182

6.8 Antenna-1 Radiated Band Edge Measurements (20MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5180MHz

Channel: 36




Date: 18.APR.2014 17:08:17

Plot 6-133. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 116 of 182

Radiated Band Edge Measurements (20MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 18.APR.2014 17:08:40

Plot 6-134. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 117 of 182

Radiated Band Edge Measurements (20MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5320MHz

Channel: 64



Date: 18.APR.2014 17:12:08

Plot 6-135. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 118 of 182

Radiated Band Edge Measurements (20MHz BW)


\$15.407(b.1)(b.2) \$15.205 \$15.209



MARKER 1
5.35025641 GHz
Ref 120.2 dBμV * Att 10 dB

* RBW 1 MHz
* VBW 3 MHz
SWT 20 ms

Marker 1 [T1]
59.78 dBμV
5.350256410 GHz



Date: 18.APR.2014 17:12:29


Plot 6-136. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 119 of 182

Radiated Band Edge Measurements (20MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6 Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 5500MHz
Channel: 100



Date: 18.APR.2014 17:14:20

Plot 6-137. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 120 of 182


Radiated Band Edge Measurements (20MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209



MARKER 1
5.469102564 GHz
Ref 120.3 dBμV * Att 10 dB

* RBW 1 MHz
* VBW 3 MHz
SWT 20 ms

Marker 1 [T1]
58.69 dBμV
5.469102564 GHz



Date: 18.APR.2014 17:14:35

Plot 6-138. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 121 of 182

Radiated Band Edge Measurements (20MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5700MHz

Channel: 140



Date: 23.APR.2014 13:12:56

Plot 6-139. Radiated Upper Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 122 of 182

6.9 Antenna-1 Radiated Band Edge Measurements (40MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5190MHz

Channel: 38



Date: 23.APR.2014 11:11:45

Plot 6-140. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 123 of 182


Radiated Band Edge Measurements (40MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209



MARKER 1
5.149615385 GHz
Ref 125.6 dBμV * Att 10 dB

* RBW 1 MHz
* VBW 3 MHz
SWT 20 ms

Marker 1 [T1]
67.77 dBμV
5.149615385 GHz



Date: 21.APR.2014 13:22:27

Plot 6-141. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 124 of 182

Radiated Band Edge Measurements (40MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5310MHz

Channel: 62




Date: 23.APR.2014 12:05:29

Plot 6-142. Radiated Restricted Upper Band Edge Plot (Average - UNII Band 2A)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 125 of 182

Radiated Band Edge Measurements (40MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 21.APR.2014 13:28:42

Plot 6-143. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 126 of 182

Radiated Band Edge Measurements (40MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5510MHz

Channel: 102



Date: 23.APR.2014 12:19:50

Plot 6-144. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 127 of 182


Radiated Band Edge Measurements (40MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209



MARKER 1
5.46974359 GHz
Ref 120.3 dBμV * Att 10 dB

* RBW 1 MHz
* VBW 3 MHz
SWT 20 ms

Marker 1 [T1]
64.20 dBμV
5.469743590 GHz



Date: 23.APR.2014 12:20:14

Plot 6-145. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 128 of 182

Radiated Band Edge Measurements (40MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5670MHz

Channel: 134



Date: 21.APR.2014 13:44:58

Plot 6-146. Radiated Upper Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 129 of 182

6.10 Antenna-1 Radiated Band Edge Measurements (80MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11n (80MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5210MHz

Channel: 42




Date: 21.APR.2014 14:45:19

Plot 6-147. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 130 of 182

Radiated Band Edge Measurements (80MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 21.APR.2014 14:45:54

Plot 6-148. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 131 of 182

Radiated Band Edge Measurements (80MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11ac (80MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5290MHz

Channel: 58




Date: 23.APR.2014 12:40:43

Plot 6-149. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 132 of 182

Radiated Band Edge Measurements (80MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 23.APR.2014 12:41:11

Plot 6-150. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 133 of 182

Radiated Band Edge Measurements (80MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11ac (80MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5530MHz

Channel: 106




Date: 23.APR.2014 12:56:04

Plot 6-151. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 134 of 182

Radiated Band Edge Measurements (80MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 23.APR.2014 12:56:26

Plot 6-152. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 135 of 182

6.11 Antenna-2 Radiated Band Edge Measurements (20MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5180MHz

Channel: 36



Date: 23.APR.2014 13:07:30

Plot 6-153. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 136 of 182

Radiated Band Edge Measurements (20MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209



MARKER 1

5.148461538 GHz

Ref 125.6 dBμV

* Att 10 dB

* RBW 1 MHz

* VBW 3 MHz


SWT 20 ms

Marker 1 [T1]

67.48 dBμV

5.148461538 GHz

1 PK
MAXH



Date: 18.APR.2014 17:21:06

Plot 6-154. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 137 of 182

Radiated Band Edge Measurements (20MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5320MHz

Channel: 64




Date: 9.JUL.2014 02:12:25

Plot 6-155. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 138 of 182

Radiated Band Edge Measurements (20MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 9.JUL.2014 02:13:11

Plot 6-156. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 139 of 182

Radiated Band Edge Measurements (20MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5500MHz

Channel: 100




Date: 9.JUL.2014 02:28:22

Plot 6-157. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 140 of 182

Radiated Band Edge Measurements (20MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 9.JUL.2014 02:29:12

Plot 6-158. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 141 of 182

6.12 Antenna-2 Radiated Band Edge Measurements (40MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5190MHz

Channel: 38



Date: 23.APR.2014 11:25:33

Plot 6-160. Radiated Restricted Lower Band Edge Plot (Average - UNII Band 1)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 143 of 182


Radiated Band Edge Measurements (40MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209



MARKER 1
5.149871795 GHz
Ref 125.6 dBμV * Att 10 dB

* RBW 1 MHz
* VBW 3 MHz
SWT 20 ms

Marker 1 [T1]
67.07 dBμV
5.149871795 GHz



Date: 21.APR.2014 13:56:57

Plot 6-161. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 144 of 182

Radiated Band Edge Measurements (40MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5310MHz

Channel: 62




Date: 9.JUL.2014 02:15:58

Plot 6-162. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 145 of 182

Radiated Band Edge Measurements (40MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 9.JUL.2014 02:15:10

Plot 6-163. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 146 of 182

Radiated Band Edge Measurements (40MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5510MHz

Channel: 102



Date: 23.APR.2014 12:23:57

Plot 6-164. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 147 of 182

Radiated Band Edge Measurements (40MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209



MARKER 1

5.469871795 GHz

Ref 120.3 dBμV

* Att 10 dB

* RBW 1 MHz

* VBW 3 MHz


SWT 20 ms

Marker 1 [T1]

65.85 dBμV

5.469871795 GHz

1 PK
MAXH



Date: 23.APR.2014 12:24:29

Plot 6-165. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 148 of 182

Radiated Band Edge Measurements (40MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5670MHz

Channel: 134



Date: 9.JUL.2014 02:44:16

Plot 6-166. Radiated Upper Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 149 of 182

6.13 Antenna-2 Radiated Band Edge Measurements (80MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11n (80MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5210MHz

Channel: 42




Date: 9.JUL.2014 01:53:01

Plot 6-167. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 150 of 182

Radiated Band Edge Measurements (80MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 9.JUL.2014 01:54:10

Plot 6-168. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 151 of 182

Radiated Band Edge Measurements (80MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11ac (80MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5290MHz

Channel: 58




Date: 9.JUL.2014 02:19:07

Plot 6-169. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 152 of 182

Radiated Band Edge Measurements (80MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 9.JUL.2014 02:19:52

Plot 6-170. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 153 of 182

Radiated Band Edge Measurements (80MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11ac (80MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5530MHz

Channel: 106




Date: 9.JUL.2014 02:34:17

Plot 6-171. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 154 of 182

Radiated Band Edge Measurements (80MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 9.JUL.2014 02:35:34

Plot 6-172. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 155 of 182

6.14 MIMO Radiated Band Edge Measurements (20MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11n (20MHz)

Worst Case Transfer Rate: MCS8

Distance of Measurements: 3 Meters

Operating Frequency: 5180MHz

Channel: 36




Date: 18.APR.2014 17:35:52

Plot 6-173. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 156 of 182

Radiated Band Edge Measurements (20MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 18.APR.2014 17:36:12

Plot 6-174. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 157 of 182

Radiated Band Edge Measurements (20MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209

Worst Case Mode: 802.11n (20MHz)

Worst Case Transfer Rate: MCS8

Distance of Measurements: 3 Meters

Operating Frequency: 5320MHz

Channel: 64



MARKER 1

5.35 GHz

* RBW 1 MHz

* VBW 3 MHz

SWT 20 ms

Marker 1 [T1]


48.91 dBμV

5.350000000 GHz

Ref 120.2 dBμV

* Att 10 dB

SWT 20 ms



Date: 18.APR.2014 17:38:37

Plot 6-175. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 158 of 182

Radiated Band Edge Measurements (20MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209



MARKER 1
5.350641026 GHz

* RBW 1 MHz

Marker 1 [T1]

* VBW 3 MHz


62.30 dBμV

Ref 120.2 dBμV

* Att 10 dB

SWT 20 ms

5.350641026 GHz



Date: 18.APR.2014 17:38:50

Plot 6-176. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 159 of 182

Radiated Band Edge Measurements (20MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11n (20MHz)

Worst Case Transfer Rate: MCS8

Distance of Measurements: 3 Meters

Operating Frequency: 5500MHz

Channel: 100



Date: 18.APR.2014 17:42:22

Plot 6-177. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 160 of 182

Radiated Band Edge Measurements (20MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209



MARKER 1

5.469871795 GHz

Ref 120.3 dBμV

* Att 10 dB

* RBW 1 MHz

* VBW 3 MHz


SWT 20 ms

Marker 1 [T1]

57.17 dBμV

5.469871795 GHz

1 PK
MAXH



Date: 18.APR.2014 17:42:36

Plot 6-178. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 161 of 182

Radiated Band Edge Measurements (20MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11n (20MHz)

Worst Case Transfer Rate: MCS8

Distance of Measurements: 3 Meters

Operating Frequency: 5700MHz

Channel: 140



Date: 18.APR.2014 17:44:12

Plot 6-179. Radiated Upper Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 162 of 182

6.15 MIMO Radiated Band Edge Measurements (40MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS8

Distance of Measurements: 3 Meters

Operating Frequency: 5190MHz

Channel: 38




Date: 23.APR.2014 11:29:39

Plot 6-180. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 163 of 182

Radiated Band Edge Measurements (40MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 21.APR.2014 14:20:25

Plot 6-181. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 164 of 182

Radiated Band Edge Measurements (40MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS8

Distance of Measurements: 3 Meters

Operating Frequency: 5310MHz

Channel: 62



Date: 23.APR.2014 12:13:16

Plot 6-182. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 165 of 182

Radiated Band Edge Measurements (40MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209



MARKER 1

5.351666667 GHz

Ref 120.2 dBμV

* Att 10 dB

* RBW 1 MHz


* VBW 3 MHz

SWT 20 ms

Marker 1 [T1]

65.73 dBμV

5.351666667 GHz




Date: 21.APR.2014 14:26:52

Plot 6-183. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 166 of 182

Radiated Band Edge Measurements (40MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209

Worst Case Mode: 802.11n (40MHz)
Worst Case Transfer Rate: MCS8
Distance of Measurements: 3 Meters
Operating Frequency: 5510MHz
Channel: 102



Date: 23.APR.2014 12:29:18

Plot 6-184. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 167 of 182

Radiated Band Edge Measurements (40MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209



MARKER 1
5.466923077 GHz

* RBW 1 MHz

Marker 1 [T1]

* VBW 3 MHz

67.36 dBμV


Ref 120.3 dBμV

* Att 10 dB

SWT 20 ms

5.466923077 GHz

1 PK
MAXH



Date: 21.APR.2014 14:32:27

Plot 6-185. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 168 of 182

Radiated Band Edge Measurements (40MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS8

Distance of Measurements: 3 Meters

Operating Frequency: 5670MHz

Channel: 134



Date: 21.APR.2014 14:37:49

Plot 6-186. Radiated Upper Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 169 of 182

6.16 MIMO Radiated Band Edge Measurements (80MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11ac (80MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5210MHz

Channel: 42




Date: 23.APR.2014 12:34:07

Plot 6-187. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 170 of 182

Radiated Band Edge Measurements (80MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 21.APR.2014 15:16:36

Plot 6-188. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 171 of 182

Radiated Band Edge Measurements (80MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11ac (80MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5290MHz

Channel: 58



Date: 23.APR.2014 12:49:50

Plot 6-189. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 172 of 182

Radiated Band Edge Measurements (80MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209



MARKER 1

5.352435897 GHz

Ref 120.2 dBμV

* Att 10 dB

* RBW 1 MHz

* VBW 3 MHz


SWT 20 ms

Marker 1 [T1]

62.11 dBμV

5.352435897 GHz

1 PK
MAXH



Date: 23.APR.2014 12:50:13

Plot 6-190. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 173 of 182

Radiated Band Edge Measurements (80MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11ac (80MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5530MHz

Channel: 106



Date: 21.APR.2014 15:21:46

Plot 6-191. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 174 of 182

Radiated Band Edge Measurements (80MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209



MARKER 1

5.459102564 GHz

* RBW 1 MHz

* VBW 3 MHz

SWT 20 ms

Marker 1 [T1]


62.37 dBμV

5.459102564 GHz

Ref 120.3 dBμV

* Att 10 dB

**1 PK
MAXH**




Date: 21.APR.2014 15:22:03

Plot 6-192. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 175 of 182

6.17 Line-Conducted Test Data

\$15.407



Plot 6-193. Line Conducted Plot with 802.11a UNII Band 1 (L1)

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.704	L1	0.1	30.90	56.00	25.10	15.80	46.00	30.20
1.106	L1	0.1	28.50	56.00	27.50	12.90	46.00	33.10
1.237	L1	0.1	26.70	56.00	29.30	11.30	46.00	34.70
1.853	L1	0.1	25.00	56.00	31.00	10.70	46.00	35.30
2.474	L1	0.1	22.30	56.00	33.70	10.50	46.00	35.50
4.022	L1	0.2	24.30	56.00	31.70	11.30	46.00	34.70

Table 6-54. Line Conducted Data with 802.11a UNII Band 1 (L1)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 36. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 176 of 182

Line-Conducted Test Data

\$15.407



Plot 6-194. Line Conducted Plot with 802.11a UNII Band 1 (N)

Frequency	Line	Corr.	QuasiPeak	Limit	Margin	Average	Limit	Margin
MHz		dB	dBμV	dBμV	dB	dBμV	dBμV	dB
0.719	N	0.1	38.50	56.00	17.50	21.40	46.00	24.60
0.953	N	0.1	37.40	56.00	18.60	16.70	46.00	29.30
1.147	N	0.1	35.80	56.00	20.20	16.90	46.00	29.10
1.232	N	0.1	34.70	56.00	21.30	16.30	46.00	29.70
1.313	N	0.1	34.40	56.00	21.60	13.60	46.00	32.40
1.896	N	0.2	32.40	56.00	23.60	14.40	46.00	31.60

Table 6-55. Line Conducted Data with 802.11a UNII Band 1 (N)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 36. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 177 of 182

Line-Conducted Test Data

\$15.407



Plot 6-195. Line Conducted Plot with 802.11a UNII Band 2A (L1)

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.557	L1	0.1	32.60	56.00	23.40	16.60	46.00	29.40
0.717	L1	0.1	31.20	56.00	24.80	16.50	46.00	29.50
0.976	L1	0.1	29.80	56.00	26.20	14.10	46.00	31.90
1.091	L1	0.1	28.60	56.00	27.40	11.90	46.00	34.10
1.264	L1	0.1	26.20	56.00	29.80	11.70	46.00	34.30
1.799	L1	0.1	24.70	56.00	31.30	10.70	46.00	35.30

Table 6-56. Line Conducted Data with 802.11a UNII Band 2A (L1)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 52. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AV Limit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 178 of 182

Line-Conducted Test Data

\$15.407



Plot 6-196. Line Conducted Plot with 802.11a UNII Band 2A (N)

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.548	N	0.1	35.30	56.00	20.70	19.10	46.00	26.90
0.580	N	0.1	31.80	56.00	24.20	15.10	46.00	30.90
0.724	N	0.1	38.70	56.00	17.30	20.70	46.00	25.30
0.960	N	0.1	37.70	56.00	18.30	19.10	46.00	26.90
1.129	N	0.1	35.30	56.00	20.70	17.80	46.00	28.20
1.300	N	0.1	35.80	56.00	20.20	16.80	46.00	29.20

Table 6-57. Line Conducted Data with 802.11a UNII Band 2A (N)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 52. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 179 of 182

Line-Conducted Test Data

\$15.407



Plot 6-197. Line Conducted Plot with 802.11a UNII Band 2C (L1)

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.551	L1	0.1	33.20	56.00	22.80	18.30	46.00	27.70
0.713	L1	0.1	30.60	56.00	25.40	16.30	46.00	29.70
1.293	L1	0.1	26.90	56.00	29.10	11.70	46.00	34.30
1.853	L1	0.1	23.30	56.00	32.70	9.40	46.00	36.60
2.027	L1	0.1	24.70	56.00	31.30	10.70	46.00	35.30
2.173	L1	0.1	21.20	56.00	34.80	7.20	46.00	38.80

Table 6-58. Line Conducted Plot with 802.11a UNII Band 2C (L1)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 100. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 180 of 182

Line-Conducted Test Data

\$15.407



Plot 6-198. Line Conducted Plot with 802.11a UNII Band 2C (N)

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.557	N	0.1	38.20	56.00	17.80	21.40	46.00	24.60
0.726	N	0.1	38.10	56.00	17.90	20.00	46.00	26.00
0.818	N	0.1	36.80	56.00	19.20	16.30	46.00	29.70
1.147	N	0.1	36.90	56.00	19.10	17.80	46.00	28.20
1.291	N	0.1	34.50	56.00	21.50	16.40	46.00	29.60
1.831	N	0.2	32.00	56.00	24.00	14.40	46.00	31.60

Table 6-59. Line Conducted Data with 802.11a UNII Band 2C (N)

Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 100. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LSMT707A	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 181 of 182

7.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Tablet Computer FCC ID: A3LSMT707A** is in compliance with Part 15E of the FCC Rules.

FCC ID: A3LSMT707A		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1407081358.A3L	Test Dates: 4/16 - 5/1/2014; 7/8 - 7/15/2014	EUT Type: Portable Tablet Computer		Page 182 of 182