



FCC 47 CFR PART 15 SUBPART E

CERTIFICATION TEST REPORT

FOR

GSM/WCDMA/LTE Tablet + Bluetooth/BLE and DTS/UNII a/b/g/n/ac and ANT+

MODEL NUMBER : SM-T715

FCC ID: A3LSMT715

REPORT NUMBER: 15K20515-E4

ISSUE DATE: MAY 18, 2015

Prepared for

**SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 443-742, KOREA**

Prepared by

**UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-823, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433**



Revision History

Rev.	Issue Date	Revisions	Revised By
--	05/18/15	Initial issue	CY Choi
A	05/27/15	Update Section 5.2 and 9	CY Choi

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	7
2. TEST METHODOLOGY	8
3. FACILITIES AND ACCREDITATION	8
4. CALIBRATION AND UNCERTAINTY	8
4.1. MEASURING INSTRUMENT CALIBRATION	8
4.2. SAMPLE CALCULATION	8
4.3. MEASUREMENT UNCERTAINTY	9
5. EQUIPMENT UNDER TEST	10
5.1. DESCRIPTION OF EUT	10
5.2. MAXIMUM OUTPUT POWER.....	11
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	12
5.4. List of test reduction and modes covering other modes:	12
5.5. WORST-CASE CONFIGURATION AND MODE	14
5.6. DESCRIPTION OF TEST SETUP.....	15
6. TEST AND MEASUREMENT EQUIPMENT	17
7. SUMMARY TABLE	18
8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS	19
8.1. ON TIME AND DUTY CYCLE RESULTS.....	19
8.2. DUTY CYCLE PLOTS	19
9. MEASUREMENT METHOD.....	22
10. ANTENNA PORT TEST RESULTS	23
10.1. 6 dB BANDWIDTH	23
10.1.1. 802.11a MODE IN THE 5.8 GHz BAND	24
10.1.2. 802.11n HT20 MODE IN THE 5.8 GHz BAND	24
10.1.3. 802.11n HT40 MODE IN THE 5.8 GHz BAND	24
10.1.4. 802.11n HT40 MODE IN THE 5.8 GHz BAND	24
10.1.5. 6 dB BANDWIDTH PLOTS	25
10.2. 26 dB BANDWIDTH	28
10.2.1. 802.11a MODE IN THE 5.2 GHz BAND	28
10.2.2. 802.11n HT20 MODE IN THE 5.2 GHz BAND	28
10.2.3. 802.11n HT40 MODE IN THE 5.2 GHz BAND	28
10.2.4. 802.11ac HT80 MODE IN THE 5.2 GHz BAND	28
10.2.5. 802.11a MODE IN THE 5.3 GHz BAND	29

10.2.6.	802.11n HT20 MODE IN THE 5.3 GHz BAND	29
10.2.7.	802.11n HT40 MODE IN THE 5.3 GHz BAND	29
10.2.8.	802.11ac HT80 MODE IN THE 5.3 GHz BAND	29
10.2.9.	802.11a MODE IN THE 5.5 GHz BAND	30
10.2.10.	802.11n HT20 MODE IN THE 5.5 GHz BAND	30
10.2.11.	802.11n HT40 MODE IN THE 5.5 GHz BAND	30
10.2.12.	802.11ac HT80 MODE IN THE 5.5 GHz BAND	30
10.2.13.	802.11a MODE IN THE 5.8 GHz BAND	31
10.2.14.	802.11n HT20 MODE IN THE 5.8 GHz BAND	31
10.2.15.	802.11n HT40 MODE IN THE 5.8 GHz BAND	31
10.2.16.	802.11ac HT80 MODE IN THE 5.8 GHz BAND	31
10.2.17.	26 dB BANDWIDTH PLOTS	32
10.3.	99% BANDWIDTH	45
10.3.1.	802.11a MODE IN THE 5.2 GHz BAND	45
10.3.2.	802.11n HT20 MODE IN THE 5.2 GHz BAND	45
10.3.3.	802.11n HT40 MODE IN THE 5.2 GHz BAND	45
10.3.4.	802.11ac HT80 MODE IN THE 5.2 GHz BAND	45
10.3.5.	802.11a MODE IN THE 5.3 GHz BAND	46
10.3.6.	802.11n HT20 MODE IN THE 5.3 GHz BAND	46
10.3.7.	802.11n HT40 MODE IN THE 5.3 GHz BAND	46
10.3.8.	802.11ac HT80 MODE IN THE 5.3 GHz BAND	46
10.3.9.	802.11a MODE IN THE 5.5 GHz BAND	47
10.3.10.	802.11n HT20 MODE IN THE 5.5 GHz BAND	47
10.3.11.	802.11n HT40 MODE IN THE 5.5 GHz BAND	47
10.3.12.	802.11ac HT80 MODE IN THE 5.5 GHz BAND	47
10.3.13.	802.11a MODE IN THE 5.8 GHz BAND	48
10.3.14.	802.11n HT20 MODE IN THE 5.8 GHz BAND	48
10.3.15.	802.11n HT40 MODE IN THE 5.8 GHz BAND	48
10.3.16.	802.11ac HT80 MODE IN THE 5.8 GHz BAND	48
10.3.17.	99% BANDWIDTH PLOTS	49
10.4.	AVERAGE POWER	62
10.4.1.	802.11a MODE IN THE 5.2 GHz BAND	62
10.4.2.	802.11n HT20 MODE IN THE 5.2 GHz BAND	62
10.4.3.	802.11n HT40 MODE IN THE 5.2 GHz BAND	62
10.4.4.	802.11ac HT80 MODE IN THE 5.2 GHz BAND	63
10.4.5.	802.11a MODE IN THE 5.3 GHz BAND	63
10.4.6.	802.11n HT20 MODE IN THE 5.3 GHz BAND	63
10.4.7.	802.11n HT40 MODE IN THE 5.3 GHz BAND	63
10.4.8.	802.11ac HT80 MODE IN THE 5.3 GHz BAND	63
10.4.9.	802.11a MODE IN THE 5.5 GHz BAND	64
10.4.10.	802.11n HT20 MODE IN THE 5.5 GHz BAND	64
10.4.11.	802.11n HT40 MODE IN THE 5.5 GHz BAND	64
10.4.12.	802.11ac HT80 MODE IN THE 5.5 GHz BAND	64
10.4.13.	802.11a MODE IN THE 5.8 GHz BAND	65
10.4.14.	802.11n HT20 MODE IN THE 5.8 GHz BAND	65
10.4.15.	802.11n HT40 MODE IN THE 5.8 GHz BAND	65
10.4.16.	802.11ac HT80 MODE IN THE 5.8 GHz BAND	65
10.5.	OUTPUT POWER AND PPSD	66
10.5.1.	802.11a MODE IN THE 5.2 GHz BAND	67

10.5.2.	802.11n HT20 MODE IN THE 5.2 GHz BAND	68
10.5.3.	802.11n HT40 MODE IN THE 5.2 GHz BAND	69
10.5.4.	802.11ac HT80 MODE IN THE 5.2 GHz BAND	70
10.5.5.	802.11a MODE IN THE 5.3 GHz BAND	71
10.5.6.	802.11n HT20 MODE IN THE 5.3 GHz BAND	72
10.5.7.	802.11n HT40 MODE IN THE 5.3 GHz BAND	73
10.5.8.	802.11ac HT80 MODE IN THE 5.3 GHz BAND	74
10.5.9.	802.11a MODE IN THE 5.5 GHz BAND	75
10.5.10.	802.11n HT20 MODE IN THE 5.5 GHz BAND	76
10.5.11.	802.11n HT40 MODE IN THE 5.5 GHz BAND	77
10.5.12.	802.11ac HT80 MODE IN THE 5.5 GHz BAND	78
10.5.13.	802.11a MODE IN THE 5.8 GHz BAND	79
10.5.14.	802.11n HT20 MODE IN THE 5.8 GHz BAND	80
10.5.15.	802.11n HT40 MODE IN THE 5.8 GHz BAND	81
10.5.16.	802.11ac HT80 MODE IN THE 5.8 GHz BAND	82
10.5.17.	OUTPUT POWER AND PPSD PLOTS	83
11.	TRANSMITTER ABOVE 1 GHz.....	96
11.1.	5.2 GHz	97
11.1.1.	TX ABOVE 1 GHz 802.11a MODE IN THE 5.2 GHz BAND	97
11.1.2.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.2 GHz BAND	105
11.1.3.	TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.2 GHz BAND	113
11.1.4.	TX ABOVE 1 GHz 802.11ac HT80 MODE IN THE 5.2 GHz BAND	119
11.2.	5.3 GHz	123
11.2.1.	TX ABOVE 1 GHz 802.11a MODE IN THE 5.3 GHz BAND	123
11.2.2.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.3 GHz BAND	131
11.2.3.	TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.3 GHz BAND	139
11.2.4.	TX ABOVE 1 GHz 802.11ac HT80 MODE IN THE 5.3 GHz BAND	145
11.3.	5.5-5.6 GHz	149
11.3.1.	TX ABOVE 1 GHz 802.11a MODE IN THE 5.5 GHz BAND	149
11.3.2.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.5 GHz BAND	159
11.3.3.	TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.5 GHz BAND	169
11.3.4.	TX ABOVE 1 GHz 802.11ac HT80 MODE IN THE 5.5 GHz BAND	179
11.4.	5.8 GHz	183
11.4.1.	TX ABOVE 1 GHz 802.11a MODE IN THE 5.8 GHz BAND	183
11.4.2.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.8 GHz BAND	193
11.4.3.	TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.8 GHz BAND	203
11.4.4.	TX ABOVE 1 GHz 802.11ac HT80 MODE IN THE 5.8 GHz BAND	211
12.	WORST-CASE BELOW 1 GHz (in the 5.3 GHz Band).....	215
13.	AC POWER LINE CONDUCTED EMISSIONS	217
14.	DYNAMIC FREQUENCY SELECTION.....	220
14.1.	OVERVIEW	220
14.1.1.	LIMITS	220
14.1.1.	TEST AND MEASUREMENT SYSTEM	224
14.1.2.	SETUP OF EUT	227

14.1.3. DESCRIPTION OF EUT	228
14.2. RESULTS FOR 20 MHz BANDWIDTH.....	229
14.2.1. TEST CHANNEL	229
14.2.2. RADAR WAVEFORM AND TRAFFIC.....	229
14.2.3. OVERLAPPING CHANNEL TESTS.....	231
14.2.4. MOVE AND CLOSING TIME	231
14.3. RESULTS FOR 40 MHz BANDWIDTH.....	234
14.3.1. TEST CHANNEL	234
14.3.2. RADAR WAVEFORM AND TRAFFIC.....	234
14.3.3. OVERLAPPING CHANNEL TESTS.....	236
14.3.4. MOVE AND CLOSING TIME	236
14.4. RESULTS FOR 80 MHz BANDWIDTH.....	239
14.4.1. TEST CHANNEL	239
14.4.2. RADAR WAVEFORM AND TRAFFIC.....	239
14.4.3. OVERLAPPING CHANNEL TESTS.....	241
14.4.4. MOVE AND CLOSING TIME	241
15. SETUP PHOTOS.....	244

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
EUT DESCRIPTION: GSM/WCDMA/LTE Tablet+Bluetooth/BLE, DTS/UNII a/b/g/n/ac and ANT+
MODEL NUMBER: SM-T715
SERIAL NUMBER: R32G300YQRF (RADIATED); R32G300Y5RF (CONDUCTED)
DATE TESTED: APRIL 16 - MAY 18, 2015

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart E	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:

Tested By:



Ji Ho Choi
Suwon Lab Manager
UL Korea, Ltd.

CY Choi
Suwon Lab Engineer
UL Korea, Ltd.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, FCC 06-96, FCC KDB 789033 D02 v01, ANSI C63.10-2009.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 443-823, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
☒	Chamber 1
☐	Chamber 2

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned}\text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m}\end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	4.14 dB
Radiated Disturbance, Above 1 GHz	5.97 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE Tablet + Bluetooth/BLE, DTS/UNII a/b/g/n/ac and ANT+.
This test report addresses the NII (UNII) operational mode.

WiFi MIMO Condition

Frequency	Mode	Antenna 1	Antenna 2
2.4 GHz	802.11b	TX / RX	TX / RX
	802.11g	TX / RX	TX / RX
	802.11n	TX / RX	TX / RX
	802.11n MIMO	TX / RX	TX / RX
5 GHz	802.11a	TX / RX	TX / RX
	802.11n	TX / RX	TX / RX
	802.11ac	TX / RX	TX / RX
	802.11n/ac MIMO	TX / RX	TX / RX

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum total conducted average output power as follows:

Frequency Range [MHz]	Mode	Output Power [dBm]		Output Power [mW]	
		Antenna1	Antenna2	Antenna1	Antenna2
5180 - 5240	802.11a	12.39	11.49	17.34	14.09
5180 - 5240	802.11n HT20 SISO	12.07	11.42	16.11	13.87
5180 - 5240	802.11n HT20 MIMO	14.71		29.58	
5190 - 5230	802.11n HT40 SISO	11.29	10.93	13.46	12.39
5190 - 5230	802.11n HT40 MIMO	13.17		20.75	
5210	802.11ac HT80 SISO	10.17	10.20	10.40	10.47
5210	802.11ac HT80 MIMO	13.12		20.51	
5260 - 5320	802.11a	12.35	11.83	17.18	15.24
5260 - 5320	802.11n HT20 SISO	11.24	11.63	13.30	14.55
5260 - 5320	802.11n HT20 MIMO	14.77		29.99	
5270 - 5310	802.11n HT40 SISO	10.80	11.12	12.02	12.94
5270 - 5310	802.11n HT40 MIMO	12.82		19.14	
5290	802.11ac HT80 SISO	9.93	10.20	9.84	10.47
5290	802.11ac HT80 MIMO	12.46		17.62	
5500 - 5720	802.11a	12.41	11.55	17.42	14.29
5500 - 5720	802.11n HT20 SISO	12.05	11.34	16.03	13.61
5500 - 5720	802.11n HT20 MIMO	14.85		30.55	
5510 - 5710	802.11n HT40 SISO	10.79	10.82	11.99	12.08
5510 - 5710	802.11n HT40 MIMO	13.54		22.59	
5530 - 5690	802.11ac HT80 SISO	10.04	10.33	10.09	10.79
5530 - 5690	802.11ac HT80 MIMO	13.05		20.18	
5745 - 5825	802.11a	12.12	11.70	16.29	14.79
5745 - 5825	802.11n HT20 SISO	11.93	11.53	15.60	14.22
5745 - 5825	802.11n HT20 MIMO	14.94		31.19	
5755 - 5795	802.11n HT40 SISO	10.55	10.85	11.35	12.16
5755 - 5795	802.11n HT40 MIMO	13.53		22.54	
5775	802.11ac HT80 SISO	9.59	10.29	9.10	10.69
5775	802.11ac HT80 MIMO	13.33		21.53	

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antenna, with a maximum gain of:

Frequency Range [MHz]		Antenna Gain [dBi]	
		Antenna 1	Antenna 2
UNII 1 5150 – 5250	5150	-0.66	-4.29
	5250	-1.70	-2.69
UNII 2A 5250 – 5350	5250	-1.70	-2.69
	5350	-1.77	-2.49
UNII 2C 5470 – 5725	5470	-1.70	-3.90
	5600	-0.57	-3.26
	5725	-1.60	-1.93
UNII 3 5725 – 5825	5725	-1.60	-1.93
	5785	-1.23	-2.31
	5850	-1.43	-2.38

5.4. List of test reduction and modes covering other modes:

UNII 1

5150 - 5250 MHz Authorized Frequency Band (Antenna port & Radiated Testing)		
Frequency Range [MHz]	Mode	Covered by
5180 - 5240	802.11a legacy 1TX/STBC 2TX	802.11a 2TX CDD
5180 - 5240	802.11HT20 1TX	802.11n HT20 2TX CDD
5180 - 5240	802.11HT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5180 - 5240	802.11ac VHT20 1TX	802.11n HT20 2TX CDD
5180 - 5240	802.11ac VHT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5180 - 5240	802.11ac VHT20 2TX CDD/Tx BF	802.11n HT20 2TX CDD
5190 - 5230	802.11n HT40 1TX	802.11n HT40 2TX CDD
5190 - 5230	802.11n HT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5190 - 5230	802.11ac VHT40 1TX	802.11n HT40 2TX CDD
5190 - 5230	802.11ac VHT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5190 - 5230	802.11ac VHT40 2TX CDD/Tx BF	802.11n HT40 2TX CDD
5210	802.11ac VHT80 1TX	802.11ac VHT80 2TX CDD
5210	802.11ac VHT80 2TX STBC/SDM/Tx BF	802.11ac VHT80 2TX CDD

UNII 2A

5250 - 5350 MHz Authorized Frequency Band (Antenna port & Radiated Testing)		
Frequency Range [MHz]	Mode	Covered by
5260 - 5320	802.11a legacy 1TX/STBC 2TX	802.11a 2TX CDD
5260 - 5320	802.11HT20 1TX	802.11n HT20 2TX CDD
5260 - 5320	802.11HT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5260 - 5320	802.11ac VHT20 1TX	802.11n HT20 2TX CDD
5260 - 5320	802.11ac VHT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5260 - 5320	802.11ac VHT20 2TX CDD/Tx BF	802.11n HT20 2TX CDD
5270 - 5310	802.11n HT40 1TX	802.11n HT40 2TX CDD
5270 - 5310	802.11n HT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5270 - 5310	802.11ac VHT40 1TX	802.11n HT40 2TX CDD
5270 - 5310	802.11ac VHT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5270 - 5310	802.11ac VHT40 2TX CDD/Tx BF	802.11n HT40 2TX CDD
5290	802.11ac VHT80 1TX	802.11ac VHT80 2TX CDD
5290	802.11ac VHT80 2TX STBC/SDM/Tx BF	802.11ac VHT80 2TX CDD

UNII 2C

5470 - 5725 MHz Authorized Frequency Band (Antenna port & Radiated Testing)		
Frequency Range [MHz]	Mode	Covered by
5500 - 5720	802.11a legacy 1TX/STBC 2TX	802.11a 2TX CDD
5500 - 5720	802.11HT20 1TX	802.11n HT20 2TX CDD
5500 - 5720	802.11HT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5500 - 5720	802.11ac VHT20 1TX	802.11n HT20 2TX CDD
5500 - 5720	802.11ac VHT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5500 - 5720	802.11ac VHT20 2TX CDD/Tx BF	802.11n HT20 2TX CDD
5510 - 5710	802.11n HT40 1TX	802.11n HT40 2TX CDD
5510 - 5710	802.11n HT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5510 - 5710	802.11ac VHT40 1TX	802.11n HT40 2TX CDD
5510 - 5710	802.11ac VHT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5510 - 5710	802.11ac VHT40 2TX CDD/Tx BF	802.11n HT40 2TX CDD
5530 - 5690	802.11ac VHT80 1TX	802.11ac VHT80 2TX CDD
5530 - 5690	802.11ac VHT80 2TX STBC/SDM/Tx BF	802.11ac VHT80 2TX CDD

UNII 3

5725 - 5850 MHz Authorized Frequency Band (Antenna port & Radiated Testing)		
Frequency Range [MHz]	Mode	Covered by
5745 - 5825	802.11a legacy 1TX/STBC 2TX	802.11a 2TX CDD
5745 - 5825	802.11HT20 1TX	802.11n HT20 2TX CDD
5745 - 5825	802.11HT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5745 - 5825	802.11ac VHT20 1TX	802.11n HT20 2TX CDD
5745 - 5825	802.11ac VHT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5745 - 5825	802.11ac VHT20 2TX CDD/Tx BF	802.11n HT20 2TX CDD
5755 - 5795	802.11n HT40 1TX	802.11n HT40 2TX CDD
5755 - 5795	802.11n HT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5755 - 5795	802.11ac VHT40 1TX	802.11n HT40 2TX CDD
5755 - 5795	802.11ac VHT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5755 - 5795	802.11ac VHT40 2TX CDD/Tx BF	802.11n HT40 2TX CDD
5775	802.11ac VHT80 1TX	802.11ac VHT80 2TX CDD
5775	802.11ac VHT80 2TX STBC/SDM/Tx BF	802.11ac VHT80 2TX CDD

5.5. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X,Y,Z, it was determined that the Z orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in the Z orientation.

Based on the baseline scan, the worst-case data rates were:

802.11a mode: 6 Mbps
802.11n HT20mode: MCS0
802.11n HT40mode: MCS0
802.11ac VHT80mode: MCS0

5.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA12EWE	N/A	N/A
Data Cable	SAMSUNG	ECB-DG925UWE	N/A	N/A
Earphone	SAMSUNG	GH59-11129H	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	0.8m	N/A
2	Audio	1	Mini-Jack	Unshielded	1.0m	N/A

TEST SETUP

The EUT is a stand-alone unit during the tests. Test software exercised the radio card.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	950	11-17-15
Antenna, Horn, 18 GHz	ETS	3115	00167211	09-20-15
Antenna, Horn, 40 GHz	ETS	3116C	00166255	09-23-15
Antenna, Horn, 40 GHz	ETS	3116C-PA	00168841	09-29-15
Preamplifier, 1000 MHz	Sonoma	310N	341282	11-17-15
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1876511	11-18-15
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	09-23-15
Bluetooth Tester	TESCOM	TC-3000C	3000C000546	11-17-15
Average Power Sensor	R&S	NRZ-Z91	102681	11-17-15
Average Power Sensor	Agilent / HP	U2000	MY54270007	09-23-15
EMI Test Receive, 40 GHz	R&S	ESU40	100439	11-17-15
EMI Test Receive, 3 GHz	R&S	ESR3	101832	11-17-15
Attenuator / Switch driver	HP	11713A	3748A04272	N/A
Low Pass Filter 3GHz	Micro-Tronics	LPS17541	009	11-17-15
High Pass Filter 5GHz	Micro-Tronics	HPS17542	009	11-17-15
High Pass Filter 6GHz	Micro-Tronics	HPM17543	010	11-17-15
LISN	R&S	ENV-216	101836	04-09-16
LISN	R&S	ENV-216	101837	04-09-16

7. SUMMARY TABLE

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result	Worst Case
15.407 (a)	Occupied Band width (26dB)	N/A	Conducted	Pass	82.700 MHz
15.407	6dB Band width (5.8Ghz)	500KHz		Pass	16.45 MHz
15.407 (a)(2)	TX Cond. Power 5.15-2.25, 5.25-5.35 & 5.47-5.725	<24dBm or 11+10Log(OBW)		Pass	12.41 dBm
15.407 (a)(3)	TX Cond. Power 5.725-5.825	< 30dBm or 17+10Log(OBW)		Pass	12.12 dBm
15.407 (a)(5)	PSD (5.2,5.3,5.5GHz)	<11dBm		Pass	4.27 dBm
15.407 (a)(5)	PSD (5.8GHz)	30dBm per 500kHz		Pass	4.20 dBm
15.207 (a)	AC Power Line conducted emissions	Section 10	Radiated	Pass	30.9 dBuV (AV)
15.407 (b) & 15.209	Radiated Spurious Emission	< 54dBuV/m		Pass	52.13dBuV/m (AV)
15.407 (h)(2)	Dynamic Frequency Selection	N/A	Radiated / Conducted	Pass	N/A

8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS

LIMITS

None; for reporting purposes only.


PROCEDURE



KDB 789033 Zero-Span Spectrum Analyzer Method.


8.1. ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time B [msec]	Period [msec]	Duty Cycle x [linear]	Duty Cycle [%]	Duty Cycle Correction Factor [dB]	1/T Minimum VBW [kHz]
802.11a	1.427	1.528	0.934	93.4%	0.30	0.701
802.11n HT20	1.335	1.435	0.930	93.0%	0.31	0.749
802.11n HT40	0.663	0.763	0.869	86.9%	0.61	1.508
802.11ac HT80	0.332	0.432	0.769	76.9%	1.14	3.014

8.2. DUTY CYCLE PLOTS







9. MEASUREMENT METHOD

KDB 789033 D02 General UNII Test Procedures New Rules v01
KDB 905462 D03 Clients Without Radar Detection New Rules v01r01

The Duty Cycle is less than 98% and consistent therefore KDB 789033 Method SA-2 is used for power and PPSD

The Duty Cycle is less than 98% and consistent, KDB 789033 Method AD with Power RMS Averaging and duty cycle correction is used.

MIMO Device: KDB 662911 v02r01

10. ANTENNA PORT TEST RESULTS

10.1. 6 dB BANDWIDTH

LIMITS

FCC §15.407

The minimum 6 dB bandwidth shall be at least 500 kHz.

TEST PROCEDURE

Reference to 789033 D02 General UNII Test Procedures New Rules v01: The transmitter output is connected to a spectrum analyzer with the RBW set to 100 kHz, the VBW $\geq 3 \times$ RBW, peak detector and max hold.

RESULTS

10.1.1. 802.11a MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]		Minimum Limit [MHz]
		Chain 0	Chain 1	
Low	5745	16.475	16.450	0.5
Mid	5785	16.475	16.450	0.5
High	5825	16.450	16.450	0.5
Worst		16.450		

10.1.2. 802.11n HT20 MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]		Minimum Limit [MHz]
		Chain 0	Chain 1	
Low	5745	17.650	17.675	0.5
Mid	5785	17.650	17.650	0.5
High	5825	17.700	17.700	0.5
Worst		17.650		


10.1.3. 802.11n HT40 MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]		Minimum Limit [MHz]
		Chain 0	Chain 1	
Low	5765	36.500	36.450	0.5
High	5795	36.400	36.400	0.5
Worst		36.400		


10.1.4. 802.11n HT40 MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]		Minimum Limit [MHz]
		Chain 0	Chain 1	
Middle	5795	5775.000	76.400	76.1
Worst		76.400		


10.1.5. 6 dB BANDWIDTH PLOTS




11n HT20 Mode Low Channel Chain 0




11n HT20 Mode Low Channel Chain 1




11n HT20 Mode Middle Channel Chain 0




11n HT20 Mode Middle Channel Chain 1




11n HT20 Mode High Channel Chain 0




11n HT20 Mode High Channel Chain 1




11n HT40 Mode Low Channel Chain 0




11n HT40 Mode Low Channel Chain 1




11n HT40 Mode High Channel Chain 0




11n HT40 Mode High Channel Chain 1



11ac HT80 Mode Middle Channel Chain 0



11ac HT80 Mode Middle Channel Chain 1



10.2. 26 dB BANDWIDTH

LIMITS

None; for reporting purposes only.

RESULTS

10.2.1. 802.11a MODE IN THE 5.2 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5180	21.560	21.520
Mid	5200	21.640	21.640
High	5240	21.600	21.560
Worst		21.640	

10.2.2. 802.11n HT20 MODE IN THE 5.2 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5180	22.000	21.880
Mid	5200	22.040	21.840
High	5240	22.120	21.880
Worst		22.120	

10.2.3. 802.11n HT40 MODE IN THE 5.2 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5190	40.200	40.020
High	5230	40.260	39.960
Worst		40.260	

10.2.4. 802.11ac HT80 MODE IN THE 5.2 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Middle	5210	82.100	82.000
Worst		82.100	

10.2.5. 802.11a MODE IN THE 5.3 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5260	21.680	21.600
Mid	5300	21.640	21.600
High	5320	21.640	21.600
Worst		21.680	

10.2.6. 802.11n HT20 MODE IN THE 5.3 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5260	21.960	21.920
Mid	5300	22.080	21.960
High	5320	21.920	21.920
Worst		22.080	

10.2.7. 802.11n HT40 MODE IN THE 5.3 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5270	40.320	39.960
High	5310	40.200	39.960
Worst		40.320	

10.2.8. 802.11ac HT80 MODE IN THE 5.3 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Middle	5290	82.700	81.800
Worst		82.700	

10.2.9. 802.11a MODE IN THE 5.5 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5500	21.680	21.640
Mid	5580	21.640	21.640
High	5700	21.640	21.640
Worst		21.680	

10.2.10. 802.11n HT20 MODE IN THE 5.5 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5500	22.040	21.920
Mid	5580	22.040	21.960
High	5700	22.040	22.000
Worst		22.040	

10.2.11. 802.11n HT40 MODE IN THE 5.5 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5510	40.260	40.080
Mid	5550	40.320	40.200
High	5670	40.320	39.960
Worst		40.320	

10.2.12. 802.11ac HT80 MODE IN THE 5.5 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5530	82.200	82.000
High	5690	82.400	81.800
Worst		82.400	

10.2.13. 802.11a MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5745	21.680	21.720
Mid	5785	21.640	21.680
High	5825	21.600	21.680
Worst		21.720	

10.2.14. 802.11n HT20 MODE IN THE 5.8 GHz BAND

Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5745	22.040	21.920
Mid	5785	21.920	22.040
High	5825	22.080	21.920
Worst		22.080	

10.2.15. 802.11n HT40 MODE IN THE 5.8 GHz BAND


Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Low	5755	40.260	39.900
High	5795	40.320	40.020
Worst		40.320	

10.2.16. 802.11ac HT80 MODE IN THE 5.8 GHz BAND


Channel	Frequency [MHz]	26 dB Bandwidth [MHz]	
		Chain 0	Chain 1
Middle	5775	82.200	81.900
Worst		82.200	

10.2.17. 26 dB BANDWIDTH PLOTS


UNII 5.2 GHz




11n HT20 Mode Low Channel Chain 0




11n HT20 Mode Low Channel Chain 1




11n HT20 Mode Middle Channel Chain 0




11n HT20 Mode Middle Channel Chain 1



11n HT20 Mode High Channel Chain 0










11n HT20 Mode High Channel Chain 1






UNII 5.3 GHz









UNII 5.5 GHz




11n HT20 Mode Low Channel Chain 0




11n HT20 Mode Low Channel Chain 1




11n HT20 Mode Middle Channel Chain 0




11n HT20 Mode Middle Channel Chain 1




11n HT20 Mode High Channel Chain 0




11n HT20 Mode High Channel Chain 1







11ac HT80 Mode Low Channel Chain 0



11ac HT80 Mode Low Channel Chain 1



11ac HT80 Mode High Channel Chain 0



11ac HT80 Mode High Channel Chain 1

