



FCC CFR47 PART 15 SUBPART C

CERTIFICATION TEST REPORT

FOR

GSM/WCDMA/LTE Tablet + Bluetooth/BLE and DTS/UNII a/b/g/n/ac and ANT+

MODEL NUMBER : SM-T715

FCC ID: A3LSMT715

REPORT NUMBER: 15K20515-E1

ISSUE DATE: MAY 29, 2015

Prepared for
SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 443-742, KOREA

Prepared by
UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-823, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433



Revision History

Rev.	Issue Date	Revisions	Revised By
--	05/18/15	Initial issue	CY Choi
A	05/29/15	Update section 5.2	CY Choi

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. MEASURING INSTRUMENT CALIBRATION	6
4.2. SAMPLE CALCULATION	6
4.3. MEASUREMENT UNCERTAINTY.....	7
5. EQUIPMENT UNDER TEST	8
5.1. DESCRIPTION OF EUT	8
5.2. MAXIMUM OUTPUT POWER.....	8
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	8
5.4. LIST OF TEST REDUCTION AND MODES.....	9
5.5. WORST-CASE CONFIGURATION AND MODE.....	9
5.6. DESCRIPTION OF TEST SETUP.....	10
6. TEST AND MEASUREMENT EQUIPMENT	12
7. MEASUREMENT METHODS	13
8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS	13
8.1. ON TIME AND DUTY CYCLE RESULTS.....	13
9. SUMMARY TABLE	14
10. ANTENNA PORT TEST RESULTS	15
10.1. 6 dB BANDWIDTH	15
10.1.1. 802.11b MODE IN THE 2.4 GHz BAND	16
10.1.2. 802.11g MODE IN THE 2.4 GHz BAND	16
10.1.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND.....	16
10.1.4. 6 dB BANDWIDTH PLOTS.....	17
10.2. 99% BANDWIDTH	23
10.2.1. 802.11b MODE IN THE 2.4 GHz BAND	23
10.2.2. 802.11g MODE IN THE 2.4 GHz BAND	23
10.2.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND.....	23
10.2.4. 99% BANDWIDTH PLOTS.....	24
10.3. OUTPUT POWER	30
10.3.1. 802.11b MODE IN THE 2.4 GHz BAND	31
10.3.2. 802.11g MODE IN THE 2.4 GHz BAND	32
10.3.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND.....	33

10.4.	PSD.....	34
10.4.1.	802.11b MODE IN THE 2.4 GHz BAND	34
10.4.2.	802.11g MODE IN THE 2.4 GHz BAND	34
10.4.3.	802.11n HT20 MODE IN THE 2.4 GHz BAND.....	34
10.4.4.	PSD PLOTS.....	35
10.5.	OUT-OF-BAND EMISSIONS.....	41
10.5.1.	802.11b MODE IN THE 2.4 GHz BAND	42
10.5.2.	802.11g MODE IN THE 2.4 GHz BAND	44
10.5.3.	802.11n HT20 MODE IN THE 2.4 GHz BAND.....	46
10.5.1.	Bandedge Emission at Channel 13	48
10.5.2.	Spurious Emission at Channel 12.....	49
10.5.3.	Spurious Emission at Channel 13.....	50
11.	RADIATED TEST RESULTS	51
11.1.	LIMITS AND PROCEDURE.....	51
11.2.	TRANSMITTER ABOVE 1 GHz.....	52
11.2.1.	TX ABOVE 1 GHz 802.11b MODE IN THE 2.4 GHz BAND	52
11.2.2.	TX ABOVE 1 GHz 802.11g MODE IN THE 2.4 GHz BAND.....	70
11.2.3.	TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 2.4 GHz BAND	88
11.3.	WORST-CASE BELOW 1 GHz	106
12.	AC POWER LINE CONDUCTED EMISSIONS	108
13.	SETUP PHOTOS	111

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
EUT DESCRIPTION: GSM/WCDMA/LTE Tablet+Bluetooth/BLE, DTS/UNII a/b/g/n/ac and ANT+
MODEL NUMBER: SM-T715
SERIAL NUMBER: R32G300YQRF (RADIATED); R32G300Y5RF (CONDUCTED)
DATE TESTED: APRIL 16 - MAY 18, 2015

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:

Tested By:



Ji Ho Choi
Suwon Lab Manager
UL Korea, Ltd.

CY Choi
Suwon Lab Engineer
UL Korea, Ltd.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 443-823, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
☒	Chamber 1
☐	Chamber 2

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned}\text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m}\end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	4.14 dB
Radiated Disturbance, Above 1 GHz	5.97 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE Tablet + Bluetooth/BLE, DTS/UNII a/b/g/n/ac and ANT+. This test report addresses the DTS (WLAN) operational mode.

WiFi MIMO Condition

Frequency	Mode	Antenna 1	Antenna 2
2.4 GHz	802.11b	TX / RX	TX / RX
	802.11g	TX / RX	TX / RX
	802.11n	TX / RX	TX / RX
	802.11n MIMO	TX / RX	TX / RX
5 GHz	802.11a	TX / RX	TX / RX
	802.11n	TX / RX	TX / RX
	802.11ac	TX / RX	TX / RX
	802.11n/ac MIMO	TX / RX	TX / RX

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum total conducted average output power as follows:

Frequency Range [MHz]	Mode	Frequency [MHz]	Output Power [dBm]		Output Power [mW]	
			Antenna1	Antenna2	Antenna1	Antenna2
2412 - 2472	802.11b	2412 - 2462	16.37	16.01	43.35	39.90
		2467 - 2472	0.48	-0.26	1.12	0.94
	802.11g	2412 - 2462	13.46	13.13	22.18	20.56
		2467 - 2472	1.32	0.58	1.36	1.14
	802.11n SISO	2412 - 2462	13.39	12.86	21.83	19.32
		2467 - 2472	0.77	0.06	1.19	1.01
	802.11n MIMO	2412 - 2462	15.79		37.93	
		2467 - 2472	3.41		2.19	

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antennas, with a antenna1's maximum gain of -4.56 dBi and antenna2's maximum gain of -9.14 dBi .

5.4. LIST OF TEST REDUCTION AND MODES

2400 - 2483.5 MHz Authorized Frequency Band (Antenna Port & Radiated Testing)		
Frequency Range [MHz]	Mode	Covered by
2412 - 2472	802.11b Legacy 1TX	802.11b Legacy 2TX
	802.11g Legacy 1TX	802.11g CDD 2TX
	802.11n 1TX	802.11n HT20 CDD 2TX
	802.11n STBC 2TX	802.11n HT20 CDD 2TX

5.5. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that Z orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Z orientation.

Based on the baseline scan, the worst-case data rates were:

802.11b mode: 1 Mbps
802.11g mode: 6 Mbps
802.11n HT20 mode: MCS0

5.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA12EWE	N/A	N/A
Data Cable	SAMSUNG	ECB-DG925UWE	N/A	N/A
Earphone	SAMSUNG	GH59-11129H	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	0.8m	N/A
2	Audio	1	Mini-Jack	Unshielded	1.0m	N/A

TEST SETUP

The EUT is a stand-alone unit during the tests. Test software exercised the radio card.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	950	11-17-15
Antenna, Horn, 18 GHz	ETS	3115	00167211	09-20-15
Antenna, Horn, 40 GHz	ETS	3116C	00166255	09-23-15
Antenna, Horn, 40 GHz	ETS	3116C-PA	00168841	09-29-15
Preamplifier, 1000 MHz	Sonoma	310N	341282	11-17-15
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1876511	11-18-15
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	09-23-15
Bluetooth Tester	TESCOM	TC-3000C	3000C000546	11-17-15
Average Power Sensor	R&S	NRZ-Z91	102681	11-17-15
Average Power Sensor	Agilent / HP	U2000	MY54270007	09-23-15
EMI Test Receive, 40 GHz	R&S	ESU40	100439	11-17-15
EMI Test Receive, 3 GHz	R&S	ESR3	101832	11-17-15
Attenuator / Switch driver	HP	11713A	3748A04272	N/A
Low Pass Filter 3GHz	Micro-Tronics	LPS17541	009	11-17-15
High Pass Filter 5GHz	Micro-Tronics	HPS17542	009	11-17-15
High Pass Filter 6GHz	Micro-Tronics	HPM17543	010	11-17-15
LISN	R&S	ENV-216	101836	04-09-16
LISN	R&S	ENV-216	101837	04-09-16

7. MEASUREMENT METHODS

KDB 558074 D01 DTS Meas Guidance v03r02: Measurement Procedure AVGPM-G is used for power and PKPSD is used for power spectral density.

Unwanted emissions within Restricted Bands are measured using traditional radiated procedures.

Band edge emissions within Restricted Bands are measured using RMS with duty cycle factor offset method.

8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS

LIMITS

None; for reporting purposes only.


PROCEDURE

KDB 789033 Zero-Span Spectrum Analyzer Method.

8.1. ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time B [msec]	Period [msec]	Duty Cycle x [linear]	Duty Cycle [%]	Duty Cycle Correction Factor [dB]	1/T Minimum VBW [kHz]
2400MHz Bands						
802.11b	8.598	8.705	0.988	98.8%	0.00	0.010
802.11g	1.427	1.530	0.933	93.3%	0.30	0.701
802.11n HT20	1.335	1.436	0.930	93.0%	0.32	0.749

Plot of Duty Cycle



9. SUMMARY TABLE

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result	Worst Case
15.247 (a)(2)	Occupied Band width (6dB)	>500KHz	Conducted	Pass	7.576 MHz
2.1051, 15.247 (d)	Band Edge / Conducted Spurious Emission	-20dBc		Pass	-29.27 dBm
15.247	TX conducted output power	<30dBm		Pass	16.37 dBm
15.247	PSD	<8dBm		Pass	-3.44 dBm
15.207 (a)	AC Power Line conducted emissions	Section 10	Power Line conducted	Pass	40.49 dBuV (QP)
15.205, 15.209	Radiated Spurious Emission	< 54dBuV/m	Radiated	Pass	51.70dBuV/m (AV)

10. ANTENNA PORT TEST RESULTS

10.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)

The minimum 6 dB bandwidth shall be at least 500 kHz.

TEST PROCEDURE

Reference to KDB 558074 D01 DTS Meas Guidance v03r02: The transmitter output is connected to a spectrum analyzer with the RBW set to 100KHz, the VBW $\geq 3 \times$ RBW, peak detector and max hold.

RESULTS

10.1.1. 802.11b MODE IN THE 2.4 GHz BAND

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]		Minimum Limit [MHz]
		Primary Antenna 1	Secondary Antenna 2	
Low	2412	8.057	8.052	0.5
Mid	2437	8.054	7.576	0.5
High	2462	8.040	8.552	0.5
12	2467	8.065	8.564	0.5
13	2472	8.527	8.521	0.5
Worst		7.576		


10.1.2. 802.11g MODE IN THE 2.4 GHz BAND


Channel	Frequency [MHz]	6 dB Bandwidth [MHz]		Minimum Limit [MHz]
		Chain 0	Chain 1	
Low	2412	15.733	16.343	0.5
Mid	2437	16.333	16.058	0.5
High	2462	16.085	15.736	0.5
12	2467	16.303	16.318	0.5
13	2472	15.739	15.686	0.5
Worst		15.686		


10.1.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND


Channel	Frequency [MHz]	6 dB Bandwidth [MHz]		Minimum Limit [MHz]
		Chain 0	Chain 1	
Low	2412	17.306	17.591	0.5
Mid	2437	17.579	16.354	0.5
High	2462	17.293	16.703	0.5
12	2467	17.569	17.563	0.5
13	2472	16.966	16.939	0.5
Worst		16.354		


10.1.4. 6 dB BANDWIDTH PLOTS














10.2. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

RESULTS

10.2.1. 802.11b MODE IN THE 2.4 GHZ BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]	
		Primary Antenna 1	Secondary Antenna 2
Low	2412	10.563	10.488
Mid	2437	10.403	10.352
High	2462	10.521	10.969
12	2467	10.597	11.018
13	2472	10.508	10.429
Worst		11.018	


10.2.2. 802.11g MODE IN THE 2.4 GHZ BAND


Channel	Frequency [MHz]	99% Bandwidth [MHz]	
		Chain 0	Chain 1
Low	2412	16.523	16.551
Mid	2437	16.505	16.457
High	2462	16.522	16.541
12	2467	16.513	16.553
13	2472	16.507	16.446
Worst		16.553	


10.2.3. 802.11n HT20 MODE IN THE 2.4 GHZ BAND

Channel	Frequency [MHz]	99% Bandwidth [MHz]	
		Chain 0	Chain 1
Low	2412	17.706	17.751
Mid	2437	17.722	17.655
High	2462	17.730	17.757
12	2467	17.687	17.740
13	2472	17.718	17.646
Worst		17.757	


10.2.4. 99% BANDWIDTH PLOTS









[Chain 0] 802.11g Mode CH. 12




[Chain 1] 802.11g Mode CH. 12





[Chain 0] 802.11g Mode CH. 13



[Chain 1] 802.11g Mode CH. 13







10.3. OUTPUT POWER

LIMITS

FCC §15.247

For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt, based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST PROCEDURE

The transmitter output is connected to a power meter.

The cable assembly insertion loss of 10.1 dB (including 10 dB pad and 0.1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

DIRECTIONAL ANTENNA GAIN

For Power: The TX chains are uncorrelated and the antenna gain is the same for each chain. The directional gain is equal to the antenna gain.

2.4GHz

Chain 0 Antenna Gain [dBi]	Chain 1 Antenna Gain [dBi]	Uncorrelated Chains Directional Gain [dBi]
-4.56	-9.14	-6.27

For PSD: The TX chains are correlated and the antenna gain is unequal among the chains. The directional gain is:

2.4GHz

Chain 0 Antenna Gain [dBi]	Chain 1 Antenna Gain [dBi]	Correlated Chains Directional Gain [dBi]
-4.56	-9.14	-3.54

RESULTS

10.3.1. 802.11b MODE IN THE 2.4 GHz BAND

Limits

Channel	Frequency [MHz]	Directional Gain Primary [dBi]	Directional Gain Secondary [dBi]	FCC Power Limit [dBm]	IC Power Limit [dBm]	IC EIRP Limit [dBm]	Max Power [dBm]
Low	2412	-4.56	-9.14	30.00	30.00	36.00	30.00
Mid	2437	-4.56	-9.14	30.00	30.00	36.00	30.00
High	2462	-4.56	-9.14	30.00	30.00	36.00	30.00
12	2467	-4.56	-9.14	30.00	30.00	36.00	30.00
13	2472	-4.56	-9.14	30.00	30.00	36.00	30.00

Results

Channel	Frequency [MHz]	Primary Meas Power [dBm]	Secondary Meas Power [dBm]	Maximum Power [dBm]	Power Limit [dBm]	Margin [dB]
Low	2412	15.22	16.07	18.68	36.00	-17.32
Mid	2437	16.21	16.26	19.25	36.00	-16.75
High	2462	15.66	14.80	18.26	36.00	-17.74
12	2467	0.48	-0.46	0.48	36.00	-35.52
13	2472	0.00	-0.26	0.00	36.00	-36.00
Worst				19.25		

- IEEE 802.11b Mode is not supported MIMO operation. So can't transmit on two antenna as same time.

10.3.2. 802.11g MODE IN THE 2.4 GHz BAND

Limits

Channel	Frequency [MHz]	Directional Gain [dBi]	FCC Power Limit [dBm]	IC Power Limit [dBm]	IC EIRP Limit [dBm]	Max Power [dBm]
Low	2412	-6.27	30.00	30.00	36.00	30.00
Mid	2437	-6.27	30.00	30.00	36.00	30.00
High	2462	-6.27	30.00	30.00	36.00	30.00
12	2467	-6.27	30.00	30.00	36.00	30.00
13	2472	-6.27	30.00	30.00	36.00	30.00

Results

Channel	Frequency [MHz]	Chain 0 Meas Power [dBm]	Chain 1 Meas Power [dBm]	Total Corr'd Power [dBm]	Power Limit [dBm]	Margin [dB]
Low	2412	12.23	12.87	15.57	30.00	-14.43
Mid	2437	12.87	13.21	16.05	30.00	-13.95
High	2462	12.50	11.79	15.17	30.00	-14.83
12	2467	1.32	0.40	3.89	30.00	-26.11
13	2472	0.90	0.58	3.75	30.00	-26.25
Worst				16.05		

10.3.3. 802.11n HT20 MODE IN THE 2.4 GHz BAND

Limits

Channel	Frequency [MHz]	Directional Gain [dBi]	FCC Power Limit [dBm]	IC Power Limit [dBm]	IC EIRP Limit [dBm]	Max Power [dBm]
Low	2412	-6.27	30.00	30.00	36.00	30.00
Mid	2437	-6.27	30.00	30.00	36.00	30.00
High	2462	-6.27	30.00	30.00	36.00	30.00
12	2467	-6.27	30.00	30.00	36.00	30.00
13	2472	-6.27	30.00	30.00	36.00	30.00

Results

Channel	Frequency [MHz]	Chain 0 Meas Power [dBm]	Chain 1 Meas Power [dBm]	Total Corr'd Power [dBm]	Power Limit [dBm]	Margin [dB]
Low	2412	12.12	12.63	15.39	30.00	-14.61
Mid	2437	12.62	12.94	15.79	30.00	-14.21
High	2462	12.10	11.56	14.85	30.00	-15.15
12	2467	0.77	0.00	3.41	30.00	-26.59
13	2472	0.65	0.06	3.38	30.00	-26.62
Worst				15.79		

10.4. PSD

LIMITS

FCC §15.247

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST PROCEDURE

Power Spectral Density was performed utilizing the “Method PKPSD (Peak PSD)” under KDB558074 D01 DTS Meas Guidance v03r02

RESULTS

10.4.1. 802.11b MODE IN THE 2.4 GHZ BAND

Channel	Frequency [MHz]	Primary Antenna 1 [dBm]	Secondary Antenna 2 [dBm]	Total PSD [dBm]	Limit [dBm]	Margin [dB]
Low	2412	-4.856	-4.287	-1.55	8.00	-9.55
Mid	2437	-4.335	-3.437	-0.85	8.00	-8.85
High	2462	-3.496	-6.011	-1.56	8.00	-9.56
12	2467	-21.090	-20.807	-20.81	8.00	-28.81
13	2472	-21.629	-19.973	-19.97	8.00	-27.97

- IEEE 802.11b Mode is not supported MIMO operation. So can't transmit on two antenna as same time.

10.4.2. 802.11g MODE IN THE 2.4 GHZ BAND

Channel	Frequency [MHz]	Chain 0 Meas [dBm]	Chain 1 Meas [dBm]	Total PSD [dBm]	Limit [dBm]	Margin [dB]
Low	2412	-13.185	-11.715	-9.38	8.00	-17.38
Mid	2437	-11.798	-11.109	-8.43	8.00	-16.43
High	2462	-11.712	-13.362	-9.45	8.00	-17.45
12	2467	-23.436	-24.222	-20.80	8.00	-28.80
13	2472	-23.659	-24.070	-20.85	8.00	-28.85

10.4.3. 802.11n HT20 MODE IN THE 2.4 GHZ BAND

Channel	Frequency [MHz]	Chain 0 Meas [dBm]	Chain 1 Meas [dBm]	Total PSD [dBm]	Limit [dBm]	Margin [dB]
Low	2412	-12.628	-12.053	-9.32	8.00	-17.32
Mid	2437	-11.579	-11.474	-8.52	8.00	-16.52
High	2462	-12.411	-11.030	-8.66	8.00	-16.66
12	2467	-23.679	-23.497	-20.58	8.00	-28.58
13	2472	-23.755	-23.290	-20.51	8.00	-28.51

10.4.4. PSD PLOTS

