

# FCC ANT<sup>+</sup> REPORT

## Certification

**Applicant Name:**

SAMSUNG Electronics Co., Ltd.

**Address:**

129, Samsung-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

**Date of Issue:**

March 18, 2019

**Location:**

HCT CO., LTD.,

74, Seoicheon-ro 578beon-gil, Majang-myeon,

Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

**Report No.:** HCT-RF-1903-FC030-R3

**FCC ID:**

**A3LSMT725**

**APPLICANT:**

**SAMSUNG Electronics Co., Ltd.**

**Model:**

SM-T725

**Additional Model:**

SM-T725N, SM-T727

**EUT Type:**

Tablet

**Max. RF Output Power:**

93.50 dBuV/m @3 m

**Frequency Range:**

2402 MHz -2480 MHz

**Modulation type**

GFSK

**FCC Classification:**

Low Power communication Device Transmitter(DXX)

**FCC Rule Part(s):**

Part 15 subpart C 15.249

**Engineering Statement:**

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.



**Report prepared by : Jeong Ho Kim**

**Engineer of Telecommunication testing center**



**Approved by : Kwon Jeong**

**Manager of Telecommunication testing center**

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

## Version

| TEST REPORT NO.      | DATE           | DESCRIPTION                                                                              |
|----------------------|----------------|------------------------------------------------------------------------------------------|
| HCT-RF-1903-FC030    | March 15, 2019 | - First Approval Report                                                                  |
| HCT-RF-1903-FC030-R1 | March 17, 2019 | - Added the all period on page 19.<br>- Revised the worst case configuration on page 19. |
| HCT-RF-1903-FC030-R2 | March 18, 2019 | - Added the 20dB bandwidth.                                                              |
| HCT-RF-1903-FC030-R3 | March 18, 2019 | - Revised the 20dB bandwidth.                                                            |

# Table of Contents

|                                                          |    |
|----------------------------------------------------------|----|
| 1. EUT DESCRIPTION .....                                 | 4  |
| 2. TEST METHODOLOGY .....                                | 5  |
| EUT CONFIGURATION .....                                  | 5  |
| EUT EXERCISE .....                                       | 5  |
| GENERAL TEST PROCEDURES .....                            | 5  |
| DESCRIPTION OF TEST MODES .....                          | 5  |
| 3. INSTRUMENT CALIBRATION.....                           | 6  |
| 4. FACILITIES AND ACCREDITATIONS .....                   | 6  |
| FACILITIES .....                                         | 6  |
| EQUIPMENT .....                                          | 6  |
| 5. ANTENNA REQUIREMENTS .....                            | 6  |
| 6. MEASUREMENT UNCERTAINTY .....                         | 7  |
| 7. DESCRIPTION OF TESTS.....                             | 8  |
| 8. SUMMARY TEST OF RESULTS .....                         | 21 |
| 9. TEST RESULT .....                                     | 22 |
| 9.1 DUTY CYCLE.....                                      | 22 |
| 9.2 BANDWIDTH .....                                      | 24 |
| 9.3 RADIATED MEASUREMENT.....                            | 26 |
| 9.3.1 FUNDAMENTAL FIELD STRENGTH LEVEL MEASUREMENT ..... | 26 |
| 9.3.2 RADIATED SPURIOUS EMISSIONS.....                   | 28 |
| 9.3.3 RADIATED BAND EDGES MEASUREMENTS.....              | 31 |
| 9.4 POWERLINE CONDUCTED EMISSIONS .....                  | 33 |
| 10. LIST OF TEST EQUIPMENT .....                         | 37 |
| 11. ANNEX A_ TEST SETUP PHOTO .....                      | 39 |

## 1. EUT DESCRIPTION

|                            |                                                         |
|----------------------------|---------------------------------------------------------|
| Model                      | SM-T725                                                 |
| Additional Model           | SM-T725N, SM-T727                                       |
| EUT Type                   | Tablet                                                  |
| Power Supply               | DC 3.85 V                                               |
| Battery Information        | Model: EB-BT725ABU<br>Type: Li-ion battery              |
| Travel Adapter Information | Model : EP-TA200<br>Manufacture: SOLUM                  |
| Keyboard Information       | Model : EJ-FT720<br>Manufacture: SAMSUNG                |
| Charging Doc Information   | Model : EE-D3200<br>Manufacture: SAMSUNG                |
| Frequency Range            | 2402 MHz - 2480 MHz                                     |
| Max. RF Output Power       | Peak : 93.50 dBuV/m @3 m<br>Average : 61.62 dBuV/m @3 m |
| Modulation Type            | GFSK                                                    |
| Number of Channels         | 79 Channels                                             |
| Antenna Specification      | Antenna type: Metal<br>Peak Gain : -5.50 dBi            |
| Date(s) of Tests           | January 17, 2019 ~ March 14, 2019                       |

## 2. TEST METHODOLOGY

The measurement procedure described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) Operating Under §15.249" were used in the measurement.

### EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.249 under the FCC Rules Part 15 Subpart C.

## GENERAL TEST PROCEDURES

### Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

### Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz. Above 1GHz with 1.5m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3.75 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.6.5 of ANSI C63.10. (Version: 2013). To record the final measurements, the analyzer detector function was set to CISPR quasi-peak mode and the bandwidth of the spectrum analyzer was set to 120 kHz for frequencies below 1 GHz or 1 MHz for frequencies above 1 GHz. For average measurements above 1 GHz, the analyzer was set to peak detector with a reduced VBW setting(RBW = 1 MHz, VBW = 1/T Hz, where T = Pulse width).

## DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

### 3. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

### 4. FACILITIES AND ACCREDITATIONS

#### FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil,

Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.

The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22.

Detailed description of test facility was submitted to the Commission and accepted dated April 02, 2018 (Registration Number: KR0032).

#### EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

### 5. ANTENNA REQUIREMENTS

#### According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

\* The antennas of this E.U.T are permanently attached.

\* The E.U.T Complies with the requirement of §15.203

## 6. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95 % level of confidence.

The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

| Parameter                                | Expanded Uncertainty ( $\pm$ dB) |
|------------------------------------------|----------------------------------|
| Conducted Disturbance (150 kHz ~ 30 MHz) | 1.82                             |
| Radiated Disturbance (9 kHz ~ 30 MHz)    | 3.40                             |
| Radiated Disturbance (30 MHz ~ 1 GHz)    | 4.80                             |
| Radiated Disturbance (1 GHz ~ 18 GHz)    | 5.70                             |
| Radiated Disturbance (18 GHz ~ 40 GHz)   | 5.71                             |

## 7. DESCRIPTION OF TESTS

### 7.1. Duty Cycle

#### Test overview


§15.35(c)

: Unless otherwise specified, e.g. § 15.255(b), when the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds.

As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The exact method of calculating the average field strength shall be submitted with any application for certification or shall be retained in the measurement data file for equipment subject to notification or verification

#### Test Configuration




## 7.2. Occupied Bandwidth

### Test overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured.

### Test Configuration




### Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

- 1) RBW = 1% to 5% of the 99% bandwidth.
- 2) VBW  $\geq 3 \times$  RBW
- 3) Detector = Peak
- 4) Trace mode = max hold
- 5) Sweep = auto couple
- 6) Allow the trace to stabilize

Note :

We tested Occupied Bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer.

**7.3. 20dB Bandwidth****Test Configuration****Test Procedure**

The transmitter output is connected to the Spectrum Analyzer.

- 1) RBW = 1% to 5% of the 20dB bandwidth.
- 2) VBW  $\geq 3 \times$  RBW
- 3) Detector = Peak
- 4) Trace mode = max hold
- 5) Sweep = auto couple
- 6) Allow the trace to stabilize

Note :

We tested 20dB Bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer.

#### 7.4. Fundamental Field Strength Level

##### Limit

| Fundamental frequency | Field strength of fundamental<br>(millivolts/meter) | Field strength of harmonics<br>(microvolts/meter) |
|-----------------------|-----------------------------------------------------|---------------------------------------------------|
| 2400-2483.5 MHz       | 50                                                  | 500                                               |


§15.249(e):

The peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

The maximum permissible average field strength level is 50 mV/m (93.98 dBuV/m).

The maximum permissible peak field strength level is 500 mV/m (113.98 dBuV/m).

##### Test Configuration



**Test Procedure**

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor( reference distance : 3 m).  
\*Distance extrapolation factor =  $20 \cdot \log (\text{test distance} / \text{specific distance})$  (dB)
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. The unit was tested with its standard battery.
8. Spectrum Setting
  - (1) Measurement Type(Peak):
    - Measured Frequency : 2402MHz, 2441MHz, 2480MHz
    - Detector = Peak
    - Trace = Maxhold
    - RBW = 1 MHz
    - VBW  $\geq 3 \cdot \text{RBW}$
  - (2) Measurement Type(Average):
    - Average value of pulsed emissions
    - Unless otherwise specified, when the radiated emission limits are expressed in terms of the average value of the emission and pulsed operation is employed, the average measurement shall determined from the peak field strength after correcting for the worst-case duty cycle as described in section 9.1.
    - DCCF =  $20 \cdot \log_{10}(\text{Pulse width} / \text{Period of the pulse train})$
9. Total(Peak) = Peak Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)  
Total(Average) = Peak Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)  
+ Duty Cycle Correction Factor

## 7.5. Radiated Test

### Limit


| Frequency (MHz) | Field Strength (uV/m) | Measurement Distance (m) |
|-----------------|-----------------------|--------------------------|
| 0.009 – 0.490   | 2400/F(kHz)           | 300                      |
| 0.490 – 1.705   | 24000/F(kHz)          | 30                       |
| 1.705 – 30      | 30                    | 30                       |
| 30-88           | 100                   | 3                        |
| 88-216          | 150                   | 3                        |
| 216-960         | 200                   | 3                        |
| Above 960       | 500                   | 3                        |

§15.249(d):  
Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.


§15.249(e):  
The peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

### Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



#### **Test Procedure of Radiated spurious emissions(Below 30 MHz)**

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The loop antenna was placed at a location 3m from the EUT
3. The EUT is placed on a turntable, which is 0.8m above ground plane.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Distance Correction Factor(0.009 MHz – 0.490 MHz) =  $40 \cdot \log(3 \text{ m}/300 \text{ m}) = -80 \text{ dB}$

Measurement Distance : 3 m

7. Distance Correction Factor(0.490 MHz – 30 MHz) =  $40 \cdot \log(3 \text{ m}/30 \text{ m}) = -40 \text{ dB}$

Measurement Distance : 3 m

#### 8. Spectrum Setting

- Frequency Range = 9 kHz ~ 30 MHz
- Detector = Peak
- Trace = Maxhold
- RBW = 9 kHz
- VBW  $\geq 3 \cdot \text{RBW}$

9. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)

10. The test results for below 30 MHz is correlated to an open site.

The result on OFS is about 2 dB higher than semi-anechoic chamber(10 m chamber)

**Test Procedure of Radiated spurious emissions(Below 1GHz)**

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
5. Spectrum Setting

(1) Measurement Type(Peak):

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Peak
- Trace = Maxhold
- RBW = 100 kHz
- VBW  $\geq 3 \times$  RBW

(2) Measurement Type(Quasi-peak):

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Quasi-Peak
- RBW = 120 kHz

\*In general, (1) is used mainly

6. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L)

**Test Procedure of Radiated spurious emissions (Above 1 GHz)**

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor( reference distance : 3 m).  
\*Distance extrapolation factor =  $20 \cdot \log (\text{test distance} / \text{specific distance})$  (dB)
6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. The unit was tested with its standard battery.
9. Spectrum Setting
  - (1) Measurement Type(Peak):
    - Measured Frequency Range : 1 GHz – 25 GHz
    - Detector = Peak
    - Trace = Maxhold
    - RBW = 1 MHz
    - VBW  $\geq 3 \cdot \text{RBW}$
  - (2) Measurement Type(Average):
    - We performed using a reduced video BW method was done with the analyzer in linear mode
    - Measured Frequency Range : 1 GHz – 25 GHz
    - Detector = Peak
    - Trace = Maxhold
    - RBW = 1 MHz
    - VBW  $\geq 1/\tau$  Hz, where  $\tau$  = pulse width in seconds

The actual setting value of VBW = 10 kHz
10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
11. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)

### **Test Procedure of Radiated Restricted Band Edge**

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor( reference distance : 3 m).  
\*Distance extrapolation factor =  $20 \cdot \log (\text{test distance} / \text{specific distance})$  (dB)
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. The unit was tested with its standard battery.
8. Spectrum Setting
  - (1) Measurement Type(Peak):
    - Measured Frequency Range = 2310 MHz ~ 2400 MHz/ 2483.5 MHz ~ 2500 MHz
    - Detector = Peak
    - Trace = Maxhold
    - RBW = 1 MHz
    - VBW  $\geq 3 \cdot \text{RBW}$
  - (2) Measurement Type(Average):
    - Measured Frequency Range = 2310 MHz ~ 2400 MHz/ 2483.5 MHz ~ 2500 MHz
    - Average value of pulsed emissions
    - Unless otherwise specified, when the radiated emission limits are expressed in terms of the average value of the emission and pulsed operation is employed, the average measurement shall determined from the peak field strength after correcting for the worst-case duty cycle as described in section 9.1.
    - DCCF =  $20 \cdot \log_{10}(\text{Pulse width} / \text{Period of the pulse train})$
9. Total(Peak) = Peak Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)  
Total(Average) = Peak Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)  
+ Duty Cycle Correction Factor

## 7.6. AC Power line Conducted Emissions

### Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN).

| Frequency Range (MHz) | Limits (dB $\mu$ V) |           |
|-----------------------|---------------------|-----------|
|                       | Quasi-peak          | Average   |
| 0.15 to 0.50          | 66 to 56*           | 56 to 46* |
| 0.50 to 5             | 56                  | 46        |
| 5 to 30               | 60                  | 50        |

\*Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

### Test Configuration

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

### Test Procedure

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors : Quasi Peak and Average Detector.

### Sample Calculation

Quasi-peak(Final Result) = Reading Value + Correction Factor

## 7.7. Worst case configuration and mode

### **Fundamental Field Strength Level & Radiated test**

1. All modes of operation were investigated and the worst case configuration results are reported.
  - Mode : Stand alone, Stand alone + External accessories(Keyboard, Charging Doc, Earphone, etc)
  - Worstcase : Stand alone
2. EUT Axis
  - Fundamental Field Strength Level : X
  - Radiated test : X
3. All period were investigated and the worst case period results are reported.
  - All period : Period 128, Period 256, Period 512
  - Worstcase : Period 128
4. SM-T725, SM-T725N, SM-T727 were tested and the worst case results are reported.  
(Worst case : SM-T725)

### **AC Power line Conducted Emissions**

1. All modes of operation were investigated and the worst case configuration results are reported.
  - Mode : Stand alone + External accessories(Keyboard, Charging Doc, Earphone, etc)+Travel Adapter,  
Stand alone + Travel Adapter
  - Worstcase : Stand alone + Travel Adapter
2. SM-T725, SM-T725N, SM-T727 were tested and the worst case results are reported.  
(Worst case : SM-T725)

### **Duty Cycle & Occupied Bandwidth**

1. All period were investigated and the worst case period results are reported.
  - All period : Period 128, Period 256, Period 512
  - Worstcase : Period 128
2. SM-T725, SM-T725N, SM-T727 were tested and the worst case results are reported.  
(Worst case : SM-T725)

## 8. SUMMARY TEST OF RESULTS

| Test Description                                                                 | FCC Part Section(s)                   | Test Limit                                                       | Test Condition | Test Result |
|----------------------------------------------------------------------------------|---------------------------------------|------------------------------------------------------------------|----------------|-------------|
| Occupied Bandwidth                                                               | §2.1049                               | N/A                                                              | Conducted      | PASS        |
| 20dB Bandwidth                                                                   | §15.215                               | N/A                                                              |                | PASS        |
| Duty Cycle                                                                       | §15.35(c)                             | N/A                                                              |                | PASS        |
| AC Power line Conducted Emissions                                                | §15.207                               | cf. Section 7.5                                                  |                | PASS        |
| Fundamental Field Strength Level                                                 | §15.249(a)(e)                         | < 50 mV/m                                                        | Radiated       | PASS        |
| Harmonic Field Strength Level                                                    | §15.249(a)(e)                         | < 500 uV/m                                                       |                | PASS        |
| General Field Strength Limits<br>(Restricted Bands and Radiated Emission Limits) | §15.205,<br>§15.209,<br>§15.249(d)(e) | < 15.209 limits or 50dB<br>below the level of the<br>fundamental |                | PASS        |


## 9. TEST RESULT

### 9.1 DUTY CYCLE


$$\begin{aligned} \text{DCCF} &= 20 \cdot \log_{10}(\text{Pulse width} / \text{Period of the pulse train}) \\ &= 20 \cdot \log_{10}(13 \times 0.1959 \text{ ms} / 100 \text{ ms}) = -31.88 \text{ dB} \end{aligned}$$

#### ■ Test Plots

Pulse Width Plot



### Period of the Pulse Train



## 9.2 BANDWIDTH


| Frequency[MHz] | 99% Bandwidth<br>(kHz) | 20dB Bandwidth<br>(kHz) |
|----------------|------------------------|-------------------------|
| 2402           | 796.78                 | 532.6                   |
| 2441           | 735.39                 | 534.2                   |
| 2480           | 755.73                 | 563.6                   |

### ■ Test Plots

Occupied Bandwidth plot (Low)



### Occupied Bandwidth plot (Mid)



### Occupied Bandwidth plot (High)




### 9.3 RADIATED MEASUREMENT.

#### 9.3.1 FUNDAMENTAL FIELD STRENGTH LEVEL MEASUREMENT

| Frequency<br>[MHz] | Reading<br>[dBuV/m] | A.F.+C.L.<br>+D.F.<br>[dB] | Ant. Pol.<br>[H/V] | D.C.C.F<br>[dB] | Total<br>[dBuV/m] | Limit<br>[dBuV/m] | Margin<br>[dB] | Measurement<br>Type |
|--------------------|---------------------|----------------------------|--------------------|-----------------|-------------------|-------------------|----------------|---------------------|
| 2402               | 88.90               | 0.49                       | V                  | 0.00            | 89.39             | 113.98            | 24.59          | PK                  |
| 2402               | 88.90               | 0.49                       | V                  | -31.88          | 57.51             | 93.98             | 36.47          | AV                  |
| 2402               | 91.10               | 0.49                       | H                  | 0.00            | 91.59             | 113.98            | 22.39          | PK                  |
| 2402               | 91.10               | 0.49                       | H                  | -31.88          | 59.71             | 93.98             | 34.27          | AV                  |
| 2441               | 87.92               | 1.28                       | V                  | 0.00            | 89.20             | 113.98            | 24.78          | PK                  |
| 2441               | 87.92               | 1.28                       | V                  | -31.88          | 57.32             | 93.98             | 36.66          | AV                  |
| 2441               | 91.28               | 1.28                       | H                  | 0.00            | 92.56             | 113.98            | 21.42          | PK                  |
| 2441               | 91.28               | 1.28                       | H                  | -31.88          | 60.68             | 93.98             | 33.30          | AV                  |
| 2480               | 90.70               | 1.15                       | V                  | 0.00            | 91.85             | 113.98            | 22.13          | PK                  |
| 2480               | 90.70               | 1.15                       | V                  | -31.88          | 59.97             | 93.98             | 34.01          | AV                  |
| 2480               | 92.35               | 1.15                       | H                  | 0.00            | 93.50             | 113.98            | 20.48          | PK                  |
| 2480               | 92.35               | 1.15                       | H                  | -31.88          | 61.62             | 93.98             | 32.36          | AV                  |

■ Test Plots (Worst case : H)

Fundamental Field Strength plot (Ch.78)



Date: 13.MAR.2019 20:29:58

**Note:**

Plot of worst case are only reported.

### 9.3.2 RADIATED SPURIOUS EMISSIONS

#### Frequency Range : 9 kHz – 30MHz

| Frequency               | Reading | Ant. factor | Cable loss | Ant. POL | Total  | Limit  | Margin |
|-------------------------|---------|-------------|------------|----------|--------|--------|--------|
| MHz                     | dBuV/m  | dBm/m       | dBm        | (H/V)    | dBuV/m | dBuV/m | dB     |
| No Critical peaks found |         |             |            |          |        |        |        |

#### Note:

1. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
2. Distance extrapolation factor =  $40 \cdot \log(\text{specific distance} / \text{test distance})$  (dB)
3. Limit line = specific Limits (dBuV) + Distance extrapolation factor
4. The test results for below 30 MHz is correlated to an open site.  
The result on OFS is about 2 dB higher than semi-anechoic chamber(10 m chamber)

#### Frequency Range : Below 1 GHz

| Frequency               | Reading | Ant. factor | Cable loss | Ant. POL | Total  | Limit  | Margin |
|-------------------------|---------|-------------|------------|----------|--------|--------|--------|
| MHz                     | dBuV/m  | dBm/m       | dBm        | (H/V)    | dBuV/m | dBuV/m | dB     |
| No Critical peaks found |         |             |            |          |        |        |        |

#### Note:

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.

**Frequency Range : Above 1 GHz**

Operation Frequency: 2402 MHz

| Frequency<br>[MHz] | Reading<br>[dBuV] | A.F + C.L - A.G +<br>D.F<br>[dB] | Pol.<br>[H/V] | Total<br>[dBuV/m] | Limit<br>[dBuV/m] | Margin<br>[dB] | Measurement<br>Type |
|--------------------|-------------------|----------------------------------|---------------|-------------------|-------------------|----------------|---------------------|
| 4804               | 49.71             | 1.83                             | V             | 51.54             | 73.98             | 22.44          | PK                  |
| 4804               | 39.23             | 1.83                             | V             | 41.06             | 53.98             | 12.92          | AV                  |
| 7206               | 49.91             | 9.65                             | V             | 59.56             | 73.98             | 14.42          | PK                  |
| 7206               | 37.26             | 9.65                             | V             | 46.91             | 53.98             | 7.07           | AV                  |
| 4804               | 51.05             | 1.83                             | H             | 52.88             | 73.98             | 21.10          | PK                  |
| 4804               | 39.46             | 1.83                             | H             | 41.29             | 53.98             | 12.69          | AV                  |
| 7206               | 50.15             | 9.65                             | H             | 59.80             | 73.98             | 14.18          | PK                  |
| 7206               | 38.47             | 9.65                             | H             | 48.12             | 53.98             | 5.86           | AV                  |

Operation Frequency: 2441 MHz


| Frequency<br>[MHz] | Reading<br>[dBuV] | A.F + C.L - A.G +<br>D.F<br>[dB] | Pol.<br>[H/V] | Total<br>[dBuV/m] | Limit<br>[dBuV/m] | Margin<br>[dB] | Measurement<br>Type |
|--------------------|-------------------|----------------------------------|---------------|-------------------|-------------------|----------------|---------------------|
| 4882               | 49.18             | 2.31                             | V             | 51.49             | 73.98             | 22.49          | PK                  |
| 4882               | 36.44             | 2.31                             | V             | 38.75             | 53.98             | 15.23          | AV                  |
| 7323               | 49.88             | 9.96                             | V             | 59.84             | 73.98             | 14.14          | PK                  |
| 7323               | 37.85             | 9.96                             | V             | 47.81             | 53.98             | 6.17           | AV                  |
| 4882               | 50.89             | 2.31                             | H             | 53.20             | 73.98             | 20.78          | PK                  |
| 4882               | 38.82             | 2.31                             | H             | 41.13             | 53.98             | 12.85          | AV                  |
| 7323               | 50.79             | 9.96                             | H             | 60.75             | 73.98             | 13.23          | PK                  |
| 7323               | 38.54             | 9.96                             | H             | 48.50             | 53.98             | 5.48           | AV                  |

Operation Frequency: 2480 MHz

| Frequency<br>[MHz] | Reading<br>[dBuV] | A.F + C.L - A.G +<br>D.F<br>[dB] | Pol.<br>[H/V] | Total<br>[dBuV/m] | Limit<br>[dBuV/m] | Margin<br>[dB] | Measurement<br>Type |
|--------------------|-------------------|----------------------------------|---------------|-------------------|-------------------|----------------|---------------------|
| 4960               | 49.44             | 2.26                             | V             | 51.70             | 73.98             | 22.28          | PK                  |
| 4960               | 38.71             | 2.26                             | V             | 40.97             | 53.98             | 13.01          | AV                  |
| 7440               | 49.22             | 9.78                             | V             | 59.00             | 73.98             | 14.98          | PK                  |
| 7440               | 37.95             | 9.78                             | V             | 47.73             | 53.98             | 6.25           | AV                  |
| 4960               | 50.77             | 2.26                             | H             | 53.03             | 73.98             | 20.95          | PK                  |
| 4960               | 39.24             | 2.26                             | H             | 41.50             | 53.98             | 12.48          | AV                  |
| 7440               | 49.97             | 9.78                             | H             | 59.75             | 73.98             | 14.23          | PK                  |
| 7440               | 38.17             | 9.78                             | H             | 47.95             | 53.98             | 6.03           | AV                  |


# Test Plots (Worst case : H)

Radiated Spurious Emissions plot – Average Reading (Ch.39 3rd Harmonic)



Date: 14.MAR.2019 09:15:56

Radiated Spurious Emissions plot – Peak Reading (Ch.39 3rd Harmonic)



Date: 14.MAR.2019 09:15:28

## Note:

Plot of worst case are only reported.

### 9.3.3 RADIATED BAND EDGES MEASUREMENTS

Operating Mode ANT+

Test Frequency 2402 MHz

| Frequency<br>[MHz] | Reading<br>[dBuV] | A.F + C.L + D.F<br>[dB] | Pol.<br>[H/V] | D.C.C.F<br>[dB] | Total<br>[dBuV/m] | Limit<br>[dBuV/m] | Margin<br>[dB] | Measurement<br>Type |
|--------------------|-------------------|-------------------------|---------------|-----------------|-------------------|-------------------|----------------|---------------------|
| 2390.0             | 51.93             | 0.85                    | H             | 0               | 52.78             | 73.98             | 21.20          | PK                  |
| 2390.0             | 51.93             | 0.85                    | H             | -31.88          | 20.90             | 53.98             | 33.08          | AV                  |
| 2390.0             | 51.36             | 0.85                    | V             | 0               | 52.21             | 73.98             | 21.77          | PK                  |
| 2390.0             | 51.36             | 0.85                    | V             | -31.88          | 20.33             | 53.98             | 33.65          | AV                  |


Operating Mode ANT+

Test Frequency 2480 MHz

| Frequency<br>[MHz] | Reading<br>[dBuV] | A.F + C.L + D.F<br>[dB] | Pol.<br>[H/V] | D.C.C.F<br>[dB] | Total<br>[dBuV/m] | Limit<br>[dBuV/m] | Margin<br>[dB] | Measurement<br>Type |
|--------------------|-------------------|-------------------------|---------------|-----------------|-------------------|-------------------|----------------|---------------------|
| 2483.5             | 55.18             | 1.15                    | H             | 0               | 56.33             | 73.98             | 17.65          | PK                  |
| 2483.5             | 55.18             | 1.15                    | H             | -31.88          | 24.45             | 53.98             | 29.53          | AV                  |
| 2483.5             | 53.63             | 1.15                    | V             | 0               | 54.78             | 73.98             | 19.20          | PK                  |
| 2483.5             | 53.63             | 1.15                    | V             | -31.88          | 22.90             | 53.98             | 31.08          | AV                  |

■ Test Plots (Worst case : V)

Radiated Band Edges plot – Peak Reading (Ch.78)



Date: 13.MAR.2019 21:04:35

**Note:**

Plot of worst case are only reported.

## 9.4 POWERLINE CONDUCTED EMISSIONS

### Conducted Emissions (Line 1)

Test


1 / 2

## HCT TEST Report

### Common Information

EUT: SM-T725  
Manufacturer: SAMSUNG  
Test Site: SHIELD ROOM  
Operating Conditions: ANT+ MODE L1

FCC CLASS B\_Exten Cable



### Final Result 1

| Frequency (MHz) | QuasiPeak (dBuV) | Bandwidth (kHz) | Filter | Line | Corr. (dB) | Margin (dB) | Limit (dBuV) |
|-----------------|------------------|-----------------|--------|------|------------|-------------|--------------|
| 0.150000        | 44.7             | 9.000           | Off    | L1   | 9.7        | 21.3        | 66.0         |
| 0.154000        | 44.4             | 9.000           | Off    | L1   | 9.7        | 21.4        | 65.8         |
| 0.548000        | 40.0             | 9.000           | Off    | L1   | 9.8        | 16.0        | 56.0         |
| 0.556000        | 39.9             | 9.000           | Off    | L1   | 9.8        | 16.1        | 56.0         |
| 0.562000        | 38.2             | 9.000           | Off    | L1   | 9.8        | 17.8        | 56.0         |
| 0.684000        | 37.3             | 9.000           | Off    | L1   | 9.8        | 18.7        | 56.0         |
| 1.188000        | 30.7             | 9.000           | Off    | L1   | 9.8        | 25.3        | 56.0         |
| 1.214000        | 30.2             | 9.000           | Off    | L1   | 9.8        | 25.8        | 56.0         |
| 1.226000        | 30.2             | 9.000           | Off    | L1   | 9.8        | 25.8        | 56.0         |
| 1.242000        | 31.3             | 9.000           | Off    | L1   | 9.9        | 24.7        | 56.0         |
| 1.262000        | 30.0             | 9.000           | Off    | L1   | 9.9        | 26.0        | 56.0         |
| 1.338000        | 28.2             | 9.000           | Off    | L1   | 9.9        | 27.8        | 56.0         |
| 9.448000        | 34.0             | 9.000           | Off    | L1   | 10.2       | 26.0        | 60.0         |
| 9.584000        | 34.3             | 9.000           | Off    | L1   | 10.2       | 25.7        | 60.0         |
| 9.752000        | 34.7             | 9.000           | Off    | L1   | 10.2       | 25.3        | 60.0         |
| 9.866000        | 34.8             | 9.000           | Off    | L1   | 10.2       | 25.2        | 60.0         |
| 9.874000        | 34.6             | 9.000           | Off    | L1   | 10.2       | 25.4        | 60.0         |
| 9.988000        | 34.4             | 9.000           | Off    | L1   | 10.2       | 25.6        | 60.0         |

Test

2 / 2

### Final Result 2

| Frequency<br>(MHz) | CAverage<br>(dBuV) | Bandwidth<br>(kHz) | Filter | Line | Corr.<br>(dB) | Margin<br>(dB) | Limit<br>(dBuV) |
|--------------------|--------------------|--------------------|--------|------|---------------|----------------|-----------------|
| 0.154000           | 32.9               | 9.000              | Off    | L1   | 9.7           | 22.9           | 55.8            |
| 0.164000           | 25.5               | 9.000              | Off    | L1   | 9.7           | 29.8           | 55.3            |
| 0.548000           | 26.9               | 9.000              | Off    | L1   | 9.8           | 19.1           | 46.0            |
| 0.552000           | 27.3               | 9.000              | Off    | L1   | 9.8           | 18.7           | 46.0            |
| 0.556000           | 26.7               | 9.000              | Off    | L1   | 9.8           | 19.3           | 46.0            |
| 0.684000           | 26.2               | 9.000              | Off    | L1   | 9.8           | 19.8           | 46.0            |
| 1.148000           | 23.3               | 9.000              | Off    | L1   | 9.8           | 22.7           | 46.0            |
| 1.176000           | 24.3               | 9.000              | Off    | L1   | 9.8           | 21.7           | 46.0            |
| 1.214000           | 23.9               | 9.000              | Off    | L1   | 9.8           | 22.1           | 46.0            |
| 1.246000           | 25.9               | 9.000              | Off    | L1   | 9.9           | 20.1           | 46.0            |
| 1.262000           | 24.0               | 9.000              | Off    | L1   | 9.9           | 22.0           | 46.0            |
| 1.338000           | 21.9               | 9.000              | Off    | L1   | 9.9           | 24.1           | 46.0            |
| 9.448000           | 26.3               | 9.000              | Off    | L1   | 10.2          | 23.7           | 50.0            |
| 9.752000           | 26.8               | 9.000              | Off    | L1   | 10.2          | 23.2           | 50.0            |
| 9.866000           | 26.7               | 9.000              | Off    | L1   | 10.2          | 23.3           | 50.0            |
| 9.874000           | 26.8               | 9.000              | Off    | L1   | 10.2          | 23.2           | 50.0            |
| 9.988000           | 26.7               | 9.000              | Off    | L1   | 10.2          | 23.3           | 50.0            |
| 19.646000          | 16.6               | 9.000              | Off    | L1   | 10.6          | 33.4           | 50.0            |

**Conducted Emissions (Line 2)**

Test


1 / 2

**HCT TEST Report**

**Common Information**

EUT: SM-T725  
Manufacturer: SAMSUNG  
Test Site: SHIELD ROOM  
Operating Conditions: ANT+ MODE N

FCC CLASS B\_Exten Cable



**Final Result 1**

| Frequency (MHz) | QuasiPeak (dBuV) | Bandwidth (kHz) | Filter | Line | Corr. (dB) | Margin (dB) | Limit (dBuV) |
|-----------------|------------------|-----------------|--------|------|------------|-------------|--------------|
| 0.154000        | 45.5             | 9.000           | Off    | N    | 9.8        | 20.3        | 65.8         |
| 0.158000        | 43.3             | 9.000           | Off    | N    | 9.8        | 22.3        | 65.6         |
| 0.166000        | 37.2             | 9.000           | Off    | N    | 9.8        | 27.9        | 65.2         |
| 0.216000        | 34.7             | 9.000           | Off    | N    | 9.9        | 28.2        | 63.0         |
| 0.222000        | 36.9             | 9.000           | Off    | N    | 9.9        | 25.8        | 62.7         |
| 0.226000        | 37.9             | 9.000           | Off    | N    | 9.9        | 24.7        | 62.6         |
| 1.224000        | 33.8             | 9.000           | Off    | N    | 10.0       | 22.2        | 56.0         |
| 1.234000        | 33.3             | 9.000           | Off    | N    | 10.0       | 22.7        | 56.0         |
| 1.240000        | 34.2             | 9.000           | Off    | N    | 10.0       | 21.8        | 56.0         |
| 1.246000        | 33.7             | 9.000           | Off    | N    | 10.0       | 22.3        | 56.0         |
| 1.254000        | 33.2             | 9.000           | Off    | N    | 10.0       | 22.8        | 56.0         |
| 1.554000        | 31.0             | 9.000           | Off    | N    | 10.1       | 25.0        | 56.0         |
| 17.888000       | 29.0             | 9.000           | Off    | N    | 10.8       | 31.0        | 60.0         |
| 18.130000       | 29.6             | 9.000           | Off    | N    | 10.8       | 30.4        | 60.0         |
| 18.300000       | 29.9             | 9.000           | Off    | N    | 10.8       | 30.1        | 60.0         |
| 18.364000       | 30.0             | 9.000           | Off    | N    | 10.8       | 30.0        | 60.0         |
| 18.806000       | 29.9             | 9.000           | Off    | N    | 10.8       | 30.1        | 60.0         |
| 19.150000       | 29.7             | 9.000           | Off    | N    | 10.8       | 30.3        | 60.0         |

Test

2 / 2

### Final Result 2

| Frequency<br>(MHz) | CAverage<br>(dBuV) | Bandwidth<br>(kHz) | Filter | Line | Corr.<br>(dB) | Margin<br>(dB) | Limit<br>(dBuV) |
|--------------------|--------------------|--------------------|--------|------|---------------|----------------|-----------------|
| 0.154000           | 33.7               | 9.000              | Off    | N    | 9.8           | 22.1           | 55.8            |
| 0.158000           | 30.3               | 9.000              | Off    | N    | 9.8           | 25.3           | 55.6            |
| 0.162000           | 26.4               | 9.000              | Off    | N    | 9.8           | 28.9           | 55.4            |
| 0.166000           | 25.6               | 9.000              | Off    | N    | 9.8           | 29.5           | 55.2            |
| 0.222000           | 25.6               | 9.000              | Off    | N    | 9.9           | 27.1           | 52.7            |
| 0.226000           | 26.4               | 9.000              | Off    | N    | 9.9           | 26.2           | 52.6            |
| 1.216000           | 27.1               | 9.000              | Off    | N    | 10.0          | 18.9           | 46.0            |
| 1.220000           | 26.9               | 9.000              | Off    | N    | 10.0          | 19.1           | 46.0            |
| 1.246000           | 27.1               | 9.000              | Off    | N    | 10.0          | 18.9           | 46.0            |
| 1.254000           | 27.2               | 9.000              | Off    | N    | 10.0          | 18.8           | 46.0            |
| 1.504000           | 25.2               | 9.000              | Off    | N    | 10.1          | 20.8           | 46.0            |
| 1.518000           | 25.3               | 9.000              | Off    | N    | 10.1          | 20.7           | 46.0            |
| 17.806000          | 20.1               | 9.000              | Off    | N    | 10.8          | 29.9           | 50.0            |
| 18.192000          | 16.4               | 9.000              | Off    | N    | 10.8          | 33.6           | 50.0            |
| 18.262000          | 16.3               | 9.000              | Off    | N    | 10.8          | 33.7           | 50.0            |
| 18.300000          | 16.5               | 9.000              | Off    | N    | 10.8          | 33.5           | 50.0            |
| 18.364000          | 16.4               | 9.000              | Off    | N    | 10.8          | 33.6           | 50.0            |
| 19.542000          | 14.9               | 9.000              | Off    | N    | 10.9          | 35.1           | 50.0            |

## 10.LIST OF TEST EQUIPMENT

### Conducted Test

| Manufacturer    | Model / Equipment                            | Calibration Date | Calibration Interval | Serial No. |
|-----------------|----------------------------------------------|------------------|----------------------|------------|
| Rohde & Schwarz | ENV216 / LISN                                | 12/12/2018       | Annual               | 102245     |
| Rohde & Schwarz | ESCI / Test Receiver                         | 06/27/2018       | Annual               | 100033     |
| ESPA            | SU-642 / Temperature Chamber                 | 03/30/2018       | Annual               | 0093008124 |
| Agilent         | N9020A / Signal Analyzer                     | 06/08/2018       | Annual               | MY51110085 |
| Agilent         | N9030A / Signal Analyzer                     | 11/20/2018       | Annual               | MY49431210 |
| Agilent         | N1911A / Power Meter                         | 04/16/2018       | Annual               | MY45100523 |
| Agilent         | N1921A / Power Sensor                        | 04/16/2018       | Annual               | MY52260025 |
| Agilent         | 87300B / Directional Coupler                 | 11/20/2018       | Annual               | 3116A03621 |
| Hewlett Packard | 11667B / Power Splitter                      | 06/07/2018       | Annual               | 05001      |
| Hewlett Packard | E3632A / DC Power Supply                     | 06/26/2018       | Annual               | KR75303960 |
| Agilent         | 8493C / Attenuator(10 dB)                    | 07/10/2018       | Annual               | 07560      |
| Rohde & Schwarz | EMC32 / Software                             | N/A              | N/A                  | N/A        |
| HCT CO., LTD.   | FCC WLAN&BT&BLE Conducted Test Software v3.0 | N/A              | N/A                  | N/A        |
| Rohde & Schwarz | CBT / Bluetooth Tester                       | 05/17/2018       | Annual               | 100422     |

### Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

### **Radiated Test**

| Manufacturer           | Model / Equipment                                          | Calibration Date | Calibration Interval | Serial No.  |
|------------------------|------------------------------------------------------------|------------------|----------------------|-------------|
| Innco system           | CO3000 / Controller(Antenna mast)                          | N/A              | N/A                  | CO3000-4p   |
| Innco system           | MA4640/800-XP-EP / Antenna Position Tower                  | N/A              | N/A                  | N/A         |
| Audix                  | EM1000 / Controller                                        | N/A              | N/A                  | 060520      |
| Audix                  | Turn Table                                                 | N/A              | N/A                  | N/A         |
| Rohde & Schwarz        | Loop Antenna                                               | 08/23/2018       | Biennial             | 1513-175    |
| Schwarzbeck            | VULB 9168 / Hybrid Antenna                                 | 04/06/2017       | Biennial             | 760         |
| Schwarzbeck            | VULB 9168 / Hybrid Antenna                                 | 08/09/2018       | Annual               | 3368        |
| Schwarzbeck            | BBHA 9120D / Horn Antenna                                  | 06/30/2017       | Biennial             | 1300        |
| Schwarzbeck            | BBHA9170 /<br>Horn Antenna(15 GHz ~ 40 GHz)                | 12/04/2017       | Biennial             | BBHA9170541 |
| Rohde & Schwarz        | FSP(9 kHz ~ 40 GHz) / Spectrum Analyzer                    | 07/24/2018       | Annual               | 100843      |
| Wainwright Instruments | WHK3.0/18G-10EF / High Pass Filter                         | 01/03/2019       | Annual               | F6          |
| Wainwright Instruments | WHFX7.0/18G-8SS / High Pass Filter                         | 05/09/2018       | Annual               | 29          |
| Wainwright Instruments | WRCJV2400/2483.5-2370/2520-60/12SS /<br>Band Reject Filter | 06/29/2018       | Annual               | 2           |
| Wainwright Instruments | WRCJV5100/5850-40/50-8EEK /<br>Band Reject Filter          | 01/03/2019       | Annual               | 2           |
| Weinschel              | 2-3 / Attenuator (3 dB)                                    | 10/10/2018       | Annual               | BR0617      |
| H+S                    | 5910-N-50-010 / Attenuator(10 dB)                          | 11/08/2018       | Annual               | NONE        |
| CERNEX                 | CBLU1183540B-01 / Power Amplifier                          | 12/21/2018       | Annual               | 25540       |
| CERNEX                 | CBL06185030 / Power Amplifier                              | 03/28/2018       | Annual               | 28550       |
| CERNEX                 | CBL18265035 / Power Amplifier                              | 01/03/2019       | Annual               | 22966       |
| CERNEX                 | CBL26405040 / Power Amplifier                              | 06/29/2018       | Annual               | 25956       |
| TESCOM                 | TC-3000C / Bluetooth Tester                                | 03/27/2018       | Annual               | 3000C000276 |

### **Note:**

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

## 11. ANNEX A\_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

| No. | Description         |
|-----|---------------------|
| 1   | HCT-RF-1903-FC027-P |
| 2   | HCT-RF-1903-FC028-P |
| 3   | HCT-RF-1903-FC029-P |
| 4   | HCT-RF-1903-FC030-P |
| 5   | HCT-RF-1903-FC031-P |
| 6   | HCT-RF-1903-FC032-P |