On your side

HCT

TEST REPORT

FCC LTE Test for SM-T725

Certification

APPLICANT
SAMSUNG Electronics Co., Ltd.

REPORT NO.
HCT-RF-1906-FC018-R1

DATE OF ISSUE
17 June 2019

HCT Co., Ltd.
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 F ax. +82 31 645 6401

HCT Co., Ltd.
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401

TEST REPORT

FCC LTE Test for SM-T725

REPORT NO.
HCT-RF-1906-FC018-R1

DATE OF ISSUE
17 June 2019

Other ID
FCC: A3LSMT725U

Applicant	**SAMSUNG Electronics Co., Ltd.** 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
Eut Type	Tablet
Model Name	SM-T725
Additional Model(s)	SM-T725N, SM-T727
Date of Receipt	May 10, 2019
FCC Rule Part(s)	§ 24, § 2
FCC Classification	PCS Licensed Transmitter (PCB)
Manufacturer	SAMSUNG Electronics Co., Ltd.

Tested by
Kwon Jeong

Technical Manager
Jong Seok Lee

HCT CO., LTD.
Soo Chan Lee
SooChan Lee / CEO

EVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	June 10, 2019	Initial Release
1	June 17, 2019	Revised the date of test Revised the date of test equipment

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section § 2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)

CONTENTS

1. GENERAL INFORMATION 5
1.1. MAXIMUM OUTPUT POWER 6
2. INTRODUCTION 7
2.1. DESCRIPTION OF EUT 7
2.2. MEASURING INSTRUMENT CALIBRATION 7
2.3. TEST FACILITY 7
3. DESCRIPTION OF TESTS 8
3.1 TEST PROCEDURE 8
3.2 RADIATED POWER 9
3.3 RADIATED SPURIOUS EMISSIONS 11
3.4 PEAK- TO- AVERAGE RATIO 12
3.5 OCCUPIED BANDWIDTH. 15
3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL 16
3.7 BAND EDGE 17
3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE 19
3.8 WORST CASE(RADIATED TEST) 20
3.9 WORST CASE(CONDUCTED TEST) 21
4. LIST OF TEST EQUIPMENT 22
5. MEASUREMENT UNCERTAINTY 23
6. SUMMARY OF TEST RESULTS 24
7. SAMPLE CALCULATION 25
8. TEST DATA 27
8.1 EQUIVALENT ISOTROPIC RADIATED POWER 27
8.2 RADIATED SPURIOUS EMISSIONS 30
8.3 PEAK-TO-AVERAGE RATIO 36
8.4 OCCUPIED BANDWIDTH 37
8.5 CONDUCTED SPURIOUS EMISSIONS 38
8.6 BAND EDGE 38
8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE 39
9. TEST PLOTS 57
10. APPENDIX A_ TEST SETUP PHOTO 166

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name:	SAMSUNG Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
FCC ID:	A3LSMT725U
Application Type:	Certification
FCC Classification:	PCS Licensed Transmitter (PCB)
FCC Rule Part(s):	§ 24, § 2
EUT Type:	Tablet
Model(s):	SM-T725
Additional Model(s):	T725N, T727
Keyboard Information	Model : EH-FT720 Manufacture: SAMSUNG
Charging Doc Information	Model : EE-D3200 Manufacture: SAMSUNG
Data Reuse	According to the Evaluation report, all of the data contained herein is reused from the reference FCC ID : A3LSMT725 report.
Tx Frequency:	1850.7 MHz – 1909.3 MHz (LTE – Band2 (1.4 MHz)) 1851.5 MHz – 1908.5 MHz (LTE – Band2 (3 MHz)) 1852.5 MHz – 1907.5 MHz (LTE – Band2 (5 MHz)) 1855.0 MHz – 1905.0 MHz (LTE – Band2 (10 MHz)) 1857.5 MHz – 1902.5 MHz (LTE – Band2 (15 MHz)) 1860.0 MHz – 1900.0 MHz (LTE – Band2 (20 MHz))
Date(s) of Tests:	March 04, 2019 ~ March 13, 2019

1.1. MAXIMUM OUTPUT POWER

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band2 (1.4)	1850.7 - 1909.3	1M09G7D	QPSK	0.157	21.95
		1M09W7D	16QAM	0.130	21.14
		1M09W7D	64QAM	0.104	20.16
LTE – Band2 (3)	1851.5 - 1908.5	2M72G7D	QPSK	0.160	22.03
		2M71W7D	16QAM	0.132	21.21
		2M71W7D	64QAM	0.105	20.22
LTE – Band2 (5)	1852.5 - 1907.5	4M52G7D	QPSK	0.159	22.02
		4M49W7D	16QAM	0.134	21.27
		4M51W7D	64QAM	0.115	20.60
LTE – Band2 (10)	1855.0 - 1905.0	8M98G7D	QPSK	0.158	21.98
		8M99W7D	16QAM	0.134	21.27
		8M98W7D	64QAM	0.107	20.31
LTE – Band2 (15)	1857.5 - 1902.5	13M4G7D	QPSK	0.149	21.74
		13M4W7D	16QAM	0.125	20.98
		13M4W7D	64QAM	0.109	20.36
LTE – Band2 (20)	1860.0 - 1900.0	17M9G7D	QPSK	0.157	21.96
		17M8W7D	16QAM	0.133	21.25
		17M9W7D	64QAM	0.111	20.45

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

The EUT was a Tablet with GSM/GPRS/EGPRS/UMTS and LTE.

It also supports IEEE 802.11 a/b/g/n/ac (HT20/40/80), ANT+, Bluetooth, BT LE.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Peak- to- Average Ratio	- KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4 - ANSI C63.26-2015 – Section 5.2.6(only GSM)
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Effective Radiated Power/ Effective Isotropic Radiated Power	- KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI C63.26-2015 – Section 5.2 - ANSI/TIA-603-E-2016 – Section 2.2.17
Radiated Spurious and Harmonic Emissions	- KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW ≥ 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points > 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

   The power is calculated by the following formula;

$$P_{d(dBm)} = Pg_{(dBm)} - \text{cable loss}_{(dB)} + \text{antenna gain}_{(dB)}$$

   Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.
3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain

These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW ≥ 3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points > 2 x span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data

3.4 PEAK- TO- AVERAGE RATIO



Test setup

① CCDF Procedure for PAPR

Test Settings

1. Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;

2. Set the number of counts to a value that stabilizes the measured CCDF curve;

3. Set the measurement interval as follows:

.- for continuous transmissions, set to 1 ms,

.- or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.

4. Record the maximum PAPR level associated with a probability of 0.1%.

② Alternate Procedure for PAPR

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as P_{Pk}.

Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record as P_{Avg}. Determine the P.A.R. from:

$$P.A.R_{(dB)} = P_{Pk\,(dBm)} - P_{Avg\,(dBm)} \quad (P_{Avg} = \text{Average Power} + \text{Duty cycle Factor})$$

Test Settings(Peak Power)

The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW ≥ 3 × RBW.

1. Set the RBW ≥ OBW.
2. Set VBW ≥ 3 × RBW.
3. Set span ≥ 2 × OBW.
4. Sweep time ≥ 10 × (number of points in sweep) × (transmission symbol period).
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the peak amplitude level.

Test Settings(Average Power)

1. Set span to 2 × to 3 × the OBW.
2. Set RBW ≥ OBW.
3. Set VBW ≥ 3 × RBW.
4. Set number of measurement points in sweep ≥ 2 × span / RBW.
5. Sweep time:

   Set ≥ [10 × (number of points in sweep) × (transmission period)] for single sweep

   (automation-compatible) measurement. The transmission period is the (on + off) time.
6. Detector = power averaging (rms).
7. Set sweep trigger to “free run.”
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.)

9. Use the peak marker function to determine the maximum amplitude level.

10. Add [10 log (1/duty cycle)] to the measured maximum power level to compute the average power during continuous transmission. For example, add [10 log (1/0.25)] = 6 dB if the duty cycle is a constant 25%.

3.5 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.
The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW ≥ 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW ≥ 3 MHz
3. Detector = RMS
4. Trace Mode = Average
5. Sweep time = auto
6. Number of points in sweep ≥ 2 * Span / RBW

3.7 BAND EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1% of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points ≥ 2 x Span/RBW
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Notes

According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of The authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one

of the emission bandwidth of the fundamental emission of the transmitter may be employed.

All measurements were done at 2 channels(low and high operational frequency range.)

The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

   The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.

2. Primary Supply Voltage:

   .- Unless otherwise specified, vary primary supply voltage from 85% to 115% of the nominal value for other than hand carried battery equipment.

   .- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.8 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
- The worst case is reported with the EUT positioning, modulations, and paging service configurations shown in the test data.
- SM-T725 & additional models were tested and the worst case results are reported.
  (Worst case : SM-T725)
- SM-T725 with Stand alone&Keyboard&Charging pad were tested and the worst case results are reported.
  (Worst case : Stand alone)
- Please refer to the table below.

[Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	QPSK, 16QAM, 64-QAM	1	0	X
Radiated Spurious and Harmonic Emissions	QPSK	1	0	Y

3.9 WORST CASE(CONDUCTED TEST)

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth	QPSK, 16QAM, 64-QAM	1.4, 3, 5, 10, 15, 20	Mid	Full RB	0
Band Edge	* QPSK	1.4	Low	1	0
			High	1	5
		3	Low	1	0
			High	1	14
		5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	49
		15	Low	1	0
			High	1	74
		20	Low	1	0
			High	1	99
		1.4, 3, 5, 10, 15, 20	Low, High	Full RB	0
Spurious and Harmonic Emissions at Antenna Terminal	* QPSK	1.4, 3, 5, 10, 15, 20	Low, Mid, High	1	0

* Worst case : Of all modulation, We have tested modulation of the high Conducted Output Power.
Conducted Output Power value can be confirmed on the SAR report.

- All modes of operation were investigated and the worst case configuration results are reported.
- SM-T725 & additional models were tested and the worst case results are reported.
(Worst case : SM-T725)

4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Date	Calibration Interval	Calibration Due
REOHDE & SCHWARZ	SCU 18 / AMPLIFIER	10094	04/17/2018	Annual	04/17/2019
Wainwright	WHK1.2/15G-10EF/H.P.F	4	04/04/2018	Annual	04/04/2019
Wainwright	WHK3.3/18G-10EF/H.P.F	2	04/04/2018	Annual	04/04/2019
Hewlett Packard	11667B / Power Splitter(DC~26.5 GHz)	5001	06/07/2018	Annual	06/07/2019
Agilent	E3632A/DC Power Supply	KR75303243	05/09/2018	Annual	05/09/2019
Schwarzbeck	UHAP/ Dipole Antenna	557	03/31/2017	Biennial	03/31/2019
Schwarzbeck	UHAP/ Dipole Antenna	558	03/31/2017	Biennial	03/31/2019
ESPEC	SU-642 / Chamber	93000718	08/07/2018	Annual	08/07/2019
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	147	09/14/2018	Annual	09/14/2019
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	9120D-1298	10/04/2018	Annual	10/04/2019
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170342	04/25/2017	Biennial	04/25/2019
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170124	04/25/2017	Biennial	04/25/2019
Agilent	N9020A/Signal Analyzer(10Hz~26.5GHz)	MY52090906	06/08/2018	Annual	06/08/2019
Hewlett Packard	8493C/ATTENUATOR(20dB)	17280	06/21/2018	Annual	06/21/2019
REOHDE & SCHWARZ	FSV40/Spectrum Analyzer(10Hz~40GHz)	100931	10/22/2018	Annual	10/22/2019
Agilent	8960 (E5515C)/ Base Station	MY48360800	09/27/2018	Annual	09/27/2019
Schwarzbeck	FMZB1513/ Loop Antenna(9kHz~30MHz)	1513-175	08/23/2018	Biennial	08/23/2020
Schwarzbeck	VULB9160/ Bilog Antenna	9160-3368	08/09/2018	Biennial	08/09/2020
Schwarzbeck	VULB9160/ Hybrid Antenna	760	04/06/2017	Biennial	04/06/2019
Anritsu Corp.	MT8821C/Wideband Radio Communication Tester	6201502997	08/13/2018	Annual	08/13/2019
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6201026545	01/30/2019	Annual	01/30/2020
REOHDE & SCHWARZ	SMB100A/ SIGNAL GENERATOR (100kHz~40GHz)	177633	07/19/2018	Annual	07/19/2019
REOHDE & SCHWARZ	ESU40 / EMI TEST RECEIVER	100524	07/27/2018	Annual	07/27/2019
HCT CO., LTD.,	FCC LTE Mobile Conducted RF Automation Test Software	-	-	-	-

Note:

1. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	E
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.71

6. SUMMARY OF TEST RESULTS

6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§ 2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§ 2.1051, § 24.238(a)	< 43 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions	PASS
Conducted Output Power	§ 2.1046	N/A	**See Note1**
Peak- to- Average Ratio	§ 24.232(d)	< 13 dB	PASS
Frequency stability / variation of ambient temperature	§ 24.235	Emission must remain in band	PASS

Note:

1. See SAR Report
2. The same samples were used for SAR and EMC

6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Equivalent Isotropic Radiated Power	§ 24.232(c)	< 2 Watts max. EIRP	PASS
Radiated Spurious and Harmonic Emissions	§ 2.1053, § 24.238(a)	< 43 + 10log10 (P[Watts]) for all out-of band emissions	PASS

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

ERP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.

2) During the test , the turn table is rotated until the maximum signal is found.

3) Record the field strength meter's level.

4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.

5) Increase the signal generator output till the field strength meter's level is equal to the item (3).

6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

EIRP = Substitute LEVEL(dBm) + Ant. Gain – CL(Cable Loss)

1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.

2) During the test , the turn table is rotated until the maximum signal is found.

3) Record the field strength meter's level.

4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.

5) Increase the signal generator output till the field strength meter's level is equal to the item (3).

6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

16QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

8. TEST DATA

8.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
1850.7	LTE B2/ 1.4 MHz	QPSK	-20.23	11.81	10.27	1.34	H	< 2.00	0.119	20.74
		16-QAM	-21.15	10.89	10.27	1.34	H		0.096	19.82
		64-QAM	-22.09	9.95	10.27	1.34	H		0.077	18.88
1880.0		QPSK	-19.11	13.02	10.29	1.36	H		0.157	21.95
		16-QAM	-19.92	12.21	10.29	1.36	H		0.130	21.14
		64-QAM	-20.90	11.23	10.29	1.36	H		0.104	20.16
1909.3		QPSK	-19.97	12.56	10.31	1.37	H		0.141	21.50
		16-QAM	-20.75	11.78	10.31	1.37	H		0.118	20.72
		64-QAM	-21.74	10.79	10.31	1.37	H		0.094	19.73

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
1851.5	LTE B2/ 3 MHz	QPSK	-20.19	11.85	10.27	1.34	H	< 2.00	0.120	20.78
		16-QAM	-21.08	10.96	10.27	1.34	H		0.097	19.89
		64-QAM	-22.02	10.02	10.27	1.34	H		0.079	18.95
1880.0		QPSK	-19.03	13.10	10.29	1.36	H		0.160	22.03
		16-QAM	-19.85	12.28	10.29	1.36	H		0.132	21.21
		64-QAM	-20.84	11.29	10.29	1.36	H		0.105	20.22
1908.5		QPSK	-19.65	12.88	10.31	1.37	H		0.152	21.82
		16-QAM	-20.41	12.12	10.31	1.37	H		0.128	21.06
		64-QAM	-21.43	11.10	10.31	1.37	H		0.101	20.04

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
1852.5	LTE B2/ 5 MHz	QPSK	-20.15	11.89	10.27	1.34	H	< 2.00	0.121	20.82
		16-QAM	-21.06	10.98	10.27	1.34	H		0.098	19.91
		64-QAM	-21.99	10.55	10.27	1.34	H		0.089	19.48
1880.0		QPSK	-19.08	13.05	10.29	1.36	H		0.158	21.98
		16-QAM	-19.88	12.25	10.29	1.36	H		0.131	21.18
		64-QAM	-20.87	11.67	10.29	1.36	H		0.115	20.60
1907.5		QPSK	-19.45	13.08	10.31	1.37	H		0.159	22.02
		16-QAM	-20.20	12.33	10.31	1.37	H		0.134	21.27
		64-QAM	-21.25	11.28	10.31	1.37	H		0.105	20.22

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
1855.0	LTE B2/ 10 MHz	QPSK	-20.04	11.96	10.28	1.34	H	< 2.00	0.123	20.89
		16-QAM	-20.92	11.08	10.28	1.34	H		0.100	20.01
		64-QAM	-21.86	10.67	10.28	1.34	H		0.091	19.61
1880.0		QPSK	-19.37	12.76	10.29	1.36	H		0.148	21.69
		16-QAM	-20.12	12.01	10.29	1.36	H		0.124	20.94
		64-QAM	-21.16	11.38	10.29	1.36	H		0.107	20.31
1905.0		QPSK	-19.38	13.04	10.31	1.37	H		0.158	21.98
		16-QAM	-20.09	12.33	10.31	1.37	H		0.134	21.27
		64-QAM	-21.17	11.35	10.31	1.37	H		0.107	20.30

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
1857.5	LTE B2/ 15 MHz	QPSK	-20.19	11.77	10.28	1.34	H	< 2.00	0.118	20.71
		16-QAM	-21.04	10.92	10.28	1.34	H		0.097	19.86
		64-QAM	-21.98	10.55	10.28	1.34	H		0.089	19.49
1880.0		QPSK	-19.32	12.81	10.29	1.36	H		0.149	21.74
		16-QAM	-20.08	12.05	10.29	1.36	H		0.125	20.98
		64-QAM	-21.11	11.43	10.29	1.36	H		0.109	20.36
1902.5		QPSK	-19.61	12.70	10.31	1.36	H		0.146	21.65
		16-QAM	-20.31	12.00	10.31	1.36	H		0.124	20.95
		64-QAM	-21.35	11.17	10.31	1.36	H		0.103	20.12

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
1860.0	LTE B2/ 20 MHz	QPSK	-20.14	11.82	10.28	1.34	H	< 2.00	0.119	20.76
		16-QAM	-20.99	10.97	10.28	1.34	H		0.098	19.91
		64-QAM	-21.95	10.58	10.28	1.34	H		0.089	19.52
1880.0		QPSK	-19.40	12.73	10.29	1.36	H		0.147	21.66
		16-QAM	-20.13	12.00	10.29	1.36	H		0.124	20.93
		64-QAM	-21.18	11.36	10.29	1.36	H		0.107	20.29
1900.0		QPSK	-19.30	13.01	10.31	1.36	H		0.157	21.96
		16-QAM	-20.01	12.30	10.31	1.36	H		0.133	21.25
		64-QAM	-21.02	11.50	10.31	1.36	H		0.111	20.45

8.2 RADIATED SPURIOUS EMISSIONS

▣ OPERATING FREQUENTY: 1880.0 MHz

▣ MEASURED OUTPUT POWER: 21.95 dBm = 0.157 W

▣ MOD: LTE B2

▣ MODULATION SIGNAL: 1.4 MHz QPSK

▣ DISTANCE: 3 meters

▣ LIMIT: 43 + 10 log10 (W) = 34.95 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
18607 (1850.7)	3,701.40	-56.62	12.51	-63.42	1.98	H	-52.89	74.84
	5,552.10	-50.71	13.62	-51.99	2.72	H	-41.09	63.05
	7,402.80	-53.31	11.50	-48.30	2.92	V	-39.72	61.68
18900 (1880.0)	3,760.00	-55.69	12.40	-62.13	2.00	H	-51.73	73.68
	5,640.00	-56.16	13.78	-56.99	2.70	H	-45.91	67.86
	7,520.00	-57.02	11.57	-51.81	2.93	H	-43.17	65.12
19193 (1909.3)	3,818.60	-53.21	12.52	-59.45	2.05	H	-48.98	70.93
	5,727.90	-55.99	13.69	-55.94	2.72	V	-44.97	66.92
	7,637.20	-57.08	11.99	-52.28	2.93	H	-43.22	65.17

▣ OPERATING FREQUENTY: 1880.0 MHz

▣ MEASURED OUTPUT POWER: 22.03 dBm = 0.160 W

▣ MOD: LTE B2

▣ MODULATION SIGNAL: 3 MHz QPSK

▣ DISTANCE: 3 meters

▣ LIMIT: 43 + 10 log10 (W) = 35.03 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
18615 (1851.5)	3,703.00	-55.57	12.51	-62.37	1.98	H	-51.84	73.87
	5,554.50	-50.18	13.63	-51.44	2.72	H	-40.53	62.56
	7,406.00	-53.78	11.50	-48.63	2.93	H	-40.06	62.09
18900 (1880.0)	3,760.00	-56.01	12.40	-62.45	2.00	H	-52.05	74.08
	5,640.00	-56.56	13.78	-57.39	2.70	H	-46.31	68.34
	7,520.00	-57.40	11.57	-52.19	2.93	H	-43.55	65.58
19185 (1908.5)	3,817.00	-53.87	12.52	-60.11	2.05	H	-49.64	71.67
	5,725.50	-57.35	13.70	-57.17	2.72	H	-46.20	68.23
	7,634.00	-57.60	11.97	-52.79	2.96	H	-43.78	65.81

▣ OPERATING FREQUENTY: 1907.50 MHz

▣ MEASURED OUTPUT POWER: 22.02 dBm = 0.159 W

▣ MOD: LTE B2

▣ MODULATION SIGNAL: 5 MHz QPSK

▣ DISTANCE: 3 meters

▣ LIMIT: 43 + 10 log10 (W) = 35.02 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
18625 (1852.5)	3,705.00	-56.26	12.50	-62.89	2.00	H	-52.38	74.40
	5,557.50	-50.06	13.64	-51.30	2.71	H	-40.37	62.39
	7,410.00	-54.69	11.50	-49.40	2.93	H	-40.83	62.85
18900 (1880.0)	3,760.00	-55.57	12.40	-62.01	2.00	H	-51.61	73.63
	5,640.00	-56.71	13.78	-57.54	2.70	H	-46.46	68.48
	7,520.00	-57.89	11.57	-52.68	2.93	H	-44.04	66.06
19175 (1907.5)	3,815.00	-52.35	12.52	-58.72	2.06	H	-48.25	70.27
	5,722.50	-57.60	13.70	-57.29	2.72	H	-46.31	68.33
	7,630.00	-58.21	11.95	-53.40	2.98	H	-44.43	66.44

▣ OPERATING FREQUENTY: 1905.00 MHz

▣ MEASURED OUTPUT POWER: 21.98 dBm = 0.158 W

▣ MOD: LTE B2

▣ MODULATION SIGNAL: 10 MHz QPSK

▣ DISTANCE: 3 meters

▣ LIMIT: 43 + 10 log10 (W) = 34.98 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
18650 (1855.0)	3,710.00	-56.48	12.49	-62.94	2.01	H	-52.46	74.44
	5,565.00	-50.99	13.65	-52.27	2.71	H	-41.33	63.31
	7,420.00	-54.47	11.51	-49.09	2.94	H	-40.52	62.51
18900 (1880.0)	3,760.00	-55.28	12.40	-61.72	2.00	H	-51.32	73.30
	5,640.00	-55.69	13.78	-56.52	2.70	H	-45.44	67.42
	7,520.00	-58.49	11.57	-53.28	2.93	H	-44.64	66.63
19150 (1905.0)	3,810.00	-51.82	12.52	-58.32	2.06	H	-47.86	69.84
	5,715.00	-57.26	13.70	-57.08	2.72	H	-46.10	68.08
	7,620.00	-58.85	11.90	-54.05	2.94	H	-45.09	67.07

▣ OPERATING FREQUENTY: 1880.00 MHz

▣ MEASURED OUTPUT POWER: 21.74 dBm = 0.149 W

▣ MOD: LTE B2

▣ MODULATION SIGNAL: 15 MHz QPSK

▣ DISTANCE: 3 meters

▣ LIMIT: 43 + 10 log10 (W) = 34.74dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
18675 (1857.5)	3,715.00	-55.52	12.49	-62.17	2.02	H	-51.70	73.44
	5,572.50	-51.52	13.66	-52.84	2.71	H	-41.89	63.63
	7,430.00	-56.77	11.51	-51.55	2.94	H	-42.98	64.72
18900 (1880.0)	3,760.00	-56.85	12.40	-63.29	2.00	H	-52.89	74.63
	5,640.00	-56.29	13.78	-57.12	2.70	H	-46.04	67.78
	7,520.00	-58.45	11.57	-53.24	2.93	H	-44.60	66.34
19125 (1902.5)	3,805.00	-53.01	12.52	-59.25	2.09	H	-48.82	70.57
	5,707.50	-57.63	13.70	-57.58	2.72	H	-46.60	68.34
	7,610.00	-57.37	11.87	-52.35	3.00	H	-43.48	65.22

▣ OPERATING FREQUENTY: 1900.00 MHz

▣ MEASURED OUTPUT POWER: 21.96 dBm = 0.157 W

▣ MOD: LTE B2

▣ MODULATION SIGNAL: 20 MHz QPSK

▣ DISTANCE: 3 meters

▣ LIMIT: 43 + 10 log10 (W) = 34.96 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
18700 (1860.0)	3,720.00	-56.75	12.48	-63.59	2.03	H	-53.14	75.10
	5,580.00	-52.12	13.69	-53.18	2.69	H	-42.18	64.14
	7,440.00	-55.92	11.52	-50.83	2.89	H	-42.20	64.16
18900 (1880.0)	3,760.00	-53.97	12.40	-60.41	2.00	H	-50.01	71.97
	5,640.00	-56.43	13.78	-57.26	2.70	H	-46.18	68.14
	7,520.00	-58.60	11.57	-53.39	2.93	H	-44.75	66.71
19100 (1900.0)	3,800.00	-53.46	12.52	-59.45	2.12	H	-49.05	71.01
	5,700.00	-58.12	13.71	-58.45	2.74	H	-47.48	69.44
	7,600.00	-58.11	11.85	-52.84	2.90	H	-43.89	65.85

8.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)
2	1.4 MHz	1880.0	QPSK	6	0	4.57
			16-QAM	6	0	5.67
			64-QAM	6	0	5.68
	3 MHz		QPSK	15	0	4.62
			16-QAM	15	0	5.77
			64-QAM	15	0	5.80
	5 MHz		QPSK	25	0	4.73
			16-QAM	25	0	5.78
			64-QAM	25	0	5.75
	10 MHz		QPSK	50	0	4.69
			16-QAM	50	0	5.75
			64-QAM	50	0	5.74
	15 MHz		QPSK	75	0	4.60
			16-QAM	75	0	5.69
			64-QAM	75	0	5.69
	20 MHz		QPSK	100	0	4.54
			16-QAM	100	0	5.66
			64-QAM	100	0	5.68

Note:

1. Plots of the EUT's Peak- to- Average Ratio are shown Page 76 ~ 93.

8.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
2	1.4 MHz	1880.0	QPSK	6	0	1.0927
			16-QAM	6	0	1.0915
			64-QAM	6	0	1.0900
	3 MHz		QPSK	15	0	2.7148
			16-QAM	15	0	2.7072
			64-QAM	15	0	2.7084
	5 MHz		QPSK	25	0	4.5198
			16-QAM	25	0	4.4931
			64-QAM	25	0	4.5090
	10 MHz		QPSK	50	0	8.9814
			16-QAM	50	0	8.9879
			64-QAM	50	0	8.9761
	15 MHz		QPSK	75	0	13.408
			16-QAM	75	0	13.443
			64-QAM	75	0	13.424
	20 MHz		QPSK	100	0	17.931
			16-QAM	100	0	17.842
			64-QAM	100	0	17.880

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 58 ~ 75.

8.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
2	1.4	1850.7	7.4013	28.591	-74.864	-46.273	-13.00
		1880.0	3.7064	27.976	-77.166	-49.190	
		1909.3	3.8201	27.976	-74.517	-46.541	
	3	1851.5	7.4018	28.591	-74.714	-46.123	
		1880.0	3.6960	27.976	-77.100	-49.124	
		1908.5	3.8201	27.976	-74.751	-46.775	
	5	1852.5	7.4023	28.591	-75.052	-46.461	
		1880.0	3.7034	27.976	-77.092	-49.116	
		1907.5	3.8201	27.976	-74.819	-46.843	
	10	1855.0	7.4028	28.591	-75.681	-47.090	
		1880.0	3.7518	27.976	-76.473	-48.497	
		1905.0	3.8196	27.976	-75.059	-47.083	
	15	1857.5	7.4038	28.591	-73.803	-45.212	
		1880.0	3.7473	27.976	-76.380	-48.404	
		1902.5	3.8191	27.976	-75.443	-47.467	
	20	1860.0	7.4048	28.591	-75.629	-47.038	
		1880.0	3.7079	27.976	-77.064	-49.088	
		1900.0	3.8186	27.976	-75.522	-47.546	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 130 ~ 165.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor(dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20	30.131

8.6 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 94 ~ 129.

8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

▣ MODE: LTE B2

▣ OPERATING FREQUENCY: 1850,700,000 Hz

▣ CHANNEL: 18607 (1.4 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	1850 699 987	0.0	0.000 000	0.000
100%		-30	1850 699 998	11.0	0.000 001	0.006
100%		-20	1850 699 976	-10.6	-0.000 001	-0.006
100%		-10	1850 699 982	-4.4	0.000 000	-0.002
100%		0	1850 699 976	-11.1	-0.000 001	-0.006
100%		+10	1850 699 992	5.4	0.000 000	0.003
100%		+30	1850 699 971	-15.4	-0.000 001	-0.008
100%		+40	1850 699 980	-6.3	0.000 000	-0.003
100%		+50	1850 699 978	-8.6	0.000 000	-0.005
Batt. Endpoint	3.400	+20	1850 699 977	-9.3	-0.000 001	-0.005



▣ MODE: LTE B2

▣ OPERATING FREQUENCY: 1851,500,000 Hz

▣ CHANNEL: 18615 (3 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	1851 500 014	0.0	0.000 000	0.000
100%		-30	1851 500 029	14.8	0.000 001	0.008
100%		-20	1851 500 030	16.2	0.000 001	0.009
100%		-10	1851 500 028	13.3	0.000 001	0.007
100%		0	1851 500 030	15.4	0.000 001	0.008
100%		+10	1851 500 030	16.0	0.000 001	0.009
100%		+30	1851 500 032	17.6	0.000 001	0.010
100%		+40	1851 500 030	15.7	0.000 001	0.008
100%		+50	1851 500 027	13.1	0.000 001	0.007
Batt. Endpoint	3.400	+20	1851 500 026	11.3	0.000 001	0.006



▣ MODE: LTE B2

▣ OPERATING FREQUENCY: 1852,500,000 Hz

▣ CHANNEL: 18625 (5 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	1852 499 995	0.0	0.000 000	0.000
100%		-30	1852 499 991	-4.1	0.000 000	-0.002
100%		-20	1852 499 999	4.1	0.000 000	0.002
100%		-10	1852 500 000	5.1	0.000 000	0.003
100%		0	1852 499 981	-14.2	-0.000 001	-0.008
100%		+10	1852 499 981	-13.9	-0.000 001	-0.008
100%		+30	1852 499 980	-14.6	-0.000 001	-0.008
100%		+40	1852 499 980	-14.6	-0.000 001	-0.008
100%		+50	1852 499 982	-12.9	-0.000 001	-0.007
Batt. Endpoint	3.400	+20	1852 499 983	-11.9	-0.000 001	-0.006



▣ MODE: LTE B2

▣ OPERATING FREQUENCY: 1855,000,000 Hz

▣ CHANNEL: 18650 (10 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	1855 000 010	0.0	0.000 000	0.000
100%		-30	1855 000 004	-5.5	0.000 000	-0.003
100%		-20	1855 000 000	-10.4	-0.000 001	-0.006
100%		-10	1855 000 020	10.5	0.000 001	0.006
100%		0	1855 000 007	-2.9	0.000 000	-0.002
100%		+10	1855 000 006	-3.8	0.000 000	-0.002
100%		+30	1855 000 006	-3.5	0.000 000	-0.002
100%		+40	1855 000 015	5.0	0.000 000	0.003
100%		+50	1855 000 018	8.2	0.000 000	0.004
Batt. Endpoint	3.400	+20	1855 000 018	8.0	0.000 000	0.004



▣ MODE: LTE B2

▣ OPERATING FREQUENCY: 1857,500,000 Hz

▣ CHANNEL: 18675 (15 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	1857 500 005	0.0	0.000 000	0.000
100%		-30	1857 500 010	4.8	0.000 000	0.003
100%		-20	1857 500 008	2.5	0.000 000	0.001
100%		-10	1857 500 021	16.2	0.000 001	0.009
100%		0	1857 500 013	8.2	0.000 000	0.004
100%		+10	1857 500 013	7.4	0.000 000	0.004
100%		+30	1857 500 017	12.2	0.000 001	0.007
100%		+40	1857 500 018	12.3	0.000 001	0.007
100%		+50	1857 500 019	14.1	0.000 001	0.008
Batt. Endpoint	3.400	+20	1857 500 016	10.6	0.000 001	0.006



▣ MODE: LTE B2

▣ OPERATING FREQUENCY: 1860,000,000 Hz

▣ CHANNEL: 18700 (20 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	1860 000 007	0.0	0.000 000	0.000
100%		-30	1859 999 995	-12.7	-0.000 001	-0.007
100%		-20	1859 999 995	-12.5	-0.000 001	-0.007
100%		-10	1859 999 994	-13.8	-0.000 001	-0.007
100%		0	1859 999 995	-12.5	-0.000 001	-0.007
100%		+10	1860 000 010	2.9	0.000 000	0.002
100%		+30	1860 000 003	-4.4	0.000 000	-0.002
100%		+40	1860 000 005	-2.8	0.000 000	-0.002
100%		+50	1859 999 991	-16.4	-0.000 001	-0.009
Batt. Endpoint	3.400	+20	1859 999 994	-13.4	-0.000 001	-0.007



▣ MODE: LTE B2

▣ OPERATING FREQUENCY: 1880,000,000 Hz

▣ CHANNEL: 18900 (1.4 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	1880 000 011	0.0	0.000 000	0.000
100%		-30	1880 000 008	-3.8	0.000 000	-0.002
100%		-20	1880 000 001	-10.8	-0.000 001	-0.006
100%		-10	1880 000 017	6.0	0.000 000	0.003
100%		0	1880 000 013	1.6	0.000 000	0.001
100%		+10	1880 000 005	-6.6	0.000 000	-0.004
100%		+30	1880 000 003	-8.1	0.000 000	-0.004
100%		+40	1880 000 020	8.5	0.000 000	0.005
100%		+50	1880 000 006	-5.9	0.000 000	-0.003
Batt. Endpoint	3.400	+20	1880 000 000	-11.9	-0.000 001	-0.006



▣ MODE: LTE B2

▣ OPERATING FREQUENCY: 1880,000,000 Hz

▣ CHANNEL: 18900 (3 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	1879 999 996	0.0	0.000 000	0.000
100%		-30	1880 000 004	8.4	0.000 000	0.004
100%		-20	1880 000 011	15.1	0.000 001	0.008
100%		-10	1880 000 006	10.0	0.000 001	0.005
100%		0	1880 000 001	4.9	0.000 000	0.003
100%		+10	1880 000 011	14.7	0.000 001	0.008
100%		+30	1880 000 007	11.4	0.000 001	0.006
100%		+40	1880 000 005	9.1	0.000 000	0.005
100%		+50	1879 999 994	-2.0	0.000 000	-0.001
Batt. Endpoint	3.400	+20	1880 000 007	11.0	0.000 001	0.006



▣ MODE: LTE B2

▣ OPERATING FREQUENCY: 1880,000,000 Hz

▣ CHANNEL: 18900 (5 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	1880 000 003	0.0	0.000 000	0.000
100%		-30	1880 000 000	-3.0	0.000 000	-0.002
100%		-20	1880 000 013	10.0	0.000 001	0.005
100%		-10	1880 000 011	7.9	0.000 000	0.004
100%		0	1880 000 020	16.7	0.000 001	0.009
100%		+10	1880 000 014	11.3	0.000 001	0.006
100%		+30	1880 000 008	5.3	0.000 000	0.003
100%		+40	1880 000 020	17.1	0.000 001	0.009
100%		+50	1880 000 013	9.8	0.000 001	0.005
Batt. Endpoint	3.400	+20	1880 000 008	5.3	0.000 000	0.003



▣ MODE: LTE B2

▣ OPERATING FREQUENCY: 1880,000,000 Hz

▣ CHANNEL: 18900 (10 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	1880 000 013	0.0	0.000 000	0.000
100%		-30	1880 000 010	-3.1	0.000 000	-0.002
100%		-20	1880 000 022	9.1	0.000 000	0.005
100%		-10	1880 000 007	-6.0	0.000 000	-0.003
100%		0	1880 000 024	11.1	0.000 001	0.006
100%		+10	1880 000 020	6.8	0.000 000	0.004
100%		+30	1880 000 026	12.4	0.000 001	0.007
100%		+40	1880 000 011	-2.0	0.000 000	-0.001
100%		+50	1880 000 019	5.6	0.000 000	0.003
Batt. Endpoint	3.400	+20	1880 000 024	10.5	0.000 001	0.006



▣ MODE: LTE B2

▣ OPERATING FREQUENCY: 1880,000,000 Hz

▣ CHANNEL: 18900 (15 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	1879 999 997	0.0	0.000 000	0.000
100%		-30	1880 000 007	10.5	0.000 001	0.006
100%		-20	1880 000 010	13.6	0.000 001	0.007
100%		-10	1879 999 992	-4.6	0.000 000	-0.002
100%		0	1879 999 993	-3.9	0.000 000	-0.002
100%		+10	1879 999 999	2.1	0.000 000	0.001
100%		+30	1880 000 000	3.6	0.000 000	0.002
100%		+40	1880 000 001	4.8	0.000 000	0.003
100%		+50	1880 000 012	15.7	0.000 001	0.008
Batt. Endpoint	3.400	+20	1879 999 994	-2.4	0.000 000	-0.001



▣ MODE: LTE B2

▣ OPERATING FREQUENCY: 1880,000,000 Hz

▣ CHANNEL: 18900 (20 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	1880 000 017	0.0	0.000 000	0.000
100%		-30	1880 000 018	1.5	0.000 000	0.001
100%		-20	1880 000 025	8.8	0.000 000	0.005
100%		-10	1880 000 032	15.3	0.000 001	0.008
100%		0	1880 000 023	6.1	0.000 000	0.003
100%		+10	1880 000 031	14.7	0.000 001	0.008
100%		+30	1880 000 024	7.8	0.000 000	0.004
100%		+40	1880 000 034	17.1	0.000 001	0.009
100%		+50	1880 000 019	2.5	0.000 000	0.001
Batt. Endpoint	3.400	+20	1880 000 026	9.5	0.000 001	0.005



▣ MODE: LTE B2

▣ OPERATING FREQUENCY: 1909,300,000 Hz

▣ CHANNEL: 19193 (1.4 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	1909 299 992	0.0	0.000 000	0.000
100%		-30	1909 299 984	-7.6	0.000 000	-0.004
100%		-20	1909 299 979	-12.9	-0.000 001	-0.007
100%		-10	1909 299 980	-11.7	-0.000 001	-0.006
100%		0	1909 299 978	-13.3	-0.000 001	-0.007
100%		+10	1909 300 005	13.0	0.000 001	0.007
100%		+30	1909 300 001	9.7	0.000 001	0.005
100%		+40	1909 299 984	-7.6	0.000 000	-0.004
100%		+50	1909 299 978	-13.8	-0.000 001	-0.007
Batt. Endpoint	3.400	+20	1909 300 001	8.9	0.000 000	0.005



▣ MODE: LTE B2

▣ OPERATING FREQUENCY: 1908,500,000 Hz

▣ CHANNEL: 19185 (3 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	1908 500 018	0.0	0.000 000	0.000
100%		-30	1908 500 027	9.6	0.000 001	0.005
100%		-20	1908 500 035	17.1	0.000 001	0.009
100%		-10	1908 500 041	23.0	0.000 001	0.012
100%		0	1908 500 035	16.9	0.000 001	0.009
100%		+10	1908 500 027	9.2	0.000 000	0.005
100%		+30	1908 500 039	21.5	0.000 001	0.011
100%		+40	1908 500 031	13.7	0.000 001	0.007
100%		+50	1908 500 009	-8.5	0.000 000	-0.004
Batt. Endpoint	3.400	+20	1908 500 035	16.8	0.000 001	0.009



▣ MODE: LTE B2

▣ OPERATING FREQUENCY: 1907,500,000 Hz

▣ CHANNEL: 19175 (5 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	1907 499 994	0.0	0.000 000	0.000
100%		-30	1907 500 002	8.2	0.000 000	0.004
100%		-20	1907 499 989	-4.4	0.000 000	-0.002
100%		-10	1907 499 986	-8.0	0.000 000	-0.004
100%		0	1907 500 004	9.8	0.000 001	0.005
100%		+10	1907 500 001	7.6	0.000 000	0.004
100%		+30	1907 499 997	3.3	0.000 000	0.002
100%		+40	1907 499 982	-11.3	-0.000 001	-0.006
100%		+50	1907 500 004	10.7	0.000 001	0.006
Batt. Endpoint	3.400	+20	1907 500 002	7.8	0.000 000	0.004



▣ MODE: LTE B2

▣ OPERATING FREQUENCY: 1905,000,000 Hz

▣ CHANNEL: 19150 (10 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	1905 000 007	0.0	0.000 000	0.000
100%		-30	1904 999 992	-14.3	-0.000 001	-0.008
100%		-20	1905 000 000	-6.7	0.000 000	-0.004
100%		-10	1904 999 990	-16.6	-0.000 001	-0.009
100%		0	1904 999 998	-8.7	0.000 000	-0.005
100%		+10	1904 999 990	-16.6	-0.000 001	-0.009
100%		+30	1905 000 000	-7.0	0.000 000	-0.004
100%		+40	1904 999 994	-12.5	-0.000 001	-0.007
100%		+50	1904 999 991	-15.8	-0.000 001	-0.008
Batt. Endpoint	3.400	+20	1905 000 001	-5.2	0.000 000	-0.003



▣ MODE: LTE B2

▣ OPERATING FREQUENCY: 1902,500,000 Hz

▣ CHANNEL: 19125 (15 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	1902 500 010	0.0	0.000 000	0.000
100%		-30	1902 500 022	11.7	0.000 001	0.006
100%		-20	1902 500 019	9.1	0.000 000	0.005
100%		-10	1902 500 016	5.8	0.000 000	0.003
100%		0	1902 500 020	10.1	0.000 001	0.005
100%		+10	1902 500 013	2.7	0.000 000	0.001
100%		+30	1902 500 004	-6.4	0.000 000	-0.003
100%		+40	1902 500 004	-6.0	0.000 000	-0.003
100%		+50	1902 500 005	-5.2	0.000 000	-0.003
Batt. Endpoint	3.400	+20	1902 500 003	-6.8	0.000 000	-0.004



▣ MODE: LTE B2

▣ OPERATING FREQUENCY: 1900,000,000 Hz

▣ CHANNEL: 19100 (20 MHz)

▣ REFERENCE VOLTAGE: 3.85 VDC

▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	1900 000 006	0.0	0.000 000	0.000
100%		-30	1900 000 012	6.0	0.000 000	0.003
100%		-20	1900 000 003	-3.5	0.000 000	-0.002
100%		-10	1900 000 002	-4.5	0.000 000	-0.002
100%		0	1899 999 998	-8.1	0.000 000	-0.004
100%		+10	1899 999 997	-9.2	0.000 000	-0.005
100%		+30	1900 000 018	11.4	0.000 001	0.006
100%		+40	1900 000 017	11.2	0.000 001	0.006
100%		+50	1900 000 017	11.1	0.000 001	0.006
Batt. Endpoint	3.400	+20	1900 000 017	10.8	0.000 001	0.006



9. TEST PLOTS

BAND 2. Occupied Bandwidth Plot (1.4M BW Ch.18900 QPSK RB 6_0)



BAND 2. Occupied Bandwidth Plot (1.4M BW Ch.18900 16QAM RB 6_0)



BAND 2. Occupied Bandwidth Plot (1.4M BW Ch.18900 64QAM RB 6_0)



BAND 2. Occupied Bandwidth Plot (3M BW Ch.18900 QPSK RB 15_0)



BAND 2. Occupied Bandwidth Plot (3M BW Ch.18900 16QAM RB 15_0)



BAND 2. Occupied Bandwidth Plot (3M BW Ch.18900 64QAM RB 15_0)



BAND 2. Occupied Bandwidth Plot (5M BW Ch.18900 QPSK RB 25_0)



BAND 2. Occupied Bandwidth Plot (5M BW Ch.18900 16QAM RB 25_0)



BAND 2. Occupied Bandwidth Plot (5M BW Ch.18900 64QAM RB 25_0)



BAND 2. Occupied Bandwidth Plot (10M BW Ch.18900 QPSK RB 50_0)



BAND 2. Occupied Bandwidth Plot (10M BW Ch.18900 16QAM RB 50_0)



BAND 2. Occupied Bandwidth Plot (10M BW Ch.18900 64QAM RB 50_0)



BAND 2. Occupied Bandwidth Plot (15M BW Ch.18900 QPSK RB 75_0)



BAND 2. Occupied Bandwidth Plot (15M BW Ch.18900 16QAM RB 75_0)



BAND 2. Occupied Bandwidth Plot (15M BW Ch.18900 64QAM RB 75_0)



BAND 2. Occupied Bandwidth Plot (20M BW Ch.18900 QPSK RB 100_0)



BAND 2. Occupied Bandwidth Plot (20M BW Ch.18900 16QAM RB 100_0)



BAND 2. Occupied Bandwidth Plot (20M BW Ch.18900 64QAM RB 100_0)



BAND 2. PAR Plot (1.4M BW Ch.18900 QPSK RB 6_0)



BAND 2. PAR Plot (1.4M BW Ch.18900 16QAM RB 6_0)



BAND 2. PAR Plot (1.4M BW Ch.18900 64QAM RB 6_0)



BAND 2. PAR Plot (3M BW Ch.18900 QPSK RB 15_0)



BAND 2. PAR Plot (3M BW Ch.18900 16QAM RB 15_0)



BAND 2. PAR Plot (3M BW Ch.18900 64QAM RB 15_0)



BAND 2. PAR Plot (5M BW Ch.18900 QPSK RB 25_0)



BAND 2. PAR Plot (5M BW Ch.18900 16QAM RB 25_0)



BAND 2. PAR Plot (5M BW Ch.18900 64QAM RB 25_0)



BAND 2. PAR Plot (10M BW Ch.18900 QPSK RB 50_0)