

TEST REPORT

FCC LTE Test for SM-T727U
Certification

APPLICANT
SAMSUNG Electronics Co., Ltd.

REPORT NO.
HCT-RF-1906-FC046-R1

DATE OF ISSUE
July 12, 2019

HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 F ax. +82 31 645 6401



HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401

TEST REPORT

FCC LTE Test for
SM-T727U

REPORT NO.
HCT-RF-1906-FC046-R1

DATE OF ISSUE
July 12, 2019

ID
FCC: A3LSMT727U

Applicant

SAMSUNG Electronics Co., Ltd.
129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Eut Type
Model Name
Additional Model(s)

Tablet
SM-T727U
SM-T727P

Date of Receipt

May 22, 2019

FCC Classification

PCS Licensed Transmitter (PCB)

Manufacturer

SAMSUNG Electronics Co., Ltd.

Tested by
Kwon Jeong

(signature)

Technical Manager
Jong Seok Lee

(signature)

HCT CO., LTD.

Soo Chan Lee
Soo Chan Lee / CEO

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	June 24, 2019	Initial Release
1	July 12, 2019	Retested the LTE B12(17)

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section § 2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C. 853(a)

CONTENTS

1. GENERAL INFORMATION	5
1.1. MAXIMUM OUTPUT POWER	6
2. INTRODUCTION	7
2.1. DESCRIPTION OF EUT	7
2.2. MEASURING INSTRUMENT CALIBRATION	7
2.3. TEST FACILITY	7
3. DESCRIPTION OF TESTS	8
3.1 TEST PROCEDURE	8
3.2 RADIATED POWER	9
3.3 RADIATED SPURIOUS EMISSIONS	10
3.4 OCCUPIED BANDWIDTH.	11
3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	12
3.6 BAND EDGE	13
3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	14
3.8 WORST CASE(RADIATED TEST)	15
3.9 WORST CASE(CONDUCTED TEST)	16
4. LIST OF TEST EQUIPMENT	17
5. MEASUREMENT UNCERTAINTY	18
6. SUMMARY OF TEST RESULTS	19
7. SAMPLE CALCULATION	20
8. TEST DATA	22
8.1 EFFECTIVE RADIATED POWER	22
8.3 RADIATED SPURIOUS EMISSIONS	24
8.3 OCCUPIED BANDWIDTH	28
8.4 CONDUCTED SPURIOUS EMISSIONS	29
8.5 BAND EDGE	29
8.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	30
9. TEST PLOTS	42
10. ANNEX A_ TEST SETUP PHOTO	92

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name:	SAMSUNG Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
FCC ID:	A3LSMT727U
Application Type:	Certification
FCC Classification:	PCS Licensed Transmitter (PCB)
FCC Rule Part(s):	§ 27, § 2
EUT Type:	Tablet
Model(s):	SM-T727U
Additional Model(s)	SM-T727P
Tx Frequency:	699.7 MHz – 715.3 MHz (LTE – Band 12 (1.4 MHz)) 700.5 MHz – 714.5 MHz (LTE – Band 12 (3 MHz)) 701.5 MHz – 713.5 MHz (LTE – Band 12/17 (5 MHz)) 704.0 MHz – 711.0 MHz (LTE – Band 12/17 (10 MHz))
Date(s) of Tests:	June 04, 2019~ July 12, 2019

1.1. MAXIMUM OUTPUT POWER

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	ERP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band12 (1.4)	699.7 – 715.3	1M09G7D	QPSK	0.036	15.53
		1M09W7D	16QAM	0.030	14.83
		1M09W7D	64QAM	0.024	13.77
LTE – Band12 (3)	700.5 – 714.5	2M71G7D	QPSK	0.037	15.64
		2M70W7D	16QAM	0.031	14.91
		2M70W7D	64QAM	0.024	13.85
LTE – Band12/17 (5)	701.5 – 713.5	4M52G7D	QPSK	0.037	15.66
		4M50W7D	16QAM	0.031	14.95
		4M53W7D	64QAM	0.024	13.89
LTE – Band12/17 (10)	704.0 – 711.0	8M99G7D	QPSK	0.036	15.59
		8M97W7D	16QAM	0.031	14.92
		8M98W7D	64QAM	0.024	13.82

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

The EUT was a Tablet with UMTS and LTE.

It also supports IEEE 802.11 a/b/g/n/ac (HT20/40/80), ANT+, Bluetooth, BT LE.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Effective Radiated Power/ Effective Isotropic Radiated Power	- KDB 971168 D01 v03r01 – Section 5.2 & 5.8 - ANSI/TIA-603-E-2016 – Section 2.2.17
Radiated Spurious and Harmonic Emissions	- KDB 971168 D01 v03r01 – Section 6.2 - ANSI/TIA-603-E-2016 – Section 2.2.12

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-E-2016 Clause 2.2.17.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW $\geq 3 \times$ RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $> 2 \times$ span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_{d(dBm)} = P_{g(dBm)} - \text{cable loss}_{(dB)} + \text{antenna gain}_{(dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.

These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference

between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA-603-E-2016.


Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $> 2 \times$ span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser
if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit)
and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets,
and channel bandwidth configurations shown in the test data

3.4 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup


Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW $\geq$ 3 MHz
3. Detector = RMS
4. Trace Mode = trace average
5. Sweep time = auto
6. Number of points in sweep $\geq 2 * \text{Span} / \text{RBW}$

3.6 BAND EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1% of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize


Test Notes

According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of The authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

All measurements were done at 2 channels(low and high operational frequency range.)

The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.

2. Primary Supply Voltage:

.- Unless otherwise specified, vary primary supply voltage from 85% to 115% of the nominal value for other than hand carried battery equipment.

.- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.8 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
- The worst case is reported with the EUT positioning, modulations, and paging service configurations shown in the test data.
- Of models SM-T727U and SM-T727P, we tested on SM-T727U model. And SM-T727U result is reported.
- This report covers the models SM-T727U and SM-T727P.
These models are identical in hardware and the only difference is that the model SM-T727P does not support operations in all frequency bands and the some bands are disabled by software.
- SM-T727U with Stand alone, Keyboard, Ear-jack and Charging pad were tested and the worst case results are reported.
(Worst case : Stand alone)
- LTE Band 12 (698 – 716 MHz, 5/10MHzbandwidth) overlaps the entire frequency range of LTE Band 17 (704 - 716 MHz) and they have the same Tune-up power.
Therefore, test data provided in this report covers Band 17 as well as Band 12.

[Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Radiated Power	QPSK, 16QAM, 64QAM	1	0	Y
Radiated Spurious and Harmonic Emissions	QPSK	1	0	Y

3.9 WORST CASE(CONDUCTED TEST)

- Worst case : Of all modulation, We have tested modulation of the high Conducted Output Power.

Conducted Output Power value can be confirmed on the SAR report.

- Of models SM-T727U and SM-T727P, we tested on SM-T727U model. And SM-T727U result is reported.

- This report covers the models SM-T727U and SM-T727P.

These models are identical in hardware and the only difference is that the model SM-T727P does not support operations in all frequency bands and the some bands are disabled by software.

- LTE Band 12 (698 – 716 MHz, 5/10MHzbandwidth) overlaps the entire frequency range of LTE Band 17 (704 - 716 MHz) and they have the same Tune-up power.

Therefore, test data provided in this report covers Band 17 as well as Band 12.

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth	QPSK, 16QAM, 64QAM	1.4, 3, 5, 10	Mid	Full RB	0
Band Edge	* QPSK	1.4	Low	1	0
			High	1	5
		3	Low	1	0
			High	1	14
		5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	49
		1.4, 3, 5, 10	Low, High	Full RB	0
			Low, Mid, High	1	0

4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Date	Calibration Interval	Calibration Due
REOHDE & SCHWARZ	SCU 18 / AMPLIFIER	10094	04/16/2019	Annual	04/16/2020
Wainwright	WHK1.2/15G-10EF/H.P.F	4	04/02/2019	Annual	04/02/2020
Wainwright	WHK3.3/18G-10EF/H.P.F	2	04/02/2019	Annual	04/02/2020
Hewlett Packard	11667B / Power Splitter(DC~26.5 GHz)	11275	05/03/2019	Annual	05/03/2020
Agilent	E3632A/DC Power Supply	KR94907824	02/21/2019	Annual	02/21/2020
Schwarzbeck	UHAP/ Dipole Antenna	557	03/29/2019	Biennial	03/29/2021
Schwarzbeck	UHAP/ Dipole Antenna	558	03/29/2019	Biennial	03/29/2021
ESPEC	SU-642 / Chamber	93000718	08/07/2018	Annual	08/07/2019
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	147	09/14/2018	Annual	09/14/2019
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	9120D-1298	10/04/2018	Annual	10/04/2019
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170342	04/29/2019	Biennial	04/29/2021
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170124	01/28/2019	Biennial	01/28/2021
Agilent	N9020A/Signal Analyzer(10Hz~26.5GHz)	MY51110063	05/08/2019	Annual	05/08/2020
Hewlett Packard	8493C/ATTENUATOR(20dB)	17280	06/04/2019	Annual	06/04/2020
REOHDE & SCHWARZ	FSV40/Spectrum Analyzer(10Hz~40GHz)	100931	10/22/2018	Annual	10/22/2019
Agilent	8960 (E5515C)/ Base Station	MY48360800	09/27/2018	Annual	09/27/2019
Schwarzbeck	FMZB1513/ Loop Antenna(9kHz~30MHz)	1513-175	08/23/2018	Biennial	08/23/2020
Schwarzbeck	VULB9160/ Bilog Antenna	9160-3368	08/09/2018	Biennial	08/09/2020
Schwarzbeck	VULB9160/ Hybrid Antenna	760	03/22/2019	Biennial	03/22/2021
Anritsu Corp.	MT8821C/Wideband Radio Communication Tester	6201502997	08/13/2018	Annual	08/13/2019
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6201026545	01/30/2019	Annual	01/30/2020
REOHDE & SCHWARZ	SMB100A/ SIGNAL GENERATOR (100kHz~40GHz)	177633	07/19/2018	Annual	07/19/2019
REOHDE & SCHWARZ	ESU40 / EMI TEST RECEIVER	100524	07/27/2018	Annual	07/27/2019
HCT CO., LTD.,	FCC LTE Mobile Conducted RF Automation Test Software	-	-	-	-

Note:

- Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ($\pm$ dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.05

6. SUMMARY OF TEST RESULTS

6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§ 2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§ 2.1051, § 27.53(g)	$< 43 + 10\log_{10} (P[\text{Watts}])$ at Band Edge and for all out-of-band emissions	PASS
Conducted Output Power	§ 2.1046	N/A	<u>See Note1</u>
Frequency stability / variation of ambient temperature	§ 2.1055, § 27.54	Emission must remain in band	PASS

Note:

1. See SAR Report
2. The same samples were used for SAR and EMC

6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Effective Radiated Power	§ 27.50(c)(10)	< 3 Watts max. ERP	PASS
Radiated Spurious and Harmonic Emissions	§ 2.1053, § 27.53(g)	$< 43 + 10\log_{10} (P[\text{Watts}])$ for all out-of band emissions	PASS

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

$$\text{ERP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level(dBm)	Substitute Level(dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

$$\text{EIRP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW

GSM BW = 249 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W

GSM BW = 249 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W

WCDMA BW = 4.17 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D

LTE BW = 4.48 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

16QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

64QAM Modulation

Emission Designator = 4M48W7D

LTE BW = 4.48 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

8. TEST DATA

8.1 EFFECTIVE RADIATED POWER

Freq (MHz)	Mod (Bandwidth)	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
								W	W	dBm
699.7	LTE B12 (1.4 MHz)	QPSK	-30.88	26.47	-10.16	0.78	V	< 3.00	0.036	15.53
		16-QAM	-31.58	25.77	-10.16	0.78	V		0.030	14.83
		64-QAM	-32.64	24.71	-10.16	0.78	V		0.024	13.77
707.5		QPSK	-31.94	25.35	-10.17	0.78	V		0.028	14.40
		16-QAM	-32.73	24.56	-10.17	0.78	V		0.023	13.61
		64-QAM	-33.70	23.59	-10.17	0.78	V		0.018	12.64
715.3		QPSK	-31.78	25.43	-10.18	0.78	V		0.028	14.47
		16-QAM	-32.50	24.71	-10.18	0.78	V		0.024	13.75
		64-QAM	-33.48	23.73	-10.18	0.78	V		0.019	12.77

Freq (MHz)	Mod (Bandwidth)	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
								W	W	dBm
700.5	LTE B12 (3 MHz)	QPSK	-30.79	26.58	-10.16	0.78	V	< 3.00	0.037	15.64
		16-QAM	-31.52	25.85	-10.16	0.78	V		0.031	14.91
		64-QAM	-32.58	24.79	-10.16	0.78	V		0.024	13.85
707.5		QPSK	-32.18	25.11	-10.17	0.78	V		0.026	14.16
		16-QAM	-32.94	24.35	-10.17	0.78	V		0.022	13.40
		64-QAM	-33.95	23.34	-10.17	0.78	V		0.017	12.39
714.5		QPSK	-31.58	25.61	-10.18	0.78	V		0.029	14.65
		16-QAM	-32.26	24.93	-10.18	0.78	V		0.025	13.97
		64-QAM	-33.31	23.88	-10.18	0.78	V		0.020	12.92

Freq (MHz)	Mod (Bandwidth)	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
								W	W	dBm
701.5	LTE B12/17 (5 MHz)	QPSK	-30.80	26.60	-10.16	0.78	V	< 3.00	0.037	15.66
		16-QAM	-31.51	25.89	-10.16	0.78	V		0.031	14.95
		64-QAM	-32.57	24.83	-10.16	0.78	V		0.024	13.89
707.5		QPSK	-32.27	25.02	-10.17	0.78	V		0.026	14.07
		16-QAM	-32.99	24.30	-10.17	0.78	V		0.022	13.35
		64-QAM	-33.94	23.35	-10.17	0.78	V		0.017	12.40
713.5		QPSK	-31.52	25.66	-10.18	0.78	V		0.030	14.70
		16-QAM	-32.26	24.92	-10.18	0.78	V		0.025	13.96
		64-QAM	-33.33	23.85	-10.18	0.78	V		0.019	12.89

Freq (MHz)	Mod (Bandwidth)	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBd)	C.L	Pol	Limit	ERP	
								W	W	dBm
704.0	LTE B12/17 (10 MHz)	QPSK	-30.87	26.53	-10.16	0.78	V	< 3.00	0.036	15.59
		16-QAM	-31.54	25.86	-10.16	0.78	V		0.031	14.92
		64-QAM	-32.64	24.76	-10.16	0.78	V		0.024	13.82
707.5		QPSK	-31.39	25.90	-10.17	0.78	V		0.031	14.95
		16-QAM	-32.09	25.20	-10.17	0.78	V		0.027	14.25
		64-QAM	-33.04	24.25	-10.17	0.78	V		0.021	13.30
711.0		QPSK	-32.15	25.07	-10.18	0.78	V		0.026	14.11
		16-QAM	-32.91	24.31	-10.18	0.78	V		0.022	13.35
		64-QAM	-33.94	23.28	-10.18	0.78	V		0.017	12.32

8.3 RADIATED SPURIOUS EMISSIONS

- ▣ OPERATING FREQUENCY: 699.7 MHz
- ▣ MEASURED OUTPUT POWER: 15.53 dBm = 0.036 W
- ▣ MODE: LTE B12
- ▣ MODULATION SIGNAL: 1.4 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ LIMIT: $43 + 10 \log_{10}(W) =$ 28.53 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBd)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
23017 (699.7)	1,399.40	-50.57	5.32	-57.13	1.16	H	-55.12	70.66
	2,099.10	-55.56	7.68	-62.05	1.44	H	-57.96	73.50
	2,798.80	-54.57	9.00	-59.65	1.72	H	-54.52	70.05
23095 (707.5)	1,415.00	-51.00	5.41	-57.42	1.17	H	-55.33	70.86
	2,122.50	-53.68	7.58	-59.59	1.46	H	-55.62	71.15
	2,830.00	-51.71	9.08	-56.92	1.72	V	-51.71	67.24
23173 (715.3)	1,430.60	-54.66	5.55	-61.55	1.17	H	-59.32	74.85
	2,145.90	-53.93	7.32	-59.19	1.47	H	-55.49	71.03
	2,861.20	-46.04	9.16	-51.03	1.74	H	-45.76	61.29
	3,576.50	-52.55	10.18	-57.47	1.95	H	-51.39	66.92
	4,291.80	-50.72	10.75	-54.33	2.25	H	-47.98	63.51

- ▣ OPERATING FREQUENCY: 700.5 MHz
- ▣ MEASURED OUTPUT POWER: 15.64 dBm = 0.037 W
- ▣ MODE: LTE B12
- ▣ MODULATION SIGNAL: 3 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ LIMIT: $43 + 10 \log_{10} (W) =$ 28.64 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBd)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
23025 (700.5)	1,401.00	-50.51	5.32	-57.07	1.16	H	-55.06	70.70
	2,101.50	-53.96	7.68	-60.45	1.44	H	-56.36	72.01
	2,802.00	-54.96	9.00	-60.04	1.72	H	-54.91	70.55
23095 (707.5)	1,415.00	-54.24	5.41	-60.66	1.17	H	-58.57	74.21
	2,122.50	-54.38	7.58	-60.29	1.46	H	-56.32	71.96
	2,830.00	-50.74	9.08	-55.95	1.72	H	-50.74	66.38
	4,245.00	-51.54	10.80	-55.35	2.20	H	-48.90	64.54
23165 (714.5)	1,429.00	-52.62	5.55	-59.51	1.17	H	-57.28	72.92
	2,143.50	-54.95	7.32	-60.21	1.47	H	-56.51	72.16
	2,858.00	-45.43	9.16	-50.42	1.74	H	-45.15	60.79
	3,572.50	-53.20	10.17	-58.08	1.93	H	-51.99	67.63
	4,287.00	-51.19	10.75	-54.80	2.25	H	-48.45	64.09

- ▣ OPERATING FREQUENCY: 701.5 MHz
- ▣ MEASURED OUTPUT POWER: 15.66 dBm = 0.037 W
- ▣ MODE: LTE B12/17
- ▣ MODULATION SIGNAL: 5 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ LIMIT: $43 + 10 \log_{10} (W) =$ 28.66 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBd)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
23035 (701.5)	1,403.00	-50.63	5.32	-57.19	1.16	H	-55.18	70.84
	2,104.50	-54.34	7.66	-60.57	1.45	H	-56.51	72.17
	2,806.00	-58.14	9.01	-63.22	1.70	H	-58.06	73.72
23095 (707.5)	1,415.00	-55.27	5.41	-61.69	1.17	H	-59.60	75.26
	2,122.50	-53.07	7.58	-58.98	1.46	H	-55.01	70.67
	2,830.00	-50.69	9.08	-55.90	1.72	H	-50.69	66.35
	4,245.00	-52.11	10.80	-55.92	2.20	H	-49.47	65.13
23155 (713.5)	1,427.00	-48.02	5.55	-54.91	1.17	H	-52.68	68.34
	2,140.50	-56.15	7.37	-61.40	1.47	H	-57.65	73.31
	2,854.00	-51.52	9.16	-56.59	1.73	H	-51.31	66.97

- ▣ OPERATING FREQUENCY: 704.0 MHz
- ▣ MEASURED OUTPUT POWER: 15.59 dBm = 0.036 W
- ▣ MODE: LTE B12/17
- ▣ MODULATION SIGNAL: 10 MHz QPSK
- ▣ DISTANCE: 3 meters
- ▣ LIMIT: $43 + 10 \log_{10} (W) =$ 28.59 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBd)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	dBc
23060 (704.0)	1,408.00	-51.45	5.38	-57.78	1.17	H	-55.72	71.32
	2,112.00	-50.83	7.63	-56.80	1.45	H	-52.77	68.37
	2,816.00	-53.03	9.03	-58.23	1.70	H	-53.05	68.64
23095 (707.5)	1,415.00	-58.21	5.41	-64.63	1.17	H	-62.54	78.13
	2,122.50	-54.62	7.58	-60.53	1.46	H	-56.56	72.15
	2,830.00	-48.30	9.08	-53.51	1.72	H	-48.30	63.89
	4,245.00	-48.28	10.80	-52.09	2.20	H	-45.64	61.23
23130 (711.0)	1,422.00	-52.29	5.44	-58.79	1.17	H	-56.67	72.26
	2,133.00	-53.30	7.47	-59.05	1.47	H	-55.20	70.79
	2,844.00	-51.22	9.13	-56.36	1.71	H	-51.09	66.68
	4,266.00	-52.24	10.79	-55.99	2.20	H	-49.55	65.14

8.3 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
12	1.4 MHz	707.5	QPSK	6	0	1.0923
			16-QAM			1.0896
			64-QAM			1.0913
	3 MHz		QPSK	15		2.7089
			16-QAM			2.7007
			64-QAM			2.7034
12(17)	5 MHz		QPSK	25		4.5152
			16-QAM			4.4982
			64-QAM			4.5265
	10 MHz		QPSK	50		8.9890
			16-QAM			8.9680
			64-QAM			8.9748

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 43 ~ 54.

8.4 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
12	1.4	699.7	3.7099	27.976	-67.233	-39.257	-13.00
		707.5	3.7074	27.976	-67.416	-39.440	
		715.3	3.1740	27.976	-67.124	-39.148	
	3	700.5	3.7079	27.976	-67.135	-39.159	
		707.5	3.6820	27.976	-67.501	-39.525	
		714.5	3.6950	27.976	-67.366	-39.390	
12(17)	5	701.5	3.7079	27.976	-67.360	-39.384	
		707.5	3.7164	27.976	-66.973	-38.997	
		713.5	3.7124	27.976	-66.972	-38.996	
	10	704.0	3.6945	27.976	-67.079	-39.103	
		707.5	3.7124	27.976	-67.512	-39.536	
		711.0	3.1561	27.976	-67.387	-39.411	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 80 ~ 91.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor(dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20	30.131


8.5 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 55 ~ 79.

8.6 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


- MODE: LTE B12
- OPERATING FREQUENCY: 699,700,000 Hz
- CHANNEL: 23017 (1.4 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	699 699 986	0.0	0.000 000	0.000
100%		-30	699 699 997	10.4	0.000 001	0.015
100%		-20	699 699 996	10.1	0.000 001	0.014
100%		-10	699 699 977	-9.2	-0.000 001	-0.013
100%		0	699 699 975	-11.0	-0.000 002	-0.016
100%		+10	699 699 973	-12.7	-0.000 002	-0.018
100%		+30	699 699 974	-11.8	-0.000 002	-0.017
100%		+40	699 699 980	-6.5	-0.000 001	-0.009
100%		+50	699 699 976	-9.7	-0.000 001	-0.014
Batt. Endpoint	3.400	+20	699 699 970	-16.3	-0.000 002	-0.023




- MODE: LTE B12
- OPERATING FREQUENCY: 700,500,000 Hz
- CHANNEL: 23025 (3 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	700 500 020	0.0	0.000 000	0.000
100%		-30	700 500 035	15.1	0.000 002	0.022
100%		-20	700 500 034	13.7	0.000 002	0.020
100%		-10	700 500 006	-13.8	-0.000 002	-0.020
100%		0	700 499 999	-21.1	-0.000 003	-0.030
100%		+10	700 500 033	13.2	0.000 002	0.019
100%		+30	700 500 034	14.2	0.000 002	0.020
100%		+40	700 500 030	10.2	0.000 001	0.015
100%		+50	700 500 033	13.2	0.000 002	0.019
Batt. Endpoint	3.400	+20	700 500 001	-19.2	-0.000 003	-0.027




- ▣ MODE: LTE B12/17
- ▣ OPERATING FREQUENCY: 701,500,000 Hz
- ▣ CHANNEL: 23035 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	701 499 980	0.0	0.000 000	0.000
100%		-30	701 499 957	-23.6	-0.000 003	-0.034
100%		-20	701 499 965	-15.2	-0.000 002	-0.022
100%		-10	701 499 967	-12.7	-0.000 002	-0.018
100%		0	701 499 961	-19.6	-0.000 003	-0.028
100%		+10	701 499 960	-20.0	-0.000 003	-0.029
100%		+30	701 499 963	-17.2	-0.000 002	-0.025
100%		+40	701 499 963	-17.6	-0.000 003	-0.025
100%		+50	701 499 957	-22.8	-0.000 003	-0.033
Batt. Endpoint	3.400	+20	701 499 961	-18.8	-0.000 003	-0.027




- ▣ MODE: LTE B12/17
- ▣ OPERATING FREQUENCY: 704,000,000 Hz
- ▣ CHANNEL: 23060 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	703 999 987	0.0	0.000 000	0.000
100%		-30	703 999 997	10.0	0.000 001	0.014
100%		-20	704 000 001	13.9	0.000 002	0.020
100%		-10	703 999 998	11.5	0.000 002	0.016
100%		0	703 999 973	-14.0	-0.000 002	-0.020
100%		+10	703 999 973	-13.7	-0.000 002	-0.019
100%		+30	703 999 969	-18.3	-0.000 003	-0.026
100%		+40	704 000 004	16.8	0.000 002	0.024
100%		+50	703 999 999	11.7	0.000 002	0.017
Batt. Endpoint	3.400	+20	703 999 993	5.8	0.000 001	0.008




- ▣ MODE: LTE B12
- ▣ OPERATING FREQUENCY: 707,500,000 Hz
- ▣ CHANNEL: 23095 (1.4 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	707 500 014	0.0	0.000 000	0.000
100%		-30	707 500 032	17.8	0.000 003	0.025
100%		-20	707 500 026	11.9	0.000 002	0.017
100%		-10	707 499 999	-14.7	-0.000 002	-0.021
100%		0	707 499 997	-16.8	-0.000 002	-0.024
100%		+10	707 500 000	-14.3	-0.000 002	-0.020
100%		+30	707 500 004	-10.2	-0.000 001	-0.014
100%		+40	707 500 004	-10.4	-0.000 001	-0.015
100%		+50	707 499 993	-21.1	-0.000 003	-0.030
Batt. Endpoint	3.400	+20	707 500 029	14.5	0.000 002	0.020




- ▣ MODE: LTE B12
- ▣ OPERATING FREQUENCY: 707,500,000 Hz
- ▣ CHANNEL: 23095 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	707 500 008	0.0	0.000 000	0.000
100%		-30	707 499 995	-12.6	-0.000 002	-0.018
100%		-20	707 499 996	-12.1	-0.000 002	-0.017
100%		-10	707 499 991	-17.0	-0.000 002	-0.024
100%		0	707 499 994	-14.2	-0.000 002	-0.020
100%		+10	707 499 993	-14.8	-0.000 002	-0.021
100%		+30	707 500 022	14.5	0.000 002	0.020
100%		+40	707 499 986	-22.3	-0.000 003	-0.032
100%		+50	707 500 001	-6.8	-0.000 001	-0.010
Batt. Endpoint	3.400	+20	707 499 988	-19.5	-0.000 003	-0.028




- ▣ MODE: LTE B12/17
- ▣ OPERATING FREQUENCY: 707,500,000 Hz
- ▣ CHANNEL: 23095 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	707 499 980	0.0	0.000 000	0.000
100%		-30	707 499 960	-20.0	-0.000 003	-0.028
100%		-20	707 499 998	18.2	0.000 003	0.026
100%		-10	707 499 990	10.2	0.000 001	0.014
100%		0	707 499 993	13.4	0.000 002	0.019
100%		+10	707 499 992	12.2	0.000 002	0.017
100%		+30	707 499 963	-17.1	-0.000 002	-0.024
100%		+40	707 499 990	10.6	0.000 001	0.015
100%		+50	707 499 991	10.9	0.000 002	0.015
Batt. Endpoint	3.400	+20	707 499 994	14.1	0.000 002	0.020




- ▣ MODE: LTE B12/17
- ▣ OPERATING FREQUENCY: 707,500,000 Hz
- ▣ CHANNEL: 23095 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	707 499 988	0.0	0.000 000	0.000
100%		-30	707 499 976	-12.2	-0.000 002	-0.017
100%		-20	707 499 973	-14.7	-0.000 002	-0.021
100%		-10	707 499 976	-12.5	-0.000 002	-0.018
100%		0	707 499 972	-15.7	-0.000 002	-0.022
100%		+10	707 499 972	-16.3	-0.000 002	-0.023
100%		+30	707 499 974	-14.0	-0.000 002	-0.020
100%		+40	707 499 971	-16.7	-0.000 002	-0.024
100%		+50	707 499 972	-16.2	-0.000 002	-0.023
Batt. Endpoint	3.400	+20	707 499 999	10.5	0.000 001	0.015




- ▣ MODE: LTE B12
- ▣ OPERATING FREQUENCY: 715,300,000 Hz
- ▣ CHANNEL: 23173 (1.4 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	715 299 989	0.0	0.000 000	0.000
100%		-30	715 299 970	-18.2	-0.000 003	-0.025
100%		-20	715 299 969	-19.3	-0.000 003	-0.027
100%		-10	715 299 971	-17.9	-0.000 003	-0.025
100%		0	715 299 970	-18.5	-0.000 003	-0.026
100%		+10	715 299 971	-18.1	-0.000 003	-0.025
100%		+30	715 299 972	-17.0	-0.000 002	-0.024
100%		+40	715 299 970	-18.6	-0.000 003	-0.026
100%		+50	715 299 972	-16.7	-0.000 002	-0.023
Batt. Endpoint	3.400	+20	715 299 979	-9.3	-0.000 001	-0.013




- ▣ MODE: LTE B12
- ▣ OPERATING FREQUENCY: 714,500,000 Hz
- ▣ CHANNEL: 23165 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	714 500 020	0.0	0.000 000	0.000
100%		-30	714 500 039	18.9	0.000 003	0.026
100%		-20	714 500 042	21.8	0.000 003	0.031
100%		-10	714 500 042	22.0	0.000 003	0.031
100%		0	714 500 045	24.7	0.000 003	0.035
100%		+10	714 500 041	21.1	0.000 003	0.030
100%		+30	714 500 044	23.5	0.000 003	0.033
100%		+40	714 500 030	9.7	0.000 001	0.014
100%		+50	714 500 045	24.9	0.000 003	0.035
Batt. Endpoint	3.400	+20	714 500 043	22.7	0.000 003	0.032




- ▣ MODE: LTE B12/17
- ▣ OPERATING FREQUENCY: 713,500,000 Hz
- ▣ CHANNEL: 23155 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	713 499 985	0.0	0.000 000	0.000
100%		-30	713 499 974	-10.8	-0.000 002	-0.015
100%		-20	713 499 997	11.8	0.000 002	0.017
100%		-10	713 499 980	-5.3	-0.000 001	-0.007
100%		0	713 499 970	-14.9	-0.000 002	-0.021
100%		+10	713 499 971	-13.7	-0.000 002	-0.019
100%		+30	713 499 973	-11.6	-0.000 002	-0.016
100%		+40	713 499 994	8.5	0.000 001	0.012
100%		+50	713 499 996	10.6	0.000 001	0.015
Batt. Endpoint	3.400	+20	713 499 966	-18.7	-0.000 003	-0.026




- ▣ MODE: LTE B12/17
- ▣ OPERATING FREQUENCY: 711,000,000 Hz
- ▣ CHANNEL: 23130 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.85 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.850	+20(Ref)	711 000 015	0.0	0.000 000	0.000
100%		-30	711 000 034	19.1	0.000 003	0.027
100%		-20	710 999 991	-24.3	-0.000 003	-0.034
100%		-10	710 999 999	-16.2	-0.000 002	-0.023
100%		0	710 999 995	-20.3	-0.000 003	-0.029
100%		+10	710 999 997	-18.5	-0.000 003	-0.026
100%		+30	710 999 993	-21.7	-0.000 003	-0.031
100%		+40	711 000 035	19.7	0.000 003	0.028
100%		+50	711 000 023	7.7	0.000 001	0.011
Batt. Endpoint	3.400	+20	711 000 032	17.2	0.000 002	0.024




9. TEST PLOTS


BAND 12. Occupied Bandwidth Plot (1.4M BW Ch.23095 QPSK_RB6_0)




BAND 12. Occupied Bandwidth Plot (1.4M BW Ch.23095 16QAM_RB6_0)




BAND 12. Occupied Bandwidth Plot (1.4M BW Ch.23095 64QAM_RB6_0)




BAND 12. Occupied Bandwidth Plot (3M BW Ch.23095 QPSK_RB15_0)




BAND 12. Occupied Bandwidth Plot (3M BW Ch.23095 16QAM_RB15_0)




BAND 12. Occupied Bandwidth Plot (3M BW Ch.23095 64QAM_RB15_0)




BAND 12/17. Occupied Bandwidth Plot (5M BW Ch.23095 QPSK_RB25_0)




BAND 12/17. Occupied Bandwidth Plot (5M BW Ch.23095 16QAM_RB25_0)



BAND 12/17. Occupied Bandwidth Plot (5M BW Ch.23095 64QAM_RB25_0)



BAND 12/17. Occupied Bandwidth Plot (10M BW Ch.23095 QPSK_RB50_0)



BAND 12/17. Occupied Bandwidth Plot (10M BW Ch.23095 16QAM_RB50_0)

