CERTIFICATION TEST REPORT

Report Number. : 4789867746-E5V2

Applicant : SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA

Model : SM-T735

FCC ID : A3LSMT735

EUT Description : GSM/WCDMA/LTE Tablet + BT/BLE, DTS/UNII a/b/g/n/ac

Test Standard(s) : FCC 47 CFR PART 15 SUBPART C

Date Of Issue:
2021-04-30

Prepared by:
UL Korea, Ltd.
26th floor, 152, Teheran-ro, Gangnam-gu Seoul, 06236, Korea

Suwon Test Site: UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433

IAS
ACCREDITED
TL-637

Revision History

Rev.	Issue Date	Revisions	Revised By
V1	2021-04-22	Initial issue	Hyunsik Yun
V2	2021-04-30	Updated to address TCB's question	Hyunsik Yun

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS 5
1.1. INTRODUCTION OF TEST DATA REUSE 6
1.2. DIFFERENCE 6
1.3. SPOT CHECK VERIFICATION DATA 6
1.4. REFERENCE DETAIL 7
2. TEST METHODOLOGY 8
3. FACILITIES AND ACCREDITATION 8
4. DECISION RULES AND MEASUREMENT UNCERTAINTY 9
4.1. METROLOGICAL TRACEABILITY 9
4.2. SAMPLE CALCULATION 9
4.3. DECISION RULES 9
4.4. MEASUREMENT UNCERTAINTY 9
5. EQUIPMENT UNDER TEST 10
5.1. EUT DESCRIPTION 10
5.2. MAXIMUM OUTPUT POWER 10
5.3. DESCRIPTION OF AVAILABLE ANTENNAS 10
5.4. WORST-CASE CONFIGURATION AND MODE 11
5.5. DESCRIPTION OF TEST SETUP 12
6. TEST AND MEASUREMENT EQUIPMENT 14
7. TEST RESULTS SUMMARY 15
8. MEASUREMENT METHODS 16
9. ANTENNA PORT TEST RESULTS 17
9.1. ON TIME AND DUTY CYCLE 17
9.2. 20 dB AND 99% BANDWIDTH 18
9.2.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION 18
9.2.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION 18
9.3. HOPPING FREQUENCY SEPARATION 21
9.3.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION 22
9.3.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION 22
9.4. NUMBER OF HOPPING CHANNELS 23
9.4.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION 24
9.4.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION 25
9.5. AVERAGE TIME OF OCCUPANCY 26
9.5.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION 27

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.5.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION.....29

9.6. OUTPUT POWER.....31
9.6.1. BASIC DATA RATE GFSK MODULATION.....31
9.6.2. ENHANCED DATA RATE Pi/4-DPSK MODULATION 31
9.6.3. ENHANCED DATA RATE 8PSK MODULATION 31
9.6.4. OUTPUT POWER PLOTS.....32

9.7. AVERAGE POWER 34
9.7.1. BASIC DATA RATE GFSK MODULATION.....34
9.7.2. ENHANCED DATA RATE PI/4-DQPSK MODULATION 34
9.7.3. ENHANCED DATA RATE 8PSK MODULATION 34

9.8. CONDUCTED SPURIOUS EMISSIONS 35
9.8.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION 36
9.8.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION.....38

10. RADIATED TEST RESULTS 40

10.1. TRANSMITTER ABOVE 1 GHz 42
10.1.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION 42
10.1.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION 49

10.2. WORST CASE BELOW 1 GHZ.....56

11. AC POWER LINE CONDUCTED EMISSIONS 57

11.1.1. AC Power Line.....58

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.

EUT DESCRIPTION: GSM/WCDMA/LTE Tablet + BT/BLE, DTS/UNII a/b/g/n/ac

MODEL: SM-T735

SERIAL NUMBER: R32R2009HKX (Conducted, Original);
R32R2009QPH, R32R2009K5M, R32R300FS7B (Radiated, Original);
R32R200DYSJ (Radiated, Spot-check);

DATE TESTED: 2021-03-16 ~ 2021-04-14(Original);
2021-04-13 ~ 2021-04-22(Spot-check);

APPLICABLE STANDARDS	
STANDARD	**TEST RESULTS**
CFR 47 Part 15 Subpart C	Complies

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:

Junwhan Lee
Suwon Lab Engineer
UL Korea, Ltd.

Tested By:

Hyunsik Yun
Suwon Lab Engineer
UL Korea, Ltd.

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

1.1. INTRODUCTION OF TEST DATA REUSE

This report referenced from the FCC ID: A3LSMT736B BT(FCC CFR 47 Part 15C).
And the applicant takes full responsibility that the test data as referenced in this report represent compliance for this FCC ID.

1.2. DIFFERENCE

The FCC ID: A3LSMT735 shares the same enclosure and circuit board as FCC ID: A3LSMT736B. The BT antennas and surrounding circuitry and layout are identical between these two units for re-used bands.

In SM-T735 model, 5G NR parts are removed from the PCB.

After confirming through preliminary radiated emissions that the performance of the FCC ID: A3LSMT736B remains representative of FCC ID: A3LSMT735. The test data of FCC ID: A3LSMT736B being submitted for this application to cover BT features.

1.3. SPOT CHECK VERIFICATION DATA

Band	Test Item	Mode	Frequency	Test Limit	Original model	Spot check model	Deviation	Remark
					SM-T736B	SM-T735		
					FCC ID : A3LSMT736B	FCC ID : A3LSMT735		
DSS BT	Band Edge	GFSK 2480	2480 MHz	54 dBuV/m	42.69 dBuV/m	41.69 dBuV/m	-1.00 dB	
	RSE	GFSK 2480	4960 MHz	74 dBuV/m	55.97 dBuV/m	46.66 dBuV/m	-9.31 dB	

Comparison of two models, upper deviation is within 3dB range and all test results are under FCC technical limits.

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

1.4. REFERENCE DETAIL

Reference application that contains the re-used reference data.

Equipment Class	Reference FCC ID	Application Type	Reference Test report	Reuse (EMC/RFX)	Report Title / Section
PCB	A3LSMT736B	Original Grant	4789841420-E2	EMC	FCC Report WWAN/ All sections
DTS	A3LSMT736B	Original Grant	4789841420-E3	EMC	Report DTS[b,g,n] WLAN/ All sections
			4789841420-E4	EMC	FCC Report BLE/ All sections
DSS	A3LSMT736B	Original Grant	4789841420-E5	EMC	FCC Report BT/ All sections
NII	A3LSMT736B	Original Grant	4789841420-E6	EMC	FCC Report UNII[a,n,ac] WLAN/ All sections

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with following methods.

1. FCC CFR 47 Part 2.
2. FCC CFR 47 Part 15.
3. KDB 558074 D01 15.247 Meas Guidance v05r02.
4. ANSI C63.10-2013.
5. KDB 484596 D01 Referencing Test Data v01

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro
☒ Chamber 1
☒ Chamber 2
☐ Chamber 3

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at https://www.iasonline.org/wp-content/uploads/2017/05/TL-637-cert-New.pdf.

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

4. DECISION RULES AND MEASUREMENT UNCERTAINTY

4.1. METROLOGICAL TRACEABILITY

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB)

36.5 dBuV + 18.7 dB/m + 0.6 dB – 26.9 dB = 28.9 dBuV/m

4.3. DECISION RULES

Decision rule for statement(s) of conformity is based on Procedure 1, Clause 4.4.2 in IEC Guide 115:2007.

4.4. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.01 dB
Radiated Disturbance, 30 MHz to 1 GHz	4.26 dB
Radiated Disturbance, 1 GHz to 18 GHz	5.90 dB
Radiated Disturbance, 18 GHz to 40 GHz	5.49 dB

Uncertainty figures are valid to a confidence level of 95%.

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

5. EQUIPMENT UNDER TEST

5.1. EUT DESCRIPTION

The EUT is a GSM/WCDMA/LTE Tablet + BT/BLE, DTS/UNII a/b/g/n/ac.
This test report addresses the BT(DSS) operational mode.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range [MHz]	Mode	Power Mode	Output Power [dBm]	Output Power [mW]
2 402 ~ 2 480	Basic GFSK	Average	17.261	53.22
		Peak	17.696	58.83
	Enhanced Pi/4-DPSK	Average	15.450	35.08
		Peak	17.893	61.56
	Enhanced 8PSK	Average	15.473	35.26
		Peak	18.517	71.07

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

The internal antenna was Permanently attached.
Therefore this E.U.T Complies with the requirement of §15.203.

The radio utilizes an internal antennas, with maximum gain of -1.71 dBi.

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission below 1GHz and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Radiated emission above 1GHz was performed with the EUT set to transmit low/mid/high channels.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

Foldable condition: Stand Alone



Note: GFSK, Pi/4-DQPSK, 8PSK average Power are all investigated, The GFSK & 8PSK Power are the worst case. Testing is based on this mode to showing compliance.

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	**Manufacturer**	**Model**	**Serial Number**	**FCC ID**
Charger	SAMSUNG	EP-TA200	R37R1XS0P35DK3	N/A
Data Cable	SAMSUNG	EP-DT725BBE	N/A	N/A

I/O CABLE

I/O Cable List						
Cable No.	**Port**	**# of identical ports**	**Connector Type**	**Cable Type**	**Cable Length (m)**	**Remarks**
1	DC Power	1	C Type	Shielded	1.0 m	N/A

TEST SETUP

The EUT is continuously communicating to the Bluetooth tester during the tests.
Test software enable BT communications.

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

SETUP DIAGRAM FOR TESTS (CONDUCTED TEST SETUP)



SETUP DIAGRAM FOR TESTS (RADIATED TEST SETUP)



UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	**Manufacturer**	**Model**	**S/N**	**Cal Due**
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	750	08-19-22
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	08-13-22
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	845	08-13-22
Antenna, Horn, 18 GHz	ETS	3115	00167211	07-27-22
Antenna, Horn, 18 GHz	ETS	3115	00161451	08-15-22
Antenna, Horn, 18 GHz	ETS	3117	00168724	07-27-22
Antenna, Horn, 18 GHz	ETS	3117	00168717	08-15-22
Antenna, Horn, 40 GHz	ETS	3116C	00166155	08-04-22
Antenna, Horn, 40 GHz	ETS	3116C	00168645	10-02-21
Preamplifier	ETS	3116C-PA	00168841	08-06-21
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-03-21
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-03-21
Preamplifier, 1000 MHz	Sonoma	310N	370599	08-06-21
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1876511	08-03-21
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	08-03-21
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	2029169	08-04-21
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	08-05-21
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-05-21
Spectrum Analyzer, 43.5 GHz	R&S	FSW43	104089	08-06-21
Average Power Sensor	Agilent / HP	U2000	MY54270007	08-05-21
Bluetooth Tester	TESCOM	TC-3000C	3000C000546	08-05-21
Power Splitter	MINI-CIRCUITS	WA1534	UL001	01-27-22
Attenuator	PASTERNACK	PE7087-10	A001	08-03-21
Attenuator	PASTERNACK	PE7087-10	A008	08-03-21
Attenuator	PASTERNACK	PE7004-10	2	08-04-21
Attenuator	PASTERNACK	PE7087-10	A009	08-03-21
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-03-21
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-03-21
EMI Test Receive, 3 GHz	R&S	ESR3	101832	08-03-21
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	009	08-03-21
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	015	08-03-21
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	020	08-04-21
High Pass Filter 3GHz	Micro-Tronics	HPM17543	010	08-03-21
High Pass Filter 3GHz	Micro-Tronics	HPM17543	015	08-03-21
High Pass Filter 3GHz	Micro-Tronics	HPM17543	020	08-04-21
High Pass Filter 6GHz	Micro-Tronics	HPS17542	009	08-03-21
High Pass Filter 6GHz	Micro-Tronics	HPS17542	016	08-03-21
High Pass Filter 6GHz	Micro-Tronics	HPS17542	021	08-04-21
LISN	R&S	ENV-216	101837	08-06-21
Antenna, Loop, 9kHz-30MHz	R&S	HFH2-Z2	100418	10-02-21

UL Software			
Description	**Manufacturer**	**Model**	**Version**
Radiated software	UL	UL EMC	Ver 9.5
AC Line Conducted software	UL	UL EMC	Ver 9.5

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

7. TEST RESULTS SUMMARY

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result
2.1051, 15.247(d)	Band Edge / Conducted Spurious Emission	-20 dBc	Conducted	PASS
15.247 (b)(1)	TX conducted output power	< 21 dBm		PASS
15.247 (a)(1)	Hopping frequency separation	> two-thirds of the 20 dB bandwidth		PASS
15.247 (a)(1)(iii)	Number of Hopping channels	More than 15 non-overlapping channels		PASS
15.247 (a)(1)(iii)	Avg Time of Occupancy	< 8 dBm		PASS
15.207(a)	AC Power Line conducted emissions	Section 11	Power Line conducted	PASS
15.205, 15.209	Radiated Spurious Emission	< 54dBuV/m(Av)	Radiated	PASS

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

8. MEASUREMENT METHODS

20dB BW : ANSI C63.10, Section 6.9.2

99% BW : ANSI C63.10, Section 6.9.3

HOPPING FREQUENCY SEPARATION : ANSI C63.10, Section 7.8.2

NUMBER OF HOPPING CHANNELS : ANSI C63.10, Section 7.8.3

AVERAGE TIME OF OCCUPANCY : ANSI C63.10, Section 7.8.4

OUTPUT POWER : ANSI C63.10, Section 7.8.5.

Out-of-band EMISSIONS (Conducted) : ANSI C63.10, Section 7.8.6, 7.8.8

Out-of-band EMISSIONS IN NON-RESTRICTED BANDS: ANSI C63.10, Section 6.

Out-of-band EMISSIONS IN RESTRICTED BANDS : ANSI C63.10, Section 6.

AC Power Line Conducted Emission : ANSI C63.10-2013, Section 6.2.

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9. ANTENNA PORT TEST RESULTS

9.1. ON TIME AND DUTY CYCLE

LIMITS

None; for reporting purposes only.

PROCEDURE

ANSI C63.10, Section 11.6 : Zero-Span Spectrum Analyzer Method.

ON TIME AND DUTY CYCLE RESULTS

Mode	On time [msec]	Period [msec]	Duty Cycle [%]	Duty Cycle Correction Factor[dB]	1/T Minimum VBW [kHz]
2 400 ~ 2 483.5 MHz Band					
Bluetooth	2.890	3.749	77.09	1.13	0.35



UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.2. 20 dB AND 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to ≥ 1% of the 20 dB bandwidth. The VBW is set to ≥ RBW. The sweep time is coupled.

RESULTS

9.2.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	20 dB Bandwidth [kHz]	99% Bandwidth [kHz]
0	2 402	782.8	810.6
39	2 441	823.5	811.6
78	2 480	828.3	814.5

9.2.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency [MHz]	20 dB Bandwidth [kHz]	99% Bandwidth [kHz]
0	2 402	1202.5	1136.4
39	2 441	1204.8	1139.6
78	2 480	1205.8	1135.2

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

- BDR

20 dB bandwidth / 0 CHANNEL



99% bandwidth / 0 CHANNEL

20 dB bandwidth / 39 CHANNEL



99% bandwidth / 39 CHANNEL

20 dB bandwidth / 78 CHANNEL



99% bandwidth / 78 CHANNEL

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_15C(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

- EDR

20 dB bandwidth / 0 CHANNEL



99% bandwidth / 0 CHANNEL

20 dB bandwidth / 39 CHANNEL



99% bandwidth / 39 CHANNEL

20 dB bandwidth / 78 CHANNEL



99% bandwidth / 78 CHANNEL

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.3. HOPPING FREQUENCY SEPARATION

LIMITS

FCC §15.247 (a) (1)

RSS-247 (5.1) (b)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hoping channel, whichever is greater.

Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to 300 kHz and the VBW is set to VBW >= RBW. The sweep time is coupled.

RESULTS

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_15C(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.3.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION



HOPPING FREQUENCY SEPARATION PLOT

9.3.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION



HOPPING FREQUENCY SEPARATION PLOT

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.4. NUMBER OF HOPPING CHANNELS

LIMITS

FCC §15.247 (a) (1) (iii)

RSS-247 (5.1) (d)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to a maximum of 1 % of the span. The analyzer is set to Max Hold.

RESULTS

Normal Mode: All Channels Observed

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.4.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION



100 MHz Span



30MHz SPAN, SEGMENT 1 OF 3



30MHz SPAN, SEGMENT 2 OF 3



30MHz SPAN, SEGMENT 3 OF 3

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.4.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION



100 MHz Span



30MHz SPAN, SEGMENT 1 OF 3



30MHz SPAN, SEGMENT 2 OF 3



30MHz SPAN, SEGMENT 3 OF 3

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.5. AVERAGE TIME OF OCCUPANCY

LIMITS

FCC §15.247 (a) (1) (iii)

RSS-247 (5.1) (d)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.

The average time of occupancy in the specified 3.16 second period (79 channels * 0.4 s) is equal to 10 * (# of pulses in 3.16 s) * pulse width.

For AFH mode, the average time of occupancy in the specified 8 second period (20 channels * 0.4 seconds) is equal to 10 * (# of pulses in 0.8 s) * pulse width.

RESULTS

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.5.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION

DH Packet	Pulse Width [msec]	Number of Pulses in 3.16 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK Normal					
DH1	0.386	32	0.123520	0.4	-0.2765
DH3	1.638	16	0.262080	0.4	-0.1379
DH5	2.884	11	0.317240	0.4	-0.0828
DH Packet	**Pulse Width [msec]**	**Number of Pulses in 0.8 seconds**	**Average Time of Occupancy [sec]**	**Limit [sec]**	**Margin [sec]**
GFSK AFH					
DH1	0.386	8	0.030880	0.4	-0.3691
DH3	1.638	4	0.065520	0.4	-0.3345
DH5	2.884	2.75	0.079310	0.4	-0.3207

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.



PULSE WIDTH – DH1

NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH1

PULSE WIDTH – DH3

NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH3



PULSE WIDTH – DH5

NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH5

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_15C(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.5.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION

DH Packet	Pulse Width [msec]	Number of Pulses in 3.16 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
8PSK Normal					
DH1	0.390	31	0.120900	0.4	-0.2791
DH3	1.640	18	0.295200	0.4	-0.1048
DH5	2.884	10	0.288400	0.4	-0.1116
DH Packet	**Pulse Width [msec]**	**Number of Pulses in 0.8 seconds**	**Average Time of Occupancy [sec]**	**Limit [sec]**	**Margin [sec]**
8PSK AFH					
DH1	0.390	7.75	0.030225	0.4	-0.3698
DH3	1.640	4.5	0.073800	0.4	-0.3262
DH5	2.884	2.5	0.072100	0.4	-0.3279

.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_15C(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.



PULSE WIDTH – 3-DH1

NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – 3-DH1



PULSE WIDTH – 3-DH3

NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – 3-DH3



PULSE WIDTH – 3-DH5

NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – 3-DH5

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_15C(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.6. OUTPUT POWER

LIMITS

§15.247 (b) (1)
The maximum antenna gain is less than 6 dBi, therefore the limit is 21 dBm.

TEST PROCEDURE
The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.

RESULTS

9.6.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	Peak Output Power [dBm]	Limit [dBm]	Margin [dB]
Low	2 402	16.464	21.000	-4.536
Mid	2 441	**17.696**	**21.000**	**-3.304**
High	2 480	16.300	21.000	-4.700
Worst		17.696	21.000	-3.304

9.6.2. ENHANCED DATA RATE Pi/4-DPSK MODULATION

Channel	Frequency [MHz]	Peak Output Power [dBm]	Limit [dBm]	Margin [dB]
Low	2 402	16.094	21.000	-4.906
Mid	2 441	**17.893**	**21.000**	**-3.107**
High	2 480	16.871	21.000	-4.129
Worst		17.893	21.000	-3.107

9.6.3. ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency [MHz]	Peak Output Power [dBm]	Limit [dBm]	Margin [dB]
Low	2 402	16.691	21.000	-4.309
Mid	2 441	**18.517**	**21.000**	**-2.483**
High	2 480	17.570	21.000	-3.430
Worst		18.517	21.000	-2.483

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.6.4. OUTPUT POWER PLOTS

PEAK OUTPUT POWER

GFSK	Pi/4-DPSK
	
0 CHANNEL	**0 CHANNEL**
	
39 CHANNEL	**39 CHANNEL**
	
78 CHANNEL	**78 CHANNEL**

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_15C(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

8PSK



0 CHANNEL



39 CHANNEL



78 CHANNEL

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_15C(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.7. AVERAGE POWER

LIMITS

None; for reporting purposes only

TEST PROCEDURE

Measurements perform using a wideband gated RF power meter.
The cable assembly insertion loss was entered as an offset in the power meter to allow for direct reading of power.

RESULTS

9.7.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	AV power [dBm]	AV power [mW]
Low	2 402	15.990	39.719
Middle	2 441	**17.261**	**53.223**
High	2 480	15.855	38.503

9.7.2. ENHANCED DATA RATE PI/4-DQPSK MODULATION

Channel	Frequency [MHz]	AV power [dBm]	AV power [mW]
Low	2 402	13.567	22.735
Middle	2 441	**15.450**	**35.075**
High	2 480	14.413	27.625

9.7.3. ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency [MHz]	AV power [dBm]	AV power [mW]
Low	2 402	13.573	22.767
Middle	2 441	**15.473**	**35.261**
High	2 480	14.441	27.804

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.8. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

Limit = -20 dBc

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

The band-edges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal hopping mode.

RESULTS

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.8.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION

SPURIOUS EMISSIONS, NON-HOPPING



0 CHANNEL BANDEDGE



OUT-OF-BAND 0 CHANNEL



IN-BAND REFERENCE LEVEL



OUT-OF-BAND 39 CHANNEL



78 CHANNEL BANDEDGE



OUT-OF-BAND 78 CHANNEL

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON



LOW BANDEDGE



HIGH BANDEDGE

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.8.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION

SPURIOUS EMISSIONS, NON-HOPPING



0 CHANNEL BANDEDGE



OUT-OF-BAND 0 CHANNEL



IN-BAND REFERENCE LEVEL



OUT-OF-BAND 39 CHANNEL



78 CHANNEL BANDEDGE



OUT-OF-BAND 78 CHANNEL

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON



LOW BANDEDGE



HIGH BANDEDGE

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

10. RADIATED TEST RESULTS

LIMITS

FCC §15.205 and §15.209

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (µV/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

FCC Part 15.205 (a) : Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.41425 ~ 8.41475	108 ~ 121.94	1300 ~ 1427	4.5 ~ 5.15	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1435 ~ 1626.5	5.35 ~ 5.46	15.35 ~ 16.2
2.1735 ~ 2.1905	12.51975 ~ 12.52025	149.9 ~ 150.05	1645.5 ~ 1646.5	7.25 ~ 7.75	17.7 ~ 21.4
4.125 ~ 4.128	12.57675 ~ 12.57725	156.52475 ~	1660 ~ 1710	8.025 ~ 8.5	22.01 ~ 23.12
4.17725 ~ 4.17775	13.36 ~ 13.41	156.52525	1718.8 ~ 1722.2	9.0 ~ 9.2	23.6 ~ 24.0
4.20725 ~ 4.20775	16.42 ~ 16.423	156.7 ~ 156.9	2200 ~ 2300	9.3 ~ 9.5	31.2 ~ 31.8
6.215 ~ 6.218	16.69475 ~ 16.69525	162.0125 ~	2310 ~ 2390	10.6 ~ 12.7	36.43 ~ 36.5
6.26775 ~ 6.26825	16.80425 ~ 16.80475	167.17	2483.5 ~ 2500	13.25 ~ 13.4	Above 38.6
6.31175 ~ 6.31225	25.5 ~ 25.67	167.72 ~ 173.2	2655 ~ 2900		
8.291 ~ 8.294	37.5 ~ 38.25	240 ~ 285	3260 ~ 3267		
8.362 ~ 8.366	73 ~ 74.6	322 ~ 335.4	3332 ~ 3339		
8.37625 ~ 8.38675	74.8 ~ 75.2	399.90 ~ 410	3345.8 ~ 3358		
		608 ~ 614	3600 ~ 4400		
		960 ~ 1240			

▪ FCC Part 15.205(b) : The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane for below 1GHz and 150 cm for above 1GHz. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz for peak measurements.(Pre-scans to detect harmonic and spurious emissions, the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 30 kHz for peak measurements.)

For band edge measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1/T (on time) for average measurement.

GFSK = 1/T = 1 / 0.00289s = 346Hz.

The minimum VBW was 346Hz, but test receiver(ESU40) couldn’t set value 347Hz. Due to this reason, testing VBW was set to 500Hz(Worst cases).

The spectrum from 1GHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.
(From 30MHz to 1GHz, test was performed with the EUT set to transmit at the channel with highest output power)

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

Note : Emission was pre-scanned from 9kHz to 30MHz; No emissions were detected which was at least 20dB below the specification limit (consider distance correction factor).
Per FCC part 15.31(o), test results were not reported.

Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open are test site.
Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the one of tests made in an open field based on KDB 414788.

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

10.1. TRANSMITTER ABOVE 1 GHz

10.1.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION

BANDEDGE (0 CHANNEL)

HORIZONTAL RESULT



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	42.32	Pk	31.8	-25.6	48.52	-	-	74	-25.48	209	127	H
2	* 2.38645	47.83	Pk	31.8	-25.6	54.03	-	-	74	-19.97	209	127	H
3	* 2.39	33.04	VA1T	31.8	-25.6	39.24	54	-14.76	-	-	209	127	H
4	* 2.38786	33.31	VA1T	31.8	-25.5	39.61	54	-14.39	-	-	209	127	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
Pk - Peak detector
VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

VERTICAL RESULT



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	43.58	Pk	31.8	-25.6	49.78	-	-	74	-24.22	166	337	V
2	* 2.34802	45.98	Pk	31.7	-25.7	51.98	-	-	74	-22.02	166	337	V
3	* 2.39	32.57	VA1T	31.8	-25.6	38.77	54	-15.23	-	-	166	337	V
4	* 2.38309	33.13	VA1T	31.8	-25.5	39.43	54	-14.57	-	-	166	337	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
Pk - Peak detector
VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_15C(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

BANDEDGE (78 CHANNEL)

HORIZONTAL RESULT



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.48351	45.48	Pk	32	-25.3	52.18	-	-	74	-21.82	207	214	H
2	* 2.48352	53.66	Pk	32	-25.3	60.36	-	-	74	-13.64	207	214	H
3	* 2.48351	34.9	VA1T	32	-25.3	41.6	54	-12.4	-	-	207	214	H
4	* 2.48391	35.99	VA1T	32	-25.3	42.69	54	-11.31	-	-	207	214	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
Pk - Peak detector
VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

VERTICAL RESULT



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.48351	50.98	Pk	32	-25.3	57.68	-	-	74	-16.32	161	315	V
2	* 2.48375	51.88	Pk	32	-25.3	58.58	-	-	74	-15.42	161	315	V
3	* 2.48351	33.22	VA1T	32	-25.3	39.92	54	-14.08	-	-	161	315	V
4	* 2.48387	35.3	VA1T	32	-25.3	42	54	-12	-	-	161	315	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
Pk - Peak detector
VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_15C(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

HARMONICS AND SPURIOUS EMISSIONS

0 CHANNEL RESULTS



HORIZONTAL



VERTICAL

RADIATED EMISSIONS

Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.80378	46.12	PKFH	34.1	-31.5	48.72	-	-	74	-25.28	55	124	H
* 4.80402	41.29	VA1T	34.1	-31.5	43.89	54	-10.11	-	-	55	124	H
* 4.80424	48.47	PKFH	34.1	-31.5	51.07	-	-	74	-22.93	37	151	V
* 4.80402	44.57	VA1T	34.1	-31.5	47.17	54	-6.83	-	-	37	151	V
7.19936	36.95	PKFH	35.9	-27.7	45.15	-	-	74	-28.85	61	213	H
7.2066	39.4	PKFH	35.9	-27.6	47.7	-	-	74	-26.3	296	144	V
9.6108	33.6	PKFH	37.1	-23.1	47.6	-	-	74	-26.4	360	100	H
9.60695	32.98	PKFH	37.1	-23	47.08	-	-	74	-26.92	360	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
PKFH FHSS/BT RB=100k for Frequencies<1GHz / RB=1MHz for Frequencies>1GHz, VB=3 x RB, Peak
VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

39 CHANNEL RESULTS



HORIZONTAL



VERTICAL

RADIATED EMISSIONS

Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.88224	46.62	PKFH	34.1	-31.4	49.32	-	-	74	-24.68	59	109	H
* 4.88194	40.31	VA1T	34.1	-31.3	43.11	54	-10.89	-	-	59	109	H
* 4.88202	49.1	PKFH	34.1	-31.3	51.9	-	-	74	-22.1	150	199	V
* 4.8818	44.78	VA1T	34.1	-31.3	47.58	54	-6.42	-	-	150	199	V
* 7.32238	38.48	PKFH	35.8	-27.3	46.98	-	-	74	-27.02	66	150	H
* 7.3233	29.1	VA1T	35.8	-27.3	37.6	54	-16.4	-	-	66	150	H
* 7.32344	42.29	PKFH	35.8	-27.3	50.79	-	-	74	-23.21	96	250	V
* 7.32302	36.21	VA1T	35.8	-27.3	44.71	54	-9.29	-	-	96	250	V
9.77061	33.03	PKFH	37.5	-23.8	46.73	-	-	74	-27.27	0	100	H
9.76315	32.81	PKFH	37.4	-23.7	46.51	-	-	74	-27.49	0	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
PKFH FHSS/BT RB=100k for Frequencies<1GHz / RB=1MHz for Frequencies>1GHz, VB=3 x RB, Peak
VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

78 CHANNEL RESULTS



HORIZONTAL



VERTICAL

RADIATED EMISSIONS

Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.95974	53.27	PKFH	34.1	-31.4	55.97	-	-	74	-18.03	149	238	V
* 4.95974	53.27	PKFH	34.1	-31.4	**31.21	54	-22.79	-	-	149	238	V
* 4.95964	46.76	PKFH	34.1	-31.4	49.46	-	-	74	-24.54	204	167	H
* 4.96002	42.87	VA1T	34.1	-31.4	45.57	54	-8.43	-	-	204	167	H
* 7.4404	43.74	PKFH	35.8	-26.8	52.74	-	-	74	-21.26	289	326	V
* 7.43998	38.04	VA1T	35.8	-26.8	47.04	54	-6.96	-	-	289	326	V
* 7.4406	39.99	PKFH	35.8	-26.8	48.99	-	-	74	-25.01	222	387	H
* 7.43998	32.61	VA1T	35.8	-26.8	41.61	54	-12.39	-	-	222	387	H
9.92171	32.72	PKFH	37.7	-21.5	48.92	-	-	74	-25.08	360	100	H
9.91975	32.53	PKFH	37.7	-21.6	48.63	-	-	74	-25.37	360	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
** Data subtracted from the peak value: 20log(2*2.890ms/100ms) = -24.76 dB
PKFH FHSS/BT RB=100k for Frequencies<1GHz / RB=1MHz for Frequencies>1GHz, VB=3 x RB, Peak
VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_15C(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

10.1.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION

BANDEDGE (0 CHANNEL)

HORIZONTAL RESULT



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	44	Pk	31.8	-25.6	50.2	-	-	74	-23.8	210	129	H
2	* 2.38796	46.43	Pk	31.8	-25.5	52.73	-	-	74	-21.27	210	129	H
3	* 2.39	32.86	VA1T	31.8	-25.6	39.06	54	-14.94	-	-	210	129	H
4	* 2.3888	33.12	VA1T	31.8	-25.5	39.42	54	-14.58	-	-	210	129	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
Pk - Peak detector
VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

VERTICAL RESULT



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	43.12	Pk	31.8	-25.6	49.32	-	-	74	-24.68	163	336	V
2	* 2.33801	46.49	Pk	31.7	-25.6	52.59	-	-	74	-21.41	163	336	V
3	* 2.39	32.51	VA1T	31.8	-25.6	38.71	54	-15.29	-	-	163	336	V
4	* 2.38246	33.21	VA1T	31.8	-25.6	39.41	54	-14.59	-	-	163	336	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
Pk - Peak detector
VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_15C(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

BANDEDGE (78 CHANNEL)

HORIZONTAL RESULT



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168717	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.48351	48.2	Pk	32	-25.3	54.9	-	-	74	-19.1	208	219	H
2	* 2.48365	52.87	Pk	32	-25.3	59.57	-	-	74	-14.43	208	219	H
3	* 2.48351	35.37	VA1T	32	-25.3	42.07	54	-11.93	-	-	208	219	H
4	* 2.48368	35.47	VA1T	32	-25.3	42.17	54	-11.83	-	-	208	219	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
Pk - Peak detector
VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.