



FCC CFR47 PART 15 SUBPART C

ANT+

C2PC CERTIFICATION TEST REPORT

FOR

GSM/WCDMA/LTE Tablet with Bluetooth, DTS/UNII a/b/g/n/ac, and ANT +

MODEL NUMBER: SM-T805

FCC ID: A3LSMT805

REPORT NUMBER: 14U17572-5 REVISION A

ISSUE DATE: May 21, 2014

Prepared for
SAMSUNG ELECTRONICS CO., LTD.
416, MAETAN 3-DONG, YEONGTONG-GU
SUWON-CITY
GYEONGGI-DO, 443-742, SOUTH KOREA

Prepared by
UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888



NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	5/2/14	Initial Issue	P. Kim
A	5/21/14	Updated antenna information	P. Zhang

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. CALIBRATION AND UNCERTAINTY.....	5
4.1. MEASURING INSTRUMENT CALIBRATION	5
4.2. SAMPLE CALCULATION	5
4.3. MEASUREMENT UNCERTAINTY.....	5
5. EQUIPMENT UNDER TEST.....	6
5.1. DESCRIPTION OF EUT	6
5.2. MAXIMUM OUTPUT FUNDAMENTAL FIELD STRENGTH	6
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	6
5.4. WORST-CASE CONFIGURATION AND MODE.....	6
5.5. DESCRIPTION OF TEST SETUP	7
6. TEST AND MEASUREMENT EQUIPMENT	9
7. LIMITS AND RESULTS	10
7.1. TRANSMITTER RADIATED EMISSIONS.....	10
7.1.1. DUTY CYCLE (From Original).....	12
7.1.2. FUNDAMENTAL FREQUENCY RADIATED EMISSION	13
7.1.3. TRANSMITTER RESTRICTED BAND EDGES	14
7.1.4. SPURIOUS BELOW 1 GHz.....	19
8. SETUP PHOTOS	22

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
416, MAETAN 3-DONG, YEONGTONG-GU
SUWON-CITY, GYEONGGI-DO, 443-742, SOUTH KOREA

EUT DESCRIPTION: GSM/WCDMA/LTE Tablet with Bluetooth, DTS/UNII a/b/g/n/ac, & ANT+

MODEL: SM-T805

SERIAL NUMBER: R32F203DVSN

DATE TESTED: April 22 - 28, 2014

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Verification Services Inc. By:



PHILIP KIM
WiSE PROGRAM MANAGER
UL Verification Services Inc.

Tested By:



ROLLY ALEGRE
WiSE TEST TECHNICIAN
UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamplifier Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 18000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a Tablet with Bluetooth, DTS/UNII a/b/g/n/ac, & ANT+.

5.2. MAXIMUM OUTPUT FUNDAMENTAL FIELD STRENGTH

The ANT+ mode has maximum output fundamental field strength as follows:

Frequency Range (MHz)	Mode	Peak E-field Strength (dBuV/m)	Avg E-field Strength (dBuV/m)	Distance (m)
2402 - 2480	ANT +	84.07	83.91	3.00

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antenna, with a maximum gain of -4.24 dBi.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X,Y,Z, it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT


Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	Samsung	Samsung	N/A	N/A
Earphone	Samsung	Samsung	N/A	N/A

I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	1.2m	N/A
2	Audio	1	Mini-Jack	Unshielded	1m	N/A

TEST SETUP

The EUT is set to continuously transmit in ANT + test mode



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	Asset	Cal Due
Antenna, Biconolog, 30MHz-1 GHz	Sunol Sciences	JB1	C01171	02/13/15
Antenna, Horn, 18GHz	EMCO	3115	C00783	10/25/14
Antenna, Horn, 26.5 GHz	ARA	MWH-1826/B	C00980	11/14/14
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00580	01/28/15
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01052	10/22/14
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01069	12/20/14
CBT Bluetooth Tester	R & S	CBT	None	07/12/14
Peak Power Meter	Agilent / HP	E4416A	C00963	12/13/14
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	12/13/14
LISN, 30 MHz	FCC	50/250-25-2	C00626	01/14/15
Reject Filter, 2.4GHz	Micro-Tronics	BRM50702	N02684	CNR

7. LIMITS AND RESULTS

7.1. TRANSMITTER RADIATED EMISSIONS

TEST PROCEDURE

ANSI C63.4

LIMIT

IC RSS-210, A2.9
FCC 15.249

Operation within the bands 902–928 MHz, 2400–2483.5 MHz, 5725–5875 MHz, and 24.0–24.25 GHz.

(a) Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/ meter)	Field strength of harmonics (microvolts/ meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.


(e) As shown in Sec. 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

Frequency (MHz)	Field strength (microvolts/meter)	Measure- ment dis- tance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100 **	3
88-216	150 **	3
216-960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

RESULTS

7.1.1. DUTY CYCLE (From Original)



7.1.2. FUNDAMENTAL FREQUENCY RADIATED EMISSION



FCC, VCCI, CISPR, CE, AUSTEL, NZ
UL, CSA, TUV, BSMI, DHHS, NVLAP
47173 BENICIA STREET, FREMONT, CA 94538, USA

Project #: 14U17528
Report #: 14U17528
Date & Time: 04/22/14
Test Engr: R. Alegre

Company: Samsung
EUT Description: Tablet + Bluetooth, DTS/UNII a/b/g/n/ac & ANT+
Test Configuration: X position
Type of Test: FCC
Mode of Operation: Transmitting : ANT+ mode


M% = ((t1+t2+t3+...)/T) * 66.83% = 0.30%

Freq. (MHz)	Pk Rdg (dBuV)	Av Rdg (dBuV)	AF (dB)	Closs (dB)	Pre-amp (dB)	Pk Level (dBuV/m)	Av Level (dBuV/m)	Pk Limit FCC B	Av Limit FCC B	Pk Margin (dB)	Avg Margin (dB)	Pol (H/V)	Az (Deg)	Height (Meter)
Low channel														
2402.00	64.31	63.42	32.10	-22.80	0.00	73.61	72.72	114.00	94.00	-40.39	-21.28	3mV	0.00	1.00
2402.00	72.70	72.41	32.10	-22.80	0.00	82.00	81.71	114.00	94.00	-32.00	-12.29	3mH	0.00	2.00
Mid channel														
2442.00	66.01	65.29	32.10	-22.80	0.00	75.31	74.59	114.00	94.00	-38.69	-19.41	3mV	0.00	1.00
2442.00	74.77	74.61	32.10	-22.80	0.00	84.07	83.91	114.00	94.00	-29.93	-10.09	3mH	0.00	2.00
High channel														
2480.00	66.19	66.30	32.10	-22.80	0.00	75.49	75.60	114.00	94.00	-38.51	-18.40	3mV	0.00	1.00
2480.00	73.90	73.15	32.10	-22.80	0.00	83.20	82.45	114.00	94.00	-30.80	-11.55	3mH	0.00	2.00

RBW/VBW setting for peak is 1MHz:3MHz
RBW/VBW setting for average is 1MHz: 1/T where T ON time

7.1.3. TRANSMITTER RESTRICTED BAND EDGES


RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cb/Fltr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	40	PK	32.1	-22.9	49.2	-	-	74	-24.8	241	99	H
2	* 2.352	43.18	PK	31.9	-23	52.08	-	-	74	-21.92	241	99	H
3	* 2.39	31.05	VB1T	32.1	-22.9	40.25	54	-13.75	-	-	241	99	H
4	* 2.383	32.01	VB1T	32.1	-22.9	41.21	54	-12.79	-	-	241	99	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band
PK - Peak detector


RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Chl/F1 tr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	41.59	PK	32.1	-22.9	50.79	-	-	74	-23.21	241	99	V
2	* 2.373	43	PK	32	-22.8	52.2	-	-	74	-21.8	241	99	V
3	* 2.39	31.37	VB1T	32.1	-22.9	40.57	54	-13.43	-	-	241	99	V
4	* 2.354	32.19	VB1T	31.9	-23	41.09	54	-12.91	-	-	241	99	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band
PK - Peak detector


RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Chl/F1 tr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	41.6	PK	32.4	-22.6	51.4	-	-	74	-22.6	241	99	H
2	* 2.493	43.22	PK	32.4	-22.7	52.92	-	-	74	-21.08	241	99	H
3	* 2.484	30.89	VB1T	32.4	-22.6	40.69	54	-13.31	-	-	241	99	H
4	2.542	31.67	VB1T	32.5	-22.5	41.67	54	-12.33	-	-	241	99	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band
PK - Peak detector

RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Chl/FI tr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	41.01	PK	32.4	-22.6	50.81	-	-	74	-23.19	241	99	V
2	* 2.49	43.76	PK	32.4	-22.7	53.46	-	-	74	-20.54	241	99	V
3	* 2.484	31.27	VB1T	32.4	-22.6	41.07	54	-12.93	-	-	241	99	V
4	2.53	31.8	VB1T	32.5	-22.7	41.6	54	-12.4	-	-	241	99	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band
PK - Peak detector

7.1.4. HARMONICS AND SPURIOUS EMISSIONS ABOVE 1GHz


HARMONICS														
		FCC, VCCI, CISPR, CE, AUSTEL, NZ UL, CSA, TUV, BSMI, DHHS, NVLAP 47173 BENICIA STREET, FREMONT, CA 94538, USA		Project #: 14U17528		Report #: 14U17528		Date & Time: 04/22/14		Test Engr: R. Alegre				
Company: Samsung		EUT Description: Tablet + Bluetooth, DTS/UNII a/b/g/n/ac & ANT+												
Test Configuration : X POSITION														
Type of Test: FCC														
Mode of Operation: Transmitting : ANT+ mode														
M% = ((t1+t2+t3+...)/T) * 66.83% = 0.30%														
Freq. (MHz)	Pk Rdg (dBuV)	Av Rdg (dBuV)	AF (dB)	Closs (dB)	Pre-amp (dB)	Pk Level (dBuV/m)	Av Level (dBuV/m)	Pk Limit FCC B	Av Limit FCC B	Pk Margin (dB)	Avg Margin (dB)	Pol (H/V)	Az (Deg)	Height (Meter)
Low channel														
4804.00	40.85	32.52	32.10	-22.80	0.00	50.15	41.82	74.00	54.00	-23.85	-12.18	3mV	0.00	1.00
4804.00	41.91	32.36	32.10	-22.80	0.00	51.21	41.66	74.00	54.00	-22.79	-12.34	3mH	0.00	2.00
Mid channel														
4884.00	41.14	32.49	32.10	-22.80	0.00	50.44	41.79	74.00	54.00	-23.56	-12.21	3mV	0.00	1.00
4884.00	41.27	32.32	32.10	-22.80	0.00	50.57	41.62	74.00	54.00	-23.43	-12.38	3mH	0.00	2.00
High channel														
4960.00	41.23	32.41	32.10	-22.80	0.00	50.53	41.71	74.00	54.00	-23.47	-12.29	3mV	0.00	1.00
4960.00	41.27	32.22	32.10	-22.80	0.00	50.57	41.52	74.00	54.00	-23.43	-12.48	3mH	0.00	2.00

RBW/VBW setting for peak is 1MHz:3MHz


RBW/VBW setting for average is 1MHz: 1/T where T ON time

7.1.5. SPURIOUS BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (HORIZONTAL)



SPURIOUS EMISSIONS 30 TO 1000 MHz (VERTICAL)



DATA

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	AF T477 (dB/m)	Amp/Cbl (dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
10	* 243.4	39.8	PK	11.5	-26.5	24.8	46.02	-21.22	0-360	200	V
1	43.175	46.71	PK	11.3	-28.7	29.31	40	-10.69	0-360	300	H
7	43.6425	54.14	PK	11	-28.7	36.44	40	-3.56	0-360	101	V
2	55.6275	41.93	PK	7	-28.6	20.33	40	-19.67	0-360	300	H
8	69.3125	45.18	PK	8.1	-28.4	24.88	40	-15.12	0-360	101	V
9	92.3475	38.53	PK	8.2	-28.1	18.63	43.52	-24.89	0-360	101	V
4	157.5	38.12	PK	12.3	-27.4	23.02	43.52	-20.5	0-360	200	H
3	186.1025	43.52	PK	11.3	-27.1	27.72	43.52	-15.8	0-360	100	H
11	214.8	39.04	PK	10.4	-26.8	22.64	43.52	-20.88	0-360	200	V
5	357.9	34.77	PK	14.7	-25.8	23.67	46.02	-22.35	0-360	200	H
6	448	31.9	PK	16.8	-26	22.7	46.02	-23.32	0-360	101	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector