WCDMA Band 5

WCDMA

Band 5
REL99

High Frequency Substitution Measurement
UL Korea, Ltd. Suwon Laboratory Chamber 2

Company: Samsung
Project #: 16K23301
Date: 04-19-16
Test Engineer: Steven Kim
Configuration: EUT ONLY, X Position
Mode: Rel 99_850 MHz

Test Equipment:
Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT)
Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
826.40	15.92	V	1.1	-1.5	13.31	38.5	-25.1	
826.40	20.23	H	1.1	-1.5	17.62	38.5	-20.8	
Mid Ch								
836.60	14.21	V	1.1	-1.4	11.72	38.5	-26.7	
836.60	20.67	H	1.1	-1.4	18.18	38.5	-20.3	
High Ch								
846.60	13.05	V	1.1	-1.3	10.67	38.5	-27.8	
846.60	21.15	H	1.1	-1.3	18.77	38.5	-19.7	

Rev. 3.17.11

WCDMA

Band 5
HSDPA

High Frequency Substitution Measurement
UL Korea, Ltd. Suwon Laboratory Chamber 2

Company: Samsung
Project #: 16K23301
Date: 04-19-16
Test Engineer: Steven Kim
Configuration: EUT ONLY, X Position
Mode: HSDPA_850 MHz

Test Equipment:
Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT)
Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
826.40	12.61	V	1.1	-1.5	10.00	38.5	-28.5	
826.40	17.62	H	1.1	-1.5	15.01	38.5	-23.4	
Mid Ch								
836.60	9.59	V	1.1	-1.4	7.10	38.5	-31.4	
836.60	18.73	H	1.1	-1.4	16.24	38.5	-22.2	
High Ch								
846.60	8.81	V	1.1	-1.3	6.43	38.5	-32.0	
846.60	21.22	H	1.1	-1.3	18.84	38.5	-19.6	

Rev. 3.17.11

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

WCDMA Band 2

WCDMA

Band 2
REL99

High Frequency Substitution Measurement
UL Korea, Ltd. Suwon Laboratory Chamber 2

Company: Samsung
Project #: 16K23301
Date: 04-18-16
Test Engineer: Steven Kim
Configuration: EUT ONLY, X Position
Mode: REL99_1900 MHz

Test Equipment:
Receiving: 3117[00168724] and Chamber 1 SMA Cables
Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
1852.40	11.45	V	1.60	8.79	18.64	33.0	-14.4	
1852.40	16.19	H	1.60	8.79	23.38	33.0	-9.6	
Mid Ch								
1880.00	11.20	V	1.62	8.62	18.20	33.0	-14.8	
1880.00	15.93	H	1.62	8.62	22.93	33.0	-10.1	
High Ch								
1907.60	10.25	V	1.63	8.45	17.07	33.0	-15.9	
1907.60	15.61	H	1.63	8.45	22.43	33.0	-10.6	

Rev. 3.17.11
Note: For Band 4 EIRP limit is 30dBm

WCDMA

Band 2
HSDPA

High Frequency Substitution Measurement
UL Korea, Ltd. Suwon Laboratory Chamber 2

Company: Samsung
Project #: 16K23301
Date: 04-19-16
Test Engineer: Steven Kim
Configuration: EUT ONLY, X Position
Mode: HSDPA_1900 MHz

Test Equipment:
Receiving: 3117[00168724] and Chamber 1 SMA Cables
Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
1852.40	10.41	V	1.60	8.79	17.60	33.0	-15.4	
1852.40	14.80	H	1.60	8.79	21.99	33.0	-11.0	
Mid Ch								
1880.00	10.02	V	1.62	8.62	17.02	33.0	-16.0	
1880.00	14.50	H	1.62	8.62	21.50	33.0	-11.5	
High Ch								
1907.60	9.21	V	1.63	8.45	16.03	33.0	-17.0	
1907.60	14.98	H	1.63	8.45	21.80	33.0	-11.2	

Rev. 3.17.11
Note: For Band 4 EIRP limit is 30dBm

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 41

LTE Band 41 20MHz QPSK

High Frequency Substitution Measurement
UL Korea, Ltd. Suwon Laboratory Chamber 2

Company: Samsung
Project #: 16K23301
Date: 04-23-16
Test Engineer: Steven Kim
Configuration: EUT / X-Position
Mode: LTE Band 41, QPSK, 20MHz

Test Equipment:
Receiving: 3117[00168724] and Chamber 1 SMA Cables
Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
2565.00	13.94	V	1.9	9.1	21.20	33.0	-11.8	
2565.00	10.22	H	1.9	9.1	17.48	33.0	-15.5	
Mid Ch								
2605.00	13.97	V	1.9	10.4	22.46	33.0	-10.5	
2605.00	11.70	H	1.9	10.4	20.19	33.0	-12.8	
High Ch								
2645.00	12.70	V	1.9	10.3	21.14	33.0	-11.9	
2645.00	10.04	H	1.9	10.3	18.48	33.0	-14.5	

Rev. 3.17.11
Note: For Band 4 EIRP limit is 30dBm

LTE Band 41 20MHz 16QAM

High Frequency Substitution Measurement
UL Korea, Ltd. Suwon Laboratory Chamber 2

Company: Samsung
Project #: 16K23301
Date: 04-23-16
Test Engineer: Steven Kim
Configuration: EUT / X-Position
Mode: LTE Band 41, 16QAM, 20MHz

Test Equipment:
Receiving: 3117[00168724] and Chamber 1 SMA Cables
Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
2565.00	12.95	V	1.9	9.1	20.21	33.0	-12.8	
2565.00	9.34	H	1.9	9.1	16.60	33.0	-16.4	
Mid Ch								
2605.00	13.02	V	1.9	10.4	21.51	33.0	-11.5	
2605.00	10.67	H	1.9	10.4	19.16	33.0	-13.8	
High Ch								
2645.00	11.71	V	1.9	10.3	20.15	33.0	-12.8	
2645.00	9.05	H	1.9	10.3	17.49	33.0	-15.5	

Rev. 3.17.11
Note: For Band 4 EIRP limit is 30dBm

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE
Band 41
15MHz
QPSK

High Frequency Substitution Measurement
UL Korea, Ltd. Suwon Laboratory Chamber 2

Company: Samsung
Project #: 16K23301
Date: 04-23-16
Test Engineer: Steven Kim
Configuration: EUT / X-Position
Mode: LTE Band 41, QPSK, 15MHz

Test Equipment:
Receiving: 3117[00168724] and Chamber 1 SMA Cables
Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
2562.50	13.77	V	1.9	9.1	21.03	33.0	-12.0	
2562.50	10.32	H	1.9	9.1	17.58	33.0	-15.4	
Mid Ch								
2605.00	14.36	V	1.9	10.4	22.85	33.0	-10.2	
2605.00	11.50	H	1.9	10.4	19.99	33.0	-13.0	
High Ch								
2647.50	12.51	V	1.9	10.3	20.95	33.0	-12.0	
2647.50	11.43	H	1.9	10.3	19.87	33.0	-13.1	

Rev. 3.17.11
Note: For Band 4 EIRP limit is 30dBm

LTE
Band 41
15MHz
16QAM

High Frequency Substitution Measurement
UL Korea, Ltd. Suwon Laboratory Chamber 2

Company: Samsung
Project #: 16K23301
Date: 04-23-16
Test Engineer: Steven Kim
Configuration: EUT / X-Position
Mode: LTE Band 41, 16QAM, 15MHz

Test Equipment:
Receiving: 3117[00168724] and Chamber 1 SMA Cables
Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
2562.50	12.77	V	1.9	9.1	20.03	33.0	-13.0	
2562.50	9.43	H	1.9	9.1	16.69	33.0	-16.3	
Mid Ch								
2605.00	13.53	V	1.9	10.4	22.02	33.0	-11.0	
2605.00	10.61	H	1.9	10.4	19.10	33.0	-13.9	
High Ch								
2647.50	11.57	V	1.9	10.3	20.01	33.0	-13.0	
2647.50	10.38	H	1.9	10.3	18.82	33.0	-14.2	

Rev. 3.17.11
Note: For Band 4 EIRP limit is 30dBm

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE
Band 41
10MHz
QPSK

High Frequency Substitution Measurement
UL Korea, Ltd. Suwon Laboratory Chamber 2

Company: Samsung
Project #: 16K23301
Date: 04-23-16
Test Engineer: Steven Kim
Configuration: EUT / X-Position
Mode: LTE Band 41, QPSK, 10MHz

Test Equipment:
Receiving: 3117[00168724] and Chamber 1 SMA Cables
Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
2560.00	13.84	V	1.9	9.1	21.10	33.0	-11.9	
2560.00	10.86	H	1.9	9.1	18.12	33.0	-14.9	
Mid Ch								
2605.00	14.77	V	1.9	10.4	23.26	33.0	-9.7	
2605.00	11.53	H	1.9	10.4	20.02	33.0	-13.0	
High Ch								
2650.00	12.98	V	1.9	10.3	21.42	33.0	-11.6	
2650.00	11.03	H	1.9	10.3	19.47	33.0	-13.5	

Rev. 3.17.11
Note: For Band 4 EIRP limit is 30dBm

LTE
Band 41
10MHz
16QAM

High Frequency Substitution Measurement
UL Korea, Ltd. Suwon Laboratory Chamber 2

Company: Samsung
Project #: 16K23301
Date: 04-23-16
Test Engineer: Steven Kim
Configuration: EUT / X-Position
Mode: LTE Band 41 16QAM, 10MHz

Test Equipment:
Receiving: 3117[00168724] and Chamber 1 SMA Cables
Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
2560.00	12.84	V	1.9	9.1	20.10	33.0	-12.9	
2560.00	9.93	H	1.9	9.1	17.19	33.0	-15.8	
Mid Ch								
2605.00	13.78	V	1.9	10.4	22.27	33.0	-10.7	
2605.00	10.74	H	1.9	10.4	19.23	33.0	-13.8	
High Ch								
2650.00	11.94	V	1.9	10.3	20.38	33.0	-12.6	
2650.00	9.97	H	1.9	10.3	18.41	33.0	-14.6	

Rev. 3.17.11
Note: For Band 4 EIRP limit is 30dBm

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE
Band 41
5MHz
QPSK

High Frequency Substitution Measurement
UL Korea, Ltd. Suwon Laboratory Chamber 2

Company: Samsung
Project #: 16K23301
Date: 04-23-16
Test Engineer: Steven Kim
Configuration: EUT / X-Position
Mode: LTE Band 41, QPSK , 5MHz

Test Equipment:
Receiving: 3117[00168724] and Chamber 1 SMA Cables
Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
2557.50	14.45	V	1.9	9.1	21.71	33.0	-11.3	
2557.50	10.92	H	1.9	9.1	18.18	33.0	-14.8	
Mid Ch								
2605.00	14.21	V	1.9	10.4	22.70	33.0	-10.3	
2605.00	12.02	H	1.9	10.4	20.51	33.0	-12.5	
High Ch								
2652.50	13.21	V	1.9	10.3	21.65	33.0	-11.3	
2652.50	9.99	H	1.9	10.3	18.43	33.0	-14.6	

Rev. 3.17.11
Note: For Band 4 EIRP limit is 30dBm

LTE
Band 41
5MHz
16QAM

High Frequency Substitution Measurement
UL Korea, Ltd. Suwon Laboratory Chamber 2

Company: Samsung
Project #: 16K23301
Date: 04-23-16
Test Engineer: Steven Kim
Configuration: EUT / X-Position
Mode: LTE Band 41 16QAM, 5MHz

Test Equipment:
Receiving: 3117[00168724] and Chamber 1 SMA Cables
Substitution: 3115[00161451] Substitution, 3m SMA Cable Warehouse

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
2557.50	13.71	V	1.9	9.1	20.97	33.0	-12.0	
2557.50	10.16	H	1.9	9.1	17.42	33.0	-15.6	
Mid Ch								
2605.00	13.08	V	1.9	10.4	21.57	33.0	-11.4	
2605.00	11.47	H	1.9	10.4	19.96	33.0	-13.0	
High Ch								
2652.50	12.30	V	1.9	10.3	20.74	33.0	-12.3	
2652.50	9.10	H	1.9	10.3	17.54	33.0	-15.5	

Rev. 3.17.11
Note: For Band 4 EIRP limit is 30dBm

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

BC0

BC0
1xRTT

High Frequency Substitution Measurement
UL Korea, Ltd. Suwon Laboratory Chamber 2

Company: Samsung
Project #: 16K23301
Date: 05-02-16
Test Engineer: Chan Park
Configuration: EUT ONLY, X Position
Mode: CDMA RTT BC0

Test Equipment:
Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT)
Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
824.70	12.97	V	1.1	-1.6	10.35	38.5	-28.1	
824.70	23.82	H	1.1	-1.6	21.20	38.5	-17.3	
Mid Ch								
836.52	13.49	V	1.1	-1.4	11.00	38.5	-27.5	
836.52	22.62	H	1.1	-1.4	20.13	38.5	-18.3	
High Ch								
848.31	11.74	V	1.1	-1.3	9.38	38.5	-29.1	
848.31	22.56	H	1.1	-1.3	20.20	38.5	-18.3	

Rev. 3.17.11
Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm

BC0
EVDO Rel.0

High Frequency Substitution Measurement
UL Korea, Ltd. Suwon Laboratory Chamber 2

Company: Samsung
Project #: 16K23301
Date: 05-02-16
Test Engineer: Chan Park
Configuration: EUT ONLY, X Position
Mode: CDMA EVDO BC0

Test Equipment:
Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT)
Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
824.70	17.19	V	1.1	-1.6	14.57	38.5	-23.9	
824.70	20.44	H	1.1	-1.6	17.82	38.5	-20.6	
Mid Ch								
836.52	14.04	V	1.1	-1.4	11.55	38.5	-26.9	
836.52	21.27	H	1.1	-1.4	18.78	38.5	-19.7	
High Ch								
848.31	13.09	V	1.1	-1.3	10.73	38.5	-27.7	
848.31	22.84	H	1.1	-1.3	20.48	38.5	-18.0	

Rev. 3.17.11
Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

11.2. FIELD STRENGTH OF SPURIOUS RADIATION

RULE PART(S)

FCC: §2.1053, §22.917, §24.238 and §27. 53

LIMIT

Part 22.917(a) & Part 24.238(a) The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB.

Part 27: (m)(4) For mobile station, the attenuation factor shall be not less than 43 + 10 log (P) dB at the channel edge and (55 + 10 log (P)dB) at the 5.5 MHz from the channel edges.

TEST PROCEDURE

ANSI / TIA / EIA 603D Clause 2.2.12; ESU40 setting reference to 971168 D01 v02r02

For peak power measurement with a ESU40:

a) Set the RBW = 100KHz for emission below 1GHz and 1MHz for emissions above 1GHz

b) Set VBW ≥ 3 × RBW;

c) Set span ≥ 1.5 times the OBW;

d) Sweep time = auto couple;

e) Detector = peak;

f) Ensure that the number of measurement points ≥ span/RBW;

g) Trace mode = max hold;

RESULTS

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

11.2.1. SPURIOUS RADIATION PLOTS

GSM 850

GSM

GSM850
GPRS

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 16K23301
Date: 04-25-16
Test Engineer: Steven Kim
Configuration: EUT / AC Adapter / Earphone, X Position
Mode: GPRS 850 MHz

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 22

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 824.2MHz									
1.6484	-10.6	V	3.0	39.1	1.0	-48.7	-13.0	-35.7	
2.4726	10.1	V	3.0	39.5	1.0	-28.4	-13.0	-15.4	
3.2968	-17.0	V	3.0	40.1	1.0	-56.1	-13.0	-43.1	
1.6484	-7.0	H	3.0	39.1	1.0	-45.1	-13.0	-32.1	
2.4726	10.3	H	3.0	39.5	1.0	-28.2	-13.0	-15.2	
3.2968	-17.1	H	3.0	40.1	1.0	-56.2	-13.0	-43.2	
Mid Ch, 836.6MHz									
1.6730	-9.1	V	3.0	39.1	1.0	-47.2	-13.0	-34.2	
2.5098	10.0	V	3.0	39.5	1.0	-28.5	-13.0	-15.5	
3.3464	-17.1	V	3.0	40.1	1.0	-56.2	-13.0	-43.2	
1.6730	-6.7	H	3.0	39.1	1.0	-44.9	-13.0	-31.9	
2.5098	10.5	H	3.0	39.5	1.0	-28.1	-13.0	-15.1	
3.3464	-17.3	H	3.0	40.1	1.0	-56.4	-13.0	-43.4	
High Ch, 848.8MHz									
1.6976	-6.0	V	3.0	39.1	1.0	-44.2	-13.0	-31.2	
2.5466	9.3	V	3.0	39.6	1.0	-29.3	-13.0	-16.3	
3.3952	-16.6	V	3.0	40.2	1.0	-55.8	-13.0	-42.8	
1.6976	-6.6	H	3.0	39.1	1.0	-44.8	-13.0	-31.8	
2.5466	5.4	H	3.0	39.6	1.0	-33.2	-13.0	-20.2	
3.3952	-16.8	H	3.0	40.2	1.0	-56.0	-13.0	-43.0	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

GSM

GSM850
EGPRS

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 16K23301
Date: 04-21-16
Test Engineer: Steven Kim
Configuration: EUT / AC Adapter / Earphone, X Position
Mode: EGPRS 850 MHz

Chamber	Pre-amplifer	Filter	Limit
Chamber 1	AFS42	Filter 1	Part 22

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 824.2MHz									
1.6484	-19.9	V	3.0	39.1	1.0	-58.0	-13.0	-45.0	
2.4726	-14.8	V	3.0	39.5	1.0	-53.3	-13.0	-40.3	
3.2968	-17.7	V	3.0	40.1	1.0	-56.8	-13.0	-43.8	
1.6484	-21.9	H	3.0	39.1	1.0	-60.0	-13.0	-47.0	
2.4726	-17.4	H	3.0	39.5	1.0	-55.9	-13.0	-42.9	
3.2968	-17.7	H	3.0	40.1	1.0	-56.8	-13.0	-43.8	
Mid Ch, 836.6MHz									
1.6730	-19.3	V	3.0	39.1	1.0	-57.4	-13.0	-44.4	
2.5098	-14.3	V	3.0	39.5	1.0	-52.9	-13.0	-39.9	
3.3464	-17.1	V	3.0	40.1	1.0	-56.2	-13.0	-43.2	
1.6730	-21.1	H	3.0	39.1	1.0	-59.2	-13.0	-46.2	
2.5098	-16.6	H	3.0	39.5	1.0	-55.1	-13.0	-42.1	
3.3464	-17.3	H	3.0	40.1	1.0	-56.5	-13.0	-43.5	
High Ch, 848.8MHz									
1.6976	-19.4	V	3.0	39.1	1.0	-57.6	-13.0	-44.6	
2.5466	-13.9	V	3.0	39.6	1.0	-52.5	-13.0	-39.5	
3.3952	-16.6	V	3.0	40.2	1.0	-55.8	-13.0	-42.8	
1.6976	-21.5	H	3.0	39.1	1.0	-59.6	-13.0	-46.6	
2.5466	-16.3	H	3.0	39.6	1.0	-54.8	-13.0	-41.8	
3.3952	-17.1	H	3.0	40.2	1.0	-56.2	-13.0	-43.2	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

GSM 1900

GSM

GSM1900
GPRS

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 16K23301
Date: 04-19-16
Test Engineer: Steven Kim
Configuration: EUT / AC Adapter / Earphone / X Position
Mode: GPRS 1900

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 24

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1850.2MHz									
3.7004	-8.3	V	3.0	40.5	1.0	-47.8	-13.0	-34.8	
5.5506	-11.5	V	3.0	40.8	1.0	-51.3	-13.0	-38.3	
7.4008	-6.0	V	3.0	40.8	1.0	-45.8	-13.0	-32.8	
3.7004	-14.4	H	3.0	40.5	1.0	-53.9	-13.0	-40.9	
5.5506	-5.3	H	3.0	40.8	1.0	-45.1	-13.0	-32.1	
7.4008	-8.0	H	3.0	40.8	1.0	-47.8	-13.0	-34.8	
Mid Ch, 1880.0MHz									
3.7600	-5.8	V	3.0	40.5	1.0	-45.3	-13.0	-32.3	
5.6400	-3.3	V	3.0	40.8	1.0	-43.1	-13.0	-30.1	
7.5200	-5.3	V	3.0	40.7	1.0	-45.0	-13.0	-32.0	
3.7600	-11.3	H	3.0	40.5	1.0	-50.8	-13.0	-37.8	
5.6400	-1.4	H	3.0	40.8	1.0	-41.2	-13.0	-28.2	
7.5200	-10.8	H	3.0	40.7	1.0	-50.5	-13.0	-37.5	
High Ch, 1909.8 MHz									
3.8196	-2.8	V	3.0	40.6	1.0	-42.4	-13.0	-29.4	
5.7294	-2.5	V	3.0	40.8	1.0	-42.3	-13.0	-29.3	
7.6392	-3.6	V	3.0	40.7	1.0	-43.2	-13.0	-30.2	
3.8196	-7.8	H	3.0	40.6	1.0	-47.4	-13.0	-34.4	
5.7294	-6.3	H	3.0	40.8	1.0	-46.1	-13.0	-33.1	
7.6392	-9.5	H	3.0	40.7	1.0	-49.2	-13.0	-36.2	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

GSM

GSM1900
EGPRS

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 16K23301
Date: 04-19-16
Test Engineer: Steven Kim
Configuration: EUT / AC Adapter / Earphone / X Position
Mode: EGPRS 1900 MHz

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 24

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1850.2MHz									
3.7004	-12.2	V	3.0	40.5	1.0	-51.7	-13.0	-38.7	
5.5506	-6.2	V	3.0	40.8	1.0	-46.0	-13.0	-33.0	
7.4008	-9.0	V	3.0	40.8	1.0	-48.8	-13.0	-35.8	
3.7000	-16.3	H	3.0	40.5	1.0	-55.8	-13.0	-42.8	
5.5500	-10.6	H	3.0	40.8	1.0	-50.4	-13.0	-37.4	
7.4000	-10.0	H	3.0	40.8	1.0	-49.8	-13.0	-36.8	
Mid Ch, 1880.0MHz									
3.7600	-10.9	V	3.0	40.5	1.0	-50.4	-13.0	-37.4	
5.6400	-10.5	V	3.0	40.8	1.0	-50.3	-13.0	-37.3	
7.5200	-9.1	V	3.0	40.7	1.0	-48.8	-13.0	-35.8	
3.7600	-14.2	H	3.0	40.5	1.0	-53.8	-13.0	-40.8	
5.6400	-10.0	H	3.0	40.8	1.0	-49.8	-13.0	-36.8	
7.5200	-10.3	H	3.0	40.7	1.0	-50.0	-13.0	-37.0	
High Ch, 1909.8 MHz									
3.8196	-9.2	V	3.0	40.6	1.0	-48.8	-13.0	-35.8	
5.7294	-11.1	V	3.0	40.8	1.0	-50.9	-13.0	-37.9	
7.6392	-8.3	V	3.0	40.7	1.0	-48.0	-13.0	-35.0	
3.8196	-13.2	H	3.0	40.6	1.0	-52.8	-13.0	-39.8	
5.7294	-11.6	H	3.0	40.8	1.0	-51.3	-13.0	-38.3	
7.6392	-10.6	H	3.0	40.7	1.0	-50.2	-13.0	-37.2	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

WCDMA Band 5

WCDMA

Band 5
REL99

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 16K23301
Date: 04-19-16
Test Engineer: Steven Kim
Configuration: EUT / AC Adapter / Earphone / X Position
Mode: Tx, REL99,850MHz

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 22

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 826.40MHz									
1.6520	-18.7	V	3.0	39.1	1.0	-56.8	-13.0	-43.8	
2.4790	-16.6	V	3.0	39.5	1.0	-55.1	-13.0	-42.1	
3.3056	-15.2	V	3.0	40.1	1.0	-54.3	-13.0	-41.3	
1.6520	-19.5	H	3.0	39.1	1.0	-57.6	-13.0	-44.6	
2.4790	-16.2	H	3.0	39.5	1.0	-54.7	-13.0	-41.7	
3.3056	-15.2	H	3.0	40.1	1.0	-54.3	-13.0	-41.3	
Mid Ch, 836.6MHz									
1.6732	-18.0	V	3.0	39.1	1.0	-56.1	-13.0	-43.1	
2.5098	-17.2	V	3.0	39.5	1.0	-55.7	-13.0	-42.7	
3.3464	-15.4	V	3.0	40.1	1.0	-54.6	-13.0	-41.6	
1.6732	-19.5	H	3.0	39.1	1.0	-57.6	-13.0	-44.6	
2.5098	-16.9	H	3.0	39.5	1.0	-55.5	-13.0	-42.5	
3.3464	-15.8	H	3.0	40.1	1.0	-54.9	-13.0	-41.9	
High Ch, 846.6MHz									
1.6932	-18.2	V	3.0	39.1	1.0	-56.4	-13.0	-43.4	
2.5390	-17.4	V	3.0	39.6	1.0	-55.9	-13.0	-42.9	
3.3860	-15.5	V	3.0	40.2	1.0	-54.6	-13.0	-41.6	
1.6932	-19.3	H	3.0	39.1	1.0	-57.5	-13.0	-44.5	
2.5390	-16.6	H	3.0	39.6	1.0	-55.2	-13.0	-42.2	
3.3860	-15.7	H	3.0	40.2	1.0	-54.9	-13.0	-41.9	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

WCDMA

Band 5
HSDPA

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 16K23301
Date: 04-19-16
Test Engineer: Steven Kim
Configuration: EUT / AC Adapter / Earphone / X Position
Mode: Tx, HSDPA,850MHz

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 22

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 826.40MHz									
1.6520	-19.6	V	3.0	39.1	1.0	-57.7	-13.0	-44.7	
2.4790	-16.7	V	3.0	39.5	1.0	-55.2	-13.0	-42.2	
3.3056	-15.8	V	3.0	40.1	1.0	-54.9	-13.0	-41.9	
1.6520	-21.1	H	3.0	39.1	1.0	-59.2	-13.0	-46.2	
2.4790	-17.4	H	3.0	39.5	1.0	-55.9	-13.0	-42.9	
3.3056	-16.1	H	3.0	40.1	1.0	-55.2	-13.0	-42.2	
Mid Ch, 836.6MHz									
1.6732	-19.4	V	3.0	39.1	1.0	-57.5	-13.0	-44.5	
2.5098	-17.1	V	3.0	39.5	1.0	-55.7	-13.0	-42.7	
3.3464	-15.9	V	3.0	40.1	1.0	-55.0	-13.0	-42.0	
1.6732	-20.3	H	3.0	39.1	1.0	-58.5	-13.0	-45.5	
2.5098	-16.6	H	3.0	39.5	1.0	-55.1	-13.0	-42.1	
3.3464	-16.2	H	3.0	40.1	1.0	-55.4	-13.0	-42.4	
High Ch, 846.6MHz									
1.6932	-18.8	V	3.0	39.1	1.0	-56.9	-13.0	-43.9	
2.5390	-15.7	V	3.0	39.6	1.0	-54.3	-13.0	-41.3	
3.3860	-15.6	V	3.0	40.2	1.0	-54.7	-13.0	-41.7	
1.6932	-19.6	H	3.0	39.1	1.0	-57.7	-13.0	-44.7	
2.5390	-15.9	H	3.0	39.6	1.0	-54.4	-13.0	-41.4	
3.3860	-16.0	H	3.0	40.2	1.0	-55.2	-13.0	-42.2	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

WCDMA Band 2

WCDMA

Band 2
REL99

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 16K23301
Date: 04-19-16
Test Engineer: Steven Kim
Configuration: EUT / AC Adapter / Earphone / X Position
Mode: Tx, REL99,1900MHz

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 24

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1852.4MHz									
3.7048	-4.7	V	3.0	40.5	1.0	-44.2	-13.0	-31.2	
5.5572	-9.8	V	3.0	40.8	1.0	-49.6	-13.0	-36.6	
7.4096	-8.1	V	3.0	40.8	1.0	-47.9	-13.0	-34.9	
3.7048	-9.9	H	3.0	40.5	1.0	-49.4	-13.0	-36.4	
5.5572	-10.5	H	3.0	40.8	1.0	-50.3	-13.0	-37.3	
7.4096	-9.2	H	3.0	40.8	1.0	-49.0	-13.0	-36.0	
Mid Ch, 1880MHz									
3.7600	-3.0	V	3.0	40.5	1.0	-42.6	-13.0	-29.6	
5.6400	-8.5	V	3.0	40.8	1.0	-48.3	-13.0	-35.3	
7.5200	-7.0	V	3.0	40.7	1.0	-46.7	-13.0	-33.7	
3.7600	-4.9	H	3.0	40.5	1.0	-44.5	-13.0	-31.5	
5.6400	-9.2	H	3.0	40.8	1.0	-49.0	-13.0	-36.0	
7.5200	-8.6	H	3.0	40.7	1.0	-48.3	-13.0	-35.3	
High Ch, 1907.6MHz									
3.8152	0.2	V	3.0	40.6	1.0	-39.4	-13.0	-26.4	
5.7228	-7.2	V	3.0	40.8	1.0	-47.0	-13.0	-34.0	
7.6304	-3.9	V	3.0	40.7	1.0	-43.6	-13.0	-30.6	
3.8152	-4.7	H	3.0	40.6	1.0	-44.3	-13.0	-31.3	
5.7228	-10.3	H	3.0	40.8	1.0	-50.1	-13.0	-37.1	
7.6304	-8.6	H	3.0	40.7	1.0	-48.3	-13.0	-35.3	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

WCDMA

Band 2
HSDPA

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 16K23301
Date: 04-19-16
Test Engineer: Steven Kim
Configuration: EUT / AC Adapter / Earphone / X Position
Mode: Tx, HSDPA,1900MHz

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	Part 24

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1852.4MHz									
3.7048	-7.1	V	3.0	40.5	1.0	-46.6	-13.0	-33.6	
5.5572	-10.9	V	3.0	40.8	1.0	-50.7	-13.0	-37.7	
7.4096	-7.8	V	3.0	40.8	1.0	-47.6	-13.0	-34.6	
3.7048	-12.5	H	3.0	40.5	1.0	-52.0	-13.0	-39.0	
5.5572	-11.5	H	3.0	40.8	1.0	-51.3	-13.0	-38.3	
7.4096	-9.4	H	3.0	40.8	1.0	-49.2	-13.0	-36.2	
Mid Ch, 1880MHz									
3.7600	-4.9	V	3.0	40.5	1.0	-44.4	-13.0	-31.4	
5.6400	-10.4	V	3.0	40.8	1.0	-50.2	-13.0	-37.2	
7.5200	-6.7	V	3.0	40.7	1.0	-46.4	-13.0	-33.4	
3.7600	-7.6	H	3.0	40.5	1.0	-47.1	-13.0	-34.1	
5.6400	-11.2	H	3.0	40.8	1.0	-51.0	-13.0	-38.0	
7.5200	-8.8	H	3.0	40.7	1.0	-48.6	-13.0	-35.6	
High Ch, 1907.6MHz									
3.8152	2.5	V	3.0	40.6	1.0	-37.1	-13.0	-24.1	
5.7228	-8.5	V	3.0	40.8	1.0	-48.3	-13.0	-35.3	
7.6304	-4.6	V	3.0	40.7	1.0	-44.3	-13.0	-31.3	
3.8152	-2.6	H	3.0	40.6	1.0	-42.2	-13.0	-29.2	
5.7228	-10.4	H	3.0	40.8	1.0	-50.2	-13.0	-37.2	
7.6304	-8.7	H	3.0	40.7	1.0	-48.4	-13.0	-35.4	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 41

LTE Band 41 20MHz QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 16K23301
Date: 04-23-16
Test Engineer: Steven Kim
Configuration: EUT / AC Adapter / Ear Phone / X-Position
Mode: TX, LTE BAND 41, 20MHz BW, QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2565 MHz)									
5.1300	-17.2	V	3.0	40.9	1.0	-57.1	-25.0	-32.1	
7.6950	-15.2	V	3.0	40.6	1.0	-54.9	-25.0	-29.9	
10.2600	-11.1	V	3.0	39.5	1.0	-49.6	-25.0	-24.6	
5.1300	-17.1	H	3.0	40.9	1.0	-57.0	-25.0	-32.0	
7.6950	-15.4	H	3.0	40.6	1.0	-55.1	-25.0	-30.1	
10.2600	-13.7	H	3.0	39.5	1.0	-52.2	-25.0	-27.2	
Mid Ch, (2605 MHz)									
5.2100	-16.3	V	3.0	40.9	1.0	-56.2	-25.0	-31.2	
7.8150	-15.0	V	3.0	40.6	1.0	-54.6	-25.0	-29.6	
10.4200	-10.5	V	3.0	39.4	1.0	-48.9	-25.0	-23.9	
5.2100	-16.9	H	3.0	40.9	1.0	-56.8	-25.0	-31.8	
7.8150	-15.5	H	3.0	40.6	1.0	-55.0	-25.0	-30.0	
10.4200	-13.0	H	3.0	39.4	1.0	-51.4	-25.0	-26.4	
High Ch, (2645 MHz)									
5.2900	-17.2	V	3.0	40.9	1.0	-57.1	-25.0	-32.1	
7.9350	-14.4	V	3.0	40.5	1.0	-53.9	-25.0	-28.9	
10.5800	-10.9	V	3.0	39.3	1.0	-49.1	-25.0	-24.1	
5.2900	-17.2	H	3.0	40.9	1.0	-57.1	-25.0	-32.1	
7.9350	-14.1	H	3.0	40.5	1.0	-53.6	-25.0	-28.6	
10.5800	-12.3	H	3.0	39.3	1.0	-50.5	-25.0	-25.5	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

LTE Band 41 20MHz 16QAM

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 16K23301
Date: 04-23-16
Test Engineer: Steven Kim
Configuration: EUT / AC Adapter / Ear Phone / X-Position
Mode: TX, LTE BAND 41, 20MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2565 MHz)									
5.1300	-17.8	V	3.0	40.9	1.0	-57.7	-25.0	-32.7	
7.6950	-15.4	V	3.0	40.6	1.0	-55.1	-25.0	-30.1	
10.2600	-11.5	V	3.0	39.5	1.0	-49.9	-25.0	-24.9	
5.1300	-17.6	H	3.0	40.9	1.0	-57.5	-25.0	-32.5	
7.6950	-15.6	H	3.0	40.6	1.0	-55.2	-25.0	-30.2	
10.2600	-14.6	H	3.0	39.5	1.0	-53.1	-25.0	-28.1	
Mid Ch, (2605 MHz)									
5.2100	-16.8	V	3.0	40.9	1.0	-56.7	-25.0	-31.7	
7.8150	-15.2	V	3.0	40.6	1.0	-54.7	-25.0	-29.7	
10.4200	-10.8	V	3.0	39.4	1.0	-49.2	-25.0	-24.2	
5.2100	-17.2	H	3.0	40.9	1.0	-57.1	-25.0	-32.1	
7.8150	-15.7	H	3.0	40.6	1.0	-55.3	-25.0	-30.3	
10.4200	-13.4	H	3.0	39.4	1.0	-51.8	-25.0	-26.8	
High Ch, (2645 MHz)									
5.2900	-17.7	V	3.0	40.9	1.0	-57.5	-25.0	-32.5	
7.9350	-14.5	V	3.0	40.5	1.0	-54.0	-25.0	-29.0	
10.5800	-11.4	V	3.0	39.3	1.0	-49.7	-25.0	-24.7	
5.2900	-17.8	H	3.0	40.9	1.0	-57.6	-25.0	-32.6	
7.9350	-14.3	H	3.0	40.5	1.0	-53.8	-25.0	-28.8	
10.5800	-12.8	H	3.0	39.3	1.0	-51.1	-25.0	-26.1	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE

Band 41

15MHz

QPSK

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 16K23301
Date: 04-23-16
Test Engineer: Steven Kim
Configuration: EUT / AC Adapter / Ear Phone / X-Position
Mode: TX, LTE BAND 41, 15MHz BW,QPSK

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2562.5 MHz)									
5.1250	-17.1	V	3.0	40.9	1.0	-57.0	-25.0	-32.0	
7.6875	-15.2	V	3.0	40.6	1.0	-54.8	-25.0	-29.8	
10.2500	-11.0	V	3.0	39.5	1.0	-49.5	-25.0	-24.5	
5.1250	-17.1	H	3.0	40.9	1.0	-57.0	-25.0	-32.0	
7.6875	-15.4	H	3.0	40.6	1.0	-55.0	-25.0	-30.0	
10.2500	-13.6	H	3.0	39.5	1.0	-52.1	-25.0	-27.1	
Mid Ch, (2605 MHz)									
5.2100	-16.3	V	3.0	40.9	1.0	-56.2	-25.0	-31.2	
7.8150	-14.9	V	3.0	40.6	1.0	-54.5	-25.0	-29.5	
10.4200	-10.4	V	3.0	39.4	1.0	-48.8	-25.0	-23.8	
5.2100	-16.8	H	3.0	40.9	1.0	-56.7	-25.0	-31.7	
7.8150	-15.5	H	3.0	40.6	1.0	-55.0	-25.0	-30.0	
10.4200	-12.9	H	3.0	39.4	1.0	-51.3	-25.0	-26.3	
High Ch, (2647.5 MHz)									
5.2950	-17.1	V	3.0	40.9	1.0	-57.0	-25.0	-32.0	
7.9425	-14.3	V	3.0	40.5	1.0	-53.7	-25.0	-28.7	
10.5900	-10.8	V	3.0	39.3	1.0	-49.1	-25.0	-24.1	
5.2950	-17.1	H	3.0	40.9	1.0	-57.0	-25.0	-32.0	
7.9425	-14.0	H	3.0	40.5	1.0	-53.4	-25.0	-28.4	
10.5900	-12.2	H	3.0	39.3	1.0	-50.4	-25.0	-25.4	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

LTE

Band 41

15MHz

16QAM

UL Korea, Ltd Suwon Laboratory
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 16K23301
Date: 04-23-16
Test Engineer: Steven Kim
Configuration: EUT / AC Adapter / Ear Phone / X-Position
Mode: TX, LTE BAND 41, 15MHz BW,16QAM

Chamber	Pre-amplifer	Filter	Limit
Chamber 2	AFS42	Filter 1	FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2562.5 MHz)									
5.1250	-17.9	V	3.0	40.9	1.0	-57.8	-25.0	-32.8	
7.6875	-15.3	V	3.0	40.6	1.0	-55.0	-25.0	-30.0	
10.2500	-11.4	V	3.0	39.5	1.0	-49.9	-25.0	-24.9	
5.1250	-17.6	H	3.0	40.9	1.0	-57.5	-25.0	-32.5	
7.6875	-15.4	H	3.0	40.6	1.0	-55.1	-25.0	-30.1	
10.2500	-14.1	H	3.0	39.5	1.0	-52.6	-25.0	-27.6	
Mid Ch, (2605 MHz)									
5.2100	-17.0	V	3.0	40.9	1.0	-56.9	-25.0	-31.9	
7.8150	-14.9	V	3.0	40.6	1.0	-54.5	-25.0	-29.5	
10.4200	-10.8	V	3.0	39.4	1.0	-49.1	-25.0	-24.1	
5.2100	-17.5	H	3.0	40.9	1.0	-57.4	-25.0	-32.4	
7.8150	-15.5	H	3.0	40.6	1.0	-55.1	-25.0	-30.1	
10.4200	-13.7	H	3.0	39.4	1.0	-52.1	-25.0	-27.1	
High Ch, (2647.5 MHz)									
5.2950	-17.9	V	3.0	40.9	1.0	-57.7	-25.0	-32.7	
7.9425	-14.3	V	3.0	40.5	1.0	-53.8	-25.0	-28.8	
10.5900	-11.3	V	3.0	39.3	1.0	-49.6	-25.0	-24.6	
5.2950	-17.8	H	3.0	40.9	1.0	-57.7	-25.0	-32.7	
7.9425	-14.0	H	3.0	40.5	1.0	-53.5	-25.0	-28.5	
10.5900	-12.5	H	3.0	39.3	1.0	-50.7	-25.0	-25.7	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.