



FCC CFR47 PART 15 SUBPART C

Bluetooth Low Energy

CERTIFICATION TEST REPORT

FOR

GSM/WCDMA/LTE Tablet + BT/BLE, DTS/UNII a/b/g/n/ac and ANT+

MODEL NUMBER : SM-T835C

FCC ID: A3LSMT835C

REPORT NUMBER: 4788506351-E2V1

ISSUE DATE: JUL 11, 2018

Prepared for
SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA

Prepared by
UL Korea, Ltd.
26th floor, 152, Teheran-ro, Gangnam-gu Seoul, 06236, Korea

Suwon Test Site: UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433



TL-637

Revision History

Rev.	Issue Date	Revisions	Revised By
V1	07/11/18	Initial issue	Junwhan Lee

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. MEASURING INSTRUMENT CALIBRATION	6
4.2. SAMPLE CALCULATION	6
4.3. MEASUREMENT UNCERTAINTY.....	7
5. EQUIPMENT UNDER TEST	8
5.1. DESCRIPTION OF EUT	8
5.2. MAXIMUM OUTPUT POWER.....	8
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	8
5.4. WORST-CASE CONFIGURATION AND MODE	8
5.5. DESCRIPTION OF TEST SETUP.....	9
6. TEST AND MEASUREMENT EQUIPMENT	11
7. REFERENCE MEASUREMENT RESULTS.....	12
7.1. ON TIME AND DUTY CYCLE RESULTS.....	12
7.2. 99% BANDWIDTH.....	13
8. MEASUREMENT METHODS	16
9. SUMMARY TABLE	17
10. ANTENNA PORT TEST RESULTS	18
10.1. 6 dB BANDWIDTH	18
10.2. OUTPUT POWER	21
10.3. AVERAGE POWER	24
10.4. PSD.....	25
10.5. OUT-OF-BAND EMISSIONS.....	28
11. RADIATED TEST RESULTS	35
11.1. LIMITS AND PROCEDURE.....	35
11.2. TRANSMITTER ABOVE 1 GHz.....	37
11.3. WORST-CASE BELOW 1 GHz	57
12. AC POWER LINE CONDUCTED EMISSIONS	61

13. SETUP PHOTOS66

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.

EUT DESCRIPTION: GSM/WCDMA/LTE Tablet + BT/BLE, DTS/UNII a/b/g/n/ac and ANT+

MODEL NUMBER: SM-T835C

SERIAL NUMBER: R22K500LEAW (RADIATED);
R22K4004WOF (CONDUCTED)

DATE TESTED: JUN 20, 2018 - JUL 11, 2018

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:

Tested By:



SungGil Park
Suwon Lab Engineer
UL Korea, Ltd.

Junwhan Lee
Suwon Lab Engineer
UL Korea, Ltd.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with following methods.

1. FCC CFR 47 Part 2.
2. FCC CFR 47 Part 15.
3. KDB 558074 D01 DTS Meas Guidance v04.
4. ANSI C63.10-2013.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro
☒ Chamber 1
☐ Chamber 2
☒ Chamber 3

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	3.86 dB
Radiated Disturbance, Above 1 GHz	5.97 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE Tablet + BT/BLE, DTS/UNII a/b/g/n/ac and ANT+. This test report addresses the DTS (BLE) operational mode.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum total conducted output power as follows:

Frequency Range [MHz]	Mode	Power Mode	Output Power [dBm]	Output Power [mW]
2402 - 2480	BLE	Peak	3.461	2.22
		Average	3.067	2.03

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an internal antenna, with a maximum gain of -1.84 dBi.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission below 1GHz and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Radiated emission above 1GHz was performed with the EUT set to transmit low/mid/high channels.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Y orientation.

Note : All radiated and power line conducted tests were performed connected with earphone and charger for evaluation of worst case mode.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA200	R37K49A2631DK3	N/A
Data Cable	SAMSUNG	EP-DN930CWE	N/A	N/A
Earphone	SAMSUNG	EO-EG920BW	N/A	N/A

I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	C Type	Shielded	1.1m	N/A
2	Audio	2	Mini-Jack	Unshielded	1.2m	N/A


TEST SETUP

The EUT is a stand-alone unit during the tests.
Test software in hidden menu exercised the EUT to enable BLE mode.


NOTE

Additional tests under 1 GHz were performed with the keyboard attached to check on all port terminated conditions. Keyboard is not an in-box item.

SETUP DIAGRAM FOR TESTS (CONDUCTED TEST SETUP)



SETUP DIAGRAM FOR TESTS (RADIATED TEST SETUP)



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	750	08-31-19
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	09-14-19
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	845	08-31-19
Antenna, Horn, 18 GHz	ETS	3115	00167211	10-14-18
Antenna, Horn, 18 GHz	ETS	3115	00161451	03-10-19
Antenna, Horn, 18 GHz	ETS	3117	00168724	05-31-19
Antenna, Horn, 18 GHz	ETS	3117	00168717	05-31-19
Antenna, Horn, 18 GHz	ETS	3117	00205959	11-29-18
Antenna, Horn, 40 GHz	ETS	3116C	00166155	12-04-19
Antenna, Horn, 40 GHz	ETS	3116C	00168645	12-04-19
Antenna, Horn, 40 GHz	ETS	3116C-PA	00168841	11-13-19
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-09-18
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-07-18
Preamplifier, 1000 MHz	Sonoma	310N	370599	08-10-18
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1876511	08-08-18
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	08-08-18
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	2029169	08-11-18
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	08-08-18
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-08-18
Average Power Sensor	Agilent / HP	U2000	MY54270007	08-08-18
Attenuator	PASTERNAK	PE7087-10	A001	08-08-18
Attenuator	PASTERNAK	PE7087-10	A008	08-08-18
Attenuator	PASTERNAK	PE7087-10	2	08-10-18
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-08-18
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-08-18
EMI Test Receive, 44 GHz	R&S	ESW44	101590	08-09-18
EMI Test Receive, 3 GHz	R&S	ESR3	101832	08-07-18
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	009	08-08-18
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	015	08-08-18
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	020	08-11-18
High Pass Filter 3GHz	Micro-Tronics	HPM17543	010	08-08-18
High Pass Filter 3GHz	Micro-Tronics	HPM17543	015	08-08-18
High Pass Filter 3GHz	Micro-Tronics	HPM17543	020	08-11-18
High Pass Filter 6GHz	Micro-Tronics	HPS17542	009	08-08-18
High Pass Filter 6GHz	Micro-Tronics	HPS17542	016	08-08-18
High Pass Filter 6GHz	Micro-Tronics	HPS17542	021	08-11-18
LISN	R&S	ENV-216	101837	08-09-18
UL Software				
Description	Manufacturer	Model	Version	
Radiated software	UL	UL EMC	Ver 9.5	
AC Line Conducted software	UL	UL EMC	Ver 9.5	


7. REFERENCE MEASUREMENT RESULTS

7.1. ON TIME AND DUTY CYCLE RESULTS

LIMITS

None: for reporting purposes only.

Mode	ON Time B [msec]	Period [msec]	Duty Cycle x [linear]	Duty Cycle [%]	Duty Cycle Correction Factor [dB]	1/T Minimum VBW [kHz]
2400MHz Bands						
BLE (1M)	0.390	0.625	0.624	62.4%	2.05	2.564
BLE (2M)	0.205	0.625	0.328	32.8%	4.85	4.885



7.2. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

TEST PROCEDURE


The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth and to 1% of the span. The VBW is set to ≥ 3 times the RBW. The spectrum analyzer internal 99% bandwidth function is utilized.

RESULTS


Data Rate [Mbps]	Channel	Frequency [MHz]	99% Bandwidth [MHz]
1	Low	2402	1.034
	Mid	2440	1.032
	High	2480	1.041
	Worst		1.041
2	Low	2402	2.037
	Mid	2440	2.035
	High	2480	2.036
	Worst		2.037

99% BANDWIDTH PLOTS

1 Mbps



2 Mbps



8. MEASUREMENT METHODS

6 dB BW : KDB 558074 D01 v04, Section 8.1.

OUTPUT POWER : KDB 558074 D01 v04, Section 9.1.1.

POWER SPECTRAL DENSITY : KDB 558074 D01 v04, Section 10.2.

Out-of-band EMISSIONS (Conducted) : KDB 558074 D01 v04, Section 11.1, 11.2.

Out-of-band EMISSIONS IN NON-RESTRICTED BANDS: KDB 558074 D01 v04, Section 11.0.

Out-of-band EMISSIONS IN RESTRICTED BANDS : KDB 558074 D01 v04, Section 12.1.

AC Power Line Conducted Emission : ANSI C63.10-2013, Section 6.2.

9. SUMMARY TABLE

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result
15.247 (a)(2)	Occupied Band width (6dB)	>500KHz	Conducted	Pass
2.1051, 15.247 (d)	Band Edge / Conducted Spurious Emission	-20dBc		Pass
15.247 (b)(3)	TX conducted output power	<30dBm		Pass
15.247 (e)	PSD	<8dBm		Pass
15.207 (a)	AC Power Line conducted emissions	Section 10	Power Line conducted	Pass
15.205, 15.209	Radiated Spurious Emission	< 54dBuV/m(Av)	Radiated	Pass

10. ANTENNA PORT TEST RESULTS

10.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)

The minimum 6 dB bandwidth shall be at least 500 kHz.

TEST PROCEDURE


Reference to KDB 558074 D01 DTS Meas Guidance v04: The transmitter output is connected to a spectrum analyzer with the RBW set to 100KHz, the VBW $\geq 3 \times$ RBW, peak detector and max hold.

RESULTS


Data Rate [Mbps]	Channel	Frequency [MHz]	6 dB Bandwidth [kHz]	Minimum Limit [kHz]
1	Low	2402	663.70	500.0
	Mid	2440	663.60	500.0
	High	2480	660.07	500.0
	Worst		660.07	500.0
2	Low	2402	1138.00	500.0
	Mid	2440	1144.75	500.0
	High	2480	1135.50	500.0
	Worst		1135.50	500.0

6 dB BANDWIDTH PLOTS

1 Mbps



2 Mbps



10.2. OUTPUT POWER

LIMITS

FCC §15.247 (b)

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 30 dBm.

TEST PROCEDURE


Peak power is measured using KDB558074 D01 DTS Meas Guidance v04 under section 9.1.1 utilizing spectrum analyzer.

RESULTS


Data Rate [Mbps]	Channel	Frequency [MHz]	Peak Power Reading [dBm]	Limit [dBm]	Margin [dB]
1	Low	2402	2.297	30.000	-27.703
	Mid	2440	2.337	30.000	-27.663
	High	2480	3.408	30.000	-26.592
	Worst		3.408	30.000	-26.592
2	Low	2402	2.479	30.000	-27.521
	Mid	2440	2.517	30.000	-27.483
	High	2480	3.461	30.000	-26.539
	Worst		3.461	30.000	-26.539

OUTPUT POWER PLOTS

1 Mbps



2 Mbps



10.3. AVERAGE POWER

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

The cable assembly insertion loss was entered as an offset in the power meter to allow for direct reading of power.

Data Rate [Mbps]	Channel	Frequency [MHz]	AV power [dBm]	AV power [mW]
1	Low	2402	2.061	1.607
	Middle	2440	2.068	1.610
	High	2480	3.067	2.026
2	Low	2402	1.827	1.523
	Middle	2440	1.896	1.547
	High	2480	2.876	1.939

10.4. PSD

LIMITS

FCC §15.247

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST PROCEDURE


Power Spectral Density was performed utilizing the “§10.2 Method PKPSD (Peak PSD)” under KDB558074 D01 DTS Meas Guidance v04

RESULTS


Data Rate	Channel	Frequency	PSD	Limit	Margin
[Mbps]		[MHz]	[dBm/3kHz]	[dBm/3kHz]	[dB]
1	Low	2402	-12.60	8.00	-20.60
	Mid	2440	-12.59	8.00	-20.59
	High	2480	-11.60	8.00	-19.60
2	Low	2402	-16.25	8.00	-24.25
	Mid	2440	-16.20	8.00	-24.20
	High	2480	-15.22	8.00	-23.22

POWER SPECTRAL DENSITY PLOTS

1 Mbps



2 Mbps



10.5. OUT-OF-BAND EMISSIONS

LIMITS

FCC §15.247 (d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.


TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer with RBW = 100 kHz, VBW = 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, bandedge (where measurements to the general radiated limits will not be made) and out-of-band emissions.


RESULTS

BANDEDGE & SPURIOUS EMISSIONS, LOW CHANNEL


1 Mbps



SPURIOUS EMISSIONS, MID CHANNEL




SPURIOUS EMISSIONS, HIGH CHANNEL




BANDEDGE & SPURIOUS EMISSIONS, LOW CHANNEL


2 Mbps



SPURIOUS EMISSIONS, MID CHANNEL



SPURIOUS EMISSIONS, HIGH CHANNEL



11. RADIATED TEST RESULTS

11.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (μV/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane for below 1GHz and 150 cm for above 1GHz. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and add duty cycle factor for average measurements. (Restricted bandedge, Final detection of spurious harmonic emissions) Duty cycle factor = $10 \log(1/x)$. For this sample: DCF = $10 \log(1/0.624) = 2.05\text{dB}$
(Spectrum Analyzer round it up to 2.05dB)

Pre-scans to detect harmonic and spurious emissions, the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 30 KHz for peak measurements.

The spectrum from 1 GHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.
(From 30MHz to 1GHz, test was performed with the EUT set to transmit at the channel with highest output power)

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

Note : Emission was pre-scanned from 9KHz to 30MHz; No emissions were detected which was at least 20dB below the specification limit (consider distance correction factor).
Per FCC part 15.31(o), test results were not reported.


Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open area test site.
Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the one of tests made in an open field based on KDB 414788.

11.2. TRANSMITTER ABOVE 1 GHz

1 Mbps

RESTRICTED BANDEDGE (LOW CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00205959)	10dB_ATT(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Altitude (Degs)	Height (cm)	Polarity
1	* 2.39	42.58	Pk	31.8	-23.3	0	51.08	-	-	74	-22.92	296	132	H
2	* 2.388	45.06	Pk	31.8	-23.3	0	53.56	-	-	74	-20.44	296	132	H
3	* 2.39	32.49	RMS	31.8	-23.3	2.05	43.04	54	-10.96	-	-	296	132	H
4	* 2.333	33.69	RMS	31.6	-23.2	2.05	44.14	54	-9.86	-	-	296	132	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	311700205959	10dB_ATT(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Pk Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	42.94	Pk		-23.3	0	51.44	-	-	74	-22.56	77	156	V
2	* 2.355	44.62	Pk		-23.3	0	53.02	-	-	74	-20.98	77	156	V
3	* 2.39	31.89	RMS		-23.3	2.05	42.44	54	-11.56	-	-	77	156	V
4	* 2.366	33.5	RMS		-23.3	2.05	43.95	54	-10.05	-	-	77	156	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

AUTHORIZED BANDEDGE (HIGH CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117[00205959]	10dB_ATT[dB]	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Altitude (Degs)	Height (cm)	Polarity
1	* 2.484	42.38	Pk	32.1	-23	0	51.48	-	-	74	-22.52	237	127	H
2	* 2.49	45.81	Pk	32.1	-23.1	0	54.81	-	-	74	-19.19	237	127	H
3	* 2.484	32.5	RMS	32.1	-23	2.05	43.65	54	-10.35	-	-	237	127	H
4	* 2.486	33.7	RMS	32.1	-23.1	2.05	44.75	54	-9.25	-	-	237	127	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00205959)	10dB_ATT(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Asimuth (Degs)	Height (cm)	Polarity
1	* 2.484	42.71	Pk	32.1	-23	0	51.81	-	-	74	-22.19	85	160	V
2	2.509	45.31	Pk	32.1	-23.2	0	54.21	-	-	74	-19.79	85	160	V
3	* 2.484	31.49	RMS	32.1	-23	2.05	42.64	54	-11.36	-	-	85	160	V
4	* 2.493	33.4	RMS	32.1	-23.1	2.05	44.45	54	-9.55	-	-	85	160	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector


RMS - RMS detection

HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00205959)	3GHz_HP(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.804	30.23	PK	33.9	-28.2	0	35.93	-	-	74	-38.07	0-360	152	H
3	7.207	25.46	PK	35.6	-24	0	37.06	-	-	74	-36.94	0-360	152	H
5	9.609	22.83	PK	36.7	-19.9	0	39.63	-	-	74	-34.37	0-360	250	H
2	* 4.805	30.06	PK	33.9	-28.2	0	35.76	-	-	74	-38.24	0-360	149	V
4	7.207	25.04	PK	35.6	-24	0	36.64	-	-	74	-37.36	0-360	149	V
6	9.609	23.04	PK	36.7	-19.9	0	39.84	-	-	74	-34.16	0-360	149	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band


PK – Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

MID CHANNEL HORIZONTAL



MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00205959)	3GHz_HP(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.881	30.2	PK	34	-28.9	0	35.3	-	-	74	-38.7	0-360	150	H
3	* 7.32	24.3	PK	35.6	-23.4	0	36.5	-	-	74	-37.5	0-360	250	H
5	9.759	22.48	PK	36.9	-19.5	0	39.88	-	-	74	-34.12	0-360	250	H
2	* 4.881	29.84	PK	34	-28.9	0	34.94	-	-	74	-39.06	0-360	250	V
4	* 7.32	24.67	PK	35.6	-23.4	0	36.87	-	-	74	-37.13	0-360	250	V
6	9.76	22.91	PK	36.9	-19.5	0	40.31	-	-	74	-33.69	0-360	149	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band


PK – Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

HIGH CHANNEL HORIZONTAL



HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00205959)	3GHz_HP(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.96	29.28	PK	34.1	-28.5	0	34.88	-	-	74	-39.12	0-360	150	H
3	* 7.441	25.09	PK	35.6	-23.2	0	37.49	-	-	74	-36.51	0-360	150	H
5	9.92	21.8	PK	37	-19.7	0	39.1	-	-	74	-34.9	0-360	150	H
2	* 4.96	29.44	PK	34.1	-28.5	0	35.04	-	-	74	-38.96	0-360	250	V
4	* 7.44	25.01	PK	35.6	-23.2	0	37.41	-	-	74	-36.59	0-360	250	V
6	9.92	22.09	PK	37	-19.7	0	39.39	-	-	74	-34.61	0-360	250	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
PK – Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

2 Mbps

RESTRICTED BANDEDGE (LOW CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117[0020599]	10dB_ATT[dB]	DC Corr [dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	41.87	Pk	31.8	-23.3	0	50.37	-	-	74	-23.63	296	130	H
2	* 2.36	45.34	Pk	31.7	-23.3	0	53.74	-	-	74	-20.26	296	130	H
3	* 2.39	32.79	RMS	31.8	-23.3	4.85	46.14	54	-7.86	-	-	296	130	H
4	* 2.374	33.75	RMS	31.7	-23.2	4.85	47.1	54	-6.9	-	-	296	130	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	311700205959	10dB_ATT(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Asimuth (Degs)	Height (cm)	Polarity
1	* 2.39	42.23	Pk	31.8	-23.3	0	50.73	-	-	74	-23.27	77	156	V
2	* 2.374	45.42	Pk	31.7	-23.2	0	53.92	-	-	74	-20.08	77	156	V
3	* 2.39	31.45	RMS	31.8	-23.3	4.85	44.8	54	-9.2	-	-	77	156	V
4	* 2.388	33.5	RMS	31.8	-23.3	4.85	46.85	54	-7.15	-	-	77	156	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

AUTHORIZED BANDEDGE (HIGH CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117[00205959]	10dB_ATT[dB]	DC Corr [dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Altitude (Degs)	Height (cm)	Polarity
1	* 2.484	42.71	Pk	32.1	-23	0	51.81	-	-	74	-22.19	237	124	H
2	2.523	45.13	Pk	32.1	-23.1	0	54.13	-	-	74	-19.87	237	124	H
3	* 2.484	31.95	RMS	32.1	-23	4.85	45.9	54	-8.1	-	-	237	124	H
4	2.561	33.29	RMS	32.1	-22.8	4.85	47.44	54	-6.56	-	-	237	124	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00205959)	10dB_ATT(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Asimuth (Degs)	Height (cm)	Polarity
1	* 2.484	41.67	Pk	32.1	-23	0	50.77	-	-	74	-23.23	85	160	V
2	2.548	45.23	Pk	32.1	-23	0	54.33	-	-	74	-19.67	85	160	V
3	* 2.484	31.7	RMS	32.1	-23	4.85	45.65	54	-8.35	-	-	85	160	V
4	2.546	33.69	RMS	32.1	-23	4.85	47.64	54	-6.36	-	-	85	160	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector


RMS - RMS detection

HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00205959)	3GHz_HP(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.805	30.06	PK	33.9	-28.2	0	35.76	-	-	74	-38.24	0-360	250	H
3	7.206	25.51	PK	35.6	-23.9	0	37.21	-	-	74	-36.79	0-360	250	H
5	9.609	23.22	PK	36.7	-19.9	0	40.02	-	-	74	-33.98	0-360	152	H
2	* 4.805	29.68	PK	33.9	-28.2	0	35.38	-	-	74	-38.62	0-360	150	V
4	7.206	25.86	PK	35.6	-23.9	0	37.56	-	-	74	-36.44	0-360	150	V
6	9.609	22.94	PK	36.7	-19.9	0	39.74	-	-	74	-34.26	0-360	150	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band


PK – Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

MID CHANNEL HORIZONTAL



MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00205959)	3GHz_HP(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.881	30.19	PK	34	-28.9	0	35.29	-	-	74	-38.71	0-360	250	H
5	9.761	23.23	PK	36.9	-19.5	0	40.63	-	-	74	-33.37	0-360	150	H
2	* 4.881	29.87	PK	34	-28.9	0	34.97	-	-	74	-39.03	0-360	250	V
3	* 7.32	24.3	PK	35.6	-23.4	0	36.5	-	-	74	-37.5	0-360	250	V
4	* 7.32	24.3	PK	35.6	-23.4	0	36.5	-	-	74	-37.5	0-360	250	V
6	9.761	22.94	PK	36.9	-19.5	0	40.34	-	-	74	-33.66	0-360	250	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band


PK – Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

HIGH CHANNEL HORIZONTAL



HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(00205959)	3GHz_HP(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.96	29.58	PK	34.1	-28.5	0	35.18	-	-	74	-38.82	0-360	150	H
3	* 7.44	24.46	PK	35.6	-23.2	0	36.86	-	-	74	-37.14	0-360	150	H
5	9.921	21.75	PK	37	-19.7	0	39.05	-	-	74	-34.95	0-360	250	H
2	* 4.96	29.48	PK	34.1	-28.5	0	35.08	-	-	74	-38.92	0-360	250	V
4	* 7.44	24.42	PK	35.6	-23.2	0	36.82	-	-	74	-37.18	0-360	250	V
6	9.92	21.62	PK	37	-19.7	0	38.92	-	-	74	-35.08	0-360	150	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band


PK – Peak Detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).


11.3. WORST-CASE BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz

HORIZONTAL PLOT



VERTICAL PLOT



BELOW 1 GHz TABLE

Trace Markers


Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	750_20170831	30-1000MHz[dB]	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	78.597	42.32	Pk	12.9	-28.6	26.62	40	-13.38	0-360	200	H
2	* 120.695	40.22	Pk	15.7	-28.2	27.72	43.52	-15.8	0-360	200	H
3	217.404	32.57	Pk	17.1	-27.5	22.17	46.02	-23.85	0-360	200	H
4	36.499	44.41	Pk	17.2	-29.9	31.71	40	-8.29	0-360	100	V
5	40.864	41.07	Pk	18.8	-29.4	30.47	40	-9.53	0-360	100	V
6	77.433	42.72	Pk	13	-28.8	26.92	40	-13.08	0-360	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band


Pk - Peak detector

SPURIOUS EMISSIONS 30 TO 1000 MHz (EQUIPPED WITH KEYBOARD)

HORIZONTAL PLOT



VERTICAL PLOT



BELOW 1 GHz TABLE

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	750_20170831	30-1000MHz[dB]	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 119.822	53	Pk	15.9	-28.1	40.8	43.52	-2.72	0-360	300	H
2	* 122.926	54.05	Pk	15.4	-28.2	41.25	43.52	-2.27	0-360	400	H
3	* 129.91	56	Pk	14.4	-28	42.4	43.52	-1.12	0-360	200	H
4	149.892	55.94	Pk	13.8	-27.9	41.84	43.52	-1.68	0-360	300	H
5	152.802	57.4	Pk	13.9	-27.8	43.5	43.52	-.02	0-360	200	H
6	335.744	49.65	Pk	20.3	-26.7	43.25	46.02	-2.77	0-360	100	H
7	71.904	52.74	Pk	14.5	-28.9	38.34	40	-1.66	0-360	100	V
8	* 74.911	52.12	Pk	13.4	-29	36.52	40	-3.48	0-360	400	V
9	145.915	53.97	Pk	13.7	-27.8	39.87	43.52	-3.65	0-360	100	V
10	150.862	56.85	Pk	13.8	-27.9	42.75	43.52	-.77	0-360	200	V
11	159.883	48.51	Pk	14.4	-27.8	35.11	43.52	-8.41	0-360	300	V
12	335.938	42.48	Pk	20.4	-26.7	36.18	46.02	-9.84	0-360	200	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

Radiated Emissions

Frequency (MHz)	Meter Reading (dBuV)	Det	750_20170831	30-1000MHz[dB]	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 119.9414	38.24	Qp	15.9	-28.1	26.04	43.52	-17.48	141	197	H
* 123.1564	35.38	Qp	15.3	-28.2	22.48	43.52	-21.04	147	190	H
* 130.1177	29.55	Qp	14.4	-28	15.95	43.52	-27.57	163	225	H
* 149.9777	42.18	Qp	13.8	-27.9	28.08	43.52	-15.44	193	241	H
152.6957	34.54	Qp	13.9	-27.8	20.64	43.52	-22.88	13	244	H
335.9534	24.03	Qp	20.4	-26.7	17.73	46.02	-28.29	148	342	H
72.0698	39.19	Qp	14.5	-28.9	24.79	40	-15.21	95	140	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Qp - Quasi-Peak detector

12. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 [*]	56 to 46 [*]
0.5-5	56	46
5-30	60	50

^{*} Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

WORST EMISSIONS

LINE 1 PLOT



LINE 1 RESULTS

Trace Markers

Range 1: Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_L1_with extension	CABLELOSS(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
1	.195	42.67	Pk	9.8	.2	52.67	63.82	-11.15	-	-
2	.195	26.89	Av	9.8	.2	36.89	-	-	53.82	-16.93
3	.252	38.82	Pk	9.5	.2	48.52	61.69	-13.17	-	-
4	.264	21.02	Av	9.5	.2	30.72	-	-	51.3	-20.58
5	.696	27.53	Pk	9.7	.2	37.43	56	-18.57	-	-
6	.696	18.56	Av	9.7	.2	28.46	-	-	46	-17.54
7	1.467	25.87	Pk	9.9	.3	36.07	56	-19.93	-	-
8	1.485	11.91	Av	9.9	.3	22.11	-	-	46	-23.89
9	12.882	25.97	Pk	9.8	.4	36.17	60	-23.83	-	-
10	12.87	12.55	Av	9.8	.4	22.75	-	-	50	-27.25
11	21.948	31.17	Pk	10.1	.4	41.67	60	-18.33	-	-
12	21.945	14.12	Av	10.1	.4	24.62	-	-	50	-25.38

Pk - Peak detector

Av - Average detection


Quasi-Peak Emissions

Range 1: Phase L1 .15 - 30MHz

Frequency (MHz)	Meter Reading (dBuV)	Det	101837_L1_with extension	CABLELOSS(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
.19575	35.26	Qp	9.8	.2	45.26	63.79	-18.53	-	-
.25275	27.95	Qp	9.5	.2	37.65	61.67	-24.02	-	-
.26475	29.6	Qp	9.5	.2	39.3	61.28	-21.98	-	-
.69675	22.84	Qp	9.7	.2	32.74	56	-23.26	-	-
1.46625	15.23	Qp	9.9	.3	25.43	56	-30.57	-	-
1.48575	16.08	Qp	9.9	.3	26.28	56	-29.72	-	-
12.8822	19.46	Qp	9.8	.4	29.66	60	-30.34	-	-
12.8702	19.34	Qp	9.8	.4	29.54	60	-30.46	-	-
21.9482	25.38	Qp	10.1	.4	35.88	60	-24.12	-	-
21.9452	25.38	Qp	10.1	.4	35.88	60	-24.12	-	-

Qp - Quasi-Peak detector

LINE 2 PLOT



LINE 2 RESULTS

Trace Markers

Range 2: Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_N_with extension	CABLELOSS(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
13	.192	40.54	Pk	9.9	.2	50.64	63.95	-13.31	-	-
14	.201	21.92	Av	9.8	.2	31.92	-	-	53.57	-21.65
15	.252	35.53	Pk	9.6	.2	45.33	61.69	-16.36	-	-
16	.261	18.59	Av	9.6	.2	28.39	-	-	51.4	-23.01
17	.708	23.49	Pk	9.8	.2	33.49	56	-22.51	-	-
18	.699	9.83	Av	9.8	.2	19.83	-	-	46	-26.17
19	3.153	25.8	Pk	9.8	.3	35.9	56	-20.1	-	-
20	3.144	8.44	Av	9.8	.3	18.54	-	-	46	-27.46
21	13.113	27.6	Pk	9.8	.4	37.8	60	-22.2	-	-
22	13.116	12.47	Av	9.8	.4	22.67	-	-	50	-27.33
23	20.79	33.32	Pk	10.1	.4	43.82	60	-16.18	-	-
24	20.778	16.78	Av	10.1	.4	27.28	-	-	50	-22.72

Pk - Peak detector

Av - Average detection

Quasi-Peak Emissions

Range 2: Phase N .15 - 30MHz

Frequency (MHz)	Meter Reading (dBuV)	Det	101837_N_with extension	CABLELOSS(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
.19275	32.04	Qp	9.9	.2	42.14	63.92	-21.78	-	-
.20025	33.18	Qp	9.8	.2	43.18	63.6	-20.42	-	-
.25275	25.73	Qp	9.6	.2	35.53	61.67	-26.14	-	-
.26175	27.05	Qp	9.6	.2	36.85	61.38	-24.53	-	-
.70725	17.9	Qp	9.8	.2	27.9	56	-28.1	-	-
.69825	19.29	Qp	9.8	.2	29.29	56	-26.71	-	-
3.15375	15.84	Qp	9.8	.3	25.94	56	-30.06	-	-
3.14325	16.14	Qp	9.8	.3	26.24	56	-29.76	-	-
13.1132	19.41	Qp	9.8	.4	29.61	60	-30.39	-	-
13.1153	19.37	Qp	9.8	.4	29.57	60	-30.43	-	-
20.7893	27.22	Qp	10.1	.4	37.72	60	-22.28	-	-
20.7773	27.03	Qp	10.1	.4	37.53	60	-22.47	-	-

Qp - Quasi-Peak detector