








LTE Band 41









9.4. FREQUENCY STABILITY

RULE PART(S)

FCC: §2.1055, §22.355, §24.235 and §27.54

LIMITS

§22.355 - The carrier frequency shall not depart from the reference frequency in excess of ± 2.5 ppm for mobile stations.

§24.235 - The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

§27.54 - The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

TEST PROCEDURE

Per KDB 971168 D01 Power Meas License Digital Systems v03r01

RESULTS

See the following pages.

9.4.1. FREQUENCY STABILITY RESULTS

GSM 850

Reference Frequency : GSM850 Low Channel 824.2 MHz / High Channel 848.8 MHz @ 20°C						
Limit: +- 2.5 ppm =		Low Channel	2060.500	Hz	High Channel	2122.000
		Frequency Deviation Measured with Time Elapse				
Power Supply [Vdc]	Environment Temperature [°C]	Low Channel		High Channel		Limit [ppm]
		[MHz]	Delta [ppm]	[MHz]	Delta [ppm]	
3.85	50	824.19998618	0.005	848.79998792	0.000	2.5
3.85	40	824.19998043	0.012	848.79998452	0.004	2.5
3.85	30	824.19998398	0.007	848.79998766	0.001	2.5
3.85	20	824.19999010	0.000	848.79998813	0.000	2.5
3.85	10	824.19998239	0.009	848.79998781	0.000	2.5
3.85	0	824.19998624	0.005	848.79998856	-0.001	2.5
3.85	-10	824.19998532	0.006	848.79998656	0.002	2.5
3.85	-20	824.19998847	0.002	848.79998178	0.007	2.5
3.85	-30	824.19998687	0.004	848.79998126	0.008	2.5

Reference Frequency : GSM850 Low Channel 824.2 MHz / High Channel 848.8 MHz @ 20°C						
Limit: +- 2.5 ppm =		Low Channel	2060.500	Hz	High Channel	2122.000
		Frequency Deviation Measured with Time Elapse				
Power Supply [Vdc]	Environment Temperature [°C]	Low Channel		High Channel		Limit [ppm]
		[MHz]	Delta [ppm]	[MHz]	Delta [ppm]	
3.85	20	824.19999010	0	848.79998813	0	2.5
4.35	20	824.19998922	0.001	848.79998705	0.001	2.5
3.65	20	824.19998679	0.004	848.79998220	0.007	2.5

GSM 1900

Limit		1850	1910	Delta (Hz)	Frequency Stability (ppm)
Condition		F low @ End of OBW	F high @ End of OBW		
Temperature	Voltage	(MHz)	(MHz)		
Normal (20C)	Normal	1850.0778	1909.9233		
Extreme (50C)		1850.0777	1909.9233	-22.2	-0.012
Extreme (40C)		1850.0777	1909.9233	-14.4	-0.008
Extreme (30C)		1850.0777	1909.9233	-17.6	-0.009
Extreme (10C)		1850.0777	1909.9233	-22.8	-0.012
Extreme (0C)		1850.0777	1909.9233	-23.0	-0.012
Extreme (-10C)		1850.0777	1909.9233	-19.6	-0.010
Extreme (-20C)		1850.0777	1909.9233	-22.3	-0.012
Extreme (-30C)		1850.0777	1909.9233	-24.0	-0.013
20C	15%	1850.0777	1909.9233	-20.8	-0.011
	-15%	1850.0777	1909.9233	-15.8	-0.008
	End Point	1850.0777	1909.9233	-15.3	-0.008

WCDMA Band 5

Reference Frequency : WCDMA Band 5 Low Channel 826.4 MHz / High Channel 846.6 MHz @ 20°C						
Limit: +/- 2.5 ppm =		Low Channel	2066.000	Hz	High Channel	2116.500
Frequency Deviation Measured with Time Elapse						
Power Supply [Vdc]	Environment Temperature [°C]	Low Channel		High Channel		Limit [ppm]
		[MHz]	Delta [ppm]	[MHz]	Delta [ppm]	
3.85	50	826.39998342	-0.003	846.59998137	0.011	2.5
3.85	40	826.39998453	-0.005	846.59998004	0.012	2.5
3.85	30	826.39998736	-0.008	846.59998032	0.012	2.5
3.85	20	826.39998056	0.000	846.59999039	0.000	2.5
3.85	10	826.39998119	-0.001	846.59998459	0.007	2.5
3.85	0	826.39998461	-0.005	846.59998858	0.002	2.5
3.85	-10	826.39998622	-0.007	846.59998253	0.009	2.5
3.85	-20	826.39998111	-0.001	846.59998537	0.006	2.5
3.85	-30	826.39998379	-0.004	846.59998191	0.010	2.5

Reference Frequency : WCDMA Band 5 Low Channel 826.4 MHz / High Channel 846.6 MHz @ 20°C						
Limit: +/- 2.5 ppm =		Low Channel	2066.000	Hz	High Channel	2116.500
Frequency Deviation Measured with Time Elapse						
Power Supply [Vdc]	Environment Temperature [°C]	Low Channel		High Channel		Limit [ppm]
		[MHz]	Delta [ppm]	[MHz]	Delta [ppm]	
3.85	20	826.39998056	0	846.59999039	0	2.5
4.35	20	826.39998409	-0.004	846.59998225	0.010	2.5
3.65	20	826.39998180	-0.002	846.59998986	0.001	2.5

WCDMA Band 2

Limit		1850	1910	Delta (Hz)	Frequency Stability (ppm)
Condition		F low @ End of OBW	F high @ End of OBW		
Temperature	Voltage	(MHz)	(MHz)		
Normal (20C)	Normal	1852.3979	1907.6021		
Extreme (50C)		1852.3979	1907.6020	-21.9	-0.012
Extreme (40C)		1852.3979	1907.6020	-18.0	-0.010
Extreme (30C)		1852.3979	1907.6020	-19.0	-0.010
Extreme (10C)		1852.3979	1907.6020	-24.9	-0.013
Extreme (0C)		1852.3979	1907.6020	-16.9	-0.009
Extreme (-10C)		1852.3979	1907.6020	-21.8	-0.012
Extreme (-20C)		1852.3979	1907.6020	-18.2	-0.010
Extreme (-30C)		1852.3979	1907.6020	-18.0	-0.010
20C	15%	1852.3979	1907.6020	-16.3	-0.009
	-15%	1852.3979	1907.6020	-24.5	-0.013
	End Point	1852.3979	1907.6020	-19.7	-0.010

LTE Band 5

Reference Frequency : LTE Band 5 Low Channel 824.7 MHz / High Channel 848.3 MHz @ 20°C						
Limit: +/- 2.5 ppm =		Low Channel	2061.750	Hz	High Channel	2120.750
		Frequency Deviation Measured with Time Elapse				
Power Supply [Vdc]	Environment Temperature [°C]	Low Channel		High Channel		Limit [ppm]
		[MHz]	Delta [ppm]	[MHz]	Delta [ppm]	
3.85	50	824.69998964	-0.007	848.29998837	0.000	2.5
3.85	40	824.69998503	-0.001	848.29998750	0.001	2.5
3.85	30	824.69998719	-0.004	848.29999086	-0.003	2.5
3.85	20	824.69998407	0.000	848.29998825	0.000	2.5
3.85	10	824.69998365	0.001	848.29998599	0.003	2.5
3.85	0	824.69998143	0.003	848.29998049	0.009	2.5
3.85	-10	824.69998051	0.004	848.29998563	0.003	2.5
3.85	-20	824.69998166	0.003	848.29998808	0.000	2.5
3.85	-30	824.69998876	-0.006	848.29998677	0.002	2.5

Reference Frequency : LTE Band 5 Low Channel 824.7 MHz / High Channel 848.3 MHz @ 20°C						
Limit: +/- 2.5 ppm =		Low Channel	2061.750	Hz	High Channel	2120.750
		Frequency Deviation Measured with Time Elapse				
Power Supply [Vdc]	Environment Temperature [°C]	Low Channel		High Channel		Limit [ppm]
		[MHz]	Delta [ppm]	[MHz]	Delta [ppm]	
3.85	20	824.69998407	0	848.29998825	0	2.5
4.35	20	824.69998084	0.004	848.29998750	0.001	2.5
3.65	20	824.69998914	-0.006	848.29998541	0.003	2.5

LTE Band 12

Limit		699	716	Delta (Hz)	Frequency Stability (ppm)
Condition		F low @ End of OBW	F high @ End of OBW		
Temperature	Voltage	(MHz)	(MHz)		
Normal (20C)	Normal	699.6995	715.3005		
Extreme (50C)		699.6994	715.3005	-5.6	-0.008
Extreme (40C)		699.6994	715.3005	-7.6	-0.011
Extreme (30C)		699.6994	715.3005	-6.5	-0.009
Extreme (10C)		699.6994	715.3005	-8.9	-0.013
Extreme (0C)		699.6994	715.3005	-4.6	-0.006
Extreme (-10C)		699.6994	715.3005	-8.3	-0.012
Extreme (-20C)		699.6994	715.3005	-14.2	-0.020
Extreme (-30C)		699.6994	715.3005	-14.7	-0.021
20C	15%	699.6994	715.3005	-13.3	-0.019
	-15%	699.6994	715.3005	-8.7	-0.012
	End Point	699.6994	715.3005	-14.5	-0.021

LTE Band 17

LTE Band 17 (Frequency range: 704-716 MHz) is covered by LTE Band 12 (Frequency range: 699-716 MHz) due to overlapping frequency range, same maximum tune-up limit and same channel bandwidth.

LTE Band 41

Limit		2496	2690	Delta (Hz)	Frequency Stability (ppm)
Condition		F low @ End of OBW	F high @ End of OBW		
Temperature	Voltage	(MHz)	(MHz)		
Normal (20C)	Normal	2498.4978	2687.5022		
Extreme (50C)		2498.4977	2687.5022	-19.8	-0.008
Extreme (40C)		2498.4977	2687.5022	-26.6	-0.010
Extreme (30C)		2498.4977	2687.5022	-24.9	-0.010
Extreme (10C)		2498.4977	2687.5022	-23.6	-0.009
Extreme (0C)		2498.4977	2687.5022	-27.2	-0.010
Extreme (-10C)		2498.4977	2687.5022	-20.6	-0.008
Extreme (-20C)		2498.4977	2687.5022	-25.4	-0.010
Extreme (-30C)		2498.4977	2687.5022	-26.6	-0.010
20C	15%	2498.4977	2687.5022	-29.8	-0.012
	-15%	2498.4977	2687.5022	-21.6	-0.008
	End Point	2498.4977	2687.5022	-22.2	-0.009

10. RADIATED TEST RESULTS

10.1. RADIATED POWER (ERP & EIRP)

RULE PART(S)

FCC: §2.1046, §22.913, §24.232 and §27.50

LIMITS

22.913(a) - The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

24.232(c) - Mobile/portable stations are limited to 2 watts e.i.r.p. peak power and the equipment must employ means to limit the power to the minimum necessary for successful communications.

27.50(h) - (2) Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

27.50(c) (10) - Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

In addition, when the transmitter power is measured in terms of average value, the peak-to-average ratio of the power shall not exceed 13dB.

TEST PROCEDURE

ANSI / TIA / EIA 603 E Clause 2.2.17; ESU40 setting reference to 971168 D01 v03r01

For radiated output power measurement with a ESU40:

a) Set the RBW $\geq$ OBW; b) Set VBW $\geq 3 \times$ RBW; c) Set span $\geq 2 \times$ RBW; d) Sweep time = auto couple; e) Detector = rms; f) Ensure that the number of measurement points $\geq$ span/RBW; g) Trace mode = max hold(GSM, WCDMA), average(LTE);

TEST RESULTS

10.1.1. ERP/EIRP Results

GSM

Band	Mode	Channel	f [MHz]	ERP / EIRP	
				[dBm]	[mW]
GSM850	GPRS	512	824.2	30.63	1156.11
		661	836.6	30.40	1096.48
		810	848.8	30.71	1177.61
	EGPRS	512	824.2	24.61	289.07
		661	836.6	24.01	251.77
		810	848.8	24.95	312.61
GSM1900	GPRS	512	1850.2	30.24	1056.82
		661	1880.0	30.25	1059.25
		810	1909.8	28.84	765.60
	EGPRS	512	1850.2	26.11	408.32
		661	1880.0	25.27	336.51
		810	1909.8	25.57	360.58

WCDMA

Band	Mode	Channel	f [MHz]	ERP / EIRP	
				[dBm]	[mW]
Band 5	REL99	4132	826.4	21.39	137.72
		4183	836.6	20.31	107.40
		4233	846.6	20.16	103.75
	HSDPA	4132	826.4	20.56	113.76
		4183	836.6	19.54	89.95
		4233	846.6	19.08	80.91
Band 2	REL99	9262	1852.4	21.91	155.24
		9400	1880.0	21.64	145.88
		9538	1907.6	20.85	121.62
	HSDPA	9262	1852.4	21.30	134.90
		9400	1880.0	21.29	134.59
		9538	1907.6	20.24	105.68

LTE Band 5

Band	BW [MHz]	Mode	RB size / RB Offset	f [MHz]	ERP / EIRP	
					[dBm]	[mW]
Band 5	10	QPSK	1/0	829.0	23.34	215.77
			1/0	836.5	22.88	194.09
			1/0	844.0	22.88	194.09
		16QAM	1/0	829.0	22.23	167.11
			1/0	836.5	21.95	156.68
			1/0	844.0	21.70	147.91
	5	QPSK	1/0	826.5	23.32	214.78
			1/0	836.5	23.13	205.59
			1/0	846.5	22.73	187.50
		16QAM	1/0	826.5	22.46	176.20
			1/0	836.5	21.80	151.36
			1/0	846.5	21.76	149.97
	3	QPSK	1/8	825.5	23.55	226.46
			1/8	836.5	22.83	191.87
			1/8	847.5	21.86	153.46
		16QAM	1/8	825.5	22.18	165.20
			1/8	836.5	21.76	149.97
			1/8	847.5	20.74	118.58
	1.4	QPSK	1/3	824.7	23.37	217.27
			1/3	836.5	22.69	185.78
			1/3	848.3	21.37	137.09
		16QAM	1/3	824.7	22.31	170.22
			1/3	836.5	21.61	144.88
			1/3	848.3	20.19	104.47

LTE Band 12

Band	BW [MHz]	Mode	RB size / RB Offset	f [MHz]	ERP / EIRP	
					[dBm]	[mW]
Band 12	10	QPSK	1/0	704.0	16.80	47.86
			1/0	707.5	17.03	50.47
			1/0	711.0	17.16	52.00
		16QAM	1/0	704.0	15.62	36.48
			1/0	707.5	16.01	39.90
			1/0	711.0	15.97	39.54
	5	QPSK	1/0	701.5	16.70	46.77
			1/0	707.5	17.07	50.93
			1/0	713.5	16.57	45.39
		16QAM	1/0	701.5	15.40	34.67
			1/0	707.5	16.10	40.74
			1/0	713.5	15.80	38.02
	3	QPSK	1/8	700.5	16.72	46.99
			1/8	707.5	16.60	45.71
			1/8	714.5	16.59	45.60
		16QAM	1/8	700.5	15.59	36.22
			1/0	707.5	15.41	34.75
			1/8	714.5	15.49	35.40
	1.4	QPSK	1/3	699.7	16.53	44.98
			1/3	707.5	16.95	49.55
			1/3	715.3	16.31	42.76
		16QAM	1/3	699.7	15.48	35.32
			1/3	707.5	15.68	36.98
			1/3	715.3	15.28	33.73

LTE Band 17

LTE Band 17 (Frequency range: 704-716 MHz) is covered by LTE Band 12 (Frequency range: 699-716 MHz) due to overlapping frequency range, same maximum tune-up limit and same channel bandwidth.

LTE Band 41

Band	BW [MHz]	Mode	RB size / RB Offset	f [MHz]	ERP / EIRP	
					[dBm]	[mW]
Band 41	20	QPSK	1/0	2506.0	23.56	226.99
			1/0	2593.0	24.84	304.79
			1/0	2680.0	22.20	165.96
		16QAM	1/0	2506.0	22.41	174.18
			1/0	2593.0	25.26	335.74
			1/0	2680.0	21.76	149.97
	15	QPSK	1/0	2503.5	21.86	153.46
			1/0	2593.0	23.24	210.86
			1/0	2682.5	21.94	156.31
		16QAM	1/0	2503.5	22.23	167.11
			1/0	2593.0	23.56	226.99
			1/0	2682.5	21.28	134.28
	10	QPSK	1/0	2501.0	23.31	214.29
			1/0	2593.0	22.83	191.87
			1/0	2685.0	21.61	144.88
		16QAM	1/0	2501.0	23.51	224.39
			1/0	2593.0	22.69	185.78
			1/0	2685.0	22.03	159.59
	5	QPSK	1/0	2498.5	19.97	99.31
			1/0	2593.0	22.60	181.97
			1/0	2687.5	22.15	164.06
		16QAM	1/0	2498.5	20.02	100.46
			1/0	2593.0	21.98	157.76
			1/0	2687.5	22.65	184.08

10.1.2.ERP/EIRP DATA

GSM 850

GSM GSM850 GPRS	UL Verification Services, Inc. High Frequency Substitution Measurement																																																																																																	
	Company:		Samsung																																																																																															
	Project #:		4788506351																																																																																															
	Date:		2018-06-19																																																																																															
	Test Engineer:		45585																																																																																															
	Configuration:		EUT / Y-Position																																																																																															
	Location:		Chamber 1																																																																																															
	Mode:		GPRS 850 MHz Fundamentals																																																																																															
	Test Equipment:																																																																																																	
	Receiving: VULB9163-750, and Chamber 2 SMA Cables																																																																																																	
Substitution: Dipole 3121_DB4, 3m N-type Cable																																																																																																		
<table><tr><th>f MHz</th><th>SG reading (dBm)</th><th>Ant. Pol. (H/V)</th><th>Cable Loss (dB)</th><th>Antenna Gain (dBd)</th><th>ERP (dBm)</th><th>Limit (dBm)</th><th>Delta (dB)</th><th>Notes</th></tr><tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>824.20</td><td>33.06</td><td>V</td><td>1.0</td><td>-1.5</td><td>30.63</td><td>38.5</td><td>-7.9</td><td></td></tr><tr><td>824.20</td><td>24.48</td><td>H</td><td>1.0</td><td>-1.5</td><td>22.05</td><td>38.5</td><td>-16.4</td><td></td></tr><tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>836.60</td><td>32.78</td><td>V</td><td>1.0</td><td>-1.4</td><td>30.40</td><td>38.5</td><td>-8.1</td><td></td></tr><tr><td>836.60</td><td>23.40</td><td>H</td><td>1.0</td><td>-1.4</td><td>21.02</td><td>38.5</td><td>-17.5</td><td></td></tr><tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>848.80</td><td>33.05</td><td>V</td><td>1.0</td><td>-1.4</td><td>30.71</td><td>38.5</td><td>-7.8</td><td></td></tr><tr><td>848.80</td><td>22.81</td><td>H</td><td>1.0</td><td>-1.4</td><td>20.47</td><td>38.5</td><td>-18.0</td><td></td></tr></table>									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									824.20	33.06	V	1.0	-1.5	30.63	38.5	-7.9		824.20	24.48	H	1.0	-1.5	22.05	38.5	-16.4		Mid Ch									836.60	32.78	V	1.0	-1.4	30.40	38.5	-8.1		836.60	23.40	H	1.0	-1.4	21.02	38.5	-17.5		High Ch									848.80	33.05	V	1.0	-1.4	30.71	38.5	-7.8		848.80	22.81	H	1.0	-1.4	20.47	38.5	-18.0	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																										
Low Ch																																																																																																		
824.20	33.06	V	1.0	-1.5	30.63	38.5	-7.9																																																																																											
824.20	24.48	H	1.0	-1.5	22.05	38.5	-16.4																																																																																											
Mid Ch																																																																																																		
836.60	32.78	V	1.0	-1.4	30.40	38.5	-8.1																																																																																											
836.60	23.40	H	1.0	-1.4	21.02	38.5	-17.5																																																																																											
High Ch																																																																																																		
848.80	33.05	V	1.0	-1.4	30.71	38.5	-7.8																																																																																											
848.80	22.81	H	1.0	-1.4	20.47	38.5	-18.0																																																																																											
GSM GSM850 EGPRS	UL Verification Services, Inc. High Frequency Substitution Measurement																																																																																																	
	Company:		Samsung																																																																																															
	Project #:		4788506351																																																																																															
	Date:		2018-06-19																																																																																															
	Test Engineer:		45585																																																																																															
	Configuration:		EUT / Y-Position																																																																																															
	Location:		Chamber 1																																																																																															
	Mode:		EGPRS 850 MHz Fundamentals																																																																																															
	Test Equipment:																																																																																																	
	Receiving: VULB9163-750, and Chamber 2 SMA Cables																																																																																																	
Substitution: Dipole 3121_DB4, 3m N-type Cable																																																																																																		
<table><tr><th>f MHz</th><th>SG reading (dBm)</th><th>Ant. Pol. (H/V)</th><th>Cable Loss (dB)</th><th>Antenna Gain (dBd)</th><th>ERP (dBm)</th><th>Limit (dBm)</th><th>Delta (dB)</th><th>Notes</th></tr><tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>824.20</td><td>27.04</td><td>V</td><td>1.0</td><td>-1.5</td><td>24.61</td><td>38.5</td><td>-13.9</td><td></td></tr><tr><td>824.20</td><td>18.33</td><td>H</td><td>1.0</td><td>-1.5</td><td>15.90</td><td>38.5</td><td>-22.6</td><td></td></tr><tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>836.60</td><td>26.39</td><td>V</td><td>1.0</td><td>-1.4</td><td>24.01</td><td>38.5</td><td>-14.5</td><td></td></tr><tr><td>836.60</td><td>17.47</td><td>H</td><td>1.0</td><td>-1.4</td><td>15.09</td><td>38.5</td><td>-23.4</td><td></td></tr><tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>848.80</td><td>27.29</td><td>V</td><td>1.0</td><td>-1.4</td><td>24.95</td><td>38.5</td><td>-13.6</td><td></td></tr><tr><td>848.80</td><td>16.44</td><td>H</td><td>1.0</td><td>-1.4</td><td>14.10</td><td>38.5</td><td>-24.4</td><td></td></tr></table>									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									824.20	27.04	V	1.0	-1.5	24.61	38.5	-13.9		824.20	18.33	H	1.0	-1.5	15.90	38.5	-22.6		Mid Ch									836.60	26.39	V	1.0	-1.4	24.01	38.5	-14.5		836.60	17.47	H	1.0	-1.4	15.09	38.5	-23.4		High Ch									848.80	27.29	V	1.0	-1.4	24.95	38.5	-13.6		848.80	16.44	H	1.0	-1.4	14.10	38.5	-24.4	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																										
Low Ch																																																																																																		
824.20	27.04	V	1.0	-1.5	24.61	38.5	-13.9																																																																																											
824.20	18.33	H	1.0	-1.5	15.90	38.5	-22.6																																																																																											
Mid Ch																																																																																																		
836.60	26.39	V	1.0	-1.4	24.01	38.5	-14.5																																																																																											
836.60	17.47	H	1.0	-1.4	15.09	38.5	-23.4																																																																																											
High Ch																																																																																																		
848.80	27.29	V	1.0	-1.4	24.95	38.5	-13.6																																																																																											
848.80	16.44	H	1.0	-1.4	14.10	38.5	-24.4																																																																																											

GSM 1900

GSM GSM1900 GPRS	UL Verification Services, Inc. High Frequency Substitution Measurement																																																																																																	
	Company:		Samsung																																																																																															
	Project #:		4788506351																																																																																															
	Date:		2018-06-21																																																																																															
	Test Engineer:		47989																																																																																															
	Configuration:		EUT / X-Position																																																																																															
	Location:		Chamber 1																																																																																															
	Mode:		GPRS 1900 MHz Fundamentals																																																																																															
	Test Equipment:																																																																																																	
	Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables Substitution: Horn 3115[00161451], 3m N-type Cable																																																																																																	
<table><tr><th>f MHz</th><th>SG reading (dBm)</th><th>Ant. Pol. (H/V)</th><th>Cable Loss (dB)</th><th>Antenna Gain (dBi)</th><th>EIRP (dBm)</th><th>Limit (dBm)</th><th>Delta (dB)</th><th>Notes</th></tr><tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>1850.20</td><td>25.18</td><td>V</td><td>4.5</td><td>9.5</td><td>30.19</td><td>33.0</td><td>-2.8</td><td></td></tr><tr><td>1850.20</td><td>25.23</td><td>H</td><td>4.5</td><td>9.5</td><td>30.24</td><td>33.0</td><td>-2.8</td><td></td></tr><tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>1880.00</td><td>24.66</td><td>V</td><td>4.5</td><td>9.2</td><td>29.34</td><td>33.0</td><td>-3.7</td><td></td></tr><tr><td>1880.00</td><td>25.57</td><td>H</td><td>4.5</td><td>9.2</td><td>30.25</td><td>33.0</td><td>-2.8</td><td></td></tr><tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>1909.80</td><td>24.51</td><td>V</td><td>4.6</td><td>8.9</td><td>28.81</td><td>33.0</td><td>-4.2</td><td></td></tr><tr><td>1909.80</td><td>24.54</td><td>H</td><td>4.6</td><td>8.9</td><td>28.84</td><td>33.0</td><td>-4.2</td><td></td></tr></table>									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1850.20	25.18	V	4.5	9.5	30.19	33.0	-2.8		1850.20	25.23	H	4.5	9.5	30.24	33.0	-2.8		Mid Ch									1880.00	24.66	V	4.5	9.2	29.34	33.0	-3.7		1880.00	25.57	H	4.5	9.2	30.25	33.0	-2.8		High Ch									1909.80	24.51	V	4.6	8.9	28.81	33.0	-4.2		1909.80	24.54	H	4.6	8.9	28.84	33.0	-4.2	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																										
Low Ch																																																																																																		
1850.20	25.18	V	4.5	9.5	30.19	33.0	-2.8																																																																																											
1850.20	25.23	H	4.5	9.5	30.24	33.0	-2.8																																																																																											
Mid Ch																																																																																																		
1880.00	24.66	V	4.5	9.2	29.34	33.0	-3.7																																																																																											
1880.00	25.57	H	4.5	9.2	30.25	33.0	-2.8																																																																																											
High Ch																																																																																																		
1909.80	24.51	V	4.6	8.9	28.81	33.0	-4.2																																																																																											
1909.80	24.54	H	4.6	8.9	28.84	33.0	-4.2																																																																																											
GSM GSM1900 EGPRS	UL Verification Services, Inc. High Frequency Substitution Measurement																																																																																																	
	Company:		Samsung																																																																																															
	Project #:		4788506351																																																																																															
	Date:		2018-06-21																																																																																															
	Test Engineer:		47989																																																																																															
	Configuration:		EUT / X-Position																																																																																															
	Location:		Chamber 1																																																																																															
	Mode:		EGPRS 1900 MHz Fundamentals																																																																																															
	Test Equipment:																																																																																																	
	Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables Substitution: Horn 3115[00161451], 3m N-type Cable																																																																																																	
<table><tr><th>f MHz</th><th>SG reading (dBm)</th><th>Ant. Pol. (H/V)</th><th>Cable Loss (dB)</th><th>Antenna Gain (dBi)</th><th>EIRP (dBm)</th><th>Limit (dBm)</th><th>Delta (dB)</th><th>Notes</th></tr><tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>1850.20</td><td>20.42</td><td>V</td><td>4.5</td><td>9.5</td><td>25.43</td><td>33.0</td><td>-7.6</td><td></td></tr><tr><td>1850.20</td><td>21.10</td><td>H</td><td>4.5</td><td>9.5</td><td>26.11</td><td>33.0</td><td>-6.9</td><td></td></tr><tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>1880.00</td><td>20.55</td><td>V</td><td>4.5</td><td>9.2</td><td>25.23</td><td>33.0</td><td>-7.8</td><td></td></tr><tr><td>1880.00</td><td>20.59</td><td>H</td><td>4.5</td><td>9.2</td><td>25.27</td><td>33.0</td><td>-7.7</td><td></td></tr><tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>1909.80</td><td>20.37</td><td>V</td><td>4.6</td><td>8.9</td><td>24.67</td><td>33.0</td><td>-8.3</td><td></td></tr><tr><td>1909.80</td><td>21.27</td><td>H</td><td>4.6</td><td>8.9</td><td>25.57</td><td>33.0</td><td>-7.4</td><td></td></tr></table>									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									1850.20	20.42	V	4.5	9.5	25.43	33.0	-7.6		1850.20	21.10	H	4.5	9.5	26.11	33.0	-6.9		Mid Ch									1880.00	20.55	V	4.5	9.2	25.23	33.0	-7.8		1880.00	20.59	H	4.5	9.2	25.27	33.0	-7.7		High Ch									1909.80	20.37	V	4.6	8.9	24.67	33.0	-8.3		1909.80	21.27	H	4.6	8.9	25.57	33.0	-7.4	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																										
Low Ch																																																																																																		
1850.20	20.42	V	4.5	9.5	25.43	33.0	-7.6																																																																																											
1850.20	21.10	H	4.5	9.5	26.11	33.0	-6.9																																																																																											
Mid Ch																																																																																																		
1880.00	20.55	V	4.5	9.2	25.23	33.0	-7.8																																																																																											
1880.00	20.59	H	4.5	9.2	25.27	33.0	-7.7																																																																																											
High Ch																																																																																																		
1909.80	20.37	V	4.6	8.9	24.67	33.0	-8.3																																																																																											
1909.80	21.27	H	4.6	8.9	25.57	33.0	-7.4																																																																																											

WCDMA Band 5

WCDMA Band 5 REL99	UL Verification Services, Inc. High Frequency Substitution Measurement																																																																																																	
	Company:		Samsung																																																																																															
	Project #:		4788506351																																																																																															
	Date:		2018-06-19																																																																																															
	Test Engineer:		45585																																																																																															
	Configuration:		EUT / Y-Position																																																																																															
	Location:		Chamber 1																																																																																															
	Mode:		Rel99 Band 5 Fundamentals																																																																																															
	Test Equipment:																																																																																																	
	Receiving: VULB9163-750, and Chamber 2 SMA Cables																																																																																																	
Substitution: Dipole 3121_DB4, 3m N-type Cable																																																																																																		
<table><tr><th>f MHz</th><th>SG reading (dBm)</th><th>Ant. Pol. (H/V)</th><th>Cable Loss (dB)</th><th>Antenna Gain (dBd)</th><th>ERP (dBm)</th><th>Limit (dBm)</th><th>Delta (dB)</th><th>Notes</th></tr><tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>826.40</td><td>23.81</td><td>V</td><td>1.0</td><td>-1.5</td><td>21.39</td><td>38.5</td><td>-17.1</td><td></td></tr><tr><td>826.40</td><td>14.80</td><td>H</td><td>1.0</td><td>-1.5</td><td>12.38</td><td>38.5</td><td>-26.1</td><td></td></tr><tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>836.60</td><td>22.69</td><td>V</td><td>1.0</td><td>-1.4</td><td>20.31</td><td>38.5</td><td>-18.2</td><td></td></tr><tr><td>836.60</td><td>14.02</td><td>H</td><td>1.0</td><td>-1.4</td><td>11.64</td><td>38.5</td><td>-26.9</td><td></td></tr><tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>846.60</td><td>22.51</td><td>V</td><td>1.0</td><td>-1.4</td><td>20.16</td><td>38.5</td><td>-18.3</td><td></td></tr><tr><td>846.60</td><td>12.85</td><td>H</td><td>1.0</td><td>-1.4</td><td>10.50</td><td>38.5</td><td>-28.0</td><td></td></tr></table>									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									826.40	23.81	V	1.0	-1.5	21.39	38.5	-17.1		826.40	14.80	H	1.0	-1.5	12.38	38.5	-26.1		Mid Ch									836.60	22.69	V	1.0	-1.4	20.31	38.5	-18.2		836.60	14.02	H	1.0	-1.4	11.64	38.5	-26.9		High Ch									846.60	22.51	V	1.0	-1.4	20.16	38.5	-18.3		846.60	12.85	H	1.0	-1.4	10.50	38.5	-28.0	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																										
Low Ch																																																																																																		
826.40	23.81	V	1.0	-1.5	21.39	38.5	-17.1																																																																																											
826.40	14.80	H	1.0	-1.5	12.38	38.5	-26.1																																																																																											
Mid Ch																																																																																																		
836.60	22.69	V	1.0	-1.4	20.31	38.5	-18.2																																																																																											
836.60	14.02	H	1.0	-1.4	11.64	38.5	-26.9																																																																																											
High Ch																																																																																																		
846.60	22.51	V	1.0	-1.4	20.16	38.5	-18.3																																																																																											
846.60	12.85	H	1.0	-1.4	10.50	38.5	-28.0																																																																																											
WCDMA Band 5 HSDPA	UL Verification Services, Inc. High Frequency Substitution Measurement																																																																																																	
	Company:		Samsung																																																																																															
	Project #:		4788506351																																																																																															
	Date:		2018-06-19																																																																																															
	Test Engineer:		45585																																																																																															
	Configuration:		EUT / Y-Position																																																																																															
	Location:		Chamber 1																																																																																															
	Mode:		HSDPA Band 5 Fundamentals																																																																																															
	Test Equipment:																																																																																																	
	Receiving: VULB9163-750, and Chamber 2 SMA Cables																																																																																																	
Substitution: Dipole 3121_DB4, 3m N-type Cable																																																																																																		
<table><tr><th>f MHz</th><th>SG reading (dBm)</th><th>Ant. Pol. (H/V)</th><th>Cable Loss (dB)</th><th>Antenna Gain (dBd)</th><th>ERP (dBm)</th><th>Limit (dBm)</th><th>Delta (dB)</th><th>Notes</th></tr><tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>826.40</td><td>22.98</td><td>V</td><td>1.0</td><td>-1.5</td><td>20.56</td><td>38.5</td><td>-17.9</td><td></td></tr><tr><td>826.40</td><td>13.60</td><td>H</td><td>1.0</td><td>-1.5</td><td>11.18</td><td>38.5</td><td>-27.3</td><td></td></tr><tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>836.60</td><td>21.92</td><td>V</td><td>1.0</td><td>-1.4</td><td>19.54</td><td>38.5</td><td>-19.0</td><td></td></tr><tr><td>836.60</td><td>13.17</td><td>H</td><td>1.0</td><td>-1.4</td><td>10.79</td><td>38.5</td><td>-27.7</td><td></td></tr><tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>846.60</td><td>21.43</td><td>V</td><td>1.0</td><td>-1.4</td><td>19.08</td><td>38.5</td><td>-19.4</td><td></td></tr><tr><td>846.60</td><td>11.69</td><td>H</td><td>1.0</td><td>-1.4</td><td>9.34</td><td>38.5</td><td>-29.2</td><td></td></tr></table>									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									826.40	22.98	V	1.0	-1.5	20.56	38.5	-17.9		826.40	13.60	H	1.0	-1.5	11.18	38.5	-27.3		Mid Ch									836.60	21.92	V	1.0	-1.4	19.54	38.5	-19.0		836.60	13.17	H	1.0	-1.4	10.79	38.5	-27.7		High Ch									846.60	21.43	V	1.0	-1.4	19.08	38.5	-19.4		846.60	11.69	H	1.0	-1.4	9.34	38.5	-29.2	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																										
Low Ch																																																																																																		
826.40	22.98	V	1.0	-1.5	20.56	38.5	-17.9																																																																																											
826.40	13.60	H	1.0	-1.5	11.18	38.5	-27.3																																																																																											
Mid Ch																																																																																																		
836.60	21.92	V	1.0	-1.4	19.54	38.5	-19.0																																																																																											
836.60	13.17	H	1.0	-1.4	10.79	38.5	-27.7																																																																																											
High Ch																																																																																																		
846.60	21.43	V	1.0	-1.4	19.08	38.5	-19.4																																																																																											
846.60	11.69	H	1.0	-1.4	9.34	38.5	-29.2																																																																																											

WCDMA Band 2

WCDMA

Band 2

REL99

UL Verification Services, Inc.

High Frequency Substitution Measurement

Company:

Samsung

Project #:

4788506351

Date:

2018-06-21

Test Engineer:

47989

Configuration:

EUT / X-Position

Location:

Chamber 1

Mode:

Rel99 Band 2 Fundamentals

Test Equipment:

Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables

Substitution: Horn 3115[00161451], 3m N-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1852.40	16.40	V	4.5	9.5	21.39	33.0	-11.6	
1852.40	16.92	H	4.5	9.5	21.91	33.0	-11.1	
Mid Ch								
1880.00	16.35	V	4.5	9.2	21.03	33.0	-12.0	
1880.00	16.96	H	4.5	9.2	21.64	33.0	-11.4	
High Ch								
1907.60	16.37	V	4.6	8.9	20.71	33.0	-12.3	
1907.60	16.51	H	4.6	8.9	20.85	33.0	-12.1	

WCDMA

Band 2

HSDPA

UL Verification Services, Inc.

High Frequency Substitution Measurement

Company:

Samsung

Project #:

4788506351

Date:

2018-06-21

Test Engineer:

47989

Configuration:

EUT / X-Position

Location:

Chamber 1

Mode:

HSDPA Band 2 Fundamentals

Test Equipment:

Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables

Substitution: Horn 3115[00161451], 3m N-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1852.40	14.57	V	4.5	9.5	19.56	33.0	-13.4	
1852.40	16.31	H	4.5	9.5	21.30	33.0	-11.7	
Mid Ch								
1880.00	15.59	V	4.5	9.2	20.27	33.0	-12.7	
1880.00	16.61	H	4.5	9.2	21.29	33.0	-11.7	
High Ch								
1907.60	15.62	V	4.6	8.9	19.96	33.0	-13.0	
1907.60	15.90	H	4.6	8.9	20.24	33.0	-12.8	

LTE Band 5

LTE
Band 5
10MHz
QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4788506351
Date: 2018-06-19
Test Engineer: 45585
Configuration: EUT / Y-Position
Location: Chamber 1
Mode: LTE_QPSK Band 5 Fundamentals, 10MHz Bandwidth

Test Equipment:

Receiving: VULB9163-750, and Chamber 2 SMA Cables
Substitution: Dipole 3121_DB4, 3m N-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
829.00	25.75	V	1.0	-1.5	23.34	38.5	-15.2	
829.00	16.60	H	1.0	-1.5	14.19	38.5	-24.3	
Mid Ch								
836.50	25.26	V	1.0	-1.4	22.88	38.5	-15.6	
836.50	15.60	H	1.0	-1.4	13.22	38.5	-25.3	
High Ch								
844.00	25.24	V	1.0	-1.4	22.88	38.5	-15.6	
844.00	15.58	H	1.0	-1.4	13.23	38.5	-25.3	

LTE
Band 5
10MHz
16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4788506351
Date: 2018-06-19
Test Engineer: 45585
Configuration: EUT / Y-Position
Location: Chamber 1
Mode: LTE_16QAM Band 5 Fundamentals, 10MHz Bandwidth

Test Equipment:

Receiving: VULB9163-750, and Chamber 2 SMA Cables
Substitution: Dipole 3121_DB4, 3m N-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
829.00	24.64	V	1.0	-1.5	22.23	38.5	-16.3	
829.00	15.28	H	1.0	-1.5	12.87	38.5	-25.6	
Mid Ch								
836.50	24.33	V	1.0	-1.4	21.95	38.5	-16.5	
836.50	14.92	H	1.0	-1.4	12.54	38.5	-26.0	
High Ch								
844.00	24.06	V	1.0	-1.4	21.70	38.5	-16.8	
844.00	14.34	H	1.0	-1.4	11.99	38.5	-26.5	

LTE Band 5 5MHz QPSK	UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 4788506351 Date: 2018-06-19 Test Engineer: 45585 Configuration: EUT / Y-Position Location: Chamber 1 Mode: LTE_QPSK Band 5 Fundamentals, 5MHz Bandwidth Test Equipment: Receiving: VULB9163-750, and Chamber 2 SMA Cables Substitution: Dipole 3121_DB4, 3m N-type Cable								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Delta	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	826.50	25.74	V	1.0	-1.5	23.32	38.5	-15.2	
	826.50	16.72	H	1.0	-1.5	14.30	38.5	-24.2	
	Mid Ch								
	836.50	25.50	V	1.0	-1.4	23.12	38.5	-15.4	
	836.50	15.70	H	1.0	-1.4	13.32	38.5	-25.2	
	High Ch								
LTE Band 5 5MHz 16QAM	846.50	25.08	V	1.0	-1.4	22.73	38.5	-15.8	
	846.50	14.88	H	1.0	-1.4	12.53	38.5	-26.0	
LTE Band 5 5MHz 16QAM	UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 4788506351 Date: 2018-06-19 Test Engineer: 45585 Configuration: EUT / Y-Position Location: Chamber 1 Mode: LTE_16QAM Band 5 Fundamentals, 5MHz Bandwidth Test Equipment: Receiving: VULB9163-750, and Chamber 2 SMA Cables Substitution: Dipole 3121_DB4, 3m N-type Cable								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Delta	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	826.50	24.88	V	1.0	-1.5	22.46	38.5	-16.0	
	826.50	15.68	H	1.0	-1.5	13.26	38.5	-25.2	
	Mid Ch								
	836.50	24.18	V	1.0	-1.4	21.80	38.5	-16.7	
	836.50	14.81	H	1.0	-1.4	12.43	38.5	-26.1	
	High Ch								
LTE Band 5 5MHz 16QAM	846.50	24.11	V	1.0	-1.4	21.76	38.5	-16.7	
	846.50	13.94	H	1.0	-1.4	11.59	38.5	-26.9	

LTE

Band 5

3MHz

QPSK

UL Verification Services, Inc.

High Frequency Substitution Measurement

Company:

Samsung

Project #:

4788506351

Date:

2018-06-19

Test Engineer:

45585

Configuration:

EUT / Y-Position

Location:

Chamber 1

Mode:

LTE_QPSK Band 5 Fundamentals, 3MHz Bandwidth

Test Equipment:

Receiving: VULB9163-750, and Chamber 2 SMA Cables

Substitution: Dipole 3121_DB4, 3m N-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
825.50	25.98	V	1.0	-1.5	23.55	38.5	-14.9	
825.50	16.64	H	1.0	-1.5	14.22	38.5	-24.3	
Mid Ch								
836.50	25.21	V	1.0	-1.4	22.83	38.5	-15.7	
836.50	15.58	H	1.0	-1.4	13.20	38.5	-25.3	
High Ch								
847.50	24.21	V	1.0	-1.4	21.86	38.5	-16.6	
847.50	20.49	H	1.0	-1.4	18.15	38.5	-20.4	

LTE

Band 5

3MHz

16QAM

UL Verification Services, Inc.

High Frequency Substitution Measurement

Company:

Samsung

Project #:

4788506351

Date:

2018-06-19

Test Engineer:

45585

Configuration:

EUT / Y-Position

Location:

Chamber 1

Mode:

LTE_16QAM Band 5 Fundamentals, 3MHz Bandwidth

Test Equipment:

Receiving: VULB9163-750, and Chamber 2 SMA Cables

Substitution: Dipole 3121_DB4, 3m N-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
825.50	24.61	V	1.0	-1.5	22.18	38.5	-16.3	
825.50	15.43	H	1.0	-1.5	13.01	38.5	-25.5	
Mid Ch								
836.50	24.14	V	1.0	-1.4	21.76	38.5	-16.7	
836.50	14.63	H	1.0	-1.4	12.25	38.5	-26.3	
High Ch								
847.50	23.09	V	1.0	-1.4	20.74	38.5	-17.8	
847.50	19.76	H	1.0	-1.4	17.42	38.5	-21.1	

LTE Band 5 1.4MHz QPSK	UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 4788506351 Date: 2018-06-19 Test Engineer: 45585 Configuration: EUT / Y-Position Location: Chamber 1 Mode: LTE_QPSK Band 5 Fundamentals, 1.4MHz Bandwidth Test Equipment: Receiving: VULB9163-750, and Chamber 2 SMA Cables Substitution: Dipole 3121_DB4, 3m N-type Cable								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Delta	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	824.70	25.79	V	1.0	-1.5	23.37	38.5	-15.1	
	824.70	16.62	H	1.0	-1.5	14.20	38.5	-24.3	
	Mid Ch								
	836.50	25.07	V	1.0	-1.4	22.69	38.5	-15.8	
	836.50	15.57	H	1.0	-1.4	13.19	38.5	-25.3	
	High Ch								
	848.30	23.71	V	1.0	-1.4	21.37	38.5	-17.1	
	848.30	13.44	H	1.0	-1.4	11.10	38.5	-27.4	
LTE Band 5 1.4MHz 16QAM	UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 4788506351 Date: 2018-06-19 Test Engineer: 45585 Configuration: EUT / Y-Position Location: Chamber 1 Mode: LTE_16QAM Band 5 Fundamentals, 1.4MHz Bandwidth Test Equipment: Receiving: VULB9163-750, and Chamber 2 SMA Cables Substitution: Dipole 3121_DB4, 3m N-type Cable								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Delta	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	824.70	24.73	V	1.0	-1.5	22.31	38.5	-16.2	
	824.70	15.44	H	1.0	-1.5	13.02	38.5	-25.5	
	Mid Ch								
	836.50	23.99	V	1.0	-1.4	21.61	38.5	-16.9	
	836.50	14.40	H	1.0	-1.4	12.02	38.5	-26.5	
	High Ch								
	848.30	22.53	V	1.0	-1.4	20.19	38.5	-18.3	
	848.30	12.50	H	1.0	-1.4	10.16	38.5	-28.3	

LTE Band 12

LTE

Band 12

10MHz

QPSK

UL Verification Services, Inc.

High Frequency Substitution Measurement

Company:

Project #:

Date:

Test Engineer:

Configuration:

Location:

Mode:

Test Equipment:

Receiving: VULB9163-750, and Chamber 2 SMA Cables

Substitution: Dipole 3121_DB4, 3m N-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
704.00	19.27	V	0.9	-1.6	16.80	34.8	-18.0	
704.00	10.31	H	0.9	-1.6	7.84	34.8	-27.0	
Mid Ch								
707.50	19.50	V	0.9	-1.6	17.03	34.8	-17.8	
707.50	10.50	H	0.9	-1.6	8.03	34.8	-26.8	
High Ch								
711.00	19.63	V	0.9	-1.6	17.16	34.8	-17.6	
711.00	11.02	H	0.9	-1.6	8.54	34.8	-26.3	

LTE

Band 12

10MHz

16QAM

UL Verification Services, Inc.

High Frequency Substitution Measurement

Company:

Project #:

Date:

Test Engineer:

Configuration:

Location:

Mode:

Test Equipment:

Receiving: VULB9163-750, and Chamber 2 SMA Cables

Substitution: Dipole 3121_DB4, 3m N-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
704.00	18.09	V	0.9	-1.6	15.62	34.8	-19.2	
704.00	9.31	H	0.9	-1.6	6.84	34.8	-28.0	
Mid Ch								
707.50	18.48	V	0.9	-1.6	16.01	34.8	-18.8	
707.50	9.65	H	0.9	-1.6	7.18	34.8	-27.6	
High Ch								
711.00	18.44	V	0.9	-1.6	15.97	34.8	-18.8	
711.00	9.93	H	0.9	-1.6	7.45	34.8	-27.3	

LTE Band 12 5MHz QPSK	UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 4788506351 Date: 2018-06-19 Test Engineer: 47989 Configuration: EUT / Y-Position Location: Chamber 1 Mode: LTE_QPSK Band 12 Fundamentals, 5MHz Bandwidth Test Equipment: Receiving: VULB9163-750, and Chamber 2 SMA Cables Substitution: Dipole 3121_DB4, 3m N-type Cable								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Delta	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	701.50	19.17	V	0.9	-1.6	16.70	34.8	-18.1	
	701.50	10.12	H	0.9	-1.6	7.66	34.8	-27.1	
	Mid Ch								
	707.50	19.54	V	0.9	-1.6	17.07	34.8	-17.7	
	707.50	10.48	H	0.9	-1.6	8.01	34.8	-26.8	
	High Ch								
LTE Band 12 5MHz 16QAM	713.50	19.05	V	0.9	-1.6	16.57	34.8	-18.2	
	713.50	10.80	H	0.9	-1.6	8.32	34.8	-26.5	
LTE Band 12 5MHz 16QAM	UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 4788506351 Date: 2018-06-19 Test Engineer: 47989 Configuration: EUT / Y-Position Location: Chamber 1 Mode: LTE_16QAM Band 12 Fundamentals, 5MHz Bandwidth Test Equipment: Receiving: VULB9163-750, and Chamber 2 SMA Cables Substitution: Dipole 3121_DB4, 3m N-type Cable								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Delta	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	701.50	17.87	V	0.9	-1.6	15.40	34.8	-19.4	
	701.50	9.55	H	0.9	-1.6	7.09	34.8	-27.7	
	Mid Ch								
	707.50	18.57	V	0.9	-1.6	16.10	34.8	-18.7	
	707.50	9.13	H	0.9	-1.6	6.66	34.8	-28.1	
	High Ch								
LTE Band 12 5MHz 16QAM	713.50	18.28	V	0.9	-1.6	15.80	34.8	-19.0	
	713.50	10.06	H	0.9	-1.6	7.58	34.8	-27.2	

LTE Band 12 3MHz QPSK	UL Verification Services, Inc. High Frequency Substitution Measurement																																																																																																	
	Company:		Samsung																																																																																															
	Project #:		4788506351																																																																																															
	Date:		2018-06-19																																																																																															
	Test Engineer:		47989																																																																																															
	Configuration:		EUT / Y-Position																																																																																															
	Location:		Chamber 1																																																																																															
	Mode:		LTE_QPSK Band 12 Fundamentals, 3MHz Bandwidth																																																																																															
	Test Equipment:																																																																																																	
	Receiving: VULB9163-750, and Chamber 2 SMA Cables																																																																																																	
Substitution: Dipole 3121_DB4, 3m N-type Cable																																																																																																		
<table><tr><th>f MHz</th><th>SG reading (dBm)</th><th>Ant. Pol. (H/V)</th><th>Cable Loss (dB)</th><th>Antenna Gain (dBd)</th><th>ERP (dBm)</th><th>Limit (dBm)</th><th>Delta (dB)</th><th>Notes</th></tr><tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>700.50</td><td>19.19</td><td>V</td><td>0.9</td><td>-1.6</td><td>16.72</td><td>34.8</td><td>-18.1</td><td></td></tr><tr><td>700.50</td><td>10.29</td><td>H</td><td>0.9</td><td>-1.6</td><td>7.83</td><td>34.8</td><td>-27.0</td><td></td></tr><tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>707.50</td><td>19.07</td><td>V</td><td>0.9</td><td>-1.6</td><td>16.60</td><td>34.8</td><td>-18.2</td><td></td></tr><tr><td>707.50</td><td>10.77</td><td>H</td><td>0.9</td><td>-1.6</td><td>8.30</td><td>34.8</td><td>-26.5</td><td></td></tr><tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>714.50</td><td>19.06</td><td>V</td><td>0.9</td><td>-1.6</td><td>16.59</td><td>34.8</td><td>-18.2</td><td></td></tr><tr><td>714.50</td><td>11.34</td><td>H</td><td>0.9</td><td>-1.6</td><td>8.86</td><td>34.8</td><td>-25.9</td><td></td></tr></table>									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									700.50	19.19	V	0.9	-1.6	16.72	34.8	-18.1		700.50	10.29	H	0.9	-1.6	7.83	34.8	-27.0		Mid Ch									707.50	19.07	V	0.9	-1.6	16.60	34.8	-18.2		707.50	10.77	H	0.9	-1.6	8.30	34.8	-26.5		High Ch									714.50	19.06	V	0.9	-1.6	16.59	34.8	-18.2		714.50	11.34	H	0.9	-1.6	8.86	34.8	-25.9	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																										
Low Ch																																																																																																		
700.50	19.19	V	0.9	-1.6	16.72	34.8	-18.1																																																																																											
700.50	10.29	H	0.9	-1.6	7.83	34.8	-27.0																																																																																											
Mid Ch																																																																																																		
707.50	19.07	V	0.9	-1.6	16.60	34.8	-18.2																																																																																											
707.50	10.77	H	0.9	-1.6	8.30	34.8	-26.5																																																																																											
High Ch																																																																																																		
714.50	19.06	V	0.9	-1.6	16.59	34.8	-18.2																																																																																											
714.50	11.34	H	0.9	-1.6	8.86	34.8	-25.9																																																																																											
LTE Band 12 3MHz 16QAM	UL Verification Services, Inc. High Frequency Substitution Measurement																																																																																																	
	Company:		Samsung																																																																																															
	Project #:		4788506351																																																																																															
	Date:		2018-06-19																																																																																															
	Test Engineer:		47989																																																																																															
	Configuration:		EUT / Y-Position																																																																																															
	Location:		Chamber 1																																																																																															
	Mode:		LTE_16QAM Band 12 Fundamentals, 3MHz Bandwidth																																																																																															
	Test Equipment:																																																																																																	
	Receiving: VULB9163-750, and Chamber 2 SMA Cables																																																																																																	
Substitution: Dipole 3121_DB4, 3m N-type Cable																																																																																																		
<table><tr><th>f MHz</th><th>SG reading (dBm)</th><th>Ant. Pol. (H/V)</th><th>Cable Loss (dB)</th><th>Antenna Gain (dBd)</th><th>ERP (dBm)</th><th>Limit (dBm)</th><th>Delta (dB)</th><th>Notes</th></tr><tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>700.50</td><td>18.06</td><td>V</td><td>0.9</td><td>-1.6</td><td>15.59</td><td>34.8</td><td>-19.2</td><td></td></tr><tr><td>700.50</td><td>8.83</td><td>H</td><td>0.9</td><td>-1.6</td><td>6.37</td><td>34.8</td><td>-28.4</td><td></td></tr><tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>707.50</td><td>17.88</td><td>V</td><td>0.9</td><td>-1.6</td><td>15.41</td><td>34.8</td><td>-19.4</td><td></td></tr><tr><td>707.50</td><td>9.44</td><td>H</td><td>0.9</td><td>-1.6</td><td>6.97</td><td>34.8</td><td>-27.8</td><td></td></tr><tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>714.50</td><td>17.96</td><td>V</td><td>0.9</td><td>-1.6</td><td>15.49</td><td>34.8</td><td>-19.3</td><td></td></tr><tr><td>714.50</td><td>10.23</td><td>H</td><td>0.9</td><td>-1.6</td><td>7.75</td><td>34.8</td><td>-27.0</td><td></td></tr></table>									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									700.50	18.06	V	0.9	-1.6	15.59	34.8	-19.2		700.50	8.83	H	0.9	-1.6	6.37	34.8	-28.4		Mid Ch									707.50	17.88	V	0.9	-1.6	15.41	34.8	-19.4		707.50	9.44	H	0.9	-1.6	6.97	34.8	-27.8		High Ch									714.50	17.96	V	0.9	-1.6	15.49	34.8	-19.3		714.50	10.23	H	0.9	-1.6	7.75	34.8	-27.0	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																										
Low Ch																																																																																																		
700.50	18.06	V	0.9	-1.6	15.59	34.8	-19.2																																																																																											
700.50	8.83	H	0.9	-1.6	6.37	34.8	-28.4																																																																																											
Mid Ch																																																																																																		
707.50	17.88	V	0.9	-1.6	15.41	34.8	-19.4																																																																																											
707.50	9.44	H	0.9	-1.6	6.97	34.8	-27.8																																																																																											
High Ch																																																																																																		
714.50	17.96	V	0.9	-1.6	15.49	34.8	-19.3																																																																																											
714.50	10.23	H	0.9	-1.6	7.75	34.8	-27.0																																																																																											

LTE Band 12 1.4MHz QPSK	UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 4788506351 Date: 2018-06-19 Test Engineer: 47989 Configuration: EUT / Y-Position Location: Chamber 1 Mode: LTE_QPSK Band 12 Fundamentals, 1.4MHz Bandwidth Test Equipment: Receiving: VULB9163-750, and Chamber 2 SMA Cables Substitution: Dipole 3121_DB4, 3m N-type Cable								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Delta	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	699.70	19.00	V	0.9	-1.6	16.53	34.8	-18.3	
	699.70	10.17	H	0.9	-1.6	7.70	34.8	-27.1	
	Mid Ch								
	707.50	19.42	V	0.9	-1.6	16.95	34.8	-17.9	
	707.50	10.89	H	0.9	-1.6	8.42	34.8	-26.4	
	High Ch								
	715.30	18.79	V	0.9	-1.6	16.31	34.8	-18.5	
	715.30	10.23	H	0.9	-1.6	7.76	34.8	-27.0	
LTE Band 12 1.4MHz 16QAM	UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 4788506351 Date: 2018-06-19 Test Engineer: 47989 Configuration: EUT / Y-Position Location: Chamber 1 Mode: LTE_16QAM Band 12 Fundamentals, 1.4MHz Bandwidth Test Equipment: Receiving: VULB9163-750, and Chamber 2 SMA Cables Substitution: Dipole 3121_DB4, 3m N-type Cable								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Delta	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	699.70	17.95	V	0.9	-1.6	15.48	34.8	-19.3	
	699.70	9.02	H	0.9	-1.6	6.55	34.8	-28.2	
	Mid Ch								
	707.50	18.15	V	0.9	-1.6	15.68	34.8	-19.1	
	707.50	9.47	H	0.9	-1.6	7.00	34.8	-27.8	
	High Ch								
	715.30	17.76	V	0.9	-1.6	15.28	34.8	-19.5	
	715.30	9.29	H	0.9	-1.6	6.82	34.8	-28.0	

LTE Band 41

LTE
Band 41
20MHz
QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4788506351
Date: 2018-06-20
Test Engineer: 47989
Configuration: EUT / Z-Position
Location: Chamber 1
Mode: LTE_QPSK Band 41 Fundamentals, 20MHz Bandwidth

Test Equipment:

Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00161451], 3m N-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
2506.00	15.40	V	5.3	10.3	20.34	33.0	-12.7	
2506.00	18.62	H	5.3	10.3	23.56	33.0	-9.4	
Mid Ch								
2593.00	14.87	V	5.4	10.1	19.54	33.0	-13.5	
2593.00	20.17	H	5.4	10.1	24.84	33.0	-8.2	
High Ch								
2680.00	13.08	V	5.5	10.2	17.72	33.0	-15.3	
2680.00	17.57	H	5.5	10.2	22.20	33.0	-10.8	

LTE
Band 41
20MHz
16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4788506351
Date: 2018-06-20
Test Engineer: 47989
Configuration: EUT / Z-Position
Location: Chamber 1
Mode: LTE_16QAM Band 41 Fundamentals, 20MHz Bandwidth

Test Equipment:

Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00161451], 3m N-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
2506.00	15.12	V	5.3	10.3	20.06	33.0	-12.9	
2506.00	17.47	H	5.3	10.3	22.41	33.0	-10.6	
Mid Ch								
2593.00	15.33	V	5.4	10.1	20.00	33.0	-13.0	
2593.00	20.59	H	5.4	10.1	25.26	33.0	-7.7	
High Ch								
2680.00	12.10	V	5.5	10.2	16.74	33.0	-16.3	
2680.00	17.13	H	5.5	10.2	21.76	33.0	-11.2	

LTE Band 41 15MHz QPSK	UL Verification Services, Inc. High Frequency Substitution Measurement																																																																																																	
	Company:		Samsung																																																																																															
	Project #:		4788506351																																																																																															
	Date:		2018-06-22																																																																																															
	Test Engineer:		45585																																																																																															
	Configuration:		EUT / Z-Position																																																																																															
	Location:		Chamber 1																																																																																															
	Mode:		LTE_QPSK Band 41 Fundamentals, 15MHz Bandwidth																																																																																															
	Test Equipment:																																																																																																	
	Receiving:		Horn 3117[00168717], and Chamber 1 SMA Cables																																																																																															
Substitution:		Horn 3115[00161451], 3m N-type Cable																																																																																																
<table><tr><th>f MHz</th><th>SG reading (dBm)</th><th>Ant. Pol. (H/V)</th><th>Cable Loss (dB)</th><th>Antenna Gain (dBi)</th><th>EIRP (dBm)</th><th>Limit (dBm)</th><th>Delta (dB)</th><th>Notes</th></tr><tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>2503.50</td><td>14.13</td><td>V</td><td>5.3</td><td>10.3</td><td>19.08</td><td>33.0</td><td>-13.9</td><td></td></tr><tr><td>2503.50</td><td>16.91</td><td>H</td><td>5.3</td><td>10.3</td><td>21.86</td><td>33.0</td><td>-11.1</td><td></td></tr><tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>2593.00</td><td>14.29</td><td>V</td><td>5.4</td><td>10.1</td><td>18.96</td><td>33.0</td><td>-14.0</td><td></td></tr><tr><td>2593.00</td><td>18.57</td><td>H</td><td>5.4</td><td>10.1</td><td>23.24</td><td>33.0</td><td>-9.8</td><td></td></tr><tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>2682.50</td><td>15.33</td><td>V</td><td>5.5</td><td>10.2</td><td>19.96</td><td>33.0</td><td>-13.0</td><td></td></tr><tr><td>2682.50</td><td>17.30</td><td>H</td><td>5.5</td><td>10.2</td><td>21.94</td><td>33.0</td><td>-11.1</td><td></td></tr></table>									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2503.50	14.13	V	5.3	10.3	19.08	33.0	-13.9		2503.50	16.91	H	5.3	10.3	21.86	33.0	-11.1		Mid Ch									2593.00	14.29	V	5.4	10.1	18.96	33.0	-14.0		2593.00	18.57	H	5.4	10.1	23.24	33.0	-9.8		High Ch									2682.50	15.33	V	5.5	10.2	19.96	33.0	-13.0		2682.50	17.30	H	5.5	10.2	21.94	33.0	-11.1	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																										
Low Ch																																																																																																		
2503.50	14.13	V	5.3	10.3	19.08	33.0	-13.9																																																																																											
2503.50	16.91	H	5.3	10.3	21.86	33.0	-11.1																																																																																											
Mid Ch																																																																																																		
2593.00	14.29	V	5.4	10.1	18.96	33.0	-14.0																																																																																											
2593.00	18.57	H	5.4	10.1	23.24	33.0	-9.8																																																																																											
High Ch																																																																																																		
2682.50	15.33	V	5.5	10.2	19.96	33.0	-13.0																																																																																											
2682.50	17.30	H	5.5	10.2	21.94	33.0	-11.1																																																																																											
LTE Band 41 15MHz 16QAM	UL Verification Services, Inc. High Frequency Substitution Measurement																																																																																																	
	Company:		Samsung																																																																																															
	Project #:		4788506351																																																																																															
	Date:		2018-06-22																																																																																															
	Test Engineer:		45585																																																																																															
	Configuration:		EUT / Z-Position																																																																																															
	Location:		Chamber 1																																																																																															
	Mode:		LTE_16QAM Band 41 Fundamentals, 15MHz Bandwidth																																																																																															
	Test Equipment:																																																																																																	
	Receiving:		Horn 3117[00168717], and Chamber 1 SMA Cables																																																																																															
Substitution:		Horn 3115[00161451], 3m N-type Cable																																																																																																
<table><tr><th>f MHz</th><th>SG reading (dBm)</th><th>Ant. Pol. (H/V)</th><th>Cable Loss (dB)</th><th>Antenna Gain (dBi)</th><th>EIRP (dBm)</th><th>Limit (dBm)</th><th>Delta (dB)</th><th>Notes</th></tr><tr><td>Low Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>2503.50</td><td>14.53</td><td>V</td><td>5.3</td><td>10.3</td><td>19.48</td><td>33.0</td><td>-13.5</td><td></td></tr><tr><td>2503.50</td><td>17.28</td><td>H</td><td>5.3</td><td>10.3</td><td>22.23</td><td>33.0</td><td>-10.8</td><td></td></tr><tr><td>Mid Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>2593.00</td><td>14.15</td><td>V</td><td>5.4</td><td>10.1</td><td>18.82</td><td>33.0</td><td>-14.2</td><td></td></tr><tr><td>2593.00</td><td>18.89</td><td>H</td><td>5.4</td><td>10.1</td><td>23.56</td><td>33.0</td><td>-9.4</td><td></td></tr><tr><td>High Ch</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>2682.50</td><td>14.83</td><td>V</td><td>5.5</td><td>10.2</td><td>19.46</td><td>33.0</td><td>-13.5</td><td></td></tr><tr><td>2682.50</td><td>16.64</td><td>H</td><td>5.5</td><td>10.2</td><td>21.28</td><td>33.0</td><td>-11.7</td><td></td></tr></table>									f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	Low Ch									2503.50	14.53	V	5.3	10.3	19.48	33.0	-13.5		2503.50	17.28	H	5.3	10.3	22.23	33.0	-10.8		Mid Ch									2593.00	14.15	V	5.4	10.1	18.82	33.0	-14.2		2593.00	18.89	H	5.4	10.1	23.56	33.0	-9.4		High Ch									2682.50	14.83	V	5.5	10.2	19.46	33.0	-13.5		2682.50	16.64	H	5.5	10.2	21.28	33.0	-11.7	
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																																										
Low Ch																																																																																																		
2503.50	14.53	V	5.3	10.3	19.48	33.0	-13.5																																																																																											
2503.50	17.28	H	5.3	10.3	22.23	33.0	-10.8																																																																																											
Mid Ch																																																																																																		
2593.00	14.15	V	5.4	10.1	18.82	33.0	-14.2																																																																																											
2593.00	18.89	H	5.4	10.1	23.56	33.0	-9.4																																																																																											
High Ch																																																																																																		
2682.50	14.83	V	5.5	10.2	19.46	33.0	-13.5																																																																																											
2682.50	16.64	H	5.5	10.2	21.28	33.0	-11.7																																																																																											

LTE Band 41 10MHz QPSK	UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 4788506351 Date: 2018-06-22 Test Engineer: 45585 Configuration: EUT / Z-Position Location: Chamber 1 Mode: LTE_QPSK Band 41 Fundamentals, 10MHz Bandwidth Test Equipment: Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables Substitution: Horn 3115[00161451], 3m N-type Cable								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Delta	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	2501.00	15.47	V	5.3	10.3	20.43	33.0	-12.6	
	2501.00	18.34	H	5.3	10.3	23.31	33.0	-9.7	
	Mid Ch								
	2593.00	15.07	V	5.4	10.1	19.74	33.0	-13.3	
	2593.00	18.16	H	5.4	10.1	22.83	33.0	-10.2	
	High Ch								
LTE Band 41 10MHz 16QAM	2685.00	14.34	V	5.5	10.2	18.97	33.0	-14.0	
	2685.00	16.98	H	5.5	10.2	21.61	33.0	-11.4	
LTE Band 41 10MHz 16QAM	UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 4788506351 Date: 2018-06-22 Test Engineer: 45585 Configuration: EUT / Z-Position Location: Chamber 1 Mode: LTE_16QAM Band 41 Fundamentals, 10MHz Bandwidth Test Equipment: Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables Substitution: Horn 3115[00161451], 3m N-type Cable								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Delta	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	2501.00	15.68	V	5.3	10.3	20.64	33.0	-12.4	
	2501.00	18.54	H	5.3	10.3	23.51	33.0	-9.5	
	Mid Ch								
	2593.00	14.91	V	5.4	10.1	19.58	33.0	-13.4	
	2593.00	18.02	H	5.4	10.1	22.69	33.0	-10.3	
	High Ch								
LTE Band 41 10MHz 16QAM	2685.00	14.78	V	5.5	10.2	19.41	33.0	-13.6	
	2685.00	17.40	H	5.5	10.2	22.03	33.0	-11.0	

LTE Band 41 5MHz QPSK	UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 4788506351 Date: 2018-06-22 Test Engineer: 45585 Configuration: EUT / Z-Position Location: Chamber 1 Mode: LTE_QPSK Band 41 Fundamentals, 5MHz Bandwidth Test Equipment: Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables Substitution: Horn 3115[00161451], 3m N-type Cable								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Delta	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	2498.50	14.30	V	5.3	10.3	19.30	33.0	-13.7	
	2498.50	14.97	H	5.3	10.3	19.97	33.0	-13.0	
	Mid Ch								
	2593.00	15.92	V	5.4	10.1	20.59	33.0	-12.4	
	2593.00	17.93	H	5.4	10.1	22.60	33.0	-10.4	
	High Ch								
LTE Band 41 5MHz 16QAM	2687.50	14.34	V	5.5	10.2	18.97	33.0	-14.0	
	2687.50	17.52	H	5.5	10.2	22.15	33.0	-10.8	
LTE Band 41 5MHz 16QAM	UL Verification Services, Inc. High Frequency Substitution Measurement Company: Samsung Project #: 4788506351 Date: 2018-06-22 Test Engineer: 45585 Configuration: EUT / Z-Position Location: Chamber 1 Mode: LTE_16QAM Band 41 Fundamentals, 5MHz Bandwidth Test Equipment: Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables Substitution: Horn 3115[00161451], 3m N-type Cable								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Delta	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	2498.50	14.28	V	5.3	10.3	19.28	33.0	-13.7	
	2498.50	15.02	H	5.3	10.3	20.02	33.0	-13.0	
	Mid Ch								
	2593.00	15.29	V	5.4	10.1	19.96	33.0	-13.0	
	2593.00	17.31	H	5.4	10.1	21.98	33.0	-11.0	
	High Ch								
LTE Band 41 5MHz 16QAM	2687.50	14.39	V	5.5	10.2	19.02	33.0	-14.0	
	2687.50	18.02	H	5.5	10.2	22.65	33.0	-10.3	

10.2. FIELD STRENGTH OF SPURIOUS RADIATION

RULE PART(S)

FCC: §2.1053, §22.917, §24.238 and §27. 53

LIMIT

Part 22.917(a) & Part 24.238(a) & Part 27.53(h) The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

Part 27: (m)(4) For mobile station, the attenuation factor shall be not less than $43 + 10 \log (P)$ dB at the channel edge and $(55 + 10 \log (P))$ dB at the 5.5 MHz from the channel edges.

Part 27.53 (g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB.

TEST PROCEDURE

ANSI / TIA / EIA 603 E Clause 2.2.12; ESU40 setting reference to 971168 D01 v03

For peak power measurement with a ESU40:

- a) Set the RBW = 100 KHz for emission below 1GHz and 1MHz for emissions above 1GHz
- b) Set VBW $\geq 3 \times$ RBW;
- c) Set span ≥ 1.5 times the OBW;
- d) Sweep time = auto couple;
- e) Detector = rms;
- f) Ensure that the number of measurement points $\geq$ span/RBW;
- g) Trace mode = max hold(GSM, LTE B41), average(WCDMA, LTE);

NOTE : Radiated spurious emissions were investigated below 30MHz, 30MHz – 1GHz and above 1GHz. There were no emissions found on below 30MHz and 30MHz – 1GHz.

RESULTS

UL Verification Services, Inc.									
Above 1GHz High Frequency Substitution Measurement									
Company:		Samsung							
Project #:		4788506351							
Date:		2018-06-20							
Test Engineer:		47989							
Configuration:		EUT / AC Adapter / Earphone, Y-Position							
Location:		Chamber 1							
Mode:		EGPRS 850 MHz Harmonics							
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamplifier (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 824.2MHz									
1648.40	-0.6	V	3.0	43.6	1.0	-43.2	-13.0	-30.2	
2472.60	-10.0	V	3.0	43.4	1.0	-52.4	-13.0	-39.4	
3296.80	-19.2	V	3.0	43.6	1.0	-61.9	-13.0	-48.9	
4121.00	-19.4	V	3.0	43.9	1.0	-62.3	-13.0	-49.3	
4945.20	-17.6	V	3.0	43.8	1.0	-60.4	-13.0	-47.4	
1648.40	-2.0	H	3.0	43.6	1.0	-44.6	-13.0	-31.6	
2472.60	-8.8	H	3.0	43.4	1.0	-51.2	-13.0	-38.2	
3296.80	-19.6	H	3.0	43.6	1.0	-62.2	-13.0	-49.2	
4121.00	-19.3	H	3.0	43.9	1.0	-62.2	-13.0	-49.2	
4945.20	-18.2	H	3.0	43.8	1.0	-61.0	-13.0	-48.0	
Mid Ch, 836.6MHz									
1673.20	0.7	V	3.0	43.6	1.0	-41.9	-13.0	-28.9	
2509.80	-7.4	V	3.0	43.4	1.0	-49.8	-13.0	-36.8	
3346.40	-20.4	V	3.0	43.6	1.0	-63.0	-13.0	-50.0	
4183.00	-19.4	V	3.0	43.9	1.0	-62.3	-13.0	-49.3	
5019.60	-17.9	V	3.0	43.8	1.0	-60.7	-13.0	-47.7	
1673.20	-3.3	H	3.0	43.6	1.0	-45.8	-13.0	-32.8	
2509.80	-8.1	H	3.0	43.4	1.0	-50.5	-13.0	-37.5	
3346.40	-20.0	H	3.0	43.6	1.0	-62.7	-13.0	-49.7	
4183.00	-19.2	H	3.0	43.9	1.0	-62.1	-13.0	-49.1	
5019.60	-18.6	H	3.0	43.8	1.0	-61.3	-13.0	-48.3	
High Ch, 848.8MHz									
1697.60	1.7	V	3.0	43.6	1.0	-40.9	-13.0	-27.9	
2546.40	-9.2	V	3.0	43.4	1.0	-51.6	-13.0	-38.6	
3395.20	-19.7	V	3.0	43.7	1.0	-62.4	-13.0	-49.4	
4244.00	-19.2	V	3.0	43.9	1.0	-62.1	-13.0	-49.1	
5092.80	-17.7	V	3.0	43.8	1.0	-60.4	-13.0	-47.4	
1697.60	-0.3	H	3.0	43.6	1.0	-42.8	-13.0	-29.8	
2546.40	-8.6	H	3.0	43.4	1.0	-51.1	-13.0	-38.1	
3395.20	-19.9	H	3.0	43.7	1.0	-62.5	-13.0	-49.5	
4244.00	-19.1	H	3.0	43.9	1.0	-62.0	-13.0	-49.0	
5092.80	-18.2	H	3.0	43.8	1.0	-61.0	-13.0	-48.0	

GSM

GSM850
EGPRS

GSM 1900

GSM GSM1900 GPRS	UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement Company: Samsung Project #: 4788506351 Date: 2018-06-21 Test Engineer: 47989 Configuration: EUT / AC Adapter / Earphone, X-Position Location: Chamber 1 Mode: GPRS 1900 MHz Harmonics									
	f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Ch, 1850.2MHz									
	3700.40	2.6	V	3.0	43.8	1.0	-40.2	-13.0	-27.2	
	5550.60	12.0	V	3.0	43.7	1.0	-30.7	-13.0	-17.7	
	7400.80	-10.0	V	3.0	42.5	1.0	-51.5	-13.0	-38.5	
	9251.00	-8.3	V	3.0	41.3	1.0	-48.5	-13.0	-35.5	
	11101.20	-12.7	V	3.0	40.9	1.0	-52.6	-13.0	-39.6	
	3700.40	-0.6	H	3.0	43.8	1.0	-43.4	-13.0	-30.4	
	5550.60	4.5	H	3.0	43.7	1.0	-38.2	-13.0	-25.2	
	7400.80	-13.4	H	3.0	42.5	1.0	-54.9	-13.0	-41.9	
	9251.00	-12.4	H	3.0	41.3	1.0	-52.7	-13.0	-39.7	
	11101.20	-15.8	H	3.0	40.9	1.0	-55.7	-13.0	-42.7	
	Mid Ch, 1880MHz									
	3760.00	5.1	V	3.0	43.8	1.0	-37.7	-13.0	-24.7	
	5640.00	9.3	V	3.0	43.7	1.0	-33.4	-13.0	-20.4	
	7520.00	-10.1	V	3.0	42.5	1.0	-51.6	-13.0	-38.6	
	9400.00	-3.5	V	3.0	41.1	1.0	-43.6	-13.0	-30.6	
	11280.00	-7.0	V	3.0	41.0	1.0	-46.9	-13.0	-33.9	
	3760.00	1.8	H	3.0	43.8	1.0	-41.0	-13.0	-28.0	
	5640.00	2.8	H	3.0	43.7	1.0	-39.9	-13.0	-26.9	
	7520.00	-13.0	H	3.0	42.5	1.0	-54.4	-13.0	-41.4	
	9400.00	-8.8	H	3.0	41.1	1.0	-49.0	-13.0	-36.0	
	11280.00	-10.4	H	3.0	41.0	1.0	-50.4	-13.0	-37.4	
	High Ch, 1909.8MHz									
	3819.60	4.1	V	3.0	43.8	1.0	-38.8	-13.0	-25.8	
	5729.40	5.9	V	3.0	43.7	1.0	-36.8	-13.0	-23.8	
	7639.20	-12.5	V	3.0	42.4	1.0	-53.9	-13.0	-40.9	
	9549.00	-7.0	V	3.0	41.0	1.0	-47.0	-13.0	-34.0	
	11458.80	-1.7	V	3.0	41.0	1.0	-41.8	-13.0	-28.8	
	3819.60	1.4	H	3.0	43.8	1.0	-41.4	-13.0	-28.4	
	5729.40	-2.5	H	3.0	43.7	1.0	-45.2	-13.0	-32.2	
	7639.20	-14.0	H	3.0	42.4	1.0	-55.4	-13.0	-42.4	
	9549.00	-9.6	H	3.0	41.0	1.0	-49.6	-13.0	-36.6	
	11458.80	-5.0	H	3.0	41.0	1.0	-45.0	-13.0	-32.0	

UL Verification Services, Inc.									
Above 1GHz High Frequency Substitution Measurement									
Company:		Samsung							
Project #:		4788506351							
Date:		2018-06-21							
Test Engineer:		47989							
Configuration:		EUT / AC Adapter / Earphone, X-Position							
Location:		Chamber 1							
Mode:		EGPRS 1900 MHz Harmonics							
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1850.2MHz									
3700.40	-5.6	V	3.0	43.8	1.0	-48.3	-13.0	-35.3	
5550.60	-0.6	V	3.0	43.7	1.0	-43.3	-13.0	-30.3	
7400.80	-16.6	V	3.0	42.5	1.0	-58.1	-13.0	-45.1	
9251.00	-15.3	V	3.0	41.3	1.0	-55.5	-13.0	-42.5	
11101.20	-16.7	V	3.0	40.9	1.0	-56.6	-13.0	-43.6	
3700.40	-8.0	H	3.0	43.8	1.0	-50.8	-13.0	-37.8	
5550.60	-7.8	H	3.0	43.7	1.0	-50.5	-13.0	-37.5	
7400.80	-16.5	H	3.0	42.5	1.0	-58.0	-13.0	-45.0	
9251.00	-17.9	H	3.0	41.3	1.0	-58.2	-13.0	-45.2	
11101.20	-14.9	H	3.0	40.9	1.0	-54.8	-13.0	-41.8	
Mid Ch, 1880MHz									
3760.00	-4.2	V	3.0	43.8	1.0	-47.0	-13.0	-34.0	
5640.00	-2.8	V	3.0	43.7	1.0	-45.5	-13.0	-32.5	
7520.00	-16.6	V	3.0	42.5	1.0	-58.1	-13.0	-45.1	
9400.00	-15.9	V	3.0	41.1	1.0	-56.1	-13.0	-43.1	
11280.00	-15.9	V	3.0	41.0	1.0	-55.9	-13.0	-42.9	
3760.00	-7.0	H	3.0	43.8	1.0	-49.8	-13.0	-36.8	
5640.00	-10.5	H	3.0	43.7	1.0	-53.2	-13.0	-40.2	
7520.00	-16.2	H	3.0	42.5	1.0	-57.6	-13.0	-44.6	
9400.00	-17.0	H	3.0	41.1	1.0	-57.1	-13.0	-44.1	
11280.00	-14.6	H	3.0	41.0	1.0	-54.6	-13.0	-41.6	
High Ch, 1909.8MHz									
3819.60	-4.1	V	3.0	43.8	1.0	-46.9	-13.0	-33.9	
5729.40	-6.8	V	3.0	43.7	1.0	-49.5	-13.0	-36.5	
7639.20	-17.3	V	3.0	42.4	1.0	-58.7	-13.0	-45.7	
9549.00	-18.0	V	3.0	41.0	1.0	-58.0	-13.0	-45.0	
11458.80	-16.1	V	3.0	41.0	1.0	-56.1	-13.0	-43.1	
3819.60	-7.3	H	3.0	43.8	1.0	-50.1	-13.0	-37.1	
5729.40	-14.0	H	3.0	43.7	1.0	-56.7	-13.0	-43.7	
7639.20	-16.7	H	3.0	42.4	1.0	-58.1	-13.0	-45.1	
9549.00	-17.4	H	3.0	41.0	1.0	-57.4	-13.0	-44.4	
11458.80	-14.6	H	3.0	41.0	1.0	-54.6	-13.0	-41.6	

GSM
GSM1900
EGPRS

WCDMA Band 5

WCDMA

Band 5
REL99

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788506351
Date: 2018-06-20
Test Engineer: 47989
Configuration: EUT / AC Adapter / Earphone, Y-Position
Location: Chamber 1
Mode: Rel99 Band 5 Harmonics

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 826.4MHz									
1652.80	-16.1	V	3.0	43.6	1.0	-58.6	-13.0	-45.6	
2479.20	-21.3	V	3.0	43.4	1.0	-63.7	-13.0	-50.7	
3305.60	-15.4	V	3.0	43.6	1.0	-58.0	-13.0	-45.0	
4132.00	-19.7	V	3.0	43.9	1.0	-62.6	-13.0	-49.6	
1652.80	-18.8	H	3.0	43.6	1.0	-61.4	-13.0	-48.4	
2479.20	-22.0	H	3.0	43.4	1.0	-64.4	-13.0	-51.4	
3305.60	-20.2	H	3.0	43.6	1.0	-62.8	-13.0	-49.8	
4132.00	-19.8	H	3.0	43.9	1.0	-62.7	-13.0	-49.7	
Mid Ch, 836.6MHz									
1673.20	-12.5	V	3.0	43.6	1.0	-55.1	-13.0	-42.1	
2509.80	-22.1	V	3.0	43.4	1.0	-64.5	-13.0	-51.5	
3346.40	-19.9	V	3.0	43.6	1.0	-62.5	-13.0	-49.5	
4183.00	-19.2	V	3.0	43.9	1.0	-62.1	-13.0	-49.1	
1673.20	-18.6	H	3.0	43.6	1.0	-61.1	-13.0	-48.1	
2509.80	-22.8	H	3.0	43.4	1.0	-65.2	-13.0	-52.2	
3346.40	-20.9	H	3.0	43.6	1.0	-63.5	-13.0	-50.5	
4183.00	-20.1	H	3.0	43.9	1.0	-62.9	-13.0	-49.9	
High Ch, 846.6MHz									
1693.20	-14.5	V	3.0	43.6	1.0	-57.0	-13.0	-44.0	
2539.80	-13.3	V	3.0	43.4	1.0	-55.7	-13.0	-42.7	
3386.40	-16.0	V	3.0	43.7	1.0	-58.7	-13.0	-45.7	
4233.00	-15.8	V	3.0	43.9	1.0	-58.7	-13.0	-45.7	
1693.20	-16.4	H	3.0	43.6	1.0	-58.9	-13.0	-45.9	
2539.80	-17.6	H	3.0	43.4	1.0	-60.1	-13.0	-47.1	
3386.40	-15.5	H	3.0	43.7	1.0	-58.1	-13.0	-45.1	
4233.00	-18.4	H	3.0	43.9	1.0	-61.3	-13.0	-48.3	

WCDMA

Band 5
HSDPA

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4788506351
Date: 2018-06-20
Test Engineer: 47989
Configuration: EUT / AC Adapter / Earphone, Y-Position
Location: Chamber 1
Mode: HSDPA Band 5 Harmonics

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 826.4MHz									
1652.80	-17.1	V	3.0	43.6	1.0	-59.6	-13.0	-46.6	
2479.20	-21.3	V	3.0	43.4	1.0	-63.8	-13.0	-50.8	
3305.60	-16.4	V	3.0	43.6	1.0	-59.0	-13.0	-46.0	
4132.00	-20.0	V	3.0	43.9	1.0	-62.9	-13.0	-49.9	
1652.80	-20.2	H	3.0	43.6	1.0	-62.8	-13.0	-49.8	
2479.20	-22.0	H	3.0	43.4	1.0	-64.4	-13.0	-51.4	
3305.60	-20.3	H	3.0	43.6	1.0	-63.0	-13.0	-50.0	
4132.00	-19.7	H	3.0	43.9	1.0	-62.6	-13.0	-49.6	
Mid Ch, 836.6MHz									
1673.20	-14.8	V	3.0	43.6	1.0	-57.4	-13.0	-44.4	
2509.80	-22.7	V	3.0	43.4	1.0	-65.1	-13.0	-52.1	
3346.40	-19.0	V	3.0	43.6	1.0	-61.7	-13.0	-48.7	
4183.00	-19.3	V	3.0	43.9	1.0	-62.2	-13.0	-49.2	
1673.20	-20.0	H	3.0	43.6	1.0	-62.5	-13.0	-49.5	
2509.80	-22.5	H	3.0	43.4	1.0	-65.0	-13.0	-52.0	
3346.40	-20.7	H	3.0	43.6	1.0	-63.3	-13.0	-50.3	
4183.00	-19.8	H	3.0	43.9	1.0	-62.6	-13.0	-49.6	
High Ch, 846.6MHz									
1693.20	-16.4	V	3.0	43.6	1.0	-59.0	-13.0	-46.0	
2539.80	-16.1	V	3.0	43.4	1.0	-58.5	-13.0	-45.5	
3386.40	-17.1	V	3.0	43.7	1.0	-59.7	-13.0	-46.7	
4233.00	-16.2	V	3.0	43.9	1.0	-59.0	-13.0	-46.0	
1693.20	-18.9	H	3.0	43.6	1.0	-61.5	-13.0	-48.5	
2539.80	-21.1	H	3.0	43.4	1.0	-63.5	-13.0	-50.5	
3386.40	-18.2	H	3.0	43.7	1.0	-60.9	-13.0	-47.9	
4233.00	-18.8	H	3.0	43.9	1.0	-61.7	-13.0	-48.7	

WCDMA Band 2

WCDMA Band 2 REL99	UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement Company: Samsung Project #: 4788506351 Date: 2018-06-21 Test Engineer: 47989 Configuration: EUT / AC Adapter / Earphone, X-Position Location: Chamber 1 Mode: Rel99 Band 2 Harmonics									
	f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Ch, 1852.4MHz									
	3704.80	-7.1	V	3.0	43.8	1.0	-49.8	-13.0	-36.8	
	5557.20	4.3	V	3.0	43.7	1.0	-38.5	-13.0	-25.5	
	7409.60	-9.6	V	3.0	42.5	1.0	-51.1	-13.0	-38.1	
	9262.00	-6.7	V	3.0	41.3	1.0	-46.9	-13.0	-33.9	
	11114.40	-9.1	V	3.0	40.9	1.0	-49.0	-13.0	-36.0	
	3704.80	-9.8	H	3.0	43.8	1.0	-52.5	-13.0	-39.5	
	5557.20	-4.7	H	3.0	43.7	1.0	-47.4	-13.0	-34.4	
	7409.60	-12.0	H	3.0	42.5	1.0	-53.5	-13.0	-40.5	
	9262.00	-11.4	H	3.0	41.3	1.0	-51.6	-13.0	-38.6	
	11114.40	-12.1	H	3.0	40.9	1.0	-52.0	-13.0	-39.0	
	Mid Ch, 1880MHz									
	3760.00	-5.5	V	3.0	43.8	1.0	-48.3	-13.0	-35.3	
	5640.00	3.2	V	3.0	43.7	1.0	-39.5	-13.0	-26.5	
	7520.00	-9.4	V	3.0	42.5	1.0	-50.9	-13.0	-37.9	
	9400.00	-4.2	V	3.0	41.1	1.0	-44.3	-13.0	-31.3	
	11280.00	-7.4	V	3.0	41.0	1.0	-47.3	-13.0	-34.3	
	3760.00	-9.6	H	3.0	43.8	1.0	-52.4	-13.0	-39.4	
	5640.00	-5.5	H	3.0	43.7	1.0	-48.2	-13.0	-35.2	
	7520.00	-10.2	H	3.0	42.5	1.0	-51.6	-13.0	-38.6	
	9400.00	-9.5	H	3.0	41.1	1.0	-49.6	-13.0	-36.6	
	11280.00	-10.1	H	3.0	41.0	1.0	-50.1	-13.0	-37.1	
	High Ch, 1907.6MHz									
	3815.20	-6.0	V	3.0	43.8	1.0	-48.8	-13.0	-35.8	
	5722.80	1.2	V	3.0	43.7	1.0	-41.5	-13.0	-28.5	
	7630.40	-6.8	V	3.0	42.4	1.0	-48.2	-13.0	-35.2	
	9538.00	-5.6	V	3.0	41.0	1.0	-45.6	-13.0	-32.6	
	11445.60	-8.2	V	3.0	41.0	1.0	-48.2	-13.0	-35.2	
	3815.20	-10.1	H	3.0	43.8	1.0	-52.9	-13.0	-39.9	
	5722.80	-4.0	H	3.0	43.7	1.0	-46.7	-13.0	-33.7	
	7630.40	-9.7	H	3.0	42.4	1.0	-51.1	-13.0	-38.1	
	9538.00	-11.0	H	3.0	41.0	1.0	-51.0	-13.0	-38.0	
	11445.60	-7.2	H	3.0	41.0	1.0	-47.2	-13.0	-34.2	

UL Verification Services, Inc.									
Above 1GHz High Frequency Substitution Measurement									
Company:		Samsung							
Project #:		4788506351							
Date:		2018-06-21							
Test Engineer:		47989							
Configuration:		EUT / AC Adapter / Earphone, X-Position							
Location:		Chamber 1							
Mode:		HSDPA Band 2 Harmonics							
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamplifier (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1852.4MHz									
3704.80	-7.7	V	3.0	43.8	1.0	-50.4	-13.0	-37.4	
5557.20	4.3	V	3.0	43.7	1.0	-38.4	-13.0	-25.4	
7409.60	-9.2	V	3.0	42.5	1.0	-50.8	-13.0	-37.8	
9262.00	-6.7	V	3.0	41.3	1.0	-46.9	-13.0	-33.9	
11114.40	-0.6	V	3.0	40.9	1.0	-40.5	-13.0	-27.5	
3704.80	-10.2	H	3.0	43.8	1.0	-53.0	-13.0	-40.0	
5557.20	-4.7	H	3.0	43.7	1.0	-47.4	-13.0	-34.4	
7409.60	-11.4	H	3.0	42.5	1.0	-53.0	-13.0	-40.0	
9262.00	-10.5	H	3.0	41.3	1.0	-50.7	-13.0	-37.7	
11114.40	-12.3	H	3.0	40.9	1.0	-52.2	-13.0	-39.2	
Mid Ch, 1880MHz									
3760.00	-5.0	V	3.0	43.8	1.0	-47.8	-13.0	-34.8	
5640.00	2.3	V	3.0	43.7	1.0	-40.4	-13.0	-27.4	
7520.00	-7.5	V	3.0	42.5	1.0	-49.0	-13.0	-36.0	
9400.00	-2.6	V	3.0	41.1	1.0	-42.8	-13.0	-29.8	
11280.00	-5.2	V	3.0	41.0	1.0	-45.1	-13.0	-32.1	
3760.00	-8.4	H	3.0	43.8	1.0	-51.2	-13.0	-38.2	
5640.00	-6.2	H	3.0	43.7	1.0	-48.9	-13.0	-35.9	
7520.00	-9.6	H	3.0	42.5	1.0	-51.0	-13.0	-38.0	
9400.00	-8.5	H	3.0	41.1	1.0	-48.7	-13.0	-35.7	
11280.00	-11.2	H	3.0	41.0	1.0	-51.2	-13.0	-38.2	
High Ch, 1907.6MHz									
3815.20	-6.7	V	3.0	43.8	1.0	-49.5	-13.0	-36.5	
5722.80	1.9	V	3.0	43.7	1.0	-40.7	-13.0	-27.7	
7630.40	-6.6	V	3.0	42.4	1.0	-48.0	-13.0	-35.0	
9538.00	-6.2	V	3.0	41.0	1.0	-46.2	-13.0	-33.2	
11445.60	-9.2	V	3.0	41.0	1.0	-49.2	-13.0	-36.2	
3815.20	-10.5	H	3.0	43.8	1.0	-53.3	-13.0	-40.3	
5722.80	-4.9	H	3.0	43.7	1.0	-47.6	-13.0	-34.6	
7630.40	-9.9	H	3.0	42.4	1.0	-51.3	-13.0	-38.3	
9538.00	-11.0	H	3.0	41.0	1.0	-51.0	-13.0	-38.0	
11445.60	-7.2	H	3.0	41.0	1.0	-47.2	-13.0	-34.2	

LTE Band 5

LTE Band 5 10MHz QPSK	UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement Company: Samsung Project #: 4788506351 Date: 2018-06-20 Test Engineer: 45585 Configuration: EUT / Adapter / Earphone, Y-Position Location: Chamber 1 Mode: LTE_QPSK Band 5 Harmonics, 10MHz Bandwidth									
	f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Ch, 829MHz									
	1658.00	-10.9	V	3.0	43.6	1.0	-53.4	-13.0	-40.4	
	2487.00	-18.2	V	3.0	43.4	1.0	-60.6	-13.0	-47.6	
	3316.00	-11.2	V	3.0	43.6	1.0	-53.8	-13.0	-40.8	
	4145.00	-13.2	V	3.0	43.9	1.0	-56.0	-13.0	-43.0	
	4974.00	-17.4	V	3.0	43.8	1.0	-60.2	-13.0	-47.2	
	1658.00	-11.9	H	3.0	43.6	1.0	-54.5	-13.0	-41.5	
	2487.00	-21.1	H	3.0	43.4	1.0	-63.5	-13.0	-50.5	
	3316.00	-20.7	H	3.0	43.6	1.0	-63.4	-13.0	-50.4	
	4145.00	-20.2	H	3.0	43.9	1.0	-63.1	-13.0	-50.1	
	4974.00	-19.6	H	3.0	43.8	1.0	-62.4	-13.0	-49.4	
	Mid Ch, 836.5MHz									
	1673.00	-7.5	V	3.0	43.6	1.0	-50.1	-13.0	-37.1	
	2509.50	-16.0	V	3.0	43.4	1.0	-58.4	-13.0	-45.4	
	3346.00	-13.6	V	3.0	43.6	1.0	-56.2	-13.0	-43.2	
	4182.50	-12.6	V	3.0	43.9	1.0	-55.5	-13.0	-42.5	
	5019.00	-15.7	V	3.0	43.8	1.0	-58.5	-13.0	-45.5	
	1673.00	-13.8	H	3.0	43.6	1.0	-56.3	-13.0	-43.3	
	2509.50	-20.2	H	3.0	43.4	1.0	-62.7	-13.0	-49.7	
	3346.00	-18.8	H	3.0	43.6	1.0	-61.5	-13.0	-48.5	
	4182.50	-20.7	H	3.0	43.9	1.0	-63.5	-13.0	-50.5	
	5019.00	-19.8	H	3.0	43.8	1.0	-62.6	-13.0	-49.6	
	High Ch, 844MHz									
	1688.00	-5.4	V	3.0	43.6	1.0	-47.9	-13.0	-34.9	
	2532.00	-19.0	V	3.0	43.4	1.0	-61.5	-13.0	-48.5	
	3376.00	-13.5	V	3.0	43.7	1.0	-56.2	-13.0	-43.2	
	4220.00	-19.3	V	3.0	43.9	1.0	-62.1	-13.0	-49.1	
	5064.00	-18.6	V	3.0	43.8	1.0	-61.4	-13.0	-48.4	
	1688.00	-12.9	H	3.0	43.6	1.0	-55.5	-13.0	-42.5	
	2532.00	-20.8	H	3.0	43.4	1.0	-63.3	-13.0	-50.3	
	3376.00	-20.9	H	3.0	43.7	1.0	-63.6	-13.0	-50.6	
	4220.00	-19.6	H	3.0	43.9	1.0	-62.4	-13.0	-49.4	
	5064.00	-19.8	H	3.0	43.8	1.0	-62.6	-13.0	-49.6	

UL Verification Services, Inc.									
Above 1GHz High Frequency Substitution Measurement									
Company:		Samsung							
Project #:		4788506351							
Date:		2018-06-20							
Test Engineer:		45585							
Configuration:		EUT / Adapter / Earphone, Y-Position							
Location:		Chamber 1							
Mode:		LTE_16QAM Band 5 Harmonics, 10MHz Bandwidth							
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 829MHz									
1658.00	-12.7	V	3.0	43.6	1.0	-55.3	-13.0	-42.3	
2487.00	-19.6	V	3.0	43.4	1.0	-62.0	-13.0	-49.0	
3316.00	-11.8	V	3.0	43.6	1.0	-54.4	-13.0	-41.4	
4145.00	-14.1	V	3.0	43.9	1.0	-57.0	-13.0	-44.0	
4974.00	-17.7	V	3.0	43.8	1.0	-60.5	-13.0	-47.5	
1658.00	-14.3	H	3.0	43.6	1.0	-56.9	-13.0	-43.9	
2487.00	-21.4	H	3.0	43.4	1.0	-63.8	-13.0	-50.8	
3316.00	-20.8	H	3.0	43.6	1.0	-63.4	-13.0	-50.4	
4145.00	-20.2	H	3.0	43.9	1.0	-63.1	-13.0	-50.1	
4974.00	-19.6	H	3.0	43.8	1.0	-62.4	-13.0	-49.4	
Mid Ch, 836.5MHz									
1673.00	-9.7	V	3.0	43.6	1.0	-52.3	-13.0	-39.3	
2509.50	-17.2	V	3.0	43.4	1.0	-59.7	-13.0	-46.7	
3346.00	-14.7	V	3.0	43.6	1.0	-57.3	-13.0	-44.3	
4182.50	-13.5	V	3.0	43.9	1.0	-56.3	-13.0	-43.3	
5019.00	-16.4	V	3.0	43.8	1.0	-59.2	-13.0	-46.2	
1673.00	-14.9	H	3.0	43.6	1.0	-57.5	-13.0	-44.5	
2509.50	-21.0	H	3.0	43.4	1.0	-63.4	-13.0	-50.4	
3346.00	-19.4	H	3.0	43.6	1.0	-62.0	-13.0	-49.0	
4182.50	-20.7	H	3.0	43.9	1.0	-63.6	-13.0	-50.6	
5019.00	-19.8	H	3.0	43.8	1.0	-62.6	-13.0	-49.6	
High Ch, 844MHz									
1688.00	-6.7	V	3.0	43.6	1.0	-49.3	-13.0	-36.3	
2532.00	-19.9	V	3.0	43.4	1.0	-62.3	-13.0	-49.3	
3376.00	-12.9	V	3.0	43.7	1.0	-55.6	-13.0	-42.6	
4220.00	-19.5	V	3.0	43.9	1.0	-62.4	-13.0	-49.4	
5064.00	-18.9	V	3.0	43.8	1.0	-61.7	-13.0	-48.7	
1688.00	-14.4	H	3.0	43.6	1.0	-56.9	-13.0	-43.9	
2532.00	-21.3	H	3.0	43.4	1.0	-63.8	-13.0	-50.8	
3376.00	-21.0	H	3.0	43.7	1.0	-63.6	-13.0	-50.6	
4220.00	-19.6	H	3.0	43.9	1.0	-62.5	-13.0	-49.5	
5064.00	-19.8	H	3.0	43.8	1.0	-62.6	-13.0	-49.6	

UL Verification Services, Inc.									
Above 1GHz High Frequency Substitution Measurement									
Company:		Samsung							
Project #:		4788506351							
Date:		2018-06-20							
Test Engineer:		45585							
Configuration:		EUT / Adapter / Earphone, Y-Position							
Location:		Chamber 1							
Mode:		LTE_QPSK Band 5 Harmonics, 5MHz Bandwidth							
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 826.5MHz									
1653.00	-4.8	V	3.0	43.6	1.0	-47.4	-13.0	-34.4	
2479.50	-17.9	V	3.0	43.4	1.0	-60.3	-13.0	-47.3	
3306.00	-12.1	V	3.0	43.6	1.0	-54.8	-13.0	-41.8	
4132.50	-15.0	V	3.0	43.9	1.0	-57.9	-13.0	-44.9	
4959.00	-17.5	V	3.0	43.8	1.0	-60.3	-13.0	-47.3	
1653.00	-13.2	H	3.0	43.6	1.0	-55.8	-13.0	-42.8	
2479.50	-20.5	H	3.0	43.4	1.0	-62.9	-13.0	-49.9	
3306.00	-20.5	H	3.0	43.6	1.0	-63.1	-13.0	-50.1	
4132.50	-20.2	H	3.0	43.9	1.0	-63.1	-13.0	-50.1	
4959.00	-19.5	H	3.0	43.8	1.0	-62.3	-13.0	-49.3	
Mid Ch, 836.5MHz									
1673.00	-9.2	V	3.0	43.6	1.0	-51.8	-13.0	-38.8	
2509.50	-17.3	V	3.0	43.4	1.0	-59.7	-13.0	-46.7	
3346.00	-14.3	V	3.0	43.6	1.0	-57.0	-13.0	-44.0	
4182.50	-20.7	V	3.0	43.9	1.0	-63.6	-13.0	-50.6	
5019.00	-18.3	V	3.0	43.8	1.0	-61.1	-13.0	-48.1	
1673.00	-12.8	H	3.0	43.6	1.0	-55.3	-13.0	-42.3	
2509.50	-21.4	H	3.0	43.4	1.0	-63.8	-13.0	-50.8	
3346.00	-21.5	H	3.0	43.6	1.0	-64.1	-13.0	-51.1	
4182.50	-20.7	H	3.0	43.9	1.0	-63.5	-13.0	-50.5	
5019.00	-19.6	H	3.0	43.8	1.0	-62.3	-13.0	-49.3	
High Ch, 846.5MHz									
1693.00	-4.9	V	3.0	43.6	1.0	-47.5	-13.0	-34.5	
2539.50	-13.8	V	3.0	43.4	1.0	-56.3	-13.0	-43.3	
3386.00	-10.9	V	3.0	43.7	1.0	-53.5	-13.0	-40.5	
4232.50	-7.9	V	3.0	43.9	1.0	-50.8	-13.0	-37.8	
5079.00	-11.4	V	3.0	43.8	1.0	-54.2	-13.0	-41.2	
1693.00	-14.3	H	3.0	43.6	1.0	-56.9	-13.0	-43.9	
2539.50	-15.5	H	3.0	43.4	1.0	-57.9	-13.0	-44.9	
3386.00	-15.3	H	3.0	43.7	1.0	-57.9	-13.0	-44.9	
4232.50	-17.3	H	3.0	43.9	1.0	-60.1	-13.0	-47.1	
5079.00	-19.1	H	3.0	43.8	1.0	-61.9	-13.0	-48.9	

UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement									
Company:		Samsung							
Project #:		4788506351							
Date:		2018-06-20							
Test Engineer:		45585							
Configuration:		EUT / Adapter / Earphone, Y-Position							
Location:		Chamber 1							
Mode:		LTE_16QAM Band 5 Harmonics, 5MHz Bandwidth							
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamplifier (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 826.5MHz									
1653.00	-6.3	V	3.0	43.6	1.0	-48.9	-13.0	-35.9	
2479.50	-18.9	V	3.0	43.4	1.0	-61.3	-13.0	-48.3	
3306.00	-12.6	V	3.0	43.6	1.0	-55.3	-13.0	-42.3	
4132.50	-15.8	V	3.0	43.9	1.0	-58.7	-13.0	-45.7	
4959.00	-17.8	V	3.0	43.8	1.0	-60.6	-13.0	-47.6	
1653.00	-14.9	H	3.0	43.6	1.0	-57.5	-13.0	-44.5	
2479.50	-21.0	H	3.0	43.4	1.0	-63.4	-13.0	-50.4	
3306.00	-20.6	H	3.0	43.6	1.0	-63.3	-13.0	-50.3	
4132.50	-20.3	H	3.0	43.9	1.0	-63.2	-13.0	-50.2	
4959.00	-19.5	H	3.0	43.8	1.0	-62.3	-13.0	-49.3	
Mid Ch, 836.5MHz									
1673.00	-10.9	V	3.0	43.6	1.0	-53.5	-13.0	-40.5	
2509.50	-18.7	V	3.0	43.4	1.0	-61.1	-13.0	-48.1	
3346.00	-15.2	V	3.0	43.6	1.0	-57.8	-13.0	-44.8	
4182.50	-20.7	V	3.0	43.9	1.0	-63.5	-13.0	-50.5	
5019.00	-18.5	V	3.0	43.8	1.0	-61.3	-13.0	-48.3	
1673.00	-14.4	H	3.0	43.6	1.0	-57.0	-13.0	-44.0	
2509.50	-21.8	H	3.0	43.4	1.0	-64.3	-13.0	-51.3	
3346.00	-21.4	H	3.0	43.6	1.0	-64.1	-13.0	-51.1	
4182.50	-20.6	H	3.0	43.9	1.0	-63.5	-13.0	-50.5	
5019.00	-19.5	H	3.0	43.8	1.0	-62.3	-13.0	-49.3	
High Ch, 846.5MHz									
1693.00	-6.1	V	3.0	43.6	1.0	-48.7	-13.0	-35.7	
2539.50	-15.2	V	3.0	43.4	1.0	-57.6	-13.0	-44.6	
3386.00	-11.9	V	3.0	43.7	1.0	-54.5	-13.0	-41.5	
4232.50	-8.9	V	3.0	43.9	1.0	-51.7	-13.0	-38.7	
5079.00	-12.4	V	3.0	43.8	1.0	-55.2	-13.0	-42.2	
1693.00	-15.5	H	3.0	43.6	1.0	-58.0	-13.0	-45.0	
2539.50	-16.5	H	3.0	43.4	1.0	-59.0	-13.0	-46.0	
3386.00	-15.9	H	3.0	43.7	1.0	-58.6	-13.0	-45.6	
4232.50	-17.7	H	3.0	43.9	1.0	-60.5	-13.0	-47.5	
5079.00	-19.2	H	3.0	43.8	1.0	-61.9	-13.0	-48.9	

UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement									
Company:		Samsung							
Project #:		4788506351							
Date:		2018-06-20							
Test Engineer:		45585							
Configuration:		EUT / Adapter / Earphone, Y-Position							
Location:		Chamber 1							
Mode:		LTE_QPSK Band 5 Harmonics, 3MHz Bandwidth							
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 825.5MHz									
1651.00	-6.2	V	3.0	43.6	1.0	-48.7	-13.0	-35.7	
2476.50	-18.8	V	3.0	43.4	1.0	-61.2	-13.0	-48.2	
3302.00	-11.0	V	3.0	43.6	1.0	-53.6	-13.0	-40.6	
4127.50	-14.4	V	3.0	43.9	1.0	-57.2	-13.0	-44.2	
4953.00	-16.6	V	3.0	43.8	1.0	-59.4	-13.0	-46.4	
1651.00	-9.1	H	3.0	43.6	1.0	-51.7	-13.0	-38.7	
2476.50	-21.1	H	3.0	43.4	1.0	-63.5	-13.0	-50.5	
3302.00	-20.7	H	3.0	43.6	1.0	-63.3	-13.0	-50.3	
4127.50	-18.1	H	3.0	43.9	1.0	-61.0	-13.0	-48.0	
4953.00	-19.6	H	3.0	43.8	1.0	-62.4	-13.0	-49.4	
Mid Ch, 836.5MHz									
1673.00	-8.6	V	3.0	43.6	1.0	-51.1	-13.0	-38.1	
2509.50	-18.4	V	3.0	43.4	1.0	-60.8	-13.0	-47.8	
3346.00	-21.5	V	3.0	43.6	1.0	-64.2	-13.0	-51.2	
4182.50	-20.3	V	3.0	43.9	1.0	-63.2	-13.0	-50.2	
5019.00	-19.2	V	3.0	43.8	1.0	-62.0	-13.0	-49.0	
1673.00	-14.2	H	3.0	43.6	1.0	-56.7	-13.0	-43.7	
2509.50	-21.4	H	3.0	43.4	1.0	-63.8	-13.0	-50.8	
3346.00	-20.8	H	3.0	43.6	1.0	-63.5	-13.0	-50.5	
4182.50	-20.1	H	3.0	43.9	1.0	-63.0	-13.0	-50.0	
5019.00	-19.7	H	3.0	43.8	1.0	-62.4	-13.0	-49.4	
High Ch, 847.5MHz									
1695.00	-11.0	V	3.0	43.6	1.0	-53.6	-13.0	-40.6	
2542.50	-16.1	V	3.0	43.4	1.0	-58.6	-13.0	-45.6	
3390.00	-11.8	V	3.0	43.7	1.0	-54.5	-13.0	-41.5	
4237.50	-13.4	V	3.0	43.9	1.0	-56.3	-13.0	-43.3	
5085.00	-15.3	V	3.0	43.8	1.0	-58.0	-13.0	-45.0	
1695.00	-13.0	H	3.0	43.6	1.0	-55.6	-13.0	-42.6	
2542.50	-16.2	H	3.0	43.4	1.0	-58.6	-13.0	-45.6	
3390.00	-18.4	H	3.0	43.7	1.0	-61.0	-13.0	-48.0	
4237.50	-17.3	H	3.0	43.9	1.0	-60.1	-13.0	-47.1	
5085.00	-19.5	H	3.0	43.8	1.0	-62.3	-13.0	-49.3	

UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement									
Company:		Samsung							
Project #:		4788506351							
Date:		2018-06-20							
Test Engineer:		45585							
Configuration:		EUT / Adapter / Earphone, Y-Position							
Location:		Chamber 1							
Mode:		LTE_16QAM Band 5 Harmonics, 3MHz Bandwidth							
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamplifier (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 825.5MHz									
1651.00	-7.7	V	3.0	43.6	1.0	-50.3	-13.0	-37.3	
2476.50	-19.9	V	3.0	43.4	1.0	-62.3	-13.0	-49.3	
3302.00	-11.5	V	3.0	43.6	1.0	-54.1	-13.0	-41.1	
4127.50	-15.4	V	3.0	43.9	1.0	-58.2	-13.0	-45.2	
4953.00	-17.1	V	3.0	43.8	1.0	-59.9	-13.0	-46.9	
1651.00	-11.3	H	3.0	43.6	1.0	-53.9	-13.0	-40.9	
2476.50	-21.7	H	3.0	43.4	1.0	-64.1	-13.0	-51.1	
3302.00	-20.6	H	3.0	43.6	1.0	-63.2	-13.0	-50.2	
4127.50	-18.4	H	3.0	43.9	1.0	-61.3	-13.0	-48.3	
4953.00	-19.5	H	3.0	43.8	1.0	-62.3	-13.0	-49.3	
Mid Ch, 836.5MHz									
1673.00	-11.8	V	3.0	43.6	1.0	-54.4	-13.0	-41.4	
2509.50	-19.6	V	3.0	43.4	1.0	-62.0	-13.0	-49.0	
3346.00	-16.5	V	3.0	43.6	1.0	-59.1	-13.0	-46.1	
4182.50	-20.2	V	3.0	43.9	1.0	-63.1	-13.0	-50.1	
5019.00	-18.2	V	3.0	43.8	1.0	-61.0	-13.0	-48.0	
1673.00	-14.7	H	3.0	43.6	1.0	-57.3	-13.0	-44.3	
2509.50	-19.9	H	3.0	43.4	1.0	-62.3	-13.0	-49.3	
3346.00	-21.0	H	3.0	43.6	1.0	-63.7	-13.0	-50.7	
4182.50	-19.7	H	3.0	43.9	1.0	-62.6	-13.0	-49.6	
5019.00	-19.3	H	3.0	43.8	1.0	-62.1	-13.0	-49.1	
High Ch, 847.5MHz									
1695.00	-12.5	V	3.0	43.6	1.0	-55.1	-13.0	-42.1	
2542.50	-17.1	V	3.0	43.4	1.0	-59.5	-13.0	-46.5	
3390.00	-13.0	V	3.0	43.7	1.0	-55.7	-13.0	-42.7	
4237.50	-13.8	V	3.0	43.9	1.0	-56.7	-13.0	-43.7	
5085.00	-16.0	V	3.0	43.8	1.0	-58.8	-13.0	-45.8	
1695.00	-14.8	H	3.0	43.6	1.0	-57.4	-13.0	-44.4	
2542.50	-17.6	H	3.0	43.4	1.0	-60.0	-13.0	-47.0	
3390.00	-18.8	H	3.0	43.7	1.0	-61.5	-13.0	-48.5	
4237.50	-17.8	H	3.0	43.9	1.0	-60.6	-13.0	-47.6	
5085.00	-19.3	H	3.0	43.8	1.0	-62.1	-13.0	-49.1	

UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement									
Company:		Samsung							
Project #:		4788506351							
Date:		2018-06-21							
Test Engineer:		51072							
Configuration:		EUT / Adapter / Earphone , Y-position							
Location:		Chamber 1							
Mode:		LTE_QPSK Band 5 Harmonics , 1.4MHz Bandwidth							
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamplifier (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 824.7MHz									
1649.40	-7.7	V	3.0	43.6	1.0	-50.3	-13.0	-37.3	
2474.10	-17.9	V	3.0	43.4	1.0	-60.3	-13.0	-47.3	
3298.80	-11.9	V	3.0	43.6	1.0	-54.5	-13.0	-41.5	
4123.50	-14.0	V	3.0	43.9	1.0	-56.8	-13.0	-43.8	
4948.20	-16.4	V	3.0	43.8	1.0	-59.2	-13.0	-46.2	
1649.40	-11.3	H	3.0	43.6	1.0	-53.9	-13.0	-40.9	
2474.10	-18.1	H	3.0	43.4	1.0	-60.5	-13.0	-47.5	
3298.80	-17.2	H	3.0	43.6	1.0	-59.9	-13.0	-46.9	
4123.50	-16.6	H	3.0	43.9	1.0	-59.5	-13.0	-46.5	
4948.20	-19.0	H	3.0	43.8	1.0	-61.8	-13.0	-48.8	
Mid Ch, 836.5MHz									
1673.00	-8.9	V	3.0	43.6	1.0	-51.5	-13.0	-38.5	
2509.50	-18.2	V	3.0	43.4	1.0	-60.6	-13.0	-47.6	
3346.00	-18.7	V	3.0	43.6	1.0	-61.4	-13.0	-48.4	
4182.50	-16.2	V	3.0	43.9	1.0	-59.0	-13.0	-46.0	
5019.00	-19.4	V	3.0	43.8	1.0	-62.2	-13.0	-49.2	
1673.00	-11.3	H	3.0	43.6	1.0	-53.9	-13.0	-40.9	
2509.50	-18.2	H	3.0	43.4	1.0	-60.7	-13.0	-47.7	
3346.00	-21.0	H	3.0	43.6	1.0	-63.7	-13.0	-50.7	
4182.50	-19.7	H	3.0	43.9	1.0	-62.6	-13.0	-49.6	
5019.00	-19.7	H	3.0	43.8	1.0	-62.5	-13.0	-49.5	
High Ch, 848.3MHz									
1696.60	-8.9	V	3.0	43.6	1.0	-51.4	-13.0	-38.4	
2544.90	-16.4	V	3.0	43.4	1.0	-58.8	-13.0	-45.8	
3393.20	-17.3	V	3.0	43.7	1.0	-59.9	-13.0	-46.9	
4241.50	-12.8	V	3.0	43.9	1.0	-55.6	-13.0	-42.6	
5089.80	-18.9	V	3.0	43.8	1.0	-61.6	-13.0	-48.6	
1696.60	-16.1	H	3.0	43.6	1.0	-58.6	-13.0	-45.6	
2544.90	-17.9	H	3.0	43.4	1.0	-60.3	-13.0	-47.3	
3393.20	-19.2	H	3.0	43.7	1.0	-61.9	-13.0	-48.9	
4241.50	-18.7	H	3.0	43.9	1.0	-61.5	-13.0	-48.5	
5089.80	-19.3	H	3.0	43.8	1.0	-62.1	-13.0	-49.1	

UL Verification Services, Inc.									
Above 1GHz High Frequency Substitution Measurement									
Company:		Samsung							
Project #:		4788506351							
Date:		2018-06-21							
Test Engineer:		51072							
Configuration:		EUT / Adapter / Earphone , Y-position							
Location:		Chamber 1							
Mode:		LTE_16QAM Band 5 Harmonics, 1.4MHz Bandwidth							
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 824.7MHz									
1649.40	-8.4	V	3.0	43.6	1.0	-51.0	-13.0	-38.0	
2474.10	-19.6	V	3.0	43.4	1.0	-62.0	-13.0	-49.0	
3298.80	-12.2	V	3.0	43.6	1.0	-54.9	-13.0	-41.9	
4123.50	-14.9	V	3.0	43.9	1.0	-57.7	-13.0	-44.7	
4948.20	-17.0	V	3.0	43.8	1.0	-59.8	-13.0	-46.8	
1649.40	-13.1	H	3.0	43.6	1.0	-55.7	-13.0	-42.7	
2474.10	-19.6	H	3.0	43.4	1.0	-62.0	-13.0	-49.0	
3298.80	-17.5	H	3.0	43.6	1.0	-60.1	-13.0	-47.1	
4123.50	-17.3	H	3.0	43.9	1.0	-60.2	-13.0	-47.2	
4948.20	-19.2	H	3.0	43.8	1.0	-62.0	-13.0	-49.0	
Mid Ch, 836.5MHz									
1673.00	-10.4	V	3.0	43.6	1.0	-53.0	-13.0	-40.0	
2509.50	-19.0	V	3.0	43.4	1.0	-61.4	-13.0	-48.4	
3346.00	-19.0	V	3.0	43.6	1.0	-61.7	-13.0	-48.7	
4182.50	-16.9	V	3.0	43.9	1.0	-59.8	-13.0	-46.8	
5019.00	-19.4	V	3.0	43.8	1.0	-62.2	-13.0	-49.2	
1673.00	-13.1	H	3.0	43.6	1.0	-55.7	-13.0	-42.7	
2509.50	-19.3	H	3.0	43.4	1.0	-61.7	-13.0	-48.7	
3346.00	-20.9	H	3.0	43.6	1.0	-63.5	-13.0	-50.5	
4182.50	-19.9	H	3.0	43.9	1.0	-62.7	-13.0	-49.7	
5019.00	-19.8	H	3.0	43.8	1.0	-62.6	-13.0	-49.6	
High Ch, 848.3MHz									
1696.60	-10.8	V	3.0	43.6	1.0	-53.4	-13.0	-40.4	
2544.90	-17.6	V	3.0	43.4	1.0	-60.0	-13.0	-47.0	
3393.20	-17.8	V	3.0	43.7	1.0	-60.4	-13.0	-47.4	
4241.50	-13.4	V	3.0	43.9	1.0	-56.3	-13.0	-43.3	
5089.80	-18.8	V	3.0	43.8	1.0	-61.6	-13.0	-48.6	
1696.60	-17.6	H	3.0	43.6	1.0	-60.2	-13.0	-47.2	
2544.90	-19.2	H	3.0	43.4	1.0	-61.6	-13.0	-48.6	
3393.20	-19.3	H	3.0	43.7	1.0	-61.9	-13.0	-48.9	
4241.50	-19.0	H	3.0	43.9	1.0	-61.9	-13.0	-48.9	
5089.80	-19.2	H	3.0	43.8	1.0	-62.0	-13.0	-49.0	

LTE Band 12

LTE Band 12 10MHz QPSK	UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement Company: Samsung Project #: 4788506351 Date: 2018-06-20 Test Engineer: 45585 Configuration: EUT / Adapter / Earphone, Y-Position Location: Chamber 1 Mode: LTE_QPSK Band 12 Harmonics, 10MHz Bandwidth									
	f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
	Low Ch, 704MHz									
	1408.00	-11.6	V	3.0	43.8	1.0	-54.4	-13.0	-41.4	
	2112.00	-21.5	V	3.0	43.3	1.0	-63.8	-13.0	-50.8	
	2816.00	-12.2	V	3.0	43.5	1.0	-54.7	-13.0	-41.7	
	3520.00	-11.1	V	3.0	43.7	1.0	-53.8	-13.0	-40.8	
	4224.00	-17.3	V	3.0	43.9	1.0	-60.1	-13.0	-47.1	
	1408.00	-13.5	H	3.0	43.8	1.0	-56.3	-13.0	-43.3	
	2112.00	-15.8	H	3.0	43.3	1.0	-58.1	-13.0	-45.1	
	2816.00	-19.0	H	3.0	43.5	1.0	-61.5	-13.0	-48.5	
	3520.00	-19.6	H	3.0	43.7	1.0	-62.3	-13.0	-49.3	
	4224.00	-19.8	H	3.0	43.9	1.0	-62.6	-13.0	-49.6	
	Mid Ch, 707.5MHz									
	1415.00	-11.6	V	3.0	43.8	1.0	-54.3	-13.0	-41.3	
	2122.50	-21.3	V	3.0	43.3	1.0	-63.7	-13.0	-50.7	
	2830.00	-12.6	V	3.0	43.5	1.0	-55.1	-13.0	-42.1	
	3537.50	-13.0	V	3.0	43.7	1.0	-55.7	-13.0	-42.7	
	4245.00	-20.6	V	3.0	43.9	1.0	-63.5	-13.0	-50.5	
	1415.00	-17.4	H	3.0	43.8	1.0	-60.2	-13.0	-47.2	
	2122.50	-22.3	H	3.0	43.3	1.0	-64.6	-13.0	-51.6	
	2830.00	-19.9	H	3.0	43.5	1.0	-62.4	-13.0	-49.4	
	3537.50	-17.8	H	3.0	43.7	1.0	-60.5	-13.0	-47.5	
	4245.00	-20.6	H	3.0	43.9	1.0	-63.4	-13.0	-50.4	
	High Ch, 711MHz									
	1422.00	-15.7	V	3.0	43.8	1.0	-58.5	-13.0	-45.5	
	2133.00	-20.1	V	3.0	43.3	1.0	-62.4	-13.0	-49.4	
	2844.00	-15.1	V	3.0	43.5	1.0	-57.6	-13.0	-44.6	
	3555.00	-14.8	V	3.0	43.7	1.0	-57.5	-13.0	-44.5	
	4266.00	-18.4	V	3.0	43.8	1.0	-61.2	-13.0	-48.2	
	1422.00	-19.7	H	3.0	43.8	1.0	-62.5	-13.0	-49.5	
	2133.00	-22.4	H	3.0	43.3	1.0	-64.7	-13.0	-51.7	
	2844.00	-20.1	H	3.0	43.5	1.0	-62.6	-13.0	-49.6	
	3555.00	-20.4	H	3.0	43.7	1.0	-63.1	-13.0	-50.1	
	4266.00	-20.3	H	3.0	43.8	1.0	-63.2	-13.0	-50.2	

UL Verification Services, Inc.									
Above 1GHz High Frequency Substitution Measurement									
Company:		Samsung							
Project #:		4788506351							
Date:		2018-06-20							
Test Engineer:		45585							
Configuration:		EUT / Adapter / Earphone, Y-Position							
Location:		Chamber 1							
Mode:		LTE_16QAM Band 12 Harmonics, 10MHz Bandwidth							
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamplifier (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 704MHz									
1408.00	-12.4	V	3.0	43.8	1.0	-55.2	-13.0	-42.2	
2112.00	-21.8	V	3.0	43.3	1.0	-64.1	-13.0	-51.1	
2816.00	-13.2	V	3.0	43.5	1.0	-55.7	-13.0	-42.7	
3520.00	-12.0	V	3.0	43.7	1.0	-54.7	-13.0	-41.7	
4224.00	-17.9	V	3.0	43.9	1.0	-60.7	-13.0	-47.7	
1408.00	-14.6	H	3.0	43.8	1.0	-57.4	-13.0	-44.4	
2112.00	-17.3	H	3.0	43.3	1.0	-59.7	-13.0	-46.7	
2816.00	-19.7	H	3.0	43.5	1.0	-62.2	-13.0	-49.2	
3520.00	-19.6	H	3.0	43.7	1.0	-62.3	-13.0	-49.3	
4224.00	-19.8	H	3.0	43.9	1.0	-62.7	-13.0	-49.7	
Mid Ch, 707.5MHz									
1415.00	-12.4	V	3.0	43.8	1.0	-55.1	-13.0	-42.1	
2122.50	-21.3	V	3.0	43.3	1.0	-63.6	-13.0	-50.6	
2830.00	-13.4	V	3.0	43.5	1.0	-55.9	-13.0	-42.9	
3537.50	-14.1	V	3.0	43.7	1.0	-56.8	-13.0	-43.8	
4245.00	-20.6	V	3.0	43.9	1.0	-63.5	-13.0	-50.5	
1415.00	-18.2	H	3.0	43.8	1.0	-61.0	-13.0	-48.0	
2122.50	-22.6	H	3.0	43.3	1.0	-64.9	-13.0	-51.9	
2830.00	-20.4	H	3.0	43.5	1.0	-62.8	-13.0	-49.8	
3537.50	-18.3	H	3.0	43.7	1.0	-61.0	-13.0	-48.0	
4245.00	-20.6	H	3.0	43.9	1.0	-63.4	-13.0	-50.4	
High Ch, 711MHz									
1422.00	-16.8	V	3.0	43.8	1.0	-59.5	-13.0	-46.5	
2133.00	-21.3	V	3.0	43.3	1.0	-63.6	-13.0	-50.6	
2844.00	-16.4	V	3.0	43.5	1.0	-58.9	-13.0	-45.9	
3555.00	-16.0	V	3.0	43.7	1.0	-58.7	-13.0	-45.7	
4266.00	-19.0	V	3.0	43.8	1.0	-61.8	-13.0	-48.8	
1422.00	-20.8	H	3.0	43.8	1.0	-63.6	-13.0	-50.6	
2133.00	-23.0	H	3.0	43.3	1.0	-65.3	-13.0	-52.3	
2844.00	-20.1	H	3.0	43.5	1.0	-62.6	-13.0	-49.6	
3555.00	-20.3	H	3.0	43.7	1.0	-63.0	-13.0	-50.0	
4266.00	-20.4	H	3.0	43.8	1.0	-63.3	-13.0	-50.3	

UL Verification Services, Inc.									
Above 1GHz High Frequency Substitution Measurement									
Company:		Samsung							
Project #:		4788506351							
Date:		2018-06-19							
Test Engineer:		47989							
Configuration:		EUT / AC Adapter / Earphone, Y-Position							
Location:		Chamber 1							
Mode:		LTE_QPSK Band 12 Harmonics, 5MHz Bandwidth							
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 701.5MHz									
1403.00	-7.5	V	3.0	43.8	1.0	-50.3	-13.0	-37.3	
2104.50	-11.7	V	3.0	43.3	1.0	-54.0	-13.0	-41.0	
2806.00	-12.2	V	3.0	43.5	1.0	-54.7	-13.0	-41.7	
3507.50	-8.5	V	3.0	43.7	1.0	-51.2	-13.0	-38.2	
4209.00	-15.8	V	3.0	43.9	1.0	-58.7	-13.0	-45.7	
1403.00	-13.2	H	3.0	43.8	1.0	-56.0	-13.0	-43.0	
2104.50	-13.5	H	3.0	43.3	1.0	-55.9	-13.0	-42.9	
2806.00	-19.6	H	3.0	43.5	1.0	-62.1	-13.0	-49.1	
3507.50	-17.7	H	3.0	43.7	1.0	-60.5	-13.0	-47.5	
4209.00	-19.6	H	3.0	43.9	1.0	-62.4	-13.0	-49.4	
Mid Ch, 707.5MHz									
1415.00	-14.8	V	3.0	43.8	1.0	-57.6	-13.0	-44.6	
2122.50	-20.7	V	3.0	43.3	1.0	-63.0	-13.0	-50.0	
2830.00	-12.6	V	3.0	43.5	1.0	-55.1	-13.0	-42.1	
3537.50	-12.5	V	3.0	43.7	1.0	-55.2	-13.0	-42.2	
4245.00	-16.5	V	3.0	43.9	1.0	-59.4	-13.0	-46.4	
1415.00	-19.7	H	3.0	43.8	1.0	-62.4	-13.0	-49.4	
2122.50	-23.0	H	3.0	43.3	1.0	-65.4	-13.0	-52.4	
2830.00	-18.4	H	3.0	43.5	1.0	-60.9	-13.0	-47.9	
3537.50	-18.0	H	3.0	43.7	1.0	-60.7	-13.0	-47.7	
4245.00	-20.0	H	3.0	43.9	1.0	-62.8	-13.0	-49.8	
High Ch, 713.5MHz									
1427.00	-6.2	V	3.0	43.8	1.0	-49.0	-13.0	-36.0	
2140.50	-14.2	V	3.0	43.3	1.0	-56.6	-13.0	-43.6	
2854.00	-13.6	V	3.0	43.5	1.0	-56.1	-13.0	-43.1	
3567.50	-10.9	V	3.0	43.7	1.0	-53.7	-13.0	-40.7	
4281.00	-14.4	V	3.0	43.8	1.0	-57.3	-13.0	-44.3	
1427.00	-14.1	H	3.0	43.8	1.0	-56.8	-13.0	-43.8	
2140.50	-16.7	H	3.0	43.3	1.0	-59.1	-13.0	-46.1	
2854.00	-19.7	H	3.0	43.5	1.0	-62.2	-13.0	-49.2	
3567.50	-19.2	H	3.0	43.7	1.0	-61.9	-13.0	-48.9	
4281.00	-19.4	H	3.0	43.8	1.0	-62.3	-13.0	-49.3	

UL Verification Services, Inc.									
Above 1GHz High Frequency Substitution Measurement									
Company:		Samsung							
Project #:		4788506351							
Date:		2018-06-19							
Test Engineer:		47989							
Configuration:		EUT / AC Adapter / Earphone, Y-Position							
Location:		Chamber 1							
Mode:		LTE_16QAM Band 12 Harmonics, 5MHz Bandwidth							
f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamplifier (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 701.5MHz									
1403.00	-8.9	V	3.0	43.8	1.0	-51.7	-13.0	-38.7	
2104.50	-13.0	V	3.0	43.3	1.0	-55.3	-13.0	-42.3	
2806.00	-13.3	V	3.0	43.5	1.0	-55.8	-13.0	-42.8	
3507.50	-10.0	V	3.0	43.7	1.0	-52.7	-13.0	-39.7	
4209.00	-16.3	V	3.0	43.9	1.0	-59.2	-13.0	-46.2	
1403.00	-14.4	H	3.0	43.8	1.0	-57.2	-13.0	-44.2	
2104.50	-14.5	H	3.0	43.3	1.0	-56.9	-13.0	-43.9	
2806.00	-19.6	H	3.0	43.5	1.0	-62.1	-13.0	-49.1	
3507.50	-18.5	H	3.0	43.7	1.0	-61.2	-13.0	-48.2	
4209.00	-19.9	H	3.0	43.9	1.0	-62.7	-13.0	-49.7	
Mid Ch, 707.5MHz									
1415.00	-15.6	V	3.0	43.8	1.0	-58.3	-13.0	-45.3	
2122.50	-21.4	V	3.0	43.3	1.0	-63.8	-13.0	-50.8	
2830.00	-13.9	V	3.0	43.5	1.0	-56.4	-13.0	-43.4	
3537.50	-14.1	V	3.0	43.7	1.0	-56.8	-13.0	-43.8	
4245.00	-17.3	V	3.0	43.9	1.0	-60.2	-13.0	-47.2	
1415.00	-20.4	H	3.0	43.8	1.0	-63.1	-13.0	-50.1	
2122.50	-23.5	H	3.0	43.3	1.0	-65.9	-13.0	-52.9	
2830.00	-19.1	H	3.0	43.5	1.0	-61.6	-13.0	-48.6	
3537.50	-18.6	H	3.0	43.7	1.0	-61.3	-13.0	-48.3	
4245.00	-20.4	H	3.0	43.9	1.0	-63.2	-13.0	-50.2	
High Ch, 713.5MHz									
1427.00	-7.6	V	3.0	43.8	1.0	-50.3	-13.0	-37.3	
2140.50	-15.1	V	3.0	43.3	1.0	-57.5	-13.0	-44.5	
2854.00	-14.5	V	3.0	43.5	1.0	-57.0	-13.0	-44.0	
3567.50	-12.1	V	3.0	43.7	1.0	-54.9	-13.0	-41.9	
4281.00	-15.5	V	3.0	43.8	1.0	-58.3	-13.0	-45.3	
1427.00	-14.9	H	3.0	43.8	1.0	-57.7	-13.0	-44.7	
2140.50	-18.0	H	3.0	43.3	1.0	-60.3	-13.0	-47.3	
2854.00	-20.1	H	3.0	43.5	1.0	-62.6	-13.0	-49.6	
3567.50	-19.2	H	3.0	43.7	1.0	-61.9	-13.0	-48.9	
4281.00	-19.3	H	3.0	43.8	1.0	-62.1	-13.0	-49.1	