



SAR EVALUATION REPORT

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

06/25/18 - 07/10/18

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Document Serial No.:

1M1806180125-01-R1.A3L

FCC ID:

A3LSMT837R4

APPLICANT:

SAMSUNG ELECTRONICS CO., LTD.

DUT Type:

Portable Tablet

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093

Model:

SM-T837R4

Equipment Class	Band & Mode	Tx Frequency	SAR
			1g Body (W/kg)
PCB	UMTS 850	826.40 - 846.60 MHz	1.23
PCB	UMTS 1900	1852.4 - 1907.6 MHz	1.27
PCB	Cell. CDMA/EVDO	824.70 - 848.31 MHz	1.40
PCB	PCS CDMA/EVDO	1851.25 - 1908.75 MHz	1.12
PCB	LTE Band 12	699.7 - 715.3 MHz	0.63
PCB	LTE Band 13	779.5 - 784.5 MHz	0.79
PCB	LTE Band 5 (Cell)	824.7 - 848.3 MHz	1.10
PCB	LTE Band 66 (AWS)	1710.7 - 1779.3 MHz	1.13
PCB	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	N/A
PCB	LTE Band 25 (PCS)	1850.7 - 1914.3 MHz	1.22
PCB	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	N/A
DTS	2.4 GHz WLAN	2412 - 2462 MHz	1.05
NII	U-NII-1	5180 - 5240 MHz	N/A
NII	U-NII-2A	5260 - 5320 MHz	1.04
NII	U-NII-2C	5500 - 5720 MHz	0.99
NII	U-NII-3	5745 - 5825 MHz	1.37
DSS/DTS	Bluetooth	2402 - 2480 MHz	0.36
Simultaneous SAR per KDB 690783 D01v01r03:			1.58

Note: This revised Test Report (S/N: 1M1806180125-01-R1.A3L) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.7 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortanez
President



The SAR Tick is an initiative of the Mobile & Wireless Forum (MWF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MWF. Further details can be obtained by emailing: sartick@mwfai.info.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 1 of 82	

T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	11
3	INTRODUCTION	12
4	DOSIMETRIC ASSESSMENT	13
5	TEST CONFIGURATION POSITIONS	14
6	RF EXPOSURE LIMITS	15
7	FCC MEASUREMENT PROCEDURES.....	16
8	RF CONDUCTED POWERS.....	22
9	SYSTEM VERIFICATION.....	51
10	SAR DATA SUMMARY	53
11	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	62
12	SAR MEASUREMENT VARIABILITY	77
13	EQUIPMENT LIST.....	78
14	MEASUREMENT UNCERTAINTIES.....	79
15	CONCLUSION.....	80
16	REFERENCES	81
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		
APPENDIX G: POWER REDUCTION VERIFICATION		
APPENDIX H: DOWNLINK LTE CA RF CONDUCTED POWERS		

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 2 of 82

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
UMTS 850	Data	826.40 - 846.60 MHz
UMTS 1900	Data	1852.4 - 1907.6 MHz
Cell. CDMA/EVDO	Data	824.70 - 848.31 MHz
PCS CDMA/EVDO	Data	1851.25 - 1908.75 MHz
LTE Band 12	Data	699.7 - 715.3 MHz
LTE Band 13	Data	779.5 - 784.5 MHz
LTE Band 5 (Cell)	Data	824.7 - 848.3 MHz
LTE Band 66 (AWS)	Data	1710.7 - 1779.3 MHz
LTE Band 4 (AWS)	Data	1710.7 - 1754.3 MHz
LTE Band 25 (PCS)	Data	1850.7 - 1914.3 MHz
LTE Band 2 (PCS)	Data	1850.7 - 1909.3 MHz
2.4 GHz WLAN	Data	2412 - 2462 MHz
U-NII-1	Data	5180 - 5240 MHz
U-NII-2A	Data	5260 - 5320 MHz
U-NII-2C	Data	5500 - 5720 MHz
U-NII-3	Data	5745 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz
ANT+	Data	2402 - 2480 MHz

1.2 Power Reduction for SAR

This device uses a power reduction mechanism for SAR compliance. The power reduction mechanism is activated when the device is used in close proximity to the user's body. FCC KDB Publication 616217 D04v01r02 Section 6 was used as a guideline for selecting SAR test distances for this device. Detailed descriptions of the power reduction mechanism are included in the operational description.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 3 of 82

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

1.3.1 Maximum PCB Output Power

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA
UMTS Band 5 (850 MHz)	Maximum	25.0	25.0	25.0
	Nominal	24.0	24.0	24.0
UMTS Band 2 (1900 MHz)	Maximum	25.0	25.0	25.0
	Nominal	24.0	24.0	24.0

Mode / Band		Modulated Average (dBm)
Cell. CDMA/EVDO	Maximum	25.5
	Nominal	24.5
PCS CDMA/EVDO	Maximum	25.5
	Nominal	24.5

Mode / Band		Modulated Average (dBm)
LTE Band 12	Maximum	25.0
	Nominal	24.0
LTE Band 13	Maximum	24.5
	Nominal	23.5
LTE Band 5 (Cell)	Maximum	25.0
	Nominal	24.0
LTE Band 66 (AWS)	Maximum	25.0
	Nominal	24.0
LTE Band 4 (AWS)	Maximum	25.0
	Nominal	24.0
LTE Band 25 (PCS)	Maximum	25.0
	Nominal	24.0
LTE Band 2 (PCS)	Maximum	25.0
	Nominal	24.0

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 4 of 82

1.3.2 Reduced PCB Output Power

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA
UMTS Band 5 (850 MHz)	Maximum	17.0	17.0	17.0
	Nominal	16.0	16.0	16.0
UMTS Band 2 (1900 MHz)	Maximum	14.0	14.0	14.0
	Nominal	13.0	13.0	13.0

Mode / Band		Modulated Average (dBm)
Cell. CDMA/EVDO	Maximum	16.0
	Nominal	15.0
PCS CDMA/EVDO	Maximum	14.0
	Nominal	13.0

Mode / Band		Modulated Average (dBm)
LTE Band 12	Maximum	14.0
	Nominal	13.0
LTE Band 13	Maximum	14.0
	Nominal	13.0
LTE Band 5 (Cell)	Maximum	16.0
	Nominal	15.0
LTE Band 66 (AWS)	Maximum	14.0
	Nominal	13.0
LTE Band 4 (AWS)	Maximum	13.0
	Nominal	12.0
LTE Band 25 (PCS)	Maximum	14.0
	Nominal	13.0
LTE Band 2 (PCS)	Maximum	13.5
	Nominal	12.5

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 5 of 82

1.3.3 Maximum WLAN and Bluetooth Output Power

Mode / Band		Modulated Average - Single Tx Chain (dBm)
IEEE 802.11b (2.4 GHz)	Maximum	14.0
	Nominal	13.0
IEEE 802.11g (2.4 GHz)	Maximum	14.0
	Nominal	13.0
IEEE 802.11n (2.4 GHz)	Maximum	14.0
	Nominal	13.0

Mode / Band		Modulated Average - Single Tx Chain (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11a (5 GHz)	Maximum	14.0		
	Nominal	13.0		
IEEE 802.11n (5 GHz)	Maximum	14.0	14.0	
	Nominal	13.0	13.0	
IEEE 802.11ac (5 GHz)	Maximum	13.0	13.0	13.0
	Nominal	12.0	12.0	12.0

Mode / Band		Modulated Average - MIMO (dBm)
IEEE 802.11n (2.4 GHz)	Maximum	17.0
	Nominal	16.0
IEEE 802.11g (2.4 GHz)	Maximum	17.0
	Nominal	16.0

Mode / Band		Modulated Average - MIMO (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11a (5 GHz)	Maximum	17.0		
	Nominal	16.0		
IEEE 802.11n (5 GHz)	Maximum	17.0	17.0	
	Nominal	16.0	16.0	
IEEE 802.11ac (5 GHz)	Maximum	16.0	16.0	16.0
	Nominal	15.0	15.0	15.0

Mode / Band		Modulated Average - Single Tx Chain (dBm)
Bluetooth	Maximum	9.5
	Nominal	8.5
Bluetooth LE	Maximum	2.6
	Nominal	1.6

FCC ID: A3LSMT837R4	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 6 of 82

1.3.4 Reduced WLAN and Bluetooth Output Power

Mode / Band		Modulated Average - Single Tx Chain (dBm)
IEEE 802.11b (2.4 GHz)	Maximum	13.0
	Nominal	12.0
IEEE 802.11g (2.4 GHz)	Maximum	13.0
	Nominal	12.0
IEEE 802.11n (2.4 GHz)	Maximum	13.0
	Nominal	12.0

Mode / Band		Modulated Average - Single Tx Chain (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11a (5 GHz)	Maximum	10.0		
	Nominal	9.0		
IEEE 802.11n (5 GHz)	Maximum	10.0	10.0	
	Nominal	9.0	9.0	
IEEE 802.11ac (5 GHz)	Maximum	10.0	10.0	10.0
	Nominal	9.0	9.0	9.0

Mode / Band		Modulated Average - MIMO (dBm)
IEEE 802.11n (2.4 GHz)	Maximum	16.0
	Nominal	15.0
IEEE 802.11g (2.4 GHz)	Maximum	16.0
	Nominal	15.0

Mode / Band		Modulated Average - MIMO (dBm)		
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth
IEEE 802.11g (5 GHz)	Maximum	13.0		
	Nominal	12.0		
IEEE 802.11n (5 GHz)	Maximum	13.0	13.0	
	Nominal	12.0	12.0	
IEEE 802.11ac (5 GHz)	Maximum	13.0	13.0	13.0
	Nominal	12.0	12.0	12.0

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 7 of 82

1.4 DUT Antenna Locations

The overall diagonal dimension of the device is > 200 mm. A diagram showing the location of the device antennas can be found in Appendix F. Exact antenna dimensions and separation distances are shown in the Technical Descriptions in the FCC filings.

Table 1-1
Device Edges/Sides for SAR Testing

Mode	Back	Top	Bottom	Right	Left
UMTS 850	Yes	Yes	No	Yes	Yes
UMTS 1900	Yes	Yes	No	Yes	Yes
Cell. EVDO	Yes	Yes	No	Yes	Yes
PCS EVDO	Yes	Yes	No	Yes	Yes
LTE Band 12	Yes	Yes	No	Yes	Yes
LTE Band 13	Yes	Yes	No	Yes	Yes
LTE Band 5 (Cell)	Yes	Yes	No	Yes	Yes
LTE Band 66 (AWS)	Yes	Yes	No	Yes	Yes
LTE Band 25 (PCS)	Yes	Yes	No	Yes	Yes
2.4 GHz WLAN Ant 1	Yes	Yes	Yes	Yes	No
2.4 GHz WLAN Ant 2	Yes	Yes	Yes	No	Yes
5 GHz WLAN Ant 1	Yes	Yes	Yes	Yes	No
5 GHz WLAN Ant 2	Yes	Yes	Yes	Yes	Yes
Bluetooth	Yes	Yes	Yes	Yes	No

Note: Per FCC KDB Publication 616217 D04v01r01, particular edges were not required to be evaluated for SAR based on the SAR exclusion threshold in KDB 447498 D01V06. Additional edges may have been evaluated for simultaneous transmission analysis.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 8 of 82

1.5 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds.

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Body
1	UMTS + 2.4 GHz WI-FI	Yes
2	UMTS + 5 GHz WI-FI	Yes
3	UMTS + 2.4 GHz Bluetooth	Yes
4	UMTS + 2.4 GHz WI-FI MIMO	Yes
5	UMTS + 5 GHz WI-FI MIMO	Yes
6	UMTS + 2.4 GHz WI-FI Ant 1 + 5 GHz WI-FI Ant 2	Yes
7	LTE + 2.4 GHz WI-FI	Yes
8	LTE + 5 GHz WI-FI	Yes
9	LTE + 2.4 GHz Bluetooth	Yes
10	LTE + 2.4 GHz WI-FI MIMO	Yes
11	LTE + 5 GHz WI-FI MIMO	Yes
12	LTE + 2.4 GHz WI-FI Ant 1 + 5 GHz WI-FI Ant 2	Yes
13	CDMA/EVDO data + 2.4 GHz WI-FI	Yes
14	CDMA/EVDO data + 5 GHz WI-FI	Yes
15	CDMA/EVDO data + 2.4 GHz Bluetooth	Yes
16	CDMA/EVDO data + 2.4 GHz WI-FI MIMO	Yes
17	CDMA/EVDO data + 5 GHz WI-FI MIMO	Yes
18	CDMA/EVDO data + 2.4 GHz WI-FI Ant 1 + 5 GHz WI-FI Ant 2	Yes

1. All licensed modes share the same antenna path and cannot transmit simultaneously.
2. This device supports 2x2 MIMO Tx for WLAN 802.11n/ac. 802.11a/g/n/ac supports CDD and STBC and 802.11n/ac additionally supports SDM. Each WLAN antenna can transmit independently or together when operating with MIMO.

1.6 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Since U-NII-1 and U-NII-2A bands have the same maximum output power and the highest reported SAR for U-NII-2A is less than 1.2 W/kg, SAR is not required for U-NII-1 band according to FCC KDB Publication 248227 D01v02r02.

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 2 Tx antenna output
- d) 256 QAM is supported
- e) TDWR and Band gap channels are supported

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 9 of 82

(B) Licensed Transmitter(s)

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

This device supports LTE Carrier Aggregation (CA) in the downlink only. All uplink communications are identical to Release 8 specifications. Per FCC KDB Publication 941225 D05A v01r02, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive. The downlink carrier aggregation exclusion analysis can be found in Appendix H.

This device supports downlink 4x4 MIMO operations for some LTE Bands. Per May 2017 TCB Workshop Guidance, SAR for downlink 4x4 MIMO was not needed since the maximum average output power in 4x4 downlink MIMO mode was not > 0.25 dB higher than the maximum output power with downlink 4x4 MIMO inactive.

This device supports LTE capabilities with overlapping transmission frequency ranges. When the supported frequency range of an LTE Band falls completely within an LTE band with a larger transmission frequency range, both LTE bands have the same target power (or the band with the larger transmission frequency range has a higher target power), and both LTE bands share the same transmission path and signal characteristics, SAR was only assessed for the band with the larger transmission frequency range.

1.7 Guidance Applied

- FCC KDB Publication 941225 D01v03r01, D05v02r04, D05Av01r02, D06v02r01 (3G/4G)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- FCC KDB Publication 616217 D04v01r02 (Tablet)
- May 2017 TCB Workshop Notes (LTE 4x4 Downlink MIMO)
- April 2018 TCB Workshop Notes (LTE Carrier Aggregation)

1.8 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units. The serial numbers used for each test are indicated alongside the results in Section 10.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 10 of 82

2

LTE INFORMATION

LTE Information			
FCC ID	A3LSMT837R4		
Form Factor	Portable Tablet		
Frequency Range of each LTE transmission band	LTE Band 12 (699.7 - 715.3 MHz)		
	LTE Band 13 (779.5 - 784.5 MHz)		
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)		
	LTE Band 66 (AWS) (1710.7 - 1779.3 MHz)		
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)		
	LTE Band 25 (PCS) (1850.7 - 1914.3 MHz)		
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)		
Channel Bandwidths	LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz		
	LTE Band 13: 5 MHz, 10 MHz		
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz		
	LTE Band 66 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz		
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz		
	LTE Band 25 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz		
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz		
Channel Numbers and Frequencies (MHz)	Low	Mid	High
LTE Band 12: 1.4 MHz	699.7 (23017)	707.5 (23095)	715.3 (23173)
LTE Band 12: 3 MHz	700.5 (23025)	707.5 (23095)	714.5 (23165)
LTE Band 12: 5 MHz	701.5 (23035)	707.5 (23095)	713.5 (23155)
LTE Band 12: 10 MHz	704 (23060)	707.5 (23095)	711 (23130)
LTE Band 13: 5 MHz	779.5 (23205)	782 (23230)	784.5 (23255)
LTE Band 13: 10 MHz	N/A	782 (23230)	N/A
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)	836.5 (20525)	848.3 (20643)
LTE Band 5 (Cell): 3 MHz	825.5 (20415)	836.5 (20525)	847.5 (20635)
LTE Band 5 (Cell): 5 MHz	826.5 (20425)	836.5 (20525)	846.5 (20625)
LTE Band 5 (Cell): 10 MHz	829 (20450)	836.5 (20525)	844 (20600)
LTE Band 66 (AWS): 1.4 MHz	1710.7 (131979)	1745 (132322)	1779.3 (132665)
LTE Band 66 (AWS): 3 MHz	1711.5 (131987)	1745 (132322)	1778.5 (132657)
LTE Band 66 (AWS): 5 MHz	1712.5 (131997)	1745 (132322)	1777.5 (132647)
LTE Band 66 (AWS): 10 MHz	1715 (132022)	1745 (132322)	1775 (132622)
LTE Band 66 (AWS): 15 MHz	1717.5 (132047)	1745 (132322)	1772.5 (132597)
LTE Band 66 (AWS): 20 MHz	1720 (132072)	1745 (132322)	1770 (132572)
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)	1732.5 (20175)	1754.3 (20393)
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)	1732.5 (20175)	1753.5 (20385)
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)	1732.5 (20175)	1752.5 (20375)
LTE Band 4 (AWS): 10 MHz	1715 (20000)	1732.5 (20175)	1750 (20350)
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)	1732.5 (20175)	1747.5 (20325)
LTE Band 4 (AWS): 20 MHz	1720 (20050)	1732.5 (20175)	1745 (20300)
LTE Band 25 (PCS): 1.4 MHz	1850.7 (26047)	1882.5 (26365)	1914.3 (26683)
LTE Band 25 (PCS): 3 MHz	1851.5 (26055)	1882.5 (26365)	1913.5 (26675)
LTE Band 25 (PCS): 5 MHz	1852.5 (26065)	1882.5 (26365)	1912.5 (26665)
LTE Band 25 (PCS): 10 MHz	1855 (26090)	1882.5 (26365)	1910 (26640)
LTE Band 25 (PCS): 15 MHz	1857.5 (26115)	1882.5 (26365)	1907.5 (26615)
LTE Band 25 (PCS): 20 MHz	1860 (26140)	1882.5 (26365)	1905 (26590)
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)	1880 (18900)	1909.3 (19193)
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)	1880 (18900)	1908.5 (19185)
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)	1880 (18900)	1907.5 (19175)
LTE Band 2 (PCS): 10 MHz	1855 (18650)	1880 (18900)	1905 (19150)
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)	1880 (18900)	1902.5 (19125)
LTE Band 2 (PCS): 20 MHz	1860 (18700)	1880 (18900)	1900 (19100)
UE Category	DL UE Cat 16 (QPSK, 16QAM, 64QAM, 256QAM) UL UE Cat 5 (QPSK, 16QAM, 64QAM)		
Modulations Supported in UL	QPSK, 16QAM, 64QAM		
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided)	YES		
A-MPR (Additional MPR) disabled for SAR Testing?	YES		
LTE Carrier Aggregation Possible Combinations	The technical description includes all the possible carrier aggregation combinations		
LTE Additional Information	LTE Release 14 Information and this device does not support full CA features on 3GPP Release 14. It supports carrier aggregation and downlink MIMO features as shown in Section 9 and Appendix H. All other uplink communications are identical to the Release 8 specifications. Uplink communications are done on the PCC unless otherwise specified. The following LTE Release 14 Features are not supported: Relay, HetNet, Enhanced eCIC, MDH, eMBMS, Cross-Carrier Scheduling, Enhanced SC-FDMA.		

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 11 of 82	

3 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 12 of 82

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 4-1
Sample SAR Area Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoomTV}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
				$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	
≤2 GHz	≤15	≤8	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
2-3 GHz	≤12	≤5	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
3-4 GHz	≤12	≤5	≤4	≤3	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥28
4-5 GHz	≤10	≤4	≤3	≤2.5	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥25
5-6 GHz	≤10	≤4	≤2	≤2	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet			Page 13 of 82

5 TEST CONFIGURATION POSITIONS

5.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

5.2 SAR Testing for Tablet per KDB Publication 616217 D04v01r02

Per FCC KDB Publication 616217 D04v01r02, the back surface and edges of the tablet should be tested for SAR compliance with the tablet touching the phantom. The SAR Exclusion Threshold in KDB 447498 D01v06 can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an adjacent tablet edge is used to determine if SAR testing is required for the adjacent edges, with the adjacent edge positioned against the phantom and the edge containing the antenna positioned perpendicular to the phantom.

5.3 Proximity Sensor Considerations

This device uses a power reduction mechanism to reduce output powers in certain use conditions when the device is used close the user's body.

When the device's antenna is within a certain distance of the user, the sensor activates and reduces the maximum allowed output power. However, the sensor is not active when the device is moved beyond the sensor triggering distance and the maximum output power is no longer limited. Therefore, additional evaluation is needed in the vicinity of the triggering distance to ensure SAR is compliant when the device is allowed to operate at a non-reduced output power level. FCC KDB Publication 616217 D04v01r02 Section 6 was used as a guideline for selecting SAR test distances for this device at these additional test positions. Sensor triggering distance summary data is included in Appendix G.

The sensor is designed to support sufficient detection range and sensitivity to cover regions of the sensors in all applicable directions since the sensor entirely covers the antennas.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 14 of 82

6 RF EXPOSURE LIMITS

6.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

6.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 6-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 15 of 82

7 FCC MEASUREMENT PROCEDURES

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

7.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

7.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is ≤ 0.25 dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is ≤ 1.2 W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

7.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

7.4 SAR Measurement Conditions for CDMA2000

The following procedures were performed according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

7.4.1 Output Power Verification

See 3GPP2 C.S0011/TIA-98-E as recommended by FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.” Maximum output power is verified on the High, Middle and Low channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. SO55 tests were measured with power control bits in the “All Up” condition.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 16 of 82

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 7-1 parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH₀ and demodulation of RC 3,4, or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH₀ data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 7-2 was applied.

Table 7-1
Parameters for Max. Power for RC1

Parameter	Units	Value
I_{or}	dBm/1.23 MHz	-104
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

Table 7-2
Parameters for Max. Power for RC3

Parameter	Units	Value
I_{or}	dBm/1.23 MHz	-86
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

5. FCHs were configured at full rate for maximum SAR with “All Up” power control bits.

7.4.2 Body SAR Measurements for EVDO Body

Hotspot Body SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0. The 3G SAR test reduction procedure is applied to Rev. A, Subtype 2 Physical layer configuration, with Rev. 0 as the primary mode; otherwise, SAR is measured for Rev. A using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0. The AT is tested with a Reverse Data Channel rate of 153.6 kbps in Subtype 0/1 Physical Layer configurations; and a Reverse Data Channel payload size of 4096 bits and Termination Target of 16 slots in Subtype 2 Physical Layer configurations.

For EVDO data devices that also support 1x RTT voice and/or data operations, the 3G SAR test reduction procedure is applied to 1x RTT RC3 and RC1 with EVDO Rev. 0 and Rev. A as the respective primary modes. Otherwise, the ‘Body-Worn Accessory SAR’ procedures in the ‘3GPP2 CDMA 2000 1x Handsets’ section are applied.

7.5 SAR Measurement Conditions for UMTS

7.5.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all “1s” or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCH_n and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

7.5.2 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH_n, for the highest reported SAR configuration in 12.2 kbps RMC.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 17 of 82

7.5.3 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

7.5.4 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

7.6 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

7.6.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

7.6.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

7.6.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

7.6.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 18 of 82

- iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to ½ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is <1.45 W/kg.

7.6.5 Downlink Only Carrier Aggregation

Conducted power measurements with LTE Carrier Aggregation (CA) (downlink only) active are made in accordance to KDB Publication 941225 D05Av01r02. The RRC connection is only handled by one cell, the primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds secondary component carrier(s) (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to specifications when downlink carrier aggregation is inactive on the PCC. Additional conducted output powers are measured with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band. Per FCC KDB Publication 941225 D05Av01r02, no SAR measurements are required for downlink only carrier aggregation configurations when the average output power with downlink only carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink only carrier aggregation inactive.

7.7 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

7.7.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

7.7.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is > 1.2 W/kg. When different maximum output powers are

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 19 of 82

specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is $> 1.2 \text{ W/kg}$. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

7.7.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

7.7.4 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is $\leq 0.8 \text{ W/kg}$, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is $> 0.8 \text{ W/kg}$, SAR is required for that position using the next highest measured output power channel. When any reported SAR is $> 1.2 \text{ W/kg}$, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is $> 1.2 \text{ W/kg}$. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

7.7.5 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

7.7.6 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 20 of 82

The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 7.7.6). When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

7.7.7 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

7.7.8 MIMO SAR considerations

Per KDB Publication 248227 D01v02r02, the simultaneous SAR provisions in KDB Publication 447498 D01v06 should be applied to determine simultaneous transmission SAR test exclusion for WIFI MIMO. If the sum of 1g single transmission chain SAR measurements is < 1.6 W/kg, no additional SAR measurements for MIMO are required. Alternatively, SAR for MIMO can be measured with all antennas transmitting simultaneously at the specified maximum output power of MIMO operation. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 21 of 82

8 RF CONDUCTED POWERS

8.1 CDMA Conducted Powers

Table 8-1
Maximum Conducted Power

Band	Channel	Frequency	TDSO SO32 [dBm]	TDSO SO32 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. A [dBm]
	F-RC	MHz	FCH+SCH	FCH	(RTAP)	(RETAP)
Cellular	1013	824.7	24.82	24.79	24.98	24.72
	384	836.52	24.78	24.77	24.81	24.62
	777	848.31	24.45	24.46	24.49	24.29
PCS	25	1851.25	24.10	24.09	24.11	23.93
	600	1880	23.98	23.97	23.99	23.81
	1175	1908.75	24.20	24.22	24.10	23.91

Table 8-2
Reduced Conducted Power

Band	Channel	Frequency	TDSO SO32 [dBm]	TDSO SO32 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. A [dBm]
	F-RC	MHz	FCH+SCH	FCH	(RTAP)	(RETAP)
Cellular	1013	824.7	15.23	15.26	15.43	15.38
	384	836.52	15.20	15.23	15.28	15.26
	777	848.31	15.06	15.10	15.14	15.13
PCS	25	1851.25	13.28	13.30	13.31	13.29
	600	1880	13.17	13.16	13.18	13.20
	1175	1908.75	13.39	13.41	13.31	13.36



Figure 8-1
Power Measurement Setup

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 22 of 82

8.2 UMTS Conducted Powers

Table 8-3
Maximum Conducted Power

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	24.05	23.97	23.92	24.08	23.98	24.04	-
6	HSDPA	Subtest 1	23.20	23.06	23.00	23.15	22.91	22.90	0
6		Subtest 2	23.39	23.16	23.05	23.13	22.96	22.93	0
6		Subtest 3	23.01	22.65	22.54	22.73	22.47	22.42	0.5
6		Subtest 4	23.09	22.69	22.54	22.74	22.46	22.46	0.5
6	HSUPA	Subtest 1	23.63	23.28	23.01	23.08	23.02	22.96	0
6		Subtest 2	21.41	21.03	21.04	21.53	21.21	20.99	2
6		Subtest 3	22.19	22.04	22.04	22.06	21.97	21.98	1
6		Subtest 4	21.18	21.04	21.01	21.06	20.94	20.95	2
6		Subtest 5	23.18	23.05	23.01	23.05	22.96	22.94	0

Table 8-4
Reduced Conducted Power

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	16.28	16.17	16.12	13.49	13.40	13.52	-
6	HSDPA	Subtest 1	15.19	15.09	15.05	12.17	12.06	12.25	0
6		Subtest 2	15.20	15.09	15.06	12.17	12.12	12.25	0
6		Subtest 3	14.70	14.53	14.59	11.65	11.59	11.78	0.5
6		Subtest 4	14.93	14.82	14.78	11.68	11.75	11.77	0.5
6	HSUPA	Subtest 1	15.21	15.12	15.09	12.20	12.09	12.28	0
6		Subtest 2	13.20	13.13	13.09	10.20	10.09	10.25	2
6		Subtest 3	14.24	14.13	14.10	11.21	11.12	11.26	1
6		Subtest 4	13.19	13.12	13.10	10.21	10.12	10.25	2
6		Subtest 5	15.21	15.12	15.11	12.21	12.11	12.28	0

This device does not support DC-HSDPA.

It is expected by the manufacturer that MPR for some HSPA subtests may be up to 2 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model.




Figure 8-2
Power Measurement Setup

FCC ID: A3LSMT837R4	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 23 of 82

8.3 LTE Conducted Powers

8.3.1 LTE Band 12

Table 8-5
LTE Band 12 Maximum Conducted Powers - 10 MHz Bandwidth

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23095 (707.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.76	0	0
	1	25	23.74		0
	1	49	23.70		0
	25	0	22.81	0-1	1
	25	12	22.77		1
	25	25	22.77		1
	50	0	22.76		1
16QAM	1	0	23.01	0-1	1
	1	25	22.98		1
	1	49	23.01		1
	25	0	21.78	0-2	2
	25	12	21.83		2
	25	25	21.77		2
	50	0	21.74		2
64QAM	1	0	21.94	0-2	2
	1	25	21.93		2
	1	49	21.90		2
	25	0	20.78	0-3	3
	25	12	20.80		3
	25	25	20.78		3
	50	0	20.79		3

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 8-6
LTE Band 12 Maximum Conducted Powers - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.90	23.83	23.91	0	0
	1	12	23.93	23.79	23.87		0
	1	24	23.91	23.79	23.87		0
	12	0	22.98	22.80	22.90	0-1	1
	12	6	22.96	22.82	22.94		1
	12	13	22.97	22.80	22.90		1
	25	0	22.94	22.77	22.94		1
16QAM	1	0	23.23	23.08	23.17	0-1	1
	1	12	23.23	23.04	23.15		1
	1	24	23.19	23.00	23.12		1
	12	0	22.00	21.84	21.98	0-2	2
	12	6	22.00	21.86	21.96		2
	12	13	21.96	21.85	21.95		2
	25	0	21.98	21.82	21.93		2
64QAM	1	0	22.16	21.97	22.12	0-2	2
	1	12	22.13	21.95	22.06		2
	1	24	22.11	21.95	22.07		2
	12	0	21.02	20.88	20.99	0-3	3
	12	6	21.03	20.90	21.00		3
	12	13	20.98	20.50	20.96		3
	25	0	20.96	20.81	20.95		3

FCC ID: A3LSMT837R4			SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet			Page 24 of 82

Table 8-7
LTE Band 12 Maximum Conducted Powers - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.99	23.82	23.89	0	0
	1	7	24.07	23.87	23.97		0
	1	14	23.97	23.80	23.86		0
	8	0	22.94	22.81	22.92	0-1	1
	8	4	22.98	22.79	22.90		1
	8	7	22.96	22.79	22.92		1
	15	0	22.98	22.76	22.87		1
16QAM	1	0	23.20	23.04	23.15	0-1	1
	1	7	23.31	23.14	23.25		1
	1	14	23.22	23.08	23.15		1
	8	0	22.02	21.87	21.96	0-2	2
	8	4	22.04	21.86	21.95		2
	8	7	21.98	21.84	21.95		2
	15	0	21.95	21.75	21.93		2
64QAM	1	0	22.13	21.95	22.08	0-2	2
	1	7	22.24	22.05	22.13		2
	1	14	22.13	21.95	22.04		2
	8	0	21.05	20.88	20.95	0-3	3
	8	4	21.04	20.84	20.99		3
	8	7	21.02	20.84	20.96		3
	15	0	20.97	20.79	20.94		3

Table 8-8
LTE Band 12 Maximum Conducted Powers -1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.85	23.67	23.86	0	0
	1	2	23.91	23.73	23.91		0
	1	5	23.84	23.66	23.82		0
	3	0	23.87	23.66	23.84		0
	3	2	23.91	23.71	23.90		0
	3	3	23.84	23.68	23.84		0
	6	0	22.85	22.68	22.86	0-1	1
16QAM	1	0	23.12	22.89	23.10	0-1	1
	1	2	23.18	22.97	23.15		1
	1	5	23.12	22.90	23.06		1
	3	0	23.02	22.80	23.00		1
	3	2	23.05	22.85	23.03		1
	3	3	23.02	22.80	22.98		1
	6	0	21.94	21.73	21.91	0-2	2
64QAM	1	0	22.02	21.83	22.02	0-2	2
	1	2	22.08	21.88	22.04		2
	1	5	22.00	21.84	22.03		2
	3	0	22.00	21.83	21.93		2
	3	2	22.05	21.86	22.02		2
	3	3	21.99	21.82	21.98		2
	6	0	20.86	20.65	20.86	0-3	3

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 25 of 82

Table 8-9
LTE Band 12 Reduced Conducted Powers - 10 MHz Bandwidth

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23095 (707.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	12.93	0	0
	1	25	12.85		0
	1	49	12.79		0
	25	0	12.96	0-1	0
	25	12	12.95		0
	25	25	12.91		0
	50	0	12.90		0
16QAM	1	0	13.29	0-1	0
	1	25	13.22		0
	1	49	13.19		0
	25	0	13.05	0-2	0
	25	12	13.05		0
	25	25	13.03		0
	50	0	13.02		0
64QAM	1	0	13.11	0-2	0
	1	25	12.99		0
	1	49	12.97		0
	25	0	13.02	0-3	0
	25	12	13.05		0
	25	25	13.01		0
	50	0	12.99		0

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 8-10
LTE Band 12 Reduced Conducted Powers - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.02	12.84	12.98	0	0
	1	12	12.93	12.78	12.89		0
	1	24	12.87	12.72	12.86		0
	12	0	12.97	12.87	13.01	0-1	0
	12	6	12.99	12.85	12.98		0
	12	13	12.94	12.79	12.90		0
	25	0	12.95	12.83	12.91		0
16QAM	1	0	13.29	13.10	13.23	0-1	0
	1	12	13.16	13.02	13.21		0
	1	24	13.09	12.99	13.04		0
	12	0	13.05	12.97	13.07	0-2	0
	12	6	13.05	12.92	13.04		0
	12	13	12.99	12.87	12.99		0
	25	0	13.04	12.88	13.01		0
64QAM	1	0	13.25	13.09	13.22	0-2	0
	1	12	13.20	13.04	13.18		0
	1	24	13.12	12.98	13.10		0
	12	0	13.08	12.96	13.06	0-3	0
	12	6	13.04	12.91	13.03		0
	12	13	13.00	12.84	12.98		0
	25	0	12.99	12.90	13.02		0

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 26 of 82	

Table 8-11
LTE Band 12 Reduced Conducted Powers - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.95	12.80	12.92	0	0
	1	7	13.00	12.87	13.01		0
	1	14	12.89	12.72	12.87		0
	8	0	12.98	12.82	12.94	0-1	0
	8	4	13.00	12.83	12.96		0
	8	7	12.94	12.79	12.93		0
	15	0	12.99	12.79	12.89		0
16QAM	1	0	13.24	13.06	13.20	0-1	0
	1	7	13.31	13.09	13.23		0
	1	14	13.12	12.97	13.09		0
	8	0	13.10	12.93	13.04	0-2	0
	8	4	13.11	12.95	13.04		0
	8	7	13.06	12.92	13.00		0
	15	0	13.01	12.83	12.98		0
64QAM	1	0	13.25	13.06	13.19	0-2	0
	1	7	13.39	13.12	13.33		0
	1	14	13.16	13.00	13.08		0
	8	0	13.09	12.93	13.03	0-3	0
	8	4	13.07	12.93	13.05		0
	8	7	13.05	12.90	12.99		0
	15	0	13.06	12.89	12.98		0

Table 8-12
LTE Band 12 Reduced Conducted Powers -1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.90	12.75	12.97	0	0
	1	2	12.97	12.75	12.99		0
	1	5	12.85	12.69	12.90		0
	3	0	12.93	12.78	12.93		0
	3	2	12.95	12.78	13.02		0
	3	3	12.90	12.74	12.94		0
	6	0	12.93	12.76	12.88	0-1	0
16QAM	1	0	13.14	13.01	13.21	0-1	0
	1	2	13.25	13.03	13.29		0
	1	5	13.14	12.98	13.12		0
	3	0	13.04	12.88	13.10		0
	3	2	13.07	12.87	13.10		0
	3	3	12.99	12.87	13.11		0
	6	0	13.01	12.80	13.00	0-2	0
64QAM	1	0	13.09	12.95	13.15	0-2	0
	1	2	13.21	13.01	13.19		0
	1	5	13.11	12.89	13.10		0
	3	0	13.03	12.83	13.00		0
	3	2	13.07	12.87	13.09		0
	3	3	13.03	12.79	13.02		0
	6	0	12.97	12.81	13.01	0-3	0

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 27 of 82

8.3.2

LTE Band 13

Table 8-13
LTE Band 13 Maximum Conducted Powers - 10 MHz Bandwidth

LTE Band 13 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.64	0	0
	1	25	23.60		0
	1	49	23.54		0
	25	0	22.71	0-1	1
	25	12	22.72		1
	25	25	22.67		1
	50	0	22.70		1
16QAM	1	0	22.75	0-1	1
	1	25	22.67		1
	1	49	22.65		1
	25	0	21.72	0-2	2
	25	12	21.69		2
	25	25	21.65		2
	50	0	21.69		2
64QAM	1	0	21.89	0-2	2
	1	25	21.74		2
	1	49	21.73		2
	25	0	20.80	0-3	3
	25	12	20.78		3
	25	25	20.73		3
	50	0	20.79		3

Table 8-14
LTE Band 13 Maximum Conducted Powers - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.49	0	0
	1	12	23.43		0
	1	24	23.48		0
	12	0	22.50	0-1	1
	12	6	22.49		1
	12	13	22.50		1
	25	0	22.50		1
16QAM	1	0	22.27	0-1	1
	1	12	22.26		1
	1	24	22.24		1
	12	0	21.40	0-2	2
	12	6	21.44		2
	12	13	21.42		2
	25	0	21.50		2
64QAM	1	0	21.96	0-2	2
	1	12	21.90		2
	1	24	21.90		2
	12	0	20.54	0-3	3
	12	6	20.56		3
	12	13	20.53		3
	25	0	20.52		3

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 28 of 82	

Table 8-15
LTE Band 13 Reduced Conducted Powers - 10 MHz Bandwidth

LTE Band 13 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	13.07	0	0
	1	25	13.03		0
	1	49	12.96		0
	25	0	13.09	0-1	0
	25	12	13.10		0
	25	25	13.05		0
	50	0	13.05		0
16QAM	1	0	13.21	0-1	0
	1	25	13.12		0
	1	49	13.06		0
	25	0	13.17	0-2	0
	25	12	13.13		0
	25	25	13.05		0
	50	0	13.12		0
64QAM	1	0	13.34	0-2	0
	1	25	13.24		0
	1	49	13.22		0
	25	0	13.26	0-3	0
	25	12	13.25		0
	25	25	13.15		0
	50	0	13.24		0

Table 8-16
LTE Band 13 Reduced Conducted Powers - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	13.04	0	0
	1	12	12.94		0
	1	24	12.94		0
	12	0	13.06	0-1	0
	12	6	13.04		0
	12	13	13.02		0
	25	0	13.01		0
16QAM	1	0	13.28	0-1	0
	1	12	13.26		0
	1	24	13.22		0
	12	0	13.08	0-2	0
	12	6	13.10		0
	12	13	13.07		0
	25	0	13.04		0
64QAM	1	0	13.27	0-2	0
	1	12	13.21		0
	1	24	13.14		0
	12	0	13.10	0-3	0
	12	6	13.11		0
	12	13	13.08		0
	25	0	13.07		0

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 29 of 82	

8.3.3 LTE Band 5 (Cell)

Table 8-17
LTE Band 5 (Cell) Maximum Conducted Powers - 10 MHz Bandwidth

LTE Band 5 (Cell) 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20525 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.20	0	0
	1	25	24.17		0
	1	49	24.07		0
	25	0	23.18	0-1	1
	25	12	23.16		1
	25	25	23.12		1
	50	0	23.14		1
16QAM	1	0	23.83	0-1	1
	1	25	23.80		1
	1	49	23.75		1
	25	0	22.18	0-2	2
	25	12	22.20		2
	25	25	22.13		2
	50	0	22.16		2
64QAM	1	0	22.65	0-2	2
	1	25	22.60		2
	1	49	22.58		2
	25	0	21.22	0-3	3
	25	12	21.20		3
	25	25	21.15		3
	50	0	21.17		3

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 8-18
LTE Band 5 (Cell) Maximum Conducted Powers - 5 MHz Bandwidth

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.28	24.18	24.18	0	0
	1	12	24.24	24.13	24.11		0
	1	24	24.20	24.14	24.10		0
	12	0	23.26	23.14	23.16	0-1	1
	12	6	23.28	23.16	23.13		1
	12	13	23.22	23.10	23.11		1
	25	0	23.22	23.12	23.09		1
16QAM	1	0	23.48	23.41	23.39	0-1	1
	1	12	23.44	23.34	23.32		1
	1	24	23.46	23.36	23.30		1
	12	0	22.36	22.21	22.21	0-2	2
	12	6	22.33	22.21	22.20		2
	12	13	22.29	22.17	22.15		2
	25	0	22.23	22.07	22.10		2
64QAM	1	0	22.87	22.78	22.74	0-2	2
	1	12	22.85	22.76	22.72		2
	1	24	22.83	22.72	22.68		2
	12	0	21.32	21.20	21.20	0-3	3
	12	6	21.34	21.22	21.19		3
	12	13	21.27	21.21	21.11		3
	25	0	21.29	21.18	21.14		3

FCC ID: A3LSMT837R4			SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet			Page 30 of 82

Table 8-19
LTE Band 5 (Cell) Maximum Conducted Powers - 3 MHz Bandwidth

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.27	24.15	24.12	0	0
	1	7	24.36	24.24	24.22		0
	1	14	24.23	24.12	24.10		0
	8	0	23.27	23.12	23.08	0-1	1
	8	4	23.29	23.18	23.09		1
	8	7	23.22	23.14	23.07		1
	15	0	23.26	23.13	23.08		1
16QAM	1	0	23.35	23.36	23.20	0-1	1
	1	7	23.38	23.38	23.25		1
	1	14	23.34	23.30	23.21		1
	8	0	22.32	22.18	22.14	0-2	2
	8	4	22.31	22.16	22.16		2
	8	7	22.29	22.16	22.12		2
	15	0	22.32	22.18	22.14		2
64QAM	1	0	22.46	22.35	22.28	0-2	2
	1	7	22.50	22.40	22.36		2
	1	14	22.44	22.30	22.27		2
	8	0	21.20	21.28	21.02	0-3	3
	8	4	21.17	21.32	21.02		3
	8	7	21.15	21.28	21.03		3
	15	0	21.36	21.04	21.19		3

Table 8-20
LTE Band 5 (Cell) Maximum Conducted Powers -1.4 MHz Bandwidth

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.20	24.10	24.00	0	0
	1	2	24.26	24.16	24.08		0
	1	5	24.22	24.10	23.98		0
	3	0	24.24	24.12	24.08		0
	3	2	24.28	24.14	24.08		0
	3	3	24.25	24.12	24.04		0
	6	0	23.22	23.08	23.04	0-1	1
16QAM	1	0	23.32	23.10	23.04	0-1	1
	1	2	23.35	23.17	23.11		1
	1	5	23.30	23.12	23.01		1
	3	0	23.32	23.00	22.98		1
	3	2	23.34	23.07	23.02		1
	3	3	23.32	23.02	23.00		1
	6	0	22.20	22.20	22.18	0-2	2
64QAM	1	0	22.40	22.20	22.12	0-2	2
	1	2	22.46	22.23	22.20		2
	1	5	22.39	22.18	22.13		2
	3	0	22.34	22.00	21.95		2
	3	2	22.38	22.05	22.00		2
	3	3	22.36	21.98	21.96		2
	6	0	21.36	21.10	21.06	0-3	3

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 31 of 82

Table 8-21
LTE Band 5 (Cell) Reduced Conducted Powers - 10 MHz Bandwidth

LTE Band 5 (Cell) 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20525 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	15.13	0	0
	1	25	14.95		0
	1	49	14.86		0
	25	0	15.14	0-1	0
	25	12	15.11		0
	25	25	15.04		0
16QAM	50	0	15.00	0-1	0
	1	0	15.25		0
	1	25	15.14		0
	1	49	15.10	0-2	0
	25	0	15.12		0
	25	12	15.10		0
64QAM	25	25	15.04	0-2	0
	50	0	15.13		0
	1	0	15.50	0-2	0
	1	25	15.47		0
	1	49	15.45	0-3	0
	25	0	15.20		0
	25	12	15.23		0
	25	25	15.16	0-3	0
	50	0	15.14		0

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 8-22
LTE Band 5 (Cell) Reduced Conducted Powers - 5 MHz Bandwidth

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	15.14	15.02	14.93	0	0
	1	12	15.06	14.94	14.89		0
	1	24	15.05	14.92	14.83		0
	12	0	15.13	15.01	14.97	0-1	0
	12	6	15.15	15.02	14.96		0
	12	13	15.11	14.97	14.91		0
	25	0	15.11	14.97	14.92		0
16QAM	1	0	15.32	15.21	15.16	0-1	0
	1	12	15.25	15.18	15.08		0
	1	24	15.26	15.08	15.11		0
	12	0	15.15	15.03	15.01	0-2	0
	12	6	15.16	15.04	14.97		0
	12	13	15.11	14.99	14.96		0
	25	0	15.09	14.97	14.91		0
64QAM	1	0	15.31	15.24	15.13	0-2	0
	1	12	15.28	15.14	15.07		0
	1	24	15.16	15.04	15.03		0
	12	0	15.14	15.03	14.98	0-3	0
	12	6	15.14	15.06	14.99		0
	12	13	15.08	14.99	14.91		0
	25	0	15.10	15.02	14.95		0

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 32 of 82	

Table 8-23
LTE Band 5 (Cell) Reduced Conducted Powers - 3 MHz Bandwidth

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	15.06	14.95	14.90	0	0
	1	7	15.15	15.00	14.92		0
	1	14	14.99	14.90	14.83		0
	8	0	15.10	14.96	14.93	0-1	0
	8	4	15.10	15.01	14.94		0
	8	7	15.09	14.96	14.90		0
	15	0	15.13	14.97	14.91		0
16QAM	1	0	15.31	15.16	15.08	0-1	0
	1	7	15.38	15.24	15.15		0
	1	14	15.24	15.11	15.03		0
	8	0	15.14	15.02	14.97	0-2	0
	8	4	15.12	15.03	14.94		0
	8	7	15.11	14.99	14.91		0
	15	0	15.06	14.96	14.89		0
64QAM	1	0	15.27	15.13	15.05	0-2	0
	1	7	15.34	15.19	15.15		0
	1	14	15.22	15.07	15.05		0
	8	0	15.12	14.99	14.90	0-3	0
	8	4	15.12	15.00	14.96		0
	8	7	15.12	14.98	14.91		0
	15	0	15.10	14.98	14.91		0

Table 8-24
LTE Band 5 (Cell) Reduced Conducted Powers -1.4 MHz Bandwidth

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	15.00	14.89	14.77	0	0
	1	2	15.07	14.94	14.86		0
	1	5	14.94	14.84	14.80		0
	3	0	15.04	14.89	14.81		0
	3	2	15.07	14.90	14.83		0
	3	3	15.01	14.90	14.82		0
	6	0	15.06	14.87	14.81	0-1	0
16QAM	1	0	15.26	15.07	15.05	0-1	0
	1	2	15.25	15.10	15.12		0
	1	5	15.18	15.06	15.02		0
	3	0	15.07	14.98	14.88		0
	3	2	15.14	15.04	14.95		0
	3	3	15.08	14.98	14.86		0
	6	0	15.05	14.94	14.88	0-2	0
64QAM	1	0	15.19	15.01	14.98	0-2	0
	1	2	15.27	15.09	15.02		0
	1	5	15.18	15.01	14.90		0
	3	0	15.11	14.96	14.85		0
	3	2	15.15	15.02	14.94		0
	3	3	15.07	14.91	14.89		0
	6	0	15.04	14.92	14.86	0-3	0

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 33 of 82

8.3.4

LTE Band 66 (AWS)

Table 8-25
LTE Band 66 (AWS) Maximum Conducted Powers - 20 MHz Bandwidth

LTE Band 66 (AWS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132072 (1720.0 MHz)	132322 (1745.0 MHz)	132572 (1770.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.57	24.75	24.82	0	0
	1	50	24.32	24.45	24.59		0
	1	99	24.34	24.52	24.61		0
	50	0	23.51	23.72	23.74	0-1	1
	50	25	23.41	23.66	23.66		1
	50	50	23.33	23.62	23.60		1
	100	0	23.52	23.66	23.67		1
16QAM	1	0	23.87	24.00	23.95	0-1	1
	1	50	23.53	23.84	23.80		1
	1	99	23.52	23.92	23.89		1
	50	0	22.43	22.72	22.73	0-2	2
	50	25	22.40	22.67	22.65		2
	50	50	22.34	22.63	22.67		2
	100	0	22.48	22.70	22.70		2
64QAM	1	0	22.70	23.00	22.97	0-2	2
	1	50	22.45	22.94	22.96		2
	1	99	22.54	22.94	22.95		2
	50	0	21.48	21.70	21.74	0-3	3
	50	25	21.48	21.71	21.72		3
	50	50	21.42	21.63	21.64		3
	100	0	21.48	21.65	21.66		3

Table 8-26
LTE Band 66 (AWS) Maximum Conducted Powers - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.44	24.61	24.62	0	0
	1	36	24.25	24.46	24.44		0
	1	74	24.25	24.45	24.43		0
	36	0	23.39	23.66	23.62	0-1	1
	36	18	23.37	23.59	23.54		1
	36	37	23.32	23.53	23.52		1
	75	0	23.34	23.56	23.55		1
16QAM	1	0	23.52	24.00	23.68	0-1	1
	1	36	23.36	23.86	23.53		1
	1	74	23.34	23.81	23.55		1
	36	0	22.32	22.67	22.53	0-2	2
	36	18	22.30	22.63	22.50		2
	36	37	22.28	22.59	22.48		2
	75	0	22.39	22.59	22.57		2
64QAM	1	0	23.00	22.92	22.46	0-2	2
	1	36	22.96	22.74	22.32		2
	1	74	22.98	22.73	22.30		2
	36	0	21.42	21.72	21.71	0-3	3
	36	18	21.40	21.68	21.64		3
	36	37	21.37	21.62	21.60		3
	75	0	21.42	21.59	21.58		3

FCC ID: A3LSMT837R4			SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 34 of 82	

Table 8-27
LTE Band 66 (AWS) Maximum Conducted Powers - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.34	24.54	24.42	0	0
	1	25	24.25	24.47	24.32		0
	1	49	24.25	24.45	24.32		0
	25	0	23.38	23.59	23.52	0-1	1
	25	12	23.36	23.56	23.51		1
	25	25	23.34	23.50	23.47		1
	50	0	23.32	23.60	23.56		1
16QAM	1	0	23.74	23.72	23.65	0-1	1
	1	25	23.65	23.58	23.54		1
	1	49	23.62	23.56	23.52		1
	25	0	22.40	22.65	22.52	0-2	2
	25	12	22.38	22.58	22.51		2
	25	25	22.33	22.56	22.48		2
	50	0	22.41	22.58	22.52		2
64QAM	1	0	22.61	22.42	22.65	0-2	2
	1	25	22.53	22.34	22.54		2
	1	49	22.48	22.36	22.48		2
	25	0	21.44	21.69	21.62	0-3	3
	25	12	21.42	21.68	21.60		3
	25	25	21.36	21.60	21.58		3
	50	0	21.39	21.64	21.52		3

Table 8-28
LTE Band 66 (AWS) Maximum Conducted Powers - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.32	24.56	24.34	0	0
	1	12	24.28	24.48	24.32		0
	1	24	24.29	24.50	24.34		0
	12	0	23.26	23.56	23.47	0-1	1
	12	6	23.25	23.54	23.45		1
	12	13	23.23	23.57	23.42		1
	25	0	23.25	23.53	23.46		1
16QAM	1	0	23.65	23.94	23.80	0-1	1
	1	12	23.62	23.85	23.78		1
	1	24	23.61	23.88	23.78		1
	12	0	22.31	22.57	22.53	0-2	2
	12	6	22.30	22.55	22.54		2
	12	13	22.27	22.53	22.52		2
	25	0	22.24	22.62	22.48		2
64QAM	1	0	22.46	22.96	22.62	0-2	2
	1	12	22.42	22.90	22.60		2
	1	24	22.38	22.92	22.58		2
	12	0	21.26	21.61	21.48	0-3	3
	12	6	21.28	21.60	21.51		3
	12	13	21.24	21.58	21.90		3
	25	0	21.26	21.56	21.44		3

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 35 of 82	

Table 8-29
LTE Band 66 (AWS) Maximum Conducted Powers - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.12	24.43	24.35	0	0
	1	7	24.20	24.51	24.46		0
	1	14	24.09	24.40	24.34		0
	8	0	23.24	23.50	23.46	0-1	1
	8	4	23.26	23.54	23.41		1
	8	7	23.20	23.48	23.42		1
	15	0	23.22	23.50	23.42		1
16QAM	1	0	23.36	23.79	23.50	0-1	1
	1	7	23.40	23.90	23.58		1
	1	14	23.30	23.74	23.44		1
	8	0	22.30	22.49	22.30	0-2	2
	8	4	22.28	22.44	22.33		2
	8	7	22.26	22.46	22.28		2
	15	0	22.16	22.54	22.42		2
64QAM	1	0	22.34	22.68	22.21	0-2	2
	1	7	22.42	22.82	22.34		2
	1	14	22.28	22.66	22.20		2
	8	0	21.24	21.56	21.52	0-3	3
	8	4	21.26	21.58	21.52		3
	8	7	21.21	21.54	21.51		3
	15	0	21.40	21.52	21.47		3

Table 8-30
LTE Band 66 (AWS) Maximum Conducted Powers -1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.08	24.52	24.28	0	0
	1	2	24.12	24.58	24.34		0
	1	5	24.04	24.53	24.26		0
	3	0	24.12	24.45	24.32		0
	3	2	24.20	24.46	24.40		0
	3	3	24.14	24.42	24.34		0
	6	0	23.12	23.41	23.36		0-1
16QAM	1	0	23.16	23.34	23.46	0-1	1
	1	2	23.24	23.42	23.52		1
	1	5	23.18	23.34	23.48		1
	3	0	23.28	23.40	23.28		1
	3	2	23.32	23.48	23.38		1
	3	3	23.26	23.42	23.33		1
	6	0	22.15	22.52	22.32		0-2
64QAM	1	0	21.94	22.65	22.42	0-2	2
	1	2	22.02	22.76	22.50		2
	1	5	21.90	22.60	22.46		2
	3	0	22.22	22.73	22.34		2
	3	2	22.27	22.77	22.42		2
	3	3	22.22	22.68	22.38		2
	6	0	21.40	21.41	21.50		0-3

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 36 of 82

Table 8-31
LTE Band 66 (AWS) Reduced Conducted Powers - 20 MHz Bandwidth

LTE Band 66 (AWS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132072 (1720.0 MHz)	132322 (1745.0 MHz)	132572 (1770.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.49	13.64	13.49	0	0
	1	50	13.23	13.45	13.34		0
	1	99	13.25	13.51	13.33		0
	50	0	13.45	13.66	13.66	0-1	0
	50	25	13.43	13.67	13.60		0
	50	50	13.35	13.57	13.53		0
	100	0	13.41	13.61	13.60		0
16QAM	1	0	13.74	13.97	13.98	0-1	0
	1	50	13.52	13.94	13.75		0
	1	99	13.51	13.89	13.76		0
	50	0	13.43	13.70	13.64	0-2	0
	50	25	13.43	13.61	13.62		0
	50	50	13.40	13.64	13.58		0
	100	0	13.42	13.61	13.63		0
64QAM	1	0	13.43	14.00	13.95	0-2	0
	1	50	13.26	13.95	13.76		0
	1	99	13.32	13.92	13.78		0
	50	0	13.56	13.72	13.68	0-3	0
	50	25	13.43	13.68	13.61		0
	50	50	13.37	13.64	13.60		0
	100	0	13.41	13.69	13.60		0

Table 8-32
LTE Band 66 (AWS) Reduced Conducted Powers - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.41	13.56	13.63	0	0
	1	36	13.24	13.41	13.43		0
	1	74	13.19	13.39	13.38		0
	36	0	13.40	13.55	13.57	0-1	0
	36	18	13.31	13.52	13.50		0
	36	37	13.28	13.46	13.46		0
	75	0	13.33	13.55	13.55		0
16QAM	1	0	13.64	13.83	13.81	0-1	0
	1	36	13.39	13.57	13.61		0
	1	74	13.36	13.61	13.62		0
	36	0	13.37	13.60	13.58	0-2	0
	36	18	13.31	13.56	13.55		0
	36	37	13.28	13.50	13.49		0
	75	0	13.33	13.54	13.52		0
64QAM	1	0	13.66	13.81	13.88	0-2	0
	1	36	13.44	13.64	13.67		0
	1	74	13.42	13.61	13.61		0
	36	0	13.39	13.57	13.54	0-3	0
	36	18	13.33	13.55	13.53		0
	36	37	13.28	13.49	13.50		0
	75	0	13.33	13.55	13.53		0

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 37 of 82	

Table 8-33
LTE Band 66 (AWS) Reduced Conducted Powers - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.34	13.50	13.51	0	0
	1	25	13.22	13.40	13.40		0
	1	49	13.22	13.36	13.37		0
	25	0	13.36	13.53	13.51	0-1	0
	25	12	13.33	13.53	13.50		0
	25	25	13.27	13.44	13.44		0
	50	0	13.30	13.49	13.47		0
16QAM	1	0	13.57	13.72	13.75	0-1	0
	1	25	13.39	13.58	13.62		0
	1	49	13.40	13.62	13.54		0
	25	0	13.33	13.55	13.51	0-2	0
	25	12	13.32	13.52	13.49		0
	25	25	13.23	13.48	13.42		0
	50	0	13.30	13.53	13.50		0
64QAM	1	0	13.49	13.70	13.72	0-2	0
	1	25	13.38	13.59	13.59		0
	1	49	13.37	13.53	13.52		0
	25	0	13.35	13.59	13.56	0-3	0
	25	12	13.34	13.56	13.54		0
	25	25	13.28	13.49	13.50		0
	50	0	13.35	13.54	13.53		0

Table 8-34
LTE Band 66 (AWS) Reduced Conducted Powers - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.18	13.45	13.45	0	0
	1	12	13.16	13.44	13.37		0
	1	24	13.15	13.40	13.38		0
	12	0	13.22	13.51	13.44	0-1	0
	12	6	13.22	13.51	13.46		0
	12	13	13.18	13.45	13.43		0
	25	0	13.19	13.43	13.45		0
16QAM	1	0	13.44	13.65	13.62	0-1	0
	1	12	13.36	13.62	13.49		0
	1	24	13.32	13.62	13.56		0
	12	0	13.26	13.51	13.49	0-2	0
	12	6	13.26	13.55	13.53		0
	12	13	13.26	13.54	13.49		0
	25	0	13.19	13.49	13.42		0
64QAM	1	0	13.35	13.67	13.58	0-2	0
	1	12	13.30	13.59	13.59		0
	1	24	13.29	13.57	13.55		0
	12	0	13.20	13.53	13.50	0-3	0
	12	6	13.23	13.54	13.50		0
	12	13	13.23	13.55	13.49		0
	25	0	13.22	13.51	13.51		0

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 38 of 82	

Table 8-35
LTE Band 66 (AWS) Reduced Conducted Powers - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.16	13.42	13.35	0	0
	1	7	13.20	13.48	13.48		0
	1	14	13.10	13.36	13.34		0
	8	0	13.20	13.43	13.44	0-1	0
	8	4	13.20	13.44	13.40		0
	8	7	13.14	13.41	13.42		0
	15	0	13.21	13.45	13.40		0
16QAM	1	0	13.39	13.62	13.58	0-1	0
	1	7	13.50	13.67	13.70		0
	1	14	13.34	13.64	13.66		0
	8	0	13.25	13.52	13.50	0-2	0
	8	4	13.29	13.53	13.51		0
	8	7	13.22	13.52	13.46		0
	15	0	13.23	13.48	13.45		0
64QAM	1	0	13.33	13.60	13.56	0-2	0
	1	7	13.42	13.70	13.69		0
	1	14	13.33	13.58	13.54		0
	8	0	13.23	13.52	13.49	0-3	0
	8	4	13.24	13.53	13.50		0
	8	7	13.23	13.48	13.47		0
	15	0	13.22	13.50	13.45		0

Table 8-36
LTE Band 66 (AWS) Reduced Conducted Powers -1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.09	13.33	13.34	0	0
	1	2	13.14	13.43	13.35		0
	1	5	13.10	13.33	13.29		0
	3	0	13.14	13.38	13.35		0
	3	2	13.16	13.40	13.40		0
	3	3	13.13	13.38	13.33		0
	6	0	13.14	13.38	13.38	0-1	0
16QAM	1	0	13.32	13.61	13.55	0-1	0
	1	2	13.38	13.55	13.56		0
	1	5	13.30	13.59	13.49		0
	3	0	13.28	13.54	13.55		0
	3	2	13.30	13.60	13.50		0
	3	3	13.29	13.52	13.52		0
	6	0	13.22	13.46	13.39	0-2	0
64QAM	1	0	13.26	13.59	13.51	0-2	0
	1	2	13.36	13.62	13.60		0
	1	5	13.25	13.55	13.50		0
	3	0	13.17	13.46	13.43		0
	3	2	13.25	13.50	13.49		0
	3	3	13.19	13.45	13.41		0
	6	0	13.13	13.43	13.39	0-3	0

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 39 of 82	

8.3.5

LTE Band 25 (PCS)

Table 8-37
LTE Band 25 (PCS) Maximum Conducted Powers - 20 MHz Bandwidth

LTE Band 25 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26140 (1860.0 MHz)	26365 (1882.5 MHz)	26590 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.32	24.18	24.60	0	0
	1	50	24.15	24.03	24.37		0
	1	99	24.13	23.89	24.33		0
	50	0	23.34	23.33	23.49	0-1	1
	50	25	23.25	23.22	23.53		1
	50	50	23.19	23.17	23.43		1
	100	0	23.18	23.21	23.42		1
16QAM	1	0	23.51	23.64	23.77	0-1	1
	1	50	23.36	23.40	23.54		1
	1	99	23.29	23.40	23.50		1
	50	0	22.26	22.29	22.43	0-2	2
	50	25	22.21	22.26	22.41		2
	50	50	22.22	22.24	22.34		2
	100	0	22.20	22.26	22.42		2
64QAM	1	0	22.51	22.77	22.88	0-2	2
	1	50	22.24	22.52	22.59		2
	1	99	22.23	22.48	22.54		2
	50	0	21.26	21.31	21.40	0-3	3
	50	25	21.18	21.22	21.38		3
	50	50	21.15	21.21	21.28		3
	100	0	21.19	21.22	21.31		3

Table 8-38
LTE Band 25 (PCS) Maximum Conducted Powers - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.25	24.32	24.48	0	0
	1	36	24.05	24.06	24.23		0
	1	74	23.98	24.03	24.25		0
	36	0	23.20	23.19	23.42	0-1	1
	36	18	23.14	23.16	23.37		1
	36	37	23.07	23.11	23.35		1
	75	0	23.15	23.14	23.38		1
16QAM	1	0	23.52	23.49	23.70	0-1	1
	1	36	23.26	23.29	23.50		1
	1	74	23.22	23.31	23.50		1
	36	0	22.21	22.20	22.42	0-2	2
	36	18	22.14	22.16	22.36		2
	36	37	22.08	22.11	22.34		2
	75	0	22.19	22.17	22.37		2
64QAM	1	0	22.46	22.43	22.64	0-2	2
	1	36	22.25	22.28	22.49		2
	1	74	22.25	22.28	22.47		2
	36	0	21.21	21.23	21.43	0-3	3
	36	18	21.18	21.18	21.36		3
	36	37	21.10	21.10	21.34		3
	75	0	21.15	21.16	21.35		3

FCC ID: A3LSMT837R4				Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 40 of 82

Table 8-39
LTE Band 25 (PCS) Maximum Conducted Powers - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.14	24.14	24.35	0	0
	1	25	24.08	24.03	24.24		0
	1	49	24.00	24.02	24.24		0
	25	0	23.17	23.17	23.35	0-1	1
	25	12	23.16	23.11	23.33		1
	25	25	23.07	23.10	23.24		1
	50	0	23.10	23.12	23.31		1
16QAM	1	0	23.34	23.41	23.53	0-1	1
	1	25	23.29	23.32	23.46		1
	1	49	23.31	23.28	23.46		1
	25	0	22.17	22.17	22.35	0-2	2
	25	12	22.16	22.15	22.33		2
	25	25	22.08	22.05	22.27		2
	50	0	22.13	22.11	22.33		2
64QAM	1	0	22.34	22.35	22.47	0-2	2
	1	25	22.20	22.21	22.44		2
	1	49	22.20	22.24	22.37		2
	25	0	21.17	21.16	21.33	0-3	3
	25	12	21.15	21.16	21.33		3
	25	25	21.11	21.10	21.29		3
	50	0	21.16	21.13	21.32		3

Table 8-40
LTE Band 25 (PCS) Maximum Conducted Powers - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.09	24.11	24.39	0	0
	1	12	24.02	24.05	24.30		0
	1	24	24.04	24.02	24.28		0
	12	0	23.11	23.08	23.40	0-1	1
	12	6	23.11	23.09	23.40		1
	12	13	23.06	23.03	23.36		1
	25	0	23.12	23.07	23.37		1
16QAM	1	0	23.38	23.32	23.65	0-1	1
	1	12	23.28	23.31	23.58		1
	1	24	23.23	23.29	23.47		1
	12	0	22.15	22.13	22.41	0-2	2
	12	6	22.18	22.15	22.43		2
	12	13	22.11	22.11	22.39		2
	25	0	22.10	22.08	22.38		2
64QAM	1	0	22.28	22.29	22.57	0-2	2
	1	12	22.21	22.25	22.53		2
	1	24	22.21	22.17	22.45		2
	12	0	21.14	21.12	21.33	0-3	3
	12	6	21.16	21.13	21.32		3
	12	13	21.15	21.12	21.30		3
	25	0	21.12	21.09	21.39		3

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 41 of 82	

Table 8-41
LTE Band 25 (PCS) Maximum Conducted Powers - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.06	24.05	24.32	0	0
	1	7	24.12	24.09	24.38		0
	1	14	23.98	23.96	24.26		0
	8	0	23.09	23.02	23.35	0-1	1
	8	4	23.08	23.08	23.39		1
	8	7	23.04	23.03	23.36		1
	15	0	23.08	23.09	23.28		1
16QAM	1	0	23.23	23.21	23.57	0-1	1
	1	7	23.36	23.38	23.67		1
	1	14	23.18	23.23	23.51		1
	8	0	22.10	22.10	22.38	0-2	2
	8	4	22.18	22.14	22.41		2
	8	7	22.14	22.08	22.35		2
	15	0	22.11	22.02	22.32		2
64QAM	1	0	22.22	22.24	22.51	0-2	2
	1	7	22.36	22.30	22.63		2
	1	14	22.18	22.21	22.44		2
	8	0	21.14	21.14	21.31	0-3	3
	8	4	21.11	21.15	21.29		3
	8	7	21.11	21.09	21.29		3
	15	0	21.09	21.06	21.33		3

Table 8-42
LTE Band 25 (PCS) Maximum Conducted Powers -1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.97	23.94	24.24	0	0
	1	2	24.02	23.94	24.32		0
	1	5	23.95	23.94	24.22		0
	3	0	23.99	24.01	24.26		0
	3	2	24.03	24.04	24.29		0
	3	3	23.97	23.99	24.29		0
	6	0	23.02	22.97	23.27	0-1	1
16QAM	1	0	23.21	23.25	23.50	0-1	1
	1	2	23.30	23.18	23.51		1
	1	5	23.26	23.16	23.36		1
	3	0	23.10	23.14	23.39		1
	3	2	23.16	23.16	23.43		1
	3	3	23.12	23.11	23.39		1
	6	0	22.08	22.05	22.34	0-2	2
64QAM	1	0	22.17	22.20	22.41	0-2	2
	1	2	22.24	22.24	22.49		2
	1	5	22.12	22.10	22.40		2
	3	0	22.07	22.11	22.29		2
	3	2	22.08	22.08	22.24		2
	3	3	22.06	22.09	22.26		2
	6	0	21.05	20.98	21.25	0-3	3

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 42 of 82

Table 8-43
LTE Band 25 (PCS) Reduced Conducted Powers - 20 MHz Bandwidth

LTE Band 25 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26140 (1860.0 MHz)	26365 (1882.5 MHz)	26590 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.33	13.19	13.44	0	0
	1	50	13.16	12.99	13.30		0
	1	99	13.06	12.93	13.19		0
	50	0	13.25	13.24	13.45	0-1	0
	50	25	13.17	13.23	13.37		0
	50	50	13.16	13.21	13.29		0
	100	0	13.19	13.23	13.38		0
16QAM	1	0	13.70	13.62	13.67	0-1	0
	1	50	13.51	13.49	13.52		0
	1	99	13.46	13.32	13.46		0
	50	0	13.30	13.28	13.43	0-2	0
	50	25	13.28	13.31	13.45		0
	50	50	13.20	13.26	13.40		0
	100	0	13.25	13.19	13.41		0
64QAM	1	0	13.45	13.33	13.93	0-2	0
	1	50	13.22	13.09	13.70		0
	1	99	13.32	13.07	13.60		0
	50	0	13.21	13.29	13.45	0-3	0
	50	25	13.10	13.24	13.35		0
	50	50	13.05	13.20	13.22		0
	100	0	13.14	13.18	13.37		0

Table 8-44
LTE Band 25 (PCS) Reduced Conducted Powers - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.22	13.17	13.34	0	0
	1	36	13.04	12.95	13.12		0
	1	74	12.94	12.96	13.19		0
	36	0	13.18	13.13	13.35	0-1	0
	36	18	13.08	13.12	13.31		0
	36	37	13.04	13.08	13.28		0
	75	0	13.11	13.10	13.33		0
16QAM	1	0	13.43	13.35	13.55	0-1	0
	1	36	13.29	13.16	13.32		0
	1	74	13.15	13.20	13.35		0
	36	0	13.15	13.15	13.39	0-2	0
	36	18	13.14	13.13	13.33		0
	36	37	13.09	13.08	13.28		0
	75	0	13.14	13.10	13.33		0
64QAM	1	0	13.43	13.47	13.63	0-2	0
	1	36	13.27	13.25	13.43		0
	1	74	13.21	13.27	13.45		0
	36	0	13.18	13.19	13.39	0-3	0
	36	18	13.13	13.12	13.31		0
	36	37	13.06	13.11	13.29		0
	75	0	13.14	13.13	13.34		0

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 43 of 82	

Table 8-45
LTE Band 25 (PCS) Reduced Conducted Powers - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.13	13.09	13.29	0	0
	1	25	13.01	13.01	13.17		0
	1	49	12.98	12.96	13.13		0
	25	0	13.12	13.11	13.31	0-1	0
	25	12	13.11	13.07	13.26		0
	25	25	13.04	13.05	13.23		0
	50	0	13.08	13.06	13.25		0
16QAM	1	0	13.34	13.34	13.48	0-1	0
	1	25	13.23	13.16	13.40		0
	1	49	13.28	13.11	13.39		0
	25	0	13.15	13.11	13.31	0-2	0
	25	12	13.14	13.08	13.29		0
	25	25	13.03	13.05	13.20		0
	50	0	13.14	13.08	13.28		0
64QAM	1	0	13.25	13.26	13.45	0-2	0
	1	25	13.21	13.19	13.38		0
	1	49	13.13	13.17	13.32		0
	25	0	13.14	13.15	13.35	0-3	0
	25	12	13.13	13.11	13.34		0
	25	25	13.10	13.07	13.27		0
	50	0	13.12	13.13	13.33		0

Table 8-46
LTE Band 25 (PCS) Reduced Conducted Powers - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.06	13.04	13.25	0	0
	1	12	12.99	12.97	13.24		0
	1	24	13.03	12.98	13.23		0
	12	0	13.07	13.05	13.34	0-1	0
	12	6	13.08	13.08	13.35		0
	12	13	13.02	13.04	13.30		0
	25	0	13.03	13.07	13.29		0
16QAM	1	0	13.24	13.27	13.54	0-1	0
	1	12	13.16	13.20	13.43		0
	1	24	13.24	13.21	13.40		0
	12	0	13.12	13.10	13.38	0-2	0
	12	6	13.12	13.12	13.37		0
	12	13	13.13	13.09	13.36		0
	25	0	13.07	13.04	13.33		0
64QAM	1	0	13.28	13.20	13.47	0-2	0
	1	12	13.19	13.17	13.39		0
	1	24	13.14	13.12	13.42		0
	12	0	13.12	13.12	13.29	0-3	0
	12	6	13.12	13.10	13.31		0
	12	13	13.14	13.10	13.32		0
	25	0	13.09	13.07	13.36		0

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 44 of 82	

Table 8-47
LTE Band 25 (PCS) Reduced Conducted Powers - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	13.02	12.99	13.19	0	0
	1	7	13.06	13.06	13.32		0
	1	14	12.98	12.95	13.20		0
	8	0	13.04	13.04	13.31	0-1	0
	8	4	13.06	13.06	13.30		0
	8	7	13.02	13.01	13.28		0
	15	0	13.02	13.02	13.23		0
16QAM	1	0	13.22	13.19	13.47	0-1	0
	1	7	13.24	13.26	13.52		0
	1	14	13.18	13.21	13.45		0
	8	0	13.12	13.09	13.34	0-2	0
	8	4	13.12	13.08	13.36		0
	8	7	13.07	13.05	13.35		0
	15	0	13.08	13.06	13.31		0
64QAM	1	0	13.18	13.14	13.46	0-2	0
	1	7	13.28	13.23	13.54		0
	1	14	13.16	13.17	13.40		0
	8	0	13.06	13.05	13.29	0-3	0
	8	4	13.08	13.08	13.30		0
	8	7	13.06	13.05	13.29		0
	15	0	13.07	13.05	13.33		0

Table 8-48
LTE Band 25 (PCS) Reduced Conducted Powers -1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	12.97	12.89	13.17	0	0
	1	2	13.00	12.98	13.22		0
	1	5	12.90	12.92	13.18		0
	3	0	12.95	12.95	13.20		0
	3	2	13.00	12.98	13.23		0
	3	3	12.96	12.95	13.20		0
	6	0	13.00	12.94	13.22	0-1	0
16QAM	1	0	13.13	13.14	13.36	0-1	0
	1	2	13.30	13.24	13.49		0
	1	5	13.14	13.12	13.41		0
	3	0	13.09	13.06	13.36		0
	3	2	13.16	13.19	13.37		0
	3	3	13.08	13.13	13.38		0
	6	0	13.03	13.02	13.30	0-2	0
64QAM	1	0	13.11	13.05	13.35	0-2	0
	1	2	13.20	13.16	13.42		0
	1	5	13.11	13.14	13.36		0
	3	0	13.05	13.02	13.24		0
	3	2	13.07	13.00	13.24		0
	3	3	13.05	12.99	13.22		0
	6	0	13.00	12.99	13.24	0-3	0

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 45 of 82	

8.4 WLAN Conducted Powers

Table 8-49
2.4 GHz WLAN Maximum Average RF Power – Ant 1

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	13.32	13.10	12.94
2437	6	12.99	12.79	12.67
2462	11	13.31	13.37	13.19

Table 8-50
2.4 GHz WLAN Maximum Average RF Power – Ant 2

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	13.32	13.17	13.05
2437	6	12.89	12.73	12.51
2462	11	12.97	12.85	12.66

Table 8-51
5 GHz WLAN Maximum Average RF Power – Ant 1

5GHz (40MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11n
		Average
5190	38	13.43
5230	46	13.29
5270	54	12.98
5310	62	13.19
5510	102	13.14
5590	118	12.87
5630	126	13.06
5710	142	12.73
5755	151	12.92
5795	159	12.45

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 46 of 82

Table 8-52
5 GHz WLAN Maximum Average RF Power – Ant 2

5GHz (40MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11n
		Average
5190	38	13.54
5230	46	12.69
5270	54	12.61
5310	62	13.12
5510	102	13.37
5590	118	13.48
5630	126	13.42
5710	142	13.36
5755	151	13.10
5795	159	13.42

Table 8-53
2.4 GHz WLAN Reduced Average RF Power – Ant 1

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	12.45	12.32	12.16
2437	6	12.14	12.04	11.85
2462	11	12.44	12.46	12.41

Table 8-54
2.4 GHz WLAN Reduced Average RF Power – Ant 2

2.4GHz Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11b	802.11g	802.11n
		Average	Average	Average
2412	1	11.60	12.47	12.34
2437	6	12.48	12.26	12.11
2462	11	11.87	11.77	12.45

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 47 of 82

Table 8-55
5 GHz WLAN Reduced Average RF Power – Ant 1

5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
		Average
5210	42	9.43
5290	58	8.47
5530	106	9.04
5610	122	9.16
5690	138	8.77
5775	155	9.26

Table 8-56
5 GHz WLAN Reduced Average RF Power – Ant 2

5GHz (80MHz) Conducted Power [dBm]		
Freq [MHz]	Channel	IEEE Transmission Mode
		802.11ac
		Average
5210	42	9.21
5290	58	9.47
5530	106	9.17
5610	122	9.13
5690	138	8.78
5775	155	8.88

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The bolded data rate and channel above were tested for SAR.




Figure 8-3
Power Measurement Setup

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 48 of 82	

8.5 Bluetooth Conducted Powers

Table 8-57
Bluetooth Average RF Power

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	1.0	0	7.44	5.551
2441	1.0	39	6.92	4.921
2480	1.0	78	8.32	6.787
2402	2.0	0	6.82	4.808
2441	2.0	39	6.36	4.328
2480	2.0	78	7.75	5.955
2402	3.0	0	6.87	4.862
2441	3.0	39	6.41	4.378
2480	3.0	78	7.80	6.027

Note: The bolded data rates and channel above were tested for SAR.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 49 of 82




Figure 8-4
Bluetooth Transmission Plot

Equation 8-1
Bluetooth Duty Cycle Calculation

$$\text{Duty Cycle} = \frac{\text{Pulse Width}}{\text{Period}} * 100\% = \frac{2.90\text{ms}}{3.75\text{ms}} * 100\% = 77.3\%$$




Figure 8-5
Power Measurement Setup

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 50 of 82

9 SYSTEM VERIFICATION

9.1 Tissue Verification

Table 9-1
Measured Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
06/25/2018	750B	22.0	700	0.967	53.869	0.959	55.726	0.83%	-3.33%
			710	0.972	53.770	0.960	55.687	1.25%	-3.44%
			740	0.982	53.724	0.963	55.570	1.97%	-3.32%
			755	0.989	53.606	0.964	55.512	2.59%	-3.43%
			770	0.993	53.601	0.965	55.453	2.90%	-3.34%
			785	0.999	53.600	0.966	55.395	3.42%	-3.24%
07/02/2018	835B	20.3	820	0.975	54.021	0.969	55.258	0.62%	-2.24%
			835	0.980	53.985	0.970	55.200	1.03%	-2.20%
			850	0.985	53.937	0.988	55.154	-0.30%	-2.21%
07/10/2018	1750B	21.8	1710	1.471	52.126	1.463	53.537	0.55%	-2.64%
			1750	1.493	51.998	1.488	53.432	0.34%	-2.68%
			1790	1.524	51.963	1.514	53.326	0.66%	-2.56%
06/25/2018	1900B	22.0	1850	1.519	51.310	1.520	53.300	-0.07%	-3.73%
			1880	1.554	51.239	1.520	53.300	2.24%	-3.87%
			1910	1.586	51.163	1.520	53.300	4.34%	-4.01%
07/02/2018	1900B	22.3	1850	1.500	51.413	1.520	53.300	-1.32%	-3.54%
			1880	1.535	51.307	1.520	53.300	0.99%	-3.74%
			1910	1.568	51.198	1.520	53.300	3.16%	-3.94%
07/02/2018	2450B	21.7	2400	1.968	50.714	1.902	52.767	3.47%	-3.89%
			2450	2.025	50.558	1.950	52.700	3.85%	-4.06%
			2500	2.084	50.421	2.021	52.636	3.12%	-4.21%
07/04/2018	2450B	22.5	2400	1.970	51.717	1.902	52.767	3.58%	-1.99%
			2450	2.038	51.523	1.950	52.700	4.51%	-2.23%
			2500	2.110	51.334	2.021	52.636	4.40%	-2.47%
07/02/2018	5200B-5800B	21.8	5240	5.485	48.261	5.346	48.960	2.60%	-1.43%
			5260	5.503	48.255	5.369	48.933	2.50%	-1.39%
			5280	5.541	48.218	5.393	48.906	2.74%	-1.41%
			5300	5.556	48.198	5.416	48.879	2.58%	-1.39%
			5320	5.588	48.157	5.439	48.851	2.74%	-1.42%
			5500	5.823	47.849	5.650	48.607	3.06%	-1.56%
			5520	5.863	47.772	5.673	48.580	3.35%	-1.66%
			5540	5.885	47.767	5.696	48.553	3.32%	-1.62%
			5580	5.935	47.696	5.743	48.499	3.34%	-1.66%
			5600	5.956	47.625	5.766	48.471	3.30%	-1.75%
			5620	5.985	47.609	5.790	48.444	3.37%	-1.72%
			5680	6.079	47.531	5.860	48.363	3.74%	-1.72%
			5700	6.108	47.519	5.883	48.336	3.82%	-1.69%
			5745	6.167	47.441	5.936	48.275	3.89%	-1.73%
			5765	6.193	47.374	5.959	48.248	3.93%	-1.81%
			5785	6.228	47.363	5.982	48.220	4.11%	-1.78%
			5800	6.258	47.325	6.000	48.200	4.30%	-1.82%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.


FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 51 of 82

9.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

**Table 9-2
System Verification Results**

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
J	750	BODY	06/25/2018	21.5	22.0	0.200	1003	3914	1.860	8.580	9.300	8.39%
J	835	BODY	07/02/2018	20.3	20.3	0.200	4d132	3914	2.010	9.710	10.050	3.50%
J	1750	BODY	07/10/2018	22.0	21.8	0.100	1150	3347	3.610	36.500	36.100	-1.10%
I	1900	BODY	06/25/2018	21.1	21.2	0.100	5d148	7406	4.190	39.600	41.900	5.81%
I	1900	BODY	07/02/2018	22.4	22.3	0.100	5d141	7406	4.130	40.000	41.300	3.25%
K	2450	BODY	07/02/2018	22.2	21.7	0.100	882	3319	5.100	50.200	51.000	1.59%
G	2450	BODY	07/04/2018	23.5	22.5	0.100	882	3332	4.850	50.200	48.500	-3.39%
D	5250	BODY	07/02/2018	22.4	21.1	0.050	1237	7357	3.600	76.900	72.000	-6.37%
D	5600	BODY	07/02/2018	22.4	21.1	0.050	1237	7357	4.000	78.500	80.000	1.91%
D	5750	BODY	07/02/2018	22.4	21.1	0.050	1237	7357	3.840	77.100	76.800	-0.39%



**Figure 9-1
System Verification Setup Diagram**



**Figure 9-2
System Verification Setup Photo**

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 52 of 82

10 SAR DATA SUMMARY

10.1 Standalone Body SAR Data

Table 10-1
UMTS Body SAR Data

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
826.40	4132	UMTS 850	RMC	25.0	24.05	0.17	16 mm	03144	1:1	back	0.618	1.245	0.769	
836.60	4183	UMTS 850	RMC	25.0	23.97	-0.12	16 mm	03144	1:1	back	0.664	1.268	0.842	
846.60	4233	UMTS 850	RMC	25.0	23.92	0.13	16 mm	03144	1:1	back	0.562	1.282	0.720	
826.40	4132	UMTS 850	RMC	25.0	24.05	-0.04	16 mm	03144	1:1	top	0.990	1.245	1.233	A1
836.60	4183	UMTS 850	RMC	25.0	23.97	0.00	16 mm	03144	1:1	top	0.939	1.268	1.191	
846.60	4233	UMTS 850	RMC	25.0	23.92	0.10	16 mm	03144	1:1	top	0.866	1.282	1.110	
836.60	4183	UMTS 850	RMC	25.0	23.97	0.02	0 mm	03144	1:1	right	0.201	1.268	0.255	
836.60	4183	UMTS 850	RMC	25.0	23.97	-0.06	0 mm	03144	1:1	left	0.111	1.268	0.141	
826.40	4132	UMTS 850	RMC	17.0	16.28	-0.13	0 mm	03144	1:1	back	0.772	1.180	0.911	
836.60	4183	UMTS 850	RMC	17.0	16.17	-0.15	0 mm	03144	1:1	back	0.772	1.211	0.935	
846.60	4233	UMTS 850	RMC	17.0	16.12	0.01	0 mm	03144	1:1	back	0.704	1.225	0.862	
826.40	4132	UMTS 850	RMC	17.0	16.28	-0.08	0 mm	03144	1:1	top	0.953	1.180	1.125	
836.60	4183	UMTS 850	RMC	17.0	16.17	-0.13	0 mm	03144	1:1	top	0.909	1.211	1.101	
846.60	4233	UMTS 850	RMC	17.0	16.12	-0.07	0 mm	03144	1:1	top	0.884	1.225	1.083	
1880.00	9400	UMTS 1900	RMC	25.0	23.98	-0.01	16 mm	01064	1:1	back	0.565	1.265	0.715	
1880.00	9400	UMTS 1900	RMC	25.0	23.98	-0.01	16 mm	01064	1:1	top	0.598	1.265	0.756	
1852.40	9262	UMTS 1900	RMC	25.0	24.08	0.00	0 mm	01064	1:1	right	0.690	1.236	0.853	
1880.00	9400	UMTS 1900	RMC	25.0	23.98	-0.02	0 mm	01064	1:1	right	0.708	1.265	0.896	
1907.60	9538	UMTS 1900	RMC	25.0	24.04	0.01	0 mm	01064	1:1	right	0.778	1.247	0.970	
1880.00	9400	UMTS 1900	RMC	25.0	23.98	-0.01	0 mm	01064	1:1	left	0.358	1.265	0.453	
1852.40	9262	UMTS 1900	RMC	14.0	13.49	-0.04	0 mm	01064	1:1	back	1.050	1.125	1.181	
1880.00	9400	UMTS 1900	RMC	14.0	13.40	0.01	0 mm	01064	1:1	back	1.030	1.148	1.182	
1907.60	9538	UMTS 1900	RMC	14.0	13.52	0.01	0 mm	01064	1:1	back	1.140	1.117	1.273	A2
1852.40	9262	UMTS 1900	RMC	14.0	13.49	0.13	0 mm	01064	1:1	top	0.787	1.125	0.885	
1880.00	9400	UMTS 1900	RMC	14.0	13.40	-0.01	0 mm	01064	1:1	top	0.749	1.148	0.860	
1907.60	9538	UMTS 1900	RMC	14.0	13.52	0.13	0 mm	01064	1:1	top	0.854	1.117	0.954	
1907.60	9538	UMTS 1900	RMC	14.0	13.52	0.04	0 mm	01064	1:1	back	1.140	1.117	1.273	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram							

Note: Blue entry indicates variability measurement.

FCC ID: A3LSMT837R4	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 53 of 82

**Table 10-2
CDMA Body SAR Data**

MEASUREMENT RESULTS														
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.52	384	Cell. CDMA	EVDO Rev. 0	25.5	24.81	-0.03	16 mm	03169	1:1	back	0.625	1.172	0.733	
824.70	1013	Cell. CDMA	EVDO Rev. 0	25.5	24.98	-0.06	16 mm	03169	1:1	top	1.240	1.127	1.397	A3
836.52	384	Cell. CDMA	EVDO Rev. 0	25.5	24.81	0.08	16 mm	03169	1:1	top	1.050	1.172	1.231	
848.31	777	Cell. CDMA	EVDO Rev. 0	25.5	24.49	0.17	16 mm	03169	1:1	top	0.784	1.262	0.989	
836.52	384	Cell. CDMA	EVDO Rev. 0	25.5	24.81	-0.03	0 mm	03169	1:1	right	0.200	1.172	0.234	
836.52	384	Cell. CDMA	EVDO Rev. 0	25.5	24.81	-0.20	0 mm	03169	1:1	left	0.111	1.172	0.130	
836.52	384	Cell. CDMA	EVDO Rev. 0	16.0	15.28	-0.05	0 mm	03169	1:1	back	0.625	1.180	0.738	
824.70	1013	Cell. CDMA	EVDO Rev. 0	16.0	15.43	-0.08	0 mm	03169	1:1	top	0.763	1.140	0.870	
836.52	384	Cell. CDMA	EVDO Rev. 0	16.0	15.28	-0.05	0 mm	03169	1:1	top	0.725	1.180	0.856	
848.31	777	Cell. CDMA	EVDO Rev. 0	16.0	15.14	-0.12	0 mm	03169	1:1	top	0.667	1.219	0.813	
824.70	1013	Cell. CDMA	EVDO Rev. 0	25.5	24.98	0.01	16 mm	03169	1:1	top	1.200	1.127	1.352	
1851.25	25	PCS CDMA	EVDO Rev. 0	25.5	24.11	0.02	16 mm	01064	1:1	back	0.627	1.377	0.863	
1880.00	600	PCS CDMA	EVDO Rev. 0	25.5	23.99	0.01	16 mm	01064	1:1	back	0.610	1.416	0.864	
1908.75	1175	PCS CDMA	EVDO Rev. 0	25.5	24.10	-0.02	16 mm	01064	1:1	back	0.672	1.380	0.927	
1851.25	25	PCS CDMA	EVDO Rev. 0	25.5	24.11	-0.03	16 mm	01064	1:1	top	0.616	1.377	0.848	
1880.00	600	PCS CDMA	EVDO Rev. 0	25.5	23.99	0.01	16 mm	01064	1:1	top	0.598	1.416	0.847	
1908.75	1175	PCS CDMA	EVDO Rev. 0	25.5	24.10	-0.03	16 mm	01064	1:1	top	0.606	1.380	0.836	
1851.25	25	PCS CDMA	EVDO Rev. 0	25.5	24.11	0.04	0 mm	01064	1:1	right	0.742	1.377	1.022	
1880.00	600	PCS CDMA	EVDO Rev. 0	25.5	23.99	0.04	0 mm	01064	1:1	right	0.772	1.416	1.093	
1908.75	1175	PCS CDMA	EVDO Rev. 0	25.5	24.10	0.04	0 mm	01064	1:1	right	0.810	1.380	1.118	
1880.00	600	PCS CDMA	EVDO Rev. 0	25.5	23.99	0.04	0 mm	01064	1:1	left	0.420	1.416	0.595	
1851.25	25	PCS CDMA	EVDO Rev. 0	14.0	13.31	0.13	0 mm	01064	1:1	back	0.798	1.172	0.935	
1880.00	600	PCS CDMA	EVDO Rev. 0	14.0	13.18	0.12	0 mm	01064	1:1	back	0.802	1.208	0.969	
1908.75	1175	PCS CDMA	EVDO Rev. 0	14.0	13.31	0.15	0 mm	01064	1:1	back	0.877	1.172	1.028	A4
1851.25	25	PCS CDMA	EVDO Rev. 0	14.0	13.31	0.00	0 mm	01064	1:1	top	0.771	1.172	0.904	
1880.00	600	PCS CDMA	EVDO Rev. 0	14.0	13.18	0.00	0 mm	01064	1:1	top	0.768	1.208	0.928	
1908.75	1175	PCS CDMA	EVDO Rev. 0	14.0	13.31	0.00	0 mm	01064	1:1	top	0.848	1.172	0.994	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram							

Note: Blue entry indicates variability measurement.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 54 of 82

Table 10-3
LTE Band 12 Body SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.0	23.76	0.00	0	03144	QPSK	1	0	16 mm	back	1:1	0.476	1.330	0.633	A5
707.50	23095	Mid	LTE Band 12	10	24.0	22.81	-0.04	1	03144	QPSK	25	0	16 mm	back	1:1	0.367	1.315	0.483	
707.50	23095	Mid	LTE Band 12	10	25.0	23.76	0.18	0	03144	QPSK	1	0	16 mm	top	1:1	0.407	1.330	0.541	
707.50	23095	Mid	LTE Band 12	10	24.0	22.81	-0.13	1	03144	QPSK	25	0	16 mm	top	1:1	0.326	1.315	0.429	
707.50	23095	Mid	LTE Band 12	10	25.0	23.76	-0.18	0	03144	QPSK	1	0	0 mm	right	1:1	0.117	1.330	0.156	
707.50	23095	Mid	LTE Band 12	10	24.0	22.81	-0.07	1	03144	QPSK	25	0	0 mm	right	1:1	0.087	1.315	0.114	
707.50	23095	Mid	LTE Band 12	10	25.0	23.76	-0.04	0	03144	QPSK	1	0	0 mm	left	1:1	0.085	1.330	0.113	
707.50	23095	Mid	LTE Band 12	10	24.0	22.81	0.00	1	03144	QPSK	25	0	0 mm	left	1:1	0.073	1.315	0.096	
707.50	23095	Mid	LTE Band 12	10	14.0	12.93	0.00	0	03144	QPSK	1	0	0 mm	back	1:1	0.391	1.279	0.500	
707.50	23095	Mid	LTE Band 12	10	14.0	12.96	-0.01	0	03144	QPSK	25	0	0 mm	back	1:1	0.392	1.271	0.498	
707.50	23095	Mid	LTE Band 12	10	14.0	12.93	0.09	0	03144	QPSK	1	0	0 mm	top	1:1	0.358	1.279	0.458	
707.50	23095	Mid	LTE Band 12	10	14.0	12.96	0.19	0	03144	QPSK	25	0	0 mm	top	1:1	0.356	1.271	0.452	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 10-4
LTE Band 13 Body SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
																(W/kg)		(W/kg)	
782.00	23230	Mid	LTE Band 13	10	24.5	23.64	0.00	0	03144	QPSK	1	0	16 mm	back	1:1	0.648	1.219	0.790	A6
782.00	23230	Mid	LTE Band 13	10	23.5	22.72	0.01	1	03144	QPSK	25	12	16 mm	back	1:1	0.505	1.197	0.604	
782.00	23230	Mid	LTE Band 13	10	24.5	23.64	0.05	0	03144	QPSK	1	0	16 mm	top	1:1	0.578	1.219	0.705	
782.00	23230	Mid	LTE Band 13	10	23.5	22.72	0.03	1	03144	QPSK	25	12	16 mm	top	1:1	0.485	1.197	0.581	
782.00	23230	Mid	LTE Band 13	10	24.5	23.64	-0.04	0	03144	QPSK	1	0	0 mm	right	1:1	0.194	1.219	0.236	
782.00	23230	Mid	LTE Band 13	10	23.5	22.72	-0.21	1	03144	QPSK	25	12	0 mm	right	1:1	0.146	1.197	0.175	
782.00	23230	Mid	LTE Band 13	10	24.5	23.64	-0.20	0	03144	QPSK	1	0	0 mm	left	1:1	0.090	1.219	0.110	
782.00	23230	Mid	LTE Band 13	10	23.5	22.72	-0.06	1	03144	QPSK	25	12	0 mm	left	1:1	0.068	1.197	0.081	
782.00	23230	Mid	LTE Band 13	10	14.0	13.07	0.03	0	03144	QPSK	1	0	0 mm	back	1:1	0.450	1.239	0.558	
782.00	23230	Mid	LTE Band 13	10	14.0	13.10	-0.05	0	03144	QPSK	25	12	0 mm	back	1:1	0.446	1.230	0.549	
782.00	23230	Mid	LTE Band 13	10	14.0	13.07	-0.04	0	03144	QPSK	1	0	0 mm	top	1:1	0.442	1.239	0.548	
782.00	23230	Mid	LTE Band 13	10	14.0	13.10	-0.05	0	03144	QPSK	25	12	0 mm	top	1:1	0.441	1.230	0.542	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 55 of 82

Table 10-5
LTE Band 5 (Cell) Body SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	24.20	0.03	0	03144	QPSK	1	0	16 mm	back	1:1	0.690	1.202	0.829	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.18	-0.15	1	03144	QPSK	25	0	16 mm	back	1:1	0.547	1.208	0.661	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.14	-0.16	1	03144	QPSK	50	0	16 mm	back	1:1	0.555	1.219	0.677	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	24.20	0.00	0	03144	QPSK	1	0	16 mm	top	1:1	0.915	1.202	1.100	A7
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.18	-0.20	1	03144	QPSK	25	0	16 mm	top	1:1	0.682	1.208	0.824	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.14	-0.05	1	03144	QPSK	50	0	16 mm	top	1:1	0.705	1.219	0.859	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	24.20	-0.01	0	03144	QPSK	1	0	0 mm	right	1:1	0.199	1.202	0.239	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.18	0.04	1	03144	QPSK	25	0	0 mm	right	1:1	0.156	1.208	0.188	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.0	24.20	0.15	0	03144	QPSK	1	0	0 mm	left	1:1	0.113	1.202	0.136	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.18	0.08	1	03144	QPSK	25	0	0 mm	left	1:1	0.094	1.208	0.114	
836.50	20525	Mid	LTE Band 5 (Cell)	10	16.0	15.13	-0.01	0	03144	QPSK	1	0	0 mm	back	1:1	0.643	1.222	0.786	
836.50	20525	Mid	LTE Band 5 (Cell)	10	16.0	15.14	-0.04	0	03144	QPSK	25	0	0 mm	back	1:1	0.646	1.219	0.787	
836.50	20525	Mid	LTE Band 5 (Cell)	10	16.0	15.13	0.00	0	03144	QPSK	1	0	0 mm	top	1:1	0.128	1.222	0.156	
836.50	20525	Mid	LTE Band 5 (Cell)	10	16.0	15.14	0.00	0	03144	QPSK	25	0	0 mm	top	1:1	0.125	1.219	0.152	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 10-6
LTE Band 66 (AWS) Body SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1770.00	132572	High	LTE Band 66 (AWS)	20	25.0	24.82	-0.07	0	02252	QPSK	1	0	16 mm	back	1:1	0.579	1.042	0.603	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.0	23.74	0.04	1	02252	QPSK	50	0	16 mm	back	1:1	0.448	1.062	0.476	
1770.00	132572	High	LTE Band 66 (AWS)	20	25.0	24.82	0.03	0	02252	QPSK	1	0	16 mm	top	1:1	0.554	1.042	0.577	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.0	23.74	-0.01	1	02252	QPSK	50	0	16 mm	top	1:1	0.446	1.062	0.474	
1720.00	132072	Low	LTE Band 66 (AWS)	20	25.0	24.57	-0.03	0	02252	QPSK	1	0	0 mm	right	1:1	0.885	1.104	0.977	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	25.0	24.75	0.01	0	02252	QPSK	1	0	0 mm	right	1:1	0.835	1.059	0.884	
1770.00	132572	High	LTE Band 66 (AWS)	20	25.0	24.82	0.08	0	02252	QPSK	1	0	0 mm	right	1:1	0.871	1.042	0.908	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.0	23.74	0.03	1	02252	QPSK	50	0	0 mm	right	1:1	0.629	1.062	0.668	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.0	23.67	0.01	1	02252	QPSK	100	0	0 mm	right	1:1	0.589	1.079	0.636	
1770.00	132572	High	LTE Band 66 (AWS)	20	25.0	24.82	0.14	0	02252	QPSK	1	0	0 mm	left	1:1	0.455	1.042	0.474	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.0	23.74	-0.06	1	02252	QPSK	50	0	0 mm	left	1:1	0.375	1.062	0.398	
1720.00	132072	Low	LTE Band 66 (AWS)	20	14.0	13.49	0.00	0	02252	QPSK	1	0	0 mm	back	1:1	0.814	1.125	0.916	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	14.0	13.64	0.02	0	02252	QPSK	1	0	0 mm	back	1:1	0.834	1.086	0.906	
1770.00	132572	High	LTE Band 66 (AWS)	20	14.0	13.49	0.00	0	02252	QPSK	1	0	0 mm	back	1:1	0.936	1.125	1.053	
1720.00	132072	Low	LTE Band 66 (AWS)	20	14.0	13.45	0.00	0	02252	QPSK	50	0	0 mm	back	1:1	0.807	1.135	0.916	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	14.0	13.67	0.06	0	02252	QPSK	50	25	0 mm	back	1:1	0.874	1.079	0.943	
1770.00	132572	High	LTE Band 66 (AWS)	20	14.0	13.66	-0.01	0	02252	QPSK	50	0	0 mm	back	1:1	0.929	1.081	1.004	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	14.0	13.61	0.00	0	02252	QPSK	100	0	0 mm	back	1:1	0.877	1.094	0.959	
1720.00	132072	Low	LTE Band 66 (AWS)	20	14.0	13.49	-0.19	0	02252	QPSK	1	0	0 mm	top	1:1	0.745	1.125	0.838	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	14.0	13.64	-0.13	0	02252	QPSK	1	0	0 mm	top	1:1	0.808	1.086	0.877	
1770.00	132572	High	LTE Band 66 (AWS)	20	14.0	13.49	-0.19	0	02252	QPSK	1	0	0 mm	top	1:1	0.831	1.125	0.935	
1720.00	132072	Low	LTE Band 66 (AWS)	20	14.0	13.45	-0.18	0	02252	QPSK	50	0	0 mm	top	1:1	0.736	1.135	0.835	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	14.0	13.67	-0.15	0	02252	QPSK	50	25	0 mm	top	1:1	0.781	1.079	0.843	
1770.00	132572	High	LTE Band 66 (AWS)	20	14.0	13.66	-0.17	0	02252	QPSK	50	0	0 mm	top	1:1	0.826	1.081	0.893	
1745.00	132322	Mid	LTE Band 66 (AWS)	20	14.0	13.61	-0.19	0	02252	QPSK	100	0	0 mm	top	1:1	0.783	1.094	0.857	
1770.00	132572	High	LTE Band 66 (AWS)	20	14.0	13.49	-0.02	0	02252	QPSK	1	0	0 mm	back	1:1	1.000	1.125	1.125	A8
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Note: Blue entry indicates variability measurement.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 56 of 82

Table 10-7
LTE Band 25 (PCS) Body SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1905.00	26590	High	LTE Band 25 (PCS)	20	25.0	24.60	0.00	0	01064	QPSK	1	0	16 mm	back	1:1	0.625	1.096	0.685	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.0	23.53	0.00	1	01064	QPSK	50	25	16 mm	back	1:1	0.480	1.114	0.535	
1905.00	26590	High	LTE Band 25 (PCS)	20	25.0	24.60	-0.01	0	01064	QPSK	1	0	16 mm	top	1:1	0.671	1.096	0.735	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.0	23.53	-0.01	1	01064	QPSK	50	25	16 mm	top	1:1	0.508	1.114	0.566	
1860.00	26140	Low	LTE Band 25 (PCS)	20	25.0	24.32	0.00	0	01064	QPSK	1	0	0 mm	right	1:1	0.709	1.169	0.829	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	25.0	24.18	0.04	0	01064	QPSK	1	0	0 mm	right	1:1	0.782	1.208	0.945	
1905.00	26590	High	LTE Band 25 (PCS)	20	25.0	24.60	0.02	0	01064	QPSK	1	0	0 mm	right	1:1	0.824	1.096	0.903	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.0	23.53	0.00	1	01064	QPSK	50	25	0 mm	right	1:1	0.668	1.114	0.744	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.0	23.42	-0.01	1	01064	QPSK	100	0	0 mm	right	1:1	0.669	1.143	0.765	
1905.00	26590	High	LTE Band 25 (PCS)	20	25.0	24.60	0.00	0	01064	QPSK	1	0	0 mm	left	1:1	0.341	1.096	0.374	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.0	23.53	0.03	1	01064	QPSK	50	25	0 mm	left	1:1	0.268	1.114	0.299	
1860.00	26140	Low	LTE Band 25 (PCS)	20	14.0	13.33	0.04	0	01064	QPSK	1	0	0 mm	back	1:1	0.994	1.167	1.160	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	14.0	13.19	0.16	0	01064	QPSK	1	0	0 mm	back	1:1	0.876	1.205	1.056	
1905.00	26590	High	LTE Band 25 (PCS)	20	14.0	13.44	0.05	0	01064	QPSK	1	0	0 mm	back	1:1	1.070	1.138	1.218	A9
1860.00	26140	Low	LTE Band 25 (PCS)	20	14.0	13.25	0.07	0	01064	QPSK	50	0	0 mm	back	1:1	0.993	1.189	1.181	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	14.0	13.24	0.20	0	01064	QPSK	50	0	0 mm	back	1:1	0.876	1.191	1.043	
1905.00	26590	High	LTE Band 25 (PCS)	20	14.0	13.45	0.04	0	01064	QPSK	50	0	0 mm	back	1:1	1.050	1.135	1.192	
1905.00	26590	High	LTE Band 25 (PCS)	20	14.0	13.38	0.04	0	01064	QPSK	100	0	0 mm	back	1:1	1.040	1.153	1.199	
1860.00	26140	Low	LTE Band 25 (PCS)	20	14.0	13.33	0.00	0	01064	QPSK	1	0	0 mm	top	1:1	0.738	1.167	0.861	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	14.0	13.19	0.00	0	01064	QPSK	1	0	0 mm	top	1:1	0.733	1.205	0.883	
1905.00	26590	High	LTE Band 25 (PCS)	20	14.0	13.44	0.03	0	01064	QPSK	1	0	0 mm	top	1:1	0.790	1.138	0.899	
1860.00	26140	Low	LTE Band 25 (PCS)	20	14.0	13.25	-0.01	0	01064	QPSK	50	0	0 mm	top	1:1	0.741	1.189	0.881	
1882.50	26365	Mid	LTE Band 25 (PCS)	20	14.0	13.24	-0.01	0	01064	QPSK	50	0	0 mm	top	1:1	0.729	1.191	0.868	
1905.00	26590	High	LTE Band 25 (PCS)	20	14.0	13.45	-0.02	0	01064	QPSK	50	0	0 mm	top	1:1	0.786	1.135	0.892	
1905.00	26590	High	LTE Band 25 (PCS)	20	14.0	13.38	-0.02	0	01064	QPSK	100	0	0 mm	top	1:1	0.781	1.153	0.900	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 57 of 82

Table 10-8
2.4 GHz WLAN Body SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													(W/kg)			(W/kg)	
2412	1	802.11b	DSSS	22	14.0	13.32	0.14	5 mm	1	00413	1	back	98.9	0.176	1.169	1.011	0.208	
2412	1	802.11b	DSSS	22	13.0	12.45	0.00	0 mm	1	00413	1	back	98.9	0.631	1.135	1.011	0.724	
2437	6	802.11b	DSSS	22	13.0	12.14	-0.02	0 mm	1	00421	1	back	98.9	0.682	1.219	1.011	0.841	
2462	11	802.11b	DSSS	22	13.0	12.44	-0.14	0 mm	1	00421	1	back	98.9	0.770	1.138	1.011	0.886	
2412	1	802.11b	DSSS	22	14.0	13.32	0.15	0 mm	1	00413	1	top	98.9	0.006	1.169	1.011	0.007	
2412	1	802.11b	DSSS	22	14.0	13.32	-0.01	0 mm	1	00413	1	bottom	98.9	0.310	1.169	1.011	0.366	
2412	1	802.11b	DSSS	22	14.0	13.32	0.04	0 mm	1	00413	1	right	98.9	0.052	1.169	1.011	0.061	
2412	1	802.11b	DSSS	22	14.0	13.32	0.03	5 mm	2	00413	1	back	99.0	0.428	1.169	1.010	0.505	
2412	1	802.11b	DSSS	22	13.0	11.60	0.09	0 mm	2	00413	1	back	99.0	0.658	1.380	1.010	0.917	
2437	6	802.11b	DSSS	22	13.0	12.48	-0.04	0 mm	2	00413	1	back	99.0	0.924	1.127	1.010	1.052	A10
2462	11	802.11b	DSSS	22	13.0	11.87	-0.03	0 mm	2	00413	1	back	99.0	0.661	1.297	1.010	0.866	
2412	1	802.11b	DSSS	22	14.0	13.32	0.11	0 mm	2	00413	1	top	99.0	0.001	1.169	1.010	0.001	
2412	1	802.11b	DSSS	22	14.0	13.32	0.11	0 mm	2	00413	1	bottom	99.0	0.129	1.169	1.010	0.152	
2412	1	802.11b	DSSS	22	14.0	13.32	0.16	0 mm	2	00413	1	left	99.0	0.007	1.169	1.010	0.008	
2437	6	802.11b	DSSS	22	13.0	12.48	-0.03	0 mm	2	00413	1	back	99.0	0.902	1.127	1.010	1.027	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body										
Spatial Peak								1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population								averaged over 1 gram										

Note: Blue entry indicates variability measurement.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 58 of 82

Table 10-9
5 GHz WLAN Body SAR

MEASUREMENT RESULTS																		
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													(W/kg)			(W/kg)	
5310	62	802.11n	OFDM	40	14.0	13.19	-0.17	5 mm	1	00413	13.5	back	94.2	0.370	1.205	1.062	0.473	
5290	58	802.11ac	OFDM	80	10.0	8.47	0.05	0 mm	1	00413	29.3	back	87.3	0.636	1.422	1.145	1.036	
5310	62	802.11n	OFDM	40	14.0	13.19	0.00	0 mm	1	00413	13.5	top	94.2	0.000	1.205	1.062	0.000	
5310	62	802.11n	OFDM	40	14.0	13.19	0.07	0 mm	1	00413	13.5	bottom	94.2	0.387	1.205	1.062	0.495	
5310	62	802.11n	OFDM	40	14.0	13.19	0.01	0 mm	1	00413	13.5	right	94.2	0.033	1.205	1.062	0.042	
5310	62	802.11n	OFDM	40	14.0	13.12	-0.15	5 mm	2	00413	13.5	back	94.4	0.149	1.225	1.059	0.193	
5290	58	802.11ac	OFDM	80	10.0	9.47	0.18	0 mm	2	00413	29.3	back	89.2	0.388	1.130	1.121	0.491	
5310	62	802.11n	OFDM	40	14.0	13.12	0.00	0 mm	2	00413	13.5	top	94.4	0.000	1.225	1.059	0.000	
5310	62	802.11n	OFDM	40	14.0	13.12	0.06	0 mm	2	00413	13.5	bottom	94.4	0.081	1.225	1.059	0.105	
5310	62	802.11n	OFDM	40	14.0	13.12	0.00	0 mm	2	00413	13.5	right	94.4	0.000	1.225	1.059	0.000	
5310	62	802.11n	OFDM	40	14.0	13.12	0.02	0 mm	2	00413	13.5	left	94.4	0.051	1.225	1.059	0.066	
5510	102	802.11n	OFDM	40	14.0	13.14	-0.19	5 mm	1	00413	13.5	back	94.2	0.346	1.219	1.062	0.448	
5530	106	802.11ac	OFDM	80	10.0	9.04	0.17	0 mm	1	00413	29.3	back	87.3	0.670	1.247	1.145	0.957	
5610	122	802.11ac	OFDM	80	10.0	9.16	0.18	0 mm	1	00413	29.3	back	87.3	0.712	1.213	1.145	0.989	
5510	102	802.11n	OFDM	40	14.0	13.14	-0.13	0 mm	1	00413	13.5	top	94.2	0.000	1.219	1.062	0.000	
5510	102	802.11n	OFDM	40	14.0	13.14	0.12	0 mm	1	00413	13.5	bottom	94.2	0.333	1.219	1.062	0.431	
5510	102	802.11n	OFDM	40	14.0	13.14	0.11	0 mm	1	00413	13.5	right	94.2	0.038	1.219	1.062	0.049	
5590	118	802.11n	OFDM	40	14.0	13.48	0.01	5 mm	2	00413	13.5	back	94.4	0.356	1.127	1.059	0.425	
5530	106	802.11ac	OFDM	80	10.0	9.17	-0.20	0 mm	2	00413	29.3	back	89.2	0.472	1.211	1.121	0.641	
5610	122	802.11ac	OFDM	80	10.0	9.13	-0.02	0 mm	2	00413	29.3	back	89.2	0.512	1.222	1.121	0.701	
5690	138	802.11ac	OFDM	80	10.0	8.78	-0.01	0 mm	2	00413	29.3	back	89.2	0.437	1.324	1.121	0.649	
5590	118	802.11n	OFDM	40	14.0	13.48	0.00	0 mm	2	00413	13.5	top	94.4	0.000	1.127	1.059	0.000	
5590	118	802.11n	OFDM	40	14.0	13.48	0.19	0 mm	2	00413	13.5	bottom	94.4	0.371	1.127	1.059	0.443	
5590	118	802.11n	OFDM	40	14.0	13.48	0.00	0 mm	2	00413	13.5	right	94.4	0.000	1.127	1.059	0.000	
5590	118	802.11n	OFDM	40	14.0	13.48	0.16	0 mm	2	00413	13.5	left	94.4	0.087	1.127	1.059	0.104	
5755	151	802.11n	OFDM	40	14.0	12.92	-0.20	5 mm	1	00413	13.5	back	94.2	0.267	1.282	1.062	0.364	
5775	155	802.11ac	OFDM	80	10.0	9.26	0.17	0 mm	1	00413	29.3	back	87.3	0.908	1.186	1.145	1.233	
5755	151	802.11n	OFDM	40	14.0	12.92	0.00	0 mm	1	00413	13.5	top	94.2	0.000	1.282	1.062	0.000	
5755	151	802.11n	OFDM	40	14.0	12.92	0.14	0 mm	1	00413	13.5	bottom	94.2	0.207	1.282	1.062	0.282	
5755	151	802.11n	OFDM	40	14.0	12.92	-0.17	0 mm	1	00413	13.5	right	94.2	0.014	1.282	1.062	0.019	
5795	159	802.11n	OFDM	40	14.0	13.42	0.11	5 mm	2	00413	13.5	back	94.4	0.216	1.143	1.059	0.261	
5775	155	802.11ac	OFDM	80	10.0	8.88	-0.12	0 mm	2	00413	29.3	back	89.2	0.394	1.294	1.121	0.572	
5795	159	802.11n	OFDM	40	14.0	13.42	0.00	0 mm	2	00413	13.5	top	94.4	0.000	1.143	1.059	0.000	
5795	159	802.11n	OFDM	40	14.0	13.42	0.14	0 mm	2	00413	13.5	bottom	94.4	0.232	1.143	1.059	0.281	
5795	159	802.11n	OFDM	40	14.0	13.42	0.00	0 mm	2	00413	13.5	right	94.4	0.000	1.143	1.059	0.000	
5795	159	802.11n	OFDM	40	14.0	13.42	0.13	0 mm	2	00413	13.5	left	94.4	0.042	1.143	1.059	0.051	
5775	155	802.11ac	OFDM	80	10.0	9.26	-0.13	0 mm	1	00413	29.3	back	87.3	1.010	1.186	1.145	1.372	A11
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body										
Spatial Peak								1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population								averaged over 1 gram										

Note: Blue entry indicates variability measurement.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 59 of 82	

**Table 10-10
DSS Body SAR**

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Cond Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)			(W/kg)	
2480	78	Bluetooth	FHSS	9.5	8.32	-0.01	0 mm	00421	1	back	77.3	0.209	1.312	1.294	0.355	A12
2480	78	Bluetooth	FHSS	9.5	8.32	-0.16	0 mm	00421	1	top	77.3	0.002	1.312	1.294	0.003	
2480	78	Bluetooth	FHSS	9.5	8.32	0.07	0 mm	00421	1	bottom	77.3	0.117	1.312	1.294	0.199	
2480	78	Bluetooth	FHSS	9.5	8.32	-0.19	0 mm	00421	1	right	77.3	0.026	1.312	1.294	0.044	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram									

10.2 SAR Test Notes

General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in FCC KDB Publication 616217 D04v01r02 and FCC KDB Publication 447498 D01v06.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
6. Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 12 for variability analysis.
7. FCC KDB Publication 616217 D04v01r02 Section 4.3, SAR tests are required for the back surface and edges of the tablet with the tablet touching the phantom. The SAR Exclusion Threshold in FCC KDB 447498 D01v06 was applied to determine SAR test exclusion for adjacent edge configurations.

CDMA Notes:

1. CDMA Body SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0 according to KDB 941225 D01v03r01 procedures for data devices. Wireless Router SAR tests for Subtype 2 of Rev.A and 1x RTT configurations were not required per the 3G SAR Test Reduction Policy in KDB Publication 941225 D01v03r01.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg for 1g evaluations then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 60 of 82	

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 7.6.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 and MCC=001 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
4. Per KDB Publication 941225 D05Av01r02, SAR for downlink only LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.

WLAN Notes:

1. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 7.7.5 for more information.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg for 1g evaluations. See Section 7.7.6 for more information.
3. Per KDB Publication 248227 D01v02r02, SAR for MIMO was evaluated by following the simultaneous SAR provisions from KDB Publication 447498 D01v06 by either evaluating the sum of the 1g SAR values of each antenna transmitting independently or making a SAR measurement with both antennas transmitting simultaneously. Please see Section 11 for complete analysis.
4. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg for 1g evaluations or all test channels were measured.
5. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.

Bluetooth Notes

1. Bluetooth SAR was measured with the device connected to a call box with hopping disabled with DH5 operation and Tx Tests test mode type. Per October 2016 TCB Workshop Notes, the reported SAR was scaled to the 100% transmission duty factor to determine compliance. See Section 8.5 for the time domain plot and calculation for the duty factor of the device.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 61 of 82

11 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

11.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

11.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1g SAR.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 62 of 82

11.3 Body SAR Simultaneous Transmission Analysis

Table 11-1
Simultaneous Transmission Scenario with 2.4 GHz WLAN

Simult Tx	Configuration	UMTS 850 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)			SPLSR		
		1	2	3	1+2	1+3	1+2+3	1+2	1+3	2+3
Body SAR	Back	0.935	0.886	1.052	See Note 1	See Note 1	See Note 1	0.01	0.01	0.03
	Top	1.233	0.007	0.001	1.240	1.234	1.241	N/A	N/A	N/A
	Bottom	0.400	0.366	0.152	0.766	0.552	0.918	N/A	N/A	N/A
	Right	0.255	0.061	0.400	0.316	0.655	0.716	N/A	N/A	N/A
	Left	0.141	0.400	0.008	0.541	0.149	0.549	N/A	N/A	N/A

Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)			SPLSR		
		1	2	3	1+2	1+3	1+2+3	1+2	1+3	2+3
Body SAR	Back	1.273	0.886	1.052	See Note 1	See Note 1	See Note 1	0.01	0.01	0.03
	Top	0.954	0.007	0.001	0.961	0.955	0.962	N/A	N/A	N/A
	Bottom	0.400	0.366	0.152	0.766	0.552	0.918	N/A	N/A	N/A
	Right	0.970	0.061	0.400	1.031	1.370	1.431	N/A	N/A	N/A
	Left	0.453	0.400	0.008	0.853	0.461	0.861	N/A	N/A	N/A

Simult Tx	Configuration	Cell. EVDO SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)			SPLSR		
		1	2	3	1+2	1+3	1+2+3	1+2	1+3	2+3
Body SAR	Back	0.738	0.886	1.052	See Note 1	See Note 1	See Note 1	0.01	0.01	0.03
	Top	1.397	0.007	0.001	1.404	1.398	1.405	N/A	N/A	N/A
	Bottom	0.400	0.366	0.152	0.766	0.552	0.918	N/A	N/A	N/A
	Right	0.234	0.061	0.400	0.295	0.634	0.695	N/A	N/A	N/A
	Left	0.130	0.400	0.008	0.530	0.138	0.538	N/A	N/A	N/A

Simult Tx	Configuration	PCS EVDO SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)			SPLSR		
		1	2	3	1+2	1+3	1+2+3	1+2	1+3	2+3
Body SAR	Back	1.028	0.886	1.052	See Note 1	See Note 1	See Note 1	0.01	0.01	0.03
	Top	0.994	0.007	0.001	1.001	0.995	1.002	N/A	N/A	N/A
	Bottom	0.400	0.366	0.152	0.766	0.552	0.918	N/A	N/A	N/A
	Right	1.118	0.061	0.400	1.179	1.518	1.579	N/A	N/A	N/A
	Left	0.595	0.400	0.008	0.995	0.603	1.003	N/A	N/A	N/A

Simult Tx	Configuration	LTE Band 12 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)			SPLSR		
		1	2	3	1+2	1+3	1+2+3	1+2	1+3	2+3
Body SAR	Back	0.633	0.886	1.052	1.519	See Note 1	See Note 1	0.01	0.01	0.03
	Top	0.541	0.007	0.001	0.548	0.542	0.549	N/A	N/A	N/A
	Bottom	0.400	0.366	0.152	0.766	0.552	0.918	N/A	N/A	N/A
	Right	0.156	0.061	0.400	0.217	0.556	0.617	N/A	N/A	N/A
	Left	0.113	0.400	0.008	0.513	0.121	0.521	N/A	N/A	N/A

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 63 of 82

Simult Tx	Configuration	LTE Band 13 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)			SPLSR		
		1	2	3	1+2	1+3	1+2+3	1+2	1+3	2+3
Body SAR	Back	0.790	0.886	1.052	See Note 1	See Note 1	See Note 1	0.01	0.01	0.03
	Top	0.705	0.007	0.001	0.712	0.706	0.713	N/A	N/A	N/A
	Bottom	0.400	0.366	0.152	0.766	0.552	0.918	N/A	N/A	N/A
	Right	0.236	0.061	0.400	0.297	0.636	0.697	N/A	N/A	N/A
	Left	0.110	0.400	0.008	0.510	0.118	0.518	N/A	N/A	N/A

Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)			SPLSR		
		1	2	3	1+2	1+3	1+2+3	1+2	1+3	2+3
Body SAR	Back	0.829	0.886	1.052	See Note 1	See Note 1	See Note 1	0.01	0.01	0.03
	Top	1.100	0.007	0.001	1.107	1.101	1.108	N/A	N/A	N/A
	Bottom	0.400	0.366	0.152	0.766	0.552	0.918	N/A	N/A	N/A
	Right	0.239	0.061	0.400	0.300	0.639	0.700	N/A	N/A	N/A
	Left	0.136	0.400	0.008	0.536	0.144	0.544	N/A	N/A	N/A

Simult Tx	Configuration	LTE Band 66 (AWS) SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)			SPLSR		
		1	2	3	1+2	1+3	1+2+3	1+2	1+3	2+3
Body SAR	Back	1.125	0.886	1.052	See Note 1	See Note 1	See Note 1	0.01	0.01	0.03
	Top	0.935	0.007	0.001	0.942	0.936	0.943	N/A	N/A	N/A
	Bottom	0.400	0.366	0.152	0.766	0.552	0.918	N/A	N/A	N/A
	Right	0.977	0.061	0.400	1.038	1.377	1.438	N/A	N/A	N/A
	Left	0.474	0.400	0.008	0.874	0.482	0.882	N/A	N/A	N/A

Simult Tx	Configuration	LTE Band 25 (PCS) SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)			SPLSR		
		1	2	3	1+2	1+3	1+2+3	1+2	1+3	2+3
Body SAR	Back	1.218	0.886	1.052	See Note 1	See Note 1	See Note 1	0.01	0.01	0.03
	Top	0.900	0.007	0.001	0.907	0.901	0.908	N/A	N/A	N/A
	Bottom	0.400	0.366	0.152	0.766	0.552	0.918	N/A	N/A	N/A
	Right	0.945	0.061	0.400	1.006	1.345	1.406	N/A	N/A	N/A
	Left	0.374	0.400	0.008	0.774	0.382	0.782	N/A	N/A	N/A

FCC ID: A3LSMT837R4			SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet			Page 64 of 82	

Table 11-2
Simultaneous Transmission Scenario with 5 GHz WLAN

Simult Tx	Configuration	UMTS 850 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)			SPLSR		
		1	2	3	1+2	1+3	1+2+3	1+2	1+3	2+3
Body SAR	Back	0.935	1.372	0.701	See Note 1	See Note 1	See Note 1	0.01	0.01	0.03
	Top	1.233	0.000	0.000	1.233	1.233	1.233	N/A	N/A	N/A
	Bottom	0.400	0.495	0.443	0.895	0.843	1.338	N/A	N/A	N/A
	Right	0.255	0.049	0.000	0.304	0.255	0.304	N/A	N/A	N/A
	Left	0.141	0.400	0.104	0.541	0.245	0.645	N/A	N/A	N/A

Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)			SPLSR		
		1	2	3	1+2	1+3	1+2+3	1+2	1+3	2+3
Body SAR	Back	1.273	1.372	0.701	See Note 1	See Note 1	See Note 1	0.02	0.01	0.03
	Top	0.954	0.000	0.000	0.954	0.954	0.954	N/A	N/A	N/A
	Bottom	0.400	0.495	0.443	0.895	0.843	1.338	N/A	N/A	N/A
	Right	0.970	0.049	0.000	1.019	0.970	1.019	N/A	N/A	N/A
	Left	0.453	0.400	0.104	0.853	0.557	0.957	N/A	N/A	N/A

Simult Tx	Configuration	Cell. EVDO SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)			SPLSR		
		1	2	3	1+2	1+3	1+2+3	1+2	1+3	2+3
Body SAR	Back	0.738	1.372	0.701	See Note 1	1.439	See Note 1	0.01	0.01	0.03
	Top	1.397	0.000	0.000	1.397	1.397	1.397	N/A	N/A	N/A
	Bottom	0.400	0.495	0.443	0.895	0.843	1.338	N/A	N/A	N/A
	Right	0.234	0.049	0.000	0.283	0.234	0.283	N/A	N/A	N/A
	Left	0.130	0.400	0.104	0.530	0.234	0.634	N/A	N/A	N/A

Simult Tx	Configuration	PCS EVDO SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)			SPLSR		
		1	2	3	1+2	1+3	1+2+3	1+2	1+3	2+3
Body SAR	Back	1.028	1.372	0.701	See Note 1	See Note 1	See Note 1	0.02	0.01	0.03
	Top	0.994	0.000	0.000	0.994	0.994	0.994	N/A	N/A	N/A
	Bottom	0.400	0.495	0.443	0.895	0.843	1.338	N/A	N/A	N/A
	Right	1.118	0.049	0.000	1.167	1.118	1.167	N/A	N/A	N/A
	Left	0.595	0.400	0.104	0.995	0.699	1.099	N/A	N/A	N/A

Simult Tx	Configuration	LTE Band 12 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)			SPLSR		
		1	2	3	1+2	1+3	1+2+3	1+2	1+3	2+3
Body SAR	Back	0.633	1.372	0.701	See Note 1	1.334	See Note 1	0.01	0.01	0.03
	Top	0.541	0.000	0.000	0.541	0.541	0.541	N/A	N/A	N/A
	Bottom	0.400	0.495	0.443	0.895	0.843	1.338	N/A	N/A	N/A
	Right	0.156	0.049	0.000	0.205	0.156	0.205	N/A	N/A	N/A
	Left	0.113	0.400	0.104	0.513	0.217	0.617	N/A	N/A	N/A

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 65 of 82

Simult Tx	Configuration	LTE Band 13 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)			SPLSR		
		1	2	3	1+2	1+3	1+2+3	1+2	1+3	2+3
Body SAR	Back	0.790	1.372	0.701	See Note 1	1.491	See Note 1	0.01	0.01	0.03
	Top	0.705	0.000	0.000	0.705	0.705	0.705	N/A	N/A	N/A
	Bottom	0.400	0.495	0.443	0.895	0.843	1.338	N/A	N/A	N/A
	Right	0.236	0.049	0.000	0.285	0.236	0.285	N/A	N/A	N/A
	Left	0.110	0.400	0.104	0.510	0.214	0.614	N/A	N/A	N/A

Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)			SPLSR		
		1	2	3	1+2	1+3	1+2+3	1+2	1+3	2+3
Body SAR	Back	0.829	1.372	0.701	See Note 1	1.530	See Note 1	0.01	0.01	0.03
	Top	1.100	0.000	0.000	1.100	1.100	1.100	N/A	N/A	N/A
	Bottom	0.400	0.495	0.443	0.895	0.843	1.338	N/A	N/A	N/A
	Right	0.239	0.049	0.000	0.288	0.239	0.288	N/A	N/A	N/A
	Left	0.136	0.400	0.104	0.536	0.240	0.640	N/A	N/A	N/A

Simult Tx	Configuration	LTE Band 66 (AWS) SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)			SPLSR		
		1	2	3	1+2	1+3	1+2+3	1+2	1+3	2+3
Body SAR	Back	1.125	1.372	0.701	See Note 1	See Note 1	See Note 1	0.02	0.01	0.03
	Top	0.935	0.000	0.000	0.935	0.935	0.935	N/A	N/A	N/A
	Bottom	0.400	0.495	0.443	0.895	0.843	1.338	N/A	N/A	N/A
	Right	0.977	0.049	0.000	1.026	0.977	1.026	N/A	N/A	N/A
	Left	0.474	0.400	0.104	0.874	0.578	0.978	N/A	N/A	N/A

Simult Tx	Configuration	LTE Band 25 (PCS) SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)			SPLSR		
		1	2	3	1+2	1+3	1+2+3	1+2	1+3	2+3
Body SAR	Back	1.218	1.372	0.701	See Note 1	See Note 1	See Note 1	0.02	0.01	0.03
	Top	0.900	0.000	0.000	0.900	0.900	0.900	N/A	N/A	N/A
	Bottom	0.400	0.495	0.443	0.895	0.843	1.338	N/A	N/A	N/A
	Right	0.945	0.049	0.000	0.994	0.945	0.994	N/A	N/A	N/A
	Left	0.374	0.400	0.104	0.774	0.478	0.878	N/A	N/A	N/A

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 66 of 82

Table 11-3

Simultaneous Transmission Scenario with 2.4 GHz WLAN Ant 1 and 5 GHz WLAN Ant 2

Simult Tx	Configuration	UMTS 850 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	SPLSR		
		1	2	3	1+2+3	1+2	1+3	2+3
Body SAR	Back	0.935	0.886	0.701	See Note 1	0.01	0.01	0.02
	Top	1.233	0.007	0.000	1.240	N/A	N/A	N/A
	Bottom	0.400	0.366	0.443	1.209	N/A	N/A	N/A
	Right	0.255	0.061	0.000	0.316	N/A	N/A	N/A
	Left	0.141	0.400	0.104	0.645	N/A	N/A	N/A

Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	SPLSR		
		1	2	3	1+2+3	1+2	1+3	2+3
Body SAR	Back	1.273	0.886	0.701	See Note 1	0.01	0.01	0.02
	Top	0.954	0.007	0.000	0.961	N/A	N/A	N/A
	Bottom	0.400	0.366	0.443	1.209	N/A	N/A	N/A
	Right	0.970	0.061	0.000	1.031	N/A	N/A	N/A
	Left	0.453	0.400	0.104	0.957	N/A	N/A	N/A

Simult Tx	Configuration	Cell. EVDO SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	SPLSR		
		1	2	3	1+2+3	1+2	1+3	2+3
Body SAR	Back	0.738	0.886	0.701	See Note 1	0.01	0.01	0.02
	Top	1.397	0.007	0.000	1.404	N/A	N/A	N/A
	Bottom	0.400	0.366	0.443	1.209	N/A	N/A	N/A
	Right	0.234	0.061	0.000	0.295	N/A	N/A	N/A
	Left	0.130	0.400	0.104	0.634	N/A	N/A	N/A

Simult Tx	Configuration	PCS EVDO SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	SPLSR		
		1	2	3	1+2+3	1+2	1+3	2+3
Body SAR	Back	1.028	0.886	0.701	See Note 1	0.01	0.01	0.02
	Top	0.994	0.007	0.000	1.001	N/A	N/A	N/A
	Bottom	0.400	0.366	0.443	1.209	N/A	N/A	N/A
	Right	1.118	0.061	0.000	1.179	N/A	N/A	N/A
	Left	0.595	0.400	0.104	1.099	N/A	N/A	N/A

Simult Tx	Configuration	LTE Band 12 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	SPLSR		
		1	2	3	1+2+3	1+2	1+3	2+3
Body SAR	Back	0.633	0.886	0.701	See Note 1	0.01	0.01	0.02
	Top	0.541	0.007	0.000	0.548	N/A	N/A	N/A
	Bottom	0.400	0.366	0.443	1.209	N/A	N/A	N/A
	Right	0.156	0.061	0.000	0.217	N/A	N/A	N/A
	Left	0.113	0.400	0.104	0.617	N/A	N/A	N/A

FCC ID: A3LSMT837R4			SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet			Page 67 of 82

Simult Tx	Configuration	LTE Band 13 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	SPLSR		
		1	2	3	1+2+3	1+2	1+3	2+3
Body SAR	Back	0.790	0.886	0.701	See Note 1	0.01	0.01	0.02
	Top	0.705	0.007	0.000	0.712	N/A	N/A	N/A
	Bottom	0.400	0.366	0.443	1.209	N/A	N/A	N/A
	Right	0.236	0.061	0.000	0.297	N/A	N/A	N/A
	Left	0.110	0.400	0.104	0.614	N/A	N/A	N/A

Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	SPLSR		
		1	2	3	1+2+3	1+2	1+3	2+3
Body SAR	Back	0.829	0.886	0.701	See Note 1	0.01	0.01	0.02
	Top	1.100	0.007	0.000	1.107	N/A	N/A	N/A
	Bottom	0.400	0.366	0.443	1.209	N/A	N/A	N/A
	Right	0.239	0.061	0.000	0.300	N/A	N/A	N/A
	Left	0.136	0.400	0.104	0.640	N/A	N/A	N/A

Simult Tx	Configuration	LTE Band 66 (AWS) SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	SPLSR		
		1	2	3	1+2+3	1+2	1+3	2+3
Body SAR	Back	1.125	0.886	0.701	See Note 1	0.01	0.01	0.02
	Top	0.935	0.007	0.000	0.942	N/A	N/A	N/A
	Bottom	0.400	0.366	0.443	1.209	N/A	N/A	N/A
	Right	0.977	0.061	0.000	1.038	N/A	N/A	N/A
	Left	0.474	0.400	0.104	0.978	N/A	N/A	N/A

Simult Tx	Configuration	LTE Band 25 (PCS) SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	SPLSR		
		1	2	3	1+2+3	1+2	1+3	2+3
Body SAR	Back	1.218	0.886	0.701	See Note 1	0.01	0.01	0.02
	Top	0.900	0.007	0.000	0.907	N/A	N/A	N/A
	Bottom	0.400	0.366	0.443	1.209	N/A	N/A	N/A
	Right	0.945	0.061	0.000	1.006	N/A	N/A	N/A
	Left	0.374	0.400	0.104	0.878	N/A	N/A	N/A

FCC ID: A3LSMT837R4	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 68 of 82

Table 11-4
Simultaneous Transmission Scenario with Bluetooth

Simult Tx	Configuration	UMTS 850 SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body SAR	Back	0.935	0.355	1.290
	Top	1.233	0.003	1.236
	Bottom	0.400	0.199	0.599
	Right	0.255	0.044	0.299
	Left	0.141	0.400	0.541

Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)	SPLSR
		1	2	1+2	1+2
Body SAR	Back	1.273	0.355	See Note 1	0.01
	Top	0.954	0.003	0.957	N/A
	Bottom	0.400	0.199	0.599	N/A
	Right	0.970	0.044	1.014	N/A
	Left	0.453	0.400	0.853	N/A

Simult Tx	Configuration	Cell. EVDO SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body SAR	Back	0.738	0.355	1.093
	Top	1.397	0.003	1.400
	Bottom	0.400	0.199	0.599
	Right	0.234	0.044	0.278
	Left	0.130	0.400	0.530

Simult Tx	Configuration	PCS EVDO SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body SAR	Back	1.028	0.355	1.383
	Top	0.994	0.003	0.997
	Bottom	0.400	0.199	0.599
	Right	1.118	0.044	1.162
	Left	0.595	0.400	0.995

Simult Tx	Configuration	LTE Band 12 SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body SAR	Back	0.633	0.355	0.988
	Top	0.541	0.003	0.544
	Bottom	0.400	0.199	0.599
	Right	0.156	0.044	0.200
	Left	0.113	0.400	0.513

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 69 of 82

Simult Tx	Configuration	LTE Band 13 SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body SAR	Back	0.790	0.355	1.145
	Top	0.705	0.003	0.708
	Bottom	0.400	0.199	0.599
	Right	0.236	0.044	0.280
	Left	0.110	0.400	0.510

Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body SAR	Back	0.829	0.355	1.184
	Top	1.100	0.003	1.103
	Bottom	0.400	0.199	0.599
	Right	0.239	0.044	0.283
	Left	0.136	0.400	0.536

Simult Tx	Configuration	LTE Band 66 (AWS) SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body SAR	Back	1.125	0.355	1.480
	Top	0.935	0.003	0.938
	Bottom	0.400	0.199	0.599
	Right	0.977	0.044	1.021
	Left	0.474	0.400	0.874

Simult Tx	Configuration	LTE Band 25 (PCS) SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body SAR	Back	1.218	0.355	1.573
	Top	0.900	0.003	0.903
	Bottom	0.400	0.199	0.599
	Right	0.945	0.044	0.989
	Left	0.374	0.400	0.774

Notes:

1. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.04 per FCC KDB 447498 D01v06. See Section 11.4 for detailed SPLS ratio analysis.
2. For SAR summation, the highest reported SAR across all test distances was used as the most conservative evaluation for simultaneous transmission analysis for each device edge.
3. When the antenna separation distance was > 50 mm, an estimated SAR of 0.4 W/kg was used to determine the simultaneous transmission SAR exclusion for test positions excluded per FCC KDB Publication 447498 D01v06.

FCC ID: A3LSMT837R4	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 70 of 82

11.4 SPLSR Evaluation and Analysis

Per FCC KDB Publication 447498 D01v06, when the sum of the standalone transmitters is more than 1.6 W/kg for 1g, the SAR sum to peak locations can be analyzed to determine SAR distribution overlaps. When the SAR peak to location ratio (shown below) for each pair of antennas is ≤ 0.04 for 1g, simultaneous SAR evaluation is not required. The distance between the transmitters was calculated using the following formula.

$$\text{Distance}_{\text{Tx1} - \text{Tx2}} = R_i = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2}$$

$$\text{SPLS Ratio} = \frac{(SAR_1 + SAR_2)^{1.5}}{R_i}$$

11.4.1 Back Side SPLSR Evaluation and Analysis

Table 11-5
Peak SAR Locations for Body Back Side

Mode/Band	x (mm)	y (mm)
2.4 GHz WLAN Ant 1	-66.80	-110.80
2.4 GHz WLAN Ant 2	31.80	-116.80
5 GHz WLAN Ant 1	-67.00	-115.00
5 GHz WLAN Ant 2	35.00	-118.00
Bluetooth	-66.80	-110.80
UMTS 850	-23.00	125.50
UMTS 1900	-38.00	118.00
Cell. EVDO	-29.00	125.50
PCS EVDO	-38.00	116.50
LTE Band 12	-24.50	128.50
LTE Band 13	-24.50	127.00
LTE Band 5 (Cell)	-23.00	125.50
LTE Band 66 (AWS)	-36.50	113.50
LTE Band 25 (PCS)	-36.50	113.50


FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 71 of 82

Table 11-6
Back Side SAR to Peak Location Separation Ratio Calculations

Antenna Pair		Standalone SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio	Plot Number
Ant "a"	Ant "b"	a	b	a+b	D _{a-b}	(a+b) ^{1.5} /D _{a-b}	
2.4 GHz WLAN Ant 1	2.4 GHz WLAN Ant 2	0.886	1.052	1.938	98.78	0.03	1
5 GHz WLAN Ant 1	5 GHz WLAN Ant 2	1.372	0.701	2.073	102.04	0.03	2
2.4 GHz WLAN Ant 1	5 GHz WLAN Ant 2	0.886	0.701	1.587	102.05	0.02	3
2.4 GHz WLAN Ant 1	UMTS 850	0.886	0.935	1.821	240.33	0.01	4, 6
2.4 GHz WLAN Ant 2	UMTS 850	1.052	0.935	1.987	248.42	0.01	4
5 GHz WLAN Ant 1	UMTS 850	1.372	0.935	2.307	244.49	0.01	5
5 GHz WLAN Ant 2	UMTS 850	0.701	0.935	1.636	250.31	0.01	5, 6
2.4 GHz WLAN Ant 1	UMTS 1900	0.886	1.273	2.159	230.61	0.01	7, 9
2.4 GHz WLAN Ant 2	UMTS 1900	1.052	1.273	2.325	244.96	0.01	7
5 GHz WLAN Ant 1	UMTS 1900	1.372	1.273	2.645	234.80	0.02	8
5 GHz WLAN Ant 2	UMTS 1900	0.701	1.273	1.974	247.03	0.01	8, 9
2.4 GHz WLAN Ant 1	Cell. EVDO	0.886	0.738	1.624	239.30	0.01	10, 12
2.4 GHz WLAN Ant 2	Cell. EVDO	1.052	0.738	1.790	249.81	0.01	10
5 GHz WLAN Ant 1	Cell. EVDO	1.372	0.738	2.110	243.48	0.01	11
5 GHz WLAN Ant 2	Cell. EVDO	0.701	0.738	1.439	251.77	0.01	11, 12
2.4 GHz WLAN Ant 1	PCS EVDO	0.886	1.028	1.914	229.12	0.01	13, 15
2.4 GHz WLAN Ant 2	PCS EVDO	1.052	1.028	2.080	243.52	0.01	13
5 GHz WLAN Ant 1	PCS EVDO	1.372	1.028	2.400	233.31	0.02	14
5 GHz WLAN Ant 2	PCS EVDO	0.701	1.028	1.729	245.60	0.01	14, 15
2.4 GHz WLAN Ant 1	LTE Band 12	0.886	0.633	1.519	243.01	0.01	16, 18
2.4 GHz WLAN Ant 2	LTE Band 12	1.052	0.633	1.685	251.68	0.01	16
5 GHz WLAN Ant 1	LTE Band 12	1.372	0.633	2.005	247.18	0.01	17
5 GHz WLAN Ant 2	LTE Band 12	0.701	0.633	1.334	253.58	0.01	17, 18
2.4 GHz WLAN Ant 1	LTE Band 13	0.886	0.790	1.676	241.53	0.01	19, 21
2.4 GHz WLAN Ant 2	LTE Band 13	1.052	0.790	1.842	250.22	0.01	19
5 GHz WLAN Ant 1	LTE Band 13	1.372	0.790	2.162	245.70	0.01	20
5 GHz WLAN Ant 2	LTE Band 13	0.701	0.790	1.491	252.12	0.01	20, 21
2.4 GHz WLAN Ant 1	LTE Band 5 (Cell)	0.886	0.829	1.715	240.33	0.01	22, 24
2.4 GHz WLAN Ant 2	LTE Band 5 (Cell)	1.052	0.829	1.881	248.42	0.01	22
5 GHz WLAN Ant 1	LTE Band 5 (Cell)	1.372	0.829	2.201	244.49	0.01	23
5 GHz WLAN Ant 2	LTE Band 5 (Cell)	0.701	0.829	1.530	250.31	0.01	23, 24
2.4 GHz WLAN Ant 1	LTE Band 66 (AWS)	0.886	1.125	2.011	226.34	0.01	25, 27
2.4 GHz WLAN Ant 2	LTE Band 66 (AWS)	1.052	1.125	2.177	240.21	0.01	25
5 GHz WLAN Ant 1	LTE Band 66 (AWS)	1.372	1.125	2.497	230.53	0.02	26
5 GHz WLAN Ant 2	LTE Band 66 (AWS)	0.701	1.125	1.826	242.29	0.01	26, 27
2.4 GHz WLAN Ant 1	LTE Band 25 (PCS)	0.886	1.218	2.104	226.34	0.01	28, 30
2.4 GHz WLAN Ant 2	LTE Band 25 (PCS)	1.052	1.218	2.270	240.21	0.01	28
5 GHz WLAN Ant 1	LTE Band 25 (PCS)	1.372	1.218	2.590	230.53	0.02	29
5 GHz WLAN Ant 2	LTE Band 25 (PCS)	0.701	1.218	1.919	242.29	0.01	29, 30
Bluetooth	UMTS 1900	0.355	1.273	1.628	230.61	0.01	31

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 72 of 82	

Table 11-7
Back Side SAR to Peak Location Separation Ratio Plots



FCC ID: A3LSMT837R4



SAR EVALUATION REPORT



Approved by:
 Quality Manager

Document S/N:

Test Dates:


DUT Type:

Page 73 of 82


1M1806180125-01-R1.A3L

06/25/18 - 07/10/18


Portable Tablet



FCC ID: A3LSMT837R4	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 74 of 82



FCC ID: A3LSMT837R4	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 75 of 82



11.5 Simultaneous Transmission Conclusion

The above numerical summed SAR results and SPLSR analysis are sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528- 2013 Section 6.3.4.1.

FCC ID: A3LSMT837R4	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 76 of 82

12 SAR MEASUREMENT VARIABILITY

12.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg
- 5) When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

Table 12-1
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS														
Band	FREQUENCY		Mode	Service	Data Rate (Mbps)	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.						(W/kg)	(W/kg)		(W/kg)			
835	824.70	1013	Cell. CDMA	EVDO Rev. 0	N/A	top	16 mm	1.240	1.200	1.03	N/A	N/A	N/A	N/A
1750	1770.00	132572	LTE Band 66 (AWS), 20 MHz Bandwidth	QPSK, 1 RB, 0 RB Offset	N/A	back	0 mm	0.936	1.000	1.07	N/A	N/A	N/A	N/A
1900	1907.60	9538	UMTS 1900	RMC	N/A	back	0 mm	1.140	1.140	1.00	N/A	N/A	N/A	N/A
2450	2437.00	6	802.11b, 22 MHz Bandwidth	DSSS , ANT 2	1	back	0 mm	0.924	0.902	1.02	N/A	N/A	N/A	N/A
5750	5775.00	155	802.11ac, 80 MHz Bandwidth	OFDM , ANT 1	29.3	back	0 mm	0.908	1.010	1.11	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT							Body							
Spatial Peak							1.6 W/kg (mW/g)							
Uncontrolled Exposure/General Population							averaged over 1 gram							

12.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for 1g and < 3.75 W/kg for 10g for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 77 of 82

13 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8594A	(9kHz-2.9GHz) Spectrum Analyzer	N/A	N/A	N/A	3051A00187
Agilent	8753ES	S-Parameter Vector Network Analyzer	8/17/2017	Annual	8/17/2018	MY40003841
Agilent	8753ES	S-Parameter Network Analyzer	2/8/2018	Annual	2/8/2019	US39170122
Agilent	E4432B	ESG-D Series Signal Generator	4/19/2018	Annual	4/19/2019	US40053896
Agilent	E4438C	ESG Vector Signal Generator	3/24/2017	Biennial	3/24/2019	MY42082385
Agilent	E4438C	ESG Vector Signal Generator	3/23/2017	Biennial	3/23/2019	MY42082659
Agilent	E5515C	8960 Series 10 Wireless Communications Test Set	11/15/2017	Annual	11/15/2018	GB42230325
Agilent	E5515C	Wireless Communications Test Set	5/22/2018	Biennial	5/22/2020	GB43193563
Agilent	E5515C	Wireless Communications Test Set	2/7/2018	Triennial	2/7/2021	GB43304447
Agilent	N4010A	Wireless Connectivity Test Set	N/A	N/A	N/A	GB44450273
Agilent	N5182A	MXG Vector Signal Generator	11/1/2017	Annual	11/1/2018	MY47420603
Agilent	N9020A	MXA Signal Analyzer	1/24/2018	Annual	1/24/2019	US46470561
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433971
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433972
Anritsu	MA24106A	USB Power Sensor	6/5/2018	Annual	6/5/2019	1231535
Anritsu	MA24106A	USB Power Sensor	6/5/2018	Annual	6/5/2019	1231538
Anritsu	MA2411B	Pulse Power Sensor	3/2/2018	Annual	3/2/2019	1207364
Anritsu	MA2411B	Pulse Power Sensor	3/2/2018	Annual	3/2/2019	1339018
Anritsu	ML2495A	Power Meter	10/22/2017	Annual	10/22/2018	941001
Anritsu	ML2495A	Power Meter	11/28/2017	Annual	11/28/2018	1039008
Anritsu	MT8820C	Radio Communication Analyzer	1/5/2018	Annual	1/5/2019	6201144418
Anritsu	MT8820C	Radio Communication Analyzer	3/20/2018	Annual	3/20/2019	6201144419
COMTech	AR85729-5	Solid State Amplifier	CBT	N/A	CBT	M155A00-009
Control Company	4040	Therm./ Clock/ Humidity Monitor	1/8/2018	Annual	1/8/2019	160473909
Control Company	4352	Ultra Long Stem Thermometer	1/8/2018	Annual	1/8/2019	160508097
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
Mini Circuits	PWR-4GHS	USB Power Sensor	1/22/2018	Annual	1/22/2019	11710030062
Mini Circuits	PWR-4GHS	USB Power Sensor	1/20/2018	Annual	1/20/2019	11710030063
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mitutoyo	CD-6-CSX	Digital Caliper	4/18/2018	Biennial	4/18/2020	13264165
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Pasternack	NC-100	Torque Wrench	4/18/2018	Annual	4/18/2019	1445
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE5011-1	Torque Wrench	7/19/2017	Biennial	7/19/2019	N/A
Rohde & Schwarz	CMW500	Radio Communication Tester	11/3/2017	Annual	11/3/2018	100976
Rohde & Schwarz	CMW500	Radio Communication Tester	5/21/2018	Annual	5/21/2019	101699
Rohde & Schwarz	CMW500	Radio Communication Tester	10/13/2017	Annual	10/13/2018	102060
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	7/20/2017	Annual	7/20/2018	132885
Rohde & Schwarz	CMW500	Radio Communication tester	7/14/2017	Annual	7/14/2018	140144
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	1/19/2018	Annual	1/19/2019	164948
Seekonk	NC-100	Torque Wrench (8" lb)	5/10/2018	Biennial	5/10/2020	21053
SPEAG	D750V3	750 MHz SAR Dipole	1/15/2018	Annual	1/15/2019	1003
SPEAG	D835V2	835 MHz SAR Dipole	1/15/2018	Annual	1/15/2019	4d132
SPEAG	D1750V2	1750 MHz SAR Dipole	7/14/2016	Biennial	7/14/2018	1150
SPEAG	D1900V2	1900 MHz SAR Dipole	2/7/2018	Annual	2/7/2019	5d148
SPEAG	D1900V2	1900 MHz SAR Dipole	4/12/2018	Annual	4/12/2019	5d141
SPEAG	D2450V2	2450 MHz SAR Dipole	2/7/2018	Annual	2/7/2019	882
SPEAG	D5GHzV2	5 GHz SAR Dipole	8/15/2017	Annual	8/15/2018	1237
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/15/2018	Annual	2/15/2019	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/9/2017	Annual	8/9/2018	1323
SPEAG	DAE4	Dasy Data Acquisition Electronics	11/9/2017	Annual	11/9/2018	1450
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/22/2018	Annual	5/22/2019	859
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/7/2018	Annual	3/7/2019	1368
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/11/2018	Annual	4/11/2019	1407
SPEAG	DAK-3.5	Dielectric Assessment Kit	9/12/2017	Annual	9/12/2018	1091
SPEAG	EX3DV4	SAR Probe	2/14/2018	Annual	2/14/2019	3914
SPEAG	ES3DV3	SAR Probe	8/14/2017	Annual	8/14/2018	3332
SPEAG	ES3DV3	SAR Probe	3/27/2018	Annual	3/27/2019	3347
SPEAG	EX3DV4	SAR Probe	5/22/2018	Annual	5/22/2019	7406
SPEAG	ES3DV3	SAR Probe	3/13/2018	Annual	3/13/2019	3319
SPEAG	EX3DV4	SAR Probe	4/18/2018	Annual	4/18/2019	7357

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 78 of 82

14 MEASUREMENT UNCERTAINTIES

a	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
Phantom & Tissue Parameters								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)	RSS					11.5	11.3	60
Expanded Uncertainty (95% CONFIDENCE LEVEL)	k=2					23.0	22.6	

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 79 of 82

15 CONCLUSION

15.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 80 of 82

16 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: A3LSMT837R4	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet	Page 81 of 82

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz), July 2016.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: A3LSMT837R4		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1806180125-01-R1.A3L	Test Dates: 06/25/18 - 07/10/18	DUT Type: Portable Tablet		Page 82 of 82

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT837R4; Type: Portable Tablet; Serial: 03144

Communication System: UID 0, UMTS; Frequency: 826.4 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 826.4 \text{ MHz}$; $\sigma = 0.977 \text{ S/m}$; $\epsilon_r = 54.006$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.6 cm

Test Date: 07-02-2018; Ambient Temp: 20.3°C; Tissue Temp: 20.3°C

Probe: EX3DV4 - SN3914; ConvF(9.57, 9.57, 9.57); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 850, Body SAR, Top Edge, Low.ch


Area Scan (10x13x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 33.75 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.46 W/kg

SAR(1 g) = 0.990 W/kg



0 dB = 1.30 W/kg = 1.14 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT837R4; Type: Portable Tablet; Serial: 01064

Communication System: UID 0, UMTS; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1907.6 \text{ MHz}$; $\sigma = 1.565 \text{ S/m}$; $\epsilon_r = 51.207$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-02-2018; Ambient Temp: 22.4°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN7406; ConvF(7.74, 7.74, 7.74); Calibrated: 5/22/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/22/2018

Phantom: Twin-SAM V4.0; Type: QD 000 P40 CC; Serial: 1167

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1900, Body SAR, Back Side, High.ch


Area Scan (15x11x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 29.62 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 2.93 W/kg

SAR(1 g) = 1.14 W/kg



0 dB = 2.30 W/kg = 3.62 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT837R4; Type: Portable Tablet; Serial: 03169

Communication System: UID 0, CDMA; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 824.7 \text{ MHz}$; $\sigma = 0.977 \text{ S/m}$; $\epsilon_r = 54.01$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.6 cm

Test Date: 07-02-2018; Ambient Temp: 20.3°C; Tissue Temp: 20.3°C

Probe: EX3DV4 - SN3914; ConvF(9.57, 9.57, 9.57); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: Cell. EVDO, Body SAR, Top Edge, Low.ch


Area Scan (10x14x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 36.74 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.85 W/kg

SAR(1 g) = 1.24 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT837R4; Type: Portable Tablet; Serial: 01064

Communication System: UID 0, CDMA; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1908.75 \text{ MHz}$; $\sigma = 1.585 \text{ S/m}$; $\epsilon_r = 51.166$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 06-25-2018; Ambient Temp: 21.1°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN7406; ConvF(7.74, 7.74, 7.74); Calibrated: 5/22/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/22/2018

Phantom: Twin-SAM V4.0; Type: QD 000 P40 CC; Serial: 1167

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: PCS EVDO, Body SAR, Back Side, High.ch


Area Scan (15x11x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.26 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 2.03 W/kg

SAR(1 g) = 0.877 W/kg



0 dB = 1.51 W/kg = 1.79 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT837R4; Type: Portable Tablet; Serial: 03144

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.971 \text{ S/m}$; $\epsilon_r = 53.795$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.6 cm

Test Date: 06-25-2018; Ambient Temp: 21.5°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN3914; ConvF(9.75, 9.75, 9.75); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 12, Body SAR, Back Side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (15x11x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.67 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.735 W/kg

SAR(1 g) = 0.476 W/kg



0 dB = 0.635 W/kg = -1.97 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT837R4; Type: Portable Tablet; Serial: 03144

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.998 \text{ S/m}$; $\epsilon_r = 53.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.6 cm

Test Date: 06-25-2018; Ambient Temp: 21.5°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN3914; ConvF(9.75, 9.75, 9.75); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 13, Body SAR, Back Side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (15x11x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.25 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.993 W/kg

SAR(1 g) = 0.648 W/kg



0 dB = 0.863 W/kg = -0.64 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT837R4; Type: Portable Tablet; Serial: 03144

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.98 \text{ S/m}$; $\epsilon_r = 53.98$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.6 cm

Test Date: 07-02-2018; Ambient Temp: 20.3°C; Tissue Temp: 20.3°C

Probe: EX3DV4 - SN3914; ConvF(9.57, 9.57, 9.57); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 5 (Cell.), Body SAR, Top Edge, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (10x13x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 31.44 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.39 W/kg

SAR(1 g) = 0.915 W/kg



0 dB = 1.23 W/kg = 0.90 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT837R4; Type: Portable Tablet; Serial: 02252

Communication System: UID 0, LTE Band 66 (AWS); Frequency: 1770 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1770 \text{ MHz}$; $\sigma = 1.509 \text{ S/m}$; $\epsilon_r = 51.981$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-10-2018; Ambient Temp: 22.0°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3347; ConvF(5.17, 5.17, 5.17); Calibrated: 3/27/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 11/9/2017

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 66 (AWS), Body SAR, Back side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (13x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 29.34 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 2.18 W/kg

SAR(1 g) = 1 W/kg



0 dB = 1.46 W/kg = 1.64 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT837R4; Type: Portable Tablet; Serial: 01064

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.581 \text{ S/m}$; $\epsilon_r = 51.176$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 06-25-2018; Ambient Temp: 21.1°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN7406; ConvF(7.74, 7.74, 7.74); Calibrated: 5/22/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/22/2018

Phantom: Twin-SAM V4.0; Type: QD 000 P40 CC; Serial: 1167

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 25 (PCS), Body SAR, Back Side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (15x11x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 28.55 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 2.68 W/kg

SAR(1 g) = 1.07 W/kg



0 dB = 2.11 W/kg = 3.24 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT837R4; Type: Portable Tablet; Serial: 00413

Communication System: UID 0, _IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2437 \text{ MHz}$; $\sigma = 2.01 \text{ S/m}$; $\epsilon_r = 50.599$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-02-2018; Ambient Temp: 22.2°C; Tissue Temp: 21.7°C

Probe: ES3DV3 - SN3319; ConvF(4.51, 4.51, 4.51); Calibrated: 3/13/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/7/2018

Phantom: LeftTwin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1375

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11b, 22 MHz Bandwidth,
Body SAR, Ch 6, 1 Mbps, Back Side, Antenna 2**


Area Scan (12x20x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 26.01 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 3.45 W/kg

SAR(1 g) = 0.924 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT837R4; Type: Portable Tablet; Serial: 00413

Communication System: UID 0, 802.11ac 5.2-5.8 GHz Band; Frequency: 5775 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5775 \text{ MHz}$; $\sigma = 6.211 \text{ S/m}$; $\epsilon_r = 47.368$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-02-2018; Ambient Temp: 22.4°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7357; ConvF(4.21, 4.21, 4.21); Calibrated: 4/18/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2018

Phantom: SAM with CRP v5.0 Left; Type: QD000P40CD; Serial: 1687

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11ac, U-NII-3, 80 MHz Bandwidth,
Body SAR, Ch 155, 29.3 Mbps, Back Side, Antenna 1**


Area Scan (15x21x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 12.85 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 8.74 W/kg

SAR(1 g) = 1.01 W/kg



0 dB = 3.88 W/kg = 5.89 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMT837R4; Type: Portable Tablet; Serial: 00421

Communication System: UID 0, Bluetooth; Frequency: 2480 MHz; Duty Cycle: 1:1.294

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2480 \text{ MHz}$; $\sigma = 2.081 \text{ S/m}$; $\epsilon_r = 51.41$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-04-2018; Ambient Temp: 23.5°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3332; ConvF(4.55, 4.55, 4.55); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Left; Type: QD000P40CA; Serial: TP:82355

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: Bluetooth, Body SAR, Ch 78, 1 Mbps, Back Side


Area Scan (16x11x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 8.545 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.700 W/kg

SAR(1 g) = 0.209 W/kg



APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1003

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.987 \text{ S/m}$; $\epsilon_r = 53.645$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-25-2018; Ambient Temp: 21.5°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN3914; ConvF(9.75, 9.75, 9.75); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.80 W/kg

SAR(1 g) = 1.86 W/kg

Deviation(1 g) = 8.39%



0 dB = 2.48 W/kg = 3.94 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d132

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.98 \text{ S/m}$; $\epsilon_r = 53.985$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-02-2018; Ambient Temp: 20.3°C; Tissue Temp: 20.3°C

Probe: EX3DV4 - SN3914; ConvF(9.57, 9.57, 9.57); Calibrated: 2/14/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/15/2018

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 3.04 W/kg

SAR(1 g) = 2.01 W/kg

Deviation(1 g) = 3.50%



0 dB = 2.69 W/kg = 4.30 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1150

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.493 \text{ S/m}$; $\epsilon_r = 51.998$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-10-2018; Ambient Temp: 22.0°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3347; ConvF(5.17, 5.17, 5.17); Calibrated: 3/27/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1450; Calibrated: 11/9/2017

Phantom: Twin-SAM V5.0 Right; Type: QD 000 P40 CD; Serial: 1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.29 W/kg

SAR(1 g) = 3.61 W/kg

Deviation(1 g) = -1.10%



0 dB = 4.48 W/kg = 6.51 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d148

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.575 \text{ S/m}$; $\epsilon_r = 51.188$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-25-2018; Ambient Temp: 21.1°C; Tissue Temp: 21.2°C

Probe: EX3DV4 - SN7406; ConvF(7.74, 7.74, 7.74); Calibrated: 5/22/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/22/2018

Phantom: Twin-SAM V4.0; Type: QD 000 P40 CC; Serial: 1167

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x11x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 7.90 W/kg

SAR(1 g) = 4.19 W/kg

Deviation(1 g) = 5.81%



0 dB = 6.57 W/kg = 8.18 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d141

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.557 \text{ S/m}$; $\epsilon_r = 51.234$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-02-2018; Ambient Temp: 22.4°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN7406; ConvF(7.74, 7.74, 7.74); Calibrated: 5/22/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/22/2018

Phantom: Twin-SAM V4.0; Type: QD 000 P40 CC; Serial: 1167

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x11x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 7.72 W/kg

SAR(1 g) = 4.13 W/kg

Deviation(1 g) = 3.25%



0 dB = 6.45 W/kg = 8.10 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 882

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 2.025 \text{ S/m}$; $\epsilon_r = 50.558$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-02-2018; Ambient Temp: 22.2°C; Tissue Temp: 21.7°C

Probe: ES3DV3 - SN3319; ConvF(4.51, 4.51, 4.51); Calibrated: 3/13/2018;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/7/2018

Phantom: LeftTwin-SAM V5.0; Type: QD 000 P40 CD; Serial: 1375

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 10.6 W/kg

SAR(1 g) = 5.1 W/kg

Deviation(1 g) = 1.59%



0 dB = 6.78 W/kg = 8.31 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 882

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 2.038 \text{ S/m}$; $\epsilon_r = 51.523$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-04-2018; Ambient Temp: 23.5°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3332; ConvF(4.55, 4.55, 4.55); Calibrated: 8/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1323; Calibrated: 8/9/2017

Phantom: SAM Left; Type: QD000P40CA; Serial: TP:82355

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 10.1 W/kg

SAR(1 g) = 4.85 W/kg

Deviation(1 g) = -3.39%



0 dB = 6.37 W/kg = 8.04 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 5.494 \text{ S/m}$; $\epsilon_r = 48.258$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-02-2018; Ambient Temp: 22.4°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7357; ConvF(4.78, 4.78, 4.78); Calibrated: 4/18/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2018

Phantom: SAM with CRP v5.0 Left; Type: QD000P40CD; Serial: 1687

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 14.8 W/kg

SAR(1 g) = 3.6 W/kg

Deviation(1 g) = -6.37%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.956 \text{ S/m}$; $\epsilon_r = 47.625$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-02-2018; Ambient Temp: 22.4°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7357; ConvF(4.2, 4.2, 4.2); Calibrated: 4/18/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2018

Phantom: SAM with CRP v5.0 Left; Type: QD000P40CD; Serial: 1687

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 17.9 W/kg

SAR(1 g) = 4 W/kg

Deviation(1 g) = 1.91%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$; $\sigma = 6.173 \text{ S/m}$; $\epsilon_r = 47.424$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-02-2018; Ambient Temp: 22.4°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7357; ConvF(4.21, 4.21, 4.21); Calibrated: 4/18/2018;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2018

Phantom: SAM with CRP v5.0 Left; Type: QD000P40CD; Serial: 1687

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5750 MHz System Verification at 17.0 dBm (50 mW)

Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 17.8 W/kg

SAR(1 g) = 3.84 W/kg

Deviation(1 g) = -0.39%

