

EMC TEST REPORT


Project No.	LBE20190155	Issue No.	0
Applicant	Name of organization	Samsung Electronics Co., Ltd.	
	Address	(Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 443-742, Republic of Korea	
	Date of application	August 22, 2019	
EUT	Type of device	☐ All other Receivers subject to part15 ☒ Class B Personal Computers and peripherals ☒ Other Class B digital devices and peripherals ☐ FM Broadcast Receiver	
	Equipment authorization	☒ Certification ☐ Supplier's Declaration of Conformity	
	FCC ID	A3LSMT867U	
	Kind of product	Portable Device	
	Model No.	SM-T867U	
	Variant Model No.	Refer to clause 4.6	
	Manufacturer	1. SAMSUNG ELECTRONICS CO., LTD. 94-1, Imsu-dong, Gumi-si, Gyengsangbuk-do, 730-722, Republic of Korea 2. SAMSUNG ELECTRONICS HUIZHOU CO.,LTD. 516229, Chenjiang Town, HuiZhou City, Guangdong Province, China	
Applied Standards		47 CFR Part 15, Subpart B, Class B / ANSI C63.4-2014	
Test Period		August 22, 2019 ~ August 27, 2019	
Issue date		August 28, 2019	
Test result : Complied The equipment under test has found to be compliant with the applied standards. (Refer to the attached test result for more detail.)			
Tested by : Mi-Young Lee 		Reviewed by : Sung-Wook Choi 	
The test results in this report only apply to the tested sample. This report must not be reproduced, except in full, without written permission from Global CS center.			
Global CS Center of Samsung Electronics Co., Ltd. (Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea			

Table of contents

1. Report Information

1.1 Revision history	3
----------------------------	---

2. Summary of test results

2.1 Emission	3
--------------------	---

3. General Information

3.1 Test facility	3
-------------------------	---

4. Test Configuration

4.1 Test Peripherals	4
4.2 EUT operating mode	5
4.3 Details of Sampling	5
4.4 Used cable description	6
4.5 Test arrangement	7
4.6 EUT Description	11
4.7 EUT Frequencies	11
4.8 Test configuration and condition	11
4.9 Measurement uncertainty	12

5. Result of individual tests

5.1 Conducted disturbance	13
5.2 Radiated disturbance	20

1. Report Information

1.1 Revision history

No.	Date of Issue	Revised detailed information
Issue 0	August 28, 2019	There are no revisions and this version is basic test report.

2. Summary of test results

2.1 Emission

The EUT has been tested according to the following specifications:

Applied	Test type	Applied standard	Result
☒	Conducted Disturbance (Mains port)	47 CFR Part 15, Subpart B / ANSI C63.4-2014 (Class B)	Complied
☒	Radiated Disturbance		Complied

3. General Information

3.1 Test facility

The Global CS center is located on Samsung Electronics Co., Ltd. at (Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, Republic of Korea.

All testing are performed in Semi-anechoic chambers conforming to the site attenuation characteristics defined by ANSI C63.4, CISPR 32, CISPR 16-1-4 and Shielded rooms.

And all antennas are properly calibrated using ANSI C63.5:2017.

The Global CS center is operated as testing laboratory in accordance with the requirements of ISO/IEC 17025:2005.

4. Test Setup configuration

4.1 Test Peripherals

The cables used for these peripherals are either permanently attached by the peripheral manufacturer or coupled with an assigned cable as defined below.

The following is a listing of the EUT and peripherals utilized during the performance of EMC test:

Mark	Description	Model No.	Serial No.	Manufacturer / Trademark	FCC ID
A	Portable Device	SM-T867U	-	SAMSUNG	A3LSMT867U
B	Battery	EB-BT725ABU	-	SAMSUNG	-
C	Headset	GHSS028-K5	-	SAMSUNG	-
D	Data Cable	EP-DG970BBE	-	SAMSUNG	-
E	Micro SD Card	64GB	-	SAMSUNG	-
F	Laptop Computer	Latitude5580	1CHRYM2	Dell	DoC
			D3HRYM2	Dell	DoC
G	Laptop AC Adapter	LA65NM130	5D77	Dell	DoC
			5B3C	Dell	DoC
H	Mouse	AA-SM7PCPB	CN57BA5903634A DV8JK281082	SAMSUNG	DoC
			CNBA5903634AD V8J31O3050	SAMSUNG	DoC
I	OTG Gender	EE-UG970	-	SAMSUNG	DoC
J	Router	DIR-806A	RF0F1D5000688	D-Link	DoC
			RF0F1D8011504	D-Link	DoC
K	Travel Adapter	EP-TA200	R37M1D55M01SE3	SAMSUNG	-
L	DP Monitor	27UD88	711NTQD8H004	LG	DoC
M	DP Monitor AC Adapter	LCAP31	EH8NN629490055062	LG	DoC
N	DP Cable	JCA141	-	j5 create	DoC
O	Charging Dock	EE-D3200	R37M3KA26B1RT3	SAMSUNG	-
P	Keyboard	EF-DT860	-	SAMSUNG	-
Q	S-pen	CP-911B-00B	-	SAMSUNG	-

This tablet device does not contain the minimum number of ports required for personal computer testing per ANSI C63.4, but the EUT is attached to a computer through its only available port, which represents worst case emissions. All other aspects of C63.4 testing requirements were maintained.

4.2 EUT operating mode

To achieve compliance applied standard specification including JAB and JBP requirement, the following mode(s) were made during compliance testing:

4.2.1 Conducted Emission

No.	Operating mode
1	Camera (rear) + Charging (w/ TA) + Cellular receiver(LTE FDD B26 Center Frequency) + Keyboard (Pogo Pin)
2	Camera (front) + Charging (w/ TA) + Keyboard (Pogo Pin)
3	Charging Dock (w/ TA)
4	Video + Audio playback from internal memory data + EMR Touch Solution (S-Pen) + Wireless Charging (S-Pen) + Charging (w/TA)
5	USB Data Communication with PC (from external memory data)

4.2.2 Radiated Emission

No.	Operating mode
1	Camera (rear) + Charging (w/ TA) + Keyboard (Pogo Pin)
2	Camera (front) + Keyboard (Pogo Pin)
3	Charging Dock (w/ TA)
4	Video + Audio playback from internal memory data + EMR Touch Solution (S-Pen) + Wireless Charging (S-Pen) + Charging (w/TA)
5	Video + Audio playback from internal memory data + Display Out (w/ USB to HDMI converter or Direct DP Cable)
6	USB Data Communication with PC (from external memory data)

4.3 Details of Sampling

Customer selected, single unit.


4.4 Used cable description

The EUT is configured, installed, arranged and operated in a manner consistent with typical applications. Interface cables/loads/devices are connected to at least one of each type of interface port of the EUT, and where practical, each cable shall be terminated in a device typical of actual usage. The type(s) of interconnecting cables to be used and the interface port (of the EUT) to which these were connected:


No.	Connected cable	Length [m]	Shielded [Y/N]	Note
1	Data Cable	1.0	Yes	From EUT to Laptop Computer
				From EUT to Travel Adapter
2	Headset	1.2	No	For EUT
3	Power	1.8	N	For Laptop Computer to Laptop AC Adapter
4	Power	1.5	N	For Laptop AC Adapter
5	LAN	1.5	N	From Laptop Computer to Router
6	USB	0.8	N	From Laptop Computer to Router for DC Power
7	USB	1.8	N	From OTG Gender to Mouse
8	DP Cable	1.1	Y	From EUT to DP Monitor
9	Power	1.2	N	From DP Monitor to DP Monitor AC Adapter
10	Power	1.8	N	For DP Monitor AC Adapter

4.5 Test arrangement


4.5.1 Conducted Emission




[Mode 1 - 2]



[Mode 3]




[Mode 4]



[Mode 5]


4.5.2 Radiated Emission




[Mode 1]




[Mode 2]




[Mode 3]



[Mode 4]



[Mode 5]



[Mode 6]

4.6 EUT Description

The EUT is a tablet type Portable Device which can operate on WCDMA FDD1/2/4/5, LTE FDD1/2/3/4/5/7/8/12/13/20/25/26/28/66/71, LTE TDD41/46 bands and incorporates a Bluetooth, ANT+, Wi-Fi, Camera, GNSS, Display Port, S-pen, Wireless Charging(S-Pen), Pogo Pin, Audio and Video player.

4.6.1 The variant models

- SM-T867R4

4.7 EUT Frequencies

The highest frequencies (Generated and used)	Frequency [MHz]
Wi-Fi	5 825

4.8 Test configuration and condition

The system was configured for testing in a typical fashion that a customer would normally use. Cables were attached to each of the available I/O Ports. Where applicable, peripherals were attached to the I/O cables. All the external I/O ports are exercised, as well as internal and the external SD card, by writing and reading arbitrary data or charging with TA.

The EUT was investigated in three orientations and the worst case orientation is reported

RX mode testing was performed with the LTE FDD26 RX Test mode at center frequency. All licensed communication Cellular RX mode, WCDMA/LTE, test results are not significantly different.

The video and music were repetitively played connected to the earphone.

The video and music were played on monitor through Display Out function using direct DP Cable or DP converter.

The camera of the EUT was operated continuously.

The EUT was exercised with S-Pen wireless charging during the testing.

Power source for the EUT operating was supplied by CVCF made by the Pacific Corp.

- Test Voltage : AC 120 V, 60 Hz

4.9 Measurement uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus: (According to CISPR 16-4-2 and UKAS M3003)

4.9.1 Emission

Test type		Measurement uncertainty (C.L. 95 %, k = 2)
Conducted disturbance	AC Mains	2.83 dB
Radiated Disturbance (Below 1 GHz)	Horizontal	4.99 dB
	Vertical	4.90 dB
Radiated Disturbance (Above 1 GHz)	Horizontal	5.13 dB
	Vertical	5.12 dB

5. Results of individual test

5.1 Conducted disturbance

The EUT is connected to a LISN via travel adapter. If the EUT is connected to the Laptop Computer USB port, the Laptop AC adapter is connected to a LISN.

Both conducted lines are measured in Quasi-Peak and CISPR-Average mode, including the worst-case data points for each tested configuration. The EUT measured in accordance with the methods described in standards.

Limits for conducted disturbance at the mains ports of Class B ITE

Frequency range Limits [MHz]	Resolution Bandwidth [kHz]	Limits [dB(μV)]	
		Quasi-peak	Average
0,15 to 0,50	9	66 to 56	56 to 46
0,50 to 5	9	56	46
5 to 30	9	60	50

NOTE 1 The lower limit shall apply at the transition frequency.
NOTE 2 The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

5.1.1 Test instrumentation


EMC No.	Test Instrument	Model name	Manufacturer	Serial No.	Calibration	
					Date	Interval (Month)
E5I-127	Two-Line V-Network	ENV216	R&S	102061	2019-08-01	12
E5I-017	EMI Test Receiver	ESU8	R&S	100483	2019-01-16	12
E5I-171	LTE Communicator	CMW500	R&S	154667	2019-08-06	12
-	Test software	EMC32	R&S	Ver 9.26.01	-	-

5.1.2 Temperature and humidity condition

Test date	2019-08-23	Test engineer	Mi-Young Lee
Climate condition	Ambient temperature	(22.1 ~ 23.0) °C	Limit (15.0 to 35.0) °C
	Relative humidity	(48.0 ~ 48.8) % R.H.	Limit (25.0 to 75.0) % R.H.
	Atmospheric pressure	(100.9 ~ 101.0) kPa	Limit (86.0 to 106.0) kPa
Test place	Shield Room (SR8)		

5.1.3 Test results

☐ Operating Mode 1: AC Mains




Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:

Frequency (MHz)	QP (dBμV)	CAV (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.530	35.6	---	56.0	20.4	L1	10.1
0.535	---	27.5	46.0	18.5	N	10.2
2.110	35.1	---	56.0	20.9	N	9.9
2.121	---	28.3	46.0	17.7	N	9.9
3.539	43.0	---	56.0	13.0	N	10.0
3.563	---	33.8	46.0	12.2	N	10.0
4.130	45.1	---	56.0	10.9	N	10.0
4.166	---	36.0	46.0	10.0	N	10.0
8.943	40.6	---	60.0	19.4	N	10.2
9.013	---	32.3	50.0	17.7	N	10.2
13.241	44.6	---	60.0	15.4	L1	10.2
13.328	---	35.6	50.0	14.4	N	10.4

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
 Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)
 QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 2: AC Mains




Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:

Frequency (MHz)	QP (dBμV)	CAV (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.254	---	26.3	51.6	25.3	N	9.8
0.263	42.3	---	61.4	19.1	L1	9.8
0.425	---	28.8	47.4	18.6	N	10.2
0.434	39.5	---	57.2	17.7	N	10.2
0.677	40.5	---	56.0	15.5	L1	10.0
0.683	---	33.7	46.0	12.3	N	10.2
3.545	42.6	---	56.0	13.4	N	10.0
3.563	---	34.6	46.0	11.4	N	10.0
4.301	45.9	---	56.0	10.1	N	10.0
4.322	---	37.1	46.0	8.9	N	10.0
8.783	41.8	---	60.0	18.2	N	10.2
8.950	---	32.9	50.0	17.1	N	10.2
13.286	---	34.8	50.0	15.2	N	10.4
13.362	45.7	---	60.0	14.3	L1	10.2

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
 Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)
 QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 3: AC Mains




Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:

Frequency (MHz)	QP (dBμV)	CAV (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.166	50.2	---	65.2	15.0	N	10.2
0.168	---	34.9	55.1	20.2	N	10.3
0.335	---	29.3	49.3	20.0	N	10.1
0.337	41.2	---	59.3	18.1	N	10.1
3.455	37.3	---	56.0	18.7	N	10.0
3.543	---	25.8	46.0	20.2	N	10.0
4.720	---	29.6	46.0	16.4	N	10.0
4.855	41.4	---	56.0	14.6	L1	9.9
9.546	39.7	---	60.0	20.3	L1	10.0
9.713	---	28.2	50.0	21.8	N	10.2
13.569	36.9	---	60.0	23.1	L1	10.2
13.745	---	27.1	50.0	22.9	L1	10.2

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
 Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)
 QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 4: AC Mains




Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:

Frequency (MHz)	QP (dBμV)	CAV (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.530	35.4	---	56.0	20.6	L1	10.1
0.683	---	32.7	46.0	13.3	N	10.2
1.444	---	27.9	46.0	18.1	N	10.0
1.946	34.4	---	56.0	21.6	N	9.9
3.548	41.5	---	56.0	14.5	N	10.0
3.566	---	33.7	46.0	12.3	N	10.0
4.144	43.6	---	56.0	12.4	N	10.0
4.247	---	35.5	46.0	10.5	N	10.0
8.957	---	31.2	50.0	18.8	N	10.2
8.957	41.6	---	60.0	18.4	N	10.2
13.358	---	34.1	50.0	15.9	N	10.4
13.394	43.2	---	60.0	16.8	L1	10.2

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
 Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)
 QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

□ Operating Mode 5: AC Mains



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:

Frequency (MHz)	QP (dBμV)	CAV (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.166	54.4	---	65.2	10.8	N	10.2
0.173	---	40.4	54.8	14.4	L1	10.2
0.287	---	27.2	50.6	23.4	L1	9.8
0.287	39.1	---	60.6	21.5	N	10.0
0.452	37.5	---	56.8	19.3	L1	10.1
0.463	---	23.9	46.6	22.7	L1	10.1
3.566	34.3	---	56.0	21.7	L1	9.9
3.602	---	25.8	46.0	20.2	N	10.0
3.842	---	27.4	46.0	18.6	N	10.0
4.007	38.0	---	56.0	18.0	L1	9.9
9.809	---	30.8	50.0	19.2	L1	10.0
9.857	36.5	---	60.0	23.5	L1	10.0

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
 Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)
 QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

5.2 Radiated disturbance

The following data lists the significant emission frequencies, measured levels, correction factors (for antenna and cables), orientation of table, polarization and height of antenna, the corrected reading, the limit, and the amount of margin.

Peak measurements were made over the changeable frequency range 30 MHz to 1 GHz at a measurement distance of 10 m for the following antenna and turntable arrangements:

Antenna Height [cm]	Antenna Polarisation	Resolution Bandwidth [kHz]	Video Bandwidth [kHz]	Turntable position [degrees]
100 ~ 400	Horizontal, Vertical	120	300	Continuous

Measurements within 6 dB of the limit were then maximized by adjusting turntable position. Final measurements were made using quasi-peak detector.

Peak/CISPR-Average measurements were made over the changeable frequency range 1 GHz to 40 GHz or 5th harmonics of the highest frequency generated or used in the device or on which the device operate or tunes at a measurement distance of 3 m for the following antenna and turntable arrangements. The measurements above 1 GHz were performed with the bore-sighting antenna aimed at the EUT.

Antenna Height [cm]	Antenna Polarisation	Resolution Bandwidth [MHz]	Video Bandwidth [MHz]	Turntable position
100 ~ 400	Horizontal, Vertical	1	3	Continuous

Measurements within 6 dB of the limit were then maximized by adjusting turntable position. Final measurements were made using peak and CISPR-average detectors.

Limits for radiated disturbance of Class B ITE at a measuring distance of 3 m and 10 m

Frequency range Limits [MHz]	Field Strength		
	3 m [$\mu\text{V/m}$]	3 m [dB($\mu\text{V/m}$)]	10 m [dB($\mu\text{V/m}$)]
30 to 88	100	40.0	29.5
88 to 216	150	43.5	33.0
216 to 960	200	46.0	35.5
Above 960	500	54.0	43.5

Note) Distance correction formula from $D_1(3\text{m})$ to $D_2(10\text{m})$

: Limit at D_2 = Limit at D_1 + $20\text{Log}(D_1 / D_2)$

Results checked manually; and points close to the limit line were re-measured.

5.2.1 Test instrumentation

EMC No.	Test Instrument	Model name	Manufacturer	Serial No.	Calibration	
					Date	Interval (Month)
E5I-021	EMI Test Receiver	ESU40	R&S	100376	2019-01-30	12
E5I-016	EMI Test Receiver	ESU8	R&S	100482	2019-05-29	12
E5I-149	Horn Antenna	HF907	R&S	102525	2018-06-15	24
E5I-039	Signal Conditioning Unit	SCU-18	R&S	10211	2019-01-23	12
E5I-037	Wide Band Horn Antenna	WBH 18-40K	R&S	11201	2019-01-31	24
E5I-042	Signal Conditioning Unit	SCU-40A	R&S	10004	2018-09-05	12
E5I-120	Bi-Log Antenna	CBL6112D	TESEQ	36997	2018-04-23	24
E5I-072	Bi-Log Antenna	CBL6112D	TESEQ	36009	2018-04-23	24
E5I-073	Preamplifier	310N	SONOMA	332016	2019-05-09	12
E5I-074	Preamplifier	310N	SONOMA	332017	2019-05-09	12
-	Test software	EP7RE	TOYO	Ver 5.8.2	-	-
-	Test software	EMC32	R&S	Ver 9.25.00	-	-


5.2.2 Temperature and humidity condition

Test date	2019-08-26 ~ 2019-08-27	Test engineer	Mi-Young Lee
Climate condition	Ambient temperature	(22.8 ~ 24.2) °C	Limit (15.0 to 35.0) °C
	Relative humidity	(48.9 ~ 51.1) % R.H.	Limit (25.0 to 75.0) % R.H.
	Atmospheric pressure	(101.2 ~ 101.6) kPa	Limit (86.0 to 106.0) kPa
Test place	Semi-Anechoic Chamber (SAC4)		

5.2.3 Test results

☐ Operating Mode 1

- Frequencies below 1 GHz



Note1) Receiving antenna polarization : Horizontal, Vertical


Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz



Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions

Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters


Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

☐ Operating Mode 2

- Frequencies below 1 GHz



Note1) Receiving antenna polarization : Horizontal, Vertical


Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz



Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions

Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters


Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

☐ Operating Mode 3

- Frequencies below 1 GHz



Note1) Receiving antenna polarization : Horizontal, Vertical


Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz



Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions


Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

☐ Operating Mode 4**- Frequencies below 1 GHz**

Note1) Receiving antenna polarization : Horizontal, Vertical


Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz



Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions

Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters


Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

☐ Operating Mode 5

- Frequencies below 1 GHz




Note1) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz

Frequency (MHz)	PK (dBμV/m)	CAV (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1 171.200	48.3	---	74.0	25.7	157.0	H	124.0	6.6
1 174.800	---	37.8	54.0	16.2	157.0	H	128.0	6.6
5 400.000	48.7	---	74.0	25.3	133.0	H	134.0	6.5
5 400.000	---	47.0	54.0	7.0	109.0	H	134.0	6.5
17 982.500	---	45.3	54.0	8.7	116.0	H	106.0	35.0
17 993.500	49.3	---	74.0	24.7	105.0	V	186.0	35.2

Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions


Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

☐ Operating Mode 6**- Frequencies below 1 GHz**


Note1) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 10 m, Antenna Height : 1 to 4 meters

Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)

Margin (QP) = Limit - Level (QP)

QP = Quasi-Peak, c.f = Correction Factor

- Frequencies above 1 GHz

Frequency (MHz)	PK (dBμV/m)	CAV (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1 594.800	41.9	---	74.0	32.1	176.0	V	77.0	9.8
1 722.800	---	34.4	54.0	19.6	183.0	H	179.0	10.8
1 860.400	43.1	---	74.0	30.9	246.0	V	150.0	11.7
1 862.800	---	30.4	54.0	23.6	246.0	V	0.0	11.7
2 123.200	54.3	---	74.0	19.7	179.0	V	16.0	12.9
2 128.800	---	39.7	54.0	14.3	189.0	V	16.0	12.9
2 996.400	45.3	---	74.0	28.7	111.0	V	92.0	16.7
3 000.000	---	32.4	54.0	21.6	117.0	V	128.0	16.8
3 450.000	44.5	---	74.0	29.5	341.0	V	111.0	2.0
3 453.000	---	28.6	54.0	25.4	348.0	V	129.0	2.0
17 994.000	---	43.8	54.0	10.2	222.0	H	99.0	35.2
17 999.500	48.9	---	74.0	25.1	240.0	H	325.0	35.3

Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions

Note 2) Receiving antenna polarization : Horizontal, Vertical

Test Distance : 3 m, Antenna Height : 1 to 4 meters

Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)

Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)

PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor