

# TEST REPORT

of

FCC Part 15 Subpart C §15.247

FCC ID: A3LSMT875

1. Equipment Under Test : Portable Tablet
2. Model Name : SM-T875
3. Variant Model Name(s) : -
4. Applicant : Samsung Electronics Co., Ltd.
5. Date of Receipt : 2020.06.04
6. Date of Test(s) : 2020.06.05 ~ 2020.07.09
7. Date of Issue : 2020.07.20

In the configuration tested, the EUT complied with the standards specified above. This test report does not assure KOLAS accreditation.

- 1) The results of this test report are effective only to the items tested.
- 2) The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as receive

Tested by:



Jinhyoung Cho

Technical Manager:



Jungmin Yang

**SGS Korea Co., Ltd. Gunpo Laboratory**

## **Table of Contents**

|                                                                                  | Page |
|----------------------------------------------------------------------------------|------|
| 1. General Information -----                                                     | 3    |
| 2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission ----- | 10   |
| 3. 20 dB Bandwidth -----                                                         | 44   |
| 4. Maximum Peak Conducted Output Power -----                                     | 52   |
| 5. Carrier Frequency Separation -----                                            | 54   |
| 6. Number of Hopping Frequencies -----                                           | 58   |
| 7. Time of Occupancy(Dwell Time) -----                                           | 64   |
| 8. AC Power Line Conducted Emission -----                                        | 84   |
| 9. Antenna Requirement -----                                                     | 88   |

## 1. General Information

### 1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Phone No. : +82 31 688 0901

Fax No. : +82 31 688 0921

### 1.2. Details of Applicant

Applicant : Samsung Electronics Co., Ltd.

Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Contact Person : Seo, Deok-ho

Phone No. : +82 10 3955 6246

### 1.3. Description of EUT

|                      |       |                                   |
|----------------------|-------|-----------------------------------|
| Kind of Product      |       | Portable Tablet                   |
| Model Name           |       | SM-T875                           |
| Power Supply         |       | DC 3.86 V                         |
| Frequency Range      |       | 2 402 MHz ~ 2 480 MHz (Bluetooth) |
| Modulation Technique |       | GFSK, $\pi/4$ DQPSK, 8DPSK        |
| Number of Channels   |       | 79 channels (Bluetooth)           |
| Antenna Type         |       | Metal Frame Antenna               |
| Antenna Gain         | Ant.1 | -5.10 dB i                        |
|                      | Ant.2 | -4.80 dB i                        |

### 1.4. Declaration by the Manufacturer

- Adaptive Frequency Hopping is supported and use at least 20 channels.
- The EUT can operate Bluetooth both Ant.1 and Ant.2, but it can't operate at the same time.

## 1.5. Test Equipment List

| Equipment                | Manufacturer                | Model                                | S/N                    | Cal. Date     | Cal. Interval | Cal. Due      |
|--------------------------|-----------------------------|--------------------------------------|------------------------|---------------|---------------|---------------|
| Signal Generator         | R&S                         | SMR40                                | 100272                 | Jun. 18, 2020 | Annual        | Jun. 18, 2021 |
| Signal Generator         | R&S                         | SMBV100A                             | 255834                 | Jun. 03, 2020 | Annual        | Jun. 03, 2021 |
| Spectrum Analyzer        | R&S                         | FSV30                                | 103210                 | Nov. 05, 2019 | Annual        | Nov. 05, 2020 |
| Spectrum Analyzer        | Agilent                     | N9030A                               | US51350132             | Nov. 15, 2019 | Annual        | Nov. 15, 2020 |
| Bluetooth Tester         | TESCOM                      | TC-3000C                             | 3000C000296            | Jun. 01, 2020 | Annual        | Jun. 01, 2021 |
| Directional Coupler      | KRYTAR                      | 152613                               | 140972                 | Jun. 11, 2020 | Annual        | Jun. 11, 2021 |
| High Pass Filter         | Wainwright Instrument GmbH  | WHK3.0/18G-10SS                      | 344                    | May 18, 2020  | Annual        | May 18, 2021  |
| High Pass Filter         | Wainwright Instrument GmbH  | WHNX7.5/26.5G-6SS                    | 15                     | Jun. 05, 2020 | Annual        | Jun. 05, 2021 |
| Low Pass Filter          | Mini-Circuits               | NLP-1200+                            | V 9500401023-2         | Jun. 01, 2020 | Annual        | Jun. 01, 2021 |
| Power Sensor             | R&S                         | NRP-Z81                              | 101421                 | Dec. 26, 2019 | Annual        | Dec. 26, 2020 |
| DC Power Supply          | Agilent                     | U8002A                               | MY50060028             | Mar. 03, 2020 | Annual        | Mar. 03, 2021 |
| Preamplifier             | H.P.                        | 8447F                                | 2944A03909             | Aug. 07, 2019 | Annual        | Aug. 07, 2020 |
| Signal Conditioning Unit | R&S                         | SCU-18                               | 10117                  | Jun. 10, 2020 | Annual        | Jun. 10, 2021 |
| Preamplifier             | MITEQ Inc.                  | JS44-18004000-35-8P                  | 1546891                | May 08, 2020  | Annual        | May 08, 2021  |
| Loop Antenna             | Schwarzbeck Mess-Elektronik | FMZB 1519                            | 1519-039               | Aug. 22, 2019 | Biennial      | Aug. 22, 2021 |
| Bilog Antenna            | Schwarzbeck Mess-Elektronik | VULB 9163                            | 396                    | Mar. 21, 2019 | Biennial      | Mar. 21, 2021 |
| Horn Antenna             | R&S                         | HF906                                | 100326                 | Feb. 14, 2020 | Annual        | Feb. 14, 2021 |
| Horn Antenna             | Schwarzbeck Mess-Elektronik | BBHA 9170                            | BBHA9170431            | Sep. 10, 2018 | Biennial      | Sep. 10, 2020 |
| Test Receiver            | R&S                         | ESU26                                | 100109                 | Feb. 18, 2020 | Annual        | Feb. 18, 2021 |
| Turn Table               | Innco systems GmbH          | DS 1200 S                            | N/A                    | N.C.R.        | N/A           | N.C.R.        |
| Controller               | Innco systems GmbH          | CONTROLLER CO3000-4P                 | CO3000/963/383 30516/L | N.C.R.        | N/A           | N.C.R.        |
| Antenna Mast             | Innco systems GmbH          | MA4640-XP-ET                         | MA4640/536/383 30516/L | N.C.R.        | N/A           | N.C.R.        |
| Anechoic Chamber         | SY Corporation              | L × W × H<br>(9.6 m × 6.4 m × 6.6 m) | N/A                    | N.C.R.        | N/A           | N.C.R.        |
| Coaxial Cable            | RFONE                       | PL520-NMNM-4M (4 m)                  | 20200324001            | May 06, 2020  | Semi-annual   | Nov. 06, 2020 |
| Coaxial Cable            | RFONE                       | PL520-NMNM-10M (10 m)                | 20200324001            | May 06, 2020  | Semi-annual   | Nov. 06, 2020 |
| Coaxial Cable            | Rosenberger                 | LA1-C006-1500                        | 131014 01/20           | Feb. 23, 2020 | Semi-annual   | Aug. 23, 2020 |
| Coaxial Cable            | Rosenberger                 | LA1-C006-1500                        | 131014 05/20           | Feb. 23, 2020 | Semi-annual   | Aug. 23, 2020 |
| Coaxial Cable            | Rosenberger                 | LA1-C006-1500                        | 131014 10/20           | Feb. 23, 2020 | Semi-annual   | Aug. 23, 2020 |
| Test Receiver            | R&S                         | ESCI 7                               | 100911                 | Feb. 19, 2020 | Annual        | Feb. 19, 2021 |
| Two-Line V-Network       | R&S                         | ENV216                               | 100190                 | May 08, 2020  | Annual        | May 08, 2021  |
| Shield Room              | SY Corporation              | L × W × H<br>(6.5 m × 3.5 m × 3.5 m) | N/A                    | N.C.R.        | N/A           | N.C.R.        |

## 1.6. Information about the FHSS characteristics:

### 1.6.1. Pseudorandom Frequency Hopping Sequence

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The nominal hop rate is 1 600 hops/s.

### 1.6.2. Equal Hopping Frequency Use

The channels of this system will be used equally over the long-term distribution of the hopsets.

### 1.6.3. Example of a 79 hopping sequence in data mode:

02, 05, 31, 24, 20, 10, 43, 36, 30, 23, 40, 06, 21, 50, 44, 09, 71, 78, 01, 13, 73, 07, 70, 72, 35, 62, 42, 11, 41, 08, 16, 29, 60, 15, 34, 61, 58, 04, 67, 12, 22, 53, 57, 18, 27, 76, 39, 32, 17, 77, 52, 33, 56, 46, 37, 47, 64, 49, 45, 38, 69, 14, 51, 26, 79, 19, 28, 65, 75, 54, 48, 03, 25, 66, 05, 16, 68, 74, 59, 63, 55

### 1.6.4. System Receiver Input Bandwidth

Each channel bandwidth is 1 MHz.

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

### 1.6.5. Equipment Description

15.247(a)(1) that the Rx input bandwidths shift frequencies in synchronization with the transmitted signals.

15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.

15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection/ hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

## 1.7. Summary of Test Results

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC Part15 Subpart C |                                                                         |          |
|----------------------------------------|-------------------------------------------------------------------------|----------|
| Section                                | Test Item(s)                                                            | Result   |
| 15.205(a)<br>15.209<br>15.247(d)       | Transmitter Radiated Spurious Emissions and Conducted Spurious Emission | Complied |
| 15.247(a)(1)                           | 20 dB Bandwidth                                                         | Complied |
| 15.247(a)(1)<br>15.247(b)(1)           | Maximum Peak Conducted Output Power                                     | Complied |
| 15.247(a)(1)                           | Carrier Frequency Separation                                            | Complied |
| 15.247(a)(1)(iii)                      | Number of Hopping Frequencies                                           | Complied |
| 15.247(a)(1)(iii)                      | Time of Occupancy (Dwell Time)                                          | Complied |
| 15.207                                 | AC Power Line Conducted Emission                                        | Complied |

## 1.8. Test Procedure(s)

The measurement procedures described in the American National Standard of Procedure for Compliance Testing of unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 558074 D01 15.247 Meas Guidance v05r02 were used in the measurement of the DUT.

## 1.9. Sample Calculation

Where relevant, the following sample calculation is provided:

### 1.9.1. Conducted Test

Offset value (dB) = Directional coupler (dB) + Cable loss (dB)

### 1.9.2. Radiation Test

Field strength level (dB $\mu$ V/m) = Measured level (dB $\mu$ V) + Antenna factor (dB) + Cable loss (dB) - Amplifier gain (dB) + Duty Factor (dB)

## 1.10. Test Report Revision

| Revision | Report Number          | Date of Issue | Description                                                               |
|----------|------------------------|---------------|---------------------------------------------------------------------------|
| 0        | F690501-RF-RTL000913   | 2020.07.09    | Initial                                                                   |
| 1        | F690501-RF-RTL000913-1 | 2020.07.15    | Added note for below 30 MHz test site, modified the equipment under test. |
| 2        | F690501-RF-RTL000913-2 | 2020.07.20    | Modified the details of applicant.                                        |

### 1.11. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| Parameter                          | Uncertainty   |
|------------------------------------|---------------|
| Conducted Disturbance              | $\pm 3.45$ dB |
| Radiated Emission, 9 kHz to 30 MHz | $\pm 3.59$ dB |
| Radiated Emission, below 1 GHz     | $\pm 5.88$ dB |
| Radiated Emission, above 1 GHz     | $\pm 5.94$ dB |

Uncertainty figures are valid to a confidence level of 95 %.

### 1.12. Descriptions of Test Mode

Preliminary tests were performed in different data rates and recorded the RF output power in the following table:

| Operation Mode | Data Rate (Mbps) | Frequency (MHz) | Packet type | RF Peak Power (dB m) |                     |
|----------------|------------------|-----------------|-------------|----------------------|---------------------|
|                |                  |                 |             | Ant.1                | Ant.2               |
| GFSK           | 1                | 2 480           | DH1         | <b><u>16.60</u></b>  | <b><u>16.12</u></b> |
|                |                  |                 | DH3         | 16.21                | 15.76               |
|                |                  |                 | DH5         | 16.04                | 15.63               |
| $\pi/4$ DQPSK  | 2                | 2 480           | DH1         | <b><u>17.77</u></b>  | <b><u>17.32</u></b> |
|                |                  |                 | DH3         | 17.49                | 16.97               |
|                |                  |                 | DH5         | 17.19                | 16.82               |
| 8DPSK          | 3                | 2 480           | DH1         | <b><u>18.23</u></b>  | <b><u>17.73</u></b> |
|                |                  |                 | DH3         | 17.84                | 17.42               |
|                |                  |                 | DH5         | 17.64                | 17.21               |


**Note;**

1. For transmitter radiated spurious emissions, conducted spurious emission, carrier frequency separation and number of hopping frequencies, GFSK / DH1 and 8DPSK / 3DH1 are tested as worst condition.
2. For 20 dB bandwidth and maximum peak conducted output power, GFSK / DH1,  $\pi/4$ DQPSK / 2DH1 and 8DPSK / 3DH1 are tested as worst condition.
3. For Time of Occupancy, GFSK / DH1, DH3, DH5 and 8DPSK / 3DH1, 3DH3, 3DH5 are tested as worst condition.


### 1.13. Duty Cycle Correction Factor of EUT

According to KDB 558074 D01 15.247 Meas Guidance v05r02, 9, as a “duty cycle correction factor”, pulse averaging with 20 log (worst case dwell time / 100 ms) has to be used for average result.

3DH5 on time (One Pulse) Plot on Channel 39



3DH5 on time (Count Pulses) Plot on Channel 39



In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time 3DH5 packet is observed;  
the period to have 3DH5 packet completing one hopping sequence is  $2.89 \text{ ms} \times 20 \text{ channels} = 57.80 \text{ ms}$

There cannot be 2 complete hopping sequences within 100 ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period.  $[100 \text{ ms} / 57.80 \text{ ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.89 \text{ ms} \times 2 = 5.78 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time:


$$20 \times \log (5.78 \text{ ms} / 100 \text{ ms}) = -24.76 \text{ dB}$$

## 2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission


### 2.1. Test Setup

#### 2.1.1. Transmitter Radiated Spurious Emissions


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz.




The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz.



The diagram below shows the test setup that is utilized to make the measurements for emission. The spurious emissions were investigated from 1 GHz to the 10<sup>th</sup> harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.



### 2.1.2. Conducted Spurious Emissions



### 2.2. Limit

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emission which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency<br>(MHz) | Field Strength<br>( $\mu V/m$ ) | Measurement Distance<br>(Meters) |
|--------------------|---------------------------------|----------------------------------|
| 0.009-0.490        | $2\ 400/F(\text{kHz})$          | 300                              |
| 0.490-1.705        | $24\ 000/F(\text{kHz})$         | 30                               |
| 1.705-30.0         | 30                              | 30                               |
| 30-88              | 100**                           | 3                                |
| 88-216             | 150**                           | 3                                |
| 216-960            | 200**                           | 3                                |
| Above 960          | 500                             | 3                                |

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

## 2.3. Test Procedures

Radiated emissions from the EUT were measured according to the dictates of ANSI C63.10-2013.

### 2.3.1. Test Procedures for emission below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then Antenna is a loop Antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the Antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum Hold Mode.

#### Note;

Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 meter open field test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788 D01 Radiated Test Site v01r01.

### 2.3.2. Test Procedures for emission from above 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site below 1 GHz and 1.5 meter above the ground at a 3 meter anechoic chamber test site above 1 GHz. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving Antenna, which was mounted on the top of a variable-height Antenna tower. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving Antenna.
3. The Antenna is a bi-log Antenna, a horn Antenna and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the Antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the Antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

#### Note;

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1 GHz.
2. For frequency above 1 GHz, set spectrum analyzer detector to peak, and resolution bandwidth is 1 MHz and video bandwidth is 3 MHz.
3. Definition of DUT Axis.  
Definition of the test orthogonal plan for EUT was described in the test setup photo.  
The test orthogonal plan of EUT is Z – axis during radiation test.

### **2.3.3. Test Procedures for Conducted Spurious Emissions**

#### **2.3.3.1. Band-edge Compliance of RF Conducted Emissions**

The transmitter output was connected to the spectrum analyzer.

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation.

RBW  $\geq$  100 kHz

VBW = 300 kHz

Sweep = auto

Detector function = peak

Trace = max hold

#### **2.3.3.2. Spurious RF Conducted Emissions**

The transmitter output was connected to the spectrum analyzer.

RBW = 1 MHz

VBW = 3 MHz

Sweep = auto

Detector function = peak

Trace = max hold

#### **2.3.3.3. TDF function**

- For plots showing conducted spurious emissions from 9 kHz to 25 GHz, all path loss of wide frequency range was investigated and compensated to spectrum analyzer as TDF function.

So, the reading values shown in plots were final result.

## 2.4. Test Results

Ambient temperature : (23 ± 1) °C  
 Relative humidity : 47 % R.H.

### 2.4.1. Radiated Spurious Emission below 1 000 MHz


The frequency spectrum from 9 kHz to 1 000 MHz was investigated. All reading values are peak values.

| Radiated Emissions |                |             | Ant. | Correction Factors |               | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|---------------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP + CL (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| 39.05              | 29.20          | Peak        | V    | 19.62              | -27.49        | 21.33           | 40.00          | 18.67       |
| 41.96              | 30.30          | Peak        | H    | 20.30              | -27.48        | 23.12           | 40.00          | 16.88       |
| 761.50             | 31.40          | Peak        | H    | 26.67              | -25.02        | 33.05           | 46.00          | 12.95       |
| Above 800.00       | Not detected   | -           | -    | -                  | -             | -               | -              | -           |

#### Remark;

1. Spurious emissions for all channels and modes were investigated and almost the same below 1 GHz.
2. Reported spurious emissions are in **EDR(Ant.1) / 3DH1 / High channel** as worst case among other modes.
3. Radiated spurious emission measurement as below.  
 (Actual = Reading + AF + AMP + CL)
4. According to §15.31(o), emission levels are not report much lower than the limits by over 20 dB.

#### - Test plot



### 2.4.2. Radiated Spurious Emission above 1 000 MHz

The frequency spectrum above 1 000 MHz was investigated. All reading values are peak values.

#### Operating Mode: GFSK (1 Mbps)\_Ant.1

##### A. Low Channel (2 402 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |         |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|---------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| *2 310.00          | 29.37          | Peak        | H    | 27.96              | 8.64    | -       | 65.97           | 74.00          | 8.03        |
| *2 310.00          | -              | -           | -    | -                  | -       | -24.76  | 41.21           | 54.00          | 12.79       |
| *2 340.23          | 31.76          | Peak        | H    | 27.84              | 8.03    | -       | 67.63           | 74.00          | 6.37        |
| *2 340.23          | -              | -           | -    | -                  | -       | -24.76  | 42.87           | 54.00          | 11.13       |
| *2 390.00          | 29.69          | Peak        | H    | 28.20              | 7.04    | -       | 64.93           | 74.00          | 9.07        |
| *2 390.00          | -              | -           | -    | -                  | -       | -24.76  | 40.17           | 54.00          | 13.83       |

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

##### B. Middle Channel (2 441 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

C. High Channel (2 480 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |         |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|---------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| *2 483.50          | 30.99          | Peak        | H    | 28.37              | 6.50    | -       | 65.86           | 74.00          | 8.14        |
| *2 483.50          | -              | -           | -    | -                  | -       | -24.76  | 41.10           | 54.00          | 12.90       |
| *2 496.28          | 32.97          | Peak        | H    | 28.31              | 6.38    | -       | <b>67.66</b>    | 74.00          | 6.34        |
| *2 496.28          | -              | -           | -    | -                  | -       | -24.76  | 42.90           | 54.00          | 11.10       |
| *2 500.00          | 29.46          | Peak        | H    | 28.30              | 6.35    | -       | 64.11           | 74.00          | 9.89        |
| *2 500.00          | -              | -           | -    | -                  | -       | -24.76  | 39.35           | 54.00          | 14.65       |

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

**Operating Mode: 8DPSK (3 Mbps)\_Ant.1**

A. Low Channel (2 402 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |         |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|---------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| *2 310.00          | 29.69          | Peak        | H    | 27.96              | 8.64    | -       | 66.29           | 74.00          | 7.71        |
| *2 310.00          | -              | -           | -    | -                  | -       | -24.76  | 41.53           | 54.00          | 12.47       |
| *2 381.87          | 31.87          | Peak        | H    | 28.12              | 7.09    | -       | 67.08           | 74.00          | 6.92        |
| *2 381.87          | -              | -           | -    | -                  | -       | -24.76  | 42.32           | 54.00          | 11.68       |
| *2 390.00          | 29.58          | Peak        | H    | 28.20              | 7.04    | -       | 64.82           | 74.00          | 9.18        |
| *2 390.00          | -              | -           | -    | -                  | -       | -24.76  | 40.06           | 54.00          | 13.94       |

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

B. Middle Channel (2 441 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

C. High Channel (2 480 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |         |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|---------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| *2 483.50          | 29.75          | Peak        | H    | 28.37              | 6.50    | -       | 64.62           | 74.00          | 9.38        |
| *2 483.50          | -              | -           | -    | -                  | -       | -24.76  | 39.86           | 54.00          | 14.14       |
| *2 483.90          | 33.22          | Peak        | H    | 28.36              | 6.50    | -       | <b>68.08</b>    | 74.00          | 5.92        |
| *2 483.90          | -              | -           | -    | -                  | -       | -24.76  | 43.32           | 54.00          | 10.68       |
| *2 500.00          | 29.15          | Peak        | H    | 28.30              | 6.35    | -       | 63.80           | 74.00          | 10.20       |
| *2 500.00          | -              | -           | -    | -                  | -       | -24.76  | 39.04           | 54.00          | 14.96       |

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

**Operating Mode: GFSK (1 Mbps)\_Ant.2**

A. Low Channel (2 402 MHz)

| Radiated Emissions |                      |             | Ant. | Correction Factors |         |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|---------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| *2 310.00          | 28.78                | Peak        | H    | 27.96              | 8.64    | -       | 65.38                 | 74.00                | 8.62        |
| *2 310.00          | -                    | -           | -    | -                  | -       | -24.76  | 40.62                 | 54.00                | 13.38       |
| *2 377.78          | 31.89                | Peak        | H    | 28.08              | 7.12    | -       | 67.09                 | 74.00                | 6.91        |
| *2 377.78          | -                    | -           | -    | -                  | -       | -24.76  | 42.33                 | 54.00                | 11.67       |
| *2 390.00          | 29.32                | Peak        | H    | 28.20              | 7.04    | -       | 64.56                 | 74.00                | 9.44        |
| *2 390.00          | -                    | -           | -    | -                  | -       | -24.76  | 39.80                 | 54.00                | 14.20       |

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -       | -                     | -                    | -           |

B. Middle Channel (2 441 MHz)

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |         | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -       | -                     | -                    | -           |

C. High Channel (2 480 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |         |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|---------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| *2 483.50          | 30.46          | Peak        | H    | 28.37              | 6.50    | -       | 65.33           | 74.00          | 8.67        |
| *2 483.50          | -              | -           | -    | -                  | -       | -24.76  | 40.57           | 54.00          | 13.43       |
| *2 492.15          | 32.47          | Peak        | H    | 28.33              | 6.42    | -       | <b>67.22</b>    | 74.00          | 6.78        |
| *2 492.15          | -              | -           | -    | -                  | -       | -24.76  | 42.46           | 54.00          | 11.54       |
| *2 500.00          | 30.16          | Peak        | H    | 28.30              | 6.35    | -       | 64.81           | 74.00          | 9.19        |
| *2 500.00          | -              | -           | -    | -                  | -       | -24.76  | 40.05           | 54.00          | 13.95       |

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

**Operating Mode: 8DPSK (3 Mbps)\_Ant.2**

Low Channel (2 402 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |         |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|---------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| *2 310.00          | 29.00          | Peak        | H    | 27.96              | 8.64    | -       | 65.60           | 74.00          | 8.40        |
| *2 310.00          | -              | -           | -    | -                  | -       | -24.76  | 40.84           | 54.00          | 13.16       |
| *2 387.75          | 31.63          | Peak        | H    | 28.18              | 7.05    | -       | 66.86           | 74.00          | 7.14        |
| *2 387.75          | -              | -           | -    | -                  | -       | -24.76  | 42.10           | 54.00          | 11.90       |
| *2 390.00          | 28.97          | Peak        | H    | 28.20              | 7.04    | -       | 64.21           | 74.00          | 9.79        |
| *2 390.00          | -              | -           | -    | -                  | -       | -24.76  | 39.45           | 54.00          | 14.55       |

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

B. Middle Channel (2 441 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |

C. High Channel (2 480 MHz)

| Radiated Emissions |                |             | Ant. | Correction Factors |         |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|---------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| *2 483.50          | 30.39          | Peak        | H    | 28.37              | 6.50    | -       | 65.26           | 74.00          | 8.74        |
| *2 483.50          | -              | -           | -    | -                  | -       | -24.76  | 40.50           | 54.00          | 13.50       |
| *2 488.44          | 32.87          | Peak        | H    | 28.35              | 6.46    | -       | <b>67.68</b>    | 74.00          | 6.32        |
| *2 488.44          | -              | -           | -    | -                  | -       | -24.76  | 42.92           | 54.00          | 11.08       |
| *2 500.00          | 29.32          | Peak        | H    | 28.30              | 6.35    | -       | 63.97           | 74.00          | 10.03       |
| *2 500.00          | -              | -           | -    | -                  | -       | -24.76  | 39.21           | 54.00          | 14.79       |

| Radiated Emissions |                |             | Ant. | Correction Factors |             |         | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | DF (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Above 1 000.00     | Not detected   | -           | -    | -                  | -           | -       | -               | -              | -           |


**Remark;**

1. "\*" means the restricted band.
2. Measuring frequencies from 1 GHz to the 10<sup>th</sup> harmonic of highest fundamental frequency.
3. Radiated emissions measured in frequency above 1 000 MHz were made with an instrument using peak/average detector mode.
4. Actual = Reading + AF + CL + (DF) or Reading + AF + AMP + CL + (DF).
5. According to § 15.31(o), emission levels are not reported much lower than the limits by over 20 dB.
6. The maximized peak measured value complies with the average limit, to perform an average measurement is unnecessary.
7. AF = Antenna Factor, CL = Cable Loss, DF = Duty Correction Factor.


## - Test plots

### Operating Mode: GFSK (1 Mbps)\_Ant.1

#### Low channel band edge




#### High channel band edge




## Operating Mode: 8DPSK (3 Mbps)\_Ant.1

### Low channel band edge




### High channel band edge




## Operating Mode: GFSK (1 Mbps)\_Ant.2

### Low channel band edge




### High channel band edge




## Operating Mode: 8DPSK (3 Mbps)\_Ant.2

### Low channel band edge




### High channel band edge




### 2.4.3. Plot of Spurious Conducted Emissions

Operating Mode: GFSK (1 Mbps)\_Ant.1


Low channel



Middle channel




## High channel




### Band edge compliance with hopping enabled

Low channel




High channel




**Operating Mode: 8DPSK (3 Mbps)\_Ant.1**


Low channel



## Middle channel




## High channel




### Band edge compliance with hopping enabled

Low channel




High channel




**Operating Mode: GFSK (1 Mbps)\_Ant.2**


Low channel



Middle channel




## High channel




## Band edge compliance with hopping enabled

Low channel




High channel






**Operating Mode: 8DPSK (3 Mbps)\_Ant.2**


Low channel



Middle channel




## High channel




### Band edge compliance with hopping enabled

Low channel




High channel



### 3. 20 dB Bandwidth

#### 3.1. Test Setup



#### 3.2. Limit

Limit: Not Applicable

#### 3.3. Test Procedure

The test follows ANSI C63.10-2013.

The 20 dB bandwidth was measured with a spectrum analyzer connected to RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency.

Use the following spectrum analyzer setting:

1. Span = approximately 2 to 5 times the 20 dB bandwidth.
2. RBW  $\geq 1\%$  to 5 % of the 20 dB bandwidth.
3. VBW  $\geq 3 \times$  RBW
4. Sweep = auto
5. Detector = peak
6. Trace = max hold

The marker-to-peak function to set the mark to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is 20 dB bandwidth of the emission.

### 3.4. Test Results


Ambient temperature : (23 ± 1) °C  
 Relative humidity : 47 % R.H.

| Operation Mode | Data Rate (Mbps) | Channel | Frequency (MHz) | 20 dB Bandwidth (MHz) |       |
|----------------|------------------|---------|-----------------|-----------------------|-------|
|                |                  |         |                 | Ant.1                 | Ant.2 |
| GFSK           | 1                | Low     | 2 402           | 0.932                 | 0.932 |
|                |                  | Middle  | 2 441           | 0.929                 | 0.929 |
|                |                  | High    | 2 480           | 0.932                 | 0.929 |
| π/4DQPSK       | 2                | Low     | 2 402           | 1.328                 | 1.325 |
|                |                  | Middle  | 2 441           | 1.325                 | 1.322 |
|                |                  | High    | 2 480           | 1.325                 | 1.325 |
| 8DPSK          | 3                | Low     | 2 402           | 1.274                 | 1.274 |
|                |                  | Middle  | 2 441           | 1.274                 | 1.274 |
|                |                  | High    | 2 480           | 1.277                 | 1.277 |


## - Test plots

### Operating Mode: GFSK\_Ant.1


#### Low Channel



#### Middle Channel




#### High Channel




Operating Mode:  $\pi/4$ DQPSK\_Ant.1


Low Channel



Middle Channel




High Channel




### Operating Mode: 8DPSK\_Ant.1


#### Low Channel



#### Middle Channel




#### High Channel




## Operating Mode: GFSK\_Ant.2


### Low Channel



### Middle Channel




### High Channel




## Operating Mode: $\pi/4$ DQPSK\_Ant.2


### Low Channel



### Middle Channel




### High Channel




## Operating Mode: 8DPSK\_Ant.2


### Low Channel



### Middle Channel




### High Channel



## 4. Maximum Peak Conducted Output Power

### 4.1. Test Setup



### 4.2. Limit

1. §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2 400-2 483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.
2. §15.247(b)(1), For frequency hopping systems operating in the 2 400-2 483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5 725-5 850 MHz band: 1 watt. For all other frequency hopping systems in the 2 400-2 483.5 MHz band: 0.125 watts.

### 4.3. Test Procedure

The test follows ANSI C63.10-2013. Using the power sensor instead of a spectrum analyzer.

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the Antenna from the EUT and then connect a low loss RF cable from the Antenna port to the Power sensor.
3. Test program: (SW name: R&S Power Viewer, Version: 3.2.0)
4. Measure peak power each channel.

#### 4.4. Test Results

Ambient temperature : (23 ± 1) °C  
Relative humidity : 47 % R.H.


| Operation Mode | Data Rate (Mbps) | Channel | Frequency (MHz) | Ant.1                       |                          | Ant.2                       |                          | Limit (dB m) |
|----------------|------------------|---------|-----------------|-----------------------------|--------------------------|-----------------------------|--------------------------|--------------|
|                |                  |         |                 | Average Power Result (dB m) | Peak Power Result (dB m) | Average Power Result (dB m) | Peak Power Result (dB m) |              |
| GFSK           | 1                | Low     | 2 402           | 14.50                       | 15.88                    | 12.79                       | 14.20                    | 30           |
|                |                  | Middle  | 2 441           | 14.83                       | 16.26                    | 14.22                       | 15.65                    |              |
|                |                  | High    | 2 480           | <u>15.15</u>                | <u>16.60</u>             | <u>15.07</u>                | <u>16.12</u>             |              |
| π/4DQPSK       | 2                | Low     | 2 402           | 13.85                       | 17.10                    | 12.09                       | 15.33                    | 20.97        |
|                |                  | Middle  | 2 441           | 14.49                       | 17.34                    | 13.83                       | 16.77                    |              |
|                |                  | High    | 2 480           | <u>14.49</u>                | <u>17.77</u>             | <u>14.01</u>                | <u>17.32</u>             |              |
| 8DPSK          | 3                | Low     | 2 402           | 13.92                       | 17.62                    | 11.71                       | 15.73                    |              |
|                |                  | Middle  | 2 441           | 14.58                       | 17.87                    | 13.81                       | 17.15                    |              |
|                |                  | High    | 2 480           | <u>14.60</u>                | <u>18.23</u>             | <u>14.01</u>                | <u>17.73</u>             |              |

#### Remark;

In the case of AFH, the limit for peak power is 0.125 W.  
Directional coupler and cable offset compensate for test program (R&S Power Viewer) before measuring.

## 5. Carrier Frequency Separation

### 5.1. Test Setup



### 5.2. Limit

§15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2 400-2 483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### 5.3. Test Procedure

The test follows ANSI C63.10-2013.

The device is operating in hopping mode between 79 channels and also supporting Adaptive Frequency Hopping with hopping between 20 channels. As compared with each operating mode, 79 channels are chosen as a representative for test.

Use the following spectrum analyzer settings:

1. Span: Wide enough to capture the peaks of two adjacent channels
2. RBW: Start with the RBW set to approximately 30 % of the channel spacing; adjust as necessary to best identify the center of each individual channel.
3. VBW  $\geq$  RBW
4. Sweep: Auto
5. Detector: Peak
6. Trace: Max hold
7. Allow the trace to stabilize.

Use the marker-delta function to determine the between the peaks of the adjacent channels.

## 5.4. Test Results

Ambient temperature :  $(23 \pm 1) ^\circ\text{C}$   
 Relative humidity : 47 % R.H.

| Operation Mode | Frequency<br>(MHz) | Adjacent Hopping<br>Channel<br>Separation<br>(kHz) | 20 dB Bandwidth<br>(kHz) |       |
|----------------|--------------------|----------------------------------------------------|--------------------------|-------|
|                |                    |                                                    | Ant.1                    | Ant.2 |
| GFSK           | 2 441              | 1 000                                              | 929                      | 929   |


| Operation Mode | Frequency<br>(MHz) | Adjacent Hopping<br>Channel<br>Separation<br>(kHz) | Two-third of 20 dB Bandwidth<br>(kHz) |       |
|----------------|--------------------|----------------------------------------------------|---------------------------------------|-------|
|                |                    |                                                    | Ant.1                                 | Ant.2 |
| 8DPSK          | 2 441              | 1 000                                              | 849                                   | 849   |

### Remark;


Measurement is made with EUT operating in hopping mode between 79 channels providing a worst case scenario as compared to AFH mode hopping between 20 channels.

- Test plots


Operating Mode: GFSK\_Ant.1




Operating Mode: 8DPSK\_Ant.1



### Operating Mode: GFSK\_Ant.2




### Operating Mode: 8DPSK\_Ant.2



## 6. Number of Hopping Frequencies

### 6.1. Test Setup



### 6.2. Limit

§15.247(a)(1)(iii), Frequency hopping systems in the 2 400-2 483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### 6.3. Test Procedure

The test follows ANSI C63.10-2013.

The device supports Adaptive Frequency Hopping and will use a minimum of 20 channels of the 79 available channels.

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
2. RBW: To identify clearly the individual channels, set the RBW to less than 30 % of the channel spacing or the 20 dB bandwidth, whichever is smaller.
3. VBW  $\geq$  RBW
4. Sweep: Auto
5. Detector function: Peak
6. Trace: Max hold
7. Allow the trace to stabilize.

#### 6.4. Test Results

Ambient temperature :  $(23 \pm 1) ^\circ\text{C}$   
 Relative humidity : 47 % R.H.


| Operation Mode | Number of Hopping Frequency | Limit     |
|----------------|-----------------------------|-----------|
| GFSK           | 79                          | $\geq 15$ |
| 8DPSK          | 79                          | $\geq 15$ |

#### Remark;


Measurement is made with EUT operating in hopping mode between 79 channels providing a worst case scenario as compared to AFH mode hopping between 20 channels.

## - Test plots


### Operating Mode: GFSK\_Ant.1




Operating Mode: 8DPSK\_Ant.1



Operating Mode: GFSK\_Ant.2




Operating Mode: 8DPSK\_Ant.2



## 7. Time of Occupancy (Dwell Time)

### 7.1. Test Set up



### 7.2. Limit

§15.247(a)(1)(iii), Frequency hopping systems in the 2 400-2 483.5 MHz band, the average time of occupancy on any frequency shall not be greater than 0.4 second within a 31.6 second period.

A period time = 0.4 (s) \* 79 = 31.6 (s)

#### \*Adaptive Frequency Hopping

A period time = 0.4 (s) \* 20 = 8 (s)

### 7.3. Test Procedure

All data rates and modes were investigated for this test. The full data for the worst case data rate are reported in this section. The test follows ANSI C63.10-2013.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect its Antenna terminal to measurement instrument via a low loss cable.
3. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
4. The Bluetooth has 3 type of payload, DH1, DH3, DH5 and 3DH1, 3DH3, 3DH5. The hopping rate is insisted of 1 600 per second.

The EUT must have its hopping function enabled. Use the following spectrum analyzer setting:

1. Span = Zero span, centered on a hopping channel.
2. RBW = 1 MHz.
3. VBW  $\geq$  RBW.
4. Sweep = As necessary to capture the entire dwell time per hopping channel.
5. Detector = Peak.
6. Trace = Max hold.

Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation, then repeat this test for each variation.

## 7.4. Test Results

Ambient temperature : (23 ± 1) °C  
 Relative humidity : 47 % R.H.

### 7.4.1. Packet Type: DH1, 3DH1

| Port  | Operation Mode | Frequency (MHz) | Dwell Time (ms) | Time of occupancy on the Tx Channel in 31.6 sec (ms) | Limit for time of occupancy on the Tx Channel in 31.6 sec (ms) |
|-------|----------------|-----------------|-----------------|------------------------------------------------------|----------------------------------------------------------------|
| Ant.1 | GFSK           | 2 441           | 0.38            | 121.60                                               | 400                                                            |
|       | 8DPSK          |                 | 0.38            | 121.60                                               |                                                                |
| Ant.2 | GFSK           |                 | 0.38            | 121.60                                               |                                                                |
|       | 8DPSK          |                 | 0.39            | 124.80                                               |                                                                |

#### Remark;

Time of occupancy on the TX channel in 31.6 sec.


Ant.1: In case of GFSK and 8DPSK:  $0.38 \times \{(1\ 600 \div 2) / 79\} \times 31.6 = 121.60\ \text{ms}$

Ant.2: In case of GFSK:  $0.38 \times \{(1\ 600 \div 2) / 79\} \times 31.6 = 121.60\ \text{ms}$


In case of 8DPSK:  $0.39 \times \{(1\ 600 \div 2) / 79\} \times 31.6 = 124.80\ \text{ms}$

## - Test plots


### Operating Mode: GFSK\_Ant.1




### Operating Mode: 8DPSK\_Ant.1



Operating Mode: GFSK\_Ant.2



Operating Mode: 8DPSK\_Ant.2



#### 7.4.2. Packet Type: DH3, 3DH3

| Port  | Operation Mode | Frequency (MHz) | Dwell Time (ms) | Time of occupancy on the Tx Channel in 31.6 sec (ms) | Limit for time of occupancy on the Tx Channel in 31.6 sec (ms) |
|-------|----------------|-----------------|-----------------|------------------------------------------------------|----------------------------------------------------------------|
| Ant.1 | GFSK           | 2 441           | 1.63            | 260.80                                               | 400                                                            |
|       | 8DPSK          |                 | 1.64            | 262.40                                               |                                                                |
| Ant.2 | GFSK           |                 | 1.64            | 262.40                                               |                                                                |
|       | 8DPSK          |                 | 1.64            | 262.40                                               |                                                                |

#### Remark;

Time of occupancy on the TX channel in 31.6 sec.


Ant.1: In case of GFSK:  $1.63 \times \{(1\ 600 \div 4) / 79\} \times 31.6 = 260.80\ \text{ms}$

In case of 8DPSK:  $1.64 \times \{(1\ 600 \div 4) / 79\} \times 31.6 = 262.40\ \text{ms}$


Ant.2: In case of GFSK and 8DPSK:  $1.64 \times \{(1\ 600 \div 4) / 79\} \times 31.6 = 262.40\ \text{ms}$

## - Test plots


### Operating Mode: GFSK\_Ant.1




### Operating Mode: 8DPSK\_Ant.1



## Operating Mode: GFSK\_Ant.2



## Operating Mode: 8DPSK\_Ant.2



#### 7.4.3. Packet Type: DH5, 3DH5

| Port  | Operation Mode | Frequency (MHz) | Dwell Time (ms) | Time of occupancy on the Tx Channel in 31.6 sec (ms) | Limit for time of occupancy on the Tx Channel in 31.6 sec (ms) |
|-------|----------------|-----------------|-----------------|------------------------------------------------------|----------------------------------------------------------------|
| Ant.1 | GFSK           | 2 441           | 2.89            | 308.27                                               | 400                                                            |
|       | 8DPSK          |                 | 2.89            | 308.27                                               |                                                                |
| Ant.2 | GFSK           |                 | 2.88            | 307.20                                               |                                                                |
|       | 8DPSK          |                 | 2.89            | 308.27                                               |                                                                |

#### Remark;

Time of occupancy on the TX channel in 31.6 sec

Ant.1: In case of GFSK and 8DPSK:  $2.89 \times \{(1\ 600 \div 6) / 79\} \times 31.6 = 308.27\ \text{ms}$

Ant.2: In case of GFSK:  $2.88 \times \{(1\ 600 \div 6) / 79\} \times 31.6 = 307.20\ \text{ms}$


In case of 8DPSK:  $2.89 \times \{(1\ 600 \div 6) / 79\} \times 31.6 = 308.27\ \text{ms}$

## - Test plots


### Operating Mode: GFSK\_Ant.1




### Operating Mode: 8DPSK\_Ant.1



## Operating Mode: GFSK\_Ant.2



## Operating Mode: 8DPSK\_Ant.2



#### 7.4.4. Packet Type: DH1, 3DH1 (Adaptive Frequency Hopping)

| Port  | Operation Mode | Frequency (MHz) | Dwell Time (ms) | Time of occupancy on the Tx Channel in 31.6 sec (ms) | Limit for time of occupancy on the Tx Channel in 31.6 sec (ms) |
|-------|----------------|-----------------|-----------------|------------------------------------------------------|----------------------------------------------------------------|
| Ant.1 | GFSK           | 2 441           | 0.38            | 60.80                                                | 400                                                            |
|       | 8DPSK          |                 | 0.39            | 62.40                                                |                                                                |
| Ant.2 | GFSK           |                 | 0.38            | 60.80                                                |                                                                |
|       | 8DPSK          |                 | 0.38            | 60.80                                                |                                                                |

#### Remark;

Time of occupancy on the TX channel in 8 sec.

Ant.1: In case of GFSK:  $0.38 \times \{(800 \div 2) / 20\} \times 8 = 60.80 \text{ ms}$

In case of 8DPSK:  $0.39 \times \{(800 \div 2) / 20\} \times 8 = 62.40 \text{ ms}$

Ant.2: In case of GFSK and 8DPSK:  $0.38 \times \{(800 \div 2) / 20\} \times 8 = 60.80 \text{ ms}$