

ELEMENT MATERIALS TECHNOLOGY

(formerly PCTEST)
7185 Oakland Mills Road, Columbia, MD 21046 USA
Tel. +1.410.290.6652 / Fax +1.410.381.1520
<http://www.element.com>



COMPLIANCE SUMMARY REPORT

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Test Site/Location:

Element, Columbia, MD, USA

Document Serial No.:

1M2505130050-21.A3L

FCC ID:

A3LSMX736B

APPLICANT:

SAMSUNG ELECTRONICS CO., LTD

Report Type:

Compliance Summary

DUT Type:

Portable Computing Device

Model:

SM-X736B



FCC ID: A3LSMX736B	COMPLIANCE SUMMARY REPORT	Approved by: Technical Manager
Document S/N: 1M2505130050-21.A3L	DUT Type: Portable Computing Device	Page 1 of 9

REV 1.1
04/11/2022

TABLE OF CONTENTS

1	STRATEGY FOR COMPLIANCE DEMONSTRATION	3
1.1	RF Exposure Evaluation Strategy	3
1.2	Nomenclature	4
1.3	Bibliography	4
2	TIME AVERAGING ALGORITHM	5
2.1	Algorithm Description	5
2.2	Basic concept of the algorithm	6
3	DUT DESCRIPTION	8
3.1	Device Overview	8
4	COMPLIANCE SUMMARY	9
4.1	RF Exposure Compliance Summary	9

FCC ID: A3LSMX736B	COMPLIANCE SUMMARY REPORT	Approved by: Technical Manager
Document S/N: 1M2505130050-21.A3L	DUT Type: Portable Computing Device	Page 2 of 9

REV 1.1
04/11/2022

1 STRATEGY FOR COMPLIANCE DEMONSTRATION

1.1 RF Exposure Evaluation Strategy

The FCC RF exposure limits defined based on time-averaged RF exposure. The device under test (DUT) uses the MediaTek TAS TA-SAR Gen 2 feature to control and manage transmitting power in real time and to ensure at all times the time-averaged RF exposure is in compliance with the FCC requirement for WWAN operations. Additionally, this device supports WLAN/BT technologies but the output power of these modems is not controlled by the TAS algorithm.

Demonstrating compliance of DUT enabled with TAS feature is completed in three parts:

0. RF Exposure Compliance Test Report Part 0: SAR Characterization

The SAR Characterization, denoted as SAR Char, determines the power limit that meets FCC exposure requirement after accounting for device design related uncertainties for each supported radio configuration and RF exposure usage scenario. The determined power limits will be loaded and stored in the EUT via the Embedded File System (EFS), and then used as inputs for TAS to operate.

For 2G/3G/4G/5G Sub6, SAR Char is derived from SAR test measurements and conducted power measurements to determine P_{Limit} for each technology/band. The P_{Limit} represents the maximum time-averaged power level for the corresponding radio/antenna configuration.

1. RF Exposure Compliance Test Report Part 1: Test in Static Transmission Condition

Part 1 demonstrates that DUT meets FCC SAR limits when transmitting at pre-determined maximum time-averaged power level: P_{Limit} for 2G/3G/4G/5G Sub6 NR. The SAR measurement in Part 1 is under static transmission condition.

The compliance for WLAN/BT radio is demonstrated at a fixed power level (fixed = maximum RF tune-up level or power-back off level).

The exposure from the simultaneous transmission of WWAN and WLAN/BT is evaluated in Part 1 report.

2. RF Exposure Compliance Test Report Part 2: Test in Dynamic Transmission Condition

Part 2 demonstrates compliance in Tx varying transmission conditions and validates MediaTek TAS. The test results reported in Part 2 demonstrates that DUT complies with FCC RF exposure requirement under Tx varying transmission scenarios, thereby validity of MediaTek TAS.

FCC ID: A3LSMX736B	COMPLIANCE SUMMARY REPORT	Approved by: Technical Manager
Document S/N: 1M2505130050-21.A3L	DUT Type: Portable Computing Device	Page 3 of 9

REV 1.1
04/11/2022

1.2 Nomenclature

Applicable Technologies	Term	Description
2G/3G/4G/5G Sub6	P_{Limit} (P_{sub6_limit})	Power level that corresponds to the exposure design target (SAR_design_target) after accounting for all device design related uncertainties
	P_{Max} (P_{UE_max})	Maximum tune up output power
	T_{SAR} ($Algo_avg_window_{Sub6}$)	Defined time averaging window for $f < 6$ GHz
	SAR_design_target	Target SAR level resulting in maximum time-averaged exposure optimized from total uncertainty
	SAR_Char	Table containing P_{Limit} for all technologies
	$regulatory_body$	Regulatory body that the algorithm is designed to comply. Algorithm's time averaging window is dependent on either FCC or ICNIRP requirements.
	$reserve_power_margin$	Margin below P_{Limit} reserved for future transmission
	$P_{reserve}$	Minimum transmit power with a designated margin below P_{Limit}
	$PUE_backoff_offset$	Parameter for calculating $PUE_backoff$. $PUE_backoff = \min(PUE_max, P_{sub6_limit} - PUE_backoff_offset)$ PUE_max is maximum TX power at which a UE can possibly transmit.
	$PUE_max_cust_offset$	Parameter for calculating PUE_max_cust . $PUE_max_cust = \min(PUE_max, P_{sub6_limit} + PUE_max_cust_offset)$
	$SPLSR_group$	Sub6 antenna group index • Antennas can be grouped based on the parameter SAR to Peak Location Separation Ratio (SPLSR) (KDB 447498). • The exposure of the antennas, which belong to the same group, should be counted together to meet total exposure ratio (TER) requirement.

1.3 Bibliography

Report Type	Report Serial Number
SAR Evaluation Report (Part 1)	1M2505130050-17.A3L
SAR Evaluation Report (Part 0)	1M2505130050-23.A3L
PD Evaluation Report (Part 0)	
Near Field PD Report (Part 1)	1M2505130050-22.A3L
RF Exposure Part 2 Test Report	TESA2507000530EN

FCC ID: A3LSMX736B	COMPLIANCE SUMMARY REPORT	Approved by: Technical Manager
Document S/N: 1M2505130050-21.A3L	DUT Type: Portable Computing Device	Page 4 of 9

REV 1.1
04/11/2022

2 TIME AVERAGING ALGORITHM

2.1 Algorithm Description

The FCC RF exposure limit is defined based on time-averaged RF exposure. When running in a wireless device, MediaTek TAS enables more elegant power control mechanisms for RF exposure management. It ensures at all times the wireless device is in compliance with the FCC limit of RF exposure time-averaged over a defined time window, denoted as T_{SAR} for specific absorption rate (SAR for transmit frequency < 6 GHz).

The TAS algorithm not only ensures the wireless device complies with RF exposure requirement, but also improves the user experience and network performance.

For a given wireless device, RF exposure is proportional to the transmitting power.

- Once the SAR of the wireless device is characterized at a transmit power level, RF exposure at a different power level for the characterized configurations can be scaled by the change in the corresponding power level.
- Therefore, for a characterized device, RF exposure compliance can be achieved through transmit power control and management.

The TAS algorithm embedded in MediaTek modems reliably controls the transmit power of the wireless device in real time to maintain the time-averaged transmit power, in turn, time-averaged RF exposure, below the predefined time-averaged power limit for each characterized technology and band.

- This predefined time-averaged power limit is denoted as P_{Limit} corresponding SAR limit (frequency < 6 GHz in this report).
- The wireless device continuously transmitting at P_{Limit} level complies with the FCC RF exposure requirement.

In a simultaneous transmission scenario, the algorithm manages all active transmitters and make sure the total exposure ratio from each transmitter not exceeding to 1.

FCC ID: A3LSMX736B	COMPLIANCE SUMMARY REPORT	Approved by: Technical Manager
Document S/N: 1M2505130050-21.A3L	DUT Type: Portable Computing Device	Page 5 of 9

REV 1.1
04/11/2022

2.2 Basic concept of the algorithm


The TAS algorithm controls and manages the instantaneous transmit power (Tx) to maintain the time-averaged Tx power and therefore, time-averaged RF exposure in compliance with FCC limits.

- If time-averaged transmit power approaches P_{Limit} , then the modem needs to limit instantaneous transmit power to ensure the time-averaged transmit power does not exceed P_{Limit} in any T_{SAR} time windows since the time-averaged RF exposure is required to comply with the FCC RF exposure limit in any T_{SAR} time window.
- The wireless device can instantaneously transmit at high transmit powers and exceed the P_{Limit} level for a short duration before limiting the power to maintain the time-averaged transmit power under P_{Limit} .
- If the wireless device transmits at high power for a long time, then the radio link needs to be dropped to be compliant with time-averaged Tx power requirement (see Figure 2-1).
- To avoid dropping the radio link, TAS algorithm starts the power limiting enforcement earlier in time to back off the Tx power to a reserve level (denoted as $P_{reserve}$), so the wireless device can maintain the radio link at a minimum reserve power level for as long as needed, and at the same time ensure the time-averaged Tx power over any defined time window is less than P_{Limit} at all times (see Figure 2-2). At all times, TAS meets the below equation:

$$time.avg.Tx\ power = \frac{1}{T_{SAR}} \int_{t-T_{SAR}}^t inst.Tx\ power(t) dt \leq P_{limit}$$

Equation 2-1

where, *time.avg.Tx power* is the transmit power averaged between $t-T_{SAR}$ and t time period; T_{SAR} is the time window defined by FCC for time-averaging RF exposure for Tx frequency less than 6GHz (sub6); *inst. Tx power (t)* is the instantaneous transmit power at t time instant; P_{Limit} is the predefined time-averaged power limit.



(a)

Figure 2-1
Transmit at high power when needed and permitted

FCC ID: A3LSMX736B	COMPLIANCE SUMMARY REPORT	Approved by: Technical Manager
Document S/N: 1M2505130050-21.A3L	DUT Type: Portable Computing Device	Page 6 of 9

REV 1.1
04/11/2022




Figure 2-2
Transmit with reserve power to support continuous transmission at a minimum power level ($P_{reserve}$)

- In the case of simultaneous transmission, TAS manages all active transmitters and make sure the total exposure ratio is less than 1

$$\sum \frac{\frac{1}{T_{SAR}} \int_{t-T_{SAR}}^t SAR(t) dt}{FCC SAR limit} \leq 1$$

Equation 2-2

FCC ID: A3LSMX736B	COMPLIANCE SUMMARY REPORT	Approved by: Technical Manager
Document S/N: 1M2505130050-21.A3L	DUT Type: Portable Computing Device	Page 7 of 9

REV 1.1
04/11/2022

3 DUT DESCRIPTION

3.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Data	824.20 - 848.80 MHz
GSM/GPRS/EDGE 1900	Data	1850.20 - 1909.80 MHz
UMTS 850	Data	826.40 - 846.60 MHz
UMTS 1750	Data	1712.4 - 1752.6 MHz
UMTS 1900	Data	1852.4 - 1907.6 MHz
LTE Band 12	Data	699.7 - 715.3 MHz
LTE Band 17	Data	706.5 - 713.5 MHz
LTE Band 13	Data	779.5 - 784.5 MHz
LTE Band 26	Data	814.7 - 848.3 MHz
LTE Band 5	Data	824.7 - 848.3 MHz
LTE Band 66	Data	1710.7 - 1779.3 MHz
LTE Band 4	Data	1710.7 - 1754.3 MHz
LTE Band 25	Data	1850.7 - 1914.3 MHz
LTE Band 2	Data	1850.7 - 1909.3 MHz
LTE Band 41	Data	2498.5 - 2687.5 MHz
NR Band n5	Data	826.5 - 846.5 MHz
NR Band n66	Data	1712.5 - 1777.5 MHz
NR Band n25	Data	1852.5 - 1912.5 MHz
NR Band n2	Data	1852.5 - 1907.5 MHz
NR Band n41	Data	2501.01 - 2685 MHz
NR Band n77	Data	3455.01 - 3544.98 MHz; 3705 - 3975 MHz
2.4 GHz WIFI	Data	2412 - 2472 MHz
5 GHz WIFI	Data	U-NII-1: 5180 - 5240 MHz U-NII-2A: 5260 - 5320 MHz U-NII-2C: 5500 - 5720 MHz U-NII-3: 5745 - 5825 MHz U-NII-4: 5845 - 5885 MHz
6 GHz WIFI	Data	U-NII-5: 5935 - 6415 MHz U-NII-6: 6435 - 6515 MHz U-NII-7: 6535 - 6875 MHz U-NII-8: 6895 - 7115 MHz
2.4 GHz Bluetooth	Data	2402 - 2480 MHz

This device uses the MediaTek TAS feature to control and manage transmitting power in real time and to ensure at all times the time-averaged RF exposure is in compliance with the FCC requirement for 2G/3G/4G/5G operations. Additionally, this device supports WLAN/BT technologies but the output power of these modems is not controlled by the TAS algorithm.

FCC ID: A3LSMX736B	COMPLIANCE SUMMARY REPORT	Approved by: Technical Manager
Document S/N: 1M2505130050-21.A3L	DUT Type: Portable Computing Device	Page 8 of 9

REV 1.1
04/11/2022

4 COMPLIANCE SUMMARY

4.1 RF Exposure Compliance Summary

All transmission scenarios that the DUT supports comply with FCC time-averaged RF exposure requirements, as shown in Table 4-1.

Table 4-1
Reported RF Exposure Levels

	RFx Evaluation	Power Level	FCC Limit	<i>Reported</i> RF Exposure Level	Test Report
SAR (W/kg)	Standalone 1g SAR	P_{limit}	1.6	1.00	FCC SAR Evaluation Report (Part 1)
	Simultaneous Tx 1g SAR	P_{limit}	1.6	1.59	

FCC ID: A3LSMX736B	COMPLIANCE SUMMARY REPORT	Approved by: Technical Manager
Document S/N: 1M2505130050-21.A3L	DUT Type: Portable Computing Device	Page 9 of 9

REV 1.1
04/11/2022