

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW is set depending on measurement frequency, as specified in Table 7-9 below
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Frequency	RBW
9 – 150kHz	200 – 300Hz
0.15 – 30MHz	9 – 10kHz
30 – 1000MHz	100 – 120kHz
> 1000MHz	1MHz

Table 7-9. RBW as a Function of Frequency

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-6. Radiated Test Setup >1GHz

FCC ID: A3LSMX930 IC: 649E-SMX930	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2505130048-02.A3L	Test Dates: 05/13/2025 - 07/01/2025	EUT Type: Portable Tablet	Page 76 of 89

Test Notes

1. The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of ANSI C63.10:2020 Section 11.12.2 were not used to evaluate this device for compliance to radiated limits. All radiated spurious emissions levels were measured in a radiated test setup.
2. All emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-8.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Average measurements were recorded using a VBW of 3kHz, per Section 4.1.4.2.3 of ANSI C63.10:2020, since 1/T is equal to just under 3kHz. This method was used because the EUT could not be configured to operate with a duty cycle > 98%. Both average and peak measurements were made using a peak detector
6. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. No significant radiated band edge emissions were found in the 2310 – 2390MHz restricted band.
8. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level $_{[dB_{\mu V/m}]} = \text{Analyzer Level}_{[dBm]} + 107 + \text{AFCL}_{[dB/m]}$
- $\text{AFCL}_{[dB/m]} = \text{Antenna Factor}_{[dB/m]} + \text{Cable Loss}_{[dB]}$
- $\text{Margin}_{[dB]} = \text{Field Strength Level}_{[dB_{\mu V/m}]} - \text{Limit}_{[dB_{\mu V/m}]}$


Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots in Section 0 was calculated using the formula:
Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain


FCC ID: A3LSMX930 IC: 649E-SMX930	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2505130048-02.A3L	Test Dates: 05/13/2025 - 07/01/2025	EUT Type: Portable Tablet	Page 77 of 89

Radiated Spurious Emission Measurements – Ant 1


§15.205 §15.209 §15.247(d)



Plot 7-101. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 0) – Ant 1



Plot 7-102. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 19) – Ant 1



Plot 7-103. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 39) – Ant 1

FCC ID: A3LSMX930 IC: 649E-SMX930	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2505130048-02.A3L	Test Dates: 05/13/2025 - 07/01/2025	EUT Type: Portable Tablet	Page 78 of 89



Radiated Spurious Emission Measurements – Antenna 1

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]

Bluetooth Mode: LE
Distance of Measurements: 3 Meters
Operating Frequency: 2402MHz
Channel: 0

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4804.00	Avg	V	-	-	-80.40	9.57	36.17	53.98	-17.81
4804.00	Peak	V	-	-	-68.59	9.57	47.98	73.98	-26.00
12010.00	Avg	V	-	-	-82.85	21.98	46.13	53.98	-7.85
12010.00	Peak	V	-	-	-72.15	21.98	56.83	73.98	-17.15

Table 7-10. Radiated Measurements @ 3 meters

Bluetooth Mode: LE
Distance of Measurements: 3 Meters
Operating Frequency: 2440MHz
Channel: 19

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4880.00	Avg	V	-	-	-80.11	9.53	36.42	53.98	-17.56
4880.00	Peak	V	-	-	-68.27	9.53	48.26	73.98	-25.72
7320.00	Avg	V	-	-	-81.79	15.34	40.55	53.98	-13.43
7320.00	Peak	V	-	-	-70.94	15.34	51.40	73.98	-22.58
12200.00	Avg	V	-	-	-83.72	22.76	46.04	53.98	-7.94
12200.00	Peak	V	-	-	-72.57	22.76	57.19	73.98	-16.79

Table 7-11. Radiated Measurements @ 3 meters

FCC ID: A3LSMX930 IC: 649E-SMX930	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2505130048-02.A3L	Test Dates: 05/13/2025 - 07/01/2025	EUT Type: Portable Tablet	Page 79 of 89



Radiated Spurious Emission Measurements – Antenna 1

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]

Bluetooth Mode: LE
Distance of Measurements: 3 Meters
Operating Frequency: 2480MHz
Channel: 39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4960.00	Avg	V	-	-	-80.39	10.34	36.95	53.98	-17.03
4960.00	Peak	V	-	-	-69.20	10.34	48.14	73.98	-25.84
7440.00	Avg	V	-	-	-81.92	15.34	40.42	53.98	-13.56
7440.00	Peak	V	-	-	-70.51	15.34	51.83	73.98	-22.15
12400.00	Avg	V	-	-	-83.71	22.92	46.21	53.98	-7.77
12400.00	Peak	V	-	-	-72.61	22.92	57.31	73.98	-16.67


Table 7-12. Radiated Measurements @ 3 meters

FCC ID: A3LSMX930 IC: 649E-SMX930	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2505130048-02.A3L	Test Dates: 05/13/2025 - 07/01/2025	EUT Type: Portable Tablet	Page 80 of 89




Radiated Spurious Emission Measurements – Antenna 2


§15.205 §15.209 §15.247(d)



Plot 7-104. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 0)



Plot 7-105. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 19)



Plot 7-106. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 39)

FCC ID: A3LSMX930 IC: 649E-SMX930		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2505130048-02-A3L	Test Dates: 05/13/2025 - 07/01/2025	EUT Type: Portable Tablet		Page 81 of 89



Radiated Spurious Emission Measurements – Antenna 2

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]

Bluetooth Mode: LE
Distance of Measurements: 3 Meters
Operating Frequency: 2402MHz
Channel: 0

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4804.00	Avg	V	-	-	-80.60	9.57	35.97	53.98	-18.01
4804.00	Peak	V	-	-	-68.91	9.57	47.66	73.98	-26.32
12010.00	Avg	V	-	-	-82.89	21.98	46.09	53.98	-7.89
12010.00	Peak	V	-	-	-72.02	21.98	56.96	73.98	-17.02

Table 7-13. Radiated Measurements @ 3 meters

Bluetooth Mode: LE
Distance of Measurements: 3 Meters
Operating Frequency: 2440MHz
Channel: 19

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4880.00	Avg	V	-	-	-80.25	9.53	36.28	53.98	-17.70
4880.00	Peak	V	-	-	-69.38	9.53	47.15	73.98	-26.83
7320.00	Avg	V	-	-	-81.74	15.34	40.60	53.98	-13.38
7320.00	Peak	V	-	-	-70.31	15.34	52.03	73.98	-21.95
12200.00	Avg	V	-	-	-83.64	22.76	46.12	53.98	-7.86
12200.00	Peak	V	-	-	-72.70	22.76	57.06	73.98	-16.92

Table 7-14. Radiated Measurements @ 3 meters

FCC ID: A3LSMX930 IC: 649E-SMX930	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2505130048-02.A3L	Test Dates: 05/13/2025 - 07/01/2025	EUT Type: Portable Tablet	Page 82 of 89



Radiated Spurious Emission Measurements – Antenna 2

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]

Bluetooth Mode: LE
Distance of Measurements: 3 Meters
Operating Frequency: 2480MHz
Channel: 39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4960.00	Avg	V	-	-	-80.61	10.34	36.73	53.98	-17.25
4960.00	Peak	V	-	-	-69.73	10.34	47.61	73.98	-26.37
7440.00	Avg	V	-	-	-81.92	15.34	40.42	53.98	-13.56
7440.00	Peak	V	-	-	-70.65	15.34	51.69	73.98	-22.29
12400.00	Avg	V	-	-	-83.32	22.92	46.60	53.98	-7.38
12400.00	Peak	V	-	-	-72.40	22.92	57.52	73.98	-16.46

Table 7-15. Radiated Measurements @ 3 meters

FCC ID: A3LSMX930 IC: 649E-SMX930	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2505130048-02.A3L	Test Dates: 05/13/2025 - 07/01/2025	EUT Type: Portable Tablet	Page 83 of 89



7.8 Radiated Restricted Band Edge Measurements


§15.205 §15.209; RSS-Gen [8.9]

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.


The amplitude offset shown in the following plots for average measurements was calculated using the formula:

Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

Bluetooth Mode:	LE
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	39



Plot 7-107. Radiated Restricted Upper Band Edge Measurement (Average) – Ant 1



Plot 7-108. Radiated Restricted Upper Band Edge Measurement (Peak) – Ant 1


FCC ID: A3LSMX930 IC: 649E-SMX930		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2505130048-02.A3L	Test Dates: 05/13/2025 - 07/01/2025	EUT Type: Portable Tablet		Page 84 of 89

© 2025 ELEMENT


Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

V11.3 5/14/2025

Bluetooth Mode: LE
 Measurement Distance: 3 Meters
 Operating Frequency: 2480MHz
 Channel: 39



Plot 7-109. Radiated Restricted Upper Band Edge Measurement (Average) – Ant 2



Plot 7-110. Radiated Restricted Upper Band Edge Measurement (Peak) – Ant 2

FCC ID: A3LSMX930 IC: 649E-SMX930	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2505130048-02.A3L	Test Dates: 05/13/2025 - 07/01/2025	EUT Type: Portable Tablet	Page 85 of 89

7.9 Line-Conducted Test Data

§15.207; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-16. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10:2020, Section 6.2

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMX930 IC: 649E-SMX930	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2505130048-02.A3L	Test Dates: 05/13/2025 - 07/01/2025	EUT Type: Portable Tablet	Page 86 of 89

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-7. Test Instrument & Measurement Setup


Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in Part 15.207 and RSS-Gen (8.8).
3. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5. $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: A3LSMX930 IC: 649E-SMX930	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2505130048-02.A3L	Test Dates: 05/13/2025 - 07/01/2025	EUT Type: Portable Tablet	Page 87 of 89



Plot 7-111. Line Conducted Plot with Bluetooth LE (L1)



Plot 7-112. Line Conducted Plot with Bluetooth LE (N)

FCC ID: A3LSMX930 IC: 649E-SMX930	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2505130048-02-A3L	Test Dates: 05/13/2025 - 07/01/2025	EUT Type: Portable Tablet	Page 88 of 89

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Tablet FCC ID: A3LSMX930, IC: 649E-SMX930** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules and RSS-247 of the ISED Canada Rules.

FCC ID: A3LSMX930 IC: 649E-SMX930	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2505130048-02.A3L	Test Dates: 05/13/2025 - 07/01/2025	EUT Type: Portable Tablet	Page 89 of 89