PCTEST Engineering Laboratory, Inc.

6660-B Dobbin Road • Columbia, MD 21045 • U.S.A.
TEL (410) 290-6652 • FAX (410) 290-6654
http://www.pctestlab.com

CERTIFICATE OF COMPLIANCE

SAMSUNG Electronics Co., Ltd..
416, Maetan-3 Dong, Paldal-Gu, Suwon City
Kyungki-Do, 442-742, KOREA
Attention: Mr. SC Lee

Dates of Tests: June 10-11, 2002
Test Report S/N: 15.220401178.A3L
Test Site: PCTEST Lab, Columbia MD

FCC ID	**A3LSP10BT**
APPLICANT	**SAMSUNG Electronics Co., Ltd..**

FCC Rule Part(s):	**§ 15.247; ANSI C-63.4 (1992)**
Classification:	**Spread Spectrum Transceiver (DSS)**
Max Output Power:	**0.293mWEIRP**
Method/System:	**Direct Sequence System (DSS)**
Equipment Type:	**Laptop w/ Bluetooth Module**
Frequency Range:	**2400 – 2483.5 MHz**
Model No(s).:	**SWB-1000m**

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C-63-4.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

Randy Ortanez
President

TABLE OF CONTENTS

ATTACHMENT A- COVER LETTER
ATTACHMENT B- ATTESTATION STATEMENT
ATTACHMENT C- TEST REPORT

SCOPE 3

INTRODUCTION (SITE DESCRIPTION) 4

PRODUCT INFORMATION 5

DESCRIPTION OF TESTS

A. CONDUCTED EMISSIONS 6
B. RADIATED EMISSIONS 7
C. RESTRICTED BANDS 8
D. ANTENNA REQUIREMENT 9
E. DIRECT SEQUENCE BANDWIDTH 10
F. MAXIMUM PEAK POWER OUTPUT 11
G. POWER DENSITY 12

RADIATED MEASUREMENTS (FUNDAMENTAL & HARMONICS) 13-15

FREQUENCY MEASUREMENTS (SPURIOUS) 16

LIST OF TEST EQUIPMENT 17

CONCLUSION 18

ATTACHMENT D- TEST PLOTS
ATTACHMENT E- FCC ID LABEL & LOCATION
ATTACHMENT F- TEST SET-UP PHOTOGRAPHS
ATTACHMENT G- EXTERNAL PHOTOGRAPHS
ATTACHMENT H- INTERNAL PHOTOGRAPHS
ATTACHMENT I- BLOCK DIAGRAM(S)
ATTACHMENT J- SCHEMATIC DIAGRAM(S)
ATTACHMENT K- OPERATIONAL DESCRIPTION
ATTACHMENT L- USER'S MANUAL
ATTACHMENT M- SAR MPE REPORT

MEASUREMENT REPORT



Scope - Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.



§2983(a) General Information

Applicant Name:	**SAMSUNG Electronics Co., Ltd.**
Address:	**416, Maetan-3 Dong, Paldal-Gu, Suwon City Kyungki-Do, 442-742, KOREA**
Attention:	**Mr. S.C Lee**

- FCC ID: **A3LSP10BT**
- Class: Spread Spectrum Transceiver (DSS)
- Type: Laptop w/ Bluetooth Module
- Freq. Range: 2401.5 – 2470.5 MHz
- Method/System: Blluetooth
- Model No(s): **SWB-1000m**
- Max. RF Output Power: 0.293mW
- Power Supply: AC Adapter Model: AD-8019
- Cable(s): Telco
- Rule Part(s): § 15.247
- Dates of Tests: June 10-11, 2002
- Place of Tests: PCTEST Lab, Columbia, MD U.S.A.
- Test Report S/N: 220401178.A3L

NOTE: The receiver portion was tested and complies with Part 15B under the verification procedure.

INTRODUCTION

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-1992) and FCC Public Notice dated July 12, 1995 entitled "Guidance on Measurement for Direct Sequence Spread Spectrum Systems" were used in the measurement of **Samsung Spread Spectrum** laptop w/ bluetooth module**.**

These measurement tests were conducted at ***PCTEST Engineering Laboratory, Inc.*** facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on October 19, 1992.

PCTEST Location

The map at right shows the location of the PCTEST Lab, its proximity to the FCC Lab, the Columbia vicinity area, the Baltimore-Washington International (BWI) airport, and the city of Baltimore, and the Washington, D.C. area. (see Figure1).



Figure 1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area.

PRODUCT INFORMATION

Equipment Description:

The Equipment under test (EUT) is the **Samsung Laptop w/ Bluetooth Module** using spread spectrum direct sequence and time division duplex techniques.

Frequency Range:	2401.5 – 2470.5 MHz
Channels:	24
Spread Spectrum Method:	DSS (Bluetooth)
Max RF Output Power:	0.293 mW

CH	Rx/Tx Freq. (MHz)	CH	Rx/Tx Freq. (MHz)	CH	Rx/Tx Freq. (MHz)
1	2401.5	9	2425.5	17	2449.5
2	2404.5	10	2428.5	18	2452.5
3	2407.5	11	2431.5	19	2455.5
4	2410.5	12	2434.5	20	2458.5
5	2413.5	13	2437.5	21	2461.5
6	2416.5	14	2440.5	22	2464.5
7	2419.5	15	2443.5	23	2467.5
8	2422.5	16	2446.5	24	2470.5

Description of Tests



Figure 4. Shielded Enclosure Line-Conducted Test Facility



Figure 2. Line Conducted Emission Test Set-Up



Figure 3. Wooden Table & Bonded LISNs



Figure 5. LISN Schematic Diagram

Conducted Emissions

The line-conducted facility is located inside a 16'x20'x10' shielded enclosure. It is manufactured by Ray Proof Series 81 (see Figure 2). The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-6. A 1m. x 1.5m. wooden table 80cm. high is placed 40cm. away from the vertical wall and 1.5m away from the side wall of the shielded room (see Figure 3). Solar Electronics and EMCO Model 3725/2 (10kHz-30MHz) 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room (see Figure 4). The EUT is powered from the Solar LISN and the support equipment is powered from the EMCO LISN. Power to the LISNs are filtered by a high-current high-insertion loss Ray Proof power line filters (100dB 14kHz-10GHz). The purpose of the filter is to attenuate ambient signal interference and this filter is also bonded to the shielded enclosure. All electrical cables are shielded by braided tinned copper zipper tubing with inner diameter of 1/2". If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the Solar LISN. LISN schematic diagram is shown in Figure 5. All interconnecting cables more than 1 meter were shortened by non-inductive bundling (serpentine fashion) to a 1-meter length. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT. The spectrum was scanned from 450kHz to 30MHz with 20 msec. sweep time. The frequency producing the maximum level was reexamined using EMI/ Field Intensity Meter and Quasi-Peak adapter. The detector function was set to CISPR quasi-peak mode. The bandwidth of the receiver was set to 10 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission. Each emission was maximized by: switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/or support equipment, and powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable; whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in Appendix C. Each EME reported was calibrated using the HP8640B signal generator.

Description of Tests (Continued)



Figure 6. 3-Meter Test Site



Figure 7. Dimensions of Outdoor Test Site



Figure 8. Turntable and System Setup



Figure 9. Normalized Site Attenuation Curves (H&V)

Radiated Emissions

Preliminary measurements were made indoors at 1 meter using broadband antennas, broadband amplifier, and spectrum analyzer to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, turntable azimuth with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30 to 200 MHz using biconical antenna and from 200 to 1000 MHz using log-spiral antenna. Above 1 GHz, linearly polarized double ridge horn antennas were used.

Final measurements were made outdoors at 3-meter test range using Roberts™ Dipole antennas or horn antenna (see Figure 6). The test equipment was placed on a wooden and plastic bench situated on a 1.5 x 2 meter area adjacent to the measurement area (see Figure 7). Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined and investigated using EMI/Field Intensity Meter and Quasi-Peak Adapter. The detector function was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 100kHz or 1 MHz depending on the frequency or type of signal.

The half-wave dipole antenna was tuned to the frequency found during preliminary radiated measurements. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8-meter high non-metallic 1 x 1.5 meter table (see Figure 8). The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each EME emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by: varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/or support equipment, and powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable; and changing the polarity of the antenna, whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in Appendix C. Each EME reported was calibrated using the HP8640B signal generator. The Theoretical Normalized Site Attenuation Curves for both horizontal and vertical polarization are shown in Figure 9.

§ 15.205 Restricted Bands

Special attention is made for the EUT's harmonic and spurious radiated emission in the restricted bands of operation. The EUT was tested from 9kHz and up to the tenth harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average measurements was used using RBW 1 MHz – VBW 10Hz and linearly polarized horn antennas. In addition, peak measurements were taken to ensure that the peak levels are not more than 20dB above the average limit. All out of band emissions, other than those created by the spreading sequency, data sequence, and the carrier modulation must not exceed the limits show int Table 2 per 15.209.

Frequency (MHz)	F/S (UV/m)	Meas. Dist. (Meters)
0.009-0.490	2400/F (kHz)	300
0.490-1.705	24000/F (kHz)	30
1.705-30.00	30	30
30.0-88.0	100	3
88.0-216.0	150	3
216.0-960.0	200	3
Above 960	500	3

Tab. 2. Radiated Emission Limits Per 15.209

Test Equipment

HP 8566B	**Spectrum Analyzer 100Hz-22HGHz**
HP83017A	**Microwave Analyzer 40dB Gain (0.5 – 26.5 GHz)**
HP 3784A	**Digital Transmission Analyzer**
EMCO 3115	**Horn Antenna (1 – 18GHz)**
HP 8495A	**20dB Attenuator (DC-40GHz) 0-70dB**
HP 8493B	**10dB Attenuator**
MicroCoax Cables	**Low Loss Microwave Cables (1-26.5 GHz)**
CDI Dipoles	**Dipole Antennas (30 – 1000 MHz)**

§ 15.203 Antenna Requirement

An intentional radiator antenna shall be designed to ensure that no antenna other that that furnished by the applicant can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with this requirement.

The SAMSUNG **SWB-1000M** unit complies with the requirement of §15.203. The antenna is a **permanently attached omni-directional antenna.**

CONCLUSION

There are no provisions for connection to an external antenna. The unit meets the Antenna Requirements of §15.203.

§15.247(a)(2) – Direct Sequence Bandwidth

Minimum Standard – 6dB bandwidth for direct sequence systems must be at least 500Hz (0.5 MHz).

Res. Bandwidth =	100 kHz (7dB/div)
Vid. BW =	100 kHz
Span =	5 MHz
Ref. Level	- 45 dBm
Sweep	5ms
Attenuator	0 dB ext. pad
20dB Bandwidth –Mkr Delta	**(20dB down from peak)**

(see attached spectrum plots)

FREQ (MHz)	Channel	20dB Bandwidth (MHz)
2402	1	0.855
2441	40	0.893
2480	79	0.885

Table 3. 20dB Bandwidth measurements

REMARKS:

PASS

§15.247(b) Maximum Peak Output Power

Minimum Standard – The maximum peak output power of the transmitter shall not exceed 1 watt.

Res. Bandwidth =	3 MHz (10dB/div)
Vid. BW =	3 MHz
Span =	10 MHz
Ref. Level	-22 dBm
Sweep	5 ms sec
Attenuator	0 dB ext. pad

Max. Power Peak + Atten = dBm ⇒ Watts

FREQ (MHz)	Channel	Power Output (dBm)	Power Output (mW)
2402	1	- 5.70	0.267
2441	40	- 5.80	0.261
2480	79	- 5.32	0.293

Table 4. Output Power Measurements

REMARKS:

PASS

§15.247(c) Power Density

Minimum Standard – The transmitted power density averaged over any 1 second interval shall not be greater than 8dBm in any 3kHz bandwidth within these bands.

Res. Bandwidth =	3 kHz (10dB/div)
Vid. BW =	3 kHz
Span =	300 kHz (3.0 MHz)
Ref. Level	- 22 dBm
Sweep	1000 sec

Peak + Atten = dBm ⇒ (Limit < 8dBm)

FREQ (MHz)	Channel	Power Density (dBm)
2401	1	- 19.5
2441	40	- 19.0
2480	79	- 19.1

Table 5. Output Power Density Data.

REMARKS:

PASS

RADIATED Measurements (Fundamental & Harmonics)

A. Transmitter Portion

Operating Frequency: 2402 MHz

Distance of Measurements: 3 meters

Channel: 1

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	DET QP/AVG	F/S (µV/m)	F/S (dBµV/m)	Margin (dB)
2402	- 50.2	32.7	V	Peak	29853.8	89.5	n/a
4804	- 97.0	40.4	V	Peak	330.75	50.39	3.61
7206	- 104.8	47.4	V	Peak	302.691	49.62	39.88
9608	< - 120						
12010	< - 120						



Figure 10. Restricted band harmonics and spurious limits.

Above 1 GHz limit is 500 uV/m (54dBu/m)

NOTES:

1. All harmonics in the restricted bands specified in §15.205 are below the limit shown in table 2. (note: * Restricted Band)

2. All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz

3. Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz

4. The peak emissions above 1 GHz are not more than 20 dB above the average limit.

5. The antenna is manipulated through typical positions, polarity and length during the tests.

6. The EUT is supplied with nominal AC voltage or/and a new/fully recharged battery.

7. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported.

8. < - 120 are below the analyzer floor level.

RADIATED Measurements (Fundamental & Harmonics) (CONT.)

B. Transmitter Portion

Operating Frequency: 2441 MHz

Distance of Measurements: 3 meters

Channel: 40

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	DET QP/AVG	F/S (µV/m)	F/S (dBµV/m)	Margin (dB)
2441	- 50.4	32.8	V	Peak	29512.1	89.4	n/a
4882	- 97.5	40.5	V	Peak	316.228	50.0	4.0
7323	- 104.9	48.0	V	Peak	319.890	50.1	3.9
9764	< - 120						
12205	< - 120						



Figure 11. Restricted band harmonics and spurious limits.

Above 1 GHz limit is 500 uV/m (54dBu/m)

NOTES:

1. All harmonics in the restricted bands specified in §15.205 are below the limit shown in table 2. (note: * Restricted Band)

2. All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz

3. Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz

4. The peak emissions above 1 GHz are not more than 20 dB above the average limit.

5. The antenna is manipulated through typical positions, polarity and length during the tests.

6. The EUT is supplied with nominal AC voltage or/and a new/fully recharged battery.

7. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported.

8. < - 120 are below the analyzer floor level.

RADIATED Measurements (Fundamental & Harmonics) (CONT.)

C. Transmitter Portion (Base)

Operating Frequency: 2480 MHz

Distance of Measurements: 3 meters

Channel: 79

FREQ. (MHz)	Level* (dBm)	AFCL (dB)	POL (H/V)	DET QP/AVG	F/S (µV/m)	F/S (dBµV/m)	Margin (dB)
2480	- 50	32.9	V	Peak	31260.8	89.9	n/a
4960	- 98	40.7	V	Peak	305.492	49.7	4.3
7440	- 105	48.2	V	Peak	323.594	50.2	3.8
9920	< - 120						
12400	< - 120						



Figure 12. Restricted band harmonics and spurious limits.

Above 1 GHz limit is 500 uV/m (54dBu/m)

NOTES:

1. All harmonics in the restricted bands specified in §15.205 are below the limit shown in table 2. (note: * Restricted Band)

2. All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz

3. Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz

4. The peak emissions above 1 GHz are not more than 20 dB above the average limit.

5. The antenna is manipulated through typical positions, polarity and length during the tests.

6. The EUT is supplied with nominal AC voltage or/and a new/fully recharged battery.

7. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported.

8. < - 120 are below the analyzer floor level.

RADIATED Measurements (Spurious)

Transmitter Portion

Operating Frequency: 2402 – 2480 MHz

Distance of Measurements: 3 meters

Channels: 1, 40, 79

FREQ. (MHz)	Level* (dBμV/m)	AFCL** (dB)	POL (H/V)	Height (m)	Azimuth (° angle)	F/S (dBμV/m)	Margin*** (dB)
66.60	- 81.72	5.820	V	3.6	80	35.940	- 8.9
120.3	- 83.02	11.52	V	3.0	90	59.620	- 8.0
166.0	- 89.16	14.66	H	1.4	210	42.220	- 11.0
400.0	- 93.90	23.70	V	2.4	10	69.230	- 9.2
440.1	- 93.86	24.66	V	2.3	180	77.670	- 8.2
666.7	- 94.31	29.32	V	1.2	200	125.94	- 4.0



Figure 13. Restricted band harmonics and spurious limits.

NOTES:

1.All emissions were investigated and the worst case emissions are reported

2. For hand-held devices, the EUT is rotated through three orthogonal axis to determine which configuration produces the maximum emissions

3. The EUT is supplied with the minimal AC voltage or/and a new/fully recharged battery.

4. The EUT was tested up to the 10th harmonic (9.3 GHz) and no significant emission was found.

Above 1 GHz limit is 500 uV/m (54dBu/m)

TEST EQUIPMENT

Type	Model	Cal. Due Date	S/N
Microwave Spectrum Analyzer	HP 8566B (100Hz-22GHz)	12/05/02	3638A08713
Microwave Spectrum Analyzer	HP 8566B (100Hz-22GHz)	04/17/03	2542A11898
Spectrum Analyzer/Tracking Gen.	HP 8591A (9kHz-1.8GHz)	06/02/02	3144A02458
Spectrum Analyzer	HP 8591A (9kHz-1.8GHz)	10/15/02	3108A02053
Spectrum Analyzer	HP 8594A (9kHz-2.9GHz)	11/02/02	3051A00187
Signal Generator*	HP 8640B (500Hz-1GHz)	06/02/02	2232A19558
Signal Generator*	HP 8640B (500Hz-1GHz)	06/02/02	1851A09816
Signal Generator*	Rohde & Schwarz (0.1-1000MHz)	09/11/02	894215/012
Ailtech/Eaton Receiver	NM 37/57A-SL (30-1000MHz)	04/12/03	0792-03271
Ailtech/Eaton Receiver	NM 37/57A (30-1000MHz)	03/11/03	0805-03334
Ailtech/Eaton Receiver	NM 17/27A (0.1-32MHz)	09/17/02	0608-03241
Quasi-Peak Adapter	HP 85650A	08/09/02	2043A00301
Ailtech/Eaton Adapter	CCA-7 CISPR/ANSI QP Adapter	03/11/03	0194-04082
RG58 Coax Test Cable	No. 167		n/a
Harmonic/Flicker Test System	HP 6841A (IEC 555-2/3)		3531A00115
Broadband Amplifier (2)	HP 8447D		1145A00470, 1937A03348
Broadband Amplifier	HP 8447F		2443A03784
Transient Limiter	HP 11947A (9kHz-200MHz)		2820A00300
Horn Antenna	EMCO Model 3115 (1-18GHz)		9704-5182
Horn Antenna	EMCO Model 3115 (1-18GHz)		9205-3874
Horn Antenna	EMCO Model 3116 (18-40GHz)		9203-2178
Biconical Antenna (4)	Eaton 94455/Eaton 94455-1/Singer 94455-1/Compliance Design		1295, 1332, 0355
Log-Spiral Antenna (3)	Ailtech/Eaton 93490-1		0608, 1103, 1104
Roberts Dipoles	Compliance Design (1 set) A100		5118
Ailtech Dipoles	DM-105A (1 set)		33448-111
EMCO LISN (2)	3816/2		1077, 1079
EMCO LISN	3725/2		2009
Microwave Preamplifier 40dB Gain	HP 83017A (0.5-26.5GHz)		3123A00181
Microwave Cables	MicroCoax (1.0-26.5GHz)		
Ailtech/Eaton Receiver	NM37/57A-SL		0792-03271
Spectrum Analyzer	HP 8591A		3034A01395
Modulation Analyzer	HP 8901A		2432A03467
NTSC Pattern Generator	Leader 408		0377433
Noise Figure Meter	HP 8970B		3106A02189
Noise Figure Meter	Ailtech 7510		TE31700
Noise Generator	Ailtech 7010		1473
Microwave Survey Meter	Holaday Model 1501 (2.450GHz)		80931
Digital Thermometer	Extech Instruments 421305		426966
Attenuator	HP 8495A (0-70dB) DC-4GHz		
Bi-Directional Coax Coupler	Narda 3020A (50-1000MHz)		
Shielded Screen Room	RF Lindgren Model 26-2/2-0		6710 (PCT270)
Shielded Semi-Anechoic Chamber	Ray Proof Model S81		R2437 (PCT278)
Environmental Chamber	Associated Systems Model 1025 (Temperature/Humidity)		PCT285

* Calibration traceable to the National Institute of Standards and Technology (NIST).

Conclusion

The data collected shows that the **SAMSUNG Laptop w/ Bluetooth Module FCC ID: A3LSP10BT** complies with Part 15C of the FCC Rules.