PCTEST ENGINEERING LABORATORY, INC.

6660 – B Dobbin Road • Columbia, MD 21045 • USA
Telephone 410.290.6652 / Fax 410.290.6654
http://www.pctestlab.com (email: randy@pctestlab.com)

CERTIFICATE OF COMPLIANCE (SAR EVALUATION)

APPLICANT NAME & ADDRESS:
Samsung Electronics Co., Ltd.
416 Maetan-3 Dong, Paldal-Ku
Suwon City Kyungki-Do 441-742, KOREA
Attn: Wallace Oh

DATE & LOCATION OF TESTING:
Dates of Tests: Mar. 21-22, 27-28, & Apr. 8, 2002
Test Report S/N: SAR.220322121.A3L
Test Site: PCTEST Lab, Columbia, MD USA

FCC ID:	**A3LSPHA500**
APPLICANT:	**Samsung Electronics Co., Ltd.**

EUT Type:	**Tri-Mode Dual-Band Analog/PCS Phone (AMPS/CDMA)**
Tx Frequency:	**824.04 – 848.97 MHz (AMPS) / 824.70 – 848.31 MHz (CDMA)** **1851.25 – 1908.75 MHz (PCS CDMA)**
Rx Frequency:	**869.04 – 893.97 MHz (AMPS) / 869.70 – 893.31 MHz (CDMA)** **1931.25 – 1988.75 MHz (PCS CDMA)**
Max. RF Output Power:	**0.319W ERP AMPS (25.033dBm) / 26.0 dBm Conducted** **0.284W ERP Cellular CDMA (24.533dBm) / 25.5 dBm Conducted** **0.355W EIRP PCS CDMA (25.501dBm) / 24.5 dBm Conducted**
Max. SAR Measurement:	**1.10W/kg AMPS Head SAR; 0.62W/kg AMPS Body SAR;** **1.05W/kg Cell. CDMA Head SAR; 0.53W/kg Cell. CDMA Body SAR;** **1.33W/kg PCS CDMA Head SAR; 0.34W/kg PCS CDMA Body SAR**
Trade Name/Model(s):	***SPH-A500***
FCC Classification:	**Licensed Portable Transmitter Held to Ear (PCE)**
FCC Rule Part(s):	**§2.1093; FCC/OET Bulletin 65 Supplement C [July 2001]**
Application Type:	**Certification**
Test Device Serial No.:	***Identical* prototype**

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE Std. C95.1-1992 and had been tested in accordance with the measurement procedures specified in FCC/OET Bulletin 65 Supplement C (2001) and IEEE Std. 1528-200X (Draft 6.4, July 2001).

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

Randy Ortanez
President

© 2002 PCTEST Engineering Laboratory, Inc.

12. SYSTEM VERIFICATION

Tissue Verification

Table 12.1 Simulated Tissue Verification

MEASURED TISSUE PARAMETERS									
Date(s)	3/15/2002	835MHz Brain		835MHz Muscle		1900MHz Brain		1900MHz Muscle	
Liquid Temperature (°C)	22.0	Target	Measured	Target	Measured	Target	Measured	Target	Measured
Dielectric Constant: ε		41.50	43.44	55.20	55.54	40.00	40.29	53.30	53.95
Conductivity: σ		0.90	0.87	0.97	0.99	1.40	1.44	1.520	1.53

Test System Validation

Prior to assessment, the system is verified to the ±10% of the specifications at 835MHz and 1900MHz by using the system validation kit(s). (Graphic Plots Attached)

Table 12.2 System Validation

	SYSTEM DIPOLE VALIDATION TARGET & MEASURED			
System Validation Kit: D-835S, S/N: 103	835MHz Brain	Targeted SAR_{1g} (mW/g) 2.375	Measured SAR_{1g} (mW/g) **2.37**	Deviation (%) **- 0.2**
System Validation Kit: D-1900S, S/N: 104	1900MHz Brain	Targeted SAR_{1g} (mW/g) 9.925	Measured SAR_{1g} (mW/g) **10.41**	Deviation (%) **+ 4.7**



Figure 12.1 Dipole Validation Test Setup

© 2002 PCTEST Engineering Laboratory, Inc.

13. SAR TEST DATA SUMMARY

See Measurement Result Data Pages

Procedures Used To Establish Test Signal

The handset was placed into simulated call mode (AMPS, Cellular CDMA & PCS CDMA modes) using manufacturers test codes. Such test signals offer a consistent means for testing SAR and are recommended for evaluating SAR [4]. When test modes are not available or inappropriate for testing a handset, the actual transmission is activated through a base station simulator or similar equipment. See data pages for actual procedure used in measurement.

Device Test Conditions

The handset is battery operated. Each SAR measurement was taken with a fully charged battery. In order to verify that the device was tested at full power, conducted output power measurements were performed before and after each SAR measurement to confirm the output power. If a conducted power deviation of more than 5% occurred, the test was repeated.

EUT Handset Reference Points



Figure 13.1 Handset Reference Points

© 2002 PCTEST Engineering Laboratory, Inc.

SAR DATA SUMMARY

Mixture Type: 835MHz Brain

14.1 MEASUREMENT RESULTS (AMPS Right Head SAR – Touch)

FREQUENCY		Modulation	Begin / End POWER‡			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
824.04	0991	AMPS	26.0	26.0	Standard	Cheek / Touch	In	**0.78**
824.04	0991	AMPS	26.0	26.0	Standard	Cheek / Touch	Out	**0.56**
836.49	0383	AMPS	26.0	26.0	Standard	Cheek / Touch	In	**1.03**
836.49	0383	AMPS	26.0	26.0	Standard	Cheek / Touch	Out	**0.86**
848.97	0799	AMPS	26.0	26.0	Standard	Cheek / Touch	In	**0.70**
848.97	0799	AMPS	26.0	26.0	Standard	Cheek / Touch	Out	**0.71**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Brain 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings. *Standard batteries are the only battery options.*

‡Power Measured	☒ Conducted	☐ ERP	☐ EIRP	
4. SAR Measurement System	☐ DASY3	☒ IDX		
Phantom Configuration	☐ Left Head	☐ Flat Phantom	☒ Right Head	
5. SAR Configuration	☒ Head	☐ Body	☐ Hand	
6. Test Signal Call Mode	☒ Manu. Test Codes	☐ Base Station Simulator		

7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15.1 cm. ± 0.1

Alfred Cirwithian
Vice President Engineering

Figure 14.1 Right Head SAR Test Setup
-- Cheek / Touch Position --

© 2002 PCTEST Engineering Laboratory, Inc.

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Brain

14.2 MEASUREMENT RESULTS (AMPS Right Head SAR – Tilt)

FREQUENCY		Modulation	Begin / End POWER‡			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
836.49	0383	AMPS	26.0	26.0	Standard	Ear / 15° Tilt	In	**0.23**
836.49	0383	AMPS	26.0	26.0	Standard	Ear / 15° Tilt	Out	**0.18**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Brain 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings. *Standard batteries are the only battery options.*
   ‡Power Measured ☒ Conducted ☐ ERP ☐ EIRP
4. SAR Measurement System ☐ DASY3 ☒ IDX
   Phantom Configuration ☐ Left Head ☐ Flat Phantom ☒ Right Head
5. SAR Configuration ☒ Head ☐ Body ☐ Hand
6. Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15.1 cm. ± 0.1
9. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July, 2001), if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tile/ear, extended and retracted) is at least 2.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).

Alfred Cirwithian
Vice President Engineering



Figure 14.5 Right Head SAR Test Setup -- Ear / 15° Tilt Position --

© 2002 PCTEST Engineering Laboratory, Inc.

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Brain

14.3 MEASUREMENT RESULTS (AMPS Left Head SAR - Touch)

FREQUENCY		Modulation	Begin / End POWER‡			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
824.04	0991	AMPS	26.0	26.0	Standard	Cheek / Touch	In	**1.10**
824.04	0991	AMPS	26.0	26.0	Standard	Cheek / Touch	Out	**0.57**
836.49	0383	AMPS	26.0	26.0	Standard	Cheek / Touch	In	**1.10**
836.49	0383	AMPS	26.0	26.0	Standard	Cheek / Touch	Out	**0.87**
848.97	0799	AMPS	26.0	26.0	Standard	Cheek / Touch	In	**0.91**
848.97	0799	AMPS	26.0	26.0	Standard	Cheek / Touch	Out	**0.78**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Brain 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings. *Standard batteries are the only battery options.*

‡Power Measured	☒ Conducted	☐ ERP	☐ EIRP	
4. SAR Measurement System	☐ DASY3	☒ IDX		
Phantom Configuration	☒ Left Head	☐ Flat Phantom	☐ Right Head	
5. SAR Configuration	☒ Head	☐ Body	☐ Hand	
6. Test Signal Call Mode	☒ Manu. Test Codes	☐ Base Station Simulator		

7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15.1 cm. ± 0.1

Alfred Cirwithian
Vice President Engineering

Figure 14.3 Left Head SAR Test Setup -- Cheek / Touch Position --

© 2002 PCTEST Engineering Laboratory, Inc.

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Brain

14.4 MEASUREMENT RESULTS (AMPS Left Head SAR – Tilt)

FREQUENCY		Modulation	Begin / End POWER‡			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
836.49	0383	AMPS	26.0	26.0	Standard	Ear / 15° Tilt	In	**0.22**
836.49	0383	AMPS	26.0	26.0	Standard	Ear / 15° Tilt	Out	**0.18**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Brain 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings. *Standard batteries are the only battery options.*

‡Power Measured	☒ Conducted	☐ ERP	☐ EIRP	
4. SAR Measurement System	☐ DASY3	☒ IDX		
Phantom Configuration	☒ Left Head	☐ Flat Phantom	☐ Right Head	
5. SAR Configuration	☒ Head	☐ Body	☐ Hand	
6. Test Signal Call Mode	☒ Manu. Test Codes	☐ Base Station Simulator		

7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15.1 cm. ± 0.1
9. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July, 2001), if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tile/ear, extended and retracted) is at least 2.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).

Alfred Cirwithian
Vice President Engineering

Figure 14.4 Left Head SAR Test Setup -- Ear / 15° Tilt Position --

© 2002 PCTEST Engineering Laboratory, Inc.

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Brain

14.5 MEASUREMENT RESULTS (CELLULAR CDMA Left Head SAR – Touch)

FREQUENCY		Modulation	Begin / End POWER‡			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
824.70	1013	CDMA	25.5	25.5	Standard	Cheek / Touch	In	**0.60**
824.70	1013	CDMA	25.5	25.5	Standard	Cheek / Touch	Out	**0.44**
836.49	383	CDMA	25.5	25.5	Standard	Cheek / Touch	In	**1.05**
836.49	383	CDMA	25.5	25.5	Standard	Cheek / Touch	Out	**0.67**
848.31	777	CDMA	25.5	25.5	Standard	Cheek / Touch	In	**0.80**
848.31	777	CDMA	25.5	25.5	Standard	Cheek / Touch	Out	**0.71**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Brain 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings. *Standard batteries are the only battery options.*

‡Power Measured	☒ Conducted	☐ ERP	☐ EIRP	
4. SAR Measurement System	☐ DASY3	☒ IDX		
Phantom Configuration	☒ Left Head	☐ Flat Phantom	☐ Right Head	
5. SAR Configuration	☒ Head	☐ Body	☐ Hand	
6. Test Signal Call Mode	☒ Manu. Test Codes	☐ Base Station Simulator		

7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15.1 cm. ± 0.1

Alfred Cirwithian
Vice President Engineering

Figure 14.5 Left Head SAR Test Setup
-- Cheek / Touch Position --

© 2002 PCTEST Engineering Laboratory, Inc.

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Brain

14.6 MEASUREMENT RESULTS (CELLULAR CDMA Right Head SAR – Touch)

FREQUENCY		Modulation	Begin / End POWER‡			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
824.70	1013	CDMA	25.5	25.5	Standard	Cheek / Touch	In	**0.59**
824.70	1013	CDMA	25.5	25.5	Standard	Cheek / Touch	Out	**0.38**
836.49	383	CDMA	25.5	25.5	Standard	Cheek / Touch	In	**0.92**
836.49	383	CDMA	25.5	25.5	Standard	Cheek / Touch	Out	**0.61**
848.31	777	CDMA	25.5	25.5	Standard	Cheek / Touch	In	**0.64**
848.31	777	CDMA	25.5	25.5	Standard	Cheek / Touch	Out	**0.58**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Brain 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings. *Standard batteries are the only battery options.*

‡Power Measured	☒ Conducted	☐ ERP	☐ EIRP	
4. SAR Measurement System	☐ DASY3	☒ IDX		
Phantom Configuration	☐ Left Head	☐ Flat Phantom	☒ Right Head	
5. SAR Configuration	☒ Head	☐ Body	☐ Hand	
6. Test Signal Call Mode	☒ Manu. Test Codes	☐ Base Station Simulator		

7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15.1 cm. ± 0.1

Alfred Cirwithian
Vice President Engineering

Figure 14.6 Right Head SAR Test Setup
-- Cheek / Touch Position --

© 2002 PCTEST Engineering Laboratory, Inc.

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Brain

14.7 MEASUREMENT RESULTS (PCS CDMA Right Head SAR – Touch)

FREQUENCY		Modulation	Begin / End POWER‡			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
1851.25	0025	PCS CDMA	24.5	24.5	Standard	Cheek / Touch	In	**1.16**
1851.25	0025	PCS CDMA	24.5	24.5	Standard	Cheek / Touch	Out	**0.25**
1880.00	0600	PCS CDMA	24.5	24.5	Standard	Cheek / Touch	In	**1.30**
1880.00	0600	PCS CDMA	24.5	24.5	Standard	Cheek / Touch	Out	**0.36**
1908.75	1175	PCS CDMA	24.5	24.5	Standard	Cheek / Touch	In	**1.19**
1908.75	1175	PCS CDMA	24.5	24.5	Standard	Cheek / Touch	Out	**0.27**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Brain 1.6 W/kg (mW/g) averaged over 1 gram**		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings. *Standard batteries are the only battery options.*

‡Power Measured	☒ Conducted	☐ ERP	☐ EIRP	
4. SAR Measurement System	☐ DASY3	☒ IDX		
Phantom Configuration	☐ Left Head	☐ Flat Phantom	☒ Right Head	
5. SAR Configuration	☒ Head	☐ Body	☐ Hand	
6. Test Signal Call Mode	☒ Manu. Test Codes	☐ Base Station Simulator		

7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15.1 cm. ± 0.1

Alfred Cirwithian
Vice President Engineering

Figure 14.7 Right Head SAR Test Setup
-- Cheek / Touch Position --

© 2002 PCTEST Engineering Laboratory, Inc.

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Brain

14.8 MEASUREMENT RESULTS (PCS CDMA Left Head SAR – Touch)

FREQUENCY		Modulation	Begin / End POWER‡			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
1851.25	0025	PCS CDMA	24.5	24.5	Standard	Cheek / Touch	In	**1.28**
1851.25	0025	PCS CDMA	24.5	24.5	Standard	Cheek / Touch	Out	**0.26**
1880.00	0600	PCS CDMA	24.5	24.5	Standard	Cheek / Touch	In	**1.33**
1880.00	0600	PCS CDMA	24.5	24.5	Standard	Cheek / Touch	Out	**0.44**
1908.75	1175	PCS CDMA	24.5	24.5	Standard	Cheek / Touch	In	**1.24**
1908.75	1175	PCS CDMA	24.5	24.5	Standard	Cheek / Touch	Out	**0.23**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Brain 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings. *Standard batteries are the only battery options.*

‡Power Measured	☒ Conducted	☐ ERP	☐ EIRP	
4. SAR Measurement System	☐ DASY3	☒ IDX		
Phantom Configuration	☒ Left Head	☐ Flat Phantom	☐ Right Head	
5. SAR Configuration	☒ Head	☐ Body	☐ Hand	
6. Test Signal Call Mode	☒ Manu. Test Codes	☐ Base Station Simulator		

7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15.1 cm. ± 0.1

Alfred Cirwithian
Vice President Engineering

Figure 14.8 Left Head SAR Test Setup
-- Cheek / Touch Position --

© 2002 PCTEST Engineering Laboratory, Inc.

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Brain

14.9 MEASUREMENT RESULTS (PCS CDMA Left Head SAR – Tilt)

FREQUENCY		Modulation	Begin / End POWER‡			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
1880.00	0600	PCS CDMA	24.5	24.5	Standard	Ear / 15° Tilt	In	**0.21**
1880.00	0600	PCS CDMA	24.5	24.5	Standard	Ear / 15° Tilt	Out	**0.05**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Brain 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings. *Standard batteries are the only battery options.*

‡Power Measured	☒ Conducted	☐ ERP	☐ EIRP	
4. SAR Measurement System	☐ DASY3	☒ IDX		
Phantom Configuration	☒ Left Head	☐ Flat Phantom	☐ Right Head	
5. SAR Configuration	☒ Head	☐ Body	☐ Hand	
6. Test Signal Call Mode	☒ Manu. Test Codes	☐ Base Station Simulator		

7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15.1 cm. ± 0.1
9. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July, 2001), if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tile/ear, extended and retracted) is at least 2.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).

Alfred Cirwithian
Vice President Engineering

Figure 14.9 Left Head SAR Test Setup
-- Ear / Tilt Position --

© 2002 PCTEST Engineering Laboratory, Inc.

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Brain

14.10 MEASUREMENT RESULTS (PCS Right Head SAR – Tilt)

FREQUENCY		Modulation	Begin / End POWER‡			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
1880.00	600	PCS CDMA	26.0	26.0	Standard	Ear / 15° Tilt	In	**0.18**
1880.00	600	PCS CDMA	26.0	26.0	Standard	Ear / 15° Tilt	Out	**0.06**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Brain 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings. *Standard batteries are the only battery options.*
   ‡Power Measured ☒ Conducted ☐ ERP ☐ EIRP
4. SAR Measurement System ☐ DASY3 ☒ IDX
   Phantom Configuration ☐ Left Head ☐ Flat Phantom ☒ Right Head
5. SAR Configuration ☒ Head ☐ Body ☐ Hand
6. Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15.1 cm. ± 0.1
9. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July, 2001), if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tile/ear, extended and retracted) is at least 2.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).

Alfred Cirwithian
Vice President Engineering



Figure 14.10 Right Head SAR Test Setup -- Ear / 15° Tilt Position --

© 2002 PCTEST Engineering Laboratory, Inc.

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Muscle

14.11 MEASUREMENT RESULTS (AMPS Body SAR w/o Holster)

FREQUENCY		Modulation	Begin / End POWER‡			Separation Distance (cm) ‡‡	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
824.04	0991	AMPS	26.0	26.0	Standard	1.5 [w/o Holster]	In	**0.44**
824.04	0991	AMPS	26.0	26.0	Standard	1.5 [w/o Holster]	Out	**0.44**
836.49	0383	AMPS	26.0	26.0	Standard	1.5 [w/o Holster]	In	**0.62**
836.49	0383	AMPS	26.0	26.0	Standard	1.5 [w/o Holster]	Out	**0.47**
848.97	0799	AMPS	26.0	26.0	Standard	1.5 [w/o Holster]	In	**0.48**
848.97	0799	AMPS	26.0	26.0	Standard	1.5 [w/o Holster]	Out	**0.42**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Muscle 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings. *Standard batteries are the only battery options.*

‡Power Measured	☒ Conducted	☐ ERP	☐ EIRP	
4. SAR Measurement System	☐ DASY3	☒ IDX		
Phantom Configuration	☐ Left Head	☒ Flat Phantom	☐ Right Head	
5. SAR Configuration	☐ Head	☒ Body	☐ Hand	
6. Test Signal Call Mode	☒ Manu. Test Codes	☐ Base Station Simulator		
7. ‡‡Test Configuration	☐ With Holster	☒ Without Holster		

8. Tissue parameters and temperatures are listed on the SAR plots.
9. Both sides of the phone were tested and the worst-case side is reported.
10. Liquid tissue depth is 15.1 cm. ± 0.1

Alfred Cirwithian
Vice President Engineering

Figure 14.11 Body SAR Test Setup
-- w/o Holster --

© 2002 PCTEST Engineering Laboratory, Inc.

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Muscle

14.12 MEASUREMENT RESULTS (CELLULAR CDMA Body SAR w/o Holster)

FREQUENCY		Modulation	Begin / End POWER‡			Separation Distance (cm) ‡‡	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
836.49	0383	CDMA	25.5	25.5	Standard	1.5 [w/o Holster]	In	**0.53**
836.49	0383	CDMA	25.5	25.5	Standard	1.5 [w/o Holster]	Out	**0.40**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Muscle 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings. *Standard batteries are the only battery options.*
   ‡Power Measured ☒ Conducted ☐ ERP ☐ EIRP
4. SAR Measurement System ☐ DASY3 ☒ IDX
   Phantom Configuration ☐ Left Head ☒ Flat Phantom ☐ Right Head
5. SAR Configuration ☐ Head ☒ Body ☐ Hand
6. Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
7. ‡‡Test Configuration ☐ With Holster ☒ Without Holster
8. Tissue parameters and temperatures are listed on the SAR plots.
9. Both sides of the phone were tested and the worst-case side is reported.
10. Liquid tissue depth is 15.1 cm. ± 0.1
11. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July, 2001), if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tile/ear, extended and retracted) is at least 2.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).

Alfred Cirwithian
Vice President Engineering

Figure 14.12 Body SAR Test Setup
-- w/o Holster --

© 2002 PCTEST Engineering Laboratory, Inc.

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Muscle

14.13 MEASUREMENT RESULTS (PCS CDMA Body SAR w/o Holster)

FREQUENCY		Modulation	Begin / End POWER‡			Separation Distance (cm) ‡‡	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
1851.25	0025	PCS CDMA	24.5	24.5	Standard	1.5 [w/o Holster]	In	**0.21**
1851.25	0025	PCS CDMA	24.5	24.5	Standard	1.5 [w/o Holster]	Out	**0.12**
1880.00	0600	PCS CDMA	24.5	24.5	Standard	1.5 [w/o Holster]	In	**0.32**
1880.00	0600	PCS CDMA	24.5	24.5	Standard	1.5 [w/o Holster]	Out	**0.05**
1908.75	1175	PCS CDMA	24.5	24.5	Standard	1.5 [w/o Holster]	In	**0.34**
1908.75	1175	PCS CDMA	24.5	24.5	Standard	1.5 [w/o Holster]	Out	**0.28**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Muscle 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings. *Standard batteries are the only battery options.*

‡Power Measured	☒ Conducted	☐ ERP	☐ EIRP	
4. SAR Measurement System	☐ DASY3	☒ IDX		
Phantom Configuration	☐ Left Head	☒ Flat Phantom	☐ Right Head	
5. SAR Configuration	☐ Head	☒ Body	☐ Hand	
6. Test Signal Call Mode	☒ Manu. Test Codes	☐ Base Station Simulator		
7. ‡‡Test Configuration	☐ With Holster	☒ Without Holster		

8. Tissue parameters and temperatures are listed on the SAR plots.
9. Both sides of the phone were tested and the worst-case side is reported.
10. Liquid tissue depth is 15.1 cm. ± 0.1

Alfred Cirwithian
Vice President Engineering

Figure 14.13 Body SAR Test Setup
-- w/o Holster --

© 2002 PCTEST Engineering Laboratory, Inc.

15. SAR TEST EQUIPMENT

Equipment Calibration

Table 15.1 Test Equipment Calibration

EQUIPMENT SPECIFICATIONS		
Type	**Calibration Date**	**Serial Number**
CRS Robot F3	February 2002	RAF0134133
CRS C500C Motion Controller	February 2002	RCB0003303
CRS Teach Pendant (Joystick)	February 2002	STP0132231
DELL Computer, Pentium 4 1.6 GHz, Windows 2000™	February 2002	
E-Field Probe E-010	February 2002	PCT002
Right Ear SAM Phantom (P-SAM-R)	February 2002	
Left Ear SAM Phantom (P-SAM-L)	February 2002	
IDX Robot End Effector (EE-103-C)	February 2002	07111223
IDX Probe Amplifier	February 2002	07111113
Validation Dipole D-835S	February 2002	PCT640
Validation Dipole D-1900S	February 2002	PCT639
Brain Equivalent Matter (835MHz)	April 2002	PCTBEM101
Brain Equivalent Matter (1900MHz)	April 2002	PCTBEM301
Muscle Equivalent Matter (835MHz)	April 2002	PCTMEM201
Muscle Equivalent Matter (1900MHz)	April 2002	PCTMEM401
Microwave Amp. Model: 5S1G4, (800MHz - 4.2GHz)	January 2002	22332
Gigatronics 8651A Power Meter	January 2002	1835299
HP-8648D (9kHz ~ 4GHz) Signal Generator	January 2002	PCT530
Amplifier Research 5S1G4 Power Amp	January 2002	PCT540
HP-8753E (30kHz ~ 3GHz) Network Analyzer	January 2002	PCT552
HP85070B Dielectric Probe Kit	January 2002	PCT501
Ambient Noise/Reflection, etc.	<12mW/kg/<3%of SAR	January 2002

NOTE:

The E-field probe was calibrated by IDX, by temperature measurement procedure. Dipole Validation measurement is performed by PCTEST Lab. before each test. The brain simulating material is calibrated by PCTEST using the dielectric probe system and network analyzer to determine the conductivity and permittivity (dielectric constant) of the brain-equivalent material.

© 2002 PCTEST Engineering Laboratory, Inc.

SAR Data Report 02032218

```
  Start        : 22-Mar-02 06:12:35 pm
  End          : 22-Mar-02 06:28:43 pm
  Code Version : 4.08
  Robot Version: 4.08

Product Data:
  Type             : SAMSUNG
  Model Number     : SPH-A500
  Serial Number    : 2
  Frequency        : 836.49 MHz
  Transmit Pwr     : 0.400 W
  Antenna Type     : Helical
  Antenna Posn.    : In

Measurement Data:
  Phantom Name        : SAM-R
  Phantom Type        : Right Ear
  Tissue Type         : Brain
  Tissue Dielectric   : 43.440
  Tissue Conductivity : 0.870
  Tissue Density      : 1.000
  Robot Name          : CRS

Probe Data:
  Probe Name              : PCT002
  Probe Type              : E Fld Triangle
  Frequency               : 835 MHz
  Tissue Type             : Brain
  Calibrated Dielectric   : 40.700
  Calibrated Conductivity :  0.890
  Calibrated Density      :  1.000
  Probe Offset            :  2.400 mm
  Conversion Factor       :  5.800
  Probe Sensitivity :  3.597   3.474   3.049   mV/(mW/cm^2)
  Amplifier Gains   :  20.00   20.00   20.00

Sample:
  Rate:         6000 Samples/Sec
  Count:        100 Samples
  NIDAQ Gain:   5

Comments:
  AMPS Mode CH-383
  Cheek
  CF=1; Amb. Temp= 21.1 'C; Liq. Temp=20.9 'C
```

Area Scan - Max Peak SAR Value at x=82.0 y=13.0 = 0.92 W/kg

Zoom Scan - Max Peak SAR Value at x=77.0 y=13.0 z=0.0 = 1.43 W/kg

Max 1g SAR at x=76.0 y=14.0 z=0.0 = 1.03 W/kg

Max 10g SAR at x=77.0 y=14.0 z=0.0 = 0.68 W/kg

SAR - Z Axis
at Hotspot x:77.0 y:13.0



1g SAR Values




SAMSUNG
Sprint

SAR Data Report 02032204

```
  Start        : 22-Mar-02 10:59:46 am
  End          : 22-Mar-02 11:29:05 am
  Code Version : 4.08
  Robot Version: 4.08

Product Data:
  Type             : SAMSUNG
  Model Number     : SPH-A500
  Serial Number    : 2
  Frequency        : 836.49 MHz
  Transmit Pwr     : 0.400 W
  Antenna Type     : Helical
  Antenna Posn.    : In

Measurement Data:
  Phantom Name        : SAM-L
  Phantom Type        : Left Ear
  Tissue Type         : Brain
  Tissue Dielectric   : 43.440
  Tissue Conductivity : 0.870
  Tissue Density      : 1.000
  Robot Name          : CRS

Probe Data:
  Probe Name              : PCT002
  Probe Type              : E Fld Triangle
  Frequency               : 835 MHz
  Tissue Type             : Brain
  Calibrated Dielectric   : 40.700
  Calibrated Conductivity :  0.890
  Calibrated Density      :  1.000
  Probe Offset            :  2.400 mm
  Conversion Factor       :  5.800
  Probe Sensitivity :  3.597   3.474   3.049   mV/(mW/cm^2)
  Amplifier Gains   :  20.00   20.00   20.00

Sample:
  Rate:         6000 Samples/Sec
  Count:        100 Samples
  NIDAQ Gain:   5

Comments:
  AMPS Mode CH-383
  Cheek
  CF=1; mb. Temp= 21.1 'C; Liq. Temp=21.0 'C
```

Area Scan - Max Peak SAR Value at x=74.0 y=8.0 = 1.05 W/kg

Zoom Scan - Max Peak SAR Value at x=77.0 y=7.0 z=0.0 = 1.63 W/kg

Max 1g SAR at x=76.0 y=8.0 z=0.0 = 1.10 W/kg

Max 10g SAR at x=75.0 y=8.0 z=0.0 = 0.73 W/kg

SAR - Z Axis
at Hotspot x:77.0 y:7.0



1g SAR Values




SAMSUNG
Sprint

SAR Data Report 02032214

```
  Start        : 22-Mar-02 05:04:18 pm
  End          : 22-Mar-02 05:19:02 pm
  Code Version : 4.08
  Robot Version: 4.08

Product Data:
  Type             : SAMSUNG
  Model Number     : SPH-A500
  Serial Number    : 2
  Frequency        : 836.49 MHz
  Transmit Pwr     : 0.400 W
  Antenna Type     : Helical
  Antenna Posn.    : In

Measurement Data:
  Phantom Name        : SAM-L
  Phantom Type        : Left Ear
  Tissue Type         : Brain
  Tissue Dielectric   : 43.440
  Tissue Conductivity : 0.870
  Tissue Density      : 1.000
  Robot Name          : CRS

Probe Data:
  Probe Name              : PCT002
  Probe Type              : E Fld Triangle
  Frequency               : 835 MHz
  Tissue Type             : Brain
  Calibrated Dielectric   : 40.700
  Calibrated Conductivity :  0.890
  Calibrated Density      :  1.000
  Probe Offset            :  2.400 mm
  Conversion Factor       :  5.800
  Probe Sensitivity :  3.597   3.474   3.049   mV/(mW/cm^2)
  Amplifier Gains   :  20.00   20.00   20.00

Sample:
  Rate:         6000 Samples/Sec
  Count:        100 Samples
  NIDAQ Gain:   5

Comments:
  AMPS Mode CH-383
  Tilt
  CF=1; Amb. Temp= 21.1 'C; Liq. Temp=21.0 'C
```

Area Scan - Max Peak SAR Value at x=50.0 y=10.0 = 0.21 W/kg

Zoom Scan - Max Peak SAR Value at x=34.0 y=12.0 z=0.0 = 0.32 W/kg

Max 1g SAR at x=51.0 y=12.0 z=0.0 = 0.22 W/kg

Max 10g SAR at x=49.0 y=10.0 z=0.0 = 0.15 W/kg


SAR - Z Axis
at Hotspot x:34.0 y:12.0
0.40
0.30
0.20
0.10
0.00
SAR (mW/g)
0
10
20
30
Z Distance (mm)

1g SAR Values




SAMSUNG
Sprint

SAR Data Report 02061009

```
  Start        : 10-Jun-02 03:40:19 pm
  End          : 10-Jun-02 03:46:28 pm
  Code Version : 4.08
  Robot Version: 4.08

Product Data:
  Type             : SAMSUNG
  Model Number     : SPH-A500
  Serial Number    : 2
  Frequency        : 836.49 MHz
  Transmit Pwr     : 0.400 W
  Antenna Type     : Helical
  Antenna Posn.    : In

Measurement Data:
  Phantom Name        : SAM-R
  Phantom Type        : Right Ear
  Tissue Type         : Brain
  Tissue Dielectric   : 43.400
  Tissue Conductivity : 0.870
  Tissue Density      : 1.000
  Robot Name          : CRS

Probe Data:
  Probe Name              : PCT002
  Probe Type              : E Fld Triangle
  Frequency               : 835 MHz
  Tissue Type             : Brain
  Calibrated Dielectric   : 40.700
  Calibrated Conductivity :  0.890
  Calibrated Density      :  1.000
  Probe Offset            :  2.400 mm
  Conversion Factor       :  5.800
  Probe Sensitivity :  3.597   3.474   3.049   mV/(mW/cm^2)
  Amplifier Gains   :  20.00   20.00   20.00

Sample:
  Rate:         6000 Samples/Sec
  Count:        100 Samples
  NIDAQ Gain:   5

Comments:
  AMPS CH-383
  Tilt
  CF=1; Amb. Temp= 22.7 'C; Liq. Temp=22.0 'C
```

Area Scan - Max Peak SAR Value at x=71.0 y=14.0 = 0.22 W/kg

Zoom Scan - Max Peak SAR Value at x=71.0 y=19.0 z=0.0 = 0.33 W/kg

Max 1g SAR at x=72.0 y=18.0 z=0.0 = 0.23 W/kg

Max 10g SAR at x=72.0 y=15.0 z=0.0 = 0.16 W/kg


SAR - Z Axis
at Hotspot x:71.0 y:19.0
0.40
0.30
0.20
0.10
0.00
SAR (mW/g)
0
10
20
30
Z Distance (mm)

1g SAR Values





SAR Data Report 02032212

```
  Start        : 22-Mar-02 04:01:10 pm
  End          : 22-Mar-02 04:30:32 pm
  Code Version : 4.08
  Robot Version: 4.08

Product Data:
  Type             : SAMSUNG
  Model Number     : SPH-A500
  Serial Number    : 2
  Frequency        : 836.49 MHz
  Transmit Pwr     : 0.355 W
  Antenna Type     : Helical
  Antenna Posn.    : In

Measurement Data:
  Phantom Name        : SAM-L
  Phantom Type        : Left Ear
  Tissue Type         : Brain
  Tissue Dielectric   : 43.440
  Tissue Conductivity : 0.870
  Tissue Density      : 1.000
  Robot Name          : CRS

Probe Data:
  Probe Name              : PCT002
  Probe Type              : E Fld Triangle
  Frequency               : 835 MHz
  Tissue Type             : Brain
  Calibrated Dielectric   : 40.700
  Calibrated Conductivity :  0.890
  Calibrated Density      :  1.000
  Probe Offset            :  2.400 mm
  Conversion Factor       :  5.800
  Probe Sensitivity :  3.597   3.474   3.049   mV/(mW/cm^2)
  Amplifier Gains   :  20.00   20.00   20.00

Sample:
  Rate:         6000 Samples/Sec
  Count:        100 Samples
  NIDAQ Gain:   5

Comments:
  CDMA Mode CH-383
  Cheek
  Amb. Temp= 21.1 'C; Liq. Temp=21.0 'C
```

Area Scan - Max Peak SAR Value at x=74.0 y=8.0 = 1.01 W/kg

Zoom Scan - Max Peak SAR Value at x=74.0 y=10.0 z=0.0 = 1.50 W/kg

Max 1g SAR at x=75.0 y=9.0 z=0.0 = 1.05 W/kg

Max 10g SAR at x=74.0 y=8.0 z=0.0 = 0.70 W/kg

SAR - Z Axis
at Hotspot x:74.0 y:10.0



1g SAR Values




SAMSUNG
Sprint

SAR Data Report 02032224

```
  Start        : 22-Mar-02 07:53:26 pm
  End          : 22-Mar-02 08:05:41 pm
  Code Version : 4.08
  Robot Version: 4.08

Product Data:
  Type             : SAMSUNG
  Model Number     : SPH-A500
  Serial Number    : 2
  Frequency        : 836.49 MHz
  Transmit Pwr     : 0.355 W
  Antenna Type     : Helical
  Antenna Posn.    : In

Measurement Data:
  Phantom Name        : SAM-R
  Phantom Type        : Right Ear
  Tissue Type         : Brain
  Tissue Dielectric   : 43.440
  Tissue Conductivity : 0.870
  Tissue Density      : 1.000
  Robot Name          : CRS

Probe Data:
  Probe Name              : PCT002
  Probe Type              : E Fld Triangle
  Frequency               : 835 MHz
  Tissue Type             : Brain
  Calibrated Dielectric   : 40.700
  Calibrated Conductivity :  0.890
  Calibrated Density      :  1.000
  Probe Offset            :  2.400 mm
  Conversion Factor       :  5.800
  Probe Sensitivity :  3.597   3.474   3.049   mV/(mW/cm^2)
  Amplifier Gains   :  20.00   20.00   20.00

Sample:
  Rate:         6000 Samples/Sec
  Count:        100 Samples
  NIDAQ Gain:   5

Comments:
  CDMA Mode CH-383
  Cheek
  Amb. Temp= 21.1 'C; Liq. Temp=20.9 'C
```

Area Scan - Max Peak SAR Value at x=75.0 y=13.0 = 0.90 W/kg

Zoom Scan - Max Peak SAR Value at x=76.0 y=13.0 z=0.0 = 1.38 W/kg

Max 1g SAR at x=76.0 y=14.0 z=0.0 = 0.92 W/kg

Max 10g SAR at x=76.0 y=14.0 z=0.0 = 0.60 W/kg

SAR - Z Axis
at Hotspot x:76.0 y:13.0



1g SAR Values




SAMSUNG
Sprint

SAR Data Report 02032125

```
  Start        : 21-Mar-02 04:02:54 pm
  End          : 21-Mar-02 04:19:22 pm
  Code Version : 4.08
  Robot Version: 4.08

Product Data:
  Type             : SAMSUNG
  Model Number     : SPH-A500
  Serial Number    : 2
  Frequency        : 1880.00 MHz
  Transmit Pwr     : 0.280 W
  Antenna Type     : Helical
  Antenna Posn.    : In

Measurement Data:
  Phantom Name        : SAM-R
  Phantom Type        : Right Ear
  Tissue Type         : Brain
  Tissue Dielectric   : 40.290
  Tissue Conductivity : 1.440
  Tissue Density      : 1.000
  Robot Name          : CRS

Probe Data:
  Probe Name              : PCT002
  Probe Type              : E Fld Triangle
  Frequency               : 1900 MHz
  Tissue Type             : Brain
  Calibrated Dielectric   : 40.200
  Calibrated Conductivity :  1.410
  Calibrated Density      :  1.000
  Probe Offset            :  2.400 mm
  Conversion Factor       :  4.700
  Probe Sensitivity :  3.000   2.995   2.653   mV/(mW/cm^2)
  Amplifier Gains   :  20.00   20.00   20.00

Sample:
  Rate:         6000 Samples/Sec
  Count:        100 Samples
  NIDAQ Gain:   5

Comments:
  PCS Mode CH-0600
  Cheek
  Amb. Temp= 21.0 'C; Liq. Temp=20.9 'C



Area Scan - Max Peak SAR Value at x=77.0 y=11.0 = 1.30 W/kg

Zoom Scan - Max Peak SAR Value at x=74.0 y=14.0 z=0.0 = 2.16 W/kg

Max 1g SAR at x=76.0 y=11.0 z=0.0 = 1.30 W/kg

Max 10g SAR at x=77.0 y=11.0 z=0.0 = 0.75 W/kg
```


SAR - Z Axis
at Hotspot x:74.0 y:14.0
SAR (mW/g)
2.2
2.0
1.8
1.6
1.4
1.2
1.0
0.8
0.6
0.4
0.2
0.0
0
10
20
30
Z Distance (mm)

1g SAR Values





SAR Data Report 02032113

```
  Start        : 21-Mar-02 12:58:28 pm
  End          : 21-Mar-02 01:16:29 pm
  Code Version : 4.08
  Robot Version: 4.08

Product Data:
  Type             : SAMSUNG
  Model Number     : SPH-A500
  Serial Number    : 2
  Frequency        : 1880.00 MHz
  Transmit Pwr     : 0.280 W
  Antenna Type     : Helical
  Antenna Posn.    : In

Measurement Data:
  Phantom Name        : SAM-L
  Phantom Type        : Left Ear
  Tissue Type         : Brain
  Tissue Dielectric   : 40.290
  Tissue Conductivity : 1.440
  Tissue Density      : 1.000
  Robot Name          : CRS

Probe Data:
  Probe Name              : PCT002
  Probe Type              : E Fld Triangle
  Frequency               : 1900 MHz
  Tissue Type             : Brain
  Calibrated Dielectric   : 40.200
  Calibrated Conductivity :  1.410
  Calibrated Density      :  1.000
  Probe Offset            :  2.400 mm
  Conversion Factor       :  4.700
  Probe Sensitivity :  3.000   2.995   2.653   mV/(mW/cm^2)
  Amplifier Gains   :  20.00   20.00   20.00

Sample:
  Rate:         6000 Samples/Sec
  Count:        100 Samples
  NIDAQ Gain:   5

Comments:
  PCS Mode CH-0600
  Cheek
  CF=1; Amb. Temp= 21.0 'C; Liq. Temp=20.8 'C



Area Scan - Max Peak SAR Value at x=90.0 y=-18.0 = 1.34 W/kg

Zoom Scan - Max Peak SAR Value at x=78.0 y=2.0 z=0.0 = 2.12 W/kg

Max 1g SAR at x=79.0 y=2.0 z=0.0 = 1.33 W/kg

Max 10g SAR at x=87.0 y=-11.0 z=0.0 = 0.91 W/kg
```


SAR - Z Axis
at Hotspot x:78.0 y:2.0
SAR (mW/g)
2.2
2.0
1.8
1.6
1.4
1.2
1.0
0.8
0.6
0.4
0.2
0.0
0
10
20
30
Z Distance (mm)

1g SAR Values




SAMSUNG

SAR Data Report 02032120

```
  Start        : 21-Mar-02 02:59:33 pm
  End          : 21-Mar-02 03:24:57 pm
  Code Version : 4.08
  Robot Version: 4.08

Product Data:
  Type             : SAMSUNG
  Model Number     : SPH-A500
  Serial Number    : 2
  Frequency        : 1880.00 MHz
  Transmit Pwr     : 0.280 W
  Antenna Type     : Helical
  Antenna Posn.    : In

Measurement Data:
  Phantom Name        : SAM-L
  Phantom Type        : Left Ear
  Tissue Type         : Brain
  Tissue Dielectric   : 40.290
  Tissue Conductivity : 1.440
  Tissue Density      : 1.000
  Robot Name          : CRS

Probe Data:
  Probe Name              : PCT002
  Probe Type              : E Fld Triangle
  Frequency               : 1900 MHz
  Tissue Type             : Brain
  Calibrated Dielectric   : 40.200
  Calibrated Conductivity :  1.410
  Calibrated Density      :  1.000
  Probe Offset            :  2.400 mm
  Conversion Factor       :  4.700
  Probe Sensitivity :  3.000   2.995   2.653   mV/(mW/cm^2)
  Amplifier Gains   :  20.00   20.00   20.00

Sample:
  Rate:         6000 Samples/Sec
  Count:        100 Samples
  NIDAQ Gain:   5

Comments:
  PCS Mode CH-0600
  Tilt
  Amb. Temp= 21.0 'C; Liq. Temp=20.8 'C
```

Area Scan - Max Peak SAR Value at x=80.0 y=-3.0 = 0.19 W/kg

Zoom Scan - Max Peak SAR Value at x=73.0 y=5.0 z=0.0 = 0.45 W/kg

Max 1g SAR at x=76.0 y=3.0 z=0.0 = 0.21 W/kg

Max 10g SAR at x=80.0 y=-4.0 z=0.0 = 0.13 W/kg


SAR - Z Axis
at Hotspot x:73.0 y:5.0
SAR (mW/g)
0.5
0.4
0.3
0.2
0.1
0.0
0
10
20
30
Z Distance (mm)

1g SAR Values



SAMSUNG
Sprint

SAR Data Report 02061006

```
  Start        : 10-Jun-02 02:29:25 pm
  End          : 10-Jun-02 02:35:30 pm
  Code Version : 4.08
  Robot Version: 4.08

Product Data:
  Type             : SAMSUNG
  Model Number     : SPH-A500
  Serial Number    : 2
  Frequency        : 1880.00 MHz
  Transmit Pwr     : 0.280 W
  Antenna Type     : Helical
  Antenna Posn.    : In

Measurement Data:
  Phantom Name        : SAM-R
  Phantom Type        : Right Ear
  Tissue Type         : Brain
  Tissue Dielectric   : 41.400
  Tissue Conductivity : 1.400
  Tissue Density      : 1.000
  Robot Name          : CRS

Probe Data:
  Probe Name              : PCT002
  Probe Type              : E Fld Triangle
  Frequency               : 1900 MHz
  Tissue Type             : Brain
  Calibrated Dielectric   : 40.200
  Calibrated Conductivity :  1.410
  Calibrated Density      :  1.000
  Probe Offset            :  2.400 mm
  Conversion Factor       :  4.700
  Probe Sensitivity :  3.000   2.995   2.653   mV/(mW/cm^2)
  Amplifier Gains   :  20.00   20.00   20.00

Sample:
  Rate:         6000 Samples/Sec
  Count:        100 Samples
  NIDAQ Gain:   5

Comments:
  PCS CH-25
  Tilt
  CF=1; Amb. Temp= 22.7 'C; Liq. Temp=22.0 'C



Area Scan - Max Peak SAR Value at x=76.0 y=8.0 = 0.14 W/kg

Zoom Scan - Max Peak SAR Value at x=60.0 y=24.0 z=0.0 = 0.35 W/kg

Max 1g SAR at x=81.0 y=6.0 z=0.0 = 0.18 W/kg

Max 10g SAR at x=81.0 y=5.0 z=0.0 = 0.11 W/kg
```


SAR - Z Axis
at Hotspot x:60.0 y:24.0
SAR (mW/g)
0.4
0.3
0.2
0.1
0.0
0
10
20
30
Z Distance (mm)

1g SAR Values





SAR Data Report 02032707

```
  Start        : 27-Mar-02 04:44:45 pm
  End          : 27-Mar-02 04:57:19 pm
  Code Version : 4.08
  Robot Version: 4.08

Product Data:
  Type             : SAMSUNG
  Model Number     : SPH-A500
  Serial Number    : 2
  Frequency        : 836.49 MHz
  Transmit Pwr     : 0.400 W
  Antenna Type     : Helical
  Antenna Posn.    : In

Measurement Data:
  Phantom Name        : SAM-FLAT
  Phantom Type        : Uniphantom
  Tissue Type         : Muscle
  Tissue Dielectric   : 55.540
  Tissue Conductivity : 0.990
  Tissue Density      : 1.000
  Robot Name          : CRS

Probe Data:
  Probe Name              : PCT002
  Probe Type              : E Fld Triangle
  Frequency               : 835 MHz
  Tissue Type             : Muscle
  Calibrated Dielectric   : 55.700
  Calibrated Conductivity :  0.990
  Calibrated Density      :  1.000
  Probe Offset            :  2.400 mm
  Conversion Factor       :  4.900
  Probe Sensitivity :  3.597   3.474   3.049   mV/(mW/cm^2)
  Amplifier Gains   :  20.00   20.00   20.00

Sample:
  Rate:         6000 Samples/Sec
  Count:        100 Samples
  NIDAQ Gain:   5

Comments:
  AMPS Mode CH-0383
  BODY
  CF=1; Amb. Temp= 21.4 'C; Liq. Temp=21.3 'C
```

Area Scan - Max Peak SAR Value at x=5.0 y=-14.0 = 0.60 W/kg

Zoom Scan - Max Peak SAR Value at x=6.0 y=-12.0 z=0.0 = 0.90 W/kg

Max 1g SAR at x=6.0 y=-13.0 z=0.0 = 0.62 W/kg

Max 10g SAR at x=7.0 y=-15.0 z=0.0 = 0.42 W/kg


SAR - Z Axis
at Hotspot x:6.0 y:-12.0
SAR (mW/g)
0.9
0.8
0.7
0.6
0.5
0.4
0.3
0.2
0.1
0.0
0
10
20
30
Z Distance (mm)

1g SAR Values





SAR Data Report 02032806

```
  Start        : 28-Mar-02 10:57:27 am
  End          : 28-Mar-02 11:09:22 am
  Code Version : 4.08
  Robot Version: 4.08

Product Data:
  Type             : SAMSUNG
  Model Number     : SPH-A500
  Serial Number    : 3
  Frequency        : 836.49 MHz
  Transmit Pwr     : 0.355 W
  Antenna Type     : Helical
  Antenna Posn.    : In

Measurement Data:
  Phantom Name        : SAM-FLAT
  Phantom Type        : Uniphantom
  Tissue Type         : Muscle
  Tissue Dielectric   : 55.540
  Tissue Conductivity : 0.990
  Tissue Density      : 1.000
  Robot Name          : CRS

Probe Data:
  Probe Name              : PCT002
  Probe Type              : E Fld Triangle
  Frequency               : 835 MHz
  Tissue Type             : Muscle
  Calibrated Dielectric   : 55.700
  Calibrated Conductivity :  0.990
  Calibrated Density      :  1.000
  Probe Offset            :  2.400 mm
  Conversion Factor       :  4.900
  Probe Sensitivity :  3.597   3.474   3.049   mV/(mW/cm^2)
  Amplifier Gains   :  20.00   20.00   20.00

Sample:
  Rate:         6000 Samples/Sec
  Count:        100 Samples
  NIDAQ Gain:   5

Comments:
  CDMA Mode CH-0383
  BODY
  CF=1; Amb. Temp= 21.8 'C; Liq. Temp=21.5 'C
```

Area Scan - Max Peak SAR Value at x=4.0 y=-15.0 = 0.52 W/kg

Zoom Scan - Max Peak SAR Value at x=3.0 y=-9.0 z=0.0 = 0.73 W/kg

Max 1g SAR at x=4.0 y=-13.0 z=0.0 = 0.53 W/kg

Max 10g SAR at x=5.0 y=-15.0 z=0.0 = 0.35 W/kg


SAR - Z Axis
at Hotspot x:3.0 y:-9.0
SAR (mW/g)
0.8
0.7
0.6
0.5
0.4
0.3
0.2
0.1
0.0
0
10
20
30
Z Distance (mm)

1g SAR Values





SAR Data Report 02040819

```
  Start        :  8-Apr-02 06:10:32 pm
  End          :  8-Apr-02 06:23:03 pm
  Code Version : 4.08
  Robot Version: 4.08

Product Data:
  Type             : SAMSUNG
  Model Number     : SPH-A500
  Serial Number    : 2
  Frequency        : 1908.75 MHz
  Transmit Pwr     : 0.280 W
  Antenna Type     : Helical
  Antenna Posn.    : In

Measurement Data:
  Phantom Name        : SAM-FLAT
  Phantom Type        : Uniphantom
  Tissue Type         : Muscle
  Tissue Dielectric   : 53.950
  Tissue Conductivity : 1.530
  Tissue Density      : 1.000
  Robot Name          : CRS

Probe Data:
  Probe Name              : PCT002
  Probe Type              : E Fld Triangle
  Frequency               : 1900 MHz
  Tissue Type             : Muscle
  Calibrated Dielectric   : 53.900
  Calibrated Conductivity :  1.480
  Calibrated Density      :  1.000
  Probe Offset            :  2.400 mm
  Conversion Factor       :  4.500
  Probe Sensitivity :  3.000   2.995   2.653   mV/(mW/cm^2)
  Amplifier Gains   :  20.00   20.00   20.00

Sample:
  Rate:         6000 Samples/Sec
  Count:        100 Samples
  NIDAQ Gain:   5

Comments:
  PCS CH-1175
  Body
  CF=1; Amb. Temp= 21.1 'C; Liq. Temp=21.0 'C
```

Area Scan - Max Peak SAR Value at x=-5.0 y=-9.0 = 0.27 W/kg

Zoom Scan - Max Peak SAR Value at x=-5.0 y=-17.0 z=0.0 = 0.84 W/kg

Max 1g SAR at x=-4.0 y=-15.0 z=0.0 = 0.34 W/kg

Max 10g SAR at x=-4.0 y=-10.0 z=0.0 = 0.18 W/kg

SAR - Z Axis
at Hotspot x:-5.0 y:-17.0



1g SAR Values