PCTEST ENGINEERING LABORATORY, INC.
6660 – B Dobbin Road • Columbia, MD 21045 • USA
Telephone 410.290.6652 / Fax 410.290.6654
http://www.pctestlab.com (email: randy@pctestlab.com)

CERTIFICATE OF COMPLIANCE (SAR EVALUATION)

APPLICANT NAME & ADDRESS:
SAMSUNG ELECTRONICS CO., LTD.
416 Maetan-3 Dong, Paldal-Ku
Suwon City Kyungki-Do 441-742, KOREA
Attn: Wallace Oh, Engineering Manager
Samsung Electronics America (QA Lab)

DATE & LOCATION OF TESTING:
Dates of Tests: April 8-12, 2002
Test Report S/N: 22/24.220408154.A3L
Test Site: PCTEST Lab, Columbia MD

FCC ID:	**A3LSPHA520**
APPLICANT:	**SAMSUNG ELECTRONICS CO., LTD.**

EUT Type:	**Tri-Mode Dual-Band Analog/PCS Phone (AMPS/CDMA)**
Tx Frequency:	**824.04 – 848.97 MHz (AMPS) / 824.70 – 848.31 MHz (CDMA)** **1851.25 – 1908.75 MHz (PCS CDMA)**
Rx Frequency:	**869.04 – 893.97 MHz (AMPS) / 869.70 – 893.31 MHz (CDMA)** **1931.25 – 1988.75 MHz (PCS CDMA)**
Max. RF Output Power:	**0.397 W ERP AMPS (25.983 dBm) / 26.5 dBm Conducted** **0.274 W ERP CDMA (24.383 dBm) / 25.0 dBm Conducted** **0.341 W EIRP PCS CDMA (25.331 dBm) / 25.0 dBm Conducted**
Max. SAR Measurement:	**1.220W/kg AMPS Head SAR; 1.110W/kg AMPS Body SAR;** **0.849W/kg CDMA Head SAR; 0.508W/kg CDMA Body SAR;** **0.601W/kg PCS CDMA Head SAR; 0.455W/kg PCS CDMA Body SAR**
Trade Name/Model(s):	***SPH-A520***
FCC Classification:	**Licensed Portable Transmitter Held to Ear (PCE)**
FCC Rule Part(s):	**§2.1093; FCC/OET Bulletin 65 Supplement C [July 2001]**
Application Type:	**Certification**
Test Device Serial No.:	***identical* prototype**

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE Std. C95.1-1992 and had been tested in accordance with the measurement procedures specified in FCC/OET Bulletin 65 Supplement C (2001) and IEEE Std. 1528-200X (Draft 6.4, July 2001).

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

Randy Ortanez
President

© 2002 PCTEST Engineering Laboratory, Inc

12. SYSTEM VERIFICATION

Tissue Verification

Table 12.1 Simulated Tissue Verification [5]

MEASURED TISSUE PARAMETERS									
Date(s)	04/01/02	835MHz Brain		835MHz Muscle		1900MHz Brain		1900MHz Muscle	
Liquid Temperature (°C)	22.9	Target	Measured	Target	Measured	Target	Measured	Target	Measured
Dielectric Constant: ε		41.50	40.64	55.20	55.45	40.00	40.29	53.30	54.70
Conductivity: σ		0.900	0.935	0.970	0.940	1.400	1.420	1.520	1.470

Test System Validation

Prior to assessment, the system is verified to the ±10% of the specifications at 835MHz and 1900MHz by using the system validation kit(s). (Graphic Plots Attached)

Table 12.2 System Validation [5]

SYSTEM DIPOLE VALIDATION TARGET & MEASURED				
System Validation Kit: D-835V2, S/N: 406	835MHz Brain	Targeted SAR_{1g} (mW/g) 2.375	Measured SAR_{1g} (mW/g) **2.33**	Deviation (%) **- 1.9**
System Validation Kit: D-1900V2, S/N: 502	1900MHz Brain	Targeted SAR_{1g} (mW/g) 9.925	Measured SAR_{1g} (mW/g) **10.2**	Deviation (%) **+ 2.7**



Figure 12.1 Dipole Validation Test Setup

© 2002 PCTEST Engineering Laboratory, Inc

13. SAR TEST DATA SUMMARY

See Measurement Result Data Pages

Procedures Used To Establish Test Signal

The handset was placed into simulated call mode (AMPS, Cellular CDMA & PCS CDMA modes) using manufacturers test codes. Such test signals offer a consistent means for testing SAR and are recommended for evaluating SAR [4]. When test modes are not available or inappropriate for testing a handset, the actual transmission is activated through a base station simulator or similar equipment. See data pages for actual procedure used in measurement.

Device Test Conditions

The handset is battery operated. Each SAR measurement was taken with a fully charged battery. In order to verify that the device was tested at full power, conducted output power measurements were performed before and after each SAR measurement to confirm the output power. If a conducted power deviation of more than 5% occurred, the test was repeated.

EUT Handset Reference Points



Figure 13.1 Handset Reference Points

© 2002 PCTEST Engineering Laboratory, Inc

SAR DATA SUMMARY

Mixture Type: 835MHz Brain

14.1 MEASUREMENT RESULTS (AMPS Right Head SAR – Touch)

FREQUENCY		Modulation	Begin / End POWER‡			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
824.04	0991	AMPS	26.6	26.5	Standard	Cheek / Touch	In	**0.881**
824.04	0991	AMPS	26.6	26.5	Standard	Cheek / Touch	Out	**0.650**
836.49	0383	AMPS	26.6	26.5	Standard	Cheek / Touch	In	**1.170**
836.49	0383	AMPS	26.6	26.5	Standard	Cheek / Touch	Out	**0.986**
848.97	0799	AMPS	26.6	26.5	Standard	Cheek / Touch	In	**1.200**
848.97	0799	AMPS	26.6	26.5	Standard	Cheek / Touch	Out	**1.220**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Brain 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings.

	‡Power Measured	☒ Conducted	☐ ERP	☐ EIRP
4.	SAR Measurement System	☒ DASY3	☐ IDX	☐
	Phantom Configuration	☐ Left Head	☐ Flat Phantom	☒ Right Head
5.	SAR Configuration	☒ Head	☐ Body	☐ Hand
6.	Test Signal Call Mode	☒ Manu. Test Codes	☐ Base Station Simulator	

7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15 cm.

Randy Ortanez
President

Figure 14.1 Right Head SAR Test Setup
-- Cheek / Touch Position --

© 2002 PCTEST Engineering Laboratory, Inc

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Brain

14.2 MEASUREMENT RESULTS (AMPS Right Head SAR – Tilt)

FREQUENCY		Modulation	Begin / End POWER‡			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
824.04	0991	AMPS	26.6	26.5	Standard	Ear / 15° Tilt	In	**0.186**
824.04	0991	AMPS	26.6	26.5	Standard	Ear / 15° Tilt	Out	**0.139**
836.49	0383	AMPS	26.6	26.5	Standard	Ear / 15° Tilt	In	**0.283**
836.49	0383	AMPS	26.6	26.5	Standard	Ear / 15° Tilt	Out	**0.233**
848.97	0799	AMPS	26.6	26.5	Standard	Ear / 15° Tilt	In	**0.296**
848.97	0799	AMPS	26.6	26.5	Standard	Ear / 15° Tilt	Out	**0.273**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Brain 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings.

	‡Power Measured	☒	Conducted	☐	ERP	☐ EIRP
4.	SAR Measurement System	☒	DASY3	☐	IDX	☐
	Phantom Configuration	☐	Left Head	☐	Flat Phantom	☒ Right Head
5.	SAR Configuration	☒	Head	☐	Body	☐ Hand
6.	Test Signal Call Mode	☒	Manu. Test Codes	☐	Base Station Simulator	

7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15 cm.

Randy Ortanez
President

Figure 14.2 Right Head SAR Test Setup
-- Ear / 15° Tilt Position --

© 2002 PCTEST Engineering Laboratory, Inc

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Brain

14.3 MEASUREMENT RESULTS (AMPS Left Head SAR - Touch)

FREQUENCY		Modulation	Begin / End POWER‡			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
824.04	0991	AMPS	26.6	26.5	Standard	Cheek / Touch	In	**0.712**
824.04	0991	AMPS	26.6	26.5	Standard	Cheek / Touch	Out	**0.584**
836.49	0383	AMPS	26.6	26.5	Standard	Cheek / Touch	In	**1.050**
836.49	0383	AMPS	26.6	26.5	Standard	Cheek / Touch	Out	**0.746**
848.97	0799	AMPS	26.6	26.5	Standard	Cheek / Touch	In	**1.080**
848.97	0799	AMPS	26.6	26.5	Standard	Cheek / Touch	Out	**1.010**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Brain 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings.

‡Power Measured	☒ Conducted	☐ ERP	☐ EIRP	
4. SAR Measurement System	☒ DASY3	☐ IDX	☐	
Phantom Configuration	☒ Left Head	☐ Flat Phantom	☐ Right Head	
5. SAR Configuration	☒ Head	☐ Body	☐ Hand	
6. Test Signal Call Mode	☒ Manu. Test Codes	☐ Base Station Simulator		

7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15 cm.

Randy Ortanez
President

Figure 14.3 Left Head SAR Test Setup -- Cheek / Touch Position --

© 2002 PCTEST Engineering Laboratory, Inc

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Brain

14.4 MEASUREMENT RESULTS (AMPS Left Head SAR – Tilt)

FREQUENCY		Modulation	Begin / End POWER‡			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
824.04	0991	AMPS	26.6	26.5	Standard	Ear / 15° Tilt	In	**0.209**
824.04	0991	AMPS	26.6	26.5	Standard	Ear / 15° Tilt	Out	**0.170**
836.49	0383	AMPS	26.6	26.5	Standard	Ear / 15° Tilt	In	**0.289**
836.49	0383	AMPS	26.6	26.5	Standard	Ear / 15° Tilt	Out	**0.215**
848.97	0799	AMPS	26.6	26.5	Standard	Ear / 15° Tilt	In	**0.290**
848.97	0799	AMPS	26.6	26.5	Standard	Ear / 15° Tilt	Out	**0.270**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Brain 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings.

‡Power Measured	☒ Conducted	☐ ERP	☐ EIRP	
4. SAR Measurement System	☒ DASY3	☐ IDX	☐	
Phantom Configuration	☒ Left Head	☐ Flat Phantom	☐ Right Head	
5. SAR Configuration	☒ Head	☐ Body	☐ Hand	
6. Test Signal Call Mode	☒ Manu. Test Codes	☐ Base Station Simulator		

7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15 cm.

Randy Ortanez
President

Figure 14.4 Left Head SAR Test Setup
-- Ear / 15° Tilt Position --

© 2002 PCTEST Engineering Laboratory, Inc

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Brain

14.5 MEASUREMENT RESULTS (CELLULAR CDMA Right Head SAR – Tilt)

FREQUENCY		Modulation	Begin / End POWER‡			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
824.70	1013	CDMA	25.1	25.0	Standard	Ear / 15° Tilt	In	**0.573**
824.70	1013	CDMA	25.1	25.0	Standard	Ear / 15° Tilt	Out	**0.427**
836.49	0383	CDMA	25.1	25.0	Standard	Ear / 15° Tilt	In	**0.789**
836.49	0383	CDMA	25.1	25.0	Standard	Ear / 15° Tilt	Out	**0.581**
848.31	0777	CDMA	25.1	25.0	Standard	Ear / 15° Tilt	In	**0.752**
848.31	0777	CDMA	25.1	25.0	Standard	Ear / 15° Tilt	Out	**0.849**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Brain 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings.

	‡Power Measured	☒	Conducted	☐	ERP	☐ EIRP
4.	SAR Measurement System	☒	DASY3	☐	IDX	☐
	Phantom Configuration	☐	Left Head	☐	Flat Phantom	☒ Right Head
5.	SAR Configuration	☒	Head	☐	Body	☐ Hand
6.	Test Signal Call Mode	☒	Manu. Test Codes	☐	Base Station Simulator	

7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15 cm.

Randy Ortanez
President

Figure 14.5 Right Head SAR Test Setup
-- Ear / 15° Tilt Position --

© 2002 PCTEST Engineering Laboratory, Inc

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Brain

14.6 MEASUREMENT RESULTS (PCS CDMA Right Head SAR – Touch)

FREQUENCY		Modulation	Begin / End POWER‡			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
1851.25	0025	CDMA	25.1	25.0	Standard	Cheek / Touch	In	**0.444**
1851.25	0025	CDMA	25.1	25.0	Standard	Cheek / Touch	Out	**0.425**
1880.00	0600	CDMA	25.1	25.0	Standard	Cheek / Touch	In	**0.375**
1880.00	0600	CDMA	25.1	25.0	Standard	Cheek / Touch	Out	**0.367**
1908.75	1175	CDMA	25.1	25.0	Standard	Cheek / Touch	In	**0.328**
1908.75	1175	CDMA	25.1	25.0	Standard	Cheek / Touch	Out	**0.320**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Brain 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings.

	‡Power Measured	☒	Conducted	☐	ERP	☐ EIRP
4.	SAR Measurement System	☒	DASY3	☐	IDX	☐
	Phantom Configuration	☐	Left Head	☐	Flat Phantom	☒ Right Head
5.	SAR Configuration	☒	Head	☐	Body	☐ Hand
6.	Test Signal Call Mode	☒	Manu. Test Codes	☐	Base Station Simulator	

7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15 cm.

Randy Ortanez
President

Figure 14.6 Right Head SAR Test Setup -- Cheek / Touch Position --

© 2002 PCTEST Engineering Laboratory, Inc

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Brain

14.7 MEASUREMENT RESULTS (PCS CDMA Right Head SAR – Tilt)

FREQUENCY		Modulation	Begin / End POWER‡			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
1851.25	0025	CDMA	25.1	25.0	Standard	Ear / 15° Tilt	In	**0.178**
1851.25	0025	CDMA	25.1	25.0	Standard	Ear / 15° Tilt	Out	**0.171**
1880.00	0600	CDMA	25.1	25.0	Standard	Ear / 15° Tilt	In	**0.145**
1880.00	0600	CDMA	25.1	25.0	Standard	Ear / 15° Tilt	Out	**0.139**
1908.75	1175	CDMA	25.1	25.0	Standard	Ear / 15° Tilt	In	**0.113**
1908.75	1175	CDMA	25.1	25.0	Standard	Ear / 15° Tilt	Out	**0.108**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Brain 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings.

	‡Power Measured	☒	Conducted	☐	ERP	☐ EIRP
4.	SAR Measurement System	☒	DASY3	☐	IDX	☐
	Phantom Configuration	☐	Left Head	☐	Flat Phantom	☒ Right Head
5.	SAR Configuration	☒	Head	☐	Body	☐ Hand
6.	Test Signal Call Mode	☒	Manu. Test Codes	☐	Base Station Simulator	

7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15 cm.

Randy Ortanez
President

Figure 14.7 Right Head SAR Test Setup
-- Ear / Tilt Position --

© 2002 PCTEST Engineering Laboratory, Inc

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Brain

14.8 MEASUREMENT RESULTS (PCS CDMA Left Head SAR – Touch)

FREQUENCY		Modulation	Begin / End POWER‡			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
1851.25	0025	CDMA	25.1	25.0	Standard	Cheek / Touch	In	**0.596**
1851.25	0025	CDMA	25.1	25.0	Standard	Cheek / Touch	Out	**0.601**
1880.00	0600	CDMA	25.1	25.0	Standard	Cheek / Touch	In	**0.582**
1880.00	0600	CDMA	25.1	25.0	Standard	Cheek / Touch	Out	**0.582**
1908.75	1175	CDMA	25.1	25.0	Standard	Cheek / Touch	In	**0.348**
1908.75	1175	CDMA	25.1	25.0	Standard	Cheek / Touch	Out	**0.331**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Brain 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings.

	‡Power Measured	☒	Conducted	☐	ERP	☐ EIRP
4.	SAR Measurement System	☒	DASY3	☐	IDX	☐
	Phantom Configuration	☒	Left Head	☐	Flat Phantom	☐ Right Head
5.	SAR Configuration	☒	Head	☐	Body	☐ Hand
6.	Test Signal Call Mode	☒	Manu. Test Codes	☐	Base Station Simulator	

7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15 cm.

Randy Ortanez
President

Figure 14.8 Left Head SAR Test Setup -- Cheek / Touch Position --

© 2002 PCTEST Engineering Laboratory, Inc

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Brain

14.9 MEASUREMENT RESULTS (PCS CDMA Left Head SAR – Tilt)

FREQUENCY		Modulation	Begin / End POWER‡			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
1851.25	0025	CDMA	25.1	25.0	Standard	Ear / 15° Tilt	In	**0.249**
1851.25	0025	CDMA	25.1	25.0	Standard	Ear / 15° Tilt	Out	**0.213**
1880.00	0600	CDMA	25.1	25.0	Standard	Ear / 15° Tilt	In	**0.212**
1880.00	0600	CDMA	25.1	25.0	Standard	Ear / 15° Tilt	Out	**0.201**
1908.75	1175	CDMA	25.1	25.0	Standard	Ear / 15° Tilt	In	**0.144**
1908.75	1175	CDMA	25.1	25.0	Standard	Ear / 15° Tilt	Out	**0.141**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Brain 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings.

‡Power Measured	☒ Conducted	☐ ERP	☐ EIRP	
4. SAR Measurement System	☒ DASY3	☐ IDX	☐	
Phantom Configuration	☒ Left Head	☐ Flat Phantom	☐ Right Head	
5. SAR Configuration	☒ Head	☐ Body	☐ Hand	
6. Test Signal Call Mode	☒ Manu. Test Codes	☐ Base Station Simulator		

7. Tissue parameters and temperatures are listed on the SAR plots.
8. Liquid tissue depth is 15 cm.

Randy Ortanez
President

Figure 14.9 Left Head SAR Test Setup
-- Ear / Tilt Position --

© 2002 PCTEST Engineering Laboratory, Inc

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Muscle

14.10 MEASUREMENT RESULTS (AMPS Body SAR w/o Holster)

FREQUENCY		Modulation	Begin / End POWER‡			Separation Distance (cm) ‡‡	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
824.04	0991	AMPS	26.6	26.5	Standard	1.5 [w/o Holster]	In	**0.797**
824.04	0991	AMPS	26.6	26.5	Standard	1.5 [w/o Holster]	Out	**0.813**
836.49	0383	AMPS	26.6	26.5	Standard	1.5 [w/o Holster]	In	**0.950**
836.49	0383	AMPS	26.6	26.5	Standard	1.5 [w/o Holster]	Out	**0.986**
848.97	0799	AMPS	26.6	26.5	Standard	1.5 [w/o Holster]	In	**1.110**
848.97	0799	AMPS	26.6	26.5	Standard	1.5 [w/o Holster]	Out	**0.999**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Muscle 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in atypical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings.

‡Power Measured	☒ Conducted	☐ ERP	☐ EIRP	
4. SAR Measurement System	☒ DASY3	☐ IDX	☐	
Phantom Configuration	☐ Left Head	☒ Flat Phantom	☐ Right Head	
5. SAR Configuration	☐ Head	☒ Body	☐ Hand	
6. Test Signal Call Mode	☒ Manu. Test Codes	☐ Base Station Simulator		
7. ‡‡Test Configuration	☐ With Holster	☒ Without Holster		

8. Tissue parameters and temperatures are listed on the SAR plots.
9. Both sides of the phone were tested and the worst-case side is reported.
10. Liquid tissue depth is 15 cm.

Randy Ortanez
President

Figure 14.10 Body SAR Test Setup -- w/o Holster --

© 2002 PCTEST Engineering Laboratory, Inc

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Muscle

14.11 MEASUREMENT RESULTS (CELLULAR CDMA Body SAR w/o Holster)

FREQUENCY		Modulation	Begin / End POWER‡			Separation Distance (cm) ‡‡	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
848.31	0777	CDMA	25.1	25.0	Standard	1.5 [w/o Holster]	In	**0.397**
848.31	0777	CDMA	25.1	25.0	Standard	1.5 [w/o Holster]	Out	**0.508**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Muscle 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in atypical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings.

	‡Power Measured	☒	Conducted	☐	ERP	☐	EIRP
4.	SAR Measurement System	☒	DASY3	☐	IDX	☐	
	Phantom Configuration	☐	Left Head	☒	Flat Phantom	☐	Right Head
5.	SAR Configuration	☐	Head	☒	Body	☐	Hand
6.	Test Signal Call Mode	☒	Manu. Test Codes	☐	Base Station Simulator		
7.	‡‡Test Configuration	☐	With Holster	☒	Without Holster		

8. Tissue parameters and temperatures are listed on the SAR plots.
9. Both sides of the phone were tested and the worst-case side is reported.
10. Liquid tissue depth is 15 cm.

Randy Ortanez
President

Figure 14.11 Body SAR Test Setup -- w/o Holster --

© 2002 PCTEST Engineering Laboratory, Inc

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Muscle

14.12 MEASUREMENT RESULTS (PCS CDMA Body SAR w/o Holster)

FREQUENCY		Modulation	Begin / End POWER‡			Separation Distance (cm) ‡‡	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
1851.25	0025	CDMA	25.1	25.0	Standard	1.5 [w/o Holster]	In	**0.310**
1851.25	0025	CDMA	25.1	25.0	Standard	1.5 [w/o Holster]	Out	**0.455**
1880.00	0600	CDMA	25.1	25.0	Standard	1.5 [w/o Holster]	In	**0.305**
1880.00	0600	CDMA	25.1	25.0	Standard	1.5 [w/o Holster]	Out	**0.446**
1908.75	1175	CDMA	25.1	25.0	Standard	1.5 [w/o Holster]	In	**0.308**
1908.75	1175	CDMA	25.1	25.0	Standard	1.5 [w/o Holster]	Out	**0.439**
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						**Muscle 1.6 W/kg (mW/g)** averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in atypical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Battery is fully charged for all readings.

	‡Power Measured	☒	Conducted	☐	ERP	☐	EIRP
4.	SAR Measurement System	☒	DASY3	☐	IDX	☐	
	Phantom Configuration	☐	Left Head	☒	Flat Phantom	☐	Right Head
5.	SAR Configuration	☐	Head	☒	Body	☐	Hand
6.	Test Signal Call Mode	☒	Manu. Test Codes	☐	Base Station Simulator		
7.	‡‡Test Configuration	☐	With Holster	☒	Without Holster		

8. Tissue parameters and temperatures are listed on the SAR plots.
9. Both sides of the phone were tested and the worst-case side is reported.
10. Liquid tissue depth is 15 cm.

Randy Ortanez
President

Figure 14.12 Body SAR Test Setup -- w/o Holster --

© 2002 PCTEST Engineering Laboratory, Inc

15. SAR TEST EQUIPMENT

Equipment Calibration

Table 15.1 Test Equipment Calibration

EQUIPMENT SPECIFICATIONS			
Type		**Calibration Date**	**Serial Number**
Stäubli Robot RX60L		February 2002	599131-01
Stäubli Robot Controller		February 2002	PCT592
Stäubli Teach Pendant (Joystick)		February 2002	3323-00161
Micron Computer, 450 MHz Pentium III, Windows NT		February 2002	PCT577
SPEAG EDC3		February 2002	321
SPEAG DAE3		February 2002	330
SPEAG E-Field Probe ET3DV6		February 2002	1560
SPEAG Dummy Probe		February 2002	PCT583
SPEAG SAM Twin Phantom V4.0		February 2002	PCT666
SPEAG Light Alignment Sensor		February 2002	205
SPEAG Validation Dipole D1900V2		February 2002	PCT613
Brain Equivalent Matter (835MHz)		April 2002	PCTBEM101
Brain Equivalent Matter (1900MHz)		April 2002	PCTBEM301
Muscle Equivalent Matter (835MHz)		April 2002	PCTMEM201
Muscle Equivalent Matter (1900MHz)		April 2002	PCTMEM401
Microwave Amp. Model: 5S1G4, (800MHz - 4.2GHz)		January 2002	22332
Gigatronics 8651A Power Meter		January 2002	1835299
HP-8648D (9kHz ~ 4GHz) Signal Generator		January 2002	PCT530
Amplifier Research 5S1G4 Power Amp		January 2002	PCT540
HP-8753E (30kHz ~ 3GHz) Network Analyzer		January 2002	PCT552
HP85070B Dielectric Probe Kit		January 2002	PCT501
Ambient Noise/Reflection, etc.	<12mW/kg/<3%of SAR	January 2002	Anechoic Room PCT01

NOTE:

The E-field probe was calibrated by SPEAG, by temperature measurement procedure. Dipole Validation measurement is performed by PCTEST Lab. before each test. The brain simulating material is calibrated by PCTEST using the dielectric probe system and network analyzer to determine the conductivity and permittivity (dielectric constant) of the brain-equivalent material.

© 2002 PCTEST Engineering Laboratory, Inc

SAMSUNG FCC ID: A3LSPHA520 -- FM Head SAR

SAM Phantom; Right Hand Section; Probe:ET3DV6 - SN1560; ConvF(6.78,6.78,6.78)

Med. Parameters 835 MHz Brain: σ = 0.94 mho/m ε_r = 40.6 ρ = 1.00 g/cm^3; Antenna Position -- Out; Crest Factor 1.0

SAR (1g): 1.22 mW/g, SAR (10g): 0.781 mW/g

SAMSUNG TriMode Phone Model: SPH-A520

FM Mode, Ch.0799 [848.97MHz]; Standard Battery; Flip = open; Ambient Temp. = 22.3°C / Meas. Tissue Temp. = 22.2°C

Conducted Power = 26.5dBm; Right Head Phantom, Cheek/Touch position

Test Date -- 04/08/2002 [FCC/OET Bulletin 65 - Supplement C, July 2001]



SAMSUNG FCC ID: A3LSPHA520 -- FM Head SAR

SAM Phantom; Right Hand Section; Probe:ET3DV6 - SN1560; ConvF(6.78,6.78,6.78)

Med. Parameters 835 MHz Brain: σ = 0.94 mho/m ε_r = 40.6 ρ = 1.00 g/cm^3; Antenna Position -- In; Crest Factor 1.0

SAR (1g): 0.296 mW/g, SAR (10g): 0.212 mW/g

SAMSUNG TriMode Phone Model: SPH-A520

FM Mode, Ch.0799 [848.97MHz]; Standard Battery; Flip = open; Ambient Temp. = 22.3°C / Meas. Tissue Temp. = 22.2°C

Conducted Power = 26.5dBm; Right Head Phantom, Ear/15° Tilt position

Test Date -- 04/08/2002 [FCC/OET Bulletin 65 - Supplement C, July 2001]



SAMSUNG FCC ID: A3LSPHA520 -- FM Head SAR

SAM Phantom; Left Hand Section; Probe:ET3DV6 - SN1560; ConvF(6.78,6.78,6.78)

Med. Parameters 835 MHz Brain: σ = 0.94 mho/m ε_r = 40.6 ρ = 1.00 g/cm^3; Antenna Position -- In; Crest Factor 1.0

SAR (1g): 1.08 mW/g, SAR (10g): 0.710 mW/g

SAMSUNG TriMode Phone Model: SPH-A520

FM Mode, Ch.0799 [848.97MHz]; Standard Battery; Flip = open; Ambient Temp. = 22.3°C / Meas. Tissue Temp. = 22.2°C

Conducted Power = 26.5dBm; Left Head Phantom, Cheek/Touch position

Test Date -- 04/08/2002 [FCC/OET Bulletin 65 - Supplement C, July 2001]



SAMSUNG FCC ID: A3LSPHA520 -- FM Head SAR

SAM Phantom; Left Hand Section; Probe:ET3DV6 - SN1560; ConvF(6.78,6.78,6.78)

Med. Parameters 835 MHz Brain: σ = 0.94 mho/m ε_r = 40.6 ρ = 1.00 g/cm^3; Antenna Position -- In; Crest Factor 1.0

SAR (1g): 0.290 mW/g, SAR (10g): 0.204 mW/g

SAMSUNG TriMode Phone Model: SPH-A520

FM Mode, Ch.0799 [848.97MHz]; Standard Battery; Flip = open; Ambient Temp. = 22.3°C / Meas. Tissue Temp. = 22.2°C

Conducted Power = 26.5dBm; Left Head Phantom, Ear/15° Tilt position

Test Date -- 04/08/2002 [FCC/OET Bulletin 65 - Supplement C, July 2001]



SAMSUNG FCC ID: A3LSPHA520 -- Cellular CDMA Head SAR

SAM Phantom; Right Hand Section; Probe:ET3DV6 - SN1560; ConvF(6.78,6.78,6.78)

Med. Parameters 835 MHz Brain: σ = 0.94 mho/m ε_r = 40.6 ρ = 1.00 g/cm^3; Antenna Position -- Out; Crest Factor 1.0

SAR (1g): 0.849 mW/g, SAR (10g): 0.551 mW/g

SAMSUNG TriMode Phone Model: SPH-A520

Cellular CDMA Mode, Ch.0777 [848.31MHz]; Standard Battery; Flip = open; Ambient Temp. = 22.3°C / Meas. Tissue Temp. = 22.2°C

Conducted Power = 25.0dBm; Right Head Phantom, Cheek/Touch position

Test Date -- 04/08/2002 [FCC/OET Bulletin 65 - Supplement C, July 2001]



SAMSUNG FCC ID: A3LSPHA520 -- PCS CDMA Head SAR

SAM Phantom; Right Hand Section; Probe:ET3DV6 - SN1560; ConvF(5.16,5.16,5.16)

Med. Parameters 1900 MHz Brain: σ = 1.42 mho/m ε_r = 40.3 ρ = 1.00 g/cm^3; Antenna Position -- In; Crest Factor 1.0

SAR (1g): 0.444 mW/g, SAR (10g): 0.297 mW/g

SAMSUNG TriMode Phone Model: SPH-A520

PCS CDMA Mode, Ch.0025 [1851.25MHz]; Standard Battery; Flip = open; Ambient Temp. = 22.3°C / Meas. Tissue Temp. = 22.1°C

Conducted Power = 25.0dBm; Right Head Phantom, Cheek/Touch position

Test Date -- 04/09/2002 [FCC/OET Bulletin 65 - Supplement C, July 2001]



SAMSUNG FCC ID: A3LSPHA520 -- PCS CDMA Head SAR

SAM Phantom; Right Hand Section; Probe:ET3DV6 - SN1560; ConvF(5.16,5.16,5.16)

Med. Parameters 1900 MHz Brain: σ = 1.42 mho/m ε_r = 40.3 ρ = 1.00 g/cm^3; Antenna Position -- In; Crest Factor 1.0

SAR (1g): 0.178 mW/g, SAR (10g): 0.109 mW/g

SAMSUNG TriMode Phone Model: SPH-A520

PCS CDMA Mode, Ch.0025 [1851.25MHz]; Standard Battery; Flip = open; Ambient Temp. = 22.3°C / Meas. Tissue Temp. = 22.1°C

Conducted Power = 25.0dBm; Right Head Phantom, Ear/15° Tilt position

Test Date -- 04/09/2002 [FCC/OET Bulletin 65 - Supplement C, July 2001]



SAMSUNG FCC ID: A3LSPHA520 -- PCS CDMA Head SAR

SAM Phantom; Left Hand Section; Probe:ET3DV6 - SN1560; ConvF(5.16,5.16,5.16)

Med. Parameters 1900 MHz Brain: σ = 1.42 mho/m ε_r = 40.3 ρ = 1.00 g/cm^3; Antenna Position -- Out; Crest Factor 1.0

SAR (1g): 0.601 mW/g, SAR (10g): 0.369 mW/g

SAMSUNG TriMode Phone Model: SPH-A520

PCS CDMA Mode, Ch.0025 [1851.25MHz]; Standard Battery; Flip = open; Ambient Temp. = 22.3°C / Meas. Tissue Temp. = 22.1°C

Conducted Power = 25.0dBm; Left Head Phantom, Cheek/Touch position

Test Date -- 04/09/2002 [FCC/OET Bulletin 65 - Supplement C, July 2001]



SAMSUNG FCC ID: A3LSPHA520 -- PCS CDMA Head SAR

SAM Phantom; Left Hand Section; Probe:ET3DV6 - SN1560; ConvF(5.16,5.16,5.16)

Med. Parameters 1900 MHz Brain: σ = 1.42 mho/m ε_r = 40.3 ρ = 1.00 g/cm^3; Antenna Position -- In; Crest Factor 1.0

SAR (1g): 0.249 mW/g, SAR (10g): 0.146 mW/g

SAMSUNG TriMode Phone Model: SPH-A520

PCS CDMA Mode, Ch.0025 [1851.25MHz]; Standard Battery; Flip = open; Ambient Temp. = 22.3°C / Meas. Tissue Temp. = 22.1°C

Conducted Power = 25.0dBm; Left Head Phantom, Ear/15° Tilt position

Test Date -- 04/09/2002 [FCC/OET Bulletin 65 - Supplement C, July 2001]



SAMSUNG FCC ID: A3LSPHA520 -- FM Body SAR

SAM Phantom; Flat Section; Probe:ET3DV6 - SN1560; ConvF(6.52,6.52,6.52)

Med. Parameters 835 MHz Muscle: σ = 0.94 mho/m ε_r = 55.5 ρ = 1.00 g/cm^3; Antenna Position -- In; Crest Factor 1.0

SAR (1g): 1.11 mW/g, SAR (10g): 0.742 mW/g

SAMSUNG TriMode Phone Model: SPH-A520

FM Mode, Ch.0799 [848.97MHz]; Standard Battery; Flip = closed; Ambient Temp. = 22.3°C / Meas. Tissue Temp. = 22.2°C

Conducted Power = 26.5dBm; Spacing = 1.5cm from back of phone (antenna side) to flat phantom, No BeltClip/No Holster

Test Date -- 04/10/2002 [FCC/OET Bulletin 65 - Supplement C, July 2001]



SAMSUNG FCC ID: A3LSPHA520 -- Cellular CDMA Body SAR

SAM Phantom; Flat Section; Probe:ET3DV6 - SN1560; ConvF(6.52,6.52,6.52)

Med. Parameters 835 MHz Muscle: σ = 0.94 mho/m ε_r = 55.5 ρ = 1.00 g/cm^3; Antenna Position -- Out; Crest Factor 1.0

SAR (1g): 0.508 mW/g, SAR (10g): 0.357 mW/g

SAMSUNG TriMode Phone Model: SPH-A520

Cellular CDMA Mode, Ch.0777 [848.31MHz]; Standard Battery; Flip = closed; Ambient Temp. = 22.3°C / Meas. Tissue Temp. = 22.2°C

Conducted Power = 25.0dBm; Spacing = 1.5cm from back of phone (antenna side) to flat phantom, No BeltClip/No Holster

Test Date -- 04/10/2002 [FCC/OET Bulletin 65 - Supplement C, July 2001]



SAMSUNG FCC ID: A3LSPHA520 -- PCS CDMA Body SAR

SAM Phantom; Flat Section; Probe:ET3DV6 - SN1560; ConvF(4.70,4.70,4.70)

Med. Parameters 1900 MHz Muscle: σ = 1.47 mho/m ε_r = 54.7 ρ = 1.00 g/cm^3; Antenna Position -- Out; Crest Factor 1.0

SAR (1g): 0.455 mW/g, SAR (10g): 0.253 mW/g

SAMSUNG TriMode Phone Model: SPH-A520

PCS CDMA Mode, Ch.0025 [1851.25MHz]; Standard Battery; Flip = closed; Ambient Temp. = 22.3°C / Meas. Tissue Temp. = 22.0°C

Conducted Power = 25.0dBm; Spacing = 1.5cm from back of phone (antenna side) to flat phantom, No BeltClip/No Holster

Test Date -- 04/10/2002 [FCC/OET Bulletin 65 - Supplement C, July 2001]



SAMSUNG FCC ID: A3LSPHA520 -- FM Head SAR

SAM Phantom; Right Hand Section; Probe: ET3DV6 - SN1560; ConvF(6.78,6.78,6.78)

Med. Parameters 835 MHz Brain: σ = 0.94 mho/m ε_r = 40.6 ρ = 1.00 g/cm^3; Antenna Position -- Out; Crest Factor 1.0

SAR (1g): 1.22 mW/g, SAR (10g): 0.781 mW/g

SAMSUNG TriMode Phone Model: SPH-A520

FM Mode, Ch.0799 [848.97MHz]; Standard Battery; Flip = open; Meas. Tissue Temp. = 22.2°C

Conducted Power = 26.5dBm; Right Head Phantom, Cheek/Touch position

Test Date -- 04/08/2002 [FCC/OET Bulletin 65 - Supplement C, July 2001]



SAMSUNG FCC ID: A3LSPHA520 -- PCS CDMA Head SAR

SAM Phantom; Left Hand Section; Probe: ET3DV6 - SN1560; ConvF(5.16,5.16,5.16)

Med. Parameters 1900 MHz Brain: σ = 1.42 mho/m ε_r = 40.3 ρ = 1.00 g/cm^3; Antenna Position -- Out; Crest Factor 1.0

SAR (1g): 0.601 mW/g, SAR (10g): 0.369 mW/g

SAMSUNG TriMode Phone Model: SPH-A520

PCS CDMA Mode, Ch.0025 [1851.25MHz]; Standard Battery; Flip = open; Meas. Tissue Temp. = 22.1°C

Conducted Power = 25.0dBm; Left Head Phantom, Cheek/Touch position

Test Date -- 04/09/2002 [FCC/OET Bulletin 65 - Supplement C, July 2001]



SAMSUNG FCC ID: A3LSPHA520 -- FM Body SAR

SAM Phantom; Flat Section; Probe: ET3DV6 - SN1560; ConvF(6.52,6.52,6.52)

Med. Parameters 835 MHz Muscle: σ = 0.94 mho/m ε_r = 55.5 ρ = 1.00 g/cm^3; Antenna Position -- In; Crest Factor 1.0

SAR (1g): 1.11 mW/g, SAR (10g): 0.742 mW/g

SAMSUNG TriMode Phone Model: SPH-A520

FM Mode, Ch.0799 [848.97MHz]; Standard Battery; Flip = closed; Ambient Temp. = 22.3°C / Meas. Tissue Temp. = 22.2°C

Conducted Power = 26.5dBm; Spacing = 1.5cm from back of phone (antenna side) to flat phantom, No BeltClip/No Holster

Test Date -- 04/10/2002 [FCC/OET Bulletin 65 - Supplement C, July 2001]



SAMSUNG FCC ID: A3LSPHA520 -- PCS CDMA Body SAR

SAM Phantom; Flat Section; Probe: ET3DV6 - SN1560; ConvF(4.70,4.70,4.70)

Med. Parameters 1900 MHz Muscle: σ = 1.47 mho/m ε_r = 54.7 ρ = 1.00 g/cm^3; Antenna Position -- Out; Crest Factor 1.0

SAR (1g): 0.455 mW/g, SAR (10g): 0.253 mW/g

SAMSUNG TriMode Phone Model: SPH-A520

PCS CDMA Mode, Ch.0025 [1851.25MHz]; Standard Battery; Flip = closed; Ambient Temp. = 22.3°C / Meas. Tissue Temp. = 22.0°C

Conducted Power = 25.0dBm; Spacing = 1.5cm from back of phone (antenna side) to flat phantom, No BeltClip/No Holster

Test Date -- 04/10/2002 [FCC/OET Bulletin 65 - Supplement C, July 2001]