


	1	2	3	4	5	6	7	8
A			Rev. No					
B								
C								
D								
E								
F								
G	Technical Description 1. Use 'FILM' provided by 'SAMSUNG' for letter and contents 2. Background color is 'WHITE', letter color is 'BLACK' (reverse for SAMSUNG LOGO) 3. Put 'release paper' on the back side after the adhesive. 4. No blur and spread for letter 5. Proceed with manufacturing process after the approval of R&D Group 6. The spec. of product must be based on approved limit samples. 7. Stock on as a ROLL 8. Unify material and color as one color (blue) for glassine paper							
H								
I								
J	MAT. White polyester 50 μ				FIN. Semitransparency OPP Lamination + UVP Coating			
K	TITLE SPH-M260		LABEL(R)-MAIN-CHINA					
L	UNIT mm		DESIGNED	CHECKED	APPROVED	PROJECTION		
	TOLERANCE +0.0/-0.1		jukyun Kim	kyeonghwan jo	junesop kim			
	SCALE N/S							
	Manufacture HANSUNG P&I		10-10-11	10-10-11	10-10-11	SHEET NO		1/1
			Doc. CODE		GH68-00000A			

The label is placed inside the battery compartment



Note: The FCC ID label shown will be readily visible at the time of purchase.