



# PCTEST Engineering Laboratory, Inc.

6660-B Dobbin Road • Columbia, MD 21045 • U.S.A.

TEL (410) 290-6652 • FAX (410) 290-6654

<http://www.pctestlab.com>



## CERTIFICATE OF COMPLIANCE FCC Part 24 & 22 Certification

**SAMSUNG ELECTRONICS CO., LTD.**  
416 Maetan-3 Dong, Paldal-Ku  
Suwon City Kyungki-Do 441-742, KOREA  
Attn: Wallace Oh, Engineering Manager  
Samsung Electronics America (QA Lab)

Dates of Tests: February 8-9 & 11-13, 2002  
Test Report S/N: 22/24.220208055.A3L  
Test Site: PCTEST Lab, Columbia MD

FCC ID

**A3LSPHN400**

APPLICANT


**SAMSUNG ELECTRONICS CO., LTD.**

**Classification:** Licensed Portable Transmitter Held to Ear (PCE)  
**FCC Rule Part(s):** §24(E), §22(H), §22.901(d); §2  
**EUT Type:** Tri-Mode Dual-Band Analog/PCS Phone (AMPS/CDMA)  
**Trade Name/Model:** SAMSUNG SCH-N400  
**Tx Frequency Range:** 824.04MHz – 848.97MHz (AMPS) / 824.70 – 848.31MHz (CDMA)  
1851.25MHz – 1908.75MHz (PCS CDMA)  
**Rx Frequency Range:** 869.04MHz – 893.97MHz (AMPS) / 869.70 – 893.31MHz (CDMA)  
1931.25MHz – 1988.75MHz (PCS CDMA)  
**Max. RF Output Power:** 0.349 W ERP AMPS (25.433 dBm) / 0.278 W ERP CDMA (24.433dBm)  
0.582 W EIRP PCS CDMA (27.651 dBm)  
**Max. SAR Measurement:** 1.250mW/g AMPS Head SAR; 1.100mW/g AMPS Body SAR;  
1.010mW/g CDMA Head SAR; 0.848mW/g CDMA Body SAR;  
0.721mW/g PCS Head SAR; 1.320mW/g PCS Body SAR;  
**Emission Designator(s):** 40K0F8W, 40K0F1D, 1M25F9W

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

  
Randy Ortanez  
President



|                                         |                                       |                                   |                                                                                       |                                 |
|-----------------------------------------|---------------------------------------|-----------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| PCTEST™ PT 22/24 REPORT                 | PCTEST EVALUATION REPORT              |                                   |  | Reviewed By:<br>Quality Manager |
| Test Report S/N:<br>22/24.220208055.A3L | Test Dates:<br>Feb. 8-9 & 11-13, 2002 | Phone Type:<br>Tri-mode Dual-Band | FCC ID:<br>A3LSPHN400                                                                 | Page 1 of 30                    |


## TABLE OF CONTENTS

---

|                      |                                          |       |
|----------------------|------------------------------------------|-------|
| <b>ATTACHMENT A:</b> | <b>COVER LETTER(S)</b>                   |       |
| <b>ATTACHMENT B:</b> | <b>ATTESTATION STATEMENT(S)</b>          |       |
| <b>ATTACHMENT C:</b> | <b>TEST REPORT</b>                       |       |
| 1.1                  | SCOPE                                    | 3     |
| 2.1                  | INTRODUCTION                             | 4     |
| 3.1                  | INSERTS PER § 2.1033(d)                  | 5     |
| 4.1                  | DESCRIPTION OF TESTS                     | 6-10  |
| 5.1                  | EFFECTIVE RADIATED POWER OUTPUT          | 11-12 |
| 6.1                  | EQUIVALENT ISOTROPIC RADIATED POWER      | 13    |
| 7.1                  | RADIATED MEASUREMENTS                    | 14-22 |
| 8.1                  | FREQUENCY STABILITY                      | 23-26 |
| 9.1                  | PLOTS OF EMISSIONS                       | 27    |
| 10.1                 | LIST OF TEST EQUIPMENT                   | 28    |
| 11.1                 | SAMPLE CALCULATIONS                      | 29    |
| 12.1                 | CONCLUSION                               | 30    |
| <b>ATTACHMENT D:</b> | <b>TEST PLOTS</b>                        |       |
| <b>ATTACHMENT E:</b> | <b>FCC ID LABEL / LOCATION</b>           |       |
| <b>ATTACHMENT F:</b> | <b>TEST SETUP PHOTOGRAPHS</b>            |       |
| <b>ATTACHMENT G:</b> | <b>EXTERNAL PHOTOGRAPHS</b>              |       |
| <b>ATTACHMENT H:</b> | <b>INTERNAL PHOTOGRAPHS</b>              |       |
| <b>ATTACHMENT I:</b> | <b>BLOCK DIAGRAM(S)</b>                  |       |
| <b>ATTACHMENT J:</b> | <b>SCHEMATIC DIAGRAM(S)</b>              |       |
| <b>ATTACHMENT K:</b> | <b>OPERATIONAL / CIRCUIT DESCRIPTION</b> |       |
| <b>ATTACHMENT L:</b> | <b>PARTS LIST/TUNE UP PROCEDURE</b>      |       |
| <b>ATTACHMENT M:</b> | <b>USER'S MANUAL</b>                     |       |
| <b>ATTACHMENT N:</b> | <b>SAR MEASUREMENT REPORT</b>            |       |
| <b>ATTACHMENT O:</b> | <b>SAR TEST DATA</b>                     |       |
| <b>ATTACHMENT P:</b> | <b>SAR TEST SETUP PHOTOGRAPHS</b>        |       |
| <b>ATTACHMENT Q:</b> | <b>DIPOLE VALIDATION PLOTS</b>           |       |
| <b>ATTACHMENT R:</b> | <b>PROBE CALIBRATION</b>                 |       |


|                                                |                                                                                                              |                                                                                       |                                        |
|------------------------------------------------|--------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>PCTEST™ PT 22/24 REPORT</b>                 |  <b>EVALUATION REPORT</b> |  | <b>Reviewed By:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>22/24.220208055.A3L | <b>Test Dates:</b><br>Feb. 8-9 & 11-13, 2002                                                                 | <b>Phone Type:</b><br>Tri-mode Dual-Band                                              | <b>FCC ID:</b><br>A3LSPHN400           |
| Page 2 of 30                                   |                                                                                                              |                                                                                       |                                        |

# MEASUREMENT REPORT



## 1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.




## § 2.1033 General Information

|                        |                                                                                     |
|------------------------|-------------------------------------------------------------------------------------|
| <b>Applicant Name:</b> | <b>SAMSUNG ELECTRONICS CO., LTD.</b>                                                |
| <b>Address:</b>        | <b>416 Maetan-3 Dong, Paldal-Ku<br/>Suwon City, Kyungki-Do, 441-742, KOREA</b>      |
| <b>Attention:</b>      | <b>Mr. Wallace Oh, Engineering Manager<br/>Samsung Electronics America (QA Lab)</b> |

- **FCC ID:** **A3LSPHN400**
- **Quantity:** Quantity production is planned
- **Emission Designators:** 1M25F9W, 40K0F8W, 40K0F1D
- **Tx Freq. Range:** 824.04 – 848.97 MHz (AMPS)  
824.70 – 848.31 MHz (CDMA)  
1851.25 – 1908.75 MHz (PCS CDMA)
- **Rx Freq. Range:** 869.04 – 893.97 MHz (AMPS)  
869.70 – 893.31 MHz (CDMA)  
1931.25 – 1988.75 MHz (PCS CDMA)
- **Max. Power Rating:** 0.349 W ERP AMPS (25.433 dBm)/ 0.278 W ERP CDMA (24.433dBm)  
0.582 W EIRP PCS CDMA (27.651 dBm)
- **FCC Classification(s):** Licensed Portable Tx Held to Ear (PCE)
- **Equipment (EUT) Type:** Tri-Mode Dual-Band Analog/PCS Phone (AMPS/CDMA)
- **Modulation(s):** AMPS / CDMA
- **Frequency Tolerance:**  $\pm 0.00025\%$  (2.5 ppm)
- **FCC Rule Part(s):** § 24(E), §22(H), §22.901(d)
- **Dates of Tests:** February 8-9 & 11-13, 2002
- **Place of Tests:** PCTEST Lab, Columbia, MD U.S.A.
- **Test Report S/N:** 22/24.220208055.A3L

|                                                |                                                                                                              |                                                                                       |                                        |
|------------------------------------------------|--------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>PCTEST™ PT 22/24 REPORT</b>                 |  <b>EVALUATION REPORT</b> |  | <b>Reviewed By:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>22/24.220208055.A3L | <b>Test Dates:</b><br>Feb. 8-9 & 11-13, 2002                                                                 | <b>Phone Type:</b><br>Tri-mode Dual-Band                                              | <b>FCC ID:</b><br>A3LSPHN400           |
| © 2002 PCTEST ENGINEERING LABORATORY, INC.     |                                                                                                              |                                                                                       | Page 3 of 30                           |


## 2.1 INTRODUCTION



**Figure 1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area.**

These measurement tests were conducted at **PCTEST Engineering Laboratory, Inc.** facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on October 19, 1992.

### Measurement Procedure



**Figure 2. Diagram of 3-meter outdoor test range**

The radiated and spurious measurements were made outdoors at a 3-meter test range (see Figure2). The equipment under test is placed on a wooden turntable 3-meters from the receive antenna.

The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.

|                                                |                                              |                                          |                                        |
|------------------------------------------------|----------------------------------------------|------------------------------------------|----------------------------------------|
| <b>PCTEST™ PT 22/24 REPORT</b>                 | <b>EVALUATION REPORT</b>                     | <b>SAMSUNG</b>                           | <b>Reviewed By:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>22/24.220208055.A3L | <b>Test Dates:</b><br>Feb. 8-9 & 11-13, 2002 | <b>Phone Type:</b><br>Tri-mode Dual-Band | <b>FCC ID:</b><br>A3LSPHN400           |
| Page 4 of 30                                   |                                              |                                          |                                        |

## 3.1 INSERTS

---

### **Function of Active Devices (Confidential)**

The Function of active devices are shown in Attachment K.

### **Block & Schematic Diagrams (Confidential)**

The block diagrams are shown in Attachment I, and the schematic diagrams are shown in Attachment J.

### **Operating Instructions**

The instruction manual is shown in Attachment M.

### **Parts List & Tune-Up Procedure (Confidential)**

The parts list & tune-up procedure is shown in Attachment L.

### **Description of Freq. Stabilization Circuit (Confidential)**

The description of frequency stabilization circuit is shown in Attachment K.

### **Description for Suppression of Spurious Radiation, for Limiting Modulation, and Harmonic Suppresion Circuits (Confidential)**

The description of suppression stabilization circuits is shown in Attachment K.

|                                         |                                                                                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| PCTEST™ PT 22/24 REPORT                 |  EVALUATION REPORT |  | Reviewed By:<br>Quality Manager |
| Test Report S/N:<br>22/24.220208055.A3L | Test Dates:<br>Feb. 8-9 & 11-13, 2002                                                                 | Phone Type:<br>Tri-mode Dual-Band                                                     | FCC ID:<br>A3LSPHN400           |

## 4.1 DESCRIPTION OF TESTS

### 4.2 Transmitter Audio Frequency Response

The frequency response of the audio modulating circuit over the frequency range 100 – 5000 Hz is measured. The audio signal generator is connected to the audio input circuit/microphone of the EUT. The audio signal input is adjusted to obtain 50% modulation at 1kHz and this point is taken as the 0dB reference. With the input held constant and below the limit at all frequencies, the audio signal generator is varied from 100 to 50 kHz.

### 4.3 Audio Low Pass Filter Frequency Response

The response in dB relative to 1kHz is measured using the HP8901 a Modulation Analyzer. For the frequency response of the audio low-pass filter, the audio input is connected at the input to the modulation limiter and the modulated stage. The audio output is connected at the output of the modulated stage. The corresponding plots are shown herein.

### 4.4 Modulation Limiting

The audio signal generator is connected to the audio input circuit/microphone of the EUT. The modulation response is measured for each of the three modulating frequencies (300Hz, 1000 Hz, and 3000Hz), and the input voltage is varied from 30% modulation ( $\pm 3.6$ kHz deviation) to at least 20dB higher than the saturation point. Measurements of modulation and the plots are attached herein. Measurements were performed for ST, SAT, and wide-band data modulations. The corresponding results are shown herein.

Note: ST, SAT, & Wide-Band data were internally generated by the EUT.




Fig. 3. Transmitter Audio Frequency & Tone Modulation Test Setup.

|                                         |                                       |                                   |                       |                                 |
|-----------------------------------------|---------------------------------------|-----------------------------------|-----------------------|---------------------------------|
| PCTEST™ PT 22/24 REPORT                 |                                       | EVALUATION REPORT                 |                       | Reviewed By:<br>Quality Manager |
| Test Report S/N:<br>22/24.220208055.A3L | Test Dates:<br>Feb. 8-9 & 11-13, 2002 | Phone Type:<br>Tri-mode Dual-Band | FCC ID:<br>A3LSPHN400 | Page 6 of 30                    |

## 4.1 DESCRIPTION OF TESTS (CONTINUED)

### 4.5 Occupied Bandwidth Emission Limits

- (a) On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB.
- (b) Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
- (c) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- (d) The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

| BLOCK | Freq. Range (MHz)<br>Transmitter (Tx) | Freq. Range (MHz)<br>Receiver (Rx) |
|-------|---------------------------------------|------------------------------------|
| A     | 1850 - 1865                           | 1930 - 1945                        |
| B     | 1870 - 1885                           | 1950 - 1965                        |
| C     | 1895 - 1910                           | 1975 - 1990                        |
| D     | 1865 - 1870                           | 1945 - 1950                        |
| E     | 1885 - 1890                           | 1965 - 1970                        |
| F     | 1890 - 1895                           | 1970 - 1975                        |

Table 1. Broadband PCS Service Frequency Blocks.

## 4.1 DESCRIPTION OF TESTS (CONTINUED)

### 4.6 Occupied Bandwidth

The audio signal generator is adjusted to 1kHz. The output level is set to  $\pm 6$ kHz deviation. With the level constant, the frequency is set to 2500Hz. Then the audio signal level is increased by 16dB. The occupied bandwidth data is obtained for the SAT (Supervisory Audio Tone), ST (Signaling Tone), WBD (Wideband data), and DTMF (Dual Tone Multi Frequencies). The results are shown on the attached graphs.

Specified Limits:

- On any frequency removed from the assigned carrier frequency by more than 20 kHz, up to and including 45kHz, the sideband is at least 26dB below the carrier.
- On any frequency removed from the assigned carrier frequency by more than 45 kHz, up to and including 90kHz, the sideband is at least 45dB below the carrier.
- On any frequency removed from the assigned carrier frequency by more than 90 kHz, up to the first multiple of the carrier frequency, the sideband is at least 60dB below the carrier or  $40 + \log_{10}$  (mean power output in Watts) dB, whichever is the smaller attenuation.

### 4.7 Spurious and Harmonic Emissions at Antenna Terminal

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to 10 GHz. The transmitter is modulated with a 2500Hz tone at a level of 16dB greater than that required to provide 50% modulation.

At the input terminals of the spectrum analyzer, an isolator (RF circulator with one port terminated with 50 ohms) and an 870 MHz to 890 MHz bandpass filter is connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The rejection of the bandpass filter to signals in the 825 – 845 MHz range is adequate to limit the transmit energy from the test transceiver which appears to a level which will allow the analyzer to measure signals less than – 90dBm. Calibration of the test receiver is performed in the 870 – 890 MHz range to insure accuracy to allow variation in the bandpass filter insertion loss to be calibrated.

### 4.8 Frequencies

At the input terminals of the spectrum analyzer, an isolator (RF pad) and an high-pass filter are connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The high-pass filter (signals below 2 GHz) is to limit the fundamental frequency from interfering with the measurement of low-level spurious and harmonic emissions and to ensure that the preamplifier is not saturated.

|                                         |                                                                                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| PCTEST™ PT 22/24 REPORT                 |  EVALUATION REPORT |  | Reviewed By:<br>Quality Manager |
| Test Report S/N:<br>22/24.220208055.A3L | Test Dates:<br>Feb. 8-9 & 11-13, 2002                                                                 | Phone Type:<br>Tri-mode Dual-Band                                                     | FCC ID:<br>A3LSPHN400           |

#### **4.9 Radiation Spurious and Harmonic Emissions**

Radiation and harmonic emissions above 1 GHz is measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.

|                                                |                                              |                                                                                                       |                              |                                                                                       |                                        |
|------------------------------------------------|----------------------------------------------|-------------------------------------------------------------------------------------------------------|------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>PCTEST™ PT 22/24 REPORT</b>                 |                                              |  EVALUATION REPORT |                              |  | <b>Reviewed By:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>22/24.220208055.A3L | <b>Test Dates:</b><br>Feb. 8-9 & 11-13, 2002 | <b>Phone Type:</b><br>Tri-mode Dual-Band                                                              | <b>FCC ID:</b><br>A3LSPHN400 | Page 9 of 30                                                                          |                                        |

## **5.0 Frequency Stability/Temperature Variation.**

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +60°C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

*Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.0001$  ( $\pm 1$  ppm) of the center frequency.*

### **Time Period and Procedure:**

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (25°C to 27°C to provide a reference).
2. The equipment is subjected to an overnight “soak” at -30°C without any power applied.
3. After the overnight “soak” at 30°C (usually 14-16 hours), the equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within a three minute interval after applying power to the transmitter.
4. Frequency measurements are made at 10°C interval up to room temperature. At least a period of one and one half-hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency were made at 10 intervals starting at 30°C up to +50°C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after reapplying power to the transmitter.
7. The artificial load is mounted external to the temperature chamber.

**NOTE: The EUT is tested down to the battery endpoint.**

|                                         |                                       |                                                                                                       |                       |                                                                                       |                                 |
|-----------------------------------------|---------------------------------------|-------------------------------------------------------------------------------------------------------|-----------------------|---------------------------------------------------------------------------------------|---------------------------------|
| PCTEST™ PT 22/24 REPORT                 |                                       |  EVALUATION REPORT |                       |  | Reviewed By:<br>Quality Manager |
| Test Report S/N:<br>22/24.220208055.A3L | Test Dates:<br>Feb. 8-9 & 11-13, 2002 | Phone Type:<br>Tri-mode Dual-Band                                                                     | FCC ID:<br>A3LSPHN400 | Page 10 of 30                                                                         |                                 |

## 5.1 Test Data

### 5.2 Effective Radiated Power Output

#### A. POWER: Low (Analog Mode)

| Freq. Tuned (MHz) | LEVEL (dBm) | POL (H/V) | ERP (W) | ERP (dBm) |
|-------------------|-------------|-----------|---------|-----------|
| 824.04            | -36.300     | V         | 0.003   | 4.973     |
| 836.49            | -36.000     | V         | 0.003   | 5.429     |
| 848.97            | -36.200     | V         | 0.003   | 5.385     |

#### B. POWER: High (Analog Mode)

| Freq. Tuned (MHz) | LEVEL (dBm) | POL (H/V) | ERP (W) | ERP (dBm) | BATTERY  |
|-------------------|-------------|-----------|---------|-----------|----------|
| 824.04            | -16.300     | V         | 0.31429 | 24.973    | Standard |
| 836.49            | -16.000     | V         | 0.34938 | 25.433    | Standard |
| 848.97            | -16.200     | V         | 0.34553 | 25.385    | Standard |

Note: Standard batteries are the only battery options for this phone

#### NOTES:

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

## 5.1 Test Data

### 5.3 Effective Radiated Power Output

#### A. POWER: **High (CDMA Mode)**

| Freq. Tuned<br>(MHz) | LEVEL<br>(dBm) | POL<br>(H/V) | ERP<br>(W) | ERP<br>(dBm) | BATTERY  |
|----------------------|----------------|--------------|------------|--------------|----------|
| 824.70               | -17.300        | V            | 0.24962    | 23.973       | Standard |
| 835.89               | -17.000        | V            | 0.27751    | 24.433       | Standard |
| 848.31               | -17.200        | V            | 0.27433    | 24.383       | Standard |

Note: Standard batteries are the only battery options for this phone

#### **NOTES:**

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

|                                         |                                                                                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| PCTEST™ PT 22/24 REPORT                 |  EVALUATION REPORT |  | Reviewed By:<br>Quality Manager |
| Test Report S/N:<br>22/24.220208055.A3L | Test Dates:<br>Feb. 8-9 & 11-13, 2002                                                                 | Phone Type:<br>Tri-mode Dual-Band                                                     | FCC ID:<br>A3LSPHN400           |
| Page 12 of 30                           |                                                                                                       |                                                                                       |                                 |

## 6.1 Test Data

### 6.2 Equivalent Isotropic Radiated Power (E.I.R.P.)

#### Radiated measurements at 3 meters

Supply Voltage: 3.6 VDC

Modulation: PCS CDMA

| FREQ .<br>(MHz) | LEVEL<br>(dBm ) | POL<br>(H/V) | Azimuth<br>(angle) | ERP<br>(dBm ) | ERP<br>(W ) | Battery  |
|-----------------|-----------------|--------------|--------------------|---------------|-------------|----------|
| 1851.25         | -15.700         | V            | 60                 | 27.381        | 0.548       | Standard |
| 1880.00         | -15.600         | V            | 60                 | 27.651        | 0.584       | Standard |
| 1908.75         | -16.000         | V            | 60                 | 27.421        | 0.554       | Standard |

Note: Standard batteries are the only battery options for this phone

#### NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

|                                         |                                                                                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| PCTEST™ PT 22/24 REPORT                 |  EVALUATION REPORT |  | Reviewed By:<br>Quality Manager |
| Test Report S/N:<br>22/24.220208055.A3L | Test Dates:<br>Feb. 8-9 & 11-13, 2002                                                                 | Phone Type:<br>Tri-mode Dual-Band                                                     | FCC ID:<br>A3LSPHN400           |
| Page 13 of 30                           |                                                                                                       |                                                                                       |                                 |

## 7.1 Test Data

### 7.2 A MPS Radiated Measurements

#### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.04 MHz  
 CHANNEL: 0991 (Low)  
 MEASURED OUTPUT POWER: 25.433 dBm = 0.349 W  
 MODULATION SIGNAL: FM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  38.43 dBc

| FREQ .<br>(MHz) | LEVEL<br>(dBm ) | POL<br>(H/V) | (dBc) |
|-----------------|-----------------|--------------|-------|
| 1648.08         | -40.98          | V            | 66.4  |
| 2472.12         | -44.48          | V            | 69.9  |
| 3296.16         | -47.38          | V            | 72.8  |
| 4120.20         | -54.28          | V            | 79.7  |
|                 |                 |              |       |

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

|                                         |                                                                                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| PCTEST™ PT 22/24 REPORT                 |  EVALUATION REPORT |  | Reviewed By:<br>Quality Manager |
| Test Report S/N:<br>22/24.220208055.A3L | Test Dates:<br>Feb. 8-9 & 11-13, 2002                                                                 | Phone Type:<br>Tri-mode Dual-Band                                                     | FCC ID:<br>A3LSPHN400           |
| Page 14 of 30                           |                                                                                                       |                                                                                       |                                 |

## 7.1 Test Data (Continued)

### 7.3A MPS Radiated Measurements

#### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.49 MHz  
 CHANNEL: 0383 (Mid)  
 MEASURED OUTPUT POWER: 25.433 dBm = 0.349 W  
 MODULATION SIGNAL: FM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  38.43 dBc

| FREQ .<br>(MHz) | LEVEL<br>(dBm ) | POL<br>(H/V) | (dBc) |
|-----------------|-----------------|--------------|-------|
| 1672.98         | -40.88          | V            | 66.3  |
| 2509.47         | -43.18          | V            | 68.6  |
| 3345.96         | -47.38          | V            | 72.8  |
| 4182.45         | -53.98          | V            | 79.4  |
|                 |                 |              |       |

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

|                                         |                                                                                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| PCTEST™ PT 22/24 REPORT                 |  EVALUATION REPORT |  | Reviewed By:<br>Quality Manager |
| Test Report S/N:<br>22/24.220208055.A3L | Test Dates:<br>Feb. 8-9 & 11-13, 2002                                                                 | Phone Type:<br>Tri-mode Dual-Band                                                     | FCC ID:<br>A3LSPHN400           |
| Page 15 of 30                           |                                                                                                       |                                                                                       |                                 |

## 7.1 Test Data (Continued)

### 7.4 A MPS Radiated Measurements

#### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.97 MHz  
 CHANNEL: 0799 (High)  
 MEASURED OUTPUT POWER: 25.433 dBm = 0.349 W  
 MODULATION SIGNAL: FM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  38.43 dBc

| FREQ .<br>(MHz) | LEVEL<br>(dBm ) | POL<br>(H/V) | (dBc) |
|-----------------|-----------------|--------------|-------|
| 1697.94         | -41.38          | V            | 66.8  |
| 2546.91         | -43.18          | V            | 68.6  |
| 3395.88         | -46.98          | V            | 72.4  |
| 4244.85         | -53.78          | V            | 79.2  |
|                 |                 |              |       |

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

|                                         |                                                                                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| PCTEST™ PT 22/24 REPORT                 |  EVALUATION REPORT |  | Reviewed By:<br>Quality Manager |
| Test Report S/N:<br>22/24.220208055.A3L | Test Dates:<br>Feb. 8-9 & 11-13, 2002                                                                 | Phone Type:<br>Tri-mode Dual-Band                                                     | FCC ID:<br>A3LSPHN400           |
| Page 16 of 30                           |                                                                                                       |                                                                                       |                                 |

## 7.1 Test Data (Continued)

### 7.5 CELLULAR CDMA Radiated Measurements

#### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.70 MHz  
 CHANNEL: 1013 (Low)  
 MEASURED OUTPUT POWER: 24.433 dBm = 0.278 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  37.43 dBc

| FREQ .<br>(MHz) | LEVEL<br>(dBm ) | POL<br>(H/V) | (dBc) |
|-----------------|-----------------|--------------|-------|
| 1649.40         | -41.98          | V            | 66.4  |
| 2474.10         | -45.58          | V            | 70.0  |
| 3298.80         | -49.18          | V            | 73.6  |
| 4123.50         | -56.28          | V            | 80.7  |
|                 |                 |              |       |

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

|                                         |                                                                                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| PCTEST™ PT 22/24 REPORT                 |  EVALUATION REPORT |  | Reviewed By:<br>Quality Manager |
| Test Report S/N:<br>22/24.220208055.A3L | Test Dates:<br>Feb. 8-9 & 11-13, 2002                                                                 | Phone Type:<br>Tri-mode Dual-Band                                                     | FCC ID:<br>A3LSPHN400           |
| Page 17 of 30                           |                                                                                                       |                                                                                       |                                 |

## 7.1 Test Data (Continued)

### 7.6 CELLULAR CDMA Radiated Measurements

#### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 835.89 MHz  
 CHANNEL: 0383 (Mid)  
 MEASURED OUTPUT POWER: 24.433 dBm = 0.278 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  37.43 dBc

| FREQ .<br>(MHz) | LEVEL<br>(dBm ) | POL<br>(H/V) | (dBc) |
|-----------------|-----------------|--------------|-------|
| 1671.78         | -42.08          | V            | 66.5  |
| 2507.67         | -43.38          | V            | 67.8  |
| 3343.56         | -47.88          | V            | 72.3  |
| 4179.45         | -54.18          | V            | 78.6  |
|                 |                 |              |       |

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

|                                         |                                                                                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| PCTEST™ PT 22/24 REPORT                 |  EVALUATION REPORT |  | Reviewed By:<br>Quality Manager |
| Test Report S/N:<br>22/24.220208055.A3L | Test Dates:<br>Feb. 8-9 & 11-13, 2002                                                                 | Phone Type:<br>Tri-mode Dual-Band                                                     | FCC ID:<br>A3LSPHN400           |
| Page 18 of 30                           |                                                                                                       |                                                                                       |                                 |

## 7.1 Test Data (Continued)

### 7.7 CELLULAR CDMA Radiated Measurements

#### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.31 MHz  
 CHANNEL: 0777 (High)  
 MEASURED OUTPUT POWER: 24.433 dBm = 0.278 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  37.43 dBc

| FREQ .<br>(MHz) | LEVEL<br>(dBm ) | POL<br>(H/V) | (dBc) |
|-----------------|-----------------|--------------|-------|
| 1696.62         | -42.68          | V            | 67.1  |
| 2544.93         | -45.18          | V            | 69.6  |
| 3393.24         | -49.78          | V            | 74.2  |
| 4241.55         | -55.48          | V            | 79.9  |
|                 |                 |              |       |

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

|                                         |                                                                                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| PCTEST™ PT 22/24 REPORT                 |  EVALUATION REPORT |  | Reviewed By:<br>Quality Manager |
| Test Report S/N:<br>22/24.220208055.A3L | Test Dates:<br>Feb. 8-9 & 11-13, 2002                                                                 | Phone Type:<br>Tri-mode Dual-Band                                                     | FCC ID:<br>A3LSPHN400           |
| Page 19 of 30                           |                                                                                                       |                                                                                       |                                 |

## 7.1 Test Data (Continued)

### 7.8 PCS CDMA Radiated Measurements

#### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1851.25 MHz  
 CHANNEL: 0025 (Low)  
 MEASURED OUTPUT POWER: 27.651 dBm = 0.582 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  40.65 dBc

| FREQ .<br>(MHz) | LEVEL<br>(dBm ) | POL<br>(H/V) | (dBc) |
|-----------------|-----------------|--------------|-------|
| 3702.50         | -36.83          | V            | 64.5  |
| 5553.75         | -40.03          | V            | 67.7  |
| 7405.00         | -51.53          | V            | 79.2  |
| 9256.25         | -57.53          | V            | 85.2  |
|                 |                 |              |       |

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

|                                         |                                                                                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| PCTEST™ PT 22/24 REPORT                 |  EVALUATION REPORT |  | Reviewed By:<br>Quality Manager |
| Test Report S/N:<br>22/24.220208055.A3L | Test Dates:<br>Feb. 8-9 & 11-13, 2002                                                                 | Phone Type:<br>Tri-mode Dual-Band                                                     | FCC ID:<br>A3LSPHN400           |

## 7.1 Test Data (Continued)

### 7.9 PCS CDMA Radiated Measurements

#### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 0600 (Mid)  
 MEASURED OUTPUT POWER: 27.651 dBm = 0.582 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  40.65 dBc

| FREQ .<br>(MHz) | LEVEL<br>(dBm ) | POL<br>(H/V) | (dBc) |
|-----------------|-----------------|--------------|-------|
| 3760.00         | -35.43          | V            | 63.1  |
| 5640.00         | -39.43          | V            | 67.1  |
| 7520.00         | -50.73          | V            | 78.4  |
| 9400.00         | -57.03          | V            | 84.7  |
|                 |                 |              |       |

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

|                                         |                                                                                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| PCTEST™ PT 22/24 REPORT                 |  EVALUATION REPORT |  | Reviewed By:<br>Quality Manager |
| Test Report S/N:<br>22/24.220208055.A3L | Test Dates:<br>Feb. 8-9 & 11-13, 2002                                                                 | Phone Type:<br>Tri-mode Dual-Band                                                     | FCC ID:<br>A3LSPHN400           |
| Page 21 of 30                           |                                                                                                       |                                                                                       |                                 |

## 7.1 Test Data (Continued)

### 7.10 PCS CDMA Radiated Measurements

#### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1908.75 MHz  
 CHANNEL: 1175 (High)  
 MEASURED OUTPUT POWER: 27.651 dBm = 0.582 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  40.65 dBc

| FREQ .<br>(MHz) | LEVEL<br>(dBm ) | POL<br>(H/V) | (dBc) |
|-----------------|-----------------|--------------|-------|
| 3817.50         | -35.23          | V            | 62.9  |
| 5726.25         | -39.13          | V            | 66.8  |
| 7635.00         | -51.03          | V            | 78.7  |
| 9543.75         | -57.03          | V            | 84.7  |
|                 |                 |              |       |

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

|                                         |                                                                                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| PCTEST™ PT 22/24 REPORT                 |  EVALUATION REPORT |  | Reviewed By:<br>Quality Manager |
| Test Report S/N:<br>22/24.220208055.A3L | Test Dates:<br>Feb. 8-9 & 11-13, 2002                                                                 | Phone Type:<br>Tri-mode Dual-Band                                                     | FCC ID:<br>A3LSPHN400           |
| Page 22 of 30                           |                                                                                                       |                                                                                       |                                 |

## 8.1 Test Data

### 8.2 FREQUENCY STABILITY (AMPS)

OPERATING FREQUENCY: 836,490,011 Hz

CHANNEL: 383


REFERENCE VOLTAGE: 3.6 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

| VOLTAGE<br>(%) | POWER<br>(VDC) | TEMP<br>(°C) | FREQ.<br>(Hz) | Deviation<br>(%) |
|----------------|----------------|--------------|---------------|------------------|
| 100 %          | 3.60           | + 20 (Ref)   | 836,490,011   | 0.000000         |
| 100 %          |                | - 30         | 836,489,902   | 0.000013         |
| 100 %          |                | - 20         | 836,489,919   | 0.000011         |
| 100 %          |                | - 10         | 836,489,927   | 0.000010         |
| 100 %          |                | 0            | 836,489,936   | 0.000009         |
| 100 %          |                | + 10         | 836,489,936   | 0.000009         |
| 100 %          |                | + 20         | 836,490,011   | 0.000000         |
| 100 %          |                | + 25         | 836,490,003   | 0.000001         |
| 100 %          |                | + 30         | 836,489,978   | 0.000004         |
| 100 %          |                | + 40         | 836,490,086   | -0.000009        |
| 100 %          |                | + 50         | 836,490,095   | -0.000010        |
| 100 %          |                | + 60         | 836,490,103   | -0.000011        |
| 85 %           | 3.17           | + 20         | 836,490,011   | 0.000000         |
| 115 %          | 4.14           | + 20         | 836,490,011   | 0.000000         |
| BATT.ENDPOINT  | 2.89           | + 20         | 836,490,011   | 0.000000         |

## 8.1 Test Data (Continued)

### 8.3 FREQUENCY STABILITY (AMPS)



|                                         |                                                                                                       |                                   |                                                                                       |               |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------|-----------------------------------|---------------------------------------------------------------------------------------|---------------|---------------------------------|
| PCTEST™ PT 22/24 REPORT                 |  EVALUATION REPORT |                                   |  |               | Reviewed By:<br>Quality Manager |
| Test Report S/N:<br>22/24.220208055.A3L | Test Dates:<br>Feb. 8-9 & 11-13, 2002                                                                 | Phone Type:<br>Tri-mode Dual-Band | FCC ID:<br>A3LSPHN400                                                                 | Page 24 of 30 |                                 |

## 8.1 Test Data

### 8.4 FREQUENCY STABILITY (PCS)

OPERATING FREQUENCY: 1,880,000,007 Hz

CHANNEL: 600


REFERENCE VOLTAGE: 3.6 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

| VOLTAGE<br>(% ) | POW ER<br>(VDC ) | TEM P<br>(°C) | FREQ .<br>(Hz) | Deviation<br>(% ) |
|-----------------|------------------|---------------|----------------|-------------------|
| 100 %           | 3.60             | + 20 (Ref)    | 1,880,000,007  | 0.000000          |
| 100 %           |                  | - 30          | 1,879,999,819  | 0.000010          |
| 100 %           |                  | - 20          | 1,879,999,800  | 0.000011          |
| 100 %           |                  | - 10          | 1,879,999,781  | 0.000012          |
| 100 %           |                  | 0             | 1,879,999,838  | 0.000009          |
| 100 %           |                  | + 10          | 1,879,999,951  | 0.000003          |
| 100 %           |                  | + 20          | 1,880,000,007  | 0.000000          |
| 100 %           |                  | + 25          | 1,879,999,951  | 0.000003          |
| 100 %           |                  | + 30          | 1,879,999,932  | 0.000004          |
| 100 %           |                  | + 40          | 1,880,000,063  | -0.000003         |
| 100 %           |                  | + 50          | 1,880,000,195  | -0.000010         |
| 100 %           |                  | + 60          | 1,880,000,195  | -0.000010         |
| 85 %            | 3.17             | + 20          | 1,880,000,007  | 0.000000          |
| 115 %           | 4.14             | + 20          | 1,880,000,007  | 0.000000          |
| BATT . ENDPOINT | 2.89             | + 20          | 1,880,000,007  | 0.000000          |

## 8.1 Test Data (Continued)

### 8.5 FREQUENCY STABILITY (PCS)



|                                         |                                                                                                       |                                   |                                                                                       |               |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------|-----------------------------------|---------------------------------------------------------------------------------------|---------------|---------------------------------|
| PCTEST™ PT 22/24 REPORT                 |  EVALUATION REPORT |                                   |  |               | Reviewed By:<br>Quality Manager |
| Test Report S/N:<br>22/24.220208055.A3L | Test Dates:<br>Feb. 8-9 & 11-13, 2002                                                                 | Phone Type:<br>Tri-mode Dual-Band | FCC ID:<br>A3LSPHN400                                                                 | Page 26 of 30 |                                 |

## 9.1 PLOT(S) OF EMISSIONS

---

(SEE ATTACHMENT D)

|                                                |                                              |                                                                                                              |                              |                                                                                                                              |
|------------------------------------------------|----------------------------------------------|--------------------------------------------------------------------------------------------------------------|------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| <b>PCTEST™ PT 22/24 REPORT</b>                 |                                              |  <b>EVALUATION REPORT</b> |                              |  <b>Reviewed By:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>22/24.220208055.A3L | <b>Test Dates:</b><br>Feb. 8-9 & 11-13, 2002 | <b>Phone Type:</b><br>Tri-mode Dual-Band                                                                     | <b>FCC ID:</b><br>A3LSPHN400 | Page 27 of 30                                                                                                                |

## 10.1 TEST EQUIPMENT

| Type                             | Model                                                                       | Cal. Due Date | S/N                    |
|----------------------------------|-----------------------------------------------------------------------------|---------------|------------------------|
| Microwave Spectrum Analyzer      | HP 8566B (100Hz-22GHz)                                                      | 08/15/02      | 3638A08713             |
| Microwave Spectrum Analyzer      | HP 8566B (100Hz-22GHz)                                                      | 04/17/02      | 2542A11898             |
| Spectrum Analyzer/Tracking Gen.  | HP 8591A (100Hz-1.8GHz)                                                     | 08/10/02      | 3144A02458             |
| Signal Generator*                | HP 8640B (500Hz-1GHz)                                                       | 06/03/02      | 2232A19558             |
| Signal Generator*                | HP 8640B (500Hz-1GHz)                                                       | 06/03/02      | 1851A09816             |
| Signal Generator*                | Rohde & Schwarz (0.1-1000MHz)                                               | 09/11/02      | 894215/012             |
| Ailtech/Eaton Receiver           | NM 37/57A-SL (30-1000MHz)                                                   | 04/12/02      | 0792-03271             |
| Ailtech/Eaton Receiver           | NM 37/57A (30-1000MHz)                                                      | 03/11/03      | 0805-03334             |
| Ailtech/Eaton Receiver           | NM 17/27A (0.1-32MHz)                                                       | 09/17/02      | 0608-03241             |
| Quasi-Peak Adapter               | HP 85650A                                                                   | 08/15/02      | 2043A00301             |
| Ailtech/Eaton Adapter            | CCA-7 CISPR/ANSI QP Adapter                                                 | 03/11/03      | 0194-04082             |
| Gigatronix Universal Power Meter | 8657A                                                                       |               | 1835256                |
| Gigatronix Power Sensor          | 80701A (0.05-18GHz)                                                         |               | 1833460                |
| Signal Generator                 | HP 8648D (9kHz-4GHz)                                                        |               | 3613A00315             |
| Amplifier Research               | 5S1G4 (5W, 800MHz-4.2GHz)                                                   |               | 22322                  |
| Network Analyzer                 | HP 8753E (30kHz-3GHz)                                                       |               | JP38020182             |
| Audio Analyzer                   | HP 8903B                                                                    |               | 3011A09025             |
| Modulation Analyzer              | HP 8901A                                                                    |               | 2432A03467             |
| Power Meter                      | HP 437B                                                                     |               | 3125U24437             |
| Power Sensor                     | HP 8482H (30μW-3W)                                                          |               | 2237A02084             |
| Harmonic/Flicker Test System     | HP 6841A (IEC 555-2/3)                                                      |               | 3531A00115             |
| Broadband Amplifier (2)          | HP 8447D                                                                    |               | 1145A00470, 1937A03348 |
| Broadband Amplifier              | HP 8447F                                                                    |               | 2443A03784             |
| Horn Antenna                     | EMCO Model 3115 (1-18GHz)                                                   | 9704-5182     |                        |
| Horn Antenna                     | EMCO Model 3115 (1-18GHz)                                                   | 9205-3874     |                        |
| Horn Antenna                     | EMCO Model 3116 (18-40GHz)                                                  |               | 9203-2178              |
| Biconical Antenna (4)            | Eaton 94455/Eaton 94455-1/Singer 94455-1/Compliance Design 1295, 1332, 0355 |               |                        |
| Log-Spiral Antenna (3)           | Ailtech/Eaton 93490-1                                                       |               | 0608, 1103, 1104       |
| Roberts Dipoles                  | Compliance Design (1 set)                                                   |               |                        |
| Ailtech Dipoles                  | DM-105A (1 set)                                                             |               | 33448-111              |
| EMCO LISN (6)                    | 3816/2                                                                      |               | 1079                   |
| Microwave Preamplifier 40dB Gain | HP 83017A (0.5-26.5GHz)                                                     |               | 3123A00181             |
| Microwave Cables                 | MicroCoax (1.0-26.5GHz)                                                     |               |                        |
| Ailtech/Eaton Receiver           | NM37/57A-SL                                                                 |               | 0792-03271             |
| Spectrum Analyzer                | HP 8594A                                                                    |               | 3051A00187             |
| Spectrum Analyzer (2)            | HP 8591A                                                                    |               | 3034A01395, 3108A02053 |
| Microwave Survey Meter           | Holaday Model 1501 (2.450GHz)                                               |               | 80931                  |
| Digital Thermometer              | Extech Instruments 421305                                                   |               | 426966                 |
| Attenuator                       | HP 8495A (0-70dB) DC-4GHz                                                   |               |                        |
| Bi-Directional Coax Coupler      | Narda 3020A (50-1000MHz)                                                    |               |                        |
| Shielded Screen Room             | RF Lindgren Model 26-2/2-0                                                  |               | 6710 (PCT270)          |
| Shielded Semi-Anechoic Chamber   | Ray Proof Model S81                                                         |               | R2437 (PCT278)         |
| Environmental Chamber            | Associated Systems Model 1025 (Temperature/Humidity)                        |               | PCT285                 |

\* Calibration traceable to the National Institute of Standards and Technology (NIST).

|                                         |                                                                                                       |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| PCTEST™ PT 22/24 REPORT                 |  EVALUATION REPORT |  | Reviewed By:<br>Quality Manager |
| Test Report S/N:<br>22/24.220208055.A3L | Test Dates:<br>Feb. 8-9 & 11-13, 2002                                                                 | Phone Type:<br>Tri-mode Dual-Band                                                     | FCC ID:<br>A3LSPHN400           |

## 11.1 SAMPLE CALCULATIONS

---

### A. Emission Designator

**Emission Designator = 1M25F9W**

CDMA BW = 1.25 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

(Measured at the 99.75% power bandwidth)

**Emission Designator = 40K0F1D**

Necessary Bandwidth:

Necessary Bandwidth (Bn), kHz = 40.0

(Measured at the 99.75% power bandwidth)

**Emission Designator = 40K0F8W**

Necessary Bandwidth:

Necessary Bandwidth (Bn), kHz = 40.0

( Measured at the 99.75% power bandwidth)

### B. Spurious Radiated Emission - PCS Band

**Example: Channel 25 PCS Mode 2<sup>nd</sup> Harmonic (3702.50 MHz)**

The receive analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the receive analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3702.50 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm - (-24.80) = 50.3 dBc

|                                         |                                       |                                   |                       |                                 |
|-----------------------------------------|---------------------------------------|-----------------------------------|-----------------------|---------------------------------|
| PCTEST™ PT 22/24 REPORT                 |                                       | EVALUATION REPORT                 |                       | Reviewed By:<br>Quality Manager |
| Test Report S/N:<br>22/24.220208055.A3L | Test Dates:<br>Feb. 8-9 & 11-13, 2002 | Phone Type:<br>Tri-mode Dual-Band | FCC ID:<br>A3LSPHN400 | Page 29 of 30                   |

## 12.1 CONCLUSION

---

The data collected shows that the **SAMSUNG Tri-Mode Dual-Band Analog/PCS Phone (AMPS/CDMA) FCC ID: A3LSPHN400** complies with all the requirements of Parts 2, 22, and 24 of the FCC rules.

|                                                |                                              |                                                                                                       |                              |                                                                                       |                                        |
|------------------------------------------------|----------------------------------------------|-------------------------------------------------------------------------------------------------------|------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>PCTEST™ PT 22/24 REPORT</b>                 |                                              |  EVALUATION REPORT |                              |  | <b>Reviewed By:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>22/24.220208055.A3L | <b>Test Dates:</b><br>Feb. 8-9 & 11-13, 2002 | <b>Phone Type:</b><br>Tri-mode Dual-Band                                                              | <b>FCC ID:</b><br>A3LSPHN400 | Page 30 of 30                                                                         |                                        |