



HCT CO., LTD.

CERTIFICATION DIVISION

SAN 136-1, AMI-RI, BUBAL-EUP, ICHEON-SI, KYOUNGKI-DO, 467-701, KOREA

TEL : +82 31 639 8518 FAX : +82 31 639 8525 www.hct.co.kr

CERTIFICATE OF COMPLIANCE

FCC PART 27 Certification

Applicant Name:

SAMSUNG Electronics Co., Ltd.
416, Maetan-3dong, Yeongtong-gu, Suwon-si,
Gyeonggi-do, Korea

Date of Issue: December 06, 2010

Test Site/Location:

HCT CO., LTD., 105-1, Jangam-ri, Majang-Myeon,
Icheon-si, Kyunggi-Do, Korea(Lab)

Test Report No.: HCTR1012FR04

FCC ID : **A3LSPI-2213282600**

APPLICANT : **SAMSUNG Electronics Co., Ltd.**

EUT Type : Mobile WiMAX Outdoor RAS
Manufacturer : SAMSUNG Electronics Co., Ltd.
Model name : SPI-2213282600
Frequency of Operation : 2590 MHz ~ 2690 MHz
FCC Rule Part(s) : FCC Part 27 Subpart (c).
Emission Designator : 4M 58G7D(QPSK), 4M58W7D(16QAM/64QAM)
Test Procedure(s) : ANSI/TIA-603C-2004
Application Type : CClass II Permissive Change
Data of issue : December 06, 2010

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that up on the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of FCC Part 27 of the FCC Rules under normal use and maintenance.



Report prepared by
: Chang Seok Choi
Test engineer of RF Team



Approved by
: Sang Jun Lee
Manager of RF Team

FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 1 of 95

Revision

TEST REPORT NO.	DATE	DESCRIPTION
HCTR1012FR04	December 06,2010	First Approval Report

FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 2 of 95

C O N T E N T S

1. GENERAL INFORMATION.....	3
1.1. CLIENT INFORMATION	3
1.2. PRODUCT INFORMATION	3
1.3. OPERATING DESCRIPTION OF EUT	3
2. TEST SUMMARY	3
2.1. STANDARDS	3
2.2. MODE OF OPERATION DURING THE TEST	3
3. STANDARDS ENVIRONMENTAL TEST CONDITIONS	3
4. TEST EQUIPMENT	3
5. CONDUCTED OUTPUT POWER.....	3
5.1. Applicable Standard	3
5.2. Test Equipment List and Details	3
5.3. Test Procedure.....	3
5.3.1. Environmental Conditions:	3
5.4. Test Result	3
5.4.1. Test Data at Output Port 1	3
5.4.2. Test Data at Output Port 2	3
5.4.3. Combined Test Data at Output Port.....	3
5.4.4. Plot Data for Output Port 1 (Conducted Output Power).....	3
5.4.5. Plot Data for Output Port 2 (Conducted Output Power).....	3
5.4.6. Combined Plot Data for Output (Conducted Output Power).....	3
6. OCCUPIED BANDWIDTH	3
6.1. Applicable Standard	3
6.2. Test Equipment List and Details	3
6.3. Test Procedure.....	3
6.3.1. Environmental Conditions:	3
6.4. Test Result	3
6.4.1. Test Data at Output 1.....	3
6.4.2. Test Data at Output Port 2	3
6.4.3. Combined Test Data at Output Port.....	3
6.4.4. Test Plot at Output Port 1	3
6.4.5. Test Plot at Output Port 2	3
6.4.6. Combined Test Plot at Output Port.....	3

FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 3 of 95

7. BAND EDGES	3
7.1. Applicable Standard	3
7.2. Test Equipment List and Details	3
7.3. Test Procedure.....	3
7.3.1. Environmental Conditions.....	3
7.4. Test Result	3
7.4.1. Test data at Output 1	3
7.4.2. Test data at Output 2	3
7.4.3. Combined Test data at Output	3
7.4.4. Plot Data at Output 1	3
7.4.5. Plot Data at Output 2	3
7.4.6. Combined Plot Data at Output	3
8. SPURIOUS EMISSION AT ANTENNA TERMINAL	3
8.1. Applicable Standard: CFR 47§2.1051, §27.53.....	3
8.2. Test Equipment List and Details	3
8.3. Test Procedure.....	3
8.3.1 Environmental Conditions:	3
8.4. Test Result	3
8.4.1. Plot Data at Output Port 1.....	3
8.4.2. Plot Data at Output Port 2.....	3
8.4.3. Combined Plot Data at Output	3
9. RADIATED SPURIOUS EMISSION	3
9.1 Applicable Standard.....	3
9.2 Test Equipment List and Details	3
9.3 Test Procedure.....	3
9.3.1 Radiated Spurious Emissions Test Setup	3
9.3.2 Environmental Conditions:	3
9.4 Test Result	3
10. FREQUECNY STABILITY	3
10.1 Applicable Standard	3
10.2 Test Equipment List and Details	3
10.3 Test Procedure.....	3
10.3.1. Environmental conditions	3
10.4. Test Result	3
10.4.1. Frequency Stability over Temperature and Voltage variation	3
11. RF EXPOSURE STATEMENT	3

FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 4 of 95

1. GENERAL INFORMATION

1.1. CLIENT INFORMATION

Company	Samsung Electronics Co., Ltd.
Contact Point	416, Maetan-3dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
Contact person	Name: JOON-HO LEE / Senior Research Engineer E-mail : joonho@samsung.com Tel: +82-31-279-3552 Fax: +82-31-279-7576

1.2. PRODUCT INFORMATION

EUT TYPE	Mobile WiMAX Outdoor RAS
EMISSION DESIGNATOR	4M58G7D (QPSK), 4M58W7D(16QAM/64QAM)
OPERATING FREQUENCY	2496 MHz ~ 2596 MHz
TX OUTPUT POWER	2 W (33 dBm) / Carrier / Path
CHANNEL BANDWIDTH	5 MHz , 10 MHz
MODULATION TYPE	OFDMA (QPSK, 16QAM, 64QAM)
MAXIMUM NUMBER OF CARRIERS/SECTORS	2 Carriers / 3 Sectors
SYSTEM INPUT VOLTAGE	DC - 48 V

FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR03	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282501	Page 5 of 95

1.3. OPERATING DESCRIPTION OF EUT

The SPI-2213, RAS of Mobile WiMAX, is controlled by ACR and connects Mobile WiMAX calls to MS.

The SPI-2213 interfaces with MS via a wireless channel observing the Mobile WiMAX standard (IEEE 802.16) and provides high-speed data service and multimedia service in wireless broadband.

To this end, the SPI-2213 provides the following functions: modulation/demodulation of packet traffic signal, scheduling and radio bandwidth allocation to manage air resources efficiently and ensure Quality of Service (QoS), Automatic Repeat request (ARQ) processing, ranging function, connection control function to transmit the information on the SPI-2213 and set/hold/disconnect the packet call connection, handover control and ACR interface function and system operation management function.

Physically, the SPI-2213 consists of a Digital Unit (DU) and a Mobile WiMAX base station Remote Radio Head (RRH). The RRH is located remotely from the DU. The DU is a digital unit of 19 in. shelf form and can be installed in an indoor or outdoor 19 in. rack. It supports a capacity up to 2Carrier/3Sector. The DU is operated in omni or sector mode depending on the features of the installation location.

An RRH is a standalone RF unit. It is installed on an outdoor wall or pole.

The SPI-2213 supports up to 2Carrier/3Sector.

FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 6 of 95

2. TEST SUMMARY

2.1. STANDARDS

The following tests were conducted on a sample of the equipment for the purpose of demonstrating compliance With **FCC Part 27**

SECTION	TEST ITEMS	RESULTS
2.1046, 27.50(h)	Conducted Output Power	Compliant
2.1049, 27.53(l)	Occupied Bandwidth	Compliant
2.1051, 27.53(l)	Spurious Emissions at Antenna Terminals	Compliant
2.1051, 27.53(l)	Band edge	Compliant
2.1053, 27.53(l)	Spurious Radiated Emissions.	Compliant
2.1055(a)(1), 27.54	Frequency Stability over Temperature variation	Compliant
2.1055(d), 27.54	Frequency stability over Voltage variation	Compliant

2.2. MODE OF OPERATION DURING THE TEST

The EUT was operated in a manner representative of the typical usage of the equipment.

During all testing, system components were manipulated within the confines of typical usage to maximize each emission. All Modulation (QPSK, 16QAM, and 64QAM) modes were tested, and the worst case was recorded in this test report.

The device does not supply antenna(s) with the system, so the dummy loads were connected to the RF output ports for radiated spurious emission testing.

FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 7 of 95

3. STANDARDS ENVIRONMENTAL TEST CONDITIONS

Temperature :	+ 15 °C to + 35 °C
Relative humidity:	30 % to 60 %
Air pressure	860 mbar to 1060 mbar

FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 8 of 95

4. TEST EQUIPMENT

Manufacturer	Model / Equipment	Serial No.	Calibration Due
Schwarzbeck	BBHA 9120D / Double Ridged Horn Antenna	296	09/23/2011
Schwarzbeck	BBHA 9120D / Double Ridged Horn Antenna	147	04/13/2011
Schwarzbeck	VULB 9168 / TRILOG Antenna	9168-200	01/06/2011
HD	MA240 / Antenna Position Tower	556	N/A
EMCO	1050 / Turn Table	114	N/A
HD GmbH	HD 100 / Controller	13	N/A
HD GmbH	KMS 560 / SlideBar	12	N/A
MITEQ	AFS44-00102650-42-10P44-PS	1532439	04/05/2011
EMCO	6502/Loop Antenna	9009-2536	01/13/2012
R&S	ESI40 / EMI TEST Receiver	831564/003	10/30/2011
Wainwright Instrument	WHF6.0/26.5G-6SS / High Pass Filter	1	05/12/2011
Agilent	6674A / DC Power Supply	3501A00901	05/14/2011
WEINSCHEL	67-30-33 / Attenuator	BU5347	01/06/2011
WEINSCHEL	67-30-33 / Attenuator	BR0530	01/14/2011
WEINSCHEL	AF117A-69-31 / STEP ATTENUATOR	11787	11/12/2011
WEINSCHEL	AF117A-69-31 / STEP ATTENUATOR	639	11/12/2011
Agilent	N9020A / MXA Signal Analyzer	US46220219	03/03/2011
Agilent	11636B / Power Divider	11377	12/24/2010
Schwarzbeck	BBHA 9120D / Double Ridged Horn Antenna	296	09/23/2011

FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 9 of 95

5. CONDUCTED OUTPUT POWER

5.1. Applicable Standard

According to FCC §2.1046 & 27.5(h)

1) *Main, booster and base stations.* (i) The maximum EIRP of a main, booster or base station shall not exceed $33 \text{ dBW} + 10\log(X/Y) \text{ dBW}$, where X is the actual channel width in MHz and Y is either 6 MHz if prior to transition or the station is in the MBS following transition or 5.5 MHz if the station is in the LBS and UBS following transition, except as provided in paragraph (h)(1)(ii) of this section.


5.2. Test Equipment List and Details

Manufacturer	Model / Equipment	Serial No.	Calibration Due
Agilent	6674A / DC Power Supply	3501A00901	05/14/2011
WEINSCHTEL	67-30-33 / Attenuator	BU5347	01/06/2011
WEINSCHTEL	67-30-33 / Attenuator	BR0530	01/14/2011
WEINSCHTEL	AF117A-69-31 / STEP ATTENUATOR	11787	11/12/2011
WEINSCHTEL	AF117A-69-31 / STEP ATTENUATOR	639	11/12/2011
Agilent	N9020A / MXA Signal Analyzer	US46220219	03/03/2011
Agilent	11636B / Power Divider	11377	12/24/2010

5.3. Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 10 of 95



According to FCC §2.1046 (A), for transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in § 2.1033(c). The electrical characteristics of the radio frequency load attached to the output terminals when this test is made shall be stated.

- 1) The radio frequency load attached to the EUT antenna terminal was 50 Ohm. The loss of the cables the test system is calibrated to correct the reading.
- 2) The spectrum analyzer was set to RMS Detector function and Average mode.
- 3) The resolution bandwidth of the spectrum analyzer was comparable to the emission bandwidth.

5.3.1. Environmental Conditions:

Temperature:	27 °C
Relative Humidity:	27 %

5.4. Test Result

: PASS

FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 11 of 95

5.4.1. Test Data at Output Port 1

Modulation	Channel	Frequency	Measured Output Power	
			dBm	W
QPSK	Low	2593.00	32.98	1.986
	Middle	2643.75	33.39	2.183
	High	2686.75	33.18	2.080
16QAM	Low	2593.00	33.50	2.239
	Middle	2643.75	33.31	2.143
	High	2686.75	33.29	2.133
64QAM	Low	2593.00	33.51	2.244
	Middle	2643.75	33.20	2.089
	High	2686.75	33.24	2.109


5.4.2. Test Data at Output Port 2

Modulation	Channel	Frequency	Measured Output Power	
			dBm	W
QPSK	Low	2593.00	33.72	2.355
	Middle	2643.75	33.38	2.178
	High	2686.75	33.70	2.344
16QAM	Low	2593.00	33.70	2.344
	Middle	2643.75	33.40	2.188
	High	2686.75	33.58	2.280
64QAM	Low	2593.00	33.70	2.344
	Middle	2643.75	33.40	2.188
	High	2686.75	33.31	2.143

5.4.3. Combined Test Data at Output Port


Modulation	Channel	Frequency	Measured Output Power	
			dBm	W
QPSK	Low	2593.00	35.06	3.206
	Middle	2643.75	34.79	3.013
	High	2686.75	34.79	3.013
16QAM	Low	2593.00	35.17	3.289
	Middle	2643.75	34.78	3.006
	High	2686.75	34.76	2.992
64QAM	Low	2593.00	35.19	3.304
	Middle	2643.75	34.79	3.013
	High	2686.75	34.74	2.979

[Combine test diagram]




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 13 of 95

5.4.4. Plot Data for Output Port 1 (Conducted Output Power)
(QPSK Low Channel)




(QPSK Middle Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 14 of 95

(QPSK High Channel)




(16QAM Low Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 15 of 95

(16QAM Middle Channel)




(16QAM High Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 16 of 95

(64QAM Low Channel)




(64QAM Middle Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 17 of 95

(64QAM High Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 18 of 95

5.4.5. Plot Data for Output Port 2 (Conducted Output Power)
(QPSK Low Channel)




(QPSK Middle Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 19 of 95

(QPSK High Channel)




(16QAM Low Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 20 of 95

(16QAM Middle Channel)




(16QAM High Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 21 of 95

(64QAM Low Channel)




(64QAM Middle Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 22 of 95

(64QAM High Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 23 of 95

5.4.6. Combined Plot Data for Output (Conducted Output Power)
(QPSK Low Channel)




(QPSK Middle Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 24 of 95

(QPSK High Channel)




(16QAM Low Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 25 of 95

(16QAM Middle Channel)




(16QAM High Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 26 of 95

(64QAM Low Channel)




(64QAM Middle Channel)



FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 27 of 95

(64QAM High Channel)



FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 28 of 95

6. OCCUPIED BANDWIDTH

6.1. Applicable Standard

Requirements: CFR 47, Section 27.53(m)(6) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (*i.e.* 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. With respect to television operations, measurements must be made of the separate visual and aural operating powers at sufficiently frequent intervals to ensure compliance with the rules.


6.2. Test Equipment List and Details

Manufacturer	Model / Equipment	Serial No.	Calibration Due
Agilent	6674A / DC Power Supply	3501A00901	05/14/2011
WEINSCHEL	67-30-33 / Attenuator	BU5347	01/06/2011
WEINSCHEL	67-30-33 / Attenuator	BR0530	01/14/2011
WEINSCHEL	AF117A-69-31 / STEP ATTENUATOR	11787	11/12/2011
WEINSCHEL	AF117A-69-31 / STEP ATTENUATOR	639	11/12/2011
Agilent	N9020A / MXA Signal Analyzer	US46220219	03/03/2011
Agilent	11636B / Power Divider	11377	12/24/2010

6.3. Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 29 of 95



The EUT was connected to a spectrum analyser enabled with an occupied bandwidth function via its antenna port. Measurements were performed to determine the occupied bandwidth in accordance with FCC Part 2.1049. The occupied bandwidth was measured from the fundamental emission at the bottom, middle and top channels. The occupied bandwidth was measured using the built in occupied bandwidth function of the spectrum analyser. It was set to measure the bandwidth where 99% of the signal power was contained. The analyser automatically configures the measurement bandwidths to make an accurate measurement based on the channel bandwidth and channel spacing of the EUT.

6.3.1. Environmental Conditions:

Temperature:	25 °C
Relative Humidity:	27 %

6.4. Test Result

: PASS

FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 30 of 95

6.4.1. Test Data at Output 1

Modulation	Channel	Frequency	Measured Bandwidth	
			99 %	26 dB
QPSK	Low	2593.00	4.5876	4.862
	Middle	2643.75	4.5878	4.862
	High	2686.75	4.5877	4.861
16QAM	Low	2593.00	4.5878	4.860
	Middle	2643.75	4.5882	4.861
	High	2686.75	4.5876	4.860
64QAM	Low	2593.00	4.5884	4.862
	Middle	2643.75	4.5880	4.861
	High	2686.75	4.5878	4.865

6.4.2. Test Data at Output Port 2

Modulation	Channel	Frequency	Measured Bandwidth	
			99 %	26 dB
QPSK	Low	2593.00	4.5881	4.860
	Middle	2643.75	4.5882	4.860
	High	2686.75	4.5881	4.861
16QAM	Low	2593.00	4.5877	4.861
	Middle	2643.75	4.5884	4.863
	High	2686.75	4.5888	4.859
64QAM	Low	2593.00	4.5882	4.861
	Middle	2643.75	4.5886	4.861
	High	2686.75	4.5876	4.859

FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 31 of 95


6.4.3. Combined Test Data at Output Port

Modulation	Channel	Frequency	Measured Bandwidth	
			99 %	26 dB
QPSK	Low	2593.00	4.5149	4.821
	Middle	2643.75	4.4979	4.819
	High	2686.75	4.4866	4.818
16QAM	Low	2593.00	4.5157	4.821
	Middle	2643.75	4.4988	4.820
	High	2686.75	4.4862	4.816
64QAM	Low	2593.00	4.5163	4.822
	Middle	2643.75	4.4988	4.818
	High	2686.75	4.4860	4.816


FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 32 of 95

6.4.4. Test Plot at Output Port 1

(QPSK Low Channel)




(QPSK Middle Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 33 of 95

(QPSK High Channel)




(16QAM Low Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 34 of 95

(16QAM Middle Channel)




(16QAM High Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 35 of 95

(64QAM Low Channel)




(64QAM Middle Channel)



FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 36 of 95


(64QAM High Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 37 of 95

6.4.5. Test Plot at Output Port 2

(QPSK Low Channel)




(QPSK Middle Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 38 of 95

(QPSK High Channel)




(16QAM Low Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 39 of 95

(16QAM Middle Channel)




(16QAM High Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 40 of 95

(64QAM Low Channel)




(64QAM Middle Channel)



FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 41 of 95


(64QAM High Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 42 of 95

6.4.6. Combined Test Plot at Output Port

(QPSK Low Channel)




(QPSK Middle Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 43 of 95

(QPSK High Channel)




(16QAM Low Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 44 of 95

(16QAM Middle Channel)




(16QAM High Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 45 of 95

(64QAM Low Channel)




(64QAM Middle Channel)



FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 46 of 95

(64QAM High Channel)



FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 47 of 95

7. BAND EDGES

7.1. Applicable Standard


According to §27.53(m), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (p) by a factor of at least $43 + 10 \log (p)$ dB.

7.2. Test Equipment List and Details

Manufacturer	Model / Equipment	Serial No.	Calibration Due
Agilent	6674A / DC Power Supply	3501A00901	05/14/2011
WEINSCHTEL	67-30-33 / Attenuator	BU5347	01/06/2011
WEINSCHTEL	67-30-33 / Attenuator	BR0530	01/14/2011
WEINSCHTEL	AF117A-69-31 / STEP ATTENUATOR	11787	11/12/2011
WEINSCHTEL	AF117A-69-31 / STEP ATTENUATOR	639	11/12/2011
Agilent	N9020A / MXA Signal Analyzer	US46220219	03/03/2011
Agilent	11636B / Power Divider	11377	12/24/2010

7.3. Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.



The center of the spectrum analyzer was set to block edge frequency.

FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 48 of 95

The EUT provides the MIMO function which is able to transmit on the same channel with same data simultaneously therefore a combiner is used to sum the individual transmitter output power.

The test data is shown as a combined output in the report.

7.3.1. Environmental Conditions

Temperature:	25 °C
Relative Humidity:	28 %

7.4. Test Result

: PASS

7.4.1. Test data at Output 1

Modulation	Channel	Measured Frequency (MHz)	Max. Measured Value (dBm)	Limit (dBm)
QPSK	Low	2593.00	-39.406	-13.0
	High	2686.75	-37.300	
16QAM	Low	2593.00	-38.058	
	High	2686.75	-36.253	
64QAM	Low	2593.00	-35.413	
	High	2686.75	-34.776	

7.4.2. Test data at Output 2

Modulation	Channel	Measured Frequency (MHz)	Max. Measured Value (dBm)	Limit (dBm)
QPSK	Low	2593.00	-36.444	-13.0
	High	2686.75	-35.726	
16QAM	Low	2593.00	-39.524	
	High	2686.75	-37.420	
64QAM	Low	2593.00	-33.969	
	High	2686.75	-41.037	

FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 49 of 95


7.4.3. Combined Test data at Output

Modulation	Channel	Measured Frequency (MHz)	Max. Measured Value (dBm)	Limit (dBm)
QPSK	Low	2593.00	-42.693	-13.0
	High	2686.75	-42.143	
16QAM	Low	2593.00	-42.143	
	High	2686.75	-44.847	
64QAM	Low	2593.00	-47.219	
	High	2686.75	-41.557	


FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 50 of 95

7.4.4. Plot Data at Output 1

(QPSK Low Channel)




(QPSK High Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 51 of 95

(16QAM Low Channel)




(16QAM High Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 52 of 95

(64QAM Low Channel)




(64QAM High Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 53 of 95

7.4.5. Plot Data at Output 2

(QPSK Low Channel)




(QPSK High Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 54 of 95

(16QAM Low Channel)




(16QAM High Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 55 of 95

(64QAM Low Channel)




(64QAM High Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 56 of 95

7.4.6. Combined Plot Data at Output

(QPSK Low Channel)




(QPSK High Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 57 of 95

(16QAM Low Channel)




(16QAM High Channel)




FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 58 of 95

(64QAM Low Channel)



(64QAM High Channel)



FCC PT.27 TEST REPORT	FCC CERTIFICATION REPORT			HCT PT.27 TEST REPORT
Test Report No. HCTR1012FR04	Date of Issue: December 06, 2010	EUT Type: Mobile WiMAX Outdoor RAS	FCC ID: A3LSPI-2213282600	Page 59 of 95