FCC/IC TEST REPORT

Test report No.:	EMC- FCC- R0211
FCC ID:	A3LSPWB4339S
IC ID:	649E-SPWB4339S
Type of equipment:	Wi-Fi module
Basic Model Name:	SPW-B4339S
Applicant:	Samsung Electronics Co., Ltd.
Max.RF Output Power:	10.37 dBm
FCC Rule Part(s):	FCC Part 15 Subpart C 15.247
IC Rule Part(s):	RSS-210 Issue 8, December 2010 RSS-GEN Issue 4, November 2014
Frequency Range:	2 402 ㎒ ~ 2 480 ㎒
Test result:	Complied

The above equipment was tested by EMC compliance Testing Laboratory for compliance with the requirements of FCC Rules and Regulations.
The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Date of receipt: 2014. 11. 17

Date of test: 2014. 12. 15 ~ 12. 22

Issued date: 2015. 01. 21

Tested by: KIM, SUNG SIN

Approved by: YU, SANG HOON

This test report shall not be reproduced except in full, Without the written approval.

[Contents]

1. Client information **3**
2. Laboratory information **4**
3. Description of E.U.T. **5**
3.1 Basic description 5
3.2 General description 6
3.3 Test frequency 7
3.4 Test Voltage 7
4. Summary of test results **8**
4.1 Standards & results 8
4.2 Uncertainty 8
5. Test results **9**
5.1 Antenna Requirement 9
5.2 Maximum Peak Output Power 10
5.3 Carrier Frequency Separation 15
5.4 20 dB Channel Bandwidth 20
5.5 Number of Hopping Channels 28
5.6 Time of Occupancy(Dwell Time) 32
5.7 Spurious Emission, Band edge and Restricted bands 37
5.8 Conducted Emission 48
6. Test equipment used for test **50**

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

1. Client information

Applicant:	Samsung Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea 443-742
Telephone number:	+82-31-277-6038
Contact person:	Lee Kyeong Min / km8489.lee@samsung.com

Manufacturer:	Samsung Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea 443-742

This test report shall not be reproduced except in full, Without the written approval.

2. Laboratory information

Address

EMC compliance Ltd.
480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
Telephone Number: 82-31-336-9919 Facsimile Number: 82-505-299-8311

Certificate

KOLAS No.: 231
FCC Site Designation No.: KR0040
FCC Site Registration No.: 687132
VCCI Site Registration No.: R-3327, G-198, C-3706, T-1849
IC Site Registration No.:8035A-2

SITE MAP

This test report shall not be reproduced except in full, Without the written approval.

3. Description of E.U.T.

3.1 Basic description

Applicant:	Samsung Electronics Co., Ltd.
Address of Applicant	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea 443-742
Manufacturer	Samsung Electronics Co., Ltd.
Address of Manufacturer	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea 443-742
Type of equipment	Wi-Fi module
Basic Model	SPW-B4339S
Serial number	N/A

This test report shall not be reproduced except in full, Without the written approval.

3.2 General description

Frequency Range	2 402 ㎒ ~ 2 480 ㎒ (Bluetooth, Bluetooth LE) 2 412 ㎒ ~ 2 472 ㎒ (802.11b/g/n_HT20) 5 180 ㎒ ~ 5 240 ㎒ (802.11a/n/ac_HT20/VHT20)_Non DFS 5 190 ㎒ ~ 5 230 ㎒ (802.11n/ac_HT40/VHT40)_Non DFS 5 210 ㎒ (802.11ac_VHT80)_Non DFS 5 260 ㎒ ~ 5 320 ㎒ (802.11a/n/ac_HT20/VHT20)_DFS 5 270 ㎒ ~ 5 310 ㎒ (802.11n/ac_HT40/VHT40)_DFS 5 290 ㎒ (802.11ac_VHT80)_DFS 5 500 ㎒ ~ 5 700 ㎒ (802.11a/n/ac_HT20/VHT20)_DFS 5 510 ㎒ ~ 5 670 ㎒ (802.11n/ac_HT40/VHT40)_DFS 5 530 ㎒ (802.11ac_VHT80)_DFS 5 745 ㎒ ~ 5 825 ㎒ (802.11a/n/ac_HT20/VHT20)_Non DFS 5 755 ㎒ ~ 5 795 ㎒ (802.11n/ac_HT40/VHT40)_Non DFS 5 775 ㎒ (802.11ac_VHT80)_Non DFS
Type of Modulation	GFSK : Bluetooth, Bluetooth LE, π/4DQPSK, 8DPSK : Bluetooth, CCK, OFDM : WIFI
Number of Channels	2.0 ㎓:79 ch (Bluetooth), 40 ch (Bluetooth LE) 13 ch (802.11b/g/n_HT20) 5.0 ㎓: 5 150 ㎒ Band: 4 ch (802.11a/n/ac_HT20/VHT20) 2 ch (802.11n/ac_HT40/VHT40) 1 ch (802.11ac_VHT80) 5 250 ㎒ Band: 4 ch (802.11a/n/ac_HT20/VHT20) 2 ch (802.11n/ac_HT40/VHT40) 1 ch (802.11ac_VHT80) 5 470 ㎒ Band: 8 ch (11a/n/ac_HT20/VHT20) 4 ch (802.11n/ac_HT40/VHT40) 1 ch (802.11ac_VHT80) 5 725 ㎒ Band: 5 ch (802.11a/n/ac_HT20/VHT20) 2 ch (802.11n/ac_HT40/VHT40) 1 ch (802.11ac_VHT80)
Type of Antenna	PCB Antenna
Antenna Gain	2 ㎓: 1.9 dBi (Bluetooth, Bluetooth LE, WiFi) 5 ㎓: 5 150 ㎒ Band: -0.7 dBi, 5 250 ㎒ Band: 1.4 dBi 5 470 ㎒ Band: 0.3 dBi, 5 725 ㎒ Band: 0.3 dBi
Transmit Power	10.37 dBm
Power supply	DC 3.3 V*
H/W Version	WLM320A_P0
S/W Version	Driver : DHD_1_141_33 WiFi F/W : 6.37.23.34.15.7
Test S/W version	M-tool 2.0.2.3
RF Power setting	set -1 for default value and applied NV Ram

* Declared by the applicant.

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

3.3 Test frequency

	Frequency
Low frequency	2 402 ㎒
Middle frequency	2 441 ㎒
High frequency	2 480 ㎒

3.4 Test Voltage

mode	Voltage
Norminal voltage	DC 3.3 V

※ 15.247 Requirements for Bluetooth transmitter

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:
  1) This system is hopping pseudo-randomly.
  2) Each frequency is used equally on the average by each transmitter.
  3) The receiver input bandwidths that match the hopping channel bandwidths of their corresponding transmitters
  4) The receiver shifts frequencies in synchronization with the transmitted signals.

- 15.247(g): The system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this Section 15.247 should the transmitter be presented with a continuous data (or information) stream.
- 15.247(h): The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

4. Summary of test results

4.1 Standards & results

FCC Rule	IC Rule	Parameter	Report Section	Test Result
15.203, 15.247(b)(4)	-	Antenna Requirement	5.1	C
15.247(b)(1), (4)	RSS-210, A8.4(2)	Maximum Peak Output Power	5.2	C
15.247(a)(1)	RSS-210, A8.1(b)	Carrier Frequency Separation	5.3	C
15.247(a)(1)	RSS-210, A8.1(a) RSS-GEN, 6.6	20dB Channel Bandwidth	5.4	C
-	RSS-GEN, 6.6	Occupied Bandwidth	5.4	C
15.247(a)(iii) 15.247(b)(1)	RSS-210, A8.1(d)	Nunber of Hopping Channel	5.5	C
15.247(a) (iii)	RSS-210, A8.1(d)	Time of Occupancy(Dwell Time)	5.6	C
15.247(d), 15.205(a), 15.209(a)	RSS-210, A8.5 RSS-GEN, 8.9, 10	Spurious Emission, BandEdge, Restricted Band	5.7	C
15.207(a)	RSS-GEN, 8.8	Conducted Emissions	5.8	C

Note: C=complies
NC= Not complies
NT=Not tested
NA=Not Applicable

* The method of measurement used to test this DSS device is FCC Public Notice DA 00-705
* The general test methods used to test on this device are ANSI C63.10: 2013

4.2 Uncertainty

Measurement Item	Expanded Uncertainty U = KUc (K = 2)	
Conducted RF power	± 1.36 dB	
Conducted Spurious Emissions	± 1.52 dB	
Radiated Spurious Emissions	30 MHz ~ 300 MHz:	+ 4.94 dB, - 5.06 dB
		+ 4.93 dB, - 5.05 dB
	300 MHz ~ 1 000 MHz:	+ 4.97 dB, - 5.08 dB
		+ 4.84 dB, - 4.96 dB
	1 GHz ~ 25 GHz:	+ 6.03 dB, - 6.05 dB
Conducted Emissions	9 kHz ~ 150 kHz:	± 3.75 dB
	150 kHz ~ 30 MHz:	± 3.36 dB

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

5. Test results

5.1 Antenna Requirement

5.1.1 Regulation

According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.1.2 Result

-Complied

The transmitter has an PCB type of antenna. The directional gain of the antenna is 1.9 dBi.

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

5.2 Maximum Peak Output Power

5.2.1 Regulation

According to §15.247(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

According to §15.247(b)(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.2.2 Measurement Procedure

The method of measurement used to test this DSS device is FCC Public Notice DA 00-705.

1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable.
3. Turn on the EUT and set it to any one measured frequency within its operating range by controlling it via UART interface or Bluetooth tester and make sure the spectrum analyzer is operated in its linear range.
4. Set the spectrum analyzer as follows: Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel RBW > the 20 dB bandwidth of the emission being measured VBW ≥ RBW Sweep = auto Detector function = peak Trace = max hold
5. Measure the highest amplitude appearing on spectral display and record the level to calculate results.
6. Repeat above procedures until all frequencies measured were complete.

This test report shall not be reproduced except in full, Without the written approval.

5.2.3 Test Result

- Complied

* GFSK

Channel	Frequency (㎒)	Result (dBm)	Limit (dBm)	Margin (dB)	Avarage Power (dBm)
Low	2 402	10.22	30.00	19.78	7.38
Middle	2 441	10.29	30.00	19.71	7.42
High	2 480	10.37	30.00	19.63	7.44

* 8DPSK

Channel	Frequency (㎒)	Result (dBm)	Limit (dBm)	Margin (dB)	Avarage Power (dBm)
Low	2 402	9.81	20.97	11.16	5.19
Middle	2 441	9.96	20.97	11.01	5.03
High	2 480	9.88	20.97	11.09	5.03

NOTE:

1. Since the directional gain of the integral antenna declared by the manufacturer (G_{ANT} = 1.9 dBi) does not exceed 6.0 dBi, there was no need to reduce the output power.
2. We took the insertion loss of the cable loss into consideration within the measuring instrument.

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

5.2.4 Test Plot

Figure 1. Plot of the Maximum Peak Output Power (Conducted)

*** GFSK**

Lowest Channel
(2 402 ㎒)



Middle Channel
(2 441 ㎒)



This test report shall not be reproduced except in full, Without the written approval.

Highest Channel
(2 480 ㎒)



*** 8DPSK**

Lowest Channel
(2 402 ㎒)



This test report shall not be reproduced except in full, Without the written approval.

Middle Channel
(2 441 ㎒)



Highest Channel
(2 480 ㎒)



This test report shall not be reproduced except in full, Without the written approval.

5.3 Carrier Frequency Separation

5.3.1 Regulation

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 ㎑ or the 20 ㏈ bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 ㎒ band may have hopping channel carrier frequencies that are separated by 25 ㎑ or two-thirds of the 20 ㏈ bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 ㎽

5.3.2 Measurement Procedure

The method of measurement used to test this DSS device is FCC Public Notice DA 00-705.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable and attenuator.
3. Turn on the EUT and set it to any one measured frequency within its operating range by controlling it via UART interface or Bluetooth tester.
4. Set the spectrum analyzer as follows: Span = wide enough to capture the peaks of two adjacent channels Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span Video (or Average) Bandwidth (VBW) ≥ RBW Sweep = auto Detector function = peak Trace = max hold
5. Measure the separation between the peaks of the adjacent channels using the marker-delta function.
6. Repeat above procedures until all frequencies measured were complete.

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

5.3.3 Test Result

- Complied

* GFSK

Channel	Carrier frequency separation (㎒)	Limit
Low	0.999	≥25 ㎑ or 20 ㏈bandwidth
Middle	1.007	≥25 ㎑ or 20 ㏈bandwidth
High	0.998	≥25 ㎑ or 20 ㏈bandwidth

* 8DPSK

Channel	Carrier frequency separation (㎒)	Limit
Low	1.003	≥25 ㎑ or two-thirds of the 20 ㏈ bandwidth
Middle	1.001	≥25 ㎑ or two-thirds of the 20 ㏈ bandwidth
High	1.005	≥25 ㎑ or two-thirds of the 20 ㏈ bandwidth

NOTE: We took the insertion loss of the cable loss into consideration within the measuring instrument.

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

5.3.4 Test Plot

Figure 2.Plot of the Carrier Frequency Separation (Conducted)

*** GFSK**

Lowest Channel
(2 402 ㎒)



Middle Channel
(2 441 ㎒)



This test report shall not be reproduced except in full, Without the written approval.

Highest Channel
(2 402 ㎒)



*** 8DPSK**

Lowest Channel
(2 402 ㎒)



480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

Middle Channel
(2 402 ㎒)



Highest Channel
(2 402 ㎒)



This test report shall not be reproduced except in full, Without the written approval.

5.4 20 dB Channel Bandwidth

5.4.1 Regulation

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 ㎑ or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 ㎒ band may have hopping channel carrier frequencies that are separated by 25 ㎑ or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 ㎽

5.4.2 Measurement Procedure

The method of measurement used to test this DSS device is FCC Public Notice DA 00-705.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable and attenuator.
3. Turn on the EUT and set it to any one measured frequency within its operating range by controlling it via UART interface or Bluetooth tester and make sure the spectrum analyzer is operated in its linear range.
4. Set the spectrum analyzer as follows: Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel RBW ≥ 1% of the 20 dB bandwidth VBW ≥ RBW Sweep = auto Detector function = peak Trace = max hold
5. Set a reference level on it equal to the highest peak value.
6. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
7. Repeat above procedures until all frequencies measured were complete..

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

5.4.3 Test Result

- Complied

* GFSK

Channel	20 dB Channel Bandwidth(㎒)	Carrier frequency Separation(㎒)	Occupied Bandwidth (99 % BW)(㎒)
Low	0.812	0.999	0.943
Middle	0.812	1.001	0.948
High	0.812	0.998	0.936

* 8DPSK

Channel	20 dB Channel Bandwidth(㎒)	Carrier frequency Separation(㎒)	Occupied Bandwidth (99 % BW)(㎒)
Low	1.339	1.003	1.211
Middle	1.338	1.001	1.208
High	1.338	1.005	1.206

NOTE: We took the insertion loss of the cable loss into consideration within the measuring instrument.

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

5.4.4 Test Plot

Figure 3.Plot of the 20 dB Channel Bandwidth / Occupied Bandwidth (Conducted)

*** GFSK (20 dB Channel Bandwidth)**

Lowest Channel
(2 402 ㎒)



Lowest Channel
(2 402 ㎒)



This test report shall not be reproduced except in full, Without the written approval.

Highest Channel
(2 480 ㎒)



*** 8DPSK (20 ㏈ Channel Bandwidth)**

Lowest Channel
(2 402 ㎒)



This test report shall not be reproduced except in full, Without the written approval.

Middle Channel
(2 480 ㎒)



Highest Channel
(2 402 ㎒)



480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

*** GFSK (Occupied Bandwidth)**

Lowest Channel
(2 402 ㎒)



Lowest Channel
(2 402 ㎒)



This test report shall not be reproduced except in full, Without the written approval.

Highest Channel
(2 480 ㎒)



*** 8DPSK (20 ㏈ Channel Bandwidth)**

Lowest Channel
(2 402 ㎒)



This test report shall not be reproduced except in full, Without the written approval.

Middle Channel
(2 480 ㎒)



Highest Channel
(2 402 ㎒)



This test report shall not be reproduced except in full, Without the written approval.

5.5 Number of Hopping Channels

5.5.1 Regulation

According to §15.247(a)(1)(iii), Frequency hopping systems in the 2400-2483.5 ㎒ band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used. According to §15.247(b)(1), For frequency hopping systems operating in the 2400-2483.5 ㎒ band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 ㎒ band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 ㎒ band: 0.125 watts.

5.5.2 Measurement Procedure

The method of measurement used to test this DSS device is FCC Public Notice DA 00-705.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable and attenuator.
3. Turn on the EUT and set the hopping function enabled by controlling it via UART interface or Bluetooth tester.
4. Set the spectrum analyzer as follows: Span = the frequency band of operation RBW ≥ 1% of the span VBW ≥ RBW Sweep = auto Detector function = peak Trace = max hold
5. Record the number of hopping channels.

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

5.5.3 Test Result

- Complied

* GFSK

Frequency	Number of hopping channel	Limit
2 402 – 2 480 ㎒	79	≥15

* 8DPSK

Frequency	Number of hopping channel	Limit
2 402 – 2 480 ㎒	79	≥15

NOTE:

1. We took the insertion loss of the cable loss into consideration within the measuring instrument.
2. Measurement is made with EUT operating in hopping mode between 79 channels providing a worse case scenario as compared to AFH mode hopping between 20 channels.

This test report shall not be reproduced except in full, Without the written approval.

5.5.4 Test Plot

Figure 4. Plot of the Number of Hopping Channels (Conducted)

*** GFSK**





This test report shall not be reproduced except in full, Without the written approval.

*** 8DPSK**





This test report shall not be reproduced except in full, Without the written approval.

5.6 Time of Occupancy(Dwell Time)

5.6.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 ㎒ band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

5.6.2 Measurement Procedure

The method of measurement used to test this DSS device is FCC Public Notice DA 00-705.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Connect the antenna port of the EUT to RF input on the spectrum analyzer via a low loss cable.
3. Turn on the EUT and set it to any one measured frequency within its operating range by controlling it via UART interface or Bluetooth tester.
4. Set the spectrum analyzer as follows: Span = zero span, centered on a hopping channel RBW = 1 ㎒ VBW ≥ RBW Sweep = as necessary to capture the entire dwell time per hopping channel Detector function = peak Trace = max hold
5. Measure the dwell time using the marker-delta function.
6. Repeat above procedures until all frequencies measured were complete.
7. Repeat this test for different modes of operation (e.g., data rate, modulation format, etc.), if applicable.

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

5.6.3 Test Result

- Complied

* Non AFH_GFSK

Channel	Reading[㎳]	Hopping rate [hop/s]	Number of Channels	Actual[s]	Limit[s]
Low	2402	266.667	79	0.308	0.40
Middle	2441	266.667	79	0.308	0.40
High	2480	266.667	79	0.308	0.40

* Non AFH_8DPSK

Channel	Reading[㎳]	Hopping rate [hop/s]	Number of Channels	Actual[s]	Limit[s]
Low	2402	266.667	79	0.308	0.40
Middle	2441	266.667	79	0.308	0.40
High	2480	266.667	79	0.308	0.40

* AFH_GFSK

Channel	Reading[㎳]	Hopping rate [hop/s]	Number of Channels	Actual[s]	Limit[s]
Low	2402	133.333	20	0.154	0.40
Middle	2441	133.333	20	0.154	0.40
High	2480	133.333	20	0.154	0.40

* AFH_8DPSK

Channel	Reading[㎳]	Hopping rate [hop/s]	Number of Channels	Actual[s]	Limit[s]
Low	2402	133.333	20	0.154	0.40
Middle	2441	133.333	20	0.154	0.40
High	2480	133.333	20	0.154	0.40

NOTE 1. Non AFH

Actual = Reading × (Hopping rate / Number of channels) × Test period
Hopping rate = 1600/time slot
Test period = 0.4 [seconds / channel] × 79 [channel] = 31.6 [seconds]

2. AFH

Actual = Reading × (Hopping rate / Number of channels) × Test period
Hopping rate = 800/time slot
Test period = 0.4 [seconds / channel] × 20 [channel] = 8 [seconds]

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

5.6.4 Test Plot

Figure 5. Plot of the Time of Occupancy (Conducted)

*** GFSK**

Lowest Channel
(2 402 ㎒)



Middle Channel
(2 441 ㎒)



This test report shall not be reproduced except in full, Without the written approval.

Highest Channel
(2 480 ㎒)



*** 8DPSK**

Lowest Channel
(2 402 ㎒)



This test report shall not be reproduced except in full, Without the written approval.

Middle Channel
(2 441 ㎒)



Highest Channel
(2 480 ㎒)



This test report shall not be reproduced except in full, Without the written approval.

5.7 Spurious Emission, Band edge and Restricted bands

5.7.1 Regulation

According to §15.247(d), in any 100 ㎑ bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 ㏈ below that in the 100 ㎑ bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 ㏈ instead of 20 ㏈. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

According to §15.209(a), Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall notexceed the field strength levels specified in the following table:

Frequency (㎒)	Field strength (㎶/m)	Measurement distance (m)
0.009 - 0.490	2400/F(㎑)	300
0.490 -1.705	24000/F(㎑)	30
1.705 – 30	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 ㎒, 76–88 ㎒, 174–216 ㎒ or 470–806 ㎒. However, operation within these frequency bands is permItted under other sections of this part, e.g., §§15.231 and 15.241.

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

According to § 15.205(a) and (b), only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.009 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	Above 38.6
13.36 - 13.41			

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

5.7.2 Measurement Procedure

The method of measurement used to test this DSS device is FCC Public Notice DA 00-705.

1) <u>Band-edge Compliance of RF Conducted Emissions</u>

1. Set the spectrum analyzer as follows:
   Span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation
   RBW ≥ 1% of the span
   VBW ≥ RBW
   Sweep = auto
   Detector function = peak
   Trace = max hold
2. Allow the trace to stabilize. Set the marker on the emission at the band-edge, or on the highest modulation product outside of the band, if this level is greater than that at the band-edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission.
3. Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.

This test report shall not be reproduced except in full, Without the written approval.

2) Spurious RF Conducted Emissions:

1. Set the spectrum analyzer as follows:
   Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
   RBW = 100 ㎑
   VBW ≥ RBW
   Sweep = auto
   Detector function = peak
   Trace = max hold
2. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
   a 4 × 4 meter at the Open Area Test Site. The EUT was tested at a distance 3 meters.
3. Each frequency found during preliminary measurements was re-examined and investigated. The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.

3) Spurious Radiated Emissions:

1. The preliminary radiated measurements were performed to determine the frequency producing the maximum emissions in an anechoic chamber at a distance of 3 meters.
2. The EUT was placed on the top of the 0.8-meter height, 1 × 1.5 meter non-metallic table. To find the maximum emission levels, the height of a measuring antenna was changed and the turntable was rotated 360˚.
3. The antenna polarization was also changed from vertical to horizontal. The spectrum was scanned from 9 ㎑ to 30 ㎒ using the loop antenna, and from 30 to 1000 ㎒ using the TRILOG broadband antenna, and from 1000 ㎒ to 26500 ㎒ using the horn antenna.
4. To obtain the final measurement data, the EUT was arranged on a turntable situated on a 4 × 4 meter at the Open Area Test Site. The EUT was tested at a distance 3 meters.
5. Each frequency found during preliminary measurements was re-examined and investigated. The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.

Note
1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 ㎑ for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1 ㎓.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 ㎒ for Peak detection and frequency above 1 ㎓.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 ㎒ and the video bandwidth is 10 ㎐ for Average detection (AV) at frequency above 1㎓.

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

5.7.3 Test Result

- Complied

1. Band edge compliance of RF Conducted Emissions was shown in figure 6.
2. Measured value of the Field strength of spurious Emissions (Radiated)

※ Noise was not measured. (Margin was more than 20 dB)
Worst value of noise floor was recorded.

*** Below 1 GHz data (Worst-case: GFSK_Highest channel)**

GFSK_Highest channel (2 480 MHz)

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Factor [dB]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
Quasi-Peak DATA. Emissions below 30 MHz							
Below 30.00	Not Detected	-	-	-	-	-	-
Quasi-Peak DATA. Emissions below 1 GHz							
562.63	120	V	19.9	-7.0	12.9	46.0	33.1
Above 600.00	Not Detected	-	-	-	-	-	-

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

*** Above 1 ㎓ data**

GFSK _Low channel (2 402 ㎒)

Frequency [㎒]	Receiver Bandwidth [㎑]	Pol. [V/H]	Reading [dB(㎶)]	Factor [dB]	Result [dB(㎶/m)]	Limit [dB(㎶/m)]	Margin [dB]
Peak DATA. Emissions above 1 ㎓							
1 666.75	1 000	V	65.6	-3.1	62.5	74.0	11.5
*2 326.75	1 000	V	55.2	1.6	56.8	74.0	17.2
2 879.25	1 000	V	52.2	2.9	55.1	74.0	18.9
Above 3 000.00	Not Detected	-	-	-	-	-	-
Average DATA. Emissions above 1 ㎓							
1 666.75	1 000	V	28.3	-3.1	25.2	54.0	28.8
*2 326.75	1 000	V	28.2	1.6	29.8	54.0	24.2
2 879.25	1 000	V	28.8	2.9	31.7	54.0	22.3
Above 3 000.00	Not Detected	-	-	-	-	-	-

* This Asterisks mean Restricted Band.

GFSK _Middle channel (2 441 ㎒)

Frequency [㎒]	Receiver Bandwidth [㎑]	Pol. [V/H]	Reading [dB(㎶)]	Factor [dB]	Result [dB(㎶/m)]	Limit [dB(㎶/m)]	Margin [dB]
Peak DATA. Emissions above 1 ㎓							
1 665.75	1 000	V	64.3	-3.1	61.2	74.0	12.8
Above 2 000.00	Not Detected	-	-	-	-	-	-
Average DATA. Emissions above 1 ㎓							
1 665.75	1 000	V	29.6	-3.1	26.5	54.0	27.5
Above 2 000.00	Not Detected	-	-	-	-	-	-

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

GFSK _High channel (2 480 ㎒)

Frequency [㎒]	Receiver Bandwidth [㎑]	Pol. [V/H]	Reading [dB(㎶)]	Factor [dB]	Result [dB(㎶/m)]	Limit [dB(㎶/m)]	Margin [dB]
Peak DATA. Emissions above 1 ㎓							
*2 332.25	1 000	V	54.6	1.6	56.2	74.0	17.8
*2 494.00	1 000	V	45.7	2.3	48.0	74.0	26.0
Above 3 000.00	Not Detected	-	-	-	-	-	-
Average DATA. Emissions above 1 ㎓							
*2 332.25	1 000	V	28.2	1.6	29.8	54.0	24.2
*2 494.00	1 000	V	27.8	2.3	30.1	54.0	23.9
Above 3 000.00	Not Detected	-	-	-	-	-	-

* This Asterisks mean Restricted Band.

8DPSK _Low channel (2 402 ㎒)

Frequency [㎒]	Receiver Bandwidth [㎑]	Pol. [V/H]	Reading [dB(㎶)]	Factor [dB]	Result [dB(㎶/m)]	Limit [dB(㎶/m)]	Margin [dB]
Peak DATA. Emissions above 1 ㎓							
1 665.25	1 000	V	58.5	-3.1	55.4	74.0	18.6
*2 324.75	1 000	V	47.9	1.6	49.5	74.0	24.5
Above 3 000.00	Not Detected	-	-	-	-	-	-
Average DATA. Emissions above 1 ㎓							
1 665.25	1 000	V	28.8	-3.1	25.7	54.0	28.3
*2 494.00	1 000	V	27.9	1.6	29.5	54.0	24.5
Above 3 000.00	Not Detected	-	-	-	-	-	-

*This Asterisks mean Restricted Band.

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

8DPSK _Middle channel (2 441 ㎒)

Frequency [㎒]	Receiver Bandwidth [㎑]	Pol. [V/H]	Reading [dB(㎶)]	Factor [dB]	Result [dB(㎶/m)]	Limit [dB(㎶/m)]	Margin [dB]
Peak DATA. Emissions above 1 ㎓							
-	Not Detected	-	-	-	-	-	-
Average DATA. Emissions above 1 ㎓							
-	Not Detected	-	-	-	-	-	-

8DPSK _High channel (2 480 ㎒)

Frequency [㎒]	Receiver Bandwidth [㎑]	Pol. [V/H]	Reading [dB(㎶)]	Factor [dB]	Result [dB(㎶/m)]	Limit [dB(㎶/m)]	Margin [dB]
Peak DATA. Emissions above 1 ㎓							
1 661.25	1 000	V	64.9	-3.2	61.7	74.0	12.3
*2 494.50	1 000	V	43.1	2.3	45.4	74.0	28.6
Above 3 000.00	Not Detected	-	-	-	-	-	-
Average DATA. Emissions above 1 ㎓							
1 661.25	1 000	V	29.6	-3.2	26.4	54.0	27.6
*2 494.50	1 000	V	28.4	2.3	30.7	54.0	23.3
Above 3 000.00	Not Detected	-	-	-	-	-	-

* This Asterisks mean Restricted Band

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

5.7.4 Test Plot

Figure 6. Plot of the Band Edge (Conducted)

*** GFSK (Without hopping)**

Lowest Channel
(2 402 ㎒)



Highest Channel
(2 480 ㎒)



This test report shall not be reproduced except in full, Without the written approval.

*** GFSK (With hopping)**

Lowest Channel
(2 402 ㎒)



Highest Channel
(2 480 ㎒)



This test report shall not be reproduced except in full, Without the written approval.

*** 8DPSK (Without hopping)**

Lowest Channel
(2 402 ㎒)



Highest Channel
(2 480 ㎒)



This test report shall not be reproduced except in full, Without the written approval.

*** 8DPSK (With hopping)**

Lowest Channel
(2 402 ㎒)



Highest Channel
(2 480 ㎒)



This test report shall not be reproduced except in full, Without the written approval.

5.8 Conducted Emission

5.8.1 Regulation

According to §15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 ㎑ to 30 ㎒, shall not exceed the limits in the following table, as measured using a 50 µH/50 Ω line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (㎒)	Conducted limit (dBµV)	
	Qausi-peak	Average
0.15 – 0.5	66 to 56 *	56 to 46 *
0.5 – 5	56	46
5 – 30	60	50

* Decreases with the logarithm of the frequency.

According to §15.107(a), for unintentional device, except for Class A digital devices, line conducted emission limits are the same as the above table.

5.8.2 Measurement Procedure

1) The EUT was placed on a wooden table of size, 1 m by 1.5 m, raised 80 ㎝ in which is located 40 ㎝ away from the vertical wall and 1.5m away from the side wall of the shielded room.

2) Each current-carrying conductor of the EUT power cord was individually connected through a 50Ω/50µH LISN, which is an input transducer to a Spectrum Analyzer or an EMI/Field Intensity Meter, to the input power source.

3) Exploratory measurements were made to identify the frequency of the emission that had the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable position, and with a typical system equipment configuration and arrangement. Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that had produced the emission with the highest amplitude relative to the limit was selected for the final measurement.

4) The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment is the system) was then performed over the frequency range of 0.15 ㎒ to 30 ㎒.

5) The measurements were made with the detector set to PEAK amplitude within a bandwidth of 10 ㎑ or to QUASI-PEAK and AVERAGE within a bandwidth of 9 ㎑. The EUT was in transmitting mode during the measurements.

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

5.8.3 Test Result

- Complied

Figure 7. plot of Conducted Emission

*Conducted worst-case data : 802.11n HT20_Middle Channel (2 437 ㎒)



Final Result

--- N_A Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]	Remark
1	0.16316	35.4	17.3	10.1	45.5	27.4	65.3	55.3	19.8	27.9	
2	0.18645	32.7	16.4	10.2	42.9	26.6	64.2	54.2	21.3	27.6	
3	3.67224	12.2	8.6	10.7	22.9	19.3	56.0	46.0	33.1	26.7	
4	7.69758	12.8	8.6	12.5	25.3	21.1	60.0	50.0	34.7	28.9	

--- L1_A Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]	Remark
1	0.16004	34.7	14.6	10.1	44.8	24.7	65.5	55.5	20.7	30.8	
2	0.37012	21.8	18.6	10.2	32.0	28.8	58.5	48.5	26.5	19.7	
3	1.00155	15.4	9.2	10.1	25.5	19.3	56.0	46.0	30.5	26.7	
4	24.84428	10.8	6.0	23.3	34.1	29.3	60.0	50.0	25.9	20.7	
5	29.4695	2.0	-2.9	27.1	29.1	24.2	60.0	50.0	30.9	25.8	

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.

6. Test equipment used for test

	Description	Manufacturer	Model No.	Serial No.	Next Cal Date.	period
■	Wideband Power Sensor	R&S	NRP-Z81	102398	15.11.27	1
■	Attenuator	HP	8491A	18591	15.05.08	1
■	Spectrum Analyzer	R&S	FSV40	100989	16.01.23	1
■	Spectrum Analyzer	R&S	FSV40	100988	16.01.23	1
■	DC Power Supply	AGILENT	E3632A	MY40008800	15.12.11	1
■	Signal Generator	R&S	SMR40	100007	15.06.10	1
■	Amplifier	Sonoma Instrument	310N	293004	15.09.25	1
■	Loop Antenna	R&S	HFH2-Z2	100355	15.06.19	2
■	Bi-Log Antenna	Schwarzbeck	VULB9163	552	16.05.14	2
■	Horn Antenna	ETS-LINDGREN	3117	155787	15.02.26	1
■	Horn Antenna	ETS.lindgren	3116	00086632	15.10.20	1
■	Spiral Antenna	COBHAM	PSA-75301R/170	406827-0001	-	-
■	Broadband Preamplifier	Schwarzbeck	BBV9718	216	15.04.22	1
■	Broadband Preamplifier	SCHWARZBECK	BBV9721	2	15.05.09	1
■	Attenuator	HP	8491A	16861	15.07.01	1
■	Highpass Filter	Wainwright Instruments GmbH	WHKX3.0/ 18G-12SS	44	16.02.02	1
■	EMI Test Receiver	R&S	ESCI	100001	15.06.24	1
■	Bluetooth Tester	TESCOM	TC-3000A	3000A310047	15.04.10	1
■	Power Divier	Aeroflex/ Weinschel,Inc	1580-1	RM987	15.04.08	1
■	Turn Table	Innco Systems	DT2000S-1t	79	-	-
■	Antenna Mast	Innco Systems	MA4000-EP	303	-	-

480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
82-31-336-9919 (Main) 82-505-299-8311 (Fax)
This test report shall not be reproduced except in full, Without the written approval.