



Light Tek Co., Ltd.

2f, No. 158, Gan Cheng Rd., Pan Chiao City
Taipei Hsien, Taiwan, R.O.C.
Tel: 886-2-89510688 Fax: 886-2-89510681

Samsung Gemini

Antenna Test Report


RD Manager	Supervisor	RD engineer	Sales engineer
Bill	Jackson	Jackson	Johnson



Light Tek Co., Ltd.

2f, No. 158, Gan Cheng Rd., Pan Chiao City
Taipei Hsien, Taiwan, R.O.C.
Tel: 886-2-89510688 Fax: 886-2-89510681

1. Mechanical dimensions





Light Tek Co., Ltd.


2f, No.158, Gan Cheng Rd., Pan Chiao City
Taipei Hsien, Taiwan, R.O.C.
Tel: 886-2-89510688 Fax: 886-2-89510681

II. Test results 1

Antenna	Application	Location	Cable dia. $\bar{u}$ mm	Cable length mm
Gemini	PIFA #1	Sidebar	1.13	250 mm

1. VSWR

Antenna	Center freg. @MHz	BW @MHz	VSWR		
			2.4GHz	2.45GHz	2.5GHz
Gemini PIFA #1	2450	100	2.25	1.91	1.93





Light Tek Co., Ltd.


2f, No.158, Gan Cheng Rd., Pan Chiao City
Taipei Hsien, Taiwan, R.O.C.
Tel: 886-2-89510688 Fax: 886-2-89510681

II. Test results 1

Antenna	Application	Location	Cable dia. $\bar{u}$ mm	Cable length mm
Gemini	PIFA #1	Sidebar	1.13	250 mm

1. Return Loss

Antenna	Center freg. @MHz	BW @MHz	VSWR		
			2.4GHz	2.45GHz	2.5GHz
Gemini PIFA #1	2450	50	-8.24	-10.02	-9.95






Light Tek Co., Ltd.

2f, No. 158, Gan Cheng Rd., Pan Chiao City
Taipei Hsien, Taiwan, R.O.C.
Tel: 886-2-89510688 Fax: 886-2-89510681

SMITH CHART





Light Tek Co., Ltd.


2f, No. 158, Gan Cheng Rd., Pan Chiao City
Taipei Hsien, Taiwan, R.O.C.
Tel: 886-2-89510688 Fax: 886-2-89510681

2. Peak Gain and Average Gain

Antenna	Gain of XY Plane(Azimuth)-Open		
	Frequency		2.45
<u>Gemini</u> <u>PIFA #1</u>	H	Peak	-1.80
		Average	-6.33
<u>Gemini</u> <u>PIFA #1</u>	V	Peak	NLRQ>
		Average	KSLPV>
<u>Gemini</u> <u>PIFA #1</u>	H+V	Peak	0.54
		Average	-3.41
		%>-5dBi	73.29

3. Radiation Pattern of XY Plane(Azimuth)-Open

— H-polarized — V- polarized — H+V- polarized





Light Tek Co., Ltd.


2f, No. 158, Gan Cheng Rd., Pan Chiao City
Taipei Hsien, Taiwan, R.O.C.
Tel: 886-2-89510688 Fax: 886-2-89510681

2. Peak Gain and Average Gain

Antenna	Gain of XY Plane(Azimuth)-Close		
	Frequency		2.45
<u>Gemini</u> <u>PIFA#1</u>	H	Peak	KRLOW>
		Average	KTLRO>
<u>Gemini</u> <u>PIFA#1</u>	V	Peak	N>
		Average	KSLTW>
<u>Gemini</u> <u>PIFA#1</u>	H+V	Peak	0.13
		Average	-3.81
		%>-5dBi	68.24

3. Radiation Pattern of XY Plane(Azimuth)-Close

— H-polarized — V- polarized — H+V- polarized





Light Tek Co., Ltd.


2f, No.158, Gan Cheng Rd., Pan Chiao City
 Taipei Hsien, Taiwan, R.O.C.
 Tel: 886-2-89510688 Fax: 886-2-89510681

II. Test results 1

Antenna	Application	Location	Cable dia. $\bar{u}$ mm	Cable length mm
Gemini	PIFA #2	front	1.13	250 mm

1. VSWR

Antenna	Center freq. @MHz	BW @MHz	VSWR		
			2.4GHz	2.45GHz	2.5GHz
Gemini PIFA #2	2450	100	1.80	1.78	2.09





Light Tek Co., Ltd.


2f, No.158, Gan Cheng Rd., Pan Chiao City
Taipei Hsien, Taiwan, R.O.C.
Tel: 886-2-89510688 Fax: 886-2-89510681

II. Test results 1

Antenna	Application	Location	Cable dia. $\bar{u}$ mm	Cable length mm
Gemini	PIFA #1	Sidebar	1.13	250 mm

1. Return Loss


Antenna	Center freg. @MHz	BW @MHz	VSWR		
			2.4GHz	2.45GHz	2.5GHz
Gemini PIFA #1	2450	100	-10-79	-10.94	-9.07





2f, No. 158, Gan Cheng Rd., Pan Chiao City
Taipei Hsien, Taiwan, R.O.C.
Tel: 886-2-89510688 Fax: 886-2-89510681

SMITH CHART





Light Tek Co., Ltd.


2f, No. 158, Gan Cheng Rd., Pan Chiao City
 Taipei Hsien, Taiwan, R.O.C.
 Tel: 886-2-89510688 Fax: 886-2-89510681

2. Peak Gain and Average Gain

Antenna	Gain of XY Plane(Azimuth)-Open		
	Frequency		2.45
<u>Gemini</u> <u>PIFA #2</u>	H	Peak	0.12
		Average	-5.74
<u>Gemini</u> <u>PIFA #2</u>	V	Peak	KOLPQ>
		Average	KWLOV>
<u>Gemini</u> <u>PIFA #2</u>	H+V	Peak	0.68
		Average	-4.14
		%>-5dBi	65.28%

3. Radiation Pattern of XY Plane(Azimuth)-Open

— H-polarized — V- polarized — H+V- polarized





Light Tek Co., Ltd.

2f, No.158, Gan Cheng Rd., Pan Chiao City
 Taipei Hsien, Taiwan, R.O.C.
 Tel: 886-2-89510688 Fax: 886-2-89510681

2. Peak Gain and Average Gain

Antenna	Gain of XY Plane(Azimuth)-Close		
	Frequency		2.45
<u>Gemini PIFA#2</u>	H	Peak	-1.38
		Average	-7.54
<u>Gemini PIFA#2</u>	V	Peak	0.43
		Average	-5.28
<u>Gemini PIFA#2</u>	H+V	Peak	0.43
		Average	-3.11
		%>-5dBi	76.85%

3. Radiation Pattern of XY Plane(Azimuth)-Close

— H-polarized — V- polarized — H+V- polarized

