

ACA-3216-A1-CC-S-W1 Specification

1. Features and Application :

This product is for WiFi/BT band

2. Explanation of Part Number :

AC A - 3216 - A1 - CC - S - W1
(1) (2) (3) (4) (5) (6) (7)

- (1) Product Type : Chip Antenna
- (2) Center Frequency/Band Code : 2.4 GHz Band
- (3) Size Code : 3.2*1.6 mm (Length * Width)
- (4) Design Revision Code : Rev.1
- (5) Antenna Type : Coupling Ceramics
- (6) Special Code : RoHS Compliant
- (7) Suffix For Special Requirements

3. Electrical Specification :


Item	Specification
Frequency Band	2400 ~ 2500 MHz
Polarization	Linear
Impedance	50 ohm Typ.
VSWR	Less than 2.5
*Peak Gain	0.97 dBi Typ.
*Peak Efficiency	71.1 % Typ.

* Test condition : Test board size 100*50 mm

Matching circuit may be required

UNLESS OTHER SPECIFIED TOLERANCES ON : X=± X.X=± X.XX=			INPAQ TECHNOLOGY CO., LTD. No. 11, Keyi St., Zhunan Township, Miaoli County 350402 , Taiwan (R.O.C.) +886-37-585-555	
ANGLES=± HOLEDIA=±				
SCALE : ----	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION		
DRAWN BY : 彭少君	CHECKED BY : 洪賢修			
DESIGNED BY : 彭少君	APPROVED BY : 謝立庭			
TITLE : ACA-3216-A1-CC-S-W1 Specification		DOCUMENT NO.	ENS000211800	SPEC REV. A0

4. Physical Dimension :




L	3.20 ± 0.30
W	1.70 ± 0.20
H	0.50 ± 0.10
A	0.30 ± 0.15
B	0.30 ± 0.15
L1	0.47 ± 0.20
W1	0.70 ± 0.20

(Unit : mm)

5. Recommended PCB Layout :


Layout




UNLESS OTHER SPECIFIED TOLERANCES ON : X=± X.X=± X.XX=± ANGLES=± HOLEDIA=±		 INPAQ TECHNOLOGY CO., LTD.	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
SCALE : -----	UNIT : mm			
DRAWN BY : 彭少君	CHECKED BY : 洪賢修			
DESIGNED BY : 彭少君	APPROVED BY : 謝立庭			
TITLE : ACA-3216-A1-CC-S-W1 Specification		DOCUMENT NO.	ENS000211800	SPEC REV. A0

Pad Dimensions on PCB Layout

Top View



Perspective View




(Unit : mm)

* Tolerance : ± 0.05 mm

UNLESS OTHER SPECIFIED TOLERANCES ON : X=± X.X=± X.XX= ANGLES=± HOLEDIA=±		 INPAQ TECHNOLOGY CO., LTD.	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
SCALE : -----	UNIT : mm			
DRAWN BY : 彭少君	CHECKED BY : 洪賢修			
DESIGNED BY : 彭少君	APPROVED BY : 謝立庭			
TITLE : ACA-3216-A1-CC-S-W1 Specification		DOCUMENT NO.	ENS000211800	SPEC REV. A0

6. Electrical Characteristics :


VSWR



Frequency (MHz)	VSWR
2400	1.94
2450	1.40
2500	1.98

Radiation Pattern :


The Gain pattern is measured in INPAQ's FAR-field chamber. DUT is placed on the table of rotator, a standard horn antenna and Vector Network Analyzer is used to collect data.




3D Chamber Definition

UNLESS OTHER SPECIFIED TOLERANCES ON : X=± X.X=± X.XX= ANGLES=± HOLEDIA=±			INPAQ TECHNOLOGY CO., LTD.	
SCALE : ----	UNIT : mm		THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
DRAWN BY : 彭少君	CHECKED BY : 洪賢修			
DESIGNED BY : 彭少君	APPROVED BY : 謝立庭			
TITLE : ACA-3216-A1-CC-S-W1 Specification		DOCUMENT NO.	ENS000211800	SPEC REV. A0

3D Gain Pattern



2450 MHz




UNLESS OTHER SPECIFIED TOLERANCES ON : X=± X.X=± X.XX= ANGLES=± HOLEDIA=±			INPAQ TECHNOLOGY CO., LTD.		
SCALE : ----	UNIT : mm				
DRAWN BY : 彭少君	CHECKED BY : 洪賢修	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION			
DESIGNED BY : 彭少君	APPROVED BY : 謝立庭				
TITLE : ACA-3216-A1-CC-S-W1 Specification		DOCUMENT NO.	ENS000211800		SPEC REV.
					A0

7. Taping Package and Label Marking :

(1) Quantity : 4000pcs/Reel, T(Thickness of chip) ≤ 1.2


(2) Paper Tape



Type	W	A	B	K	t	F	P
3216	8±0.1	1.9~2.1	3.50~3.60	Max. 1.40	0.22±0.05	3.50±0.1	4.00±0.1


(Unit: mm)

(3) Tape Packing




(4) Cover Tape Peel Off Force

$$5g \cdot f \leq \text{Peel-Off Force} \leq 70g \cdot f$$



(5) Reel Dimensions

Reel Material: Polystyrene



W	A	B
9±0.5	178±1	13+0.5/-0.2
11.4±0.5	178±1	13+0.5/-0.2

(Unit: mm)

UNLESS OTHER SPECIFIED TOLERANCES ON : X=± X.X=± X.XX=± ANGLES=± HOLEDIA=±			INPAQ TECHNOLOGY CO., LTD.	
SCALE : ----	UNIT : mm			
DRAWN BY : 彭少君	CHECKED BY : 洪賢修	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION		
DESIGNED BY : 彭少君	APPROVED BY : 謝立庭			
TITLE : ACA-3216-A1-CC-S-W1 Specification		DOCUMENT NO.	ENS000211800	SPEC REV.
				A0

8. Environmental Characteristics :

(1) Reliability Test

Item	Condition	Specification
Thermal shock	1. 30±3 minutes at -40°C±5°C, 2. Convert to +105°C (5 minutes) 3. 30±3 minutes at +105°C±5°C, 4. Convert to -40°C (5 minutes) 5. Total 100 continuous cycles	No apparent damage Fulfill the electrical spec. after test.
Humidity resistance	1. Humidity : 85% R.H. 2. Temperature : 85±5°C 3. Time : 1000 hours.	No apparent damage Fulfill the electrical spec. after test.
High temperature resistance	1. Temperature : 150°C±5°C 2. Time : 1000 hours.	No apparent damage Fulfill the electrical spec. after test.
Low temperature resistance	1. Temperature : -40°C±5°C 2. Time : 1000 hours.	No apparent damage Fulfill the electrical spec. after test.
Soldering heat resistance	1. Solder bath temperature : 260±5°C 2. Bathing time : 10±1 seconds	No apparent damage
Solderability	The dipped surface of the terminal shall be at least 95% covered with solder after dipped in solder bath of 245±5°C for 3±1 seconds.	No apparent damage

(2) Storage condition

(a) At warehouse :

The temperature should be within 0 ~ 30°C and humidity should be less than 60% RH.

The product should be used within 1 year from the time of delivery.

(b) On board :


The temperature should be within -40 ~ 85°C and humidity should be less than 85% RH.

(3) Operating temperature range

Operating temperature range : -40 ~ +105°C.

UNLESS OTHER SPECIFIED TOLERANCES ON : X=± X.X=± X.XX= ANGLES=± HOLEDIA=±			INPAQ TECHNOLOGY CO., LTD.	
SCALE : -----	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION		
DRAWN BY : 彭少君	CHECKED BY : 洪賢修			
DESIGNED BY : 彭少君	APPROVED BY : 謝立庭			
TITLE : ACA-3216-A1-CC-S-W1 Specification		DOCUMENT NO.	ENS000211800	SPEC REV.
				A0

9. Recommended reflow soldering :



A	1 st rising temperature	The normal to Preheating temperature	30s to 60s
B	Preheating	140°C to 160°C	60s to 120s
C	2 nd rising temperature	Preheating to 200°C	20s to 40s
D	Main heating	if 220°C	50s~60s
		if 230°C	40s~50s
		if 240°C	30s~40s
		if 250°C	20s~40s
		if 260°C	20s~40s
E	Regular cooling	200°C to 100°C	1°C/s ~ 4°C/s

*reference: J-STD-020C

(1) Soldering gun procedure

Note the follows, in case of using solder gun for replacement.

- (a) The tip temperature must be less than 350°C for the period within 3 seconds by using soldering gun under 30 W.
- (b) The soldering gun tip shall not touch this product directly.

(2) Soldering volume

Note that excess of soldering volume will easily get crack the body of this product.

UNLESS OTHER SPECIFIED TOLERANCES ON : X=± X.X=± X.XX=± ANGLES=± HOLEDIA=±		 INPAQ TECHNOLOGY CO., LTD.	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
SCALE : -----	UNIT : mm			
DRAWN BY : 彭少君	CHECKED BY : 洪賢修			
DESIGNED BY : 彭少君	APPROVED BY : 謝立庭			
TITLE : ACA-3216-A1-CC-S-W1 Specification		DOCUMENT NO.	ENS000211800	SPEC REV. A0