

SAR EVALUATION REPORT

Test Report No.	OT-186-RWD-002
AGR.No.	A183A-208
Applicant	Samsung Electronics Co.,Ltd. 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea.
Model Name	S4335-AW
DUT Type	Digital Flat Panel X-ray Detector
Application Type	Certification
FCC ID	A3LWBW880A
Date of Report	June 05, 2018
Date of Test	May 16, 2018 ~ Jun 04, 2018
Test Laboratory	ONETECH 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea
Procedures	KDB 447498, KDB 865664 IEEE 1528-2013 ANSI/IEEE C95.1, C95.3 FCC CFR §2.1093 RSS-102 Issue 5
Max SAR(1g)	1.488 W/kg
Test Opinion	Satisfied to FCC requirements
Report Author	Jungwook Kim  _____ June 05, 2018
Test Engineer	JungHun Park  _____ June 05, 2018

This report details the results of the testing carried out on one sample, the results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distribute in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of ONETECH Corp. or testing done by ONETECH Corp. In connection with distribution or use of the product described in this report must be approved by ONETECH Corp. in writing.

TABLE OF CONTENTS

1. DUT INFORMATION	3
2. INTRODUCTION	4
3. SAR MEASUREMENT SETUP	5
4. MEASUREMENT UNCERTAINTY	9
5. ANSI/IEEE C95.1-2005 RF EXPOSURE LIMIT	11
6. SYSTEM AND LIQUID VERIFICATION	12
7. SAR MEASUREMENT PROCEDURES	19
8. TEST EQUIPMENT LIST	21
9. RF CONDUCTED POWER	22
10. SAR TEST RESULTS	33
ANNEX A. SYSTEM VERIFICATION PLOTS	44
ANNEX B. SAR TEST PLOTS	56
ANNEX C. PHOTOGRAPHS	76
ANNEX D. ANTENNA INFORMATION	79
ANNEX E. PROBE AND DIPOLE CALIBRATION CERTIFICATES	81

1. DUT INFORMATION

DUT Description	Digital Flat Panel X-ray Detector
Model Name	S4335-AW
Multiple Model Name	S4335-AWV
Serial Number	Identical Prototype
Mode of Operation	WLAN
TX Frequency Range	2 412 MHz ~ 2 462 MHz (802.11b/g/n) 5 180 MHz ~ 5 240 MHz (802.11a/n/ac) / 5 260 MHz ~ 5 320 MHz (802.11a/n/ac) 5 500 MHz ~ 5 700 MHz (802.11a/n/ac) / 5 745 MHz ~ 5 825 MHz (802.11a/n/ac)
Maximum Average Conducted Power	802.11b : 8.99 dBm (Max. Allowed target power : 8 ± 2.5 dBm)
Body Worn Accessory	N/A
Antenna Type & Gain	Main Antenna Type, Aux Antenna Type : Patch Antenna Main Antenna Gain : 2 400 MHz : 0.4 dBi / 2 450 MHz : 2.9 dBi / 2 500 MHz : 1.9 dBi 5 200 MHz : 5.6 dBi / 5 300 MHz : 7.3 dBi / 5 400 MHz : 5.9 dBi 5 500 MHz : 4.3 dBi / 5 600 MHz : 3.5 dBi / 5 700 MHz : 4.9 dBi 5 800 MHz : 2.1 dBi Aux Antenna Gain : 2 400 MHz : -0.1 dBi / 2 450 MHz : 2.0 dBi / 2 500 MHz : 1.5 dBi 5 200 MHz : 3.9 dBi / 5 300 MHz : 2.8 dBi / 5 400 MHz : 4.2 dBi 5 500 MHz : 2.3 dBi / 5 600 MHz : 1.0 dBi / 5 700 MHz : 3.0 dBi 5 800 MHz : 4.3 dBi
Antenna Operation	2 Antenna Transmit
Battery	DC 11.4 V / 3 400 mAh

Equipment Class	Band	Highest Reported SAR 1g (W/kg)
DTS	2.4 GHz WALN	0.575
NII	5.2 GHz WALN	0.859
	5.3 GHz WALN	1.088
	5.6 GHz WALN	0.829
	5.8 GHz WALN	1.089
Simultaneous SAR per KDB 690783 D01v01r03		1.488

2. INTRODUCTION

The FCC and Industry Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices.

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz and Health Canada RF Exposure Guidelines Safety Code 6. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

2.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ).

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dV} \right)$$

SAR is expressed in units of watts per kilogram (W/kg). SAR can be related to the electric field at a point by


$$SAR = \frac{\sigma |E|^2}{\rho}$$

where:

- σ = conductivity of the tissue (S/m)
- ρ = mass density of the tissue (kg/m³)
- E = rms electric field strength (V/m)

3. SAR MEASUREMENT SETUP

- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- Data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing,
- AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.



3.1 Dasy 5 system

DASY52 SAR	
	DASY52 SAR is a cost-effective package for demonstration of compliance of mobile phones with specific absorption rate (SAR) limits. The fastest and most accurate scanner on the market, it is fully compatible with all worldwide standards for transmitters operating at the ear or near the body (<200 mm from the skin).
	Components (typical configuration) 1 TX90XL Stäubli Robot and Controller CS8c incl. Cabinet 1 EOCx Electro Optical Converter (mounted on robot arm) 1 Robot Stand for TX90XL 1 Robot Arm Extension and Adaptors 1 Robot Remote Control 1 LB5 Light Beam Switch for Probe Tooling (incl. LB Adaptor) 1 Light Beam Mounting Plate 1 DASY5 Measurement Server 1 PC Intel Core 2 Dual / 3.16 GHz (or higher) incl. Color-Monitor 23" ~ 4 GB RAM, 220 GB HD (or larger) / Win7 1 SAM Twin Phantom V5.0 incl. Support DASY5 1 MD4HHTV5 Mounting Device for Hand-Held Transmitters 1 DAEx Data Acquisition Electronics 1 ES3DVx SAR Probe (incl. ConvF for HSL at 900 and 1750 MHz)


3.2 E-Field Probe (EX3DV4)

EX3DV4 Smallest Isotropic E-Field Probe for Dosimetric Measurements (Preliminary Specifications)	
	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	ISO/IEC 17025 calibration service available.
Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)
Dynamic Range	10 μ W/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.

3.3 E-Field Probe(ES3DV3)

ES3DV3 Isotropic E-Field Probe for Dosimetric Measurements	
	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	ISO/IEC 17025 calibration service available.
Frequency	10 MHz to 4 GHz; Linearity: ± 0.2 dB (30 MHz to 4 GHz)
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)
Dynamic Range	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm
Application	General dosimetry up to 4 GHz Dosimetry in strong gradient fields Compliance tests of mobile phones
Compatibility	DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI

3.4 ELI Phantom

ELI Phantom	
	The ELI phantom is used for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles. ELI V5.0 and higher has the same shell geometry and is manufactured from the same material as ELI V4.0, but has reinforced top structure. ELI V6.0, released in August 2014, has the same shell geometry as ELI V4.0 but offers increased longterm stability.
Material	Vinyl ester, fiberglass reinforced (VE-GF)
Liquid Compatibility	The phantom shell is compatible with SPEAG tissue simulating liquids (sugar and oil based). Use of other liquids may render the phantom warranty void (see note or consult SPEAG support).
Shell Thickness	2.0 $\pm$ 0.2 mm (bottom plate)
Dimensions	Major axis: 600 mm Minor axis: 400 mm
Filling Volume	approx. 30 liters
Support	DASY6: standard-size platform slot DASY52 stand-alone: SPEAG standard phantom table
Accessories	Mounting Device and Adaptors

3.5 Mounting Device



Mounting Device for Laptops

MD4LAPV5 - Mounting Device for Laptops and other Body-Worn Transmitters

In combination with the Twin SAM V5.0/V5.0c or ELI Phantoms, the Mounting Device (Body-Worn) enables testing of transmitter devices according to IEC 62209-2 specifications. The device holder can be locked for positioning at flat phantom section.

Material: Polyoxymethylene (POM), PET-G, Foam

4. MEASUREMENT UNCERTAINTY

Uncertainty of SAR equipment for measurement Body 0.3 GHz to 3 GHz

No.		Error Description	Uncertainty Value (1 g) (%)	Uncertainty Value (10 g) (%)	Probe Dist.	Div.	C_1 (1 g)	C_2 (10 g)	$U_1(\theta)$ (1 g)	$U_2(\theta)$ (10 g)	V_i or V_{eff}
1	$U(PR_{cal})$	Probe Calibration	6.30	6.30	N	1.00	1.00	1.00	6.30	6.30	∞
2	$U(PR_{is})$	Isotropy	1.87	1.87	R	$\sqrt{3}$	1.00	1.00	1.08	1.08	∞
3	$U(L)$	Linearity	0.60	0.60	R	$\sqrt{3}$	1.00	1.00	0.35	0.35	∞
4	$U(PR_{mod})$	Probe modulation response	2.40	2.40	R	$\sqrt{3}$	1.00	1.00	1.39	1.39	∞
6	$U(DL)$	Detection Limits	1.00	1.00	R	$\sqrt{3}$	1.00	1.00	0.58	0.58	∞
5	$U(SE)$	Boundary effect	1.00	1.00	R	$\sqrt{3}$	1.00	1.00	0.58	0.58	∞
7	$U(RE)$	Readout Electronics	0.30	0.30	N	1.00	1.00	1.00	0.30	0.30	∞
8	$U(T_{res})$	Response Time	0.80	0.80	R	$\sqrt{3}$	1.00	1.00	0.46	0.46	∞
9	$U(T_{int})$	Integration Time	2.60	2.60	R	$\sqrt{3}$	1.00	1.00	1.50	1.50	∞
10	$U(A_{amb})$	RF ambient conditions-noise	3.00	3.00	R	$\sqrt{3}$	1.00	1.00	1.73	1.73	∞
11	$U(A_{ref})$	RF ambient conditions-reflections	3.00	3.00	R	$\sqrt{3}$	1.00	1.00	1.73	1.73	∞
12	$U(PR_{pos})$	Probe positioner mech. Restrictions	0.40	0.40	R	$\sqrt{5}$	1.00	1.00	0.23	0.23	∞
13	$U(PR_{pos})$	Probe positioning with respect to phantom shell	2.90	2.90	R	$\sqrt{3}$	1.00	1.00	1.67	1.67	∞
14	$U(PP_{max})$	Post-processing(for max. SAR evaluation)	2.00	2.00	R	$\sqrt{5}$	1.00	1.00	1.15	1.15	∞
15	$U(DU)$	Device Holder Uncertainty	3.60	3.60	N	1.00	1.00	1.00	3.60	3.60	5.00
16	$U(PO_{pos})$	Test sample positioning	0.92	0.94	N	1.00	1.00	1.00	0.92	0.94	9.00
17	$U(PS)$	Power scaling	0.00	0.00	R	$\sqrt{5}$	1.00	1.00	0.00	0.00	∞
18	$U(PD)$	Drift of output power(measured SAR drift)	5.00	5.00	R	$\sqrt{3}$	1.00	1.00	2.89	2.89	∞
19	$U(PL)$	Phantom Uncertainty	6.10	6.10	R	$\sqrt{3}$	1.00	1.00	3.52	3.52	∞
20	$U(CS_{avg})$	Algorithm for correcting SAR for deviations in permittivity and conductivity	1.90	1.90	N	1.00	1.00	0.84	1.90	1.60	∞
21	$U(EC_{me})$	Liquid Conductivity (meas.)	1.39	1.26	N	1.00	0.78	0.71	1.08	0.89	5.00
22	$U(EP_{me})$	Liquid Permittivity (meas.)	0.34	0.38	N	1.00	0.23	0.26	0.08	0.10	5.00
23	$U(EC_{temp})$	Liquid conductivity(temperature uncertainty)	1.87	1.71	R	$\sqrt{3}$	0.78	0.71	0.84	0.70	∞
24	$U(EP_{temp})$	Liquid permittivity(temperature uncertainty)	0.11	0.13	R	$\sqrt{3}$	0.23	0.26	0.01	0.02	∞
$U(sar)$ Combined standard uncertainty (%)									9.82	9.73	275
Extended uncertainty U(%)									19.63	19.47	

Uncertainty of SAR equipment for measurement Body 3 GHz to 6 GHz

No.		Error Description	Uncertainty Value (1 g) (%)	Uncertainty Value (10 g) (%)	Probe Dist.	Div.	C_1 (1 g)	C_2 (10 g)	$U_1(g)$ (1 g)	$U_2(g)$ (10 g)	V_i or V_{eff}
1	$U(PR_{cal})$	Probe Calibration	6.30	6.30	N	1.00	1.00	1.00	6.30	6.30	∞
2	$U(PR_{is})$	Isotropy	1.87	1.87	R	$\sqrt{3}$	1.00	1.00	1.08	1.08	∞
3	$U(L)$	Linearity	0.60	0.60	R	$\sqrt{3}$	1.00	1.00	0.35	0.35	∞
4	$U(PR_{mod})$	Probe modulation response	2.40	2.40	R	$\sqrt{3}$	1.00	1.00	1.39	1.39	∞
6	$U(DL)$	Detection Limits	1.00	1.00	R	$\sqrt{3}$	1.00	1.00	0.58	0.58	∞
5	$U(BE)$	Boundary effect	2.00	2.00	R	$\sqrt{3}$	1.00	1.00	1.15	1.15	∞
7	$U(RE)$	Readout Electronics	0.30	0.30	N	1.00	1.00	1.00	0.30	0.30	∞
8	$U(T_{res})$	Response Time	0.80	0.80	R	$\sqrt{3}$	1.00	1.00	0.46	0.46	∞
9	$U(T_{int})$	Integration Time	2.60	2.60	R	$\sqrt{3}$	1.00	1.00	1.50	1.50	∞
10	$U(A_{amb})$	RF ambient conditions-noise	3.00	3.00	R	$\sqrt{3}$	1.00	1.00	1.73	1.73	∞
11	$U(A_{ref})$	RF ambient conditions-reflections	3.00	3.00	R	$\sqrt{3}$	1.00	1.00	1.73	1.73	∞
12	$U(PR_{pos})$	Probe positioner mech. Restrictions	0.80	0.80	R	$\sqrt{3}$	1.00	1.00	0.46	0.46	∞
13	$U(PR_{pos})$	Probe positioning with respect to phantom shell	6.70	6.70	R	$\sqrt{3}$	1.00	1.00	3.87	3.87	∞
14	$U(PP_{max})$	Post-processing(for max. SAR evaluation)	4.00	4.00	R	$\sqrt{3}$	1.00	1.00	2.31	2.31	∞
15	$U(DU)$	Device Holder Uncertainty	3.60	3.60	N	1.00	1.00	1.00	3.60	3.60	5.00
16	$U(PO_{pos})$	Test sample positioning	1.81	1.42	N	1.00	1.00	1.00	1.81	1.42	9.00
17	$U(PS)$	Power scaling	0.00	0.00	R	$\sqrt{3}$	1.00	1.00	0.00	0.00	∞
18	$U(PO)$	Drift of output power(measured SAR drift)	5.00	5.00	R	$\sqrt{3}$	1.00	1.00	2.89	2.89	∞
19	$U(PL)$	Phantom Uncertainty	6.60	6.60	R	$\sqrt{3}$	1.00	1.00	3.81	3.81	∞
20	$U(CS_{alg})$	Algorithm for correcting SAR for deviations in permittivity and conductivity	1.90	1.90	N	1.00	1.00	0.84	1.90	1.60	∞
21	$U(ELC_{me})$	Liquid Conductivity (meas.)	1.29	1.18	N	1.00	0.78	0.71	1.01	0.84	5.00
22	$U(ELP_{me})$	Liquid Permittivity (meas.)	0.59	0.67	N	1.00	0.23	0.26	0.14	0.17	5.00
23	$U(ELC_{temp})$	Liquid conductivity(temperature uncertainty)	0.95	0.87	R	$\sqrt{3}$	0.78	0.71	0.43	0.36	∞
24	$U(ELP_{temp})$	Liquid permittivity(temperature uncertainty)	0.05	0.06	R	$\sqrt{3}$	0.23	0.26	0.01	0.01	∞
		$U(sar)$ Combined standard uncertainty (%)							10.84	10.72	396
		Extended uncertainty $U(\%)$							21.68	21.44	

5. ANSI/IEEE C95.1-2005 RF EXPOSURE LIMIT

In order for users to be aware of the body-worn operating requirements for meeting RF exposure compliance, operating instructions and cautions statements are included in the user's manual.

5.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

5.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Human Exposure Limits

	UNCONTROLLED ENVIRONMENT General Population (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT Professional Population (W/kg) or (mW/g)
SPATIAL PEAK SAR ¹ Brain	1.60	8.00
SPATIAL AVERAGE SAR ² Whole Body	0.08	0.40
SPATIAL PEAK SAR ³ Hands, Feet, Ankles, Wrists	4.00	20.00


¹ The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

² The Spatial Average value of the SAR averaged over the whole body.

³ The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

6. SYSTEM AND LIQUID VERIFICATION

6.1 System Verification setup



The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:

1. Signal Generator
2. Amplifier
3. Directional Coupler
4. Power Meter
5. Calibrated Dipole

The output power on dipole port must be calibrated to 30 dBm (1000 mW) before dipole is connected.

Numerical reference SAR values (W/kg) for reference dipole and flat phantom

1	2	3	4	5	6
Frequency MHz	Phantom shell thickness mm	1 g SAR W/kg	10 g SAR W/kg	Local SAR at surface (above feedpoint) W/kg	Local SAR at surface (y = 2 cm offset from feedpoint) W/kg
300	6.3	3.02	2.04	4.40	2.10
300	2.0	2.85	1.94	4.14	2.00
450	6.3	4.92	3.28	7.20	3.20
450	2.0	4.58	3.06	6.75	2.98
750	2.0	8.49	5.55	12.6	4.59
835	2.0	9.56	6.22	14.1	4.90
900	2.0	10.9	6.99	15.4	5.40
1 450	2.0	29.0	16.0	50.2	6.50
1 800	2.0	35.4	20.1	69.5	6.80
1 900	2.0	39.7	20.5	72.1	6.60
1 950	2.0	40.5	20.9	72.7	6.60
2 000	2.0	41.1	21.1	74.6	6.50
2 450	2.0	52.4	24.0	104	7.70
2 585	2.0	55.9	24.4	119	7.90
2 600	2.0	55.3	24.6	113	8.29
3 000	2.0	63.8	25.7	140	9.50
3 500	2.0	67.1	25.0	169	12.1
3 700	2.0	67.4	24.2	175	12.7
5 000	2.0	77.9	22.1	305	15.1
5 200	2.0	76.5	21.5	310	15.9
5 500	2.0	83.3	23.4	349	16.1
5 800	2.0	78.0	21.9	341	20.3

6.2 Liquid Validation

The dielectric parameters were checked prior to assessment using the DAK dielectric probe kit. The dielectric parameters measured are reported in each correspondent section.

6.3 Recommended Tissue Dielectric Parameters

The head and body tissue dielectric parameters recommended by KDB865664 have been incorporated in the following table.

Target Frequency	Head		Body	
(MHz)	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

(ϵ_r = relative permittivity, σ = conductivity and $\rho = 1000 \text{ kg/m}^3$)

6.4 Liquid Confirmation Results

6.4.1 System Verification

Frequency (MHz)	Tissue Type	Liquid Temp.(°C)	Parameter	Target Value	Measured Value	Deviation	Limit (%)	Date
2 450	Head	20.9	Permittivity	39.2	37.9	-3.26%	± 5	2018. May. 16
			Conductivity	1.80	1.80	0.01%	± 5	
2 450	Head	20.9	Permittivity	39.2	38.4	-2.15%	± 5	2018. May. 29
			Conductivity	1.80	1.78	-1.26%	± 5	
2 450	Body	21.1	Permittivity	52.7	50.8	-3.61%	± 5	2018. May. 17
			Conductivity	1.95	1.99	2.25%	± 5	
2 450	Body	21.1	Permittivity	52.7	51.3	-2.71%	± 5	2018. May. 29
			Conductivity	1.95	2.01	3.02%	± 5	
5 200	Head	21.1	Permittivity	36.0	35.2	-2.19%	± 5	2018. Jun. 04
			Conductivity	4.66	4.55	-2.39%	± 5	
5 300	Head	21.2	Permittivity	35.9	35.9	0.10%	± 5	2108. May. 18
			Conductivity	4.76	4.77	0.19%	± 5	
5 600	Head	21.0	Permittivity	35.5	34.7	-2.15%	± 5	2108. May. 23
			Conductivity	5.07	5.05	-0.35%	± 5	
5 800	Head	21.0	Permittivity	35.3	34.3	-2.87%	± 5	2108. May. 23
			Conductivity	5.27	5.29	0.32%	± 5	
5 200	Body	21.2	Permittivity	49.0	47.5	-3.22%	± 5	2018. Jun. 01
			Conductivity	5.35	5.46	1.94%	± 5	
5 300	Body	21.3	Permittivity	48.9	47.7	-2.50%	± 5	2108. May. 25
			Conductivity	5.46	5.55	1.48%	± 5	
5 600	Body	21.2	Permittivity	48.5	47.7	-1.57%	± 5	2018. May. 30
			Conductivity	5.79	6.00	3.65%	± 5	
5 800	Body	21.0	Permittivity	48.2	46.7	-3.14%	± 5	2018. May. 31
			Conductivity	6.00	6.22	3.61%	± 5	

6.4.2 Test Channel

Frequency (MHz)	Tissue Type	Liquid Temp.(°C)	Parameter	Target Value	Measured Value	Deviation	Limit (%)	Date
2 412	Head	20.9	Permittivity	39.3	38.0	-3.10%	± 5	2018. May. 16
			Conductivity	1.76	1.75	-0.49%	± 5	
2 437	Head	20.9	Permittivity	39.2	37.9	-3.29%	± 5	2018. May. 16
			Conductivity	1.79	1.78	-0.21%	± 5	
2 462	Head	20.9	Permittivity	39.2	38.3	-2.18%	± 5	2018. May. 29
			Conductivity	1.81	1.79	-1.17%	± 5	
2 412	Body	21.1	Permittivity	52.8	50.9	-3.50%	± 5	2018. May. 17
			Conductivity	1.90	1.95	2.58%	± 5	
2 437	Body	21.1	Permittivity	52.7	50.8	-3.56%	± 5	2018. May. 17
			Conductivity	1.93	1.98	2.38%	± 5	
2 462	Body	21.1	Permittivity	52.7	51.2	-2.76%	± 5	2018. May. 29
			Conductivity	1.96	2.02	2.81%	± 5	
5 180	Head	21.1	Permittivity	36.0	35.2	-2.24%	± 5	2018. Jun. 04
			Conductivity	4.64	4.51	-2.76%	± 5	
5 220	Head	21.1	Permittivity	36.0	35.2	-2.18%	± 5	2018. Jun. 04
			Conductivity	4.68	4.58	-2.25%	± 5	
5 240	Head	21.1	Permittivity	36.0	35.1	-2.30%	± 5	2018. Jun. 04
			Conductivity	4.70	4.58	-2.47%	± 5	
5 260	Head	21.2	Permittivity	35.9	36.0	0.22%	± 5	2018. May. 18
			Conductivity	4.72	4.7	0.18%	± 5	
5 300	Head	21.2	Permittivity	35.9	35.93	0.10%	± 5	2018. May. 18
			Conductivity	4.76	4.77	0.19%	± 5	
5 320	Head	21.2	Permittivity	35.9	35.90	0.05%	± 5	2018. May. 18
			Conductivity	4.78	4.80	0.36%	± 5	
5 500	Head	21.0	Permittivity	35.7	35.0	-1.94%	± 5	2018. May. 23
			Conductivity	4.97	4.93	-0.73%	± 5	
5 560	Head	21.0	Permittivity	35.6	34.8	-1.99%	± 5	2018. May. 23
			Conductivity	5.03	5.00	-0.55%	± 5	
5 700	Head	21.0	Permittivity	35.4	34.5	-2.53%	± 5	2018. May. 23
			Conductivity	5.17	5.17	0.00%	± 5	

Frequency (MHz)	Tissue Type	Liquid Temp.(°C)	Parameter	Target Value	Measured Value	Deviation	Limit (%)	Date
5 745	Head	21.0	Permittivity	35.4	34.4	-2.60%	± 5	2018. May. 23
			Conductivity	5.21	5.22	0.11%	± 5	
5 785	Head	21.0	Permittivity	35.3	34.3	-2.82%	± 5	2018. May. 23
			Conductivity	5.25	5.26	0.17%	± 5	
5 825	Head	21.0	Permittivity	35.3	34.3	-2.88%	± 5	2018. May. 23
			Conductivity	5.29	5.31	0.39%	± 5	
5 180	Body	21.2	Permittivity	49.1	47.5	-3.24%	± 5	2018. Jun. 01
			Conductivity	5.33	5.43	1.84%	± 5	
5 220	Body	21.2	Permittivity	49.0	47.4	-3.31%	± 5	2018. Jun. 01
			Conductivity	5.38	5.48	1.87%	± 5	
5 240	Body	21.2	Permittivity	95.0	47.3	-50.23%	± 5	2018. Jun. 01
			Conductivity	5.40	5.50	1.87%	± 5	
5 260	Body	21.3	Permittivity	49.0	47.6	-2.75%	± 5	2018. May. 25
			Conductivity	5.42	5.47	0.97%	± 5	
5 300	Body	21.3	Permittivity	48.9	47.7	-2.50%	± 5	2018. May. 25
			Conductivity	5.46	5.55	1.48%	± 5	
5 320	Body	21.3	Permittivity	48.9	47.6	-2.60%	± 5	2018. May. 25
			Conductivity	5.49	5.56	1.35%	± 5	
5 500	Body	21.2	Permittivity	48.6	47.8	-1.72%	± 5	2018. May. 30
			Conductivity	5.68	5.86	3.10%	± 5	
5 560	Body	21.2	Permittivity	48.5	47.8	-1.49%	± 5	2018. May. 30
			Conductivity	5.75	5.96	3.74%	± 5	
5 700	Body	21.2	Permittivity	48.3	47.6	-1.59%	± 5	2018. May. 30
			Conductivity	5.90	6.13	3.92%	± 5	
5 745	Body	21.0	Permittivity	48.3	47.0	-2.70%	± 5	2018. May. 31
			Conductivity	5.94	6.16	3.82%	± 5	
5 785	Body	21.0	Permittivity	48.2	46.8	-3.06%	± 5	2018. May. 31
			Conductivity	5.98	6.17	3.27%	± 5	
5 825	Body	21.0	Permittivity	48.2	46.7	-2.99%	± 5	2018. May. 31
			Conductivity	6.02	6.26	4.00%	± 5	

6.5 System Verification Results

Freq. (MHz)	Tissue Type	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (mW)	Dipole S/N	Probe S/N	Measured SAR 1g	1W Normalized SAR 1g	1W Target SAR 1g	Deviation	Date
2 450	Head	21.1	20.9	250	923	3832	13.1	52.4	51.9	0.96%	2018, May, 16
2 450	Head	21.1	20.9	250	923	3832	13.2	52.8	51.9	1.73%	2018, May, 29
2 450	Body	21.3	21.1	250	923	3832	13.0	52.0	51.3	1.36%	2018, May, 17
2 450	Body	21.3	21.1	250	923	3832	13.4	53.6	51.3	4.48%	2018, May, 29
5 200	Head	21.3	21.1	250	1094	3832	19.6	78.4	79.9	-1.88%	2018, Jun, 04
5 300	Head	21.7	21.2	250	1094	3832	21.5	86.0	83.3	3.24%	2018, May, 18
5 600	Head	21.2	21.0	250	1094	3832	21.2	84.8	85.8	-1.17%	2018, May, 23
5 800	Head	21.4	21.0	250	1094	3832	20.8	83.2	82.4	0.97%	2018, May, 23
5 200	Body	21.4	21.2	250	1094	3832	18.7	74.8	75.8	-1.32%	2018, Jun, 01
5 300	Body	21.4	21.3	250	1094	3832	19.9	79.6	77.9	2.18%	2018, May, 25
5 600	Body	21.4	21.2	250	1094	3832	21.2	84.8	82.3	3.04%	2018, May, 30
5 800	Body	21.2	21.0	250	1094	3832	19.8	79.2	79.6	-0.50%	2018, May, 31

7. SAR MEASUREMENT PROCEDURES

Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The Minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. The minimum distance of probe sensors to surface is 2 mm. This distance cannot be smaller than the Distance of sensor calibration points to probe tip as defined in the probe properties.

Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing.

For example, a 2 dB range is required in IEEE Standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan). If only one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of Zoom Scans has to be increased accordingly.

Step 3: Zoom Scan

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The Zoom Scan measures 5x5x7 points within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1 g and 10 g and displays these values next to the job's label.

Step 4: Power drift measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

Step 5: Z-Scan

The Z Scan measures points along a vertical straight line. The line runs along the Z-axis of a one dimensional grid. In order to get a reasonable extrapolation, the extrapolated distance should not be larger than the step size in Z-direction.

* Z Scan Report on Liquid Measure the height ANNEX C. Liquid Depth photo to replace

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <u>reported</u> SAR from the area scan based <i>1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

8. TEST EQUIPMENT LIST

Manufacturer	Model	Serial No.	CaL.Due	Used
STAUBLI	RX90XL	F07/56X0A1/A/01	N/A	V
STAUBLI	CS8C Speag TX90XL	F07/56X0A1/C/01	N/A	V
Speag	SE UMS 011 AA	1019	N/A	V
STAUBLI	SP1	D 211 421 02	N/A	V
Di-Soric	LB5	80	N/A	V
SPEAG	ELI4 Phantom	TP-1030	N/A	V
SPEAG	Twin Phantom	TP-1112	N/A	
SPEAG	Twin Phantom	TP-1069	N/A	
SPEAG	Mounting Device	N/A	N/A	
SPEAG	Mounting Device	SM LH1 001 AC	N/A	V
Agilent	85033E	N/A	N/A	V
SPEAG	SD 000 D04 BJ	444	2018-11-22	
SPEAG	SD 000 D04 BM	663	2018-06-19	V
SPEAG	EX3DV4	3832	2019-02-21	V
SPEAG	EX3DV4	3716	2018-11-27	
SPEAG	ES3DV3	3171	2018-07-21	
SPEAG	D835V2	4d172	2018-07-20	
SPEAG	D1750V2	1122	2018-07-21	
SPEAG	D1950V2	1156	2018-07-28	
SPEAG	D2450V2	923	2018-11-21	V
SPEAG	D5GHzV2	1094	2018-11-22	V
Speag	DAK-3.5 Short	1140	2018-11-21	V
Agilent	8648C	3847U03002	2018-09-11	V
HP	8665B	3744A01333	2018-09-11	V
EMPOWER	BBS3Q7ELY-2001	1009D/C0105	2018-09-11	V
VARIAN	VZC6961K11212	6673	2018-09-11	V
HP	778D	12679	2018-09-12	V
Agilent	772D	2839A01119	2018-09-11	
HP	437B	3125U25121	2018-09-12	V
Agilent	E4419B	MY41291366	2018-09-12	V
HP	8481H	3318A18722	2018-09-18	V
HP	8481A	1550A14928	2018-09-18	V
HP	8481D	3643A17398	2018-09-14	V
WAINWRIGHT	WLJS1500-6EF	1	2018-09-12	
WAINWRIGHT	WLJS6000-7EF	1	2018-09-12	V
Agilent	E8357A	US41070399	2018-09-11	V
HP	8564E	3650A00756	2018-09-12	V
LKM Electronic GmbH	DTM3000-Spezial	3247	2018-09-14	V
CAS	TE-201	14011777-2	2018-09-14	V
Bird	50-6A-MFN-30	14100882-2	2018-09-11	V
LITEPOINT	IQ_xel	IQXL02555	2019-05-18	V

9. RF CONDUCTED POWER

9.1 802.11b

Mode (Antenna)	Freq. (MHz)	CH	Conducted Power (dBm)				Tolerance (dBm)
			Data Rate (Mbps)				
			1	2	5.5	11	
802.11b (Main)	2 412	1	8.36	8.38	8.34	8.32	8 ± 2.5
	2 437	6	8.68	8.65	8.63	8.63	
	2 462	11	5.42	5.27	5.25	5.13	5 ± 2.5

Mode (Antenna)	Freq. (MHz)	CH	Conducted Power (dBm)				Tolerance (dBm)
			Data Rate (Mbps)				
			1	2	5.5	11	
802.11b (Aux)	2 412	1	7.98	7.93	7.87	7.95	8 ± 2.5
	2 437	6	8.99	8.90	8.89	8.87	
	2 462	11	5.03	5.10	5.07	5.19	5 ± 2.5

9.2 802.11g

Mode (Antenna)	Freq. (MHz)	CH	Conducted Power (dBm)								Tolerance (dBm)
			Data Rate (Mbps)								
			6	9	12	18	24	36	48	54	
802.11g (Main)	2 412	1	7.68	7.60	7.58	7.63	7.35	7.70	7.72	7.79	8 ± 2.5
	2 437	6	7.89	7.89	7.85	7.95	7.67	7.96	8.24	8.05	
	2 462	11	4.48	4.45	4.43	4.44	4.25	4.53	4.68	4.63	5 ± 2.5

Mode (Antenna)	Freq. (MHz)	CH	Conducted Power (dBm)								Tolerance (dBm)
			Data Rate (Mbps)								
			6	9	12	18	24	36	48	54	
802.11g (Aux)	2 412	1	7.39	7.42	7.25	7.38	7.17	7.63	7.70	7.63	8 ± 2.5
	2 437	6	8.14	8.09	7.97	8.18	7.67	8.27	8.14	8.30	
	2 462	11	4.46	4.45	4.33	4.50	4.05	4.53	4.63	4.65	5 ± 2.5

9.3 802.11n HT20

Mode (Antenna)	Freq. (MHz)	CH	Conducted Power (dBm)								Tolerance (dBm)
			Data Rate (Mbps)								
			MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15	
802.11n HT20 (Main)	2 412	1	7.97	7.41	7.42	7.49	7.73	7.71	7.76	7.84	8 ± 2.5
	2 437	6	8.17	7.62	7.70	7.72	8.07	8.11	8.11	8.11	
	2 462	11	4.73	4.29	4.28	4.23	4.59	4.67	4.62	4.70	5 ± 2.5

Mode (Antenna)	Freq. (MHz)	CH	Conducted Power (dBm)								Tolerance (dBm)
			Data Rate (Mbps)								
			MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15	
802.11n HT20 (Aux)	2 412	1	7.64	7.14	7.07	7.22	7.59	7.62	7.55	7.58	8 ± 2.5
	2 437	6	8.33	7.84	7.92	7.95	8.15	8.24	8.20	8.15	
	2 462	11	4.75	4.14	4.21	4.29	4.56	4.62	4.69	4.62	5 ± 2.5

9.4 802.11n HT40

Mode (Antenna)	Freq. (MHz)	CH	Conducted Power (dBm)								Tolerance (dBm)
			Data Rate (Mbps)								
			MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15	
802.11n HT40 (Main)	2 422	3	8.15	7.62	7.46	7.05	7.31	7.98	7.91	7.92	8 ± 2.5
	2 437	6	8.15	7.49	7.48	7.00	7.36	7.97	7.90	7.91	
	2 452	9	4.86	4.26	4.27	3.79	4.06	4.60	4.71	4.70	5 ± 2.5

Mode (Antenna)	Freq. (MHz)	CH	Conducted Power (dBm)								Tolerance (dBm)
			Data Rate (Mbps)								
			MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15	
802.11n HT40 (Aux)	2 422	3	8.12	7.56	7.41	6.91	7.31	7.95	7.85	7.89	8 ± 2.5
	2 437	6	8.26	7.73	7.62	7.06	7.46	8.02	8.00	8.00	
	2 452	9	4.79	4.22	4.11	3.62	4.11	4.76	4.69	4.78	5 ± 2.5

9.5 802.11a

Mode (Antenna)	Freq. (MHz)	CH	Conducted Power (dBm)								Tolerance (dBm)
			Data Rate (Mbps)								
			6	9	12	18	24	36	48	54	
U-NII 1 (Main)	5 180	36	6.58	6.65	6.14	6.05	6.01	6.03	5.86	5.72	6.5 ± 2.5
	5 200	40	6.86	6.87	6.31	6.28	6.38	6.09	6.29	6.06	
	5 220	44	6.41	6.45	5.87	5.88	5.88	5.53	5.63	5.63	
	5 240	48	6.82	6.84	6.24	6.36	6.26	6.02	6.08	6.18	
U-NII 2A (Main)	5 260	52	7.05	7.01	6.44	6.58	6.51	6.48	6.28	6.33	7 ± 2.5
	5 280	56	6.78	6.64	6.11	6.22	5.89	5.77	5.93	5.90	
	5 300	60	7.10	6.95	6.62	6.65	6.60	6.64	6.52	6.52	
	5 320	64	7.10	6.94	6.46	6.56	6.49	6.39	6.34	6.36	
U-NII 2C (Main)	5 500	100	6.31	6.27	5.75	6.65	6.61	5.78	5.88	5.81	
	5 520	104	6.58	6.57	5.94	6.18	6.10	5.79	5.89	5.86	
	5 540	108	6.06	6.25	5.64	5.68	5.61	5.61	5.65	5.60	
	5 560	112	7.21	7.13	6.75	6.95	6.56	6.42	6.51	6.45	
	5 580	116	6.15	6.18	5.65	5.66	5.41	5.51	5.57	5.33	
	5 600	120	6.62	6.56	6.00	5.91	5.64	5.72	5.80	5.64	
	5 620	124	7.14	6.99	6.46	6.52	6.34	6.16	6.23	6.19	
	5 640	128	6.24	6.10	5.36	5.46	5.54	5.35	5.22	5.14	
	5 660	132	6.59	6.65	6.02	6.14	5.85	5.82	5.76	5.79	
	5 680	136	6.78	6.65	6.14	6.19	6.03	5.79	5.85	5.82	
5 700	140	6.27	6.23	5.72	5.62	5.67	5.58	5.52	5.38		
U-NII 3 (Main)	5 745	149	5.63	5.64	5.11	4.99	4.94	4.90	4.87	4.72	6 ± 2.5
	5 765	153	5.45	5.47	4.92	4.95	4.89	4.73	4.80	4.47	
	5 785	157	6.12	6.10	5.62	5.65	5.31	5.38	5.42	5.48	
	5 805	161	5.50	5.55	4.88	5.00	4.68	4.61	4.77	4.87	
	5 825	165	6.03	5.98	5.41	5.31	5.37	5.27	5.38	5.19	

Mode (Antenna)	Freq. (MHz)	CH	Conducted Power (dBm)								Tolerance (dBm)
			Data Rate (Mbps)								
			6	9	12	18	24	36	48	54	
U-NII 1 (Aux)	5 180	36	6.02	6.42	5.99	5.72	5.43	5.58	5.52	5.80	6.5 ± 2.5
	5 200	40	7.27	7.30	6.78	6.48	6.46	6.28	6.30	6.19	
	5 220	44	6.24	6.30	5.76	5.59	5.23	5.34	5.16	5.26	
	5 240	48	6.59	6.52	5.87	5.76	5.58	5.51	5.59	5.61	
U-NII 2A (Aux)	5 260	52	7.66	7.67	7.30	6.97	6.76	6.81	6.74	6.69	7 ± 2.5
	5 280	56	6.90	6.97	6.42	6.44	5.94	6.02	5.72	5.76	
	5 300	60	7.08	7.12	6.44	6.31	6.21	6.22	6.23	6.16	
	5 320	64	7.33	7.33	6.71	6.59	6.44	6.65	6.43	6.19	
U-NII 2C (Aux)	5 500	100	7.79	7.69	7.21	7.03	6.86	6.91	6.96	7.07	
	5 520	104	8.77	8.76	8.20	8.12	7.84	7.89	7.80	7.77	
	5 540	108	8.56	8.78	8.12	8.03	7.86	7.80	7.77	7.69	
	5 560	112	8.26	8.18	7.63	7.46	7.38	7.28	7.18	7.18	
	5 580	116	9.12	9.04	8.44	8.30	7.96	8.05	8.05	8.09	
	5 600	120	7.61	8.12	7.49	7.21	7.08	6.99	6.91	6.93	
	5 620	124	8.26	8.19	7.61	7.62	7.44	7.34	7.13	7.11	
	5 640	128	8.64	8.60	8.06	8.07	7.68	7.68	7.59	7.68	
	5 660	132	7.65	7.60	7.00	6.89	6.72	6.73	6.56	6.65	
	5 680	136	8.42	8.50	7.90	7.72	7.41	7.57	7.39	7.68	
	5 700	140	7.77	8.06	7.41	7.36	7.02	7.20	7.15	7.00	
U-NII 3 (Aux)	5 745	149	7.13	7.23	6.68	6.39	6.14	6.31	6.16	6.17	6 ± 2.5
	5 765	153	6.21	6.24	5.56	5.54	5.42	5.26	5.25	5.05	
	5 785	157	6.77	6.65	6.14	6.17	5.89	5.75	5.65	5.99	
	5 805	161	6.51	6.41	5.86	5.70	5.42	5.50	5.36	5.41	
	5 825	165	5.37	5.34	4.76	4.80	4.52	4.39	4.48	4.58	

9.6 802.11n HT20

Mode (Antenna)	Freq. (MHz)	CH	Conducted Power (dBm)								Tolerance (dBm)
			Data Rate (Mbps)								
			MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15	
U-NII 1 (Main)	5 180	36	6.48	6.62	6.83	6.65	6.56	6.45	6.67	6.61	6.5 ± 2.5
	5 200	40	7.03	6.80	6.92	6.89	6.84	6.79	6.68	6.73	
	5 220	44	6.40	6.31	6.42	6.55	6.46	6.16	6.27	6.27	
	5 240	48	7.07	6.88	6.87	6.82	6.74	6.66	6.96	6.69	
U-NII 2A (Main)	5 260	52	7.38	7.32	7.39	7.14	7.17	7.14	7.06	7.15	7 ± 2.5
	5 280	56	7.22	7.23	7.11	7.15	7.11	7.11	7.17	7.07	
	5 300	60	7.50	7.47	7.47	7.47	7.42	7.44	7.51	7.38	
	5 320	64	7.15	7.14	7.20	7.17	7.39	7.21	7.06	7.17	
U-NII 2C (Main)	5 500	100	6.29	6.24	6.35	6.43	6.35	6.34	6.12	6.24	
	5 520	104	6.20	6.29	6.38	6.31	6.24	6.33	6.26	6.41	
	5 540	108	6.07	6.14	6.18	6.34	6.07	6.15	6.08	6.15	
	5 560	112	7.21	7.16	7.07	6.93	7.01	6.90	6.81	6.89	
	5 580	116	6.06	5.95	5.89	6.06	6.02	5.99	5.91	5.98	
	5 600	120	6.54	6.60	6.49	6.59	6.32	6.42	6.46	6.53	
	5 620	124	6.93	6.89	6.98	6.98	6.96	6.90	6.92	6.93	
	5 640	128	6.21	6.20	6.18	6.11	6.00	6.01	6.03	6.02	
	5 660	132	6.99	6.96	7.05	7.08	6.88	6.85	7.02	6.98	
	5 680	136	6.70	6.80	6.73	6.78	6.77	6.58	6.62	6.72	
	5 700	140	6.34	6.45	6.33	6.27	6.32	6.20	6.29	6.22	
U-NII 3 (Main)	5 745	149	5.81	5.71	5.79	5.81	5.64	5.68	5.60	5.61	6 ± 2.5
	5 765	153	5.73	5.87	5.69	5.71	5.64	5.79	5.78	5.62	
	5 785	157	6.49	6.43	6.43	6.46	6.44	6.41	6.30	6.32	
	5 805	161	5.61	5.56	5.68	5.60	5.60	5.54	5.48	5.49	
	5 825	165	6.45	6.43	6.53	6.30	6.46	6.34	6.41	6.37	

Mode (Antenna)	Freq. (MHz)	CH	Conducted Power (dBm)								Tolerance (dBm)
			Data Rate (Mbps)								
			MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15	
U-NII 1 (Aux)	5 180	36	6.27	6.23	6.27	6.37	6.00	5.95	6.03	6.25	6.5 ± 2.5
	5 200	40	7.13	7.07	7.10	6.83	6.73	6.68	6.72	6.71	
	5 220	44	6.08	6.09	6.09	5.94	5.84	5.85	5.79	6.17	
	5 240	48	6.39	6.34	6.25	6.22	6.15	6.11	6.19	5.89	
U-NII 2A (Aux)	5 260	52	7.52	7.54	7.75	7.42	7.16	7.18	7.11	7.21	7 ± 2.5
	5 280	56	6.70	6.74	6.86	6.51	6.31	6.37	6.13	6.16	
	5 300	60	6.87	6.86	6.82	6.83	6.74	6.54	6.57	6.69	
	5 320	64	7.11	6.98	7.08	7.04	6.88	7.00	6.87	6.93	
U-NII 2C (Aux)	5 500	100	7.51	7.55	7.49	7.45	7.41	7.36	7.34	7.36	
	5 520	104	8.51	8.58	8.54	8.53	8.38	8.28	8.25	8.14	
	5 540	108	8.47	8.57	8.65	8.55	8.49	8.22	8.18	8.22	
	5 560	112	8.17	8.13	8.14	8.11	7.82	7.74	7.66	7.72	
	5 580	116	8.85	8.83	8.82	8.80	8.51	8.53	8.46	8.25	
	5 600	120	7.96	7.93	7.91	7.90	7.57	7.59	7.40	7.43	
	5 620	124	8.09	8.01	8.04	8.15	7.93	7.75	7.78	7.73	
	5 640	128	8.36	8.26	8.38	8.32	8.19	8.04	8.04	8.19	
	5 660	132	7.55	7.38	7.46	7.36	7.30	7.18	7.11	7.07	
	5 680	136	8.24	8.24	8.28	8.18	8.21	7.94	8.05	7.91	
	5 700	140	7.51	7.76	7.87	7.75	7.74	7.69	7.57	7.50	
U-NII 3 (Aux)	5 745	149	7.06	7.03	7.19	6.87	6.64	7.10	6.71	6.71	6 ± 2.5
	5 765	153	6.00	5.98	5.96	5.99	5.79	5.82	5.67	5.68	
	5 785	157	6.46	6.48	6.55	6.58	6.27	6.38	6.19	6.34	
	5 805	161	6.24	6.12	6.23	6.29	6.12	6.05	5.86	5.81	
	5 825	165	5.28	5.10	5.22	5.23	4.94	5.00	5.02	4.96	

9.7 802.11ac VHT20

Mode (Antenna)	Freq. (MHz)	CH	Conducted Power (dBm)									Tolerance (dBm)
			Data Rate (Mbps)									
			MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	
U-NII 1 (Main)	5 180	36	6.43	6.36	6.47	6.58	6.44	6.50	6.41	6.35	6.53	6.5 ± 2.5
	5 200	40	6.64	6.48	6.68	6.80	6.67	6.65	6.87	6.72	6.73	
	5 220	44	6.25	6.06	6.36	6.41	6.29	6.18	6.09	6.24	6.33	
	5 240	48	6.75	6.54	6.77	6.72	6.67	6.67	6.80	6.73	6.70	
U-NII 2A (Main)	5 260	52	7.15	7.05	7.34	7.41	7.12	7.24	7.23	7.12	7.21	7 ± 2.5
	5 280	56	7.13	6.96	7.16	7.20	7.03	7.18	7.08	7.17	7.07	
	5 300	60	7.31	7.27	7.42	7.47	7.51	7.54	7.55	7.48	7.41	
	5 320	64	7.03	6.98	7.15	7.32	7.25	7.22	7.10	7.19	7.05	
U-NII 2C (Main)	5 500	100	6.07	6.03	6.25	6.27	6.24	6.40	6.33	6.29	6.42	
	5 520	104	6.10	6.05	6.32	6.33	6.37	6.35	6.32	6.47	6.42	
	5 540	108	6.05	5.95	6.17	6.26	6.09	6.18	6.13	6.24	6.16	
	5 560	112	7.04	7.00	7.17	7.11	7.08	7.08	6.98	7.12	6.97	
	5 580	116	5.94	5.84	5.99	6.27	6.04	6.04	5.96	5.96	6.08	
	5 600	120	6.49	6.45	6.64	6.63	6.62	6.48	6.47	6.65	6.52	
	5 620	124	6.99	6.80	6.81	7.06	6.96	6.94	6.90	6.92	6.94	
	5 640	128	6.12	6.14	6.19	6.13	6.02	6.10	6.27	6.06	5.92	
	5 660	132	6.99	6.91	7.04	7.05	6.93	7.01	6.86	6.93	6.87	
	5 680	136	6.65	6.56	6.80	6.63	6.84	6.81	6.75	6.71	6.84	
5 700	140	6.31	6.17	6.39	6.22	6.24	6.22	6.26	6.31	6.17		
U-NII 3 (Main)	5 745	149	5.66	5.54	5.68	5.76	5.75	5.63	5.67	5.50	5.61	6 ± 2.5
	5 765	153	5.79	5.70	5.84	5.64	5.74	5.85	5.85	5.81	5.76	
	5 785	157	6.36	6.22	6.50	6.45	6.39	6.45	6.56	6.49	6.34	
	5 805	161	5.46	5.36	5.61	5.64	5.51	5.61	5.50	5.63	5.30	
	5 825	165	6.28	6.32	6.45	6.49	6.48	6.54	6.42	6.50	6.51	

Mode (Antenna)	Freq. (MHz)	CH	Conducted Power (dBm)									Tolerance (dBm)
			Data Rate (Mbps)									
			MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	
U-NII 1 (Aux)	5 180	36	6.23	6.05	6.24	6.04	5.99	5.90	6.24	6.07	6.08	6.5 ± 2.5
	5 200	40	6.92	6.92	6.99	6.69	6.67	6.71	6.74	6.92	6.72	
	5 220	44	6.06	5.95	6.12	5.74	5.66	5.68	5.82	5.71	5.72	
	5 240	48	6.22	6.14	6.29	6.01	6.00	6.27	6.22	5.91	5.84	
U-NII 2A (Aux)	5 260	52	7.53	7.41	7.51	7.24	7.16	7.15	7.15	7.16	7.14	7 ± 2.5
	5 280	56	6.69	6.50	6.70	6.45	6.65	6.30	6.42	6.43	6.33	
	5 300	60	6.87	6.71	6.82	6.80	6.80	6.70	6.64	6.72	6.67	
	5 320	64	6.94	6.90	7.04	6.91	6.96	6.91	7.00	6.95	6.99	
U-NII 2C (Aux)	5 500	100	7.49	7.33	7.43	7.38	7.44	7.29	7.37	7.31	7.35	
	5 520	104	8.53	8.41	8.59	8.47	8.23	8.33	8.30	8.34	8.23	
	5 540	108	8.45	8.32	8.55	8.38	8.34	8.25	8.32	8.20	8.11	
	5 560	112	8.00	7.89	8.00	7.87	7.89	7.94	7.71	7.63	7.68	
	5 580	116	8.77	8.68	8.79	8.49	8.60	8.45	8.41	8.33	8.36	
	5 600	120	7.86	7.72	7.90	7.72	7.53	7.70	7.38	7.44	7.41	
	5 620	124	8.06	7.86	8.00	7.90	7.95	7.75	7.77	7.84	7.69	
	5 640	128	8.28	8.22	8.41	8.19	8.08	8.15	8.11	8.18	7.96	
	5 660	132	7.36	7.21	7.30	7.26	7.30	7.23	7.10	7.06	7.12	
	5 680	136	8.19	8.03	8.17	8.08	8.01	8.00	7.98	7.93	7.88	
5 700	140	7.93	7.82	7.84	7.78	7.65	7.70	7.57	7.54	7.61		
U-NII 3 (Aux)	5 745	149	7.04	6.87	6.99	6.81	6.67	6.70	6.64	6.57	6.50	6 ± 2.5
	5 765	153	6.05	5.85	5.99	5.83	5.77	5.88	5.83	5.69	5.59	
	5 785	157	6.43	6.36	6.51	6.46	6.18	6.32	6.37	6.37	6.28	
	5 805	161	6.25	6.17	6.19	6.05	5.95	5.93	5.99	5.95	5.86	
	5 825	165	5.31	4.95	5.14	4.98	4.96	5.06	4.95	4.87	4.91	

9.8 802.11n HT40

Mode (Antenna)	Freq. (MHz)	CH	Conducted Power (dBm)								Tolerance (dBm)
			Data Rate (Mbps)								
			MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15	
U-NII 1 (Main)	5 190	38	6.74	6.60	6.67	6.58	6.89	6.52	6.51	6.53	6.5 ± 2.5
	5 230	46	6.71	6.57	6.51	6.60	6.42	6.49	6.49	6.48	
U-NII 2A (Main)	5 270	54	7.35	7.26	7.25	7.27	7.24	7.31	7.33	7.26	7 ± 2.5
	5 310	62	7.31	7.34	7.29	7.43	7.44	7.55	7.27	7.35	
U-NII 2C (Main)	5 510	102	6.79	6.83	6.75	6.82	6.83	6.84	6.98	6.96	
	5 550	110	6.92	6.76	6.80	6.84	6.79	6.71	6.66	6.89	
	5 590	118	6.18	6.03	6.07	6.15	6.16	6.12	6.19	6.23	
	5 630	126	6.42	6.65	6.47	6.56	6.68	6.60	6.39	6.44	
	5 670	134	7.21	7.01	7.08	6.99	7.05	6.97	7.07	6.97	
U-NII 3 (Main)	5 755	151	5.81	5.62	5.66	5.75	5.72	5.71	5.83	5.67	6 ± 2.5
	5 795	159	6.15	6.16	6.14	6.34	6.07	6.23	6.10	6.34	

Mode (Antenna)	Freq. (MHz)	CH	Conducted Power (dBm)								Tolerance (dBm)
			Data Rate (Mbps)								
			MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15	
U-NII 1 (Aux)	5 190	38	6.85	6.77	6.61	6.52	6.54	6.55	6.48	6.57	6.5 ± 2.5
	5 230	46	6.54	6.18	6.10	6.05	6.04	6.07	5.93	5.95	
U-NII 2A (Aux)	5 270	54	7.20	7.04	7.01	6.97	6.87	6.80	6.77	6.77	7 ± 2.5
	5 310	62	7.05	6.97	6.87	6.86	6.81	6.75	6.82	6.79	
U-NII 2C (Aux)	5 510	102	8.12	8.15	8.02	8.17	8.08	7.84	7.95	7.96	
	5 550	110	8.34	8.20	8.10	8.13	7.96	7.86	8.02	7.86	
	5 590	118	8.21	8.13	8.10	8.04	7.92	7.86	7.78	7.87	
	5 630	126	8.36	8.19	8.11	7.92	7.96	7.84	8.01	7.79	
	5 670	134	7.83	7.79	7.70	7.82	7.66	7.62	7.57	7.52	
U-NII 3 (Aux)	5 755	151	6.71	6.56	6.43	6.27	6.33	6.19	6.33	6.28	6 ± 2.5
	5 795	159	6.55	6.28	6.17	6.10	6.15	6.21	6.29	6.26	

9.9 802.11ac VHT40

Mode (Antenna)	Freq. (MHz)	CH	Conducted Power (dBm)										Tolerance (dBm)
			Data Rate (Mbps)										
			MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	
U-NII 1 (Main)	5 190	38	6.67	6.64	6.57	6.72	6.73	6.85	6.62	6.56	6.64	6.63	6.5 ± 2.5
	5 230	46	6.59	6.52	6.55	6.59	6.68	6.59	6.60	6.71	6.53	6.58	
U-NII 2A (Main)	5 270	54	7.17	7.18	7.20	7.25	7.38	7.28	7.31	7.35	7.25	7.32	7 ± 2.5
	5 310	62	7.33	7.32	7.33	7.37	7.49	7.36	7.40	7.54	7.26	7.44	
U-NII 2C (Main)	5 510	102	6.92	6.88	6.83	6.88	7.10	7.02	6.90	7.00	7.10	7.00	
	5 550	110	6.79	6.89	6.86	6.82	7.00	6.89	6.83	6.76	6.77	6.84	
	5 590	118	6.03	6.05	6.02	6.26	6.26	6.22	6.17	6.15	6.22	6.24	
	5 630	126	6.29	6.50	6.63	6.83	6.72	6.63	6.77	6.42	6.45	6.48	
	5 670	134	6.98	7.03	7.08	7.06	7.19	7.02	7.09	7.02	7.02	7.02	
U-NII 3 (Main)	5 755	151	5.74	5.68	5.61	5.65	5.75	5.83	5.91	5.85	5.65	5.73	6 ± 2.5
	5 795	159	5.99	6.08	6.06	6.13	6.16	6.21	6.17	6.05	6.23	5.99	

Mode (Antenna)	Freq. (MHz)	CH	Conducted Power (dBm)										Tolerance (dBm)
			Data Rate (Mbps)										
			MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	
U-NII 1 (Aux)	5 190	38	6.80	6.65	6.60	6.47	6.62	6.47	6.52	6.49	6.60	6.58	6.5 ± 2.5
	5 230	46	6.10	6.11	6.06	6.07	6.11	6.03	6.08	5.97	5.93	5.91	
U-NII 2A (Aux)	5 270	54	7.08	6.96	6.98	7.09	7.00	6.77	6.71	6.75	6.76	6.66	7 ± 2.5
	5 310	62	7.06	7.00	6.88	6.82	6.98	6.82	6.78	6.71	6.79	6.73	
U-NII 2C (Aux)	5 510	102	8.07	8.01	7.98	8.26	8.15	8.11	7.97	7.88	7.97	7.85	
	5 550	110	8.19	8.11	8.10	8.11	8.01	8.07	7.78	7.88	7.93	7.79	
	5 590	118	8.22	8.09	8.01	8.07	8.01	7.76	7.95	7.83	7.92	7.85	
	5 630	126	8.24	8.21	8.14	8.04	8.00	8.03	7.93	7.90	7.95	7.87	
	5 670	134	7.79	7.64	7.71	7.60	7.78	7.65	7.56	7.52	7.69	7.49	
U-NII 3 (Aux)	5 755	151	6.68	6.65	6.44	6.28	6.48	6.35	6.19	6.29	6.32	6.23	6 ± 2.5
	5 795	159	6.63	6.26	6.24	6.15	5.96	6.10	6.19	6.23	6.28	6.16	

9.10 802.11ac VHT80

Mode (Antenna)	Freq. (MHz)	CH	Conducted Power (dBm)										Tolerance (dBm)
			Data Rate (Mbps)										
			MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	
U-NII 1 (Main)	5 210	42	6.87	6.93	6.80	6.97	6.83	6.67	6.65	6.59	6.66	6.70	6.5 ± 2.5
U-NII 2A (Main)	5 290	58	7.48	7.60	7.52	7.54	7.44	7.32	7.51	7.47	7.39	7.53	7 ± 2.5
U-NII 2C (Main)	5 530	106	6.80	6.88	6.75	6.85	6.94	6.90	6.91	6.83	6.86	6.88	
	5 610	122	6.91	6.97	6.79	6.77	6.71	6.62	6.67	6.64	6.57	6.57	
	5 690	138	7.10	7.17	7.13	7.05	7.00	7.01	6.81	6.78	6.62	6.70	
U-NII 3 (Main)	5 775	155	5.85	6.10	6.06	6.00	5.99	5.92	5.82	5.89	5.98	6.03	6 ± 2.5

Mode (Antenna)	Freq. (MHz)	CH	Conducted Power (dBm)										Tolerance (dBm)
			Data Rate (Mbps)										
			MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	
U-NII 1 (Aux)	5 210	42	6.56	6.65	6.63	6.41	6.21	6.27	6.14	6.27	6.32	6.23	6.5 ± 2.5
U-NII 2A (Aux)	5 290	58	7.49	7.58	7.44	7.27	7.12	7.12	7.23	7.20	7.10	7.17	7 ± 2.5
U-NII 2C (Aux)	5 530	106	8.57	8.52	8.33	8.04	8.13	7.98	7.98	7.88	7.87	7.83	
	5 610	122	8.37	8.50	8.28	8.32	8.15	8.08	8.03	7.99	8.03	7.91	
	5 690	138	7.69	7.94	7.78	7.66	7.57	7.42	7.41	7.37	7.29	7.37	
U-NII 3 (Aux)	5 775	155	6.71	6.82	6.71	6.59	6.52	6.39	6.39	6.33	6.49	6.40	6 ± 2.5

10.SAR TEST RESULTS

< 2.4 GHz Main Antenna - 802.11b Head Tissue SAR_0mm distance from Phantom >

Position	Freq. (MHz)	CH	Conducted Power (dBm)	Max. Allowed Power (dBm)	Scaling Factor	Duty Factor	Measured 1g SAR (W/kg)	Duty Cal. SAR (W/kg)	Reported SAR (W/kg)
Front	2 412	1	8.36	10.50	1.64	1.011	0.192	0.194	0.318
	2 437	6	8.68	10.50	1.52	1.008	0.336	0.339	0.515
	2 462	11	5.42	7.50	1.61	1.006	0.300	0.302	0.487

< 2.4 GHz Aux Antenna - 802.11b Head Tissue SAR_0mm distance from Phantom >

Position	Freq. (MHz)	CH	Conducted Power (dBm)	Max. Allowed Power (dBm)	Scaling Factor	Duty Factor	Measured 1g SAR (W/kg)	Duty Cal. SAR (W/kg)	Reported SAR (W/kg)
Front	2 412	1	7.98	10.50	1.79	1.007	0.137	0.138	0.246
	2 437	6	8.99	10.50	1.42	1.007	0.296	0.298	0.422
	2 462	11	5.03	7.50	1.77	1.007	0.220	0.222	0.391

< 2.4 GHz Head Tissue - Simultaneous Transmission SAR >

Position	Main Antenna (W/kg)	Aux Antenna (W/kg)	Sum of peak SAR (W/kg)
Front	0.515	0.422	0.937

< 2.4 GHz Main Antenna - 802.11b Body Tissue SAR_0mm distance from Phantom >

Position	Freq. (MHz)	CH	Conducted Power (dBm)	Max. Allowed Power (dBm)	Scaling Factor	Duty Factor	Measured 1g SAR (W/kg)	Duty Cal. SAR (W/kg)	Reported SAR (W/kg)
Front	2 412	1	8.36	10.50	1.64	1.011	0.253	0.256	0.419
	2 437	6	8.68	10.50	1.52	1.008	0.288	0.290	0.441
	2 462	11	5.42	7.50	1.61	1.006	0.323	0.325	0.525
Back	2 437	6	8.68	10.50	1.52	1.008	0.182	0.183	0.279
Bottom	2 437	6	8.68	10.50	1.52	1.008	0.284	0.286	0.435

< 2.4 GHz Aux Antenna - 802.11b Body Tissue SAR_0mm distance from Phantom >

Position	Freq. (MHz)	CH	Conducted Power (dBm)	Max. Allowed Power (dBm)	Scaling Factor	Duty Factor	Measured 1g SAR (W/kg)	Duty Cal. SAR (W/kg)	Reported SAR (W/kg)
Front	2 412	1	7.98	10.50	1.79	1.007	0.186	0.187	0.335
	2 437	6	8.99	10.50	1.42	1.007	0.403	0.406	0.575
	2 462	11	5.03	7.50	1.77	1.006	0.225	0.226	0.400
Back	2 437	6	8.93	10.50	1.44	1.007	0.190	0.191	0.275
Right	2 437	6	8.93	10.50	1.44	1.007	0.309	0.311	0.447

< 2.4 GHz Body Tissue – Simultaneous Transmission SAR >

Position	Main Antenna (W/kg)	Aux Antenna (W/kg)	Sum of peak SAR (W/kg)
Front	0.525	0.575	1.100
Back	0.279	0.275	0.554
Bottom	0.435	0.400	0.835
Right	0.077	0.447	0.524

< 5.2 GHz Main Antenna - 802.11n HT20 Head Tissue SAR_0mm distance from Phantom >

Position	Freq. (MHz)	CH	Conducted Power (dBm)	Max. Allowed Power (dBm)	Scaling Factor	Duty Factor	Measured 1g SAR (W/kg)	Duty Cal. SAR (W/kg)	Reported SAR (W/kg)
Front	5 180	36	6.48	9.00	1.79	1.140	0.052	0.059	0.106
	5 220	44	6.40	9.00	1.82	1.146	0.074	0.085	0.155
	5 240	48	7.07	9.00	1.56	1.152	0.079	0.091	0.142

< 5.2 GHz Aux Antenna - 802.11n HT40 Head Tissue SAR_0mm distance from Phantom >

Position	Freq. (MHz)	CH	Conducted Power (dBm)	Max. Allowed Power (dBm)	Scaling Factor	Duty Factor	Measured 1g SAR (W/kg)	Duty Cal. SAR (W/kg)	Reported SAR (W/kg)
Front	5 190	38	6.85	9.00	1.64	1.148	0.103	0.118	0.194
	5 230	46	6.54	9.00	1.76	1.142	0.209	0.239	0.421

< 5.2 GHz Head Tissue - Simultaneous Transmission SAR >

Position	Main Antenna (W/kg)	Aux Antenna (W/kg)	Sum of peak SAR (W/kg)
Front	0.155	0.421	0.576

< 5.3 GHz Main Antenna - 802.11ac VHT80 Head Tissue SAR_0mm distance from Phantom >

Position	Freq. (MHz)	CH	Conducted Power (dBm)	Max. Allowed Power (dBm)	Scaling Factor	Duty Factor	Measured 1g SAR (W/kg)	Duty Cal. SAR (W/kg)	Reported SAR (W/kg)
Front	5 290	58	7.60	9.50	1.55	1.168	0.232	0.271	0.420

< 5.3 GHz Aux Antenna - 802.11n HT20 Head Tissue SAR_0mm distance from Phantom >

Position	Freq. (MHz)	CH	Conducted Power (dBm)	Max. Allowed Power (dBm)	Scaling Factor	Duty Factor	Measured 1g SAR (W/kg)	Duty Cal. SAR (W/kg)	Reported SAR (W/kg)
Front	5 260	52	7.75	9.50	1.50	1.138	0.211	0.240	0.359
	5 300	60	6.86	9.50	1.84	1.145	0.133	0.152	0.280
	5 320	64	6.82	9.50	1.85	1.139	0.108	0.123	0.228

< 5.3 GHz Head Tissue - Simultaneous Transmission SAR >

Position	Main Antenna (W/kg)	Aux Antenna (W/kg)	Sum of peak SAR (W/kg)
Front	0.420	0.359	0.779

< 5.6 GHz Main Antenna - 802.11a Head Tissue SAR_0mm distance from Phantom >

Position	Freq. (MHz)	CH	Conducted Power (dBm)	Max. Allowed Power (dBm)	Scaling Factor	Duty Factor	Measured 1g SAR (W/kg)	Duty Cal. SAR (W/kg)	Reported SAR (W/kg)
Front	5 500	100	6.31	9.50	2.08	1.167	0.104	0.121	0.253
	5 560	112	7.23	9.50	1.69	1.167	0.174	0.203	0.342
	5 700	140	6.27	9.50	2.10	1.167	0.296	0.345	0.727

< 5.6 GHz Aux Antenna - 802.11ac VHT80 Head Tissue SAR_0mm distance from Phantom >

Position	Freq. (MHz)	CH	Conducted Power (dBm)	Max. Allowed Power (dBm)	Scaling Factor	Duty Factor	Measured 1g SAR (W/kg)	Duty Cal. SAR (W/kg)	Reported SAR (W/kg)
Front	5 530	106	8.57	9.50	1.24	1.158	0.230	0.266	0.330
	5 610	122	8.37	9.50	1.30	1.157	0.129	0.149	0.194

< 5.6 GHz Head Tissue - Simultaneous Transmission SAR >

Position	Main Antenna (W/kg)	Aux Antenna (W/kg)	Sum of peak SAR (W/kg)
Front	0.727	0.330	1.057

< 5.8 GHz Main Antenna - 802.11ac VHT20 Head Tissue SAR_0mm distance from Phantom >

Position	Freq. (MHz)	CH	Conducted Power (dBm)	Max. Allowed Power (dBm)	Scaling Factor	Duty Factor	Measured 1g SAR (W/kg)	Duty Cal. SAR (W/kg)	Reported SAR (W/kg)
Front	5 745	149	5.67	8.50	1.92	1.132	0.125	0.142	0.271
	5 785	157	6.56	8.50	1.56	1.132	0.144	0.163	0.255
	5 825	165	6.42	8.50	1.61	1.132	0.099	0.112	0.181

< 5.8 GHz Aux Antenna - 802.11a Head Tissue SAR_0mm distance from Phantom >

Position	Freq. (MHz)	CH	Conducted Power (dBm)	Max. Allowed Power (dBm)	Scaling Factor	Duty Factor	Measured 1g SAR (W/kg)	Duty Cal. SAR (W/kg)	Reported SAR (W/kg)
Front	5 745	149	7.23	8.50	1.34	1.125	0.099	0.111	0.149
	5 785	157	6.65	8.50	1.53	1.125	0.107	0.120	0.184
	5 825	165	5.34	8.50	2.07	1.125	0.098	0.111	0.229

< 5.8 GHz Head Tissue - Simultaneous Transmission SAR >

Position	Main Antenna (W/kg)	Aux Antenna (W/kg)	Sum of peak SAR (W/kg)
Front	0.270	0.229	0.499

< 5.2 GHz Main Antenna - 802.11n HT20 Body Tissue SAR_0mm distance from Phantom >

Position	Freq. (MHz)	CH	Conducted Power (dBm)	Max. Allowed Power (dBm)	Scaling Factor	Duty Factor	Measured 1g SAR (W/kg)	Duty Cal. SAR (W/kg)	Reported SAR (W/kg)
Front	5 180	36	6.48	9.00	1.79	1.140	0.039	0.044	0.079
	5 220	44	6.40	9.00	1.82	1.146	0.056	0.064	0.117
	5 240	48	7.07	9.00	1.56	1.152	0.066	0.076	0.119
Back	5 220	44	6.40	9.00	1.82	1.146	0.017	0.019	0.035
Bottom	5 180	36	6.48	9.00	1.79	1.140	0.322	0.367	0.656
	5 220	44	6.40	9.00	1.82	1.146	0.324	0.371	0.676
	5 240	48	7.07	9.00	1.56	1.152	0.356	0.410	0.640

< 5.2 GHz Aux Antenna - 802.11n HT40 Body Tissue SAR_0mm distance from Phantom >

Position	Freq. (MHz)	CH	Conducted Power (dBm)	Max. Allowed Power (dBm)	Scaling Factor	Duty Factor	Measured 1g SAR (W/kg)	Duty Cal. SAR (W/kg)	Reported SAR (W/kg)
Front	5 190	38	6.85	9.00	1.64	1.148	0.081	0.093	0.153
	5 230	46	6.54	9.00	1.76	1.142	0.159	0.182	0.320
Back	5 190	38	6.85	9.00	1.64	1.148	0.028	0.032	0.053
Right	5 190	38	6.85	9.00	1.64	1.148	0.466	0.535	0.878
	5 230	46	6.54	9.00	1.76	1.142	0.541	0.618	1.089

< 5.2 GHz Body Tissue - Simultaneous Transmission SAR >

Position	Main Antenna (W/kg)	Aux Antenna (W/kg)	Sum of peak SAR (W/kg)
Front	0.119	0.320	0.439
Back	0.035	0.053	0.088
Bottom	0.676	0.400	1.076
Right	0.093	1.089	1.182

< 5.3 GHz Main Antenna - 802.11ac VHT80 Body Tissue SAR_0mm distance from Phantom >

Position	Freq. (MHz)	CH	Conducted Power (dBm)	Max. Allowed Power (dBm)	Scaling Factor	Duty Factor	Measured 1g SAR (W/kg)	Duty Cal. SAR (W/kg)	Reported SAR (W/kg)
Front	5 290	58	7.60	9.50	1.55	1.168	0.169	0.197	0.306
Back	5 290	58	7.60	9.50	1.55	1.168	0.034	0.040	0.062
Bottom	5 290	58	7.60	9.50	1.55	1.168	0.401	0.468	0.725

< 5.3 GHz Aux Antenna - 802.11n HT20 Body Tissue SAR_0mm distance from Phantom >

Position	Freq. (MHz)	CH	Conducted Power (dBm)	Max. Allowed Power (dBm)	Scaling Factor	Duty Factor	Measured 1g SAR (W/kg)	Duty Cal. SAR (W/kg)	Reported SAR (W/kg)
Front	5 260	52	7.75	9.50	1.50	1.138	0.198	0.225	0.337
	5 300	60	6.86	9.50	1.84	1.145	0.118	0.135	0.248
	5 320	64	6.82	9.50	1.85	1.139	0.096	0.109	0.203
Back	5 300	60	6.86	9.50	1.84	1.145	0.032	0.037	0.067
Right	5 260	52	7.75	9.50	1.50	1.138	0.478	0.544	0.814
	5 300	60	6.86	9.50	1.84	1.145	0.403	0.461	0.847
	5 320	64	6.82	9.50	1.85	1.139	0.407	0.464	0.859

< 5.3 GHz Body Tissue - Simultaneous Transmission SAR >

Position	Main Antenna (W/kg)	Aux Antenna (W/kg)	Sum of peak SAR (W/kg)
Front	0.306	0.337	0.643
Back	0.062	0.067	0.129
Bottom	0.725	0.400	1.125
Right	0.104	0.859	0.963

< 5.6 GHz Main Antenna - 802.11a Body Tissue SAR_0mm distance from Phantom >

Position	Freq. (MHz)	CH	Conducted Power (dBm)	Max. Allowed Power (dBm)	Scaling Factor	Duty Factor	Measured 1g SAR (W/kg)	Duty Cal. SAR (W/kg)	Reported SAR (W/kg)
Front	5 500	100	6.31	9.50	2.08	1.167	0.076	0.089	0.185
	5 560	112	7.23	9.50	1.69	1.167	0.145	0.169	0.285
	5 700	140	6.27	9.50	2.10	1.167	0.297	0.347	0.729
Back	5 560	112	7.23	9.50	1.69	1.167	0.030	0.035	0.059
Bottom	5 500	100	31.00	9.50	0.01	1.167	0.158	0.184	0.001
	5 560	112	7.23	9.50	1.69	1.167	0.202	0.236	0.398
	5 700	140	6.27	9.50	2.10	1.167	0.443	0.517	1.088

< 5.6 GHz Aux Antenna - 802.11ac VHT80 Body Tissue SAR_0mm distance from Phantom >

Position	Freq. (MHz)	CH	Conducted Power (dBm)	Max. Allowed Power (dBm)	Scaling Factor	Duty Factor	Measured 1g SAR (W/kg)	Duty Cal. SAR (W/kg)	Reported SAR (W/kg)
Front	5 530	106	8.57	9.50	1.24	1.158	0.223	0.258	0.320
	5 610	122	8.37	9.50	1.30	1.157	0.137	0.159	0.206
Back	5 530	106	8.57	9.50	1.24	1.158	0.074	0.086	0.106
Right	5 530	106	8.57	9.50	1.24	1.158	0.264	0.306	0.379
	5 610	122	8.37	9.50	1.30	1.157	0.135	0.156	0.203

< 5.6 GHz Body Tissue - Simultaneous Transmission SAR >

Position	Main Antenna (W/kg)	Aux Antenna (W/kg)	Sum of peak SAR (W/kg)
Front	0.729	0.320	1.049
Back	0.059	0.106	0.165
Bottom	1.088	0.400	1.488
Right	0.106	0.379	0.485

< 5.8 GHz Main Antenna - 802.11ac VHT20 Body Tissue SAR_0mm distance from Phantom >

Position	Freq. (MHz)	CH	Conducted Power (dBm)	Max. Allowed Power (dBm)	Scaling Factor	Duty Factor	Measured 1g SAR (W/kg)	Duty Cal. SAR (W/kg)	Reported SAR (W/kg)
Front	5 745	149	5.67	8.50	1.92	1.132	0.151	0.171	0.328
	5 785	157	6.56	8.50	1.56	1.132	0.121	0.137	0.214
	5 825	165	6.42	8.50	1.61	1.132	0.102	0.115	0.186
Back	5 785	157	6.56	8.50	1.56	1.132	0.040	0.045	0.071
Bottom	5 745	149	5.67	8.50	1.92	1.132	0.323	0.366	0.702
	5 785	157	6.56	8.50	1.56	1.132	0.312	0.353	0.552
	5 825	165	6.42	8.50	1.61	1.132	0.218	0.247	0.398

< 5.8 GHz Aux Antenna - 802.11a Body Tissue SAR_0mm distance from Phantom >

Position	Freq. (MHz)	CH	Conducted Power (dBm)	Max. Allowed Power (dBm)	Scaling Factor	Duty Factor	Measured 1g SAR (W/kg)	Duty Cal. SAR (W/kg)	Reported SAR (W/kg)
Front	5 745	149	7.23	8.50	1.34	1.150	0.088	0.101	0.136
	5 785	157	6.65	8.50	1.53	1.138	0.085	0.097	0.148
	5 825	165	5.00	8.50	2.24	1.138	0.077	0.088	0.196
Back	5 785	157	6.65	8.50	1.53	1.138	0.038	0.043	0.066
Right	5 745	149	7.23	8.50	1.34	1.150	0.230	0.265	0.354
	5 785	157	6.65	8.50	1.53	1.138	0.307	0.349	0.535
	5 825	165	5.34	8.50	2.07	1.138	0.352	0.401	0.829

< 5.8 GHz Body Tissue - Simultaneous Transmission SAR >

Position	Main Antenna (W/kg)	Aux Antenna (W/kg)	Sum of peak SAR (W/kg)
Front	0.328	0.196	0.524
Back	0.071	0.066	0.137
Bottom	0.702	0.400	1.102
Right	0.098	0.829	0.927

Note.

- 1) The SAR test is exempted for the right and the bottom side of the EUT because the separation distance between the main antenna and the right side and between the Aux antenna and the bottom side are more than 25 mm.
- 2) Simultaneous transmission SAR test was excluded according to KDB 447498.
 - For the right position of Main antenna, the value was calculated by 4.3.2.b).1)
 - For the bottom position of Aux antenna, 0.4 W/kg was applied by 4.3.2.b).2)

ANNEX A. SYSTEM VERIFICATION PLOTS

< 2 450 MHz Head Tissue / Date : May 16, 2018 >

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:923

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.8$ mho/m; $\epsilon_r = 37.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(7.28, 7.28, 7.28); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

2 450 MHz SPC/Area Scan (71x101x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 20.5 mW/g


2 450 MHz SPC/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 105.1 V/m; Power Drift = 0.132 dB

Peak SAR (extrapolated) = 27.5 W/kg

SAR(1 g) = 13.1 mW/g; SAR(10 g) = 6.05 mW/g

Maximum value of SAR (measured) = 20.1 mW/g



0 dB = 20.1mW/g

< 2 450 MHz Head Tissue / Date : May 29, 2018 >

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:923

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.78$ mho/m; $\epsilon_r = 38.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(7.28, 7.28, 7.28); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

2 450 MHz SPC/Area Scan (71x101x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 20.6 mW/g


2 450 MHz SPC/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 98.3 V/m; Power Drift = 0.091 dB

Peak SAR (extrapolated) = 27.8 W/kg

SAR(1 g) = 13.2 mW/g; SAR(10 g) = 6.09 mW/g

Maximum value of SAR (measured) = 20.1 mW/g



0 dB = 20.1mW/g

< 2 450 MHz Body Tissue / Date : May 17, 2018 >

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:923

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.99$ mho/m; $\epsilon_r = 50.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(7.28, 7.28, 7.28); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

2 450 MHz SPC/Area Scan (71x101x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 20.2 mW/g


2 450 MHz SPC/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 97.2 V/m; Power Drift = 0.074 dB

Peak SAR (extrapolated) = 26.8 W/kg

SAR(1 g) = 13 mW/g; SAR(10 g) = 6.04 mW/g

Maximum value of SAR (measured) = 19.8 mW/g



0 dB = 19.8mW/g

< 2 450 MHz Body Tissue / Date : May 29, 2018 >

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:923

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 2.01$ mho/m; $\epsilon_r = 51.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(7.28, 7.28, 7.28); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

2 450 MHz SPC/Area Scan (71x101x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 20.4 mW/g


2 450 MHz SPC/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 91.8 V/m; Power Drift = 0.069 dB

Peak SAR (extrapolated) = 27.7 W/kg

SAR(1 g) = 13.4 mW/g; SAR(10 g) = 6.23 mW/g

Maximum value of SAR (measured) = 20.4 mW/g



0 dB = 20.4mW/g

< 5 200 MHz Head Tissue / Date : Jun 04, 2018 >

DUT: Dipole 5GHz; Type: D5GHzV2; Serial: D5GHzV2 - SN:1094

Communication System: CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5200$ MHz; $\sigma = 4.55$ mho/m; $\epsilon_r = 35.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(5.5, 5.5, 5.5); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

5 200 MHz SPC/Area Scan (81x121x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 40.8 mW/g


5 200 MHz SPC/Zoom Scan (8x8x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 78.9 V/m; Power Drift = 0.038 dB

Peak SAR (extrapolated) = 84.3 W/kg

SAR(1 g) = 19.6 mW/g; SAR(10 g) = 5.61 mW/g

Maximum value of SAR (measured) = 38.1 mW/g



0 dB = 38.1mW/g

< 5 300 MHz Head Tissue / Date : May 18, 2018 >

DUT: Dipole 5GHz; Type: D5GHzV2; Serial: D5GHzV2 - SN:1094

Communication System: CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5300$ MHz; $\sigma = 4.77$ mho/m; $\epsilon_r = 35.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(5.34, 5.34, 5.34); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

5 300 MHz SPC/Area Scan (81x121x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 44.2 mW/g


5 300 MHz SPC/Zoom Scan (8x8x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 88.9 V/m; Power Drift = 0.073 dB

Peak SAR (extrapolated) = 95.2 W/kg

SAR(1 g) = 21.5 mW/g; SAR(10 g) = 6.17 mW/g

Maximum value of SAR (measured) = 41.8 mW/g



0 dB = 41.8mW/g

< 5 600 MHz Head Tissue / Date : May 23, 2018 >

DUT: Dipole 5GHz; Type: D5GHzV2; Serial: D5GHzV2 - SN:1094

Communication System: CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5600$ MHz; $\sigma = 5.05$ mho/m; $\epsilon_r = 34.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(4.74, 4.74, 4.74); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

5 600 MHz SPC/Area Scan (81x121x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 45.9 mW/g


5 600 MHz SPC/Zoom Scan (8x8x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 88.8 V/m; Power Drift = 0.074 dB

Peak SAR (extrapolated) = 96 W/kg

SAR(1 g) = 21.2 mW/g; SAR(10 g) = 5.98 mW/g

Maximum value of SAR (measured) = 41.5 mW/g



0 dB = 41.5mW/g

< 5 800 MHz Head Tissue / Date : May 23, 2018 >

DUT: Dipole 5GHz; Type: D5GHzV2; Serial: D5GHzV2 - SN:1094

Communication System: CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5800 \text{ MHz}$; $\sigma = 5.29 \text{ mho/m}$; $\epsilon_r = 34.3$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(4.68, 4.68, 4.68); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

5 800 MHz SPC/Area Scan (81x121x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Maximum value of SAR (interpolated) = 44.9 mW/g


5 800 MHz SPC/Zoom Scan (8x8x12)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 87.8 V/m; Power Drift = 0.115 dB

Peak SAR (extrapolated) = 97.9 W/kg

SAR(1 g) = 20.8 mW/g; SAR(10 g) = 5.85 mW/g

Maximum value of SAR (measured) = 41.2 mW/g



0 dB = 41.2mW/g

< 5 200 MHz Body Tissue / Date : Jun 01, 2018 >

DUT: Dipole 5GHz; Type: D5GHzV2; Serial: D5GHzV2 - SN:1094

Communication System: CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5200$ MHz; $\sigma = 5.46$ mho/m; $\epsilon_r = 47.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(5.02, 5.02, 5.02); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

5 200 MHz SPC/Area Scan (81x121x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 38.8 mW/g


5 200 MHz SPC/Zoom Scan (8x8x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 73.3 V/m; Power Drift = 0.066 dB

Peak SAR (extrapolated) = 84.2 W/kg

SAR(1 g) = 18.7 mW/g; SAR(10 g) = 5.26 mW/g

Maximum value of SAR (measured) = 36.6 mW/g



0 dB = 36.6mW/g

< 5 300 MHz Body Tissue / Date : May 25, 2018 >

DUT: Dipole 5GHz; Type: D5GHzV2; Serial: D5GHzV2 - SN:1094

Communication System: CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5300$ MHz; $\sigma = 5.55$ mho/m; $\epsilon_r = 47.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(4.86, 4.86, 4.86); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

5 300 MHz SPC/Area Scan (81x121x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 41.4 mW/g


5 300 MHz SPC/Zoom Scan (8x8x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 82.3 V/m; Power Drift = -0.018 dB

Peak SAR (extrapolated) = 89.6 W/kg

SAR(1 g) = 19.9 mW/g; SAR(10 g) = 5.59 mW/g

Maximum value of SAR (measured) = 39 mW/g



0 dB = 39mW/g

< 5 600 MHz Body Tissue / Date : May 30, 2018 >

DUT: Dipole 5GHz; Type: D5GHzV2; Serial: D5GHzV2 - SN:1094

Communication System: CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5600$ MHz; $\sigma = 6$ mho/m; $\epsilon_r = 47.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(4.21, 4.21, 4.21); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

5 600 MHz SPC/Area Scan (81x121x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 44.2 mW/g


5 600 MHz SPC/Zoom Scan (8x8x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 78.9 V/m; Power Drift = 0.051 dB

Peak SAR (extrapolated) = 99.3 W/kg

SAR(1 g) = 21.2 mW/g; SAR(10 g) = 5.84 mW/g

Maximum value of SAR (measured) = 41.9 mW/g



0 dB = 41.9mW/g

< 5 800 MHz Body Tissue / Date : May 31, 2018 >

DUT: Dipole 5GHz; Type: D5GHzV2; Serial: D5GHzV2 - SN:1094

Communication System: CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5800 \text{ MHz}$; $\sigma = 6.22 \text{ mho/m}$; $\epsilon_r = 46.7$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(4.33, 4.33, 4.33); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

5 800 MHz SPC/Area Scan (81x121x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Maximum value of SAR (interpolated) = 43.5 mW/g


5 800 MHz SPC/Zoom Scan (8x8x12)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 70.5 V/m; Power Drift = 0.012 dB

Peak SAR (extrapolated) = 96.1 W/kg

SAR(1 g) = 19.8 mW/g; SAR(10 g) = 5.5 mW/g

Maximum value of SAR (measured) = 40.4 mW/g



0 dB = 40.4mW/g

ANNEX B. SAR TEST PLOTS

< 802.11b_Head Tissue_CH 6_Front_0mm_Main Antenna / Date : May 16, 2018 >

DUT: S4335-AW; Type: Sample; Serial: Not Specified

Communication System: 802.11 b/g/n; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 2437$ MHz; $\sigma = 1.78$ mho/m; $\epsilon_r = 37.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(7.28, 7.28, 7.28); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

802.11b_ch6_1 Mbps_Front_Main/Area Scan (91x51x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.504 mW/g


802.11b_ch6_1 Mbps_Front_Main/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.4 V/m; Power Drift = -0.013 dB

Peak SAR (extrapolated) = 1.07 W/kg

SAR(1 g) = 0.336 mW/g; SAR(10 g) = 0.128 mW/g

Maximum value of SAR (measured) = 0.546 mW/g



< 802.11b_Head Tissue_CH 6_Front_0mm_Aux Antenna / Date : May 16, 2018 >

DUT: S4335-AW; Type: Sample; Serial: Not Specified

Communication System: 802.11 b/g/n; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 2437$ MHz; $\sigma = 1.78$ mho/m; $\epsilon_r = 37.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(7.28, 7.28, 7.28); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

802.11b_ch6_1 Mbps_Front_Aux/Area Scan (51x91x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.542 mW/g


802.11b_ch6_1 Mbps_Front_Aux/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12 V/m; Power Drift = -0.147 dB

Peak SAR (extrapolated) = 0.851 W/kg

SAR(1 g) = 0.296 mW/g; SAR(10 g) = 0.113 mW/g

Maximum value of SAR (measured) = 0.524 mW/g



< 802.11b_Body Tissue_CH 11_Front_0mm_Main Antenna / Date : May 29, 2018 >

DUT: S4335-AW; Type: Sample; Serial: Not Specified

Communication System: 802.11 b/g/n; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 2462$ MHz; $\sigma = 2.02$ mho/m; $\epsilon_r = 51.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(7.28, 7.28, 7.28); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

802.11b_ch11_1 Mbps_Front_Main/Area Scan (91x51x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.468 mW/g


802.11b_ch11_1 Mbps_Front_Main/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14 V/m; Power Drift = -0.029 dB

Peak SAR (extrapolated) = 0.999 W/kg

SAR(1 g) = 0.323 mW/g; SAR(10 g) = 0.106 mW/g

Maximum value of SAR (measured) = 0.547 mW/g



< 802.11b_Body Tissue_CH 6_Front_0mm_Aux Antenna / Date : May 17, 2018 >

DUT: S4335-AW; Type: Sample; Serial: Not Specified

Communication System: 802.11 b/g/n; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 2437$ MHz; $\sigma = 1.98$ mho/m; $\epsilon_r = 50.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(7.28, 7.28, 7.28); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

802.11b_ch6_1 Mbps_Front_Aux/Area Scan (51x91x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.747 mW/g


802.11b_ch6_1 Mbps_Front_Aux/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.5 V/m; Power Drift = -0.066 dB

Peak SAR (extrapolated) = 1.12 W/kg

SAR(1 g) = 0.403 mW/g; SAR(10 g) = 0.155 mW/g

Maximum value of SAR (measured) = 0.739 mW/g



< 802.11n HT20_Head Tissue_CH 44_Front_0mm_Main Antenna / Date : Jun 04, 2018 >

DUT: S4335-AW; Type: Sample; Serial: Not Specified

Communication System: 802.11a; Frequency: 5220 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5220$ MHz; $\sigma = 4.58$ mho/m; $\epsilon_r = 35.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(5.5, 5.5, 5.5); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

802.11n HT20_ch 44_MSC8_Front_Main/Area Scan (101x61x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.181 mW/g


802.11n HT20_ch 44_MSC8_Front_Main/Zoom Scan (9x9x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 4.27 V/m; Power Drift = 0.126 dB

Peak SAR (extrapolated) = 0.569 W/kg

SAR(1 g) = 0.074 mW/g; SAR(10 g) = 0.013 mW/g

Maximum value of SAR (measured) = 0.191 mW/g



0 dB = 0.191mW/g

< 802.11n HT40_Head Tissue_CH 46_Front_0mm_Aux Antenna / Date : Jun 04, 2018 >

DUT: S4335-AW; Type: Sample; Serial: Not Specified

Communication System: 802.11a; Frequency: 5230 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 5230$ MHz; $\sigma = 4.58$ mho/m; $\epsilon_r = 35.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(5.5, 5.5, 5.5); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

802.11n HT40_ch 46_MCS8_Front_Aux/Area Scan (61x111x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.535 mW/g


802.11n HT40_ch 46_MCS8_Front_Aux/Zoom Scan (9x9x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 3.36 V/m; Power Drift = -0.189 dB

Peak SAR (extrapolated) = 1.3 W/kg

SAR(1 g) = 0.209 mW/g; SAR(10 g) = 0.048 mW/g

Maximum value of SAR (measured) = 0.532 mW/g



0 dB = 0.532mW/g

< 802.11ac VHT80_Head Tissue_CH 58_Front_0mm_Main Antenna / Date : May 18, 2018 >

DUT: S4335-AW; Type: Sample; Serial: Not Specified

Communication System: 802.11a; Frequency: 5290 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 5290$ MHz; $\sigma = 4.76$ mho/m; $\epsilon_r = 36$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(5.34, 5.34, 5.34); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

802.11ac VHT80_ch 58_MSC1_Front_Main/Area Scan (101x61x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.528 mW/g


802.11ac VHT80_ch 58_MSC1_Front_Main/Zoom Scan (9x9x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 9.68 V/m; Power Drift = -0.014 dB

Peak SAR (extrapolated) = 1.69 W/kg

SAR(1 g) = 0.232 mW/g; SAR(10 g) = 0.045 mW/g

Maximum value of SAR (measured) = 0.609 mW/g



< 802.11n HT20_Head Tissue_CH 52_Front_0mm_Aux Antenna / Date : May 18, 2018 >

DUT: S4335-AW; Type: Sample; Serial: Not Specified

Communication System: 802.11a; Frequency: 5260 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5260$ MHz; $\sigma = 4.73$ mho/m; $\epsilon_r = 36$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(5.34, 5.34, 5.34); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

802.11n HT20_ch 52_MCS10_Front_Aux/Area Scan (61x111x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.336 mW/g


802.11n HT20_ch 52_MCS10_Front_Aux/Zoom Scan (9x9x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 6.04 V/m; Power Drift = 0.079 dB

Peak SAR (extrapolated) = 1.34 W/kg

SAR(1 g) = 0.211 mW/g; SAR(10 g) = 0.049 mW/g

Maximum value of SAR (measured) = 0.564 mW/g



0 dB = 0.564mW/g

< 802.11a_Head Tissue_CH 140_Front_0mm_Main Antenna / Date : May 23, 2018 >

DUT: S4335-AW; Type: Sample; Serial: Not Specified

Communication System: 802.11a; Frequency: 5700 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5700$ MHz; $\sigma = 5.17$ mho/m; $\epsilon_r = 34.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(4.74, 4.74, 4.74); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

802.11a_ch 140_6 Mbps_Front_Main/Area Scan (101x61x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.776 mW/g


802.11a_ch 140_6 Mbps_Front_Main/Zoom Scan (9x9x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 9.45 V/m; Power Drift = -0.021 dB

Peak SAR (extrapolated) = 2.28 W/kg

SAR(1 g) = 0.296 mW/g; SAR(10 g) = 0.062 mW/g

Maximum value of SAR (measured) = 0.807 mW/g



0 dB = 0.807mW/g

< 802.11ac VHT80_Head Tissue_CH 106_Front_0mm_Aux Antenna / Date : May 23, 2018 >

DUT: S4335-AW; Type: Sample; Serial: Not Specified

Communication System: 802.11a; Frequency: 5530 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 5530$ MHz; $\sigma = 4.97$ mho/m; $\epsilon_r = 34.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(4.82, 4.82, 4.82); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

802.11ac VHT80_ch 106_MCS0_Front_Aux/Area Scan (61x111x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.426 mW/g


802.11ac VHT80_ch 106_MCS0_Front_Aux/Zoom Scan (9x9x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 5.1 V/m; Power Drift = 0.103 dB

Peak SAR (extrapolated) = 1.63 W/kg

SAR(1 g) = 0.230 mW/g; SAR(10 g) = 0.050 mW/g

Maximum value of SAR (measured) = 0.633 mW/g



< 802.11ac VHT20_Head Tissue_CH 149_Front_0mm_Main Antenna / Date : May 23, 2018 >

DUT: S4335-AW; Type: Sample; Serial: Not Specified

Communication System: 802.11a; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 5745$ MHz; $\sigma = 5.22$ mho/m; $\epsilon_r = 34.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(4.68, 4.68, 4.68); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

802.11ac VHT20_ch 149_MCS6_Front_Main/Area Scan (101x61x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.355 mW/g


802.11ac VHT20_ch 149_MCS6_Front_Main/Zoom Scan (9x9x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 6.14 V/m; Power Drift = 0.056 dB

Peak SAR (extrapolated) = 1.45 W/kg

SAR(1 g) = 0.125 mW/g; SAR(10 g) = 0.029 mW/g

Maximum value of SAR (measured) = 0.345 mW/g



< 802.11a_Head Tissue_CH 165_Front_0mm_Aux Antenna / Date : May 23, 2018 >

DUT: S4335-AW; Type: Sample; Serial: Not Specified

Communication System: 802.11a; Frequency: 5825 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 5825$ MHz; $\sigma = 5.32$ mho/m; $\epsilon_r = 34.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(4.68, 4.68, 4.68); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

802.11a_ch 165_9 Mbps_Front_Aux/Area Scan (61x111x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.197 mW/g


802.11a_ch 165_9 Mbps_Front_Aux/Zoom Scan (9x9x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 4.46 V/m; Power Drift = 0.098 dB

Peak SAR (extrapolated) = 0.491 W/kg

SAR(1 g) = 0.098 mW/g; SAR(10 g) = 0.024 mW/g

Maximum value of SAR (measured) = 0.260 mW/g



< 802.11n HT20_Body Tissue_CH 44_Bottom_0mm_Main Antenna / Date : Jun 01, 2018 >

DUT: S4335-AW; Type: Sample; Serial: Not Specified

Communication System: 802.11a; Frequency: 5220 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5220$ MHz; $\sigma = 5.48$ mho/m; $\epsilon_r = 47.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(5.02, 5.02, 5.02); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

802.11n HT20_ch 44_MSC8_Bottom_Main/Area Scan (51x121x1): Measurement grid:
dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.442 mW/g


802.11n HT20_ch 44_MSC8_Bottom_Main/Zoom Scan (9x9x12)/Cube 0: Measurement grid:
dx=4mm, dy=4mm, dz=2mm

Reference Value = 2.56 V/m; Power Drift = 0.148 dB

Peak SAR (extrapolated) = 4.13 W/kg

SAR(1 g) = 0.324 mW/g; SAR(10 g) = 0.044 mW/g

Maximum value of SAR (measured) = 0.894 mW/g



0 dB = 0.894mW/g

< 802.11n HT40_Body Tissue_CH 46_Right_0 mm_Aux Antenna / Date : Jun 01, 2018 >

DUT: S4335-AW; Type: Sample; Serial: Not Specified

Communication System: 802.11a; Frequency: 5230 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 5230$ MHz; $\sigma = 5.49$ mho/m; $\epsilon_r = 47.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(5.02, 5.02, 5.02); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

802.11n HT40_ch 46_MCS8_Right_Aux/Area Scan (51x111x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.732 mW/g


802.11n HT40_ch 46_MCS8_Right_Aux/Zoom Scan (9x9x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 3.39 V/m; Power Drift = -0.174 dB

Peak SAR (extrapolated) = 5.6 W/kg

SAR(1 g) = 0.541 mW/g; SAR(10 g) = 0.076 mW/g

Maximum value of SAR (measured) = 1.59 mW/g



0 dB = 1.59mW/g

< 802.11ac VHT80_Body Tissue_CH 58_Bottom_0mm_Main Antenna / Date : May 25, 2018 >

DUT: S4335-AW; Type: Sample; Serial: Not Specified

Communication System: 802.11a; Frequency: 5290 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 5290$ MHz; $\sigma = 5.53$ mho/m; $\epsilon_r = 47.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(4.86, 4.86, 4.86); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

802.11ac VHT80_ch 58_MSC1_Bottom_Main/Area Scan (51x121x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.542 mW/g


802.11ac VHT80_ch 58_MSC1_Bottom_Main/Zoom Scan (9x9x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 2.76 V/m; Power Drift = -0.052 dB

Peak SAR (extrapolated) = 4.88 W/kg

SAR(1 g) = 0.401 mW/g; SAR(10 g) = 0.059 mW/g

Maximum value of SAR (measured) = 1.12 mW/g



< 802.11n HT20_Body Tissue_CH 64_Right_0mm_Aux Antenna / Date : May 25, 2018 >

DUT: S4335-AW; Type: Sample; Serial: Not Specified

Communication System: 802.11a; Frequency: 5320 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5320$ MHz; $\sigma = 5.56$ mho/m; $\epsilon_r = 47.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(4.86, 4.86, 4.86); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

802.11n HT20_ch 64_MCS10_Right_Aux/Area Scan (51x111x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 1.19 mW/g


802.11n HT20_ch 64_MCS10_Right_Aux/Zoom Scan (9x9x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 3.46 V/m; Power Drift = -0.00906 dB

Peak SAR (extrapolated) = 4.36 W/kg

SAR(1 g) = 0.407 mW/g; SAR(10 g) = 0.059 mW/g

Maximum value of SAR (measured) = 1.38 mW/g



0 dB = 1.38mW/g

< 802.11a_Body Tissue_CH 140_Bottom_0mm_Main Antenna / Date : May 30, 2018 >

DUT: S4335-AW; Type: Sample; Serial: Not Specified

Communication System: 802.11a; Frequency: 5700 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5700 \text{ MHz}$; $\sigma = 6.13 \text{ mho/m}$; $\epsilon_r = 47.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(4.33, 4.33, 4.33); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

802.11a_ch 140_6 Mbps_Bottom_Main/Area Scan (51x121x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Maximum value of SAR (interpolated) = 0.835 mW/g


802.11a_ch 140_6 Mbps_Bottom_Main/Zoom Scan (9x9x12)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 3.9 V/m; Power Drift = 0.157 dB

Peak SAR (extrapolated) = 4.56 W/kg

SAR(1 g) = 0.443 mW/g; SAR(10 g) = 0.072 mW/g

Maximum value of SAR (measured) = 1.33 mW/g



0 dB = 1.33mW/g

< 802.11ac VHT80_Body Tissue_CH 106_Right_0mm_Aux Antenna / Date : May 30, 2018 >

DUT: S4335-AW; Type: Sample; Serial: Not Specified

Communication System: 802.11a; Frequency: 5530 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 5530$ MHz; $\sigma = 5.91$ mho/m; $\epsilon_r = 47.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(4.34, 4.34, 4.34); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

802.11ac VHT80_ch 106_MCS0_Right_Aux/Area Scan (51x111x1): Measurement grid:
dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.849 mW/g


802.11ac VHT80_ch 106_MCS0_Right_Aux/Zoom Scan (9x9x12)/Cube 0: Measurement grid:
dx=4mm, dy=4mm, dz=2mm

Reference Value = 5.04 V/m; Power Drift = -0.096 dB

Peak SAR (extrapolated) = 2.91 W/kg

SAR(1 g) = 0.264 mW/g; SAR(10 g) = 0.055 mW/g

Maximum value of SAR (measured) = 0.972 mW/g



< 802.11ac VHT20_Body Tissue_CH 149_Bottom_0mm_Main Antenna / Date : May 31, 2018 >

DUT: S4335-AW; Type: Sample; Serial: Not Specified

Communication System: 802.11a; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 5745$ MHz; $\sigma = 6.16$ mho/m; $\epsilon_r = 47$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(4.33, 4.33, 4.33); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

802.11ac VHT20_ch 149_MCS6_Bottom_Main/Area Scan (51x121x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.482 mW/g


802.11ac VHT20_ch 149_MCS6_Bottom_Main/Zoom Scan (9x9x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 4.38 V/m; Power Drift = 0.139 dB

Peak SAR (extrapolated) = 3.17 W/kg

SAR(1 g) = 0.323 mW/g; SAR(10 g) = 0.053 mW/g

Maximum value of SAR (measured) = 1.28 mW/g



< 802.11a_Body Tissue_CH 165_Right_0mm_Aux Antenna / Date : May 31, 2018 >

DUT: S4335-AW; Type: Sample; Serial: Not Specified

Communication System: 802.11a; Frequency: 5825 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 5825$ MHz; $\sigma = 6.26$ mho/m; $\epsilon_r = 46.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3832; ConvF(4.33, 4.33, 4.33); Calibrated: 2018-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn663; Calibrated: 2017-07-19
- Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1030
- Measurement SW: DASY5, V5.0 Build 125; SEMCAD X Version 13.4 Build 125

802.11a_ch 165_9 Mbps_Right_Aux/Area Scan (51x111x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.858 mW/g


802.11a_ch 165_9 Mbps_Right_Aux/Zoom Scan (9x9x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 3.43 V/m; Power Drift = 0.148 dB

Peak SAR (extrapolated) = 3.79 W/kg

SAR(1 g) = 0.352 mW/g; SAR(10 g) = 0.055 mW/g

Maximum value of SAR (measured) = 1.06 mW/g




ANNEX C. PHOTOGRAPHS

< System Verification >




< 2 450 MHz >




< 5 GHz >


< Liquid Depth >



< 2 450 MHz Head >



< 2 450 MHz Body >




< 5 GHz Head >




< 5 GHz Body >

ANNEX D. ANTENNA INFORMATION

< Antenna Location >




< Antenna Data Sheet >



Frequency	Efficiency	Average Gain			Max Gain		
		Ver	Hor	Total	Ver	Hor	Total
2400.000000 MHz	26.3 %	-19.6 dBi	-6.0 dBi	-5.8 dBi	-10.3 dBi	0.3 dBi	0.4 dBi
2450.000000 MHz	44.1 %	-17.8 dBi	-3.7 dBi	-3.6 dBi	-8.2 dBi	2.9 dBi	2.9 dBi
2500.000000 MHz	35.2 %	-18.7 dBi	-4.7 dBi	-4.5 dBi	-9.9 dBi	1.9 dBi	1.9 dBi
5200.000000 MHz	56.8 %	-12.2 dBi	-2.9 dBi	-2.5 dBi	-0.3 dBi	5.3 dBi	5.6 dBi
5300.000000 MHz	86.0 %	-11.3 dBi	-1.0 dBi	-0.7 dBi	1.4 dBi	7.1 dBi	7.3 dBi
5400.000000 MHz	61.9 %	-12.9 dBi	-2.5 dBi	-2.1 dBi	0.1 dBi	5.7 dBi	5.9 dBi
5500.000000 MHz	42.5 %	-14.7 dBi	-4.1 dBi	-3.7 dBi	-1.3 dBi	4.0 dBi	4.3 dBi
5600.000000 MHz	36.6 %	-14.9 dBi	-4.8 dBi	-4.4 dBi	-1.5 dBi	3.1 dBi	3.5 dBi
5700.000000 MHz	47.6 %	-12.2 dBi	-3.8 dBi	-3.2 dBi	0.0 dBi	4.3 dBi	4.9 dBi
5800.000000 MHz	29.8 %	-13.5 dBi	-6.0 dBi	-5.3 dBi	-2.5 dBi	1.9 dBi	2.1 dBi

< Main Antenna >



Frequency	Efficiency	Average Gain			Max Gain		
		Ver	Hor	Total	Ver	Hor	Total
2400.000000 MHz	14.6 %	-12.1 dBi	-10.8 dBi	-8.3 dBi	-5.4 dBi	-1.3 dBi	-0.1 dBi
2450.000000 MHz	21.8 %	-10.2 dBi	-9.1 dBi	-6.6 dBi	-3.5 dBi	0.8 dBi	2.0 dBi
2500.000000 MHz	19.7 %	-10.7 dBi	-9.5 dBi	-7.1 dBi	-3.5 dBi	0.3 dBi	1.5 dBi
5200.000000 MHz	42.1 %	-8.0 dBi	-5.8 dBi	-3.8 dBi	0.1 dBi	3.3 dBi	3.9 dBi
5300.000000 MHz	30.6 %	-9.5 dBi	-7.1 dBi	-5.1 dBi	-3.7 dBi	2.2 dBi	2.8 dBi
5400.000000 MHz	40.4 %	-8.3 dBi	-5.9 dBi	-3.9 dBi	-2.0 dBi	3.5 dBi	4.2 dBi
5500.000000 MHz	26.2 %	-9.9 dBi	-8.0 dBi	-5.8 dBi	-3.1 dBi	1.3 dBi	2.3 dBi
5600.000000 MHz	20.6 %	-10.5 dBi	-9.3 dBi	-6.9 dBi	-3.6 dBi	0.0 dBi	1.0 dBi
5700.000000 MHz	20.5 %	-10.7 dBi	-9.2 dBi	-6.9 dBi	-1.6 dBi	1.7 dBi	3.0 dBi
5800.000000 MHz	26.3 %	-9.8 dBi	-8.0 dBi	-5.8 dBi	1.4 dBi	2.8 dBi	4.3 dBi

< Aux Antenna >

ANNEX E. PROBE AND DIPOLE CALIBRATION CERTIFICATES

< E-Field Probe : EX3DV4 – SN 3716 >

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client: **Onetech (Dymstec)** Certificate No: **EX3-3832_Feb18**

CALIBRATION CERTIFICATE

Object: **EX3DV4 - SN:3832**

Calibration procedure(s): **QA CAL-01.v9, QA CAL-12.v9, QA CAL-14.v4, QA CAL-23.v5,
QA CAL-25.v6
Calibration procedure for dosimetric E-field probes**

Calibration date: **February 21, 2018**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (MATE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02525)	Apr-18
Reference 20 dB Attenuator	SN: 55277 (20x)	07-Apr-17 (No. 217-02528)	Apr-18
Reference Probe ES3DV2	SN: 3013	30-Dec-17 (No. ES3-3013, Dec17)	Dec-18
DAE4	SN: 660	21-Dec-17 (No. DAE4-660, Dec17)	Dec-18
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
RF generator HP 8648C	SN: US3842U01700	04-Aug-99 (in house check Jun-16)	In house check: Jun-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18

Calibrated by: **Jeton Kasrati** Function: **Laboratory Technician** Signature: 

Approved by: **Katja Pokovic** Function: **Technical Manager** Signature: 

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Issued: February 22, 2018

Certificate No: EX3-3832_Feb18

Page 1 of 39

Calibration Laboratory of
Schmid & Partner
Engineering AG
 Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization ϕ	ϕ rotation around probe axis
Polarization θ	θ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\theta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}: Assessed for E-field polarization $\theta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z} = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; V_R_{x,y,z}: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. V_R is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

Certificate No: EX3-3832_Feb18

Page 2 of 39

EX3DV4 – SN:3832

February 21, 2018

Probe EX3DV4

SN:3832

Manufactured: November 7, 2011
Calibrated: February 21, 2018

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

EX3DV4-- SN:3832

February 21, 2018

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3832

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^{2/3}$) ^A	0.44	0.43	0.57	$\pm 10.1 \%$
DCP (mV) ^B	96.4	104.5	97.9	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	144.7	$\pm 3.5 \%$
		Y	0.0	0.0	1.0		147.9	
		Z	0.0	0.0	1.0		132.6	

Note: For details on UID parameters see Appendix.

Sensor Model Parameters

	C1 fF	C2 fF	α V^{-1}	T1 $\text{ms}\cdot\text{V}^{-2}$	T2 $\text{ms}\cdot\text{V}^{-1}$	T3 ms	T4 V^{-2}	T5 V^{-1}	T6
X	50.26	372.8	35.32	18.56	0.744	5.096	0.931	0.467	1.007
Y	46.38	353.8	36.96	15.73	0.988	5.079	0.000	0.653	1.01
Z	48.64	356.8	34.59	21.38	0.412	5.100	0.980	0.392	1.009

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter; uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

EX3DV4- SN:3832

February 21, 2018

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3832

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^H (mm)	Unc (k=2)
150	52.3	0.76	11.52	11.52	11.52	0.00	1.00	± 13.3 %
300	45.3	0.87	11.16	11.16	11.16	0.08	1.20	± 13.3 %
450	43.5	0.87	10.51	10.51	10.51	0.15	1.30	± 13.3 %
750	41.9	0.89	10.23	10.23	10.23	0.48	0.90	± 12.0 %
835	41.5	0.90	9.54	9.54	9.54	0.47	0.88	± 12.0 %
1750	40.1	1.37	8.36	8.36	8.36	0.38	0.86	± 12.0 %
1950	40.0	1.40	7.96	7.96	7.96	0.43	0.82	± 12.0 %
2450	39.2	1.80	7.28	7.28	7.28	0.35	0.80	± 12.0 %
5200	36.0	4.66	5.50	5.50	5.50	0.30	1.80	± 13.1 %
5300	35.9	4.76	5.34	5.34	5.34	0.30	1.80	± 13.1 %
5500	35.6	4.96	4.82	4.82	4.82	0.40	1.80	± 13.1 %
5600	35.5	5.07	4.74	4.74	4.74	0.40	1.80	± 13.1 %
5800	35.3	5.27	4.68	4.68	4.68	0.40	1.80	± 13.1 %

^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4- SN:3832

February 21, 2018

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3832

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^c	Relative Permittivity ^f	Conductivity (S/m) ^f	ConvF X	ConvF Y	ConvF Z	Alpha ^g	Depth ^g (mm)	Unc (k=2)
150	61.9	0.80	11.02	11.02	11.02	0.00	1.00	± 13.3 %
300	58.2	0.92	10.69	10.69	10.69	0.05	1.20	± 13.3 %
450	56.7	0.94	10.56	10.56	10.56	0.09	1.30	± 13.3 %
750	55.5	0.96	9.38	9.38	9.38	0.35	1.02	± 12.0 %
835	55.2	0.97	9.15	9.15	9.15	0.46	0.80	± 12.0 %
1750	53.4	1.49	7.78	7.78	7.78	0.39	0.80	± 12.0 %
1950	53.3	1.52	7.72	7.72	7.72	0.45	0.80	± 12.0 %
2450	52.7	1.95	7.28	7.28	7.28	0.33	0.80	± 12.0 %
5200	49.0	5.30	5.02	5.02	5.02	0.35	1.90	± 13.1 %
5300	48.9	5.42	4.86	4.86	4.86	0.35	1.90	± 13.1 %
5500	48.6	5.65	4.34	4.34	4.34	0.40	1.90	± 13.1 %
5600	48.5	5.77	4.21	4.21	4.21	0.40	1.90	± 13.1 %
5800	48.2	6.00	4.33	4.33	4.33	0.40	1.90	± 13.1 %

^c Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.


^f At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^g Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4- SN:3832

February 21, 2018

Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

EX3DV4- SN:3832

February 21, 2018

Receiving Pattern (ϕ), $\theta = 0^\circ$





Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

EX3DV4- SN:3832

February 21, 2018

Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell, $f_{\text{eval}} = 1900 \text{ MHz}$)



Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)


Certificate No: EX3-3832_Feb18

Page 9 of 39


EX3DV4- SN:3832

February 21, 2018

Conversion Factor Assessment



Deviation from Isotropy in Liquid Error (ϕ , θ), $f = 900 \text{ MHz}$



Certificate No: EX3-3832_Feb18

Page 10 of 39

EX3DV4- SN:3832

February 21, 2018

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3832

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	54.2
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

< Dipole Antenna : D2450V2 – SN 923 >

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client **Onetech (Dymstec)**

Certificate No: D2450V2-923_Nov17

CALIBRATION CERTIFICATE																																																											
Object	D2450V2 - SN:923																																																										
Calibration procedure(s)	QA CAL-05.v9 Calibration procedure for dipole validation kits above 700 MHz																																																										
Calibration date:	November 21, 2017																																																										
This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate. All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%. Calibration Equipment used (M&TE critical for calibration) <table border="1"> <thead> <tr> <th>Primary Standards</th> <th>ID #</th> <th>Cal Date (Certificate No.)</th> <th>Scheduled Calibration</th> </tr> </thead> <tbody> <tr> <td>Power meter NRP</td> <td>SN: 104778</td> <td>04-Apr-17 (No. 217-02521/02522)</td> <td>Apr-18</td> </tr> <tr> <td>Power sensor NRP-Z91</td> <td>SN: 103244</td> <td>04-Apr-17 (No. 217-02521)</td> <td>Apr-18</td> </tr> <tr> <td>Power sensor NRP-Z91</td> <td>SN: 103245</td> <td>04-Apr-17 (No. 217-02522)</td> <td>Apr-18</td> </tr> <tr> <td>Reference 20 dB Attenuator</td> <td>SN: 5058 (20k)</td> <td>07-Apr-17 (No. 217-02528)</td> <td>Apr-18</td> </tr> <tr> <td>Type-N mismatch combination</td> <td>SN: 5047.2 / 06327</td> <td>07-Apr-17 (No. 217-02529)</td> <td>Apr-18</td> </tr> <tr> <td>Reference Probe EX3DV4</td> <td>SN: 7349</td> <td>31-May-17 (No. EX3-7349_May17)</td> <td>May-18</td> </tr> <tr> <td>DAE4</td> <td>SN: 601</td> <td>26-Oct-17 (No. DAE4-601_Oct17)</td> <td>Oct-18</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>Secondary Standards</th> <th>ID #</th> <th>Check Date (in house)</th> <th>Scheduled Check</th> </tr> </thead> <tbody> <tr> <td>Power meter EPM-442A</td> <td>SN: GB37480704</td> <td>07-Oct-15 (in house check Oct-16)</td> <td>In house check: Oct-18</td> </tr> <tr> <td>Power sensor HP 8481A</td> <td>SN: US37292763</td> <td>07-Oct-15 (in house check Oct-16)</td> <td>In house check: Oct-18</td> </tr> <tr> <td>Power sensor HP 8481A</td> <td>SN: MY41092317</td> <td>07-Oct-15 (in house check Oct-16)</td> <td>In house check: Oct-18</td> </tr> <tr> <td>RF generator R&S SMT-06</td> <td>SN: 100972</td> <td>15-Jun-15 (in house check Oct-16)</td> <td>In house check: Oct-18</td> </tr> <tr> <td>Network Analyzer HP 8753E</td> <td>SN: US37390585</td> <td>18-Oct-01 (in house check Oct-17)</td> <td>In house check: Oct-18</td> </tr> </tbody> </table>				Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration	Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18	Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18	Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02522)	Apr-18	Reference 20 dB Attenuator	SN: 5058 (20k)	07-Apr-17 (No. 217-02528)	Apr-18	Type-N mismatch combination	SN: 5047.2 / 06327	07-Apr-17 (No. 217-02529)	Apr-18	Reference Probe EX3DV4	SN: 7349	31-May-17 (No. EX3-7349_May17)	May-18	DAE4	SN: 601	26-Oct-17 (No. DAE4-601_Oct17)	Oct-18	Secondary Standards	ID #	Check Date (in house)	Scheduled Check	Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18	Power sensor HP 8481A	SN: US37292763	07-Oct-15 (in house check Oct-16)	In house check: Oct-18	Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18	RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18	Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18
Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration																																																								
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18																																																								
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18																																																								
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02522)	Apr-18																																																								
Reference 20 dB Attenuator	SN: 5058 (20k)	07-Apr-17 (No. 217-02528)	Apr-18																																																								
Type-N mismatch combination	SN: 5047.2 / 06327	07-Apr-17 (No. 217-02529)	Apr-18																																																								
Reference Probe EX3DV4	SN: 7349	31-May-17 (No. EX3-7349_May17)	May-18																																																								
DAE4	SN: 601	26-Oct-17 (No. DAE4-601_Oct17)	Oct-18																																																								
Secondary Standards	ID #	Check Date (in house)	Scheduled Check																																																								
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18																																																								
Power sensor HP 8481A	SN: US37292763	07-Oct-15 (in house check Oct-16)	In house check: Oct-18																																																								
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18																																																								
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18																																																								
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18																																																								
Calibrated by:	Name Michael Weber	Function Laboratory Technician	Signature 																																																								
Approved by:	Katja Pokovic	Technical Manager																																																									
This calibration certificate shall not be reproduced except in full without written approval of the laboratory. Issued: November 21, 2017																																																											

Certificate No: D2450V2-923_Nov17

Page 1 of 8

Calibration Laboratory of
Schmid & Partner
Engineering AG
 Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2450 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.2	1.80 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	37.8 $\pm$ 6 %	1.86 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	13.3 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	51.9 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	6.16 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.3 W/kg $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	52.7	1.95 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	51.5 $\pm$ 6 %	2.02 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	13.1 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	51.3 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	6.08 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	24.0 W/kg $\pm$ 16.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	$54.7 \Omega + 1.4 j\Omega$
Return Loss	- 26.7 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	$50.2 \Omega + 4.1 j\Omega$
Return Loss	- 27.7 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.158 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	September 26, 2013

DASY5 Validation Report for Head TSL

Date: 21.11.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 923

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.86$ S/m; $\epsilon_r = 37.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.12, 8.12, 8.12); Calibrated: 31.05.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 114.3 V/m; Power Drift = -0.04 dB


Peak SAR (extrapolated) = 27.0 W/kg

SAR(1 g) = 13.3 W/kg; SAR(10 g) = 6.16 W/kg

Maximum value of SAR (measured) = 22.0 W/kg



Impedance Measurement Plot for Head TSL



DASY5 Validation Report for Body TSL

Date: 21.11.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 923

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 2.02$ S/m; $\epsilon_r = 51.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.1, 8.1, 8.1); Calibrated: 31.05.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 106.8 V/m; Power Drift = -0.05 dB


Peak SAR (extrapolated) = 25.9 W/kg

SAR(1 g) = 13.1 W/kg; SAR(10 g) = 6.08 W/kg

Maximum value of SAR (measured) = 20.7 W/kg



Impedance Measurement Plot for Body TSL



< Dipole Antenna : D5GHzV2 – SN 1094 >

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
S Service suisse d'étalonnage
C Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **Onetech (Dymstec)**

Certificate No: **D5GHzV2-1094_Nov17**

CALIBRATION CERTIFICATE

Object **D5GHzV2 - SN:1094**

Calibration procedure(s) **QA CAL-22.v2
Calibration procedure for dipole validation kits between 3-6 GHz**

Calibration date: **November 22, 2017**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02522)	Apr-18
Reference 20 dB Attenuator	SN: 5058 (20k)	07-Apr-17 (No. 217-02528)	Apr-18
Type-N mismatch combination	SN: 5047.2 / 06327	07-Apr-17 (No. 217-02529)	Apr-18
Reference Probe EX3DV4	SN: 3503	31-Dec-16 (No. EX3-3503_Dec16)	Dec-17
DAE4	SN: 601	26-Oct-17 (No. DAE4-601_Oct17)	Oct-18
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18

	Name	Function	Signature
Calibrated by:	Michael Weber	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: November 22, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: D5GHzV2-1094_Nov17

Page 1 of 16

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
S Service suisse d'étalonnage
C Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom V5.0	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy = 4.0 mm, dz = 1.4 mm	Graded Ratio = 1.4 (Z direction)
Frequency	5200 MHz $\pm$ 1 MHz 5300 MHz $\pm$ 1 MHz 5500 MHz $\pm$ 1 MHz 5600 MHz $\pm$ 1 MHz 5800 MHz $\pm$ 1 MHz	

Head TSL parameters at 5200 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	36.0	4.66 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	35.8 $\pm$ 6 %	4.49 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5200 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.01 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	79.9 W/kg $\pm$ 19.9 % (k=2)
SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.29 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	22.8 W/kg $\pm$ 19.5 % (k=2)

Head TSL parameters at 5300 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.9	4.76 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	35.6 ± 6 %	4.59 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5300 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.35 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	83.3 W / kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.38 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	23.7 W/kg ± 19.5 % (k=2)

Head TSL parameters at 5500 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.6	4.96 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	35.4 ± 6 %	4.78 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5500 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.46 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	84.4 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.40 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	23.9 W/kg ± 19.5 % (k=2)

Head TSL parameters at 5600 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.5	5.07 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	35.2 ± 6 %	4.89 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5600 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.61 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	85.8 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.45 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.4 W/kg ± 19.5 % (k=2)

Head TSL parameters at 5800 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.3	5.27 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	34.9 ± 6 %	5.10 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5800 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.27 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	82.4 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.34 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	23.3 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5200 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	49.0	5.30 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	47.0 ± 6 %	5.41 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5200 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.64 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	75.8 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.13 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	21.1 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5300 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.9	5.42 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	46.8 ± 6 %	5.54 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5300 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.86 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	77.9 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.20 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	21.8 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5500 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.6	5.65 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	46.4 ± 6 %	5.80 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5500 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	8.28 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	82.1 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.28 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	22.5 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5600 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.5	5.77 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	46.3 ± 6 %	5.94 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5600 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	8.30 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	82.3 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.31 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	22.8 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5800 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.2	6.00 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	45.9 ± 6 %	6.22 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	-----	-----

SAR result with Body TSL at 5800 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	8.03 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	79.6 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.22 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	21.9 W/kg ± 19.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL at 5200 MHz

Impedance, transformed to feed point	49.0 Ω - 10.8 j Ω
Return Loss	- 19.2 dB

Antenna Parameters with Head TSL at 5300 MHz

Impedance, transformed to feed point	48.5 Ω - 9.3 j Ω
Return Loss	- 20.4 dB

Antenna Parameters with Head TSL at 5500 MHz

Impedance, transformed to feed point	52.3 Ω - 8.2 j Ω
Return Loss	- 21.6 dB

Antenna Parameters with Head TSL at 5600 MHz

Impedance, transformed to feed point	55.1 Ω - 6.7 j Ω
Return Loss	- 22.0 dB

Antenna Parameters with Head TSL at 5800 MHz

Impedance, transformed to feed point	55.5 Ω - 8.2 j Ω
Return Loss	- 20.6 dB

Antenna Parameters with Body TSL at 5200 MHz

Impedance, transformed to feed point	48.4 Ω - 9.7 j Ω
Return Loss	- 20.0 dB

Antenna Parameters with Body TSL at 5300 MHz

Impedance, transformed to feed point	48.7 Ω - 7.0 j Ω
Return Loss	- 22.9 dB

Antenna Parameters with Body TSL at 5500 MHz

Impedance, transformed to feed point	52.1 Ω - 6.1 j Ω
Return Loss	- 24.0 dB

Antenna Parameters with Body TSL at 5600 MHz

Impedance, transformed to feed point	55.5 Ω - 5.6 j Ω
Return Loss	- 22.6 dB

Antenna Parameters with Body TSL at 5800 MHz

Impedance, transformed to feed point	56.1 Ω - 7.5 j Ω
Return Loss	- 20.8 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.203 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	September 24, 2010

DASY5 Validation Report for Head TSL

Date: 22.11.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1094

Communication System: UID 0 - CW; Frequency: 5200 MHz, Frequency: 5300 MHz, Frequency: 5500 MHz, Frequency: 5600 MHz, Frequency: 5800 MHz

Medium parameters used: $f = 5200$ MHz; $\sigma = 4.49$ S/m; $\epsilon_r = 35.8$; $\rho = 1000$ kg/m³,

Medium parameters used: $f = 5300$ MHz; $\sigma = 4.59$ S/m; $\epsilon_r = 35.6$; $\rho = 1000$ kg/m³,

Medium parameters used: $f = 5500$ MHz; $\sigma = 4.78$ S/m; $\epsilon_r = 35.4$; $\rho = 1000$ kg/m³,

Medium parameters used: $f = 5600$ MHz; $\sigma = 4.89$ S/m; $\epsilon_r = 35.2$; $\rho = 1000$ kg/m³,

Medium parameters used: $f = 5800$ MHz; $\sigma = 5.1$ S/m; $\epsilon_r = 34.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.76, 5.76, 5.76); Calibrated: 31.12.2016, ConvF(5.35, 5.35, 5.35); Calibrated: 31.12.2016, ConvF(5.2, 5.2, 5.2); Calibrated: 31.12.2016, ConvF(5.09, 5.09, 5.09); Calibrated: 31.12.2016, ConvF(5.01, 5.01, 5.01); Calibrated: 31.12.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5200 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 72.21 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 29.4 W/kg

SAR(1 g) = 8.01 W/kg; SAR(10 g) = 2.29 W/kg

Maximum value of SAR (measured) = 18.6 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5300 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 73.13 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 30.2 W/kg


SAR(1 g) = 8.35 W/kg; SAR(10 g) = 2.38 W/kg

Maximum value of SAR (measured) = 19.2 W/kg


Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5500 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 71.97 V/m; Power Drift = -0.03 dB
Peak SAR (extrapolated) = 33.4 W/kg
SAR(1 g) = 8.46 W/kg; SAR(10 g) = 2.4 W/kg
Maximum value of SAR (measured) = 20.2 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 72.74 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 34.1 W/kg
SAR(1 g) = 8.61 W/kg; SAR(10 g) = 2.45 W/kg
Maximum value of SAR (measured) = 20.6 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5800 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 70.28 V/m; Power Drift = -0.09 dB
Peak SAR (extrapolated) = 34.1 W/kg
SAR(1 g) = 8.27 W/kg; SAR(10 g) = 2.34 W/kg
Maximum value of SAR (measured) = 20.1 W/kg



Impedance Measurement Plot for Head TSL



DASY5 Validation Report for Body TSL

Date: 21.11.2017

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1094

Communication System: UID 0 - CW; Frequency: 5200 MHz, Frequency: 5300 MHz, Frequency: 5500 MHz, Frequency: 5600 MHz, Frequency: 5800 MHz

Medium parameters used: $f = 5200 \text{ MHz}$; $\sigma = 5.41 \text{ S/m}$; $\epsilon_r = 47$; $\rho = 1000 \text{ kg/m}^3$,

Medium parameters used: $f = 5300 \text{ MHz}$; $\sigma = 5.54 \text{ S/m}$; $\epsilon_r = 46.8$; $\rho = 1000 \text{ kg/m}^3$,

Medium parameters used: $f = 5500 \text{ MHz}$; $\sigma = 5.8 \text{ S/m}$; $\epsilon_r = 46.4$; $\rho = 1000 \text{ kg/m}^3$,

Medium parameters used: $f = 5600 \text{ MHz}$; $\sigma = 5.94 \text{ S/m}$; $\epsilon_r = 46.3$; $\rho = 1000 \text{ kg/m}^3$,

Medium parameters used: $f = 5800 \text{ MHz}$; $\sigma = 6.22 \text{ S/m}$; $\epsilon_r = 45.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.29, 5.29, 5.29); Calibrated: 31.12.2016, ConvF(5.04, 5.04, 5.04); Calibrated: 31.12.2016, ConvF(4.62, 4.62, 4.62); Calibrated: 31.12.2016, ConvF(4.57, 4.57, 4.57); Calibrated: 31.12.2016, ConvF(4.48, 4.48, 4.48); Calibrated: 31.12.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5200 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$

Reference Value = 65.18 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 29.5 W/kg

SAR(1 g) = 7.64 W/kg; SAR(10 g) = 2.13 W/kg

Maximum value of SAR (measured) = 17.6 W/kg

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5300 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$

Reference Value = 65.21 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 30.9 W/kg


SAR(1 g) = 7.86 W/kg; SAR(10 g) = 2.2 W/kg

Maximum value of SAR (measured) = 18.4 W/kg


Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5500 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 66.30 V/m; Power Drift = -0.09 dB
Peak SAR (extrapolated) = 34.7 W/kg
SAR(1 g) = 8.28 W/kg; SAR(10 g) = 2.28 W/kg
Maximum value of SAR (measured) = 19.8 W/kg

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 65.75 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 35.2 W/kg
SAR(1 g) = 8.3 W/kg; SAR(10 g) = 2.31 W/kg
Maximum value of SAR (measured) = 19.9 W/kg

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5800 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 64.03 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 36.1 W/kg
SAR(1 g) = 8.03 W/kg; SAR(10 g) = 2.22 W/kg
Maximum value of SAR (measured) = 19.7 W/kg



Impedance Measurement Plot for Body TSL



< Dielectric Probe : DAK-3.5 SN 1140 >

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **Onetech (Dymstec)**

Certificate No: **OCP-DAK3.5-1140_Nov17**

CALIBRATION CERTIFICATE

Object **DAK-3.5 - SN: 1140**

Calibration procedure(s) **QA CAL-33.v2
Calibration of dielectric parameter probes**

Calibration date: **November 21, 2017**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility; environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
OCP DAK-3.5 (weighted)	SN: 1249	10-Oct-17 (OCP-DAK3.5-1249_Oct17)	Oct-18
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Rohde & Schwarz ZVA50	T0170	6-Jun-17 (in house check Jun-17)	Jun-18
Digital Thermometer DTM3000	2148	19-May-17 (DTM-2148_May17)	May-18
Methanol 99.9% Type 34860	STBF2902V	20-Apr-17 (bottle opened, check Apr-17)	Apr-18
Head Liquid, HSL U12	121204-1	20-Apr-17 (in house check Apr-17)	Apr-18
0.1 mol/L NaCl solution Type 35275	SZBF3280V	20-Apr-17 (in house check Apr-17)	Apr-18
0.05 mol/L NaCl solution	160413-1	20-Apr-17 (in house check Apr-17)	Apr-18
Head Gel, SL AGH U08 AB-B	150430	20-Apr-17 (in house check Apr-17)	Apr-18
Solid Substrate	AK9	20-Apr-17 (in house check Apr-17)	Apr-18

Calibrated by: **Name** **Function**
Claudio Leubler **Laboratory Technician**

Approved by: **Name** **Function**
Katja Pokovic **Technical Manager**

Issued: November 21, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: OCP-DAK3.5-1140_Nov17

Page 1 of 13

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
S Service suisse d'étalonnage
C Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

References

- [1] IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- [2] IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- [3] IEC 62209-2 Ed.1, "Human Exposure to Radio Frequency Fields from Handheld and Body-Mounted Wireless Communication Devices – Human models, Instrumentation, and Procedures Part 2: Procedure to determine the specific absorption rate (SAR) for mobile wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- [4] A. P. Gregory and R. N. Clarke, "NPL Report MAT 23", January 2012
- [5] Tables of the Complex Permittivity of Dielectric Reference Liquids at Frequencies up to 5 GHz
- [6] DAK Professional Handbook, SPEAG, December 2016
- [7] A. Toropainen et al, "Method for accurate measurement of complex permittivity of tissue equivalent liquids", Electronics Letters 36 (1) 2000 pp32-34
- [8] J. Hilland, "Simple sensor system for measuring the dielectric properties of saline solutions", Meas. Sci. Technol. 8 pp901-910 (1997)
- [9] K. Nörtemann, J. Hilland and U. Kaatz, "Dielectric Properties of Aqueous NaCl Solutions at Microwave Frequencies", J. Phys. Chem. A 101 pp6864-6869 (1997)
- [9] R. Buchner, G. T. Heftner and Peter M. May, "Dielectric Relaxation of Aqueous NaCl Solutions", J. Phys. Chem. A 103 (1) (1999)

Description of the dielectric probe

Dielectric probes are used to measure the dielectric parameters of tissue simulating media in a wide frequency range. The complex permittivity $\epsilon_r = (\epsilon'/\epsilon_0) - j(\epsilon''/\epsilon_0)$ is determined from the S parameters measured with a vector network analyzer (VNA) with software specific to the probe type. The parameters of interest e.g. in standards [1, 2, 3] and for other applications are presented and calculated as follows:

(Relative) permittivity ϵ' (real part of $\epsilon_r = (\epsilon'/\epsilon_0) - j(\epsilon''/\epsilon_0)$ where $\epsilon_0 = 8.854 \text{ pF/m}$ is the permittivity in free space)

Conductivity $\sigma = 2 \pi f \epsilon'' \epsilon_0$,

Loss Tangent $= (\epsilon''/\epsilon')$

The **OCP** (open ended coaxial) is a cut off section of 50 Ohm transmission line, similar to the system described in [1, 2, 3, 5], used for contact measurement. The material is measured either by touching the probe to the surface of a solid/gel or by immersing it into a liquid media. The electromagnetic fields at the probe end fringe into the material to be measured, and its parameters are determined from the change of the S_{11} parameters. With larger diameter of the dielectrics, the probe can be used down to lower frequencies.

The flange surrounding the active area shapes the near field similar to a semi-infinite geometry and is inserted fully into the measured lossy liquid.

The probe is connected with a phase and amplitude stable cable to a VNA which is then calibrated with Open, Short and a Liquid with well-known parameters. All parts in the setup influencing the amplitude and phase of the signal are important and shall remain stable.

Handling of the item

Before usage, the active probe area has to be cleaned from any material residuals potentially contaminating the reference standards. The metal and dielectric surface must be protected to keep the precision of the critical mechanical dimensions. The connector and cable quality are critical; any movements between calibration and measurement shall be avoided. The temperature must be stable and must not differ from the material temperature.

Methods Applied and Interpretation of Parameters

- The calibration of the dielectric probe system is done in the steps described below for the desired frequency range and calibration package (SAR/MRI liquids, Semi-solid/solid material). Because the standard calibration in step 3 is critical for the results in steps 4 to 8, the sequence 3 to 8 is repeated 3 times. As a result, the result from these 3 sets is represented.
1. Configuration and mechanical / optical status.
 2. Measurement resolution is 5 MHz from 10 to 300 MHz, 50 MHz from 300 to 6000 MHz and 250 MHz from 6 to 20 GHz.
 3. Standard calibration uses Air / Short / Liquid. 1 liter liquid quantity is used to reduce the influence the reflections. The liquid type is selected depending on the lowest frequency and probe diameter:
DAK-1.2, DAK-3.5, Agilent OCP: de-ionized water (approx. 22 °C)
DAK-12: saline solution with static conductivity 1 S/m (approx. 22 °C)
NPL OCP: pure ethanol (approx. 22 °C)
 4. The cable used in the setup stays in a fixed position, i.e. the probe is fixed and measuring from the top in an angle of typ. 20° from the vertical axis. For DAK and Agilent probes, the refresh function (air standard) is used previous to the individual measurements in order to compensate for possible deviations from cable movements. After insertion of the probe into a liquid, the possible air bubbles are removed from the active surface.
 5. Measurement of multiple shorts if not already available from the calibration in the previous step (NPL). Evaluation of the deviation from the previous calibration short with graphical representation of the complex quantities and magnitude over the frequency range. Probe specific short is used. This assessment shows ability to define a short circuit at the end of the probe for the VNA calibration in the setup which is essential at high frequencies and depends on the probe surface quality.
 6. Measurement of validation liquids in a quantity of 1 liter at well defined temperature. Evaluation of the deviations from the target. The targets base on traceable data from reference sources. The deviation of the measurement is graphically presented for permittivity and conductivity (for lossy liquids) or loss tangent (for low losses at low frequencies).
 7. Measurement of lossy liquids in a quantity of 1 liter at well defined temperature. Head tissue simulating liquid or saline solution with 0.5 S/m static conductivity are representative. The target data base on traceable data from reference sources or from multiple measurements with precision reference probes or different evaluations such as transmission line or slotted line methods. Evaluation of the deviation from the target and graphical representation for permittivity and conductivity over the frequency range
 8. Semi-solid / solid material calibration:
Measurements of an elastic lossy broadband semi-solid gel with parameters close to the head tissue target. Measurements of a planar very low loss solid microwave-substrate. The average of 4 measurements of the same sample at different location is shown as a single result. The deviation of the permittivity and conductivity from the reference data is evaluated.
Measurements of a planar very low loss solid microwave-substrate. The average of 4 measurements of the same sample at different location is shown as a single result. The relative deviation of the permittivity and the absolute deviation of the loss tangent is evaluated.
The targets base on multiple measurements (on the same material batch at identical temperature) on convex and planar surfaces with precision reference OCP.

- The measurement on semi-solid / solid materials is sensitive to the quality and planarity of the probe contact area, such as air gaps due to imperfect probes (resulting lower permittivity values).
9. Table for the probe uncertainty: The uncertainty of the probe depending on probe type, size, material parameter range and frequency is given in a table. It represents the best measurement capability of the specific probe but does not include the material (deviation from the target values).
 10. Appendix with detailed results of all measurements with the uncertainties for the specific measurement. In addition to the probe uncertainty (see above), it includes the uncertainty of the reference material used for the measurement. A set of results from independent calibrations represents the capability of the setup and the lossy materials used, including the precision of the measured material and the influence of temperature deviations. Temperature and operator influence was minimized and gives a good indication of the achievable repeatability of a measurement.
 11. Summary assessment of the measured deviations and detailed comments if not typical for the probe type.

Dielectric probe identification and configuration data

Item description

Probe type	OCP Open-ended coaxial probe
Probe name	SPEAG Dielectric Assessment Kit DAK-3.5
Type No	SM DAK 040 CA
Serial No	1140
Description	Open-ended coaxial probe with flange Flange diameter: 19.0 mm Dielectric diameter: 3.5 mm Material: stainless steel
Connector 1	PC 3.5 pos.
Software version	DAK Measurement Solver 2.4.0.807 Calibration Type: Air / short / water (set to measured water temp.) Probe type: "DAK3.5" (software setting)
Further settings	VNA bandwidth setting: 50 Hz

SCS 0108 Accessories used for customer probe calibration

Cable	Huber & Suhner Sucoflex 404, SN: 4361, length 1 m, PC3.5 neg. – PC3.5 neg.
Short	DAK-3.5 shorting block, type SM DAK 200 BA Contact area covered with cleaned Cu stripe

Additional items used during measurements

Adapter 1	PC3.5 pos. – PC2.4 (VNA side)
Adapter 2	PC3.5 pos. – PC3.5 neg. (probe side)

Notes

- Before the calibration, the connectors of the probe and cable were inspected and cleaned.
- Probe visual inspection: according to requirements
- Short inspection: according to the requirements

Probe Uncertainty

The following tables provide material and frequency specific uncertainties (k=2) for the dielectric probe. The values in the tables represent the measurement capability for the probe when measuring a material in the indicated parameter range. They include all uncertainties of

- probe system
- possible systematic errors due to the design
- calibration
- temperature differences during the calibration and measurements, as described,
- VNA noise

Apart from the material used for the calibration (de-ionized water), material uncertainties of the reference materials used during the measurement in Appendix A are not included in these tables.

DAK-3.5				
Permittivity range		Frequency range	(sigma / LT range)	Unc. (k=2)
1 – 15		10 MHz - 20 MHz		---
		20 MHz - 200 MHz		---
		200 MHz - 3 GHz	LT < 0.1	2.4%
		3 GHz - 6 GHz	LT < 0.1	2.0%
		6 GHz - 20 GHz	LT < 0.1	2.1%
10 – 40		10 MHz - 20 MHz		---
		20 MHz - 200 MHz		---
		200 MHz - 3 GHz	sigma : 1 – 10 S/m	1.9%
		3 GHz - 6 GHz	sigma : 1 – 10 S/m	2.3%
		6 GHz - 20 GHz	sigma > 10 S/m	3.5%
35 – 100		10 MHz - 20 MHz		---
		20 MHz - 200 MHz		---
		200 MHz - 3 GHz	sigma : 1 – 10 S/m	1.8%
		3 GHz - 6 GHz	sigma : 1 – 10 S/m	1.9%
		6 GHz - 20 GHz	sigma > 10 S/m	2.4%
Conductivity range (S/m)		Frequency range	(epsilon / LT range)	Unc. (k=2)
1 – 10		10 MHz - 20 MHz		---
		20 MHz - 200 MHz		---
		200 MHz - 3 GHz	eps : 35 - 100	2.7%
		3 GHz - 6 GHz	eps : 35 - 100	3.0%
		6 GHz - 20 GHz	eps : 10 - 40	3.0%
Loss tangent range		Frequency range	(epsilon / LT range)	Unc. (k=2)
< 0.1		10 MHz - 20 MHz		---
		20 MHz - 200 MHz		---
		200 MHz - 3 GHz	eps : 1 - 15	0.03
		3 GHz - 6 GHz	eps : 1 - 15	0.03
		6 GHz - 20 GHz	eps : 1 - 15	0.03

Calibration Results

Uncertainty limits ($k=2$) for the material measurements in the figures of Appendix A are represented with red dashed lines. These uncertainties contain - in addition to probe uncertainty - the uncertainty of the material target parameter determination. The measurements show the results obtained from independent calibrations for the same material. The differences between the individual measurement curves give therefore an indication for the obtainable repeatability and shall lie within the uncertainties stated in the tables.

Materials for DAK-3.5 calibration:

Appendix A with curves for Methanol, HSL, and 0.05 mol/L NaCl solution (200 MHz - 6 GHz, optional 20 GHz), HS gel and low loss solid substrate are optional.

Appendix A: Detailed Results (additional assessments outside the scope of SCS0108)

A.1 Probe appearance and calibration sequence

A.1.1 Appearance

The OCP appearance is fully according to the expectations:

- the flange surface is intact

A.1.2 Calibration sequence

The following sequence was repeated 3 times in the low frequency range from 200 – 300 MHz in 5 MHz steps and in the high frequency range from 300 to 6000 MHz in 50 MHz steps, and from 6 GHz to 20 GHz in 250 MHz steps.

- Air
- Short 1 short, then immediate verification with a second short (with eventual repetition)
- Water De-ionized water, temperature measured and set in the software (for DAK-12 0.1 mol/L saline solution, temperature measured and set in the software)
- Methanol Pure methanol, temperature measured and set in the software
- Liquids Measurement of further liquids (e.g. Head tissue simulating liquid and 0.05 mol/l saline)
- Cleaning Probe washed with water and isopropanol at the end of the sequence.
- Shorts 4 additional separate short measurements to determine the deviation from the original
- Refresh Refresh with Air
- Solid 4 separate solid low loss planar substrate measurements to determine one average (optional)
- Semisolid 4 separate head gel measurements on fresh intact surface to determine one average (optional)
- Cleaning Probe washed with water and isopropanol at the end of the sequence

Evaluation of the additional shorts from the calibrated (ideal) short point at the left edge of the Smith Chart, represented as magnitude over the frequency range (fig. 2.1.x) and in polar representation (fig. 2.2.x).

Evaluation of the Liquid measurements and representation of the permittivity and conductivity deviation from their reference data at the measurement temperature. The results of each of the 3 calibrations is shown in the appendix for each material (fig. 3ff) in black, red, blue. The red dashed line shows the uncertainty of the reference material parameter determination.

Evaluation of the Semisolid measurements (optional) by representing the 3 average deviations (each resulting from the 4 separate measurements per set), equivalent to the liquid measurement. Representation of the permittivity and conductivity deviation from their reference data at the nominal temperature.

Evaluation of the Solid measurements (optional) by representing the 3 average deviations (each resulting from the 4 separate measurements per set), equivalent to the liquid measurement. Representation of the permittivity deviation from their reference data and the loss tangent at the nominal temperature.

A.2 Short residual magnitudes

After each of the 3 calibrations with a single short (as per the DAK software), 4 additional separate, short measurements were performed after the liquid measurements and evaluated from the S11 data. The residuals in the graphs represent the deviation from the ideal short point on the polar representation on the VNA screen.




Fig. 2.1a Magnitude of the residual of the shorts, 200 MHz – 20 GHz, after calibration a)




Fig. 2.1b Magnitude of the residual of the shorts, 200 MHz – 20 GHz, after calibration b)




Fig. 2.1c Magnitude of the residual of the shorts, 200 MHz – 20 GHz, after calibration c)




Fig. 2.2a-c Complex representation of the residuals of the shorts, 200 MHz - 20 GHz, after calibrations a)-b) in the top and c) in the bottom

All shorts have good quality. Some minor deviations might be visible from contact quality (left - right).

A.3 Methanol

Methanol (99.9% pure) was measured at a temperature of 22 ± 2 °C. The liquid temperature was stabilized within 0.05 °C of the desired temperature. Deviations are presented relative to the nominal material parameters at this temperature, calculated from NPL data for this temperature.




Fig. 3.1 Methanol permittivity deviation from target, 200 MHz – 20 GHz




Fig. 3.2 Methanol conductivity deviation from target, 200 MHz – 20 GHz

Conductivity error can be high at low frequencies due to the low absolute conductivity values.

A.4 Head Tissue

Broadband head simulating liquid was measured at a temperature of 22 ± 2 °C. The liquid temperature was stabilized within 0.05 °C of the desired temperature. Deviations are presented relative to the reference data for this material. Those parameters have been evaluated from multiple measurements on the used bath with precision reference OCP and further methods.




Fig. 4.1 HSL permittivity deviation from target, 200 MHz – 20 GHz




Fig. 4.2 HSL conductivity deviation from target, 200 MHz – 20 GHz

A.5 0.05 mol/L NaCl solution

0.05 mol/L NaCl / water solution has a static conductivity of 0.5 S/m, similar to MRI HCL (High Conductivity Liquid). It was measured at a temperature of 22 ± 2 °C. The liquid temperature was stabilized within 0.05 °C of the desired temperature. Deviations are presented relative to the reference data for this material. These parameters have been derived from the theoretical model according to [7], matched to the measurements from reference probes and other sources. A quantity of 1 liter was used for the measurement.




Fig. 5.1 0.05 mol/L solution permittivity deviation from target, 200 MHz – 20 GHz




Fig. 5.2 0.05 mol/L solution conductivity deviation from target, 200 MHz – 20 GHz

Appendix B: Nominal parameters of reference materials used for calibration (additional assessments outside the scope of SCS0108)




Fig. B.1 Permittivity of reference materials




Fig. B.2 Conductivity of reference materials




Fig. B.3 Loss tangent of reference materials