

RADIO PERFORMANCE TEST REPORT

Test Report No. : OT-21O-RWD-048
Reception No. : 2110004560
Applicant : Samsung Electronics Co Ltd
Address : 19 Chapin Rd., Building D, Pine Brook, New Jersey, 07058, United States
Manufacturer : Samsung Electronics Co Ltd
Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do 16677, Korea
Type of Equipment : Wi-Fi/BT Transceiver
FCC ID. : A3LWCB735M
Model Name : WCB735M
Multiple Model Name : N/A
Serial number : N/A
Total page of Report : 181 pages (including this page)
Date of Incoming : October 07, 2021
Date of issue : October 28, 2021


SUMMARY

The equipment complies with the regulation; **FCC PART 15 SUBPART C Section 15.247**

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.





Tested by
 Ju Yun Park / Manager
 ONETECH Corp.

Reviewed by
 Tae-Ho, Kim / Senior Manager
 ONETECH Corp.

Approved by
 Ki-Hong, Nam / General Manager
 ONETECH Corp.

CONTENTS

	Page
1. VERIFICATION OF COMPLIANCE	7
2. TEST SUMMARY	8
2.1 TEST ITEMS AND RESULTS	8
2.2 ADDITIONS, DEVIATIONS, EXCLUSIONS FROM STANDARDS.....	8
2.3 RELATED SUBMITTAL(S) / GRANT(S)	8
2.4 PURPOSE OF THE TEST	8
2.5 TEST METHODOLOGY.....	8
2.6 TEST FACILITY.....	8
3. GENERAL INFORMATION.....	9
3.1 PRODUCT DESCRIPTION.....	9
3.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	14
4. EUT MODIFICATIONS.....	14
5. SYSTEM TEST CONFIGURATION	15
5.1 JUSTIFICATION.....	15
5.2 PERIPHERAL EQUIPMENT	15
5.3 MODE OF OPERATION DURING THE TEST	16
5.4 CONFIGURATION OF TEST SYSTEM.....	27
5.5 ANTENNA REQUIREMENT	27
6. PRELIMINARY TEST	27
6.1 AC POWER LINE CONDUCTED EMISSIONS TESTS.....	27
6.2 GENERAL RADIATED EMISSIONS TESTS	27
7. MINIMUM 6 dB BANDWIDTH.....	28
7.1 OPERATING ENVIRONMENT	28
7.2 TEST SET-UP	28
7.3 TEST DATE	28
7.4 TEST DATA FOR 802.11B WLAN MODE.....	29
7.4.1 Test data for Antenna 0	29
7.4.2 Test data for Antenna 1	32
7.5 TEST DATA FOR 802.11G WLAN MODE	35
7.5.1 Test data for Antenna 0	35
7.5.2 Test data for Antenna 1	38
7.6 TEST DATA FOR 802.11N_HT20 WLAN MODE.....	41

This Report is not correlated with the authentication of KOLAS

It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

7.6.1 Test data for Antenna 0	41
7.6.2 Test data for Antenna 1	44
7.7 TEST DATA FOR 802.11N_HT40 WLAN MODE	47
7.7.1 Test data for Antenna 0	47
7.7.2 Test data for Antenna 1	50
8. MAXIMUM CONDUCTED (AVERAGE) OUTPUT POWER	53
8.1 OPERATING ENVIRONMENT	53
8.2 TEST SET-UP	53
8.3 TEST DATE	53
8.4 TEST DATA FOR 802.11B WLAN MODE	54
8.4.1 Test data for Antenna 0	54
8.4.2 Test data for Antenna 1	54
8.5 TEST DATA FOR 802.11G WLAN MODE	55
8.5.1 Test data for Antenna 0	55
8.5.2 Test data for Antenna 1	55
8.5.3 Test data for Multiple Transmit	56
8.6 TEST DATA FOR 802.11N_HT20 WLAN MODE	57
8.6.1 Test data for Antenna 0	57
8.6.2 Test data for Antenna 1	57
8.6.3 Test data for Multiple Transmit	58
8.7 TEST DATA FOR 802.11N_HT40 WLAN MODE	59
8.7.1 Test data for Antenna 0	59
8.7.2 Test data for Antenna 1	59
8.7.3 Test data for Multiple Transmit	60
9. 100 kHz BANDWIDTH OUTSIDE THE FREQUENCY BAND	61
9.1 OPERATING ENVIRONMENT	61
9.2 TEST SET-UP FOR CONDUCTED MEASUREMENT	61
9.3 TEST SET-UP FOR RADIATED MEASUREMENT	61
9.4 TEST DATE	61
9.5 TEST DATA FOR CONDUCTED EMISSION	62
9.5.1 Test data for 802.11b WLAN Mode	62
9.5.2 Test data for 802.11g WLAN Mode	78
9.5.3 Test data for 802.11n_HT20 WLAN Mode	94
9.5.4 Test data for 802.11n_HT40 WLAN Mode	110
9.6 TEST DATA FOR RADIATED EMISSION	126
9.6.1 Radiated Emission which fall in the Restricted Band	126

This Report is not correlated with the authentication of KOLAS

It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

9.6.2 Spurious & Harmonic Radiated Emission.....	131
10. PEAK POWER SPECTRUL DENSITY	141
10.1 OPERATING ENVIRONMENT	141
10.2 TEST SET-UP	141
10.3 TEST DATE	141
10.4 TEST DATA FOR 802.11B WLAN MODE.....	142
10.4.1 Test data for Antenna 0	142
10.4.2 Test data for Antenna 1	145
10.5 TEST DATA FOR 802.11G WLAN MODE	148
10.5.1 Test data for Antenna 0	148
10.5.2 Test data for Antenna 1	151
10.5.3 Test data for Multiple Transmit	154
10.6 TEST DATA FOR 802.11N_HT20 WLAN MODE.....	155
10.6.1 Test data for Antenna 0	155
10.6.2 Test data for Antenna 1	158
10.6.3 Test data for Multiple Transmit	161
10.7 TEST DATA FOR 802.11N_HT40 WLAN MODE.....	162
10.7.1 Test data for Antenna 0	162
10.7.2 Test data for Antenna 1	165
10.7.3 Test data for Multiple Transmit	168
11. RADIATED EMISSION TEST	169
11.1 OPERATING ENVIRONMENT	169
11.2 TEST SET-UP	169
11.3 TEST DATE	169
11.4 TEST DATA FOR 30 MHz ~ 1 000 MHz	170
11.4.1 Test data for WLAN 2.4 GHz	170
11.4.2 Test data for Intermodulation Mode(Bluetooth LE + WLAN 2.4 GHz + WLAN 5 GHz)	171
11.4.3 Test data for Intermodulation Mode(Bluetooth + WLAN 2.4 GHz + WLAN 5 GHz)	172
11.5 TEST DATA FOR BELOW 30 MHz	173
11.6 TEST DATA FOR ABOVE 1 GHz	173
12. CONDUCTED EMISSION TEST	174
12.1 OPERATING ENVIRONMENT	174
12.2 TEST SET-UP	174
12.3 TEST DATE	174
12.4 TEST DATA.....	175
12.4.1 Test data for WLAN 2.4 GHz	175

This Report is not correlated with the authentication of KOLAS

It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

<i>12.4.2 Test data for Intermodulation Mode(Bluetooth LE + WLAN 2.4 GHz + WLAN 5 GHz)</i>	177
<i>12.4.3 Test data for Intermodulation Mode(Bluetooth + WLAN 2.4 GHz + WLAN 5 GHz)</i>	179
13. LIST OF TEST EQUIPMENT	181

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-21O-RWD-048	October 28, 2021	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : Samsung Electronics Co Ltd
 Address : 19 Chapin Rd., Building D, Pine Brook, New Jersey, 07058, United States
 Contact Person : Jenni Chun / General Manager
 Telephone No. : 973-808-6375
 FCC ID : A3LWCB735M
 Model Name : WCB735M
 Brand Name : 
 Serial Number : N/A
 Date : October 28, 2021

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM
E.U.T. DESCRIPTION	Modular Transmitter, Wi-Fi/BT Transceiver
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2020
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. TEST SUMMARY

2.1 Test items and results

SECTION	TEST ITEMS	RESULTS
15.247 (a) (2)	Minimum 6 dB Bandwidth	Met the Limit / PASS
15.247 (b) (3)	Maximum Conducted(average) Output Power	Met the Limit / PASS
15.247 (d)	100 kHz Bandwidth Outside the Frequency Band	Met the Limit / PASS
15.247 (d)	Radiated Emission which fall in the Restricted Band	Met the Limit / PASS
15.247 (e)	Peak Power Spectral Density	Met the Limit / PASS
15.209	Radiated Emission Limits	Met the Limit / PASS
15.207	Conducted Limits	Met the Limit / PASS
15.203	Antenna Requirement	Met requirement / PASS

2.2 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

2.3 Related Submittal(s) / Grant(s)

Original submittal only

2.4 Purpose of the test

To determine whether the equipment under test fulfills the requirements of the regulation stated in FCC PART 15 SUBPART C Section 15.247.

2.5 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2020. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

2.6 Test Facility

The Onetech Corp. has been designated to perform equipment testing in compliance with ISO/IEC 17025.

The Electromagnetic compatibility measurement facilities are located at 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea.

-. Site Filing:

VCCI (Voluntary Control Council for Interference) – Registration No. R-20122/ C-14617/ G-10666/ T-11842

ISED (Innovation, Science and Economic Development Canada) – Registration No. Site# 3736A-3

KOLAS (Korea Laboratory Accreditation Scheme) - Accreditation NO. KT085

FCC (Federal Communications Commission) - Accreditation No. KR0013

RRA (Radio Research Agency) – Designation No. KR0013

This Report is not correlated with the authentication of KOLAS

It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

3. GENERAL INFORMATION

3.1 Product Description

The Samsung Electronics Co Ltd, Model WCB735M (referred to as the EUT in this report) is a Wi-Fi/BT Transceiver. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	Wi-Fi/BT Transceiver	
Temperature Range	-20 °C ~ 50 °C	
OPERATING FREQUENCY	Bluetooth LE	2 402 MHz ~ 2 480 MHz
	Bluetooth	2 402 MHz ~ 2 480 MHz
	WLAN 2.4 GHz	2 412 MHz ~ 2 472 MHz (802.11b/g/n(HT20))
		2 422 MHz ~ 2 462 MHz (802.11n(HT40))
	WLAN 5 150 MHz ~ 5 250 MHz Band	5 180 MHz ~ 5 240 MHz (802.11a/n(HT20)/ac(VHT20))
		5 190 MHz ~ 5 230 MHz (802.11n(HT40)/ac(VHT40))
		5 210 MHz (802.11ac(VHT80))
	WLAN 5 250 MHz ~ 5 350 MHz Band	5 260 MHz ~ 5 320 MHz (802.11a/n(HT20)/ac(VHT20))
		5 270 MHz ~ 5 310 MHz (802.11n(HT40)/ac(VHT40))
		5 290 MHz (802.11ac(VHT80))
	WLAN 5 470 MHz ~ 5 725 MHz Band	5 500 MHz ~ 5 720 MHz (802.11a/n(HT20)/ac(VHT20))
		5 510 MHz ~ 5 710 MHz (802.11n(HT40)/ac(VHT40))
		5 530 MHz ~ 5 690 MHz (802.11ac(VHT80))
	WLAN 5 725 MHz ~ 5 850 MHz Band	5 745 MHz ~ 5 825 MHz (802.11a/n(HT20)/ac(VHT20))
		5 755 MHz ~ 5 795 MHz (802.11n(HT40)/ac(VHT40))
		5 775 MHz (802.11ac(VHT80))
MODULATION TYPE	Bluetooth LE	GFSK for 1 Mbps / 2 Mbps
	Bluetooth	GFSK for 1Mbps, $\pi/4$ -DQPSK for 2Mbps, 8-DPSK for 3Mbps
	WLAN 2.4 GHz	802.11b: DSSS Modulation(DBPSK/DQPSK/CCK)
		802.11g/n(HT20)/n(HT40): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)
	WLAN 5 GHz	802.11a/n(HT20)/n(HT40)/ac(VHT80): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)

RF OUTPUT POWER	Bluetooth LE	1 Mbps	11.26 dBm
		2 Mbps	11.15 dBm
	Bluetooth	1 Mbps	11.22 dBm
		2 Mbps	11.05 dBm
		3 Mbps	11.08 dBm
	WLAN 2.4 GHz	Antenna 0	16.69 dBm(802.11b) 12.83 dBm(802.11g) 12.70 dBm(802.11n_HT20) 10.93 dBm(802.11n_HT40)
		Antenna 1	17.51 dBm(802.11b) 13.75 dBm(802.11g) 13.63 dBm(802.11n_HT20) 11.59 dBm(802.11n_HT40)
		Multiple Antenna	16.32 dBm(802.11g) 16.20 dBm(802.11n_HT20) 14.28 dBm(802.11n_HT40)
	WLAN 5 150 MHz ~ 5 250 MHz Band	Antenna 0	12.39 dBm(802.11a) 12.48 dBm(802.11n_HT20) 10.15 dBm(802.11n_HT40) 8.75 dBm(802.11ac_VHT80)
		Antenna 1	12.80 dBm(802.11a) 12.63 dBm(802.11n_HT20) 10.10 dBm(802.11n_HT40) 9.08 dBm(802.11ac_VHT80)
		Multiple Antenna	15.53 dBm(802.11a) 15.50 dBm(802.11n_HT20) 13.09 dBm(802.11n_HT40) 11.93 dBm(802.11ac_VHT80)

RF OUTPUT POWER	WLAN 5 250 MHz ~ 5 350 MHz Band	Antenna 0	12.47 dBm(802.11a) 12.35 dBm(802.11n_HT20) 11.08 dBm(802.11n_HT40) 7.81 dBm(802.11ac_VHT80)
		Antenna 1	13.15 dBm(802.11a) 13.18 dBm(802.11n_HT20) 11.86 dBm(802.11n_HT40) 8.48 dBm(802.11ac_VHT80)
		Multiple Antenna	15.83 dBm(802.11a) 15.80 dBm(802.11n_HT20) 14.50 dBm(802.11n_HT40) 11.17 dBm(802.11ac_VHT80)
	WLAN 5 470 MHz ~ 5 725 MHz Band	Antenna 0	12.40 dBm(802.11a) 12.32 dBm(802.11n_HT20) 11.38 dBm(802.11n_HT40) 8.18 dBm(802.11ac_VHT80)
		Antenna 0_Straddle	9.55 dBm(802.11a) 9.78 dBm(802.11n_HT20) 9.69 dBm(802.11n_HT40) 5.92 dBm(802.11ac_VHT80)
		Antenna 1	13.23 dBm(802.11a) 13.26 dBm(802.11n_HT20) 11.56 dBm(802.11n_HT40) 8.66 dBm(802.11ac_VHT80)
		Antenna 1_Straddle	11.34 dBm(802.11a) 10.85 dBm(802.11n_HT20) 10.66 dBm(802.11n_HT40) 6.74 dBm(802.11ac_VHT80)

RF OUTPUT POWER	WLAN 5 470 MHz ~ 5 725 MHz Band	Multiple Antenna	15.77 dBm(802.11a) 15.73 dBm(802.11n_HT20) 14.48 dBm(802.11n_HT40) 11.44 dBm(802.11ac_VHT80)
		Multiple Antenna _Straddle	13.55 dBm(802.11a) 13.36 dBm(802.11n_HT20) 13.21 dBm(802.11n_HT40) 9.36 dBm(802.11ac_VHT80)
	WLAN 5 725 MHz ~ 5 850 MHz Band	Antenna 0	11.78 dBm(802.11a) 11.93 dBm(802.11n_HT20) 11.13 dBm(802.11n_HT40) 10.55 dBm(802.11ac_VHT80)
		Antenna 0_Straddle	2.36 dBm(802.11a) 2.57 dBm(802.11n_HT20) -2.23 dBm(802.11n_HT40) -8.75 dBm(802.11ac_VHT80)
		Antenna 1	13.20 dBm(802.11a) 13.34 dBm(802.11n_HT20) 12.30 dBm(802.11n_HT40) 11.66 dBm(802.11ac_VHT80)
		Antenna 1_Straddle	3.84 dBm(802.11a) 3.43 dBm(802.11n_HT20) -0.99 dBm(802.11n_HT40) -7.34 dBm(802.11ac_VHT80)
		Multiple Antenna	15.56 dBm(802.11a) 15.70 dBm(802.11n_HT20) 14.76 dBm(802.11n_HT40) 14.15 dBm(802.11ac_VHT80)
		Multiple Antenna _Straddle	6.17 dBm(802.11a) 6.03 dBm(802.11n_HT20) 1.44 dBm(802.11n_HT40) -4.98 dBm(802.11ac_VHT80)

ANTENNA TYPE	Chip Antenna		
ANTENNA GAIN	Bluetooth LE	0.62 dBi	
	Bluetooth	0.62 dBi	
	WLAN 2.4 GHz	Antenna 0	-0.42 dBi
		Antenna 1	-1.71 dBi
		Multiple Antenna	1.99 dBi
	5 150 MHz ~ 5 250 MHz Band	Antenna 0	-0.72 dBi
		Antenna 1	1.83 dBi
		Multiple Antenna	3.75 dBi
	5 250 MHz ~ 5 350 MHz Band	Antenna 0	-0.80 dBi
		Antenna 1	0.37 dBi
		Multiple Antenna	2.83 dBi
	5 470 MHz ~ 5 725 MHz Band	Antenna 0	-1.33 dBi
		Antenna 1	-0.17 dBi
		Multiple Antenna	2.30 dBi
	5 725 MHz ~ 5 850 MHz Band	Antenna 0	-1.43 dBi
		Antenna 1	0.26 dBi
		Multiple Antenna	2.51 dBi
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)		40 MHz	

3.2 Alternative type(s)/model(s); also covered by this test report.

-, None

4. EUT MODIFICATIONS

-, None

5. SYSTEM TEST CONFIGURATION

5.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
Main Board	Samsung Electronics Co Ltd	M80B(V1.0)	N/A

5.2 Peripheral equipment

Defined as equipment needed for correct operation of the EUT, but not considered as tested:

Model	Manufacturer	Description	Connected to
WCB735M	Samsung Electronics Co Ltd	Wi-Fi/BT Transceiver (EUT)	-
HP Probook	HP	Notebook PC	EUT
PPP009L-E	LIE-ON TECHNOLOGY (CHANGZHOU)CO.,LTD.	AC Adapter	-

5.3 Mode of operation during the test

For the testing, software used to control the EUT for staying in continuous transmitting mode is programmed.

-. Frequency / Channel Operations

Channel	Frequency
1	2 412
2	2 417
3	2 422
4	2 427
5	2 432
6	2 437
7	2 442
8	2 447
9	2 452
10	2 457
11	2 462
12	2 467
13	2 472

Modulation	DATA RATE	OUTPUT POWER[dBm]	
		Antenna 0	Antenna 1
802.11 b (Low Channel)	1 Mbps	16.69	16.86
	2 Mbps	16.61	16.80
	5.5 Mbps	16.57	16.77
	11 Mbps	16.53	16.76
802.11 g (Low Channel)	6 Mbps	12.83	13.75
	9 Mbps	12.77	13.65
	12 Mbps	12.73	13.56
	18 Mbps	12.70	13.52
	24 Mbps	12.68	13.50
	36 Mbps	12.22	12.88
	48 Mbps	11.18	11.79
	54 Mbps	11.17	11.77
802.11 HT 20 (Low Channel)	6.5 Mbps	12.70	13.63
	13 Mbps	12.59	13.59
	19.5 Mbps	12.50	13.54
	26 Mbps	12.45	13.51
	39 Mbps	11.98	12.87
	52 Mbps	11.96	12.90
	58.5 Mbps	10.91	11.81
	65 Mbps	10.89	11.79
802.11 HT 40 (Low Channel)	13.5 Mbps	10.93	11.59
	27 Mbps	10.87	11.55
	40.5 Mbps	10.83	11.53
	54 Mbps	10.80	11.49
	81 Mbps	10.33	10.88
	108 Mbps	10.31	10.78
	121.5 Mbps	9.24	10.00
	135 Mbps	9.22	9.96

-. The worse case data rate for each modulation is determined 1 Mbps(Ant.0/Ant.1) for IEEE 802.11b, 6 Mbps(Ant.0/Ant.1) for IEEE 802.11g, 6.5 Mbps(Ant.0/Ant.1) for HT20, 13.5 Mbps(Ant.0/Ant.1) for HT40.

-. To get a maximum emission levels from the EUT, the EUT was moved throughout the XY, XZ, and YZ planes and the worst case is "XY" axis.

Modulation	DATA RATE	OUTPUT POWER[dBm]	
		Antenna 0	Antenna 1
802.11 b (Middle Channel)	1 Mbps	16.58	17.22
	2 Mbps	16.50	17.16
	5.5 Mbps	16.46	17.13
	11 Mbps	16.42	17.12
802.11 g (Middle Channel)	6 Mbps	12.80	13.30
	9 Mbps	12.74	13.20
	12 Mbps	12.70	13.11
	18 Mbps	12.67	13.07
	24 Mbps	12.65	13.05
	36 Mbps	12.19	12.43
	48 Mbps	11.15	11.34
	54 Mbps	11.14	11.32
802.11 HT 20 (Middle Channel)	6.5 Mbps	12.60	13.17
	13 Mbps	12.49	13.13
	19.5 Mbps	12.40	13.08
	26 Mbps	12.35	13.05
	39 Mbps	11.88	12.41
	52 Mbps	11.86	12.44
	58.5 Mbps	10.81	11.35
	65 Mbps	10.79	11.33
802.11 HT 40 (Middle Channel)	13.5 Mbps	10.86	11.31
	27 Mbps	10.80	11.27
	40.5 Mbps	10.76	11.25
	54 Mbps	10.73	11.21
	81 Mbps	10.26	10.60
	108 Mbps	10.24	10.50
	121.5 Mbps	9.17	9.72
	135 Mbps	9.15	9.68

-. The worse case data rate for each modulation is determined 1 Mbps(Ant.0/Ant.1) for IEEE 802.11b, 6 Mbps(Ant.0/Ant.1) for IEEE 802.11g, 6.5 Mbps(Ant.0/Ant.1) for HT20, 13.5 Mbps(Ant.0/Ant.1) for HT40.

-. To get a maximum emission levels from the EUT, the EUT was moved throughout the XY, XZ, and YZ planes and the worst case is "XY" axis.

Modulation	DATA RATE	OUTPUT POWER[dBm]	
		Antenna 0	Antenna 1
802.11 b (High Channel_11)	1 Mbps	16.49	17.48
	2 Mbps	16.41	17.42
	5.5 Mbps	16.37	17.39
	11 Mbps	16.33	17.38
802.11 g (High Channel_11)	6 Mbps	12.68	12.93
	9 Mbps	12.62	12.83
	12 Mbps	12.58	12.74
	18 Mbps	12.55	12.70
	24 Mbps	12.53	12.68
	36 Mbps	12.07	12.06
	48 Mbps	11.03	10.97
	54 Mbps	11.02	10.95
802.11 HT 20 (High Channel_11)	6.5 Mbps	12.51	12.83
	13 Mbps	12.40	12.79
	19.5 Mbps	12.31	12.74
	26 Mbps	12.26	12.71
	39 Mbps	11.79	12.07
	52 Mbps	11.77	12.10
	58.5 Mbps	10.72	11.01
	65 Mbps	10.70	10.99
802.11 HT 40 (High Channel_9)	13.5 Mbps	10.83	11.02
	27 Mbps	10.77	10.98
	40.5 Mbps	10.73	10.96
	54 Mbps	10.70	10.92
	81 Mbps	10.23	10.31
	108 Mbps	10.21	10.21
	121.5 Mbps	9.14	9.43
	135 Mbps	9.12	9.39

-. The worse case data rate for each modulation is determined 1 Mbps(Ant.0/Ant.1) for IEEE 802.11b, 6 Mbps(Ant.0/Ant.1) for IEEE 802.11g, 6.5 Mbps(Ant.0/Ant.1) for HT20, 13.5 Mbps(Ant.0/Ant.1) for HT40.

-. To get a maximum emission levels from the EUT, the EUT was moved throughout the XY, XZ, and YZ planes and the worst case is "XY" axis.

Modulation	DATA RATE	OUTPUT POWER[dBm]	
		Antenna 0	Antenna 1
802.11 b (High Channel_12)	1 Mbps	16.42	17.50
	2 Mbps	16.34	17.44
	5.5 Mbps	16.30	17.41
	11 Mbps	16.26	17.40
802.11 g (High Channel_12)	6 Mbps	12.57	12.83
	9 Mbps	12.51	12.73
	12 Mbps	12.47	12.64
	18 Mbps	12.44	12.60
	24 Mbps	12.42	12.58
	36 Mbps	11.96	11.96
	48 Mbps	10.92	10.87
	54 Mbps	10.91	10.85
802.11 HT 20 (High Channel_12)	6.5 Mbps	12.44	12.70
	13 Mbps	12.33	12.66
	19.5 Mbps	12.24	12.61
	26 Mbps	12.19	12.58
	39 Mbps	11.72	11.94
	52 Mbps	11.70	11.97
	58.5 Mbps	10.65	10.88
	65 Mbps	10.63	10.86
802.11 HT 40 (High Channel_10)	13.5 Mbps	10.78	10.92
	27 Mbps	10.72	10.88
	40.5 Mbps	10.68	10.86
	54 Mbps	10.65	10.82
	81 Mbps	10.18	10.21
	108 Mbps	10.16	10.11
	121.5 Mbps	9.09	9.33
	135 Mbps	9.07	9.29

-. The worse case data rate for each modulation is determined 1 Mbps(Ant.0/Ant.1) for IEEE 802.11b, 6 Mbps(Ant.0/Ant.1) for IEEE 802.11g, 6.5 Mbps(Ant.0/Ant.1) for HT20, 13.5 Mbps(Ant.0/Ant.1) for HT40.

-. To get a maximum emission levels from the EUT, the EUT was moved throughout the XY, XZ, and YZ planes and the worst case is "XY" axis.

Modulation	DATA RATE	OUTPUT POWER[dBm]	
		Antenna 0	Antenna 1
802.11 b (High Channel_13)	1 Mbps	16.28	17.51
	2 Mbps	16.20	17.45
	5.5 Mbps	16.16	17.42
	11 Mbps	16.12	17.41
802.11 g (High Channel_13)	6 Mbps	11.68	11.84
	9 Mbps	11.62	11.74
	12 Mbps	11.58	11.65
	18 Mbps	11.55	11.61
	24 Mbps	11.53	11.59
	36 Mbps	11.07	10.97
	48 Mbps	10.03	9.88
	54 Mbps	10.02	9.86
802.11 HT 20 (High Channel_13)	6.5 Mbps	11.53	11.79
	13 Mbps	11.42	11.75
	19.5 Mbps	11.33	11.70
	26 Mbps	11.28	11.67
	39 Mbps	10.81	11.03
	52 Mbps	10.79	11.06
	58.5 Mbps	9.74	9.97
	65 Mbps	9.72	9.95
802.11 HT 40 (High Channel_11)	13.5 Mbps	10.72	10.75
	27 Mbps	10.66	10.71
	40.5 Mbps	10.62	10.69
	54 Mbps	10.59	10.65
	81 Mbps	10.12	10.04
	108 Mbps	10.10	9.94
	121.5 Mbps	9.03	9.16
	135 Mbps	9.01	9.12

-. The worse case data rate for each modulation is determined 1 Mbps(Ant.0/Ant.1) for IEEE 802.11b, 6 Mbps(Ant.0/Ant.1) for IEEE 802.11g, 6.5 Mbps(Ant.0/Ant.1) for HT20, 13.5 Mbps(Ant.0/Ant.1) for HT40.

-. To get a maximum emission levels from the EUT, the EUT was moved throughout the XY, XZ, and YZ planes and the worst case is "XY" axis.

-. Duty Cycle

Mode	Tx On Time [ms]	Tx Off Time [ms]	Duty Cycle [%]	Correction Factor [dB]
802.11 b_Antenna 0	-	-	100.00	-
802.11 g_Antenna 0	-	-	100.00	-
802.11 HT 20_Antenna 0	-	-	100.00	-
802.11 HT 40_Antenna 0	-	-	100.00	-
802.11 b_Antenna 1	-	-	100.00	-
802.11 g_Antenna 1	-	-	100.00	-
802.11 HT 20_Antenna 1	-	-	100.00	-
802.11 HT 40_Antenna 1	-	-	100.00	-

Note – Duty Cycle : (Tx On Time / (Tx On Time + Tx Off Time)) * 100

Correction Factor : 10 * Log(1 / (Duty Cycle / 100))

-. Test Plot




This Report is not correlated with the authentication of KOLAS


It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



802.11 HT 20_Antenna 0




802.11 HT 40_Antenna 0

This Report is not correlated with the authentication of KOLAS


It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)


ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)




802.11 b_Antenna 1



802.11 g_Antenna 1



802.11 HT 20_Antenna 1



802.11 HT 40_Antenna 1

This Report is not correlated with the authentication of KOLAS

It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

5.4 Configuration of Test System

Line Conducted Test: The EUT was connected to USB and the power of USB was connected to Notebook PC. All supporting equipments were connected to another LISN. Preliminary Power line Conducted Emission test was performed by using the procedure in ANSI C63.10: 2020 to determine the worse operating conditions.

Radiated Emission Test: Preliminary radiated emissions test were conducted using the procedure in ANSI C63.10: 2020 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 meter Semi Anechoic Chamber.

The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.

5.5 Antenna Requirement

For intentional device, according to section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Construction:

The antenna of the EUT is Chip Antenna on the main board in the EUT, so no consideration of replacement by the user.

6. PRELIMINARY TEST

6.1 AC Power line Conducted Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
Transmitting Mode	X

6.2 General Radiated Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
Transmitting Mode	X


7. MINIMUM 6 dB BANDWIDTH

7.1 Operating environment

Temperature : 23 °C
Relative humidity : 45 % R.H.

7.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz, and peak detection was used. The 6 dB bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 6 dB.



7.3 Test Date

October 07, 2021 ~ October 20, 2021


7.4 Test data for 802.11b WLAN Mode


7.4.1 Test data for Antenna 0

-. Test Result : Pass


CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)	LIMIT (MHz)	Margin (MHz)
Low	2 412.00	9.04	0.50	8.54
Middle	2 437.00	9.04	0.50	8.54
High 11	2 462.00	9.04	0.50	8.54
High 12	2 467.00	9.04	0.50	8.54
High 13	2 472.00	9.04	0.50	8.54

Remark. Margin = Measured Value - Limit





Middle Channel




High Channel 11

This Report is not correlated with the authentication of KOLAS


It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



High Channel 12



High Channel 13

This Report is not correlated with the authentication of KOLAS

It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)


ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)


7.4.2 Test data for Antenna 1

-. Test Result : Pass


CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)	LIMIT (MHz)	Margin (MHz)
Low	2 412.00	9.09	0.50	8.59
Middle	2 437.00	9.04	0.50	8.54
High 11	2 462.00	9.09	0.50	8.59
High 12	2 467.00	9.09	0.50	8.59
High 13	2 472.00	9.09	0.50	8.59

Remark. Margin = Measured Value - Limit





Middle Channel




High Channel 11

This Report is not correlated with the authentication of KOLAS


It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



High Channel 12



High Channel 13

This Report is not correlated with the authentication of KOLAS

It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)


7.5 Test data for 802.11g WLAN Mode


7.5.1 Test data for Antenna 0

-. Test Result : Pass


CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)	LIMIT (MHz)	Margin (MHz)
Low	2 412.00	16.33	0.50	15.83
Middle	2 437.00	16.28	0.50	15.78
High 11	2 462.00	16.33	0.50	15.83
High 12	2 467.00	16.33	0.50	15.83
High 13	2 472.00	16.33	0.50	15.83

Remark. Margin = Measured Value - Limit





Middle Channel




High Channel 11

This Report is not correlated with the authentication of KOLAS


It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



High Channel 12



High Channel 13

This Report is not correlated with the authentication of KOLAS

It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)


ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

7.5.2 Test data for Antenna 1

-. Test Result : Pass

CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)	LIMIT (MHz)	Margin (MHz)
Low	2 412.00	16.28	0.50	15.78
Middle	2 437.00	16.28	0.50	15.78
High 11	2 462.00	16.33	0.50	15.83
High 12	2 467.00	16.33	0.50	15.83
High 13	2 472.00	16.33	0.50	15.83

Remark. Margin = Measured Value – Limit




This Report is not correlated with the authentication of KOLAS


It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



Middle Channel




High Channel 11

This Report is not correlated with the authentication of KOLAS


It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



High Channel 12



High Channel 13

This Report is not correlated with the authentication of KOLAS

It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)


7.6 Test data for 802.11n_HT20 WLAN Mode


7.6.1 Test data for Antenna 0

-. Test Result : Pass


CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)	LIMIT (MHz)	Margin (MHz)
Low	2 412.00	17.53	0.50	17.03
Middle	2 437.00	17.53	0.50	17.03
High 11	2 462.00	17.53	0.50	17.03
High 12	2 467.00	17.53	0.50	17.03
High 13	2 472.00	17.53	0.50	17.03

Remark. Margin = Measured Value - Limit





Middle Channel




High Channel 11

This Report is not correlated with the authentication of KOLAS


It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



High Channel 12




High Channel 13


7.6.2 Test data for Antenna 1

-. Test Result : Pass


CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)	LIMIT (MHz)	Margin (MHz)
Low	2 412.00	17.53	0.50	17.03
Middle	2 437.00	17.53	0.50	17.03
High 11	2 462.00	16.93	0.50	16.43
High 12	2 467.00	16.23	0.50	15.73
High 13	2 472.00	17.53	0.50	17.03

Remark. Margin = Measured Value - Limit





Middle Channel




High Channel 11

This Report is not correlated with the authentication of KOLAS


It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



High Channel 12



High Channel 13


This Report is not correlated with the authentication of KOLAS

It should not be reproduced except in full, without the written approval of ONETECH Corp.


OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



Middle Channel




High Channel 9

This Report is not correlated with the authentication of KOLAS


It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



High Channel 10



High Channel 11

This Report is not correlated with the authentication of KOLAS

It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)


ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)


7.7.2 Test data for Antenna 1

-. Test Result : Pass


CHANNEL	FREQUENCY (MHz)	6 dB Bandwidth (MHz)	LIMIT (MHz)	Margin (MHz)
Low	2 422.00	36.46	0.50	35.96
Middle	2 437.00	36.46	0.50	35.96
High 9	2 452.00	36.46	0.50	35.96
High 10	2 457.00	36.46	0.50	35.96
High 11	2 462.00	36.46	0.50	35.96

Remark. Margin = Measured Value - Limit





Middle Channel




High Channel 9

This Report is not correlated with the authentication of KOLAS


It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



High Channel 10



High Channel 11

This Report is not correlated with the authentication of KOLAS

It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

8. MAXIMUM CONDUCTED (AVERAGE) OUTPUT POWER

8.1 Operating environment

Temperature : 23 ° C


Relative humidity : 45 % R.H.

8.2 Test set-up

The maximum peak output power was measured with the wide band sensor connected to the antenna output of the EUT.

The Wide Band Sensor is measured when the EUT is transmitting at the appropriate center frequency its maximum power control level as described in Section 8.3(558074 D01 15.247 Meas Guidance v05r02).

Since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required.



8.3 Test Date

October 07, 2021 ~ October 20, 2021

8.4 Test data for 802.11b WLAN Mode

8.4.1 Test data for Antenna 0

-. Test Result : Pass

-. Duty Cycle : > 98 %

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 412.00	16.69	30.00	13.31
MIDDLE	2 437.00	16.58	30.00	13.42
HIGH 11	2 462.00	16.49	30.00	13.51
HIGH 12	2 467.00	16.42	30.00	13.58
HIGH 13	2 472.00	16.28	30.00	13.72

Remark : Margin = Limit – Measured Value (=Power Sensor Reading + Cable Loss)

8.4.2 Test data for Antenna 1

-. Test Result : Pass

-. Duty Cycle : > 98 %

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 412.00	16.86	30.00	13.14
MIDDLE	2 442.00	17.22	30.00	12.78
HIGH 11	2 462.00	17.48	30.00	12.52
HIGH 12	2 467.00	17.50	30.00	12.50
HIGH 13	2 472.00	17.51	30.00	12.49

Remark : Margin = Limit – Measured Value (=Power Sensor Reading + Cable Loss)

8.5 Test data for 802.11g WLAN Mode

8.5.1 Test data for Antenna 0

-. Test Result : Pass

-. Duty Cycle : > 98 %

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 412.00	12.83	30.00	17.17
MIDDLE	2 442.00	12.80	30.00	17.20
HIGH 11	2 462.00	12.68	30.00	17.32
HIGH 12	2 467.00	12.57	30.00	17.43
HIGH 13	2 472.00	11.68	30.00	18.32

Remark : Margin = Limit – Measured Value (=Power Sensor Reading + Cable Loss)

8.5.2 Test data for Antenna 1

-. Test Result : Pass

-. Duty Cycle : > 98 %

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 412.00	13.75	30.00	16.25
MIDDLE	2 442.00	13.30	30.00	16.70
HIGH 11	2 462.00	12.93	30.00	17.07
HIGH 12	2 467.00	12.83	30.00	17.17
HIGH 13	2 472.00	11.84	30.00	18.16

Remark : Margin = Limit – Measured Value (=Power Sensor Reading + Cable Loss)

8.5.3 Test data for Multiple Transmit

-. Test Result : Pass

-. Duty Cycle : > 98 %

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 412.00	16.32	30.00	13.68
MIDDLE	2 437.00	16.07	30.00	13.93
HIGH 11	2 462.00	15.82	30.00	14.18
HIGH 12	2 467.00	15.71	30.00	14.29
HIGH 13	2 472.00	14.77	30.00	15.23

Remark 1 : Margin = Limit – Measured Value (=Power Sensor Reading + Cable Loss)

Remark 2 : Calculated Output Power= 10log (10(Antenna0 Output Power/10)+10(Antenna1 Output Power/10))

Remark 3 : Directional gain = 10*log[(10G0/20+10G1/20)2/N] dBi

8.6 Test data for 802.11n_HT20 WLAN Mode

8.6.1 Test data for Antenna 0

-. Test Result : Pass

-. Duty Cycle : > 98 %

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 412.00	12.70	30.00	17.30
MIDDLE	2 442.00	12.60	30.00	17.40
HIGH 11	2 462.00	12.51	30.00	17.49
HIGH 12	2 467.00	12.44	30.00	17.56
HIGH 13	2 472.00	11.53	30.00	18.47

Remark : Margin = Limit – Measured Value (=Power Sensor Reading + Cable Loss)

8.6.2 Test data for Antenna 1

-. Test Result : Pass

-. Duty Cycle : > 98 %

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 412.00	13.63	30.00	16.37
MIDDLE	2 437.00	13.17	30.00	16.83
HIGH 11	2 462.00	12.83	30.00	17.17
HIGH 12	2 467.00	12.70	30.00	17.30
HIGH 13	2 472.00	11.79	30.00	18.21

Remark : Margin = Limit – Measured Value (=Power Sensor Reading + Cable Loss)

8.6.3 Test data for Multiple Transmit

-. Test Result : Pass

-. Duty Cycle : > 98 %

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 412.00	16.20	30.00	13.80
MIDDLE	2 437.00	15.90	30.00	14.10
HIGH 11	2 462.00	15.68	30.00	14.32
HIGH 12	2 467.00	15.58	30.00	14.42
HIGH 13	2 472.00	14.67	30.00	15.33

Remark 1 : Margin = Limit – Measured Value (=Power Sensor Reading + Cable Loss)

Remark 2 : Calculated Output Power= $10\log (10^{(\text{Antenna0 Output Power}/10)}+10^{(\text{Antenna1 Output Power}/10)})$

Remark 3 : Directional gain = $10*\log[(10^{G0/20}+10^{G1/20})^2/N]$ dBi

8.7 Test data for 802.11n_HT40 WLAN Mode

8.7.1 Test data for Antenna 0

-. Test Result : Pass

-. Duty Cycle : > 98 %

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 422.00	10.93	30.00	19.07
MIDDLE	2 442.00	10.86	30.00	19.14
HIGH 9	2 452.00	10.83	30.00	19.17
HIGH 10	2 457.00	10.78	30.00	19.22
HIGH 11	2 462.00	10.72	30.00	19.28

Remark : Margin = Limit – Measured Value (=Power Sensor Reading + Cable Loss)

8.7.2 Test data for Antenna 1

-. Test Result : Pass

-. Duty Cycle : > 98 %

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 422.00	11.59	30.00	18.41
MIDDLE	2 437.00	11.31	30.00	18.69
HIGH 9	2 452.00	11.02	30.00	18.98
HIGH 10	2 457.00	10.92	30.00	19.08
HIGH 11	2 462.00	10.75	30.00	19.25

Remark : Margin = Limit – Measured Value (=Power Sensor Reading + Cable Loss)

8.7.3 Test data for Multiple Transmit

-. Test Result : Pass

-. Duty Cycle : > 98 %

CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 422.00	14.28	30.00	15.72
MIDDLE	2 437.00	14.10	30.00	15.90
HIGH 9	2 452.00	13.94	30.00	16.06
HIGH 10	2 457.00	13.86	30.00	16.14
HIGH 11	2 462.00	13.75	30.00	16.25

Remark 1 : Margin = Limit – Measured Value (=Power Sensor Reading + Cable Loss)

Remark 2 : Calculated Output Power= $10\log (10^{(\text{Antenna0 Output Power}/10)}+10^{(\text{Antenna1 Output Power}/10)})$

Remark 3 : Directional gain = $10*\log[(10^{G0/20}+10^{G1/20})^2/N]$ dBi


9. 100 kHz BANDWIDTH OUTSIDE THE FREQUENCY BAND

9.1 Operating environment

Temperature : 23 ° C
Relative humidity : 45 % R.H.

9.2 Test set-up for conducted measurement

The antenna output of the EUT was connected to the spectrum analyzer. The resolution and video bandwidth is set to 100 kHz, and peak detection was used.



9.3 Test set-up for radiated measurement

The radiated emissions measurements were performed on the 3 m semi anechoic chamber. The EUT was placed on turntable approximately 1.5 m above the ground plane.

The frequency spectrum from 30 MHz to 26.5 GHz was scanned and maximum emission levels at each frequency recorded. The system was rotated 360°, and the antenna was varied in the height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for horizontal and vertical polarization of the receiving antenna.


9.4 Test Date

October 07, 2021 ~ October 20, 2021

9.5 Test data for conducted emission

9.5.1 Test data for 802.11b WLAN Mode


9.5.1.1 Test data for Antenna 0




This Report is not correlated with the authentication of KOLAS

It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)



High Channel 11




High Channel 12


This Report is not correlated with the authentication of KOLAS

It should not be reproduced except in full, without the written approval of ONETECH Corp.


OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)







Low Channel



Low Channel



Middle Channel




Middle Channel

This Report is not correlated with the authentication of KOLAS


It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



High Channel 11




High Channel 11

This Report is not correlated with the authentication of KOLAS


It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)


ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)




High Channel 12



High Channel 12



High Channel 13



High Channel 13


This Report is not correlated with the authentication of KOLAS

It should not be reproduced except in full, without the written approval of ONETECH Corp.


OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

9.5.1.2 Test data for Antenna 1



Low Channel




Middle Channel

This Report is not correlated with the authentication of KOLAS


It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)


ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)




High Channel 11




High Channel 12





Low Channel




Low Channel

This Report is not correlated with the authentication of KOLAS


It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



Middle Channel




Middle Channel

This Report is not correlated with the authentication of KOLAS


It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



High Channel 11



High Channel 11