

FCC 15.247& RSS-247 2.4 GHz Test Report

for

Samsung Electronics Co., Ltd.

**129 Samsung-ro, Yeongtong-gu Suwon-Si Gyeonggi-do 16677
Korea (Republic Of)**

Product Name : Wi-Fi/BT Transceiver
Model Name : WCT750M
Brand : SAMSUNG
FCC ID : A3LWCT750M
IC : 649E-WCT750M

**Prepared by: : AUDIX Technology Corporation,
EMC Department**



The test report is based on a single evaluation of one sample of the above-mentioned products. It does not imply an assessment of the whole production and does not permit the use of the test lab logo. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

TABLE OF CONTENTS

Description	Page
TEST REPORT CERTIFICATION.....	4
1. REVISION RECORD OF TEST REPORT	5
2. SUMMARY OF TEST RESULTS	6
3. GENERAL INFORMATION	7
3.1. Description of Application	7
3.2. Description of EUT	8
3.3. Antenna Information	10
3.4. EUT Specifications Assessed in Current Report	12
3.5. Description of Key Components	12
3.6. Test Configuration	13
3.7. Tested Supporting System List	15
3.8. Setup Configuration	15
3.9. Operating Condition of EUT	15
3.10. Description of Test Facility	16
3.11. Measurement Uncertainty	17
4. MEASUREMENT EQUIPMENT LIST	19
4.1. Conducted Emission Measurement	19
4.2. Radiated Emission Measurement	20
4.3. RF Conducted Measurement	20
5. CONDUCTED EMISSION	21
5.1. Block Diagram of Test Setup	21
5.2. Conducted Emission Limit	21
5.3. Test Procedure	21
5.4. Test Results	22
6. RADIATED EMISSION	23
6.1. Block Diagram of Test Setup	23
6.2. Radiated Emission Limits	24
6.3. Test Procedure	25
6.4. Measurement Result Explanation	26
6.5. Test Results	26
7. 20dB BANDWIDTH	27
7.1. Block Diagram of Test Setup	27
7.2. Specification Limits	27
7.3. Test Procedure	27
7.4. Test Results	27
8. CARRIER FREQUENCY SEPARATION	28
8.1. Block Diagram of Test Setup	28
8.2. Specification Limits	28
8.3. Test Procedure	28
8.4. Test Results	28
9. TIME OF OCCUPANCY	29
9.1. Block Diagram of Test Setup	29
9.2. Specification Limits	29
9.3. Test Procedure	29



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

9.4. Test Results	29
10. NUMBER OF HOPPING CHANNELS	30
10.1. Block Diagram of Test Setup	30
10.2. Specification Limits.....	30
10.3. Test Procedure	30
10.4. Test Results	30
11. MAXIMUM PEAK OUTPUT POWER	31
11.1. Block Diagram of Test Setup	31
11.2. Specification Limits.....	31
11.3. Test Procedure	31
11.4. Test Results	31
12. EMISSION LIMITATIONS	32
12.1. Block Diagram of Test Setup	32
12.2. Specification Limits.....	32
12.3. Test Procedure	32
12.4. Test Results	32
13. DEVIATION TO TEST SPECIFICATIONS	33

APPENDIX A TEST DATA AND PLOTS
APPENDIX B TEST PHOTOGRAPHS



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

TEST REPORT CERTIFICATION

Applicant : Samsung Electronics Co., Ltd.
Manufacturer : Samsung Electronics Co., Ltd.
Factory : Chengdu Xuguang Technology Co., Ltd.
EUT Description
(1) Product : Wi-Fi/BT Transceiver
(2) Model : WCT750M
(3) Brand : SAMSUNG
(4) Power Rating : DC 5V

Applicable Standards:

47 CFR FCC Part 15 Subpart C
RSS-Gen (Issue 5), April 2018
RSS-247 (Issue 2), February 2017
ANSI C63.10:2013

Audix Technology Corp. tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report.

Audix Technology Corp. does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens and samples.

Date of Report: 2019. 12. 16

Reviewed by:

(Annie Yu/Administrator)

Approved by:

(Johnny Hsueh/Section Manager)



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

1. REVISION RECORD OF TEST REPORT

Edition No	Issued Date	Revision Summary	Report Number
0	2019. 12. 16	Original Report	EM-F190493

2. SUMMARY OF TEST RESULTS

Rule		Description	Results
FCC	IC		
15.207	RSS-Gen §8.8	Conducted Emission	PASS
15.247(d)/15.205	RSS-Gen §8.9 RSS-247 §5.5	Radiated Band Edge and Radiated Spurious Emission	PASS
15.247(a)(1)	RSS-247 §5.1(2)	20dB Bandwidth	PASS
15.247(a)(1)	RSS-247 §5.1(2)	Carrier Frequency Separation	PASS
15.247(a)(1)(iii)	RSS-247 §5.1(4)	Time of Occupancy	PASS
15.247(a)(1)(iii)	RSS-247 §5.1(4)	Number of Hopping Channels	PASS
15.247(b)(1)	RSS-247 §5.1(2)	Maximum Peak Output Power	PASS
15.247(d)	RSS-247 §5.5	Conducted Band Edges and Conducted Spurious Emission	PASS
15.203	RSS-Gen §6.8	Antenna Requirement	Compliance
Note: The uncertainties value is not used in determining the result.			

3. GENERAL INFORMATION

3.1. Description of Application

Applicant	Samsung Electronics Co., Ltd. 129 Samsung-ro, Yeongtong-gu Suwon-Si Gyeonggi-do 16677 Korea (Republic Of)
Manufacturer	Samsung Electronics Co., Ltd. 129 Samsung-ro, Yeongtong-gu Suwon-Si Gyeonggi-do 16677 Korea (Republic Of)
Factory	Chengdu Xuguang Technology Co., Ltd. No. 86 2 nd Section, Park Road, Longquanyi District, Chengdu City, Sichuan Province, P.R China
Product	Wi-Fi/BT Transceiver The EUT has two chipsets (MT7668AUN and MT7915DUN).
Model	WCT750M
Brand	SAMSUNG

3.2. Description of EUT

Test Model	WCT750M																																														
Serial Number	N/A																																														
Power Rating	DC 5V																																														
RF Features	Chipset: MT7668AUN WLAN: 802.11 a/b/g/n/ac Bluetooth: BT and BLE (BT 5.0) Chipset: MT7915DUN WLAN: 802.11 a/b/g/n/ac/ax																																														
Transmit Type	Chipset: MT7668AUN <table border="1"> <thead> <tr> <th colspan="2">2.4 GHz</th> </tr> </thead> <tbody> <tr> <td>802.11b</td><td>2T2R</td> </tr> <tr> <td>802.11g</td><td>2T2R</td> </tr> <tr> <td>802.11n-HT20</td><td>2T2R</td> </tr> <tr> <td>802.11n-HT40</td><td>2T2R</td> </tr> <tr> <td>BT/BLE</td><td>1T1R</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th colspan="2">UNII Bands</th> </tr> </thead> <tbody> <tr> <td>802.11a</td><td>2T2R</td> </tr> <tr> <td>802.11n-HT20/802.11ac-VHT20</td><td>2T2R</td> </tr> <tr> <td>802.11n-HT40/802.11ac-VHT40</td><td>2T2R</td> </tr> <tr> <td>802.11ac-VHT80</td><td>2T2R</td> </tr> </tbody> </table> Chipset: MT7915DUN <table border="1"> <thead> <tr> <th colspan="2">2.4 GHz</th> </tr> </thead> <tbody> <tr> <td>802.11b</td><td>2T2R</td> </tr> <tr> <td>802.11g</td><td>2T2R</td> </tr> <tr> <td>802.11n-HT20</td><td>2T2R</td> </tr> <tr> <td>802.11n-HT40</td><td>2T2R</td> </tr> <tr> <td>802.11ax-HE20</td><td>2T2R</td> </tr> <tr> <td>802.11ax-HE40</td><td>2T2R</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th colspan="2">UNII Bands</th> </tr> </thead> <tbody> <tr> <td>802.11a</td><td>2T2R</td> </tr> <tr> <td>802.11n-HT20/802.11ac-VHT20/802.11ax-HE20</td><td>2T2R</td> </tr> <tr> <td>802.11n-HT40/802.11ac-VHT40/802.11ax-HE40</td><td>2T2R</td> </tr> <tr> <td>802.11ac-VHT80/802.11ax-HE80</td><td>2T2R</td> </tr> </tbody> </table>	2.4 GHz		802.11b	2T2R	802.11g	2T2R	802.11n-HT20	2T2R	802.11n-HT40	2T2R	BT/BLE	1T1R	UNII Bands		802.11a	2T2R	802.11n-HT20/802.11ac-VHT20	2T2R	802.11n-HT40/802.11ac-VHT40	2T2R	802.11ac-VHT80	2T2R	2.4 GHz		802.11b	2T2R	802.11g	2T2R	802.11n-HT20	2T2R	802.11n-HT40	2T2R	802.11ax-HE20	2T2R	802.11ax-HE40	2T2R	UNII Bands		802.11a	2T2R	802.11n-HT20/802.11ac-VHT20/802.11ax-HE20	2T2R	802.11n-HT40/802.11ac-VHT40/802.11ax-HE40	2T2R	802.11ac-VHT80/802.11ax-HE80	2T2R
2.4 GHz																																															
802.11b	2T2R																																														
802.11g	2T2R																																														
802.11n-HT20	2T2R																																														
802.11n-HT40	2T2R																																														
BT/BLE	1T1R																																														
UNII Bands																																															
802.11a	2T2R																																														
802.11n-HT20/802.11ac-VHT20	2T2R																																														
802.11n-HT40/802.11ac-VHT40	2T2R																																														
802.11ac-VHT80	2T2R																																														
2.4 GHz																																															
802.11b	2T2R																																														
802.11g	2T2R																																														
802.11n-HT20	2T2R																																														
802.11n-HT40	2T2R																																														
802.11ax-HE20	2T2R																																														
802.11ax-HE40	2T2R																																														
UNII Bands																																															
802.11a	2T2R																																														
802.11n-HT20/802.11ac-VHT20/802.11ax-HE20	2T2R																																														
802.11n-HT40/802.11ac-VHT40/802.11ax-HE40	2T2R																																														
802.11ac-VHT80/802.11ax-HE80	2T2R																																														
Software Version	N/A																																														



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Sample Status	Mass production
Date of Receipt	2019. 11. 19
Date of Test	2019. 11. 26 ~ 12.13
Interface Ports of EUT	None
Accessories Supplied	None

3.3. Antenna Information

Chipset: MT7668AUN					
No.	Antenna Part Number	Manufacture	Antenna Type	Frequency (MHz)	Max Gain (dBi)
1.	WA-P-LALBLB-12-001 (WiFi 1)	INPAQ	Pattern Antenna	2400	-6.07
				2425	-4.16
				2450	-3.06
				2485	-6.29
				5150	-2.28
				5250	-4.15
				5350	-6.35
				5450	-5.62
				5550	2.22
				5650	-1.03
				5750	-6.66
				5850	-8.24
2.	WA-P-LALBLB-12-001 (WiFi 2)	INPAQ	Pattern Antenna	2400	-10.56
				2425	-10.64
				2450	-9.74
				2485	-13.08
				5150	-5.32
				5250	-4.92
				5350	-5.89
				5450	-7.83
				5550	-8.29
				5650	-3.72
				5750	0.79
				5850	-5.95
3	WA-P-LALBLB-12-001 (BT)	INPAQ	Pattern Antenna	2400	-10.18
				2425	-8.43
				2450	-4.74
				2480	-3.57

Chipset: MT7915DUN					
No.	Antenna Part Number	Manufacture	Antenna Type	Frequency (MHz)	Max Gain (dBi)
1.	WA-P-LBLB-04-075 (WiFi 3)	INPAQ	Pattern Antenna	2400	-2.86
				2425	-3.93
				2450	-3.69
				2485	-3.67
				5150	-3.20
				5250	-4.57
				5350	-0.06
				5450	-2.23
				5550	-2.99
				5650	-4.01
				5750	-1.21
				5850	-6.05
2.	WA-P-LBLB-04-075 (WiFi 4)	INPAQ	Pattern Antenna	2400	-10.13
				2425	-8.11
				2450	-7.48
				2485	-9.23
				5150	-4.94
				5250	-8.03
				5350	-4.95
				5450	-3.44
				5550	-4.92
				5650	-3.48
				5750	-7.84
				5850	-4.78

3.4. EUT Specifications Assessed in Current Report

Mode	Fundamental Range (MHz)	Channel Number	Modulation	Data Rate (Mbps)
Bluetooth	2402-2480	79	FHSS (GFSK, $\pi/4$ DQPSK, 8-DPSK)	1/2/3

Channel List							
Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)
00	2402	20	2422	40	2442	60	2462
01	2403	21	2423	41	2443	61	2463
02	2404	22	2424	42	2444	62	2464
03	2405	23	2425	43	2445	63	2465
04	2406	24	2426	44	2446	64	2466
05	2407	25	2427	45	2447	65	2467
06	2408	26	2428	46	2448	66	2468
07	2409	27	2429	47	2449	67	2469
08	2410	28	2430	48	2450	68	2470
09	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.5. Description of Key Components


None

3.6. Test Configuration

Mode	TX _{on} (ms)	TX _{on+off} (ms)	1/ TX _{on} (kHz)	Duty Cycle Correction Factor (DCCF) (dB)
GFSK	2.880	100	0.347	-30.81
8-DPSK	2.880	100	0.347	-30.81

Note: Duty Cycle Correction Factor (DCCF)= 20log(TX_{on}/100ms)

“TX_{on+off}” means the period of the pulse train or 100ms if the pulse train length is greater than 100ms



AC Conduction
Normal operation

Item		Modulation	Data Rate	Test Channel
Radiated Test Case	Radiated Band Edge ^{Note1}	GFSK	1Mbps	00/78
		8-DPSK	3Mbps	00/78
	Radiated Spurious Emission ^{Note1}	GFSK	1Mbps	00/39/78
Conducted Test Case	20dB Bandwidth	GFSK	1Mbps	00/39/78
		8-DPSK	3Mbps	00/39/78
	Carrier Frequency Separation	GFSK	1Mbps	00/39/78
		8-DPSK	3Mbps	00/39/78
	Time of Occupancy	GFSK	1Mbps	00/39/78
		8-DPSK	3Mbps	00/39/78
	Number of Hopping Channels	GFSK	1Mbps	39
		8-DPSK	3Mbps	39
	Maximum Peak Output Power	GFSK	1Mbps	00/39/78
		8-DPSK	3Mbps	00/39/78
	Band Edges	GFSK	1Mbps	00/78
		8-DPSK	3Mbps	00/78
	Spurious Emission	GFSK	1Mbps	00/39/78
		8-DPSK	3Mbps	00/39/78

Note 1: ☐ Mobile Device

☒ Portable Device, and 3 axis were assessed. The worst scenario for Radiated Spurious Emission as follow: ☒ Lie ☐ Side ☐ Stand

Note 2: We performed testing of the highest and lowest data rate.

3.7. Tested Supporting System List

3.7.1. Support Peripheral Unit

No.	Product	Brand	Model No.	Serial No.	Approval
1.	Notebook PC	ASUS	X5502E	N/A	Contains FCC ID: PPD-AAR5B225
2.	Test JIG	N/A	N/A	N/A	N/A

3.7.2. Cable Lists

No.	Cable Description Of The Above Support Units
1.	Adapter: Chicony, M/N CPA09-A065N1, DC Cord : Shielded, Undetachable, 1.8m, Bonded a ferrite core AC Power Cord : Unshielded, Detachable, 1.8m
2.	Bus→USB Cable: Unshielded, detachable, 0.2m*2

3.8. Setup Configuration

3.8.1. EUT Configuration for Power Line & Radiated Emission

TEST JIG	EUT
----------	-----

3.8.2. EUT Configuration for RF Conducted Test Items

TEST JIG	EUT
----------	-----

3.9. Operating Condition of EUT

Test program “WCN Combo Tool” is used for enabling BT function under continues transmitting and choosing data rate/ channel.

3.10. Description of Test Facility

Name of Test Firm	Audix Technology Corporation / EMC Department No. 53-11, Dingfu, Linkou Dist., New Taipei City 244, Taiwan Tel: +886-2-26092133 Fax: +886-2-26099303 Website : www.audixtech.com Contact e-mail: attemc_report@audixtech.com
Accreditations	The laboratory is accredited by following organizations under ISO/IEC 17025:2017 (1) NVLAP(USA) NVLAP Lab Code 200077-0 (2) TAF(Taiwan) No. 1724
Test Facilities	FCC OET Designation Number under APEC MRA by NCC is : TW1724 ISED CAB Identifier Number under APEC TEL MRA by NCC is TW1724 (1) No.8 Shielded Room (2) No.1 3m Semi Anechoic Chamber (3) Fully Anechoic Chamber

3.11.Measurement Uncertainty

Test Items/Facilities		Frequency Range	Uncertainty
Conduction Test		150kHz~30MHz	±3.50dB
Radiation Test	No.1 3m Semi Anechoic Chamber	30MHz-200MHz, 3m, Horizontal	±3.9dB
		200MHz-1000MHz, 3m, Horizontal	±4.3dB
		30MHz-200MHz, 3m, Vertical	±4.5dB
		200MHz-1000MHz, 3m, Vertical	±4.1dB
		1GHz-6GHz, 3m	±5.1dB
		6GHz-18GHz, 3m	±5.5dB
	No.3 3m Semi Anechoic Chamber	30MHz-200MHz, 3m, Horizontal	±4.7dB
		200MHz-1000MHz, 3m, Horizontal	±4.5dB
		30MHz-200MHz, 3m, Vertical	±4.3dB
		200MHz-1000MHz, 3m, Vertical	±4.1dB
	No.4 3m Semi Anechoic Chamber	30MHz-200MHz, 3m, Horizontal	±4.1dB
		200MHz-1000MHz, 3m, Horizontal	±4.4dB
		30MHz-200MHz, 3m, Vertical	±4.2dB
		200MHz-1000MHz, 3m, Vertical	±5.0dB
		1GHz-6GHz, 3m	±4.4dB
		6GHz-18GHz, 3m	±4.1dB
	No.5 3m Semi Anechoic Chamber	30MHz-200MHz, 3m, Horizontal	±4.0dB
		200MHz-1000MHz, 3m, Horizontal	±4.0dB
		30MHz-200MHz, 3m, Vertical	±4.2dB
		200MHz-1000MHz, 3m, Vertical	±4.4dB
		1GHz-6GHz, 3m	±4.3dB
		6GHz-18GHz, 3m	±4.6dB
	No.2 10m Semi Anechoic Chamber	30MHz-200MHz, 3m, Horizontal	±4.3dB
		200MHz-1000MHz, 3m, Horizontal	±4.3dB
		30MHz-200MHz, 3m, Vertical	±4.1dB
		200MHz-1000MHz, 3m, Vertical	±4.4dB
		1GHz-6GHz, 3m	±4.2dB
		6GHz-18GHz, 3m	±4.3dB
	Fully Anechoic Chamber	30MHz~1000MHz	±4.7dB
		1GHz~18GHz	±5.3dB

Remark : Uncertainty = $ku_c(y)$



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Test Item	Uncertainty
20dB Bandwidth	$\pm 0.2\text{kHz}$
Carrier Frequency Separation	$\pm 0.2\text{kHz}$
Time of Occupancy	$\pm 0.03\text{sec}$
Maximum peak Output power	$\pm 0.52\text{dB}$
Conducted Emission Limitations	$\pm 0.13\text{dB}$



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

4. MEASUREMENT EQUIPMENT LIST

4.1. Conducted Emission Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Test Receiver	R&S	ESR3	101774	2019. 01. 23	1 Year
2.	A.M.N.	R&S	ENV4200	100169	2019. 11. 13	1 Year
3.	L.I.S.N.	Kyoritsu	KNW-407	8-855-9	2019. 12. 10	1 Year
4.	Pulse Limiter	R&S	ESH3-Z2	100354	2019. 01. 12	1 Year
5.	Digital Thermo-Hygro Meter	iMax	HTC-1	No.8 S/R	2019. 04. 20	1 Year
6.	Test Software	Audix	e3	V6.120619c	N.C.R.	N.C.R.

4.2. Radiated Emission Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A-526	MY53400071	2019. 09. 11	1 Year
2.	Spectrum Analyzer	Keysight	N9010B-544	MY55460198	2019. 05. 06	1 Year
3.	Test Receiver	R & S	ESCS30	100338	2019. 06. 12	1 Year
4.	Amplifier	HP	8447D	2944A06305	2019. 01. 30	1 Year
5.	Amplifier	HP	8449B	3008A02678	2019. 03. 07	1 Year
6.	Amplifier	Keysight	83051A	MY53010042	2019. 08. 08	1 Year
7.	Bilog Antenna	TESEQ	CBL6112D	33821	2019. 01. 19	1 Year
8.	Loop Antenna	R&S	HFH2-Z2	891847/27	2017.12. 18	2 Years
9	Double-Ridged Waveguide Horn	ETS-Lindgren	3117	00135902	2019. 03. 13	1 Year
10.	Horn Antenna	COM-POWER	AH-840	101092	2019. 05. 14	1 Year
11.	2.4GHz Notch Filter	K&L	7NSL10-244 1.5/E130.5-O /O	1	2019. 07. 24	1 Year
12.	3GHz Notch Filter	Microwave	H3G018G1	484796	2019. 08. 21	1 Year
13.	Coaxial Cable	MIYAZAKI	5D2W	RE-11	2019. 02. 01	1 Year
14.	Coaxial Cable	HUBER+SUHNER	SUCOFLEX 104	RF CABLE-01	2019. 09. 20	1 Year
15.	Coaxial Cable	HUBER+SUHNER	SUCOFLEX 102	No.1 18-40GHz Cable	2019. 02. 01	1 Year
16.	Digital Thermo-Hygro Meter	iMax	HTC-1	No.1 3m A/C	2019. 04. 20	1 Year
17.	Digital Thermo-Hygro Meter	EVERY DAY	E-512	RF-02	2019. 04. 20	1 Year
18.	Test Software	Audix	e3	V6.120619c	N.C.R.	N.C.R.
19.	Test Software	Audix	e3	V6.110601	N.C.R.	N.C.R.

4.3. RF Conducted Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Keysight	N9020B-544	MY57120357	2019. 01. 17	1 Year
2.	Power Meter	Anritsu	ML2487A	6K00005406	2019. 05. 02	1 Year
3.	Power Meter	Anritsu	ML2495A	1145008	2019. 11. 06	1 Year
4.	Power Sensor	Anritsu	MA2491A	030873	2019. 05. 02	1 Year
5.	Power Sensor	Anritsu	MA2411B	1126096	2019. 11. 06	1 Year
6.	Digital Thermo-Hygro Meter	Shenzhen Datronn Electronics	KT-905	RF	2019. 04. 20	1 Year


5. CONDUCTED EMISSION

5.1. Block Diagram of Test Setup

5.1.1. Block Diagram of EUT

Indicated as section 3.8

5.1.2. Shielded Room Setup Diagram



5.2. Conducted Emission Limit

Frequency	Conducted Limit	
	Quasi-Peak Level	Average Level
150kHz ~ 500kHz	66 ~ 56 dB μ V	56 ~ 46 dB μ V
500kHz ~ 5MHz	56 dB μ V	46 dB μ V
5MHz ~ 30MHz	60 dB μ V	50 dB μ V

Remark1.: If the average limit is met when using a Quasi-Peak detector, the measurement using the average detector is not required.

2.: The lower limit applies to the band edges.

5.3. Test Procedure

- 5.3.1. To set up the EUT as indicated in ANSI C 63.10. The EUT was placed on the table which has 80 cm height to the ground and 40 cm distance to the conducting wall.
- 5.3.2. Power supplier of the EUT was connected to the AC mains through an Artificial Mains Network (A.M.N.).
- 5.3.3. The AC power supplies to all peripheral devices must be provided through line impedance stabilization network (L.I.S.N.)
- 5.3.4. Checking frequency range from 150kHz to 30 MHz and record the emission which does not have 20 dB below limit.



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

5.4. Test Results

Please refer to Appendix A.


6. RADIATED EMISSION

6.1. Block Diagram of Test Setup


6.1.1. Block Diagram of EUT

Indicated as section 3.8


6.1.2. Setup Diagram for 9kHz-30MHz



6.1.3. Setup Diagram for 30-1000MHz



6.1.4. Setup Diagram for above 1GHz



6.2. Radiated Emission Limits

In any 100kHz bandwidth outside the frequency band, the radio frequency power produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level. In addition, radiated emissions which fall in restricted bands, as defined in Section 15.205/RSS-Gen Section 8.10 table 6, must also comply with the radiated emission limits specified as below.

Frequency (MHz)	Distance(m)	Limits	
		dBμV/m	μV/m
0.009 - 0.490	300	67.6-20 log f(kHz)	2400/f kHz
0.490 - 1.705	30	87.6-20 log f(kHz)	24000/f kHz
1.705 - 30	30	29.5	30
30 - 88	3	40.0	100
88- 216	3	43.5	150
216- 960	3	46.0	200
Above 960	3	54.0	500
Above 1000	3	74.0 dBμV/m (Peak) 54.0 dBμV/m (Average)	

Remark : (1) $\text{dB}\mu\text{V/m} = 20 \log (\mu\text{V/m})$

- (2) The tighter limit applies to the edge between two frequency bands.
- (3) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- (4) Fundamental and emission fall within operation band are exempted from this section.
- (5) Pursuant to ANSI C63.10: 6.6.4.3, if the maximized peak measured value complies with the average limit, then it is unnecessary to perform an average measurement.

6.3. Test Procedure

Frequency Range 9kHz~30MHz:

The EUT setup on the turntable which has 0.8 m height to the ground. The turn table rotated 360 degrees and antenna fixed to 1 m to find the maximum emission level. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2013 regulation.

- (1) RBW = 9kHz with peak and average detector.
- (2) Detector: average and peak (9kHz-490kHz)
Q.P. (490kHz-30MHz)

Frequency Range 30MHz ~ 25GHz:

The EUT setup on the turn table which has 80 cm (for 30-1000 MHz) and 1.5m (for above 1GHz) height to the ground. The turn table rotated 360 degrees and antenna varied from 1 m to 4 m (for 30-1000MHz) or antenna varied from 1 m to 3 m (for above 1GHz) to find the maximum emission level. Both horizontal and vertical polarization are required. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2013 regulation.

Frequency below 1GHz:

Spectrum Analyzer is used for pre-testing with following setting:

- (1) RBW = 120KHz
- (2) VBW $\geq 3 \times$ RBW.
- (3) Detector = Peak.
- (4) Sweep time = auto.
- (5) Trace mode = max hold.
- (6) Allow sweeps to continue until the trace stabilizes.

Note 1: When peak-detected value is lower than limit that the measurement using the Q.P. detector is not required, otherwise using Q.P. for final measurement.

Note 2: When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds.

Frequency above 1GHz to 10th harmonic(up to 25 GHz):

Peak Detector:

- (1) RBW = 1MHz
- (2) VBW $\geq 3 \times$ RBW.
- (3) Detector = Peak.
- (4) Sweep time = auto.
- (5) Trace mode = max hold.
- (6) Allow sweeps to continue until the trace stabilizes.

Note: When peak-detected value is lower than limit that the measurement using the average detector is not required, otherwise using average detector for final measurement.

Average Detector:☐ **Option 1:**

- (1) RBW = 1MHz
- (2) VBW $\geq 1/T$.
- (3) Detector = Peak.
- (4) Sweep time = auto.
- (5) Trace mode = max hold.
- (6) Allow sweeps to continue until the trace stabilizes.

☒ **Option 2:**

Average Emission Level = Peak Emission Level + D.C.C.F.

6.4. Measurement Result Explanation

☒ Peak Emission Level = Antenna Factor + Cable Loss + Meter Reading (including Preamp factor if test used)

☐ Average Emission Level = Antenna Factor + Cable Loss + Meter Reading (including Preamp factor if test used)

☒ Average Emission Level = Peak Emission Level + DCCF

Duty Cycle Correction Factor (DCCF) = $20\log(TX_{on}/TX_{on+off})$ presented in section 3.6


☐ ERP = Peak Emission Level - 95.2dB - 2.14dB (or Actual Gain)

6.5. Test Results

Please refer to Appendix A.

7. 20dB BANDWIDTH

7.1. Block Diagram of Test Setup



7.2. Specification Limits

Alternatively, frequency hopping systems operating in the 2400-2483.5MHz band may have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

7.3. Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:


- (1) Set RBW close to 1% to 5% of OBW.
- (2) Set $VBW \geq 3 \times RBW$.
- (3) Detector = Peak.
- (4) Trace mode = Max hold.
- (5) Sweep = Auto couple.
- (6) Allow the trace to stabilize.
- (7) Setting channel bandwidth function x dB to -20 dB to record the final bandwidth.

7.4. Test Results

Please refer to Appendix A

8. CARRIER FREQUENCY SEPARATION

8.1. Block Diagram of Test Setup



8.2. Specification Limits

Alternatively, frequency hopping systems operating in the 2400-2483.5MHz band may have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output no greater than 125mW.

8.3. Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:


- (1) Span = Wide enough to capture the peaks of two adjacent channels
- (2) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- (3) VBW $\geq$ RBW
- (4) Sweep = Auto
- (5) Detector function = Peak
- (6) Trace = Max hold
- (7) Allow the trace to stabilize.

8.4. Test Results

Please refer to Appendix A

9. TIME OF OCCUPANCY

9.1. Block Diagram of Test Setup



9.2. Specification Limits

Frequency hopping systems in the 2400-2483.5MHz shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by number of hopping channels employed.

9.3. Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:


- (1) Span: Zero span, centered on a hopping channel.
- (2) RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1/T$, where T is the expected dwell time per channel.
- (3) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- (4) Detector function = Peak
- (5) Trace = Max hold

9.4. Test Results

Please refer to Appendix A

10. NUMBER OF HOPPING CHANNELS

10.1. Block Diagram of Test Setup



10.2. Specification Limits

Frequency hopping systems which use fewer than 20 hopping frequencies may employ intelligent hopping techniques to avoid interference to other transmissions. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 non-overlapping channels.

10.3. Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:


- (1) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- (2) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- (3) VBW $\geq$ RBW
- (4) Sweep = Auto
- (5) Detector function = Peak
- (6) Trace = m=Max hold
- (7) Allow the trace to stabilize.

10.4. Test Results

Please refer to Appendix A

11. MAXIMUM PEAK OUTPUT POWER

11.1. Block Diagram of Test Setup



11.2. Specification Limits

The Limits of maximum Peak Output Power for frequency hopping systems in 2400-2483.5MHz is: 0.125Watt. (21dBm)

11.3. Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:


- (a) Use the following spectrum analyzer settings
 - (1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - (2) RBW > 20 dB bandwidth of the emission being measured.
 - (3) VBW $\geq$ RBW
 - (4) Sweep: Auto
 - (5) Detector function: Peak
 - (6) Trace: Max hold
- (b) Allow trace to stabilize.
- (c) Use the marker-to-peak function to set the marker to the peak of the emission.

11.4. Test Results

Please refer to Appendix A

12. EMISSION LIMITATIONS

12.1. Block Diagram of Test Setup



12.2. Specification Limits

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, that the required attenuation shall be 30 dB instead of 20 dB.

Attenuation below the general limits specified in Section 15.209(a)/RSS-Gen Section 8.9 table 4 is not required. In addition, radiated emissions which fall in restricted bands, as defined in Section 15.205(a)/RSS-Gen Section 8.10 table 6, must also comply with the radiated emission limits specified in Section 15.209(a)/RSS-Gen Section 8.9 table 4 (See Section 15.205(c)).

12.3. Test Procedure

Following measurement procedure is reference to ANSI C63.10:2013:

- (1) Set span wide enough to capture the peak level of the in-band emission and all spurious emissions; up to 10th harmonic.
- (2) RBW = 100 kHz
- (3) VBW ≥ RBW
- (4) Sweep = Auto
- (5) Detector function = Peak
- (6) Trace = Max hold

12.4. Test Results

Please refer to Appendix A



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

13.DEVIATION TO TEST SPECIFICATIONS

【NONE】



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

APPENDIX A

Tel: +886 2 26099301
Fax: +886 2 26099303

APPDNDIX A

TEST DATA AND PLOTS

(Model: WCT750M)

TABLE OF CONTENTS

A.1 CONDUCTED EMISSION	2
A.2 RADIATED EMISSION	4
A.2.1 Emissions within Restricted Frequency Bands.....	4
A.2.2 Emissions outside the frequency band:.....	13
A.2.3 Emissions in Non-restricted Frequency Bands:.....	13
A.3 20dB BANDWIDTH	14
A.3.1 6dB Bandwidth Result.....	14
A.3.2 Measurement Plots	15
A.4 CARRIER FREQUENCY SEPARATION	16
A.5 TIME OF OCCUPANCY.....	18
A.5.1 Time of Occupancy	18
A.6 NUMBER OF HOPPING CHANNELS	28
A.7 MAXIMUM PEAK OUTPUT POWER	29
A.7.1 Maximum Peak Output Power.....	29
A.7.2 Measurement Plots	30
A.8 EMISSION LIMITATIONS MEASUREMENT	31
A.8.1 Band Edge.....	31
A.8.2 Spurious Emission	33


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

A.1 CONDUCTED EMISSION

Test Date	2019/12/13	Temp./Hum.	23°C/55%
Test Voltage	DC 5V (via Test JIG)	Tested By	Chucky Chiu

Data: 8 File: \\nas-server\01測試組\01-01 測試組公用\01-01b TEST & PHOTO\2019\C1M1911XX



Site no. : No.8 Shielded Room Data no. : 8
Condition : ENV4200 (169) (A) LISN Phase : NEUTRAL
Limit : FCC PART 15C
Env. / Ins. : 23°C / 55% ESR3 (1774) Engineer : Chucky Chiu
EUT : WCT750M(MT7668)
Power Rating : DC 5V(VIA USB)
Test Mode : Operating

	Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Pulse Att. (dB)	Reading (dBμV)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
1	0.170	10.70	0.04	9.86	18.84	39.44	54.94	15.50	Average
2	0.170	10.70	0.04	9.86	32.81	53.41	64.94	11.53	QP
3	0.212	10.64	0.04	9.86	14.17	34.71	53.14	18.43	Average
4	0.212	10.64	0.04	9.86	29.13	49.67	63.14	13.47	QP
5	0.469	10.52	0.04	9.86	11.09	31.51	46.54	15.03	Average
6	0.469	10.52	0.04	9.86	22.55	42.97	56.54	13.57	QP
7	0.876	10.50	0.05	9.86	5.65	26.06	46.00	19.94	Average
8	0.876	10.50	0.05	9.86	14.28	34.69	56.00	21.31	QP
9	3.840	10.67	0.09	9.87	3.96	24.59	46.00	21.41	Average
10	3.840	10.67	0.09	9.87	10.59	31.22	56.00	24.78	QP
11	22.775	14.50	0.21	9.97	5.69	30.37	50.00	19.63	Average
12	22.775	14.50	0.21	9.97	10.19	34.87	60.00	25.13	QP


Remarks: 1. Emission Level= AMN Factor + Cable Loss + Pulse Att. + Reading.
2. If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Test Date	2019/12/13	Temp./Hum.	23°C/55%
Test Voltage	DC 5V (via Test JIG)	Tested By	Chucky Chiu

Data: 7 File: \\nas-server\01測試組\01-01 測試組公用\01-01b TEST & PHOTO\2019\CI1M1911XX



Site no. : No.8 Shielded Room Data no. : 7
Condition : ENV4200 (169)(A) LISN Phase : LINE
Limit : FCC PART 15C
Env. / Ins. : 23°C / 55% ESR3 (1774) Engineer : Chucky Chiu
EUT : WCT750M(MT7668)
Power Rating : DC 5V(VIA USB)
Test Mode : Operating

	Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Pulse Att. (dB)	Reading (dBμV)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
1	0.166	10.66	0.04	9.86	19.15	39.71	55.16	15.45	Average
2	0.166	10.66	0.04	9.86	33.51	54.07	65.16	11.09	QP
3	0.212	10.60	0.04	9.86	19.46	39.96	53.14	13.18	Average
4	0.212	10.60	0.04	9.86	30.31	50.81	63.14	12.33	QP
5	0.431	10.49	0.04	9.86	10.55	30.94	47.24	16.30	Average
6	0.431	10.49	0.04	9.86	20.44	40.83	57.24	16.41	QP
7	0.474	10.49	0.04	9.86	12.29	32.68	46.45	13.77	Average
8	0.474	10.49	0.04	9.86	22.75	43.14	56.45	13.31	QP
9	4.006	10.61	0.09	9.87	6.59	27.16	46.00	18.84	Average
10	4.006	10.61	0.09	9.87	13.83	34.40	56.00	21.60	QP
11	22.180	13.89	0.20	9.96	5.55	29.60	50.00	20.40	Average
12	22.180	13.89	0.20	9.96	10.63	34.68	60.00	25.32	QP

Remarks: 1. Emission Level= AMN Factor + Cable Loss + Pulse Att. + Reading.
2. If the average limit is met when using a quasi-peak detector,
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.

A.2 RADIATED EMISSION

Test Date	2019/12/12 ~ 13	Temp./Hum.	22 ~ 23°C / 54 ~ 56%
Test Voltage	DC 5V (via Test JIG)	Tested By	Kuper Hsu

A.2.1 Emissions within Restricted Frequency Bands

A.2.1.1 Frequency 9kHz~30MHz

The emissions (9kHz~30MHz) not reported for there is no emission be found.

A.2.1.2 Frequency Below 1 GHz

Mode	GFSK	Frequency	TX 2441MHz
------	------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
77.53	13.25	2.00	17.73	32.98	40.00	7.02	Peak
123.12	18.46	2.57	9.94	30.97	43.50	12.53	Peak
182.29	15.52	3.25	14.61	33.38	43.50	10.12	Peak
238.55	18.26	3.83	16.67	38.76	46.00	7.24	Peak
479.11	23.45	6.58	7.71	37.74	46.00	8.26	Peak
664.38	25.21	7.20	5.78	38.19	46.00	7.81	Peak

Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
56.19	13.31	1.67	9.83	24.81	40.00	15.19	Peak
123.12	18.46	2.57	6.15	27.18	43.50	16.32	Peak
191.99	15.92	3.35	7.15	26.42	43.50	17.08	Peak
245.34	18.58	3.90	5.29	27.77	46.00	18.23	Peak
290.93	19.56	4.35	3.03	26.94	46.00	19.06	Peak
479.11	23.45	6.58	4.06	34.09	46.00	11.91	Peak


Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

A.2.1.3 Frequency Above 1 GHz to 10th harmonics

Band Edge:

Mode	GFSK	Frequency	TX 2402MHz
------	------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2321.40	32.00	8.47	7.37	47.84	74.00	26.16	Peak
2390.04	32.00	8.52	4.78	45.30	74.00	28.70	Peak
@ 2401.80	32.03	8.52	55.41	95.96	---	---	Peak


Emission Frequency (MHz)	Peak Emission Level (dBμV/m)	DCCF (dB)	Average Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark
2321.40	47.84	-30.81	17.03	54.00	36.97	Average
2390.04	45.30	-30.81	14.49	54.00	39.51	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	GFSK	Frequency	TX 2402MHz
------	------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2312.16	32.00	8.46	7.68	48.14	74.00	25.86	Peak
2390.04	32.00	8.52	4.79	45.31	74.00	28.69	Peak
@ 2401.80	32.03	8.52	49.35	89.90	---	---	Peak


Emission Frequency (MHz)	Peak Emission Level (dBμV/m)	DCCF (dB)	Average Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark
2312.16	48.14	-30.81	17.33	54.00	36.67	Average
2390.04	45.31	-30.81	14.50	54.00	39.50	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	GFSK	Frequency	TX 2480MHz
------	------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2479.70	32.58	8.58	52.64	93.80	---	---	Peak
2483.30	32.57	8.58	3.96	45.11	74.00	28.89	Peak
2796.95	32.86	8.66	6.72	48.24	74.00	25.76	Peak


Emission Frequency (MHz)	Peak Emission Level (dBμV/m)	DCCF (dB)	Average Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark
2483.30	45.11	-30.81	14.30	54.00	39.70	Average
2796.95	48.24	-30.81	17.43	54.00	36.57	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	GFSK	Frequency	TX 2480MHz
------	------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Detector
@ 2479.70	32.58	8.58	42.67	83.83	---	---	Peak
2483.30	32.57	8.58	4.41	45.56	74.00	28.44	Peak
2896.85	32.98	8.69	6.43	48.10	74.00	25.90	Peak

Emission Frequency (MHz)	Peak Emission Level (dBUV/m)	DCCF (dB)	Average Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
2483.30	45.56	-30.81	14.75	54.00	39.25	Average
2896.85	48.10	-30.81	17.29	54.00	36.71	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.

Audix Technology Corp.


No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

Mode	8-DPSK	Frequency	TX 2402MHz
------	--------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2339.40	32.00	8.48	7.28	47.76	74.00	26.24	Peak
2390.04	32.00	8.52	5.18	45.70	74.00	28.30	Peak
@ 2401.80	32.03	8.52	55.56	96.11	---	---	Peak


Emission Frequency (MHz)	Peak Emission Level (dBμV/m)	DCCF (dB)	Average Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark
2339.40	47.76	-30.81	16.95	54.00	37.05	Average
2390.04	45.70	-30.81	14.89	54.00	39.11	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	8-DPSK	Frequency	TX 2402MHz
------	--------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2344.92	32.00	8.48	7.20	47.68	74.00	26.32	Peak
2390.04	32.00	8.52	5.13	45.65	74.00	28.35	Peak
@ 2402.16	32.03	8.52	48.98	89.53	---	---	Peak


Emission Frequency (MHz)	Peak Emission Level (dBμV/m)	DCCF (dB)	Average Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark
2344.92	47.68	-30.81	16.87	54.00	37.13	Average
2390.04	45.65	-30.81	14.84	54.00	39.16	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	8-DPSK	Frequency	TX 2480MHz
------	--------	-----------	------------



Antenna at Horizontal Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2479.70	32.58	8.58	52.48	93.64	---	---	Peak
2483.30	32.57	8.58	5.85	47.00	74.00	27.00	Peak
2893.70	32.96	8.68	6.17	47.81	74.00	26.19	Peak


Emission Frequency (MHz)	Peak Emission Level (dBμV/m)	DCCF (dB)	Average Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark
2483.30	47.00	-30.81	16.19	54.00	37.81	Average
2893.70	47.81	-30.81	17.00	54.00	37.00	Average

Remark: The "@" means fundamental frequency, it is ignored in this section.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	8-DPSK	Frequency	TX 2480MHz
------	--------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
@ 2479.70	32.58	8.58	42.81	83.97	---	---	Peak
2483.30	32.57	8.58	4.45	45.60	74.00	28.40	Peak
2864.00	32.78	8.68	6.72	48.18	74.00	25.82	Peak

Emission Frequency (MHz)	Peak Emission Level (dBμV/m)	DCCF (dB)	Average Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark
2483.30	45.60	-30.81	14.79	54.00	39.21	Average
2864.00	48.18	-30.81	17.37	54.00	36.63	Average

Remark: The “@” means fundamental frequency, it is ignored in this section.

Audix Technology Corp.

No. 53-11, Dingfu, Linkou, Dist.,

New Taipei City 244, Taiwan

Tel: +886 2 26099301

Fax: +886 2 26099303

A.2.2 Emissions outside the frequency band:

The emissions (up to 25GHz) not reported for there is no emission be found.

A.2.3 Emissions in Non-restricted Frequency Bands:

All emission levels below the FCC 15.209(a)/RSS-Gen Section 8.9 table 4 general radiated emissions limits is not required.

A.3 20dB BANDWIDTH


Test Date	2019/11/26 ~ 12/02	Temp./Hum.	23°C/59~66%
Cable Loss	0.8dB	Tested By	Kuper Hsu
Test Voltage	DC 5V (via Test JIG)		

A.3.1 6dB Bandwidth Result

Mode	Centre Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz) (Reference only)	2/3 (20dB Bandwidth)
GFSK	2402	0.9224	0.86849	0.615
	2441	0.9223	0.86912	0.615
	2480	0.9220	0.87284	0.615
8-DPSK	2402	1.246	1.1550	0.831
	2441	1.246	1.1616	0.831
	2480	1.250	1.1613	0.833


Remark: The maximum two-thirds of the 20dB bandwidth is the limit for carrier frequency separation presented.

A.3.2 Measurement Plots




A.4 CARRIER FREQUENCY SEPARATION

Test Date	2019/11/26 ~ 12/02	Temp./Hum.	23°C/59~66%
Cable Loss	0.8dB	Tested By	Kuper Hsu
Test Voltage	DC 5V (via Test JIG)		




8-DPSK

2402MHz




2441MHz

adjacent channel of left carrier frequency




2441MHz

adjacent channel of right carrier frequency



2480MHz



A.5 TIME OF OCCUPANCY

Test Date	2019/11/26 ~ 12/02	Temp./Hum.	23°C/59~66%
Cable Loss	0.8dB	Tested By	Kuper Hsu
Test Voltage	DC 5V (via Test JIG)		

A.5.1 Time of Occupancy

Mode	Centre Frequency (MHz)	Mode	Each second appearance transmission	Time of Occupancy (ms)	Maximum accumulated Time of Occupancy (ms)	Limit (ms)
GFSK	2402	DH1	8	0.370	93.536	<400
		DH3	5	1.635	258.330	<400
		DH5	3	2.880	273.024	<400

Observation Period:

$$79 \text{ channels} * 0.4 \text{ seconds} = 31.6 \text{ seconds}$$

DH1 Mode

For each second of 8 transmission appearance, the longest time of occupancy is
8 transmission * 31.6 seconds * 0.370 ms = 93.536 ms (<400ms)

DH3 Mode

For each second of 5 transmission appearance, the longest time of occupancy is
5 transmission * 31.6 seconds * 1.635 ms = 258.330 ms (<400ms)

DH5 Mode

For each second of 3 transmission appearance, the longest time of occupancy is
3 transmission * 31.6 seconds * 2.880 ms = 273.024 ms (<400ms)

Mode	Centre Frequency (MHz)	Mode	Each second appearance transmission	Time of Occupancy (ms)	Maximum accumulated Time of Occupancy (ms)	Limit (ms)
GFSK	2441	DH1	8	0.370	93.536	<400
		DH3	5	1.630	257.540	<400
		DH5	3	2.880	273.024	<400

Observation Period:

$$79 \text{ channels} * 0.4 \text{ seconds} = 31.6 \text{ seconds}$$

DH1 Mode

For each second of 8 transmission appearance, the longest time of occupancy is
8 transmission * 31.6 seconds * 0.370 ms = 93.536 ms (<400ms)

DH3 Mode

For each second of 5 transmission appearance, the longest time of occupancy is
5 transmission * 31.6 seconds * 1.630 ms = 257.540 ms (<400ms)

DH5 Mode

For each second of 3 transmission appearance, the longest time of occupancy is
3 transmission * 31.6 seconds * 2.880 ms = 273.024 ms (<400ms)

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

Mode	Centre Frequency (MHz)	Mode	Each second appearance transmission	Time of Occupancy (ms)	Maximum accumulated Time of Occupancy (ms)	Limit (ms)
GFSK	2480	DH1	8	0.370	93.536	<400
		DH3	5	1.630	257.540	<400
		DH5	3	2.880	273.024	<400

Observation Period:

79 channels* **0.4** seconds= **31.6** seconds

DH1 Mode

For each second of **8** transmission appearance, the longest time of occupancy is
8 transmission* **31.6** seconds* **0.370** ms= **93.536** ms (<400ms)


DH3 Mode

For each second of **5** transmission appearance, the longest time of occupancy is
5 transmission* **31.6** seconds* **1.630** ms= **257.540** ms (<400ms)

DH5 Mode

For each second of **3** transmission appearance, the longest time of occupancy is
3 transmission* **31.6** seconds* **2.880** ms= **273.024** ms (<400ms)


● Measurement Plots



GFSK

2441MHz


DH1



DH3




DH5



GFSK

2480MHz


DH1



DH3



DH5



Mode	Centre Frequency (MHz)	Mode	Each second appearance transmission	Time of Occupancy (ms)	Maximum accumulated Time of Occupancy (ms)	Limit (ms)
8-DPSK	2402	3DH1	5	0.380	60.040	<400
		3DH3	5	1.630	257.540	<400
		3DH5	3	2.880	273.024	<400

Observation Period:

 $79 \text{ channels} * 0.4 \text{ seconds} = 31.6 \text{ seconds}$ **3DH1 Mode**

For each second of 5 transmission appearance, the longest time of occupancy is
5 transmission * 31.6 seconds * 0.380 ms = 60.040 ms (<400ms)

3DH3 Mode

For each second of 5 transmission appearance, the longest time of occupancy is
5 transmission * 31.6 seconds * 1.630 ms = 257.540 ms (<400ms)

3DH5 Mode

For each second of 3 transmission appearance, the longest time of occupancy is
3 transmission * 31.6 seconds * 2.880 ms = 273.024 ms (<400ms)

Mode	Centre Frequency (MHz)	Mode	Each second appearance transmission	Time of Occupancy (ms)	Maximum accumulated Time of Occupancy (ms)	Limit (ms)
8-DPSK	2441	3DH1	5	0.380	60.040	<400
		3DH3	5	1.630	257.540	<400
		3DH5	3	2.880	273.024	<400

Observation Period:

 $79 \text{ channels} * 0.4 \text{ seconds} = 31.6 \text{ seconds}$ **3DH1 Mode**

For each second of 5 transmission appearance, the longest time of occupancy is
5 transmission * 31.6 seconds * 0.380 ms = 60.040 ms (<400ms)

3DH3 Mode

For each second of 5 transmission appearance, the longest time of occupancy is
5 transmission * 31.6 seconds * 1.630 ms = 257.540 ms (<400ms)

3DH5 Mode

For each second of 3 transmission appearance, the longest time of occupancy is
3 transmission * 31.6 seconds * 2.880 ms = 273.024 ms (<400ms)

Mode	Centre Frequency (MHz)	Mode	Each second appearance transmission	Time of Occupancy (ms)	Maximum accumulated Time of Occupancy (ms)	Limit (ms)
8-DPSK	2480	3DH1	5	0.380	60.040	<400
		3DH3	5	1.630	257.540	<400
		3DH5	3	2.880	273.024	<400

Observation Period:

79 channels * **0.4** seconds = **31.6** seconds

3DH1 Mode

For each second of **5** transmission appearance, the longest time of occupancy is
5 transmission * **31.6** seconds * **0.380** ms = **60.040** ms (<400ms)


3DH3 Mode

For each second of **5** transmission appearance, the longest time of occupancy is
5 transmission * **31.6** seconds * **1.630** ms = **257.540** ms (<400ms)

3DH5 Mode

For each second of **3** transmission appearance, the longest time of occupancy is
3 transmission * **31.6** seconds * **2.880** ms = **273.024** ms (<400ms)


● Measurement Plots



8-DPSK

2441MHz


3DH1



3DH3




3DH5




8-DPSK

2480MHz


3DH1



3DH3



3DH5




Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

A.6 NUMBER OF HOPPING CHANNELS

Test Date	2019/11/26 ~ 12/02	Temp./Hum.	23°C/59~66%
Cable Loss	0.8dB	Tested By	Kuper Hsu
Test Voltage	DC 5V (via Test JIG)		




A.7 MAXIMUM PEAK OUTPUT POWER

Test Date	2019/11/26 ~ 12/02	Temp./Hum.	23°C/59~66%
Cable Loss	0.8dB	Tested By	Kuper Hsu
Test Voltage	DC 5V (via Test JIG)		

A.7.1 Maximum Peak Output Power

Mode	Centre Frequency (MHz)	Maximum Peak Output Power		Limit
		dBm	W	
GFSK	2402	12.33	0.017	21dBm (0.125W)
	2441	12.34	0.017	
	2480	11.82	0.015	
8-DPSK	2402	11.82	0.015	
	2441	11.89	0.015	
	2480	11.85	0.015	


A.7.2 Measurement Plots



A.8 EMISSION LIMITATIONS MEASUREMENT


Test Date	2019/11/26 ~ 12/02	Temp./Hum.	23°C/59~66%
Cable Loss	0.8dB	Tested By	Kuper Hsu
Test Voltage	DC 5V (via Test JIG)		

A.8.1 Band Edge



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303




Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303

A.8.2 Spurious Emission


Test Date	2019/11/26 ~ 12/02	Temp./Hum.	23°C/59~66%
Cable Loss	0.8dB	Tested By	Kuper Hsu
Test Voltage	DC 5V (via Test JIG)		



Note: All results have been included cable loss.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan


Tel: +886 2 26099301
Fax: +886 2 26099303



Note: All results have been included cable loss.

Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

Tel: +886 2 26099301
Fax: +886 2 26099303



Note: All results have been included cable loss.



Audix Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

APPENDIX B

Tel: +886 2 26099301
Fax: +886 2 26099303

APPDNDIX B

TEST PHOTOGRAPHS

(Model: WCT750M)