



Maximum Permissible Exposure

FCC, Part 15 §1.1310

Industry Canada RSS-Gen §5.6

Calculations for Maximum Permissible Exposure Levels

Power Density = P_d (mW/cm²) = $EIRP / (4\pi d^2)$

$EIRP = P * G$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = $10^{(G \text{ (dBi)} / 10)}$

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1.0 mW/cm²

The calculations in the table below use highest gain antennas for the client EUT. Where the antenna gain exceeds 6dBi the transmitter power is reduced to meet the EIRP requirements. These calculations represent worst case in terms of the exposure levels.
Frequency Band 5150 – 5250 MHz

Transmitter Pair	Antenna Gain (dBi)	Numeric Gain (numeric)	Output Power (mW)	Peak Output Power (dBm)	Correlation Gain (dB)	Total (mW)	Total (dBm)
A1/A3	4.5	2.82	49.0	15.8	3.0	144.5	--
A3/A4	4.5	2.82	47.9	16.8	3.0	186.2	--
M1/M2	4.5	2.82	49.0	16.9	3.0	190.5	--
Total						521.2	27.2

Calculated Safe Distance @ 1mW/cm ² Limit(cm) for correlated transmitter, transmitting	Distance (cm)
27.2 dBm	6.44

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

Specification

Maximum Permissible Exposure Limits

FCC §1.1310 Limit = 1mW / cm² from 1.310 Table 1

RSS-Gen §5.6 Category I and Category II equipment shall comply with the applicable requirements of RSS-102.