

# TEST REPORT

of

FCC Part 15 Subpart B&C §15.247/RSS-210 Issue 7, RSS-Gen Issue 2

FCC ID/IC Certification: A3LWEP300/649E-WEP300

Equipment Under Test : Bluetooth Mono Headset  
Model Name : WEP300  
Serial No. : N / A  
Applicant : SAMSUNG ELECTRONICS CO.,LTD.  
Manufacturer : SAMSUNG ELECTRONICS CO.,LTD.  
Date of Test(s) : 2008.09.24 ~ 2008.09.29  
Date of Issue : 2008.09.30

In the configuration tested, the EUT complied with the standards specified above.

Tested By:



Date

2008.09.30

Duke Ko

Approved By



Date

2008.09.30

Jim Kim

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

# INDEX

| <b><u>Table of Contents</u></b>                             | <b>Page</b> |
|-------------------------------------------------------------|-------------|
| <b>1. General Information -----</b>                         | <b>3</b>    |
| <b>2. Transmitter AC Power Line Conducted Emission-----</b> | <b>6</b>    |
| <b>3. Receiver AC Power Line Conducted Emission-----</b>    | <b>11</b>   |
| <b>4. Transmitter Radiated Spurious Emissions -----</b>     | <b>15</b>   |
| <b>5. Receiver Radiated Spurious Emission-----</b>          | <b>21</b>   |

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## 1. General Information

### 1.1. Testing Laboratory

SGS Testing Korea Co., Ltd.  
- 705, Dongchun-Dong Sooji-Gu, Yongin-Shi, Kyungki-Do, South Korea.  
[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)  
Telephone : +82 +31 428 5700  
FAX : +82 +31 427 2371

### 1.2. Details of Applicant

Applicant : SAMSUNG ELECTRONICS CO.,LTD.  
Address : 416, Maetan-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea  
Contact Person : Yoo, Jungheon  
Phone No. : +82 +31 301 4179  
Fax No. : +82 +31 301 5998

### 1.3. Description of EUT

|                              |                                           |
|------------------------------|-------------------------------------------|
| <b>Kind of Product</b>       | Bluetooth Mono Headset                    |
| <b>Model Name</b>            | WEP300                                    |
| <b>Serial Number</b>         | N / A                                     |
| <b>Power Supply</b>          | DC 3.7 V (Li-poly Battery)                |
| <b>Adapter's Information</b> | Input : AC 100~240 V / Output : DC 4.75 V |
| <b>Frequency Range</b>       | 2402 ~ 2480 MHz                           |
| <b>Modulation Technique</b>  | GFSK                                      |
| <b>Number of Channels</b>    | 79                                        |
| <b>Operating Conditions</b>  | -20 ~ 60 °C                               |
| <b>Antenna Type</b>          | Integral Type (Chip Antenna)              |

### 1.4. Details of modification

-N/A

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

## 1.5. Information about the FHSS characteristics:

### 1.5.1. Pseudorandom Frequency Hopping Sequence

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The nominal hop rate is 1600 hops/s.

### 1.5.2. Equal Hopping Frequency Use

All Bluetooth units participating in the piconet are time and hop-synchronized to the channel.

### 1.5.3. System Receiver Input Bandwidth

Each channel bandwidth is 1MHz

## 1.6. Test Equipment List

| EQUIPMENT               | MANUFACTURER               | MODEL                              | CAL DUE.      |
|-------------------------|----------------------------|------------------------------------|---------------|
| Bluetooth Tester        | TESOM                      | TC-3000B                           | Dec. 11, 2008 |
| Two-Line V-Network      | R & S                      | ENV216                             | Jan. 17, 2009 |
| Test Receiver           | Rohde & Schwarz            | ESVS10                             | Mar. 21, 2009 |
| Test Receiver           | ESHS 10                    | Rohde & Schwarz                    | Jul. 21, 2009 |
| Preamplifier            | Agilent                    | 8449B                              | May 09, 2009  |
| High Pass Filter        | Wainwright Instrument GmbH | WHK3.0/18 G-11SS                   | Dec. 06, 2008 |
| Ultra-Broadband Antenna | Rohde & Schwarz            | HL562                              | Oct. 11, 2008 |
| Horn Antenna            | Electro-Metrics            | HF906                              | Nov. 13, 2009 |
| Anechoic Chamber        | SY Corporation             | L x W x H<br>6.5 m x 3.5 m x 3.5 m | Feb. 15, 2009 |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

### 1.7. Summary of Test Results

The EUT has been tested according to the following specifications:

| APPLIED STANDARD:FCC Part15, RSS-210,RSS-Gen |                            |                                              |          |
|----------------------------------------------|----------------------------|----------------------------------------------|----------|
| Section in FCC 15                            | Section in RSS-210 RSS-Gen | Test Item                                    | Result   |
| 15.207                                       | RSS-Gen 7.2.2              | Transmitter AC Power Line Conducted Emission | Complied |
| 15.107                                       | RSS-Gen 7.2.2              | Receiver AC Power Line Conducted Emission    | Complied |
| 15.205(a)<br>15.209<br>15.247(d)             | A8.5                       | Transmitter Radiated Spurious Emissions      | Complied |
| 15.109(a)                                    | RSS-Gen 6                  | Receiver Radiated Spurious Emission          | Complied |

### 1.8. Conclusion of worst-case

The field strength of spurious emission was measured in three orthogonal EUT positions(X-axis, Y-axis and Z-axis). Worst case is Z-axis.

### 1.9 Test report revision

| Revision | Report number        | Description |
|----------|----------------------|-------------|
| 0        | F690501/RF-RTL002702 | Initial     |


*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

## 2. Transmitter AC Power Line Conducted Emission

### 2.1. Test Setup



### 2.2. Limit

According to §15.207(a) for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 uH/50 ohm line impedance stabilization network(LISN).

Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequency ranges.

| Frequency of Emission (MHz) | Conducted limit (dBμV) |         |
|-----------------------------|------------------------|---------|
|                             | Quasi-peak             | Average |
| 0.15 – 0.50                 | 66-56*                 | 56-46*  |
| 0.50 – 5.00                 | 56                     | 46      |
| 5.00 – 30.0                 | 60                     | 50      |

\* Decreases with the logarithm of the frequency.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

---

### 2.3. Test Procedures

Radiated emissions from the EUT were measured according to the dictates of ANSI C63.4:2003

1. The test procedure is performed in a 6.5m × 3.6m × 3.6m (L×W×H) shielded room. The EUT along with its peripherals were placed on a 1.0m(W)× 1.5m(L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.
2. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room.
3. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.
4. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

---

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## 2.4. Test Results

The following table shows the highest levels of conducted emissions on both phase of Hot and Neutral line.

Ambient temperature : 24 °C      Relative humidity : 47 % R.H.

Frequency range : 0.15 MHz – 30 MHz

Measured Bandwidth : 9 kHz

| FREQ.<br>(MHz) | LEVEL(dBuV) |         | LINE | LIMIT(dBuV) |         | MARGIN(dB) |         |
|----------------|-------------|---------|------|-------------|---------|------------|---------|
|                | Q-Peak      | Average |      | Q-Peak      | Average | Q-Peak     | Average |
| 0.16           | 25.40       | 13.20   | H    | 65.46       | 55.46   | 40.06      | 42.26   |
| 3.42           | 27.80       | 16.50   | H    | 56.00       | 46.00   | 28.20      | 29.50   |
| 3.67           | 16.10       | 12.20   | H    | 56.00       | 46.00   | 39.90      | 33.80   |
| 3.84           | 21.10       | 12.50   | H    | 56.00       | 46.00   | 34.90      | 33.50   |
| 4.55           | 15.40       | 12.60   | H    | 56.00       | 46.00   | 40.60      | 33.40   |
| 0.16           | 30.70       | 17.80   | N    | 65.46       | 55.46   | 34.76      | 37.66   |
| 0.24           | 35.60       | 24.00   | N    | 62.26       | 52.26   | 26.66      | 28.26   |
| 0.35           | 34.60       | 22.80   | N    | 59.08       | 49.08   | 24.48      | 26.28   |
| 0.49           | 32.40       | 21.60   | N    | 56.17       | 46.17   | 23.77      | 24.57   |
| 0.58           | 30.60       | 20.60   | N    | 56.00       | 46.00   | 25.40      | 25.40   |

Note ;

Line ( H ) : Hot

Line ( N ) : Neutral


*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

## Plot of Conducted Power line

Test mode : (Hot)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

Test mode : (Neutral)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

### 3. Receiver AC Power Line Conducted Emission

#### 3.1. Test Setup- Same as clause 2.1.

#### 3.2. Limit

According to §15.107(a) Except for Class A digital devices, for equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

| Frequency of Emission (MHz) | Conducted limit (dB $\mu$ V) |         |
|-----------------------------|------------------------------|---------|
|                             | Quasi-peak                   | Average |
| 0.15 – 0.50                 | 66-56*                       | 56-46*  |
| 0.50 – 5.00                 | 56                           | 46      |
| 5.00 – 30.0                 | 60                           | 50      |

\* Decreases with the logarithm of the frequency.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

### 3.3. Test Procedures- Same as clause 2.3.

### 3.4. Test Results

The following table shows the highest levels of conducted emissions on both phase of Hot and Neutral line;  
Addition,

Ambient temperature : 24 °C      Relative humidity : 47 % R.H.

Frequency range : 0.15 MHz – 30 MHz

Measured Bandwidth : 9 kHz

| FREQ.<br>(MHz) | LEVEL(dBuV) |         | LINE | LIMIT(dBuV) |         | MARGIN(dB) |         |
|----------------|-------------|---------|------|-------------|---------|------------|---------|
|                | Q-Peak      | Average |      | Q-Peak      | Average | Q-Peak     | Average |
| 0.15           | 26.20       | 16.10   | H    | 66.00       | 56.00   | 39.80      | 39.90   |
| 0.18           | 21.50       | 14.30   | H    | 64.49       | 54.49   | 42.99      | 40.19   |
| 0.34           | 23.50       | 16.50   | H    | 59.20       | 49.20   | 35.70      | 32.70   |
| 3.40           | 22.60       | 15.80   | H    | 56.00       | 46.00   | 33.40      | 30.20   |
| 0.15           | 27.20       | 17.10   | N    | 66.00       | 56.00   | 38.80      | 38.90   |
| 0.19           | 24.10       | 17.30   | N    | 64.04       | 54.04   | 39.94      | 36.74   |
| 0.26           | 21.70       | 15.50   | N    | 61.43       | 51.43   | 39.73      | 35.93   |

Note ;

Line ( H ) : Hot

Line ( N ) : Neutral


*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

## Plot of Conducted Power line

Test mode : (Hot)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

Test mode : (Neutral)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)


## 4. Transmitter Radiated Spurious Emissions

### 4.1. Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to 24 GHz Emissions.



*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## 4.2. Limit

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement , provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval , as permitted under paragraph(b)(3) of this section , the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in section §15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section §15.205(a), must also comply the radiated emission limits specified in section §15.209(a) (see section §15.205(c))

According to § 15.209(a), Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

| Frequency<br>(MHz) | Distance<br>(Meters) | Field Strength<br>(dBμV/m) | Field Strength<br>(μV/m) |
|--------------------|----------------------|----------------------------|--------------------------|
| 30 - 88            | 3                    | 40.0                       | 100                      |
| 88 – 216           | 3                    | 43.5                       | 150                      |
| 216 – 960          | 3                    | 46.0                       | 200                      |
| Above 960          | 3                    | 54.0                       | 500                      |

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

### 4.3. Test procedures

Radiated emissions from the EUT were measured according to the dictates of ANSI C63.4:2003

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
3. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

#### NOTE ;

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1 GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz for Peak detection and frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1 GHz.

---

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

#### 4.4. Test result

Ambient temperature : 24 °C      Relative humidity : 47 % R.H.

##### 4.4.1. Spurious Radiated Emission

The frequency spectrum from 30 MHz to 1000 MHz was investigated. Emission levels are not reported much lower than the limits by over 30 dB. All reading values are quasi-peak values.

| Radiated Emissions |                |             | Ant  | Correction Factors |             | Total           | FCC Limit      |             |
|--------------------|----------------|-------------|------|--------------------|-------------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBuV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | Actual (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
| 34.850             | 34.8           | Q.P.        | V    | 16.78              | -27.76      | 23.82           | 40.0           | 16.18       |
| 39.700             | 37.3           | Q.P.        | V    | 14.16              | -27.68      | 23.78           | 40.0           | 16.22       |
| 51.825             | 45.9           | Q.P.        | V    | 7.03               | -27.53      | 25.41           | 40.0           | 14.59       |
| 93.050             | 38.8           | Q.P.        | V    | 8.62               | -27.10      | 20.32           | 43.5           | 23.18       |
| 100.325            | 38.9           | Q.P.        | V    | 8.91               | -27.06      | 20.76           | 43.5           | 22.74       |
| Above 200.000      | Not detected   | -           | -    | -                  | -           | -               | -              | -           |

#### Remark:

1. All spurious emission at channels are almost the same below 1 GHz, so that the channel was chosen at representative in final test.
2. “\*” means the restricted band.
3. Actual = Reading + AF + AMP + CL
4. The emission levels above 200 MHz are very lower than the limit by over 30 dB.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

#### 4.4.2. Spurious Radiated Emission

The frequency spectrum above 1000 MHz was investigated. Emission levels are not reported much lower than the limits by over 30 dB. All reading values are peak values.

##### A. Low Channel (2402 MHz)

| Radiated Emissions |                |             | Ant  | Correction Factors |                  | Total           | FCC Limit      |             |
|--------------------|----------------|-------------|------|--------------------|------------------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBuV) | Detect Mode | Pol. | AF (dB/m)          | Amp Gain+CL (dB) | Actual (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
| 2390.00*           | 47.20          | Peak        | V    | 28.05              | -28.19           | 47.06           | 74.00          | 26.94       |
| 4804.48            | 44.52          | Peak        | V    | 32.95              | -24.78           | 52.70           | 74.00          | 21.30       |
| Above 4900.00      | Not detected   | -           | -    | -                  | -                | -               | -              | -           |

##### B. Middle Channel (2441 MHz)

| Radiated Emissions |                |             | Ant  | Correction Factors |                  | Total           | FCC Limit      |             |
|--------------------|----------------|-------------|------|--------------------|------------------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBuV) | Detect Mode | Pol. | AF (dB/m)          | Amp Gain+CL (dB) | Actual (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
| 4882.57            | 45.47          | Peak        | V    | 33.17              | -25.07           | 53.57           | 74.00          | 20.43       |
| Above 4900.00      | Not detected   | -           | -    | -                  | -                | -               | -              | -           |

##### C. High Channel (2480 MHz)

| Radiated Emissions |                |             | Ant  | Correction Factors |                  | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|------------------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBuV) | Detect Mode | Pol. | AF (dB/m)          | Amp Gain+CL (dB) | Actual (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
| 2483.50*           | 48.86          | Peak        | V    | 28.18              | -28.14           | 48.90           | 74.00          | 25.10       |
| 4960.18            | 44.08          | Peak        | V    | 33.39              | -24.95           | 52.52           | 74.00          | 21.48       |
| Above 5000.00      | Not detected   | -           | -    | -                  | -                | -               | -              | -           |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## Remarks ;

1. “\*” means the restricted band.
2. Measuring frequencies from 1 GHz to the 10<sup>th</sup> harmonic of highest fundamental Frequency.
3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using peak/average detector mode.
4. Average test would be performed if the peak result were greater than the average limit.
5. Actual = Reading + AF + Amp Gain + CL

---

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## 5. Receiver Radiated spurious emissions

### 5.1. Test setup - Same as clause 4.1.

#### 5.1.1. Receiver Radiated Spurious Emissions - Same as clause 4.1.1.

### 5.2. Limit

According to §15.109(a), Except for Class A digital devices, the field strength of radiated emission from unintentional radiator at a distance of 3 m shall not exceed the following values:

| Frequency<br>(MHz) | Distance<br>(Meters) | Radiated<br>(dBμV/m) | Radiated<br>(μV/m) |
|--------------------|----------------------|----------------------|--------------------|
| 30 - 88            | 3                    | 40.0                 | 100                |
| 88 – 216           | 3                    | 43.5                 | 150                |
| 216 – 960          | 3                    | 46.0                 | 200                |
| Above 960          | 3                    | 54.0                 | 500                |

### 5.3. Test Procedures - Same as clause 4.3.

Radiated emissions from the EUT were measured according to the dictates of ANSI C63.4:2003

#### 5.3.1. Test Procedures for Radiated Spurious Emissions- Same as clause 4.3.1.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

SGS Testing Korea Co., Ltd.

[www.electrolab.kr.sgs.com](http://www.electrolab.kr.sgs.com)

## 5.4. Test Results

Ambient temperature : 24 °C      Relative humidity : 47 % R.H.

### 3.4.1. Spurious Radiated Emission

The frequency spectrum from 30 MHz to 1000 MHz was investigated. Emission levels are not reported much lower than the limits by over 30 dB. All reading values are quasi-peak values.

| Radiated Emissions |                |             | Ant  | Correction Factors |             | Total           | FCC Limit      |             |
|--------------------|----------------|-------------|------|--------------------|-------------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBuV) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | Actual (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
| 39.700             | 40.1           | Q.P.        | V    | 14.16              | -27.68      | 26.58           | 40.0           | 13.42       |
| 51.825             | 44.0           | Q.P.        | V    | 7.03               | -27.53      | 23.51           | 40.0           | 16.49       |
| 61.525             | 45.8           | Q.P.        | V    | 4.06               | -27.45      | 22.41           | 40.0           | 17.59       |
| 93.050             | 39.1           | Q.P.        | V    | 8.62               | -27.10      | 20.62           | 43.5           | 22.88       |
| 100.325            | 38.3           | Q.P.        | V    | 8.91               | -27.06      | 20.16           | 43.5           | 23.34       |
| Above 200.000      | Not detected   | -           | -    | -                  | -           | -               | -              | -           |

#### Remark:

1. All spurious emission at channels are almost the same below 1 GHz, so that the channel was chosen at representative in final test.
2. “\*” means the restricted band.
3. Actual = Reading + AF + AMP + CL
4. The emission levels above 200 MHz are very lower than the limit by over 30 dB.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*