

TEST REPORT



CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2020-01939
Page (1) / (35) Pages

1. Client

- Name : Samsung Electronics Co Ltd
- Address : 19 Chapin Rd., Building D, Pine Brook, New Jersey
- Date of Receipt : 2020-04-24

2. Manufacturer

- Name : Samsung Electronics Co., Ltd.
- Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea, 16677

3. Use of Report : For FCC & IC Certification

4. Test Sample / Model : Audio Transceiver / WSN720S


5. Date of Test : 2020-04-30 to 2020-05-11

6. Test Standard(method) used : FCC 47 CFR part 15 subpart E 15.407 RSS-247 Issue 2

7. Testing Environment: Temp.: (23 ± 1) °C, Humidity: (48 ± 5) % R.H.

8. Test Results : Compliance

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full.

Affirmation	Tested by	Technical Manager
	Bongseok Kim: (Signature) 	Young-taek Lee: (Signature) 

2020-05-11

Republic of KOREA **CTK Co., Ltd.**



CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2020-01939
Page (2) / (35) Pages

REPORT REVISION HISTORY

Date	Revision	Page No
2020-05-11	Issued (CTK-2020-01939)	all

This report shall not be reproduced except in full, without the written approval of CTK Co., Ltd. This document may be altered or revised by CTK Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CTK Co., Ltd. will constitute fraud and shall nullify the document.

CONTENTS

1.0 General Product Description	4
1.1 Client Information	4
1.2 Product Information.....	4
1.3 Peripheral Devices	4
2.0 Facility and Accreditations	5
2.1 Test Facility.....	5
2.2 Laboratory Accreditations and Listings	5
2.3 Calibration Details of Equipment Used for Measurement	5
3.0 Test Specifications.....	6
3.1 Standards.....	6
3.2 Mode of operation during the test	7
3.3 Maximum Measurement Uncertainty	7
4.0 Technical Characteristic Test	8
4.1 ON Time, Duty Cycle.....	8
4.2 26dB Bandwidth and 99 % Bandwidth.....	9
4.3 6dB Bandwidth.....	12
4.4 Maximum Conducted Output Power	15
4.5 Power Spectral Density	18
4.6 Frequency Stability	21
4.7 Unwanted Emissions	22
4.8 AC Conducted Emissions	31
APPENDIX A – Test Equipment Used For Tests	34

 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501	Report No.: CTK-2020-01939 Page (4) / (35) Pages	
---	---	--	--

1.0 General Product Description

1.1 Client Information

Company	Samsung Electronics Co., Ltd.
Contact Point	19 Chapin Rd., Building D, Pine Brook, New Jersey
Contact Person	Name : Minhyung Cho E-mail : mh719.cho@samsung.com Tel : +82-31-277-2688

1.2 Product Information

FCC ID	A3LWSN720S
IC	649E-WSN720S
Product Description	Audio Transceiver
Model name	WSN720S
Operating Frequency	5 180 MHz - 5 240 MHz(3 channels) 5 736 MHz - 5 814 MHz(3 channels) 5 823.5 MHz (Add 1 Channel)
RF Output Power	5 180 MHz - 5 240 MHz : 14.66 dBm (29.24 mW) 5 736 MHz - 5 823.5 MHz : 8.74 dBm (7.48 mW)
Antenna type	PCB Antenna
Antenna gain	5.2 GHz band : 3.7 dBi (Antenna A), 4.3 dBi (Antenna B) 5.8 GHz band : 4.4 dBi (Antenna A), 4.2 dBi (Antenna B)
Type of Modulation	QPSK
Power Source	DC 5.0 V
Firmware Version Id Number(FVIN)	TX : V245 RX : V138
Test Software(Version)	MP Tool(1.0.0.1)

1.3 Peripheral Devices

Device	Manufacturer	Model No.	Serial No.
Note Computer	HP	15-bs563TU	CND7253QRM
AC/DC Adapter	HP	HSTNN-LA40	854054-001

2.0 Facility and Accreditations

2.1 Test Facility

The measurement facility is located at (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yong-in-si, Gyeonggi-do, Korea.

2.2 Laboratory Accreditations and Listings

Country	Agency	Registration Number
USA	FCC	805871
CANADA	ISED	8737A-2
KOREA	NRRA	KR0025

2.3 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.

3.0 Test Specifications

3.1 Standards

FCC Part Section(s)	Requirement(s)	Status (Note 1)	Test Condition
15.407(e)	6 dB Bandwidth	C	Conducted
15.407	26 dB Bandwidth and 99% Bandwidth	C	
15.407(a)(1)	Conducted Output Power	C	
15.407(a)(1)	Power Spectral Density	C	
15.407(g)	Frequency Stability	C	
15.407 (b)	Undesirable emission	C	Radiated
15.209, 15.407 (b)(5),(6)	Radiated Spurious Emission	C	
15.207	AC Conducted Emissions	C	Line Conducted
<i>Note 1:</i> C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable			
<i>Note 2:</i> The data in this test report are traceable to the national or international standards.			

ISED Part Section(s)	Requirement(s)	Status (Note 1)	Test Condition
RSS-247 6.2.4.1	6 dB Bandwidth	C	Conducted
-	26 dB Bandwidth and 99% Bandwidth	C	
RSS-247 6.2.1.1, 6.2.4.1	Conducted Output Power	C	
RSS-247 6.2.1.1, 6.2.4.1	Power Spectral Density	C	
RSS-247 6.2.1.2, 6.2.4.2	Undesirable emission	C	Radiated
RSS-Gen 6.13	Radiated Spurious Emission	C	
RSS-Gen 8.8	AC Conducted Emissions	C	Line Conducted
<i>Note 1:</i> C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable			
<i>Note 2:</i> The data in this test report are traceable to the national or international standards.			

The sample was tested according to the following specification:
FCC Part 15.407, ANSI C63.10-2013, RSS-247 Issue 2

The tests were performed according to the method of measurements prescribed in
KDB No.789033.

3.2 Mode of operation during the test

The UUT is operated in a manner representative of the typical of the equipments.
During at testing, system components were manipulated within the confines of typical usage to maximize each emission.
The results are only attached worst cases.

Operating Frequency

Frequency Band	Lowest channel	Middle channel	Highest channel	Add Channel
5.2 GHz	5 180 MHz	5 210 MHz	5 240 MHz	-
5.8 GHz	5 736 MHz	5 762 MHz	5 814 MHz	5 823.5 MHz (Test frequency)


Test antenna

Antenna 1	Antenna 2
ANT-A	ANT-B

Duty cycle

Test item	Duty cycle
Radiated emission	19 %(On time : 0.48 ms, Off :2.04 ms)
Conducted emission	100 %

The Worst Case Measurement Configuration

Tests Item	Radiated Emissions
EUT faces identified relative to view from receiving antenna	

3.3 Maximum Measurement Uncertainty

The value of the measurement uncertainty for the measurement of each parameter.
Coverage factor $k = 2$, Confidence levels of 95 %

Description	Uncertainty
Conducted measurement Power	1.5 dB
Occupied Bandwidth	0.1 MHz
Radiated Emissions (9 kHz to 30 MHz)	1.29 dB
Radiated Emissions (30 MHz to 1 GHz)	4.26 dB
Radiated Emissions (above 1 GHz)	5.14 dB
AC Conducted Emissions	2.3 dB

4.0 Technical Characteristic Test


4.1 ON Time, Duty Cycle

Test Procedures

KDB 789033 Zero-Span Spectrum Analyzer Method.

Test Data:

ON Time (ms)	Period (ms)	TX OFF (ms)	Duty Cycle (linear)	Duty Cycle (%)
0.48	2.52	2.04	0.19	19.0



Date: 11.MAY.2020 20:26:28

4.2 26dB Bandwidth and 99 % Bandwidth

Test Procedures(ANSI C63.10-2013 6.9.2)

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 26 dB relative to the maximum level measured in the fundamental emission.

Test Procedures(ANSI C63.10-2013 6.9.3)

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission.

Use the 99% power bandwidth function of the instrument and report the measured bandwidth.

Test Settings :

Center frequency = the highest, middle and the lowest channels

- a) RBW = approximately 1 % of the emission bandwidth
- b) VBW $\geq$ RBW
- c) Detector = peak
- d) Trace mode = Max hold
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

Limit :

NA

Test Data:

ANT-A

Frequency Band	Frequency [MHz]	26 dB Bandwidth [MHz]	99% Bandwidth [MHz]	Result
5.8 GHz	5 823.5	16.69	13.935	Complies

ANT-B

Frequency Band	Frequency [MHz]	26 dB Bandwidth [MHz]	99% Bandwidth [MHz]	Result
5.8 GHz	5 823.5	16.68	13.930	Complies


See next pages for actual measured spectrum plots.




CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2020-01939
Page (11) / (35) Pages

ANT-A



ANT-B



4.3 6dB Bandwidth

Test Procedures(ANSI C63.10-2013 6.9.2)

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Test Settings :

Center frequency = the highest, middle and the lowest channels

- a) RBW = 100 kHz
- b) VBW $\geq 3 \times$ RBW
- c) Detector = peak
- d) Trace mode = Max hold
- e) Sweep = auto couple
- f) Allow trace to fully stabilize
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Limit :

6 dB Bandwidth > 500 kHz

Test Data:

ANT-A

Frequency Band	Frequency [MHz]	6 dB Bandwidth [MHz]	Result
5.8 GHz	5 823.5	9.824	Complies

ANT-B

Frequency Band	Frequency [MHz]	6 dB Bandwidth [MHz]	Result
5.8 GHz	5 823.5	9.822	Complies


See next pages for actual measured spectrum plots.




CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2020-01939
Page (14) / (35) Pages

ANT-A



ANT-B




4.4 Maximum Conducted Output Power

Test Procedures

Maximum Conducted Output Power(KDB 789033, Method SA-1)

The transmitter output is connected to a spectrum analyzer and the analyzer's internal channel power integration function is used to integrate the power over a bandwidth greater than or equal to the 99% bandwidth.



Test Settings :

Center frequency = the highest, middle and the lowest channels

- a) RBW = 1 MHz
- b) VBW $\geq 3 \times$ RBW
- c) Sweep time = auto
- d) Detector = power averaging (rms)
- e) Trace mode = Average at least 100

Limit

5.2 GHz band : Not exceed $10+10\log(B) = 10+10\log(15.4) = 21.9$ dBm (155 mW)

5.8 GHz band : Not exceed 1 W (30 dBm)

Test Data

ANT-A

Frequency Band	Frequency [MHz]	Measurement data [dBm]	Limit [dBm]	Result
5.8 GHz	5 823.5	7.94	30	Complies

ANT-B

Frequency Band	Frequency [MHz]	Measurement data [dBm]	Limit [dBm]	Result
5.8 GHz	5 823.5	8.53	30	Complies


See next pages for actual measured spectrum plots.




CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2020-01939
Page (17) / (35) Pages

ANT-A



ANT-B



 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501	Report No.: CTK-2020-01939 Page (18) / (35) Pages	
---	---	---	--

4.5 Power Spectral Density

Test Procedures

Maximum Power Spectral Density (KDB 789033, Method SA-1)

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

Test Settings :

Center frequency = the highest, middle and the lowest channels

- a) RBW = 1 MHz, 500 KHz (UNII 3)
- b) VBW = 3 MHz, 1.5 MHz (UNII 3)
- c) Sweep time = auto
- d) Detector = power averaging (rms)
- e) Trace mode = Average at least 100

Limit

5.2 GHz band FCC : Not exceed 17 dBm in any 1 MHz band

5.2 GHz band IC : Not exceed 10 dBm in any 1 MHz band(e.i.r.p.)

5.8 GHz band : Not exceed 30 dBm in any 500 kHz band

Test Data

ANT-A

Frequency Band	Frequency [MHz]	Measurement data [dBm]	Limit [dBm]	Result
5.8 GHz	5 823.5	-3.364	30	Complies

ANT-B

Frequency Band	Frequency [MHz]	Measurement data [dBm]	Limit [dBm]	Result
5.8 GHz	5 823.5	-2.694	30	Complies

See next pages for actual measured spectrum plots.

ANT-A



ANT-B



4.6 Frequency Stability

Test Procedures

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -20 °C and +50 °C (Declaration by the Manufacturer). The temperature was incremented by 10 °C intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded.

Limit

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user manual.

Frequency Error (kHz)								
Frequency [MHz]	Temperature							
	-20 °C	-10 °C	0 °C	10 °C	20 °C	30 °C	40 °C	50 °C
5 823.5	-92.67	-90.69	-95.41	-113.13	-121.36	-147.86	-154.66	-164.68

Note :

Based on the results of the frequency stability test shown above the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature range as tested.

This modular transmitter have its own power supply regulation.

4.7 Unwanted Emissions

Test Location

- ☒ 10 m SAC (test distance : ☐ 10 m, ☒ 3 m)
☒ 3 m SAC (test distance : 3 m)

Test Procedures

- 1) In the frequency range of 9 kHz to 30 MHz, magnetic field is measured with Loop Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- 2) In the frequency range above 30 MHz, Bi-Log Test Antenna(30 MHz to 1 GHz) and Horn Test Antenna(above 1 GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is carried from 1m to 4m above the ground to determine the maximum value of the field strength. The emissions levels at both horizontal and vertical polarizations should be tested.

Test Settings:

Frequency Range = 9 kHz ~ 40 GHz

- a) RBW = 1 MHz for $f \geq 1$ GHz, 120 kHz for $f < 1$ GHz, 9 kHz for $f < 30$ MHz
- b) VBW $\geq$ RBW
- c) Sweep time = auto

Limit

- 15.209(a) / RSS-Gen

Frequency(MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	48.5 - 13.8	300
0.490-1.705	24000/F(kHz)	33.8 - 23	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

** Except as provided in 15.209(g).fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72MHz, 76-88MHz, 174-216MHz, 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g.15.231 and 15.241.


- 15.407, KDB 789033

E.I.R.P -27 dBm/MHz


$E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2$, for $d = 3\text{m}$

Test Setup:


- 1) For field strength of emissions from 9 kHz to 30 MHz



- 2) For field strength of emissions from 30 MHz to 1 GHz



3) For field strength of emissions above 1 GHz




Test Results

1) 9 kHz to 30 MHz

Test mode : ANT-B(Worst Case)

The requirements are:

☒ Complies



Result : Emissions more than 20 dB below the limit don't need to be reported.


2) 30 MHz to 1 GHz

Test mode : ANT-B(Worst Case)

The requirements are:

☒ Complies

Test Data



Spectrum Selection

No.	Frequency (P)	Reading	c.f	Result PK	Limit QP	Margin QP	Height	Angle
	[MHz]	[dB(uV)]	[dB(1/m)]	[dB(uV/m)]	[dB(uV/m)]	[dB]	[cm]	[deg]
1	226.789	H 48.3	-12.4	35.9	46.0	10.1	101.0	216.0
2	236.489	H 53.2	-11.4	41.8	46.0	4.2	101.0	264.0
3	240.490	H 49.2	-10.9	38.3	46.0	7.7	101.0	257.0
4	280.254	H 45.3	-7.9	37.4	46.0	8.6	101.0	264.0
5	280.624	H 46.9	-9.0	37.9	46.0	8.1	101.0	264.0
6	683.774	H 33.1	1.1	34.2	46.0	11.8	399.0	45.0

Remark :


1. Result = Reading + c.f(correction factor)
2. Correction factor = Antenna factor + Cable loss + 6 dB attenuator
3. This data is the Peak(PK) value.

3) 1 GHz to 18 GHz

Test mode : ANT-B(Worst Case)

The requirements are:

☒ Complies



No.	Frequency [MHz]	Polarization	Reading [dBuV]	c.f [dB/m]	Result [dBuV/m]	Limit [dBuA/m]	Margin[dB]	Remark
1	1656.625	H	50.4	-6.5	43.9	54	10.1	Peak
2	2124.125	H	49.9	-3.6	46.3	54	7.7	Peak
3	2130.500	V	52.3	-3.7	48.6	54	5.4	Peak
4	4266.125	V	48.4	0.8	49.2	54	4.8	Peak

Remark :

1. Result = Reading + c.f(Correction factor)
2. Correction factor = Antenna factor + Cable loss - Amp. Gain
3. This data is the Peak(PK) value.

4) 18 GHz to 26.5 GHz


Test mode : ANT-B(Worst Case)

The requirements are:

☒ Complies

Model Name : WSN720S
Manufacturer : SAMSUNG
Mode : 5824MHz

Model Type :



No.	Frequency [MHz]	(P)	Reading [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin AV [dB]	Height [cm]	Angle [deg]
1	26685.620	V	49.4	10.1	59.5	-----	74.0	-----	14.5	-----	154.6	6.8
2	26586.060	H	49.2	10.5	59.7	-----	74.0	-----	14.3	-----	145.4	140.9
3	26545.560	H	37.7	10.7	-----	48.4	-----	54.0	-----	5.6	145.4	67.3
4	26543.880	V	37.7	10.7	-----	48.4	-----	54.0	-----	5.6	154.6	336.6

Remark :

1. Result = Reading + c.f(Correction factor)
2. Correction factor = Antenna factor + Cable loss - Amp. Gain

6) 26.5 GHz to 40 GHz


Test mode : ANT-B(Worst Case)

The requirements are:

☒ Complies

Model Name : WSN720S
Manufacturer : SAMSUNG
Mode : 6824MHz

Model Type :




No.	Frequency [MHz]	(P)	Reading [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin AV [dB]	Height [cm]	Angle [deg]
1	39805.940	H	39.1	19.9	59.0	---	74.0	---	15.0	---	140.7	194.0
2	39984.810	H	27.3	20.2	---	47.5	---	54.0	---	6.5	140.7	0.0
3	39981.440	V	38.8	20.2	59.0	---	74.0	---	15.0	---	154.6	316.4
4	34554.440	V	31.7	15.4	---	47.1	---	54.0	---	6.9	154.6	359.9

Remark :

1. Result = Reading + c.f(Correction factor)
2. Correction factor = Antenna factor + Cable loss - Amp. Gain

Band emissions mask

Test mode : ANT-B(Worst Case)



Result : Emissions more than 20 dB below the limit don't need to be reported.

4.8 AC Conducted Emissions

A radio apparatus that is designed to be connected to the public utility (AC) power line shall ensure that the radio frequency voltage, which is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz-30 MHz, shall not exceed the limits.

Instrument Settings

IF Band Width: 9 kHz

Test Procedures

The EUT was placed on a non-metallic table 0.8m above the metallic, grounded floor and 0.4m from the reference ground plane wall. The distance to other metallic surfaces was at least 0.8m.

Amplitude measurements were performed with a quasi-peak detector and an average detector.

Limit

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average**
0.15 ~ 0.5	66 to 56*	56 to 46*
0.5 ~ 5	56	46
5 ~ 30	60	50

* The level decreases linearly with the logarithm of the frequency.

** A linear average detector is required.

Test Results

The requirements are:


☒ Complies

Test Data

Test mode : ANT-B(Worst Case)

[LINE]

3CE_Class B_L1



Final Result 1


Frequency (MHz)	QuasiPeak (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	43.9	1000.0	9.000	On	L1	9.8	22.1	66.0
0.190500	48.1	1000.0	9.000	On	L1	9.8	15.9	64.0
4.344000	35.9	1000.0	9.000	On	L1	9.9	20.1	56.0
4.546500	35.8	1000.0	9.000	On	L1	9.9	20.2	56.0
19.612500	40.8	1000.0	9.000	On	L1	10.1	19.2	60.0
20.463000	42.7	1000.0	9.000	On	L1	10.1	17.3	60.0

Final Result 2

Frequency (MHz)	CAverage (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.190500	35.5	1000.0	9.000	On	L1	9.8	18.5	54.0
4.443000	29.4	1000.0	9.000	On	L1	9.9	16.6	46.0
4.546500	28.9	1000.0	9.000	On	L1	9.9	17.1	46.0
6.859500	32.9	1000.0	9.000	On	L1	9.9	17.1	50.0
19.612500	35.1	1000.0	9.000	On	L1	10.1	14.9	50.0
20.188500	36.2	1000.0	9.000	On	L1	10.1	13.8	50.0

[NEUTRAL]

3CE_Class B_N



Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.154500	44.0	1000.0	9.000	On	N	9.8	21.7	65.8
0.195000	46.1	1000.0	9.000	On	N	9.8	17.7	63.8
0.253500	40.8	1000.0	9.000	On	N	9.7	20.9	61.6
2.260500	36.4	1000.0	9.000	On	N	9.8	19.6	56.0
2.593500	35.7	1000.0	9.000	On	N	9.8	20.3	56.0
20.472000	39.8	1000.0	9.000	On	N	10.1	20.2	60.0

Final Result 2

Frequency (MHz)	CAverage (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.186000	35.4	1000.0	9.000	On	N	9.8	18.8	54.2
0.244500	32.5	1000.0	9.000	On	N	9.7	19.4	51.9
2.278500	26.8	1000.0	9.000	On	N	9.8	19.2	46.0
2.445000	27.5	1000.0	9.000	On	N	9.8	18.5	46.0
19.522500	30.7	1000.0	9.000	On	N	10.1	19.3	50.0
20.292000	32.4	1000.0	9.000	On	N	10.1	17.6	50.0

APPENDIX A – Test Equipment Used For Tests

	Name of Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Signal Analyzer	Agilent	N9020B	MY57431080	2020-04-17	2021-04-17
2	Spectrum Analyzer	Rohde & Schwarz	FSP-30	100994	2019-10-16	2020-10-16
2	Signal Generator	Rohde & Schwarz	SMB100A	175528	2020-04-28	2021-04-28
3	EMI Test Receiver	Rohde & Schwarz	ESCI7	100814	2019-10-22	2020-10-22
4	Bilog Antenna	Schaffner	CBL6111C	2551	2019-04-17	2021-04-17
5	Active Loop Antenna	SCHWARZBECK	FMZB 1513	1513-125	2020-04-16	2022-04-16
6	6dB Attenuator	Rohde & Schwarz	DNF	272.4110.50-2	2019-10-25	2020-10-25
7	6dB Attenuator	NONE	6dB	190557	2019-10-17	2020-10-17
8	AMPLIFIER	SONOMA	310	291721	2020-01-22	2021-01-22
9	EMI Test Receiver	Rohde & Schwarz	ESU40	100336	2020-01-17	2021-01-17
10	LISN	Rohde & Schwarz	ENV216	101235	2020-01-17	2021-01-17
11	EMI Test Receiver	Rohde & Schwarz	ESCI3	100032	2020-01-17	2021-01-17
12	Preamplifier	Agilent	8449B	3008A01504	2019-12-17	2020-12-17
13	Singnal Conditioning Unit	Rohde & Schwarz	SCU-40	10023	2019-10-16	2020-10-16
14	Horn Antenna	ETS-Lindgren	3116	00062916	2020-04-20	2021-04-20
15	Horn Antenna	ETS-Lindgren	3117	00154525	2019-09-25	2020-09-25
16	Band Reject Filter	Micro Tronics	BRM50716	G184	2020-01-20	2021-01-20

	Cable	Manufacturer	Model No.	Serial No.	Check Date
1	RF Cable (Radiated)	HUBER+SUHNER	SUCOFLEX 104	MY27558/4	2020-04-27
2	RF Cable (Radiated)	HUBER+SUHNER	SUCOFLEX 104	N/A (below 1GHz)	2020-04-27
3	RF Cable (Radiated)	HUBER+SUHNER	SUCOFLEX 104	MY27573/4	2020-04-27
4	RF Cable (Radiated)	HUBER+SUHNER	SUCOFLEX 106	N/A (above 1GHz)	2020-04-27
5	RF Cable (Radiated)	HUBER+SUHNER	SUCOFLEX 102	MY2374/2	2020-04-27
6	RF Cable (Radiated)	HUBER+SUHNER	SUCOFLEX 102	MY4728/2	2020-04-27
7	RF Cable (Radiated)	HUBER+SUHNER	SUCOFLEX 102	MY14858/4	2020-04-27
8	RF Cable (Conducted)	JUNFLON	MWX221	1512S148	2020-04-27
9	Cable	CANARE	AC power line	N/A	2020-04-27
10	Cable	CANARE	3m loop	N/A	2020-04-27