

RF EXPOSURE REPORT



Report No.: 15070819-FCC-H

Applicant	Shenzhen Creative Industry Co., Ltd.	
Product Name	Video Baby Monitor	
Model No.	OT240M	
Serial No.	N/A	
Test Standard	FCC 2.1091	
Test Date	September 10 to November 05, 2015	
Issue Date	November 09, 2015	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification ☒		
Equipment did not comply with the specification ☐		
<i>Winnie Zhang</i>	<i>David Huang</i>	
Winnie Zhang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	15070819-FCC-H
Page	3 of 8

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. FCC §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)	7
6.1 APPLICABLE STANDARD	7
6.2 TEST RESULT	8

1. Report Revision History

Report No.	Report Version	Description	Issue Date
15070819-FCC-H	NONE	Original	November 09, 2015

2. Customer information

Applicant Name	Shenzhen Creative Industry Co., Ltd.
Applicant Add	2/F, Block 3, Nanyou Tian'an Industry Town, Guangd, Shenzhen, China, 518054
Manufacturer	MC Devices Co., Ltd.
Manufacturer Add	Suite 516 BLD 4, National Software Base, Ke ji zhong 2 Road, Shenzhen Hi-Tech Park, Shenzhen, 518.57, China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Labview of SIEMIC version 2.0

4. Equipment under Test (EUT) Information

Description of EUT:	Video Baby Monitor
Main Model:	OT240M
Serial Model:	N/A
Equipment Category :	DSS
Antenna Gain:	FHSS: 3dBi 433MHz Receiver: 0dBi
Input Power:	Adapter: Model :PS10E050K2000UU Input :100-240Vac, 50/60Hz, 0.35A Output :5.0Vdc, 2000mA
Trade Name :	N/A
FCC ID:	A49IPC240
Type of Modulation:	FHSS
RF Operating Frequency (ies):	FHSS: 2409.75-2475 MHz Receiver: 433MHz
Number of Channels:	FHSS: 19CH Receiver: 1CH

5. FCC §2.1091 - Maximum Permissible exposure (MPE)

6.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission' s guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

6.2 Test Result

Type	Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Limit (mW)	Result
Output power	FHSS	Low	2409.750	14.49	14.5±1	125	Pass
		Mid	2442.375	14.34	14.5±1	125	Pass
		High	2475.000	14.11	14.5±1	125	Pass

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For the antenna manufacturer provide only used limited to ERP/EIRP or radiated spurious emission test. The MPE evaluation as below:

Maximum output power at antenna input terminal: 15.5(dBm)

Maximum output power at antenna input terminal: 35.48(mW)

Prediction distance: >20 (cm)

Predication frequency: 2409.75 (MHz) High

frequency Antenna Gain (typical): 3 (dBi)

The worst case is power density at predication frequency at 20 cm: 0.01(mW/cm²)

MPE limit for general population exposure at prediction frequency: 1.0 (mW/cm²)

0.01(mW/cm²) < 1.0 (mW/cm²)

Result: Pass