



PSB Singapore

Choose certainty.
Add value.

TÜV SÜD PSB Pte Ltd - 1 Science Park Drive, Singapore 118221

Maximum Permissible Exposure

Date: 26 July 2017

E-LOG and Fleet Management Device
Host: DC200S
Contains FCC ID: A4C01005A & QIPXS8

Rules:

1.
47 CFR 1.1310 Table 1B of– Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure

Frequency range (MHz)	Power density (mW/cm ²)
300 – 1500	f/1500
1,500 – 100000	1.0

$$S = P \cdot G / (4 \cdot \pi \cdot R^2)$$

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

Results:

MPE of each transmitter under standalone operation does not reach maximum allowed MPE value.
Please refer to page 2 for calculation procedures.

2.
KDB 447498 D01 General RF Exposure Guidance v06, clause 7.2. Transmitters used in mobile device exposure conditions for simultaneous transmission operations

Results:

Σ of MPE ratios is $= 0.551 \leq 1.0$ so simultaneous transmission MPE test exclusion applies for device.

Telephone : +65 6778 7777
Fax No. : +65 6779 7088
www.tuv-sud-psb.sg

TUV®

TÜV SÜD PSB Pte Ltd
1 Science Park Drive
Singapore 118221
Reg. No. : 199002667R

Calculations 850 MHz band

Maximum average output power at Antenna terminal: **30.49 dBm**

(Max average power = 33.50 dBm – 3.01 dBm duty cycle)

G = 0.51dBi

Prediction distance R: 20 cm

Prediction frequency: 824.20 MHz

MPE limit S: 0.5495 mW/cm²

$$S = P \cdot G / (4 \cdot \pi \cdot R^2) = 0.251 \text{ mW/cm}^2$$

Calculations 1900 MHz band

Maximum average output power at Antenna terminal: **27.29 dBm**

(Max average power = 30.30 dBm – 3.01 dBm duty cycle)

G = 2.09 dBi

Prediction distance R: 20 cm

Prediction frequency: 1880.00 MHz

MPE limit S: 1 mW/cm²

$$S = P \cdot G / (4 \cdot \pi \cdot R^2) = 0.172 \text{ mW/cm}^2$$

Calculations 2400 MHz band

Maximum average output power at Antenna terminal:

P: 117.5 mW [WLAN 2412 – 2462 MHz] (averaged over 30 min)

P: 68 mW [Bluetooth 2402 – 2480 MHz] (averaged over 30 min)

P: 23 mW [Bluetooth LE 2402 – 2480 MHz] (averaged over 30 min)

D: Duty cycle: 100 % = 1

G = 6 dBi = 4 (Highest array gain for MiMo with 2 antennas)

Prediction distance R: 20 cm

Prediction frequency: 2400.00 MHz

MPE limit S: 1 mW/cm²

$$S = P \cdot G / (4 \cdot \pi \cdot R^2) = 0.094 \text{ mW/cm}^2$$